

An improved upper bound on the K_4 Ramsey multiplicity constant and other formally verified results from OpenMath 2026

Woohyuk Kang^{1,2} Hyunjin Lee³ Sanghyeon Lee⁴ Youchan Oh⁵

¹HTPeo ²Kyung Hee University ³University of Cambridge
⁴Korea University ⁵Seoul National University

October 2026

Abstract

We report the results obtained by our team during OpenMath 2026, a one-week event in which only formally verified mathematics was counted. Our main result is a weighted two-colouring template on 1024 blocks whose monochromatic- K_4 density shows that the K_4 Ramsey multiplicity constant satisfies $c_4 \leq 0.0301399120$, improving the previous upper bound $10486266368/768^4 \approx 0.0301422734$ due to McKay. The template, the lifting argument and the existence of the limit defining c_4 are checked in Lean 4 with Mathlib, using only the standard axioms. We also prove in Lean that several infinite families of cubic graphs have star chromatic index at most 5 and that every bridgeless cubic loopless multigraph on at most 14 vertices has star chromatic index at most 6, and we reduce the Dvořák–Mohar–Šámal conjecture to named open hypotheses; the conjecture itself remains open. Finally, we formalize known results attached to sixteen Erdős problems, together with Schönberger’s and Petersen’s theorems, and report results on the scored tasks of the event, three of which carry Lean certificates. Most of the mathematics and all Lean code were produced by AI systems directed by the authors.

1 Introduction

OpenMath 2026 (held as the *Open Problems Hack at MIT*, 27 September–3 October 2026) invited teams to produce machine-checked mathematics on open problems in one week [5]. Problems were posed as scored tasks on the AutoLab platform; a passing evaluation was required but was explicitly not regarded as a proof, and results were counted only when formalized. This paper collects what our team obtained, states precisely what is proved and by which system, and records what was already known.

Ramsey multiplicity. Let $\text{mono}_{K_4}(m)$ be the least number of monochromatic copies of K_4 over all two-colourings of the edges of K_m , and $c_4 = \lim_{m \rightarrow \infty} \text{mono}_{K_4}(m)/\binom{m}{4}$. Erdős conjectured $c_4 = 1/32$; Thomason disproved this with a construction giving $c_4 < 0.03050$ and later improved it, and further small improvements followed, among them one by Even-Zohar and Linial, as described by Parczyk, Pokutta, Spiegel and Szabó [10]. They proved $c_4 \leq 4551721 \cdot 2^{-24} \cdot 3^{-2} < 0.03015$ from the blow-up sequence of a Cayley graph on 768 vertices, and a note at the end of their paper reports that McKay, by local search starting from that graph, found a graph with value $10486266368/768^4 \approx 0.0301422734$. The best known lower bound, $c_4 > 0.0296$, is due to Grzesik, Lee, Lidický and Volec using flag algebras, as cited in [10]. We prove the following.

Theorem 1.1. $c_4 \leq \frac{200137750014677779172692777477}{6640289795261907019148161833841} \approx 0.030139911990$.

E-mail addresses: massis.kang@htpeo.com (W. Kang), hl728@cam.ac.uk (H. Lee), ymhlsh4065@korea.ac.kr (S. Lee), thomasoh0408@snu.ac.kr (Y. Oh).

The improvement over McKay’s value is about 2.4×10^{-6} ; it narrows the gap to the lower bound by about 0.4% and does not determine c_4 . The certificate is an explicit template, and the whole deduction, including the existence of the limit, is checked in Lean (Section 2).

Star edge-colouring. A star edge-colouring is a proper edge-colouring without bichromatic paths or cycles of length four. Dvořák, Mohar and Šámal [1] proved that every subcubic graph has star chromatic index at most 7 and conjectured that 6 colours always suffice. We do not settle the conjecture. Our formal development works with loopless multigraphs, which include the subcubic simple graphs of the conjecture. In Section 3 we prove in Lean that the flower snarks, the Goldberg snarks, the generalized Petersen graphs $GP(n, k)$ with $k \leq 15$ and the Möbius ladders have star chromatic index at most 5, that every bridgeless cubic loopless multigraph on at most 14 vertices has star chromatic index at most 6, and that the multigraph form of the conjecture is equivalent to a statement about bridgeless cubic multigraphs on at least 16 vertices.

Formalizations and scored tasks. Section 4 describes Lean proofs of known results attached to sixteen Erdős problems [2], stated exactly as in the formal-conjectures repository [3], and of Schönberger’s and Petersen’s theorems for Mathlib’s simple graphs. Section 5 reports our results on the scored tasks, among them 471 triangles formed by 39 lines in the Kobon triangle problem. Section 6 describes how AI systems were used, and Section 7 lists what is not proved. All Lean sources, build logs and certificates are available [11].

Verification conventions. Unless stated otherwise, every theorem in this paper is a Lean 4.33.1 declaration [7] over Mathlib v4.33.1 [8] that compiles without errors, and its `#print axioms` output lists only `propext`, `Classical.choice` and `Quot.sound`. No stated theorem depends on `sorry`, on added axioms or on `native_decide`.

2 The K_4 Ramsey multiplicity constant

Templates. A template on n blocks consists of positive integer weights $w_1, \dots, w_n$ with total Q and a symmetric red/blue colouring of the pairs of blocks, including each block with itself. Replacing block i by $t w_i$ vertices and colouring each edge by the colour of its pair of blocks gives a colouring of K_{tQ} ; its number of monochromatic K_4 divided by $(tQ)^4/24$ is bounded by N/Q^4 , where N is the weighted count of monochromatic quadruples of blocks. Hence $c_4 \leq N/Q^4$ for every template.

The certificate. Our template has $n = 1024$ blocks, integer weights with total $Q = 50762939$, and $N = 200137750014677779172692777477$, so N/Q^4 is the fraction in Theorem 1.1. The Lean development proves the bound in the following form, together with the exact value of N/Q^4 and the symmetry of the template.

```
theorem ramseyMultK4_limit_lt_ref :
  ∃ L : ℝ,
    Filter.Tendsto (fun m : ℕ => (minMonoK4 m : ℝ) / (m.choose 4 : ℝ))
      Filter.atTop (nhds L) ∧
    L < 10486266368 / 768 ^ 4
```

Two companion statements bound the same limit by N/Q^4 and give the bound for every $m \geq 4$ rather than only in the limit (`ramseyMultK4_le_sol` and `minMonoK4_density_le_sol`).

What is checked and what is trusted. The count N is split into 2×1024 per-block sums, each evaluated by the Lean kernel (`decide +kernel`) on a packed bit-mask representation; a general lemma proves that the packed evaluation equals the literal definition for every template.

The blow-up lemma, the monotonicity argument that gives the existence of the limit, and the comparison with McKay’s value are ordinary Lean proofs. The build consists of 2048 generated modules and took about four CPU hours. Two steps lie outside the kernel: the transcription of the template from its data file into Lean, which is performed by one script and checked by an independent one, and the agreement of the Lean definitions with the informal notion of c_4 , which we discuss in the accompanying packet.

How the template was found. We started from the 768-vertex Cayley graph used in [10]. Simulated annealing and tabu search acted on the orbits of vertex pairs under its automorphism group; near-twin blocks were then split until 1024 blocks were reached, the weights were optimized continuously and rounded to integers, and the result was refined by basin hopping. Every candidate was re-scored exactly with the organisers’ evaluator. Weight polishing alone and integer rounding gave no further gain, and a re-splitting strategy that was still improving at the end of the event did not overtake the best template. The template scored first of thirteen entries on the corresponding task at the end of the event.

3 Star edge-colouring of subcubic multigraphs

We write $\chi'_s(G)$ for the star chromatic index. The following are proved in Lean for multigraphs given by explicit edge lists.

Theorem 3.1. $\chi'_s(G) \leq 5$ for every flower snark J_n ($n \geq 5$ odd), every Goldberg snark, every generalized Petersen graph $GP(n, k)$ with $1 \leq k \leq 15$ and $n \geq 2k + 1$ other than $GP(3, 1)$, every Möbius ladder, and every member of a family of Petersen-type inflations.

Theorem 3.2. Every bridgeless cubic loopless multigraph on at most 14 vertices satisfies $\chi'_s(G) \leq 6$.

Theorem 3.3. Every subcubic loopless multigraph has star chromatic index at most 6 if and only if every bridgeless cubic loopless multigraph on at least 16 vertices, together with each of its leaf-extended subgraphs, is star 6-edge-colourable (`dms_iff_cubic16`).

We also proved that a list of explicitly stated hypotheses implies the conjecture; each hypothesis is open, and the reduction carries no evidence that they hold. The agreement of the edge lists in Theorem 3.1 with the textbook definitions of the families is checked by a script and not proved as a graph isomorphism. These results were produced by an automated system in which language-model agents proposed lemmas, a Lean service accepted or rejected them, and a second model family audited the accepted statements. Our attempts on the remaining core case, cyclically 4-edge-connected cubic graphs, did not succeed; the informal studies are archived and are not claimed.

4 Formalizations of known results

For each family in Table 1, the Lean file is the formal-conjectures [3] file at a fixed commit with the `sorry` of the target statement replaced by a proof; the statements are textually unchanged. We searched formal-conjectures, the public pull requests of the awards repository for these problems and several public collections of Lean proofs for earlier formalizations. Several candidates were dropped because a proof already existed, and “no earlier formal proof” should be read as relative to these searches.

Table 1: Formalized families. Numbers refer to [2]; theorem names omit the common prefix `erdos_n.variants`.

Problem	Result formalized	Weight
G-PM	Schönberger’s and Petersen’s theorems for connected cubic bridgeless simple graphs	main
942	<code>limsup</code>	main
44	greedy Sidon construction	main
123	<code>powers_2_3</code>	main
918	three variants <code>eq_aleph_0</code>	main
292	<code>mul</code> , <code>two_mul</code> , <code>prime_pow</code>	main
395	<code>one</code> : the radius-one counterexample of Carnielli and Carolino	main
698	<code>erdos_szekeres</code>	main
939	<code>seven</code> , <code>eight</code>	main
477	<code>S_sq</code> and the quadratic case with $a \mid b$ (Sekanina’s theorem and its generalization)	main
295, 703, 748, 1136	helper lemma; <code>zero</code> ; <code>lower_bound</code> ; <code>multiples_of_three</code>	minor
358, 619, 1148	odd-divisor identity; diameter-three completion; <code>weaker</code>	minor

5 Results on the scored tasks

Table 2 lists our results on the AutoLab tasks of the event, with standings as read shortly before the deadline; entries with identical scores share a rank.

Table 2: Results on the scored tasks.

Task	Result	Standing	Lean
K_4 Ramsey multiplicity	Theorem 1.1	1st of 13	yes
Kobon triangles, 39 lines	471 triangles	1st of 3	yes
Busy Beaver, 6 states	halts after 249,881 steps	tied 1st of 12	yes
Grothendieck witnesses	ratio 1393/985, 80 bits	tied 1st of 9	yes
Kobon triangles, 18 lines	93 triangles	tied 1st of 15	no
3×3 matrix multiplication	rank 23, support 139	tied 2nd of 11	no
Collatz modular descent	234 rules, full coverage	5th of 8	no

Kobon triangles. Starting from the Füredi–Palásti arrangement [4], which gives 468 triangles for 39 lines, simulated annealing on the line parameters produced 39 lines with integer coefficients that bound 471 triangles; the upper bound for 39 lines is $\lfloor 39 \cdot 37/3 \rfloor = 481$. The certificate `Kobon.kobon_nonoverlapping` states that there are 39 pairwise distinct lines and 471 triples of them, each bounding a non-degenerate triangle whose open interior meets none of the lines, the 471 triangles being pairwise disjoint. The table of known values in OEIS A006066 [9] lists no value for 39 lines; we have not searched the literature further and do not claim the value as new.

Busy Beaver. The six-state, two-symbol machine

`OLE1LA_1LC1RH_1RA1RF_ORFORD_1RD1LB_1LC1RD`

halts from the blank tape after exactly 249,881 steps, visits all six states and leaves 554 ones on a span of 735 cells; this is proved in core Lean without Mathlib. The value equals the best one on the task. We did not prove that it is the largest halting time below the hidden step budget: an exhaustive search organised by the strongly connected structure of the transition graph excluded 31 of 32 classes and was stopped before finishing the last one.

Grothendieck constant. For the matrix $\begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix}$ with rational unit vectors, the certificate shows that every admissible constant in the finite-dimensional Grothendieck inequality is at least $1393/985$, and at least $\sqrt{2}$ with exact vectors; Tsirelson’s bound shows that no witness on this matrix can do better. These facts are classical.

Other tasks. The remaining results reproduce known constructions; the matrix-multiplication scheme is one of the rank-23 schemes published by Heule, Kauers and Seidl [6], and searches for support below 139 were unsuccessful. A further result of a team member is the only entry on the held-out evaluation of the Ramsey task, with a slightly weaker template.

Remark. Two of us obtained a solution of Erdős problem #1038, determining the infimum and the supremum of the measure of $\{x : |f(x)| < 1\}$ over monic real polynomials with all roots in $[-1, 1]$, and formalized it in Lean. While doing so we found that a proof by the same approach had been announced and that a Lean proof was already public. Our development is an independent implementation of a known result, and we claim no credit for it; it is archived with the other material [11].

6 Use of AI systems

The results of Section 3 came from an automated system running on one 16-core server, in which Claude agents (Anthropic) proposed and proved lemmas, a Lean service accepted or rejected each submitted fact, and GPT models (OpenAI) audited the accepted statements; about 786 informal facts were recorded. The Ramsey search, all Lean certificates, the formalizations of Section 4 and the work on the scored tasks were carried out in Claude Code and Codex sessions directed by the authors. The recorded usage was about 8.6×10^7 output tokens, all under subscription plans; the usage of two authors was not recorded. Every proof in this paper was written by an AI system and checked by the Lean kernel and by scripts. No author has reviewed the proofs line by line; the authors’ role was to choose problems, direct the systems, check the statements against the literature and decide what to claim. The text of this paper was drafted with the help of an AI system and edited by the authors.

7 What is and is not proved

Theorem 1.1 improves the upper bound on c_4 numerically; c_4 is not determined, and we have not checked whether an improvement on McKay’s value has appeared since 2024. The Dvořák–Mohar–Šámal conjecture is open; Theorem 3.3 and the reduction to named hypotheses do not bring it measurably closer to a proof. The formalizations of Section 4 concern known mathematics, and the claim that they are the first formal proofs rests on searches whose limits we have stated. The evaluators of the scored tasks are not formalized; where we compare a certificate with an evaluation, we compare with a transcription of the evaluator or with its signed report. Natural next steps are a search for templates on more than 1024 blocks, an extension of Theorem 3.2 to larger orders, and a formal treatment of the cyclically 4-edge-connected case.

Acknowledgements. We thank the organisers of OpenMath 2026 and the AutoLab team for the problems and the evaluation infrastructure. The Erdős statements and definitions are those of the formal-conjectures project [3]; our work also relies on Lean [7] and Mathlib [8].

References

- [1] Z. Dvořák, B. Mohar and R. Šámal, Star chromatic index, *J. Graph Theory* 72 (2013), no. 3, 313–326, doi:10.1002/jgt.21644; arXiv:1011.3376.

- [2] T. F. Bloom, Erdős problems, <https://www.erdosproblems.com>, accessed October 2026.
- [3] Google DeepMind, Formal Conjectures, <https://github.com/google-deepmind/formal-conjectures>, commit df3f12d7.
- [4] Z. Füredi and I. Palásti, Arrangements of lines with a large number of triangles, *Proc. Amer. Math. Soc.* 92 (1984), 561–566, doi:10.1090/S0002-9939-1984-0760946-2.
- [5] Open Problems Hack at MIT (OpenMath 2026), Competition and Judging Handbook, <https://rsihouse.ai/openmath/handbook.pdf>.
- [6] M. J. H. Heule, M. Kauers and M. Seidl, New ways to multiply 3×3 -matrices, arXiv:1905.10192, 2019.
- [7] L. de Moura and S. Ullrich, The Lean 4 theorem prover and programming language, in *Automated Deduction – CADE 28*, Lecture Notes in Comput. Sci., Springer, 2021, 625–635, doi:10.1007/978-3-030-79876-5_37.
- [8] The mathlib Community, The Lean mathematical library, in *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP 2020)*, ACM, 2020, 367–381, doi:10.1145/3372885.3373824; arXiv:1910.09336.
- [9] OEIS Foundation, Kobon triangles: maximal number of nonoverlapping triangles that can be formed from n lines drawn in the plane, Sequence A006066, <https://oeis.org/A006066>, accessed October 2026.
- [10] O. Parczyk, S. Pokutta, C. Spiegel and T. Szabó, New Ramsey multiplicity bounds and search heuristics, *Found. Comput. Math.* 25 (2025), 1777–1814, doi:10.1007/s10208-024-09675-6; arXiv:2206.04036.
- [11] Lean sources, certificates and records of this work, <https://github.com/lavaskiller/openmath-2026-htpeo>; state at the deadline: commit 76c63b8.