

Codeforces Round #257 (Div. 1)

A. Jzzhu and Chocolate

time limit per test: 1 second
 memory limit per test: 256 megabytes
 input: standard input
 output: standard output

Jzzhu has a big rectangular chocolate bar that consists of $n \times m$ unit squares. He wants to cut this bar exactly k times. Each cut must meet the following requirements:

- each cut should be straight (horizontal or vertical);
- each cut should go along edges of unit squares (it is prohibited to divide any unit chocolate square with cut);
- each cut should go inside the whole chocolate bar, and all cuts must be distinct.

The picture below shows a possible way to cut a 5×6 chocolate for 5 times.



Imagine Jzzhu have made k cuts and the big chocolate is splitted into several pieces. Consider the smallest (by area) piece of the chocolate, Jzzhu wants this piece to be as large as possible. What is the maximum possible area of smallest piece he can get with exactly k cuts? The area of a chocolate piece is the number of unit squares in it.

Input

A single line contains three integers n, m, k ($1 \leq n, m \leq 10^9$; $1 \leq k \leq 2 \cdot 10^9$).

Output

Output a single integer representing the answer. If it is impossible to cut the big chocolate k times, print -1.

Examples

input
3 4 1
output
6
input
6 4 2
output
8
input
2 3 4
output
-1

Note

In the first sample, Jzzhu can cut the chocolate following the picture below:



In the second sample the optimal division looks like this:



In the third sample, it's impossible to cut a 2×3 chocolate 4 times.

B. Jzzhu and Cities

time limit per test: 2 seconds
memory limit per test: 256 megabytes
input: standard input
output: standard output

Jzzhu is the president of country A. There are n cities numbered from 1 to n in his country. City 1 is the capital of A. Also there are m roads connecting the cities. One can go from city u_i to v_i (and vise versa) using the i -th road, the length of this road is x_i . Finally, there are k train routes in the country. One can use the i -th train route to go from capital of the country to city s_i (and vise versa), the length of this route is y_i .

Jzzhu doesn't want to waste the money of the country, so he is going to close some of the train routes. Please tell Jzzhu the maximum number of the train routes which can be closed under the following condition: the length of the shortest path from every city to the capital mustn't change.

Input

The first line contains three integers n, m, k ($2 \leq n \leq 10^5$; $1 \leq m \leq 3 \cdot 10^5$; $1 \leq k \leq 10^5$).

Each of the next m lines contains three integers u_i, v_i, x_i ($1 \leq u_i, v_i \leq n$; $u_i \neq v_i$; $1 \leq x_i \leq 10^9$).

Each of the next k lines contains two integers s_i and y_i ($2 \leq s_i \leq n$; $1 \leq y_i \leq 10^9$).

It is guaranteed that there is at least one way from every city to the capital. Note, that there can be multiple roads between two cities. Also, there can be multiple routes going to the same city from the capital.

Output

Output a single integer representing the maximum number of the train routes which can be closed.

Examples

input
5 5 3 1 2 1 2 3 2 1 3 3 3 4 4 1 5 5 3 5 4 5 5 5
output
2

input
2 2 3 1 2 2 2 1 3 2 1 2 2 2 3
output
2

C. Jzzhu and Apples

time limit per test: 1 second
memory limit per test: 256 megabytes
input: standard input
output: standard output

Jzzhu has picked n apples from his big apple tree. All the apples are numbered from 1 to n . Now he wants to sell them to an apple store.

Jzzhu will pack his apples into groups and then sell them. Each group must contain two apples, and the greatest common divisor of numbers of the apples in each group must be greater than 1. Of course, each apple can be part of at most one group.

Jzzhu wonders how to get the maximum possible number of groups. Can you help him?

Input

A single integer n ($1 \leq n \leq 10^5$), the number of the apples.

Output

The first line must contain a single integer m , representing the maximum number of groups he can get. Each of the next m lines must contain two integers — the numbers of apples in the current group.

If there are several optimal answers you can print any of them.

Examples

input
6
output
2 6 3 2 4
input
9
output
3 9 3 2 4 6 8
input
2
output
0

D. Jzzhu and Numbers

time limit per test: 2 seconds
memory limit per test: 256 megabytes
input: standard input
output: standard output

Jzzhu have n non-negative integers a_1, a_2, \dots, a_n . We will call a sequence of indexes i_1, i_2, \dots, i_k ($1 \leq i_1 < i_2 < \dots < i_k \leq n$) a group of size k .

Jzzhu wonders, how many groups exists such that $a_{i_1} \& a_{i_2} \& \dots \& a_{i_k} = 0$ ($1 \leq k \leq n$)? Help him and print this number modulo 1000000007 ($10^9 + 7$). Operation $X \& Y$ denotes bitwise AND operation of two numbers.

Input

The first line contains a single integer n ($1 \leq n \leq 10^6$). The second line contains n integers a_1, a_2, \dots, a_n ($0 \leq a_i \leq 10^6$).

Output

Output a single integer representing the number of required groups modulo 1000000007 ($10^9 + 7$).

Examples

input
3 2 3 3
output
0
input
4 0 1 2 3
output
10
input
6 5 2 0 5 2 1
output
53

E. Jzzhu and Squares

time limit per test: 3 seconds
memory limit per test: 256 megabytes
input: standard input
output: standard output

Jzzhu has two integers, n and m . He calls an integer point (x, y) of a plane special if $0 \leq x \leq n$ and $0 \leq y \leq m$. Jzzhu defines a unit square as a square with corners at points (x, y) , $(x + 1, y)$, $(x + 1, y + 1)$, $(x, y + 1)$, where x and y are some integers.

Let's look at all the squares (their sides not necessarily parallel to the coordinate axes) with corners at the special points. For each such square Jzzhu paints a dot in every unit square that is fully inside it. After that some unit squares can contain several dots. Now Jzzhu wonders, how many dots he has painted on the plane. Find this number modulo 1000000007 ($10^9 + 7$).

Input

The first line contains a single integer t ($1 \leq t \leq 10^5$) — the number of tests.

Each of the next t lines contains the description of the test: two integers n and m ($1 \leq n, m \leq 10^6$) — the value of variables for the current test.

Output

For each test output the total number of dots modulo 1000000007 ($10^9 + 7$).

Examples

input
4 1 3 2 2 2 5 3 4
output
3 8 26 58