

Codeforces Round #347 (Div. 2)

A. Complicated GCD

time limit per test: 1 second
memory limit per test: 256 megabytes
input: standard input
output: standard output

Greatest common divisor $GCD(a, b)$ of two positive integers a and b is equal to the biggest integer d such that both integers a and b are divisible by d . There are many efficient algorithms to find greatest common divisor $GCD(a, b)$, for example, Euclid algorithm.

Formally, find the biggest integer d , such that all integers $a, a + 1, a + 2, \dots, b$ are divisible by d . To make the problem even more complicated we allow a and b to be up to googol, 10^{100} — such number do not fit even in 64-bit integer type!

Input

The only line of the input contains two integers a and b ($1 \leq a \leq b \leq 10^{100}$).

Output

Output one integer — greatest common divisor of all integers from a to b inclusive.

Examples

input
1 2
output
1
input
61803398874989484820458683436563811772030917980576 61803398874989484820458683436563811772030917980576
output
61803398874989484820458683436563811772030917980576

B. Rebus

time limit per test: 1 second
memory limit per test: 256 megabytes
input: standard input
output: standard output

You are given a rebus of form $? + ? - ? + ? = n$, consisting of only question marks, separated by arithmetic operation '+' and '-', equality and positive integer n . The goal is to replace each question mark with some positive integer from 1 to n , such that equality holds.

Input

The only line of the input contains a rebus. It's guaranteed that it contains no more than **100** question marks, integer n is positive and doesn't exceed **1 000 000**, all letters and integers are separated by spaces, arithmetic operations are located only between question marks.

Output

The first line of the output should contain "Possible" (without quotes) if rebus has a solution and "Impossible" (without quotes) otherwise.

If the answer exists, the second line should contain any valid rebus with question marks replaced by integers from **1** to n . Follow the format given in the samples.

Examples

input
? + ? - ? + ? + ? = 42
output
Possible 9 + 13 - 39 + 28 + 31 = 42

input
? - ? = 1
output
Impossible

input
? = 1000000
output
Possible 1000000 = 1000000

C. International Olympiad

time limit per test: 1 second
memory limit per test: 256 megabytes
input: standard input
output: standard output

International Abbreviation Olympiad takes place annually starting from 1989. Each year the competition receives an abbreviation of form $\text{IAO}'y$, where y stands for some number of consequent last digits of the current year. Organizers always pick an abbreviation with non-empty string y that has never been used before. Among all such valid abbreviations they choose the shortest one and announce it to be the abbreviation of this year's competition.

For example, the first three Olympiads (years 1989, 1990 and 1991, respectively) received the abbreviations $\text{IAO}'9$, $\text{IAO}'0$ and $\text{IAO}'1$, while the competition in 2015 received an abbreviation $\text{IAO}'15$, as $\text{IAO}'5$ has been already used in 1995.

You are given a list of abbreviations. For each of them determine the year it stands for.

Input

The first line of the input contains a single integer n ($1 \leq n \leq 1000$) — the number of abbreviations to process.

Then n lines follow, each containing a single abbreviation. It's guaranteed that each abbreviation contains at most nine digits.

Output

For each abbreviation given in the input, find the year of the corresponding Olympiad.

Examples

input
5 IAO'15 IAO'2015 IAO'1 IAO'9 IAO'0
output
2015 12015 1991 1989 1990

input
4 IAO'9 IAO'99 IAO'999 IAO'9999
output
1989 1999 2999 9999

D. Graph Coloring

time limit per test: 1 second
memory limit per test: 256 megabytes
input: standard input
output: standard output

You are given an undirected graph that consists of n vertices and m edges. Initially, each edge is colored either red or blue. Each turn a player picks a single vertex and switches the color of **all** edges incident to it. That is, all red edges with an endpoint in this vertex change the color to blue, while all blue edges with an endpoint in this vertex change the color to red.

Find the minimum possible number of moves required to make the colors of all edges equal.

Input

The first line of the input contains two integers n and m ($1 \leq n, m \leq 100\,000$) — the number of vertices and edges, respectively.

The following m lines provide the description of the edges, as the i -th of them contains two integers u_i and v_i ($1 \leq u_i, v_i \leq n$, $u_i \neq v_i$) — the indices of the vertices connected by the i -th edge, and a character c_i ($c_i \in \{B, R\}$) providing the initial color of this edge. If c_i equals 'R', then this edge is initially colored red. Otherwise, c_i is equal to 'B' and this edge is initially colored blue. It's guaranteed that there are no self-loops and multiple edges.

Output

If there is no way to make the colors of all edges equal output -1 in the only line of the output. Otherwise first output k — the minimum number of moves required to achieve the goal, then output k integers a_1, a_2, \dots, a_k , where a_i is equal to the index of the vertex that should be used at the i -th move.

If there are multiple optimal sequences of moves, output any of them.

Examples

input
3 3 1 2 B 3 1 R 3 2 B
output
1 2
input
6 5 1 3 R 2 3 R 3 4 B 4 5 R 4 6 R
output
2 3 4
input
4 5 1 2 R 1 3 R 2 3 B 3 4 B 1 4 B
output
-1

E. To Hack or not to Hack

time limit per test: 1 second
memory limit per test: 256 megabytes
input: standard input
output: standard output

Consider a regular Codeforces round consisting of three problems that uses dynamic scoring.

You are given an almost final scoreboard. For each participant (including yourself), the time of the accepted submission for each of the problems is given. Also, for each solution you already know whether you are able to hack it or not. The only changes in the scoreboard that will happen before the end of the round are your challenges.

What is the best place you may take at the end?

More formally, n people are participating (including yourself). For any problem, if it was solved by exactly k people at the end of the round, the maximum score for this problem is defined as:

1. If $n < 2k \leq 2n$, then the maximum possible score is 500;
2. If $n < 4k \leq 2n$, then the maximum possible score is 1000;
3. If $n < 8k \leq 2n$, then the maximum possible score is 1500;
4. If $n < 16k \leq 2n$, then the maximum possible score is 2000;
5. If $n < 32k \leq 2n$, then the maximum possible score is 2500;
6. If $32k \leq n$, then the maximum possible score is 3000.

Let the maximum possible score for some problem be equal to S . Then a contestant who didn't manage to get it accepted (or his solution was hacked) earns 0 points for this problem. If he got the the solution accepted t minutes after the beginning of the round (and his solution wasn't hacked), he earns $\frac{s \cdot (250 - t)}{250}$ points for this problem.

The overall score of a participant is equal to the sum of points he earns for each problem plus 100 points for each successful hack (only you make hacks).

The resulting place you get is equal to one plus the number of participants who's overall score is strictly greater than yours.

Input

The first line of the input contains a single integer n ($1 \leq n \leq 5000$) — the number of participants. You are the participant number 1.

Each of the following n lines contains three integers a_i , b_i and c_i . Here $a_i = 0$ means that the participant number i didn't manage to accept first problem. If $1 \leq a_i \leq 120$, then the participant number i got the first problem accepted a_i minutes after the start of the contest and you cannot hack this solution. Finally, $-120 \leq a_i \leq -1$ means that the participant number i got the first problem accepted $-a_i$ minutes after the start of the contest and you can hack this solution. Similarly, b_i and c_i provide the information regarding second and third problems in the same format.

It's guaranteed that integers a_1 , b_1 and c_1 are non-negative.

Output

Print the only integer — the best place you can take at the end of the round.

Examples

input
4 120 120 1 61 61 120 -61 61 120 0 0 0
output
1

input
4 0 0 119 -3 -17 -42 0 7 0 51 0 0
output
2

Note

Consider the first sample. If you do not hack any solutions, you will win the contest (scoreboard to the left). However, if you hack the

solution of the first problem of the third participant (the only one you can hack), the maximum score for the first problem will change and you will finish second (scoreboard to the right).

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----