

**Codeforces Round #172 (Div. 1)****A. Rectangle Puzzle**

time limit per test: 2 seconds

memory limit per test: 256 megabytes

input: standard input

output: standard output

You are given two rectangles on a plane. The centers of both rectangles are located in the origin of coordinates (meaning the center of the rectangle's symmetry). The first rectangle's sides are parallel to the coordinate axes: the length of the side that is parallel to the  $Ox$  axis, equals  $w$ , the length of the side that is parallel to the  $Oy$  axis, equals  $h$ . The second rectangle can be obtained by rotating the first rectangle relative to the origin of coordinates by angle  $\alpha$ .

Your task is to find the area of the region which belongs to both given rectangles. This region is shaded in the picture.

**Input**

The first line contains three integers  $w, h, \alpha$  ( $1 \leq w, h \leq 10^6$ ;  $0 \leq \alpha \leq 180$ ). Angle  $\alpha$  is given in degrees.

**Output**

In a single line print a real number — the area of the region which belongs to both given rectangles.

The answer will be considered correct if its relative or absolute error doesn't exceed  $10^{-6}$ .

**Examples**

<b>input</b>
1 1 45
<b>output</b>
0.828427125

  

<b>input</b>
6 4 30
<b>output</b>
19.668384925

**Note**

The second sample has been drawn on the picture above.

## B. Maximum Xor Secondary

time limit per test: 1 second  
memory limit per test: 256 megabytes  
input: standard input  
output: standard output

Bike loves looking for the second maximum element in the sequence. The second maximum element in the sequence of distinct numbers  $x_1, x_2, \dots, x_k$  ( $k > 1$ ) is such maximum element  $x_j$ , that the following inequality holds:  $x_j \neq \max_{i=1}^k x_i$ .

The lucky number of the sequence of distinct positive integers  $x_1, x_2, \dots, x_k$  ( $k > 1$ ) is the number that is equal to the bitwise excluding OR of the maximum element of the sequence and the second maximum element of the sequence.

You've got a sequence of distinct positive integers  $s_1, s_2, \dots, s_n$  ( $n > 1$ ). Let's denote sequence  $s_l, s_{l+1}, \dots, s_r$  as  $s[l..r]$  ( $1 \leq l < r \leq n$ ). Your task is to find the maximum number among all lucky numbers of sequences  $s[l..r]$ .

Note that as all numbers in sequence  $s$  are distinct, all the given definitions make sense.

### Input

The first line contains integer  $n$  ( $1 < n \leq 10^5$ ). The second line contains  $n$  distinct integers  $s_1, s_2, \dots, s_n$  ( $1 \leq s_i \leq 10^9$ ).

### Output

Print a single integer — the maximum lucky number among all lucky numbers of sequences  $s[l..r]$ .

### Examples

input
5 5 2 1 4 3
output
7

  

input
5 9 8 3 5 7
output
15

### Note

For the first sample you can choose  $s[4..5] = \{4, 3\}$  and its lucky number is  $(4 \text{ xor } 3) = 7$ . You can also choose  $s[1..2]$ .

For the second sample you must choose  $s[2..5] = \{8, 3, 5, 7\}$ .

## C. Game on Tree

time limit per test: 1 second  
memory limit per test: 256 megabytes  
input: standard input  
output: standard output

Momiji has got a rooted tree, consisting of  $n$  nodes. The tree nodes are numbered by integers from  $1$  to  $n$ . The root has number  $1$ . Momiji decided to play a game on this tree.

The game consists of several steps. On each step, Momiji chooses one of the remaining tree nodes (let's denote it by  $V$ ) and removes all the subtree nodes with the root in node  $V$  from the tree. Node  $V$  gets deleted as well. The game finishes when the tree has no nodes left. In other words, the game finishes after the step that chooses the node number  $1$ .

Each time Momiji chooses a new node uniformly among all the remaining nodes. Your task is to find the expectation of the number of steps in the described game.

### Input

The first line contains integer  $n$  ( $1 \leq n \leq 10^5$ ) — the number of nodes in the tree. The next  $n - 1$  lines contain the tree edges. The  $i$ -th line contains integers  $a_i, b_i$  ( $1 \leq a_i, b_i \leq n$ ;  $a_i \neq b_i$ ) — the numbers of the nodes that are connected by the  $i$ -th edge.

It is guaranteed that the given graph is a tree.

### Output

Print a single real number — the expectation of the number of steps in the described game.

The answer will be considered correct if the absolute or relative error doesn't exceed  $10^{-6}$ .

### Examples

<b>input</b>
2 1 2
<b>output</b>
1.50000000000000000000

<b>input</b>
3 1 2 1 3
<b>output</b>
2.00000000000000000000

### Note

In the first sample, there are two cases. One is directly remove the root and another is remove the root after one step. Thus the expected steps are:

$$1 \times (1/2) + 2 \times (1/2) = 1.5$$

In the second sample, things get more complex. There are two cases that reduce to the first sample, and one case cleaned at once. Thus the expected steps are:

$$1 \times (1/3) + (1 + 1.5) \times (2/3) = (1/3) + (5/3) = 2$$

## D. k-Maximum Subsequence Sum

time limit per test: 5 seconds  
memory limit per test: 256 megabytes  
input: standard input  
output: standard output

Consider integer sequence  $a_1, a_2, \dots, a_n$ . You should run queries of two types:

- The query format is " $0\ i\ val$ ". In reply to this query you should make the following assignment:  $a_i = val$ .
- The query format is " $1\ l\ r\ k$ ". In reply to this query you should print the maximum sum of at most  $k$  non-intersecting subsegments of sequence  $a_l, a_{l+1}, \dots, a_r$ . Formally, you should choose at most  $k$  pairs of integers  $(x_1, y_1), (x_2, y_2), \dots, (x_t, y_t)$  ( $l \leq x_1 \leq y_1 < x_2 \leq y_2 < \dots < x_t \leq y_t \leq r$ ;  $t \leq k$ ) such that the sum  $a_{x_1} + a_{x_1+1} + \dots + a_{y_1} + a_{x_2} + a_{x_2+1} + \dots + a_{y_2} + \dots + a_{x_t} + a_{x_t+1} + \dots + a_{y_t}$  is as large as possible. Note that you should choose at most  $k$  subsegments. Particularly, you can choose 0 subsegments. In this case the described sum considered equal to zero.

### Input

The first line contains integer  $n$  ( $1 \leq n \leq 10^5$ ), showing how many numbers the sequence has. The next line contains  $n$  integers  $a_1, a_2, \dots, a_n$  ( $|a_i| \leq 500$ ).

The third line contains integer  $m$  ( $1 \leq m \leq 10^5$ ) — the number of queries. The next  $m$  lines contain the queries in the format, given in the statement.

All changing queries fit into limits:  $1 \leq i \leq n, |val| \leq 500$ .

All queries to count the maximum sum of at most  $k$  non-intersecting subsegments fit into limits:  $1 \leq l \leq r \leq n, 1 \leq k \leq 20$ . It is guaranteed that the number of the queries to count the maximum sum of at most  $k$  non-intersecting subsegments doesn't exceed 10000.

### Output

For each query to count the maximum sum of at most  $k$  non-intersecting subsegments print the reply — the maximum sum. Print the answers to the queries in the order, in which the queries follow in the input.

### Examples

input
9 9 -8 9 -1 -1 -1 9 -8 9 3 1 1 9 1 1 1 9 2 1 4 6 3
output
17 25 0

input
15 -4 8 -3 -10 10 4 -7 -7 0 -6 3 8 -10 7 2 15 1 3 9 2 1 6 12 1 0 6 5 0 10 -7 1 4 9 1 1 7 9 1 0 10 -3 1 4 10 2 1 3 13 2 1 4 11 2 0 15 -9 0 13 -9 0 11 -10 1 5 14 2 1 6 12 1
output
14 11 15 0 15 26 18

**Note**

In the first query of the first example you can select a single pair (1, 9). So the described sum will be 17.

Look at the second query of the first example. How to choose two subsegments? (1, 3) and (7, 9)? Definitely not, the sum we could get from (1, 3) and (7, 9) is 20, against the optimal configuration (1, 7) and (9, 9) with 25.

The answer to the third query is 0, we prefer select nothing if all of the numbers in the given interval are negative.

## E. Sequence Transformation

time limit per test: 3 seconds  
memory limit per test: 256 megabytes  
input: standard input  
output: standard output

You've got a non-decreasing sequence  $x_1, x_2, \dots, x_n$  ( $1 \leq x_1 \leq x_2 \leq \dots \leq x_n \leq q$ ). You've also got two integers  $a$  and  $b$  ( $a \leq b$ ;  $a \cdot (n - 1) < q$ ).

Your task is to transform sequence  $x_1, x_2, \dots, x_n$  into some sequence  $y_1, y_2, \dots, y_n$  ( $1 \leq y_i \leq q$ ;  $a \leq y_{i+1} - y_i \leq b$ ). The transformation price is the following sum:  $\sum_{i=1}^{n-1} (y_{i+1} - x_i)^2$ . Your task is to choose such sequence  $y$  that minimizes the described transformation price.

### Input

The first line contains four integers  $n, q, a, b$  ( $2 \leq n \leq 6000$ ;  $1 \leq q, a, b \leq 10^9$ ;  $a \cdot (n - 1) < q$ ;  $a \leq b$ ).

The second line contains a non-decreasing integer sequence  $x_1, x_2, \dots, x_n$  ( $1 \leq x_1 \leq x_2 \leq \dots \leq x_n \leq q$ ).

### Output

In the first line print  $n$  real numbers — the sought sequence  $y_1, y_2, \dots, y_n$  ( $1 \leq y_i \leq q$ ;  $a \leq y_{i+1} - y_i \leq b$ ). In the second line print the minimum transformation price, that is,  $\sum_{i=1}^{n-1} (y_{i+1} - x_i)^2$ .

If there are multiple optimal answers you can print any of them.

The answer will be considered correct if the absolute or relative error doesn't exceed  $10^{-6}$ .

### Examples

<b>input</b>
3 6 2 2 1 4 6
<b>output</b>
1.666667 3.666667 5.666667 0.666667

<b>input</b>
10 100000 8714 9344 3378 14705 17588 22672 32405 34309 37446 51327 81228 94982
<b>output</b>
1.000000 8715.000000 17429.000000 26143.000000 34857.000000 43571.000000 52285.000000 61629.000000 70973.000000 80317.000000 797708674.000000