



Transports Transport
Canada Canada
Aviation Civile / Civil Aviation
401-1550 avenue D'Estimauville
Québec QC G1J 0C8

Le 2 février 2021 / February 2nd, 2021

Votre référence / Your file

Notre référence / Our file

5258-14954-1
SGDDI # 17231850

Monsieur Yves Bernier
ORIZON AVIATION QUÉBEC INC.
820, 8^e avenue de l'Aéroport
Québec QC G2G 0M4

**OBJET: RÉVISION NO 6 AU CALENDRIER
DE MAINTENANCE Q-0798**

**SUBJECT: REVISION 6 TO THE
MAINTENANCE SCHEDULE Q-0798**

Monsieur,

La révision n° 6 à votre calendrier de maintenance numéro **Q-0798**, applicable à vos aéronefs modèle Cessna 152 soumise récemment pour notre évaluation a été évaluée et est satisfaisante.

Veuillez agréer, Monsieur, nos salutations distinguées.

Sir:

The amendment n° 6 of your Maintenance Schedule n° **Q-0798**, applicable to your aircrafts model Cessna 152, recently submitted to our office has been reviewed and found satisfactory.

Regards,

Guerard,
Claude

Signature numérique
de Guerard, Claude
Date : 2021.02.03
08:42:32 -05'00'

Claude Guérard

Inspecteur de la sécurité de l'Aviation civile / Civil Aviation Safety Inspector
Navigabilité / Airworthiness

Aviation civile – Région du Québec / Civil Aviation – Quebec Region

Tel: (418) 254-4748

Fax: 1 (855) 633-3697

claudio.guerard@tc.gc.ca

CG/el

Canada



Small Aircraft Maintenance Schedule Approval Approbation du calendrier de maintenance pour les petits aéronefs

Operator – Exploitant Orizon Aviation Québec		Aircraft type/model(s) – Type/modèle(s) de l'aéronef : Cessna 152	
Type of operation – Type d'exploitation			
☒ Flying training operations pursuant to CAR IV Formation au pilotage, conformément au RAC IV		☐ Commercial operations pursuant to CAR VII Opérations commerciales, conformément au RAC VII	
☐ Private operation pursuant to CAR VI Exploitation privée, conformément au RAC VI			
Aircraft role(s) – Rôle(s) de l'aéronef Formation au pilotage			
Annual utilization ¹ Utilisation annuelle ¹		Min Hr. – Heures 400	
		Cycles 700	
		Max Hr. – Heures 700	
		Cycles	
This approval is conditional upon the information specified above. In the event an aircraft's actual annual utilization is outside the range specified, or type of operation or aircraft role differs from that stated, the operator must undertake a review of this schedule, identify any amendments necessary to cater for the change in circumstances, and obtain Transport Canada approval to incorporate those amendments.		Cette approbation dépend des renseignements énoncés ci-dessus. Si l'utilisation annuelle réelle de l'aéronef dépasse la limite précisée, ou si le type d'exploitation ou le rôle de l'aéronef diffère de celui qui est énoncé, l'exploitant doit entreprendre un examen de ce calendrier, identifier les modifications nécessaires pour tenir compte des changements de conditions et obtenir de Transports Canada l'autorisation d'incorporer ces modifications.	
 Signature of Operator Signature de l'exploitant		2020-12-04 Date (yyyy - mm - dd) Date (aaaa - mm - jj)	
 For Minister of Transport Pour le ministre des Transports		2021-02-02 Date (yyyy - mm - dd) Date (aaaa - mm - jj)	
TCR-062		Q-0798	
Transport Canada Approval No. N° d'approbation de Transports Canada			

Revision status (Transport Canada use only) ¹ – État de la révision (À l'usage de Transports Canada seulement) ²				
Pages 1 to 18	Pages 1 to 14 (All)	Pages	Pages	Pages
Rev. Rév. 5	Rev. Rév. 6	Rev. Rév.	Rev. Rév.	Rev. Rév.
Date ³ 2016-04-27	Date ³ 2020-12-04	Date ³	Date ³	Date ³
Pages	Pages	Pages	Pages	Pages
Rev. Rév.	Rev. Rév.	Rev. Rév.	Rev. Rév.	Rev. Rév.
Date ³	Date ³	Date ³	Date ³	Date ³

¹ Complete this section only where the maintenance schedule approval is predicated upon an anticipated level of utilization.
Ne remplir cette section que si l'approbation du calendrier de maintenance est fondée sur le niveau prévu d'utilisation.

² Revision section refers to all pages in the approved schedule, including this approval document. Where the same page is referenced in more than one block, the most recent revision indicated supersedes all earlier references.

La section révision renvoie à toutes les pages du calendrier approuvé, y compris le présent document d'approbation. Lorsque l'on renvoie à la même page plus d'une fois dans le même bloc, la révision la plus récente indiquée remplace toutes les autres références.

³ Please use date format of (yyyy - mm - dd).

S'il vous plaît utilisez le format du date (aaaa - mm - jj).

General Conditions

- This document, together with the additional pages referenced herein, constitutes the minimum scheduled maintenance to be performed. Nothing contained in, or omitted from the maintenance schedule absolves the operator from the responsibility for ensuring the aircraft are maintained in an airworthy condition.
- Nothing in this document shall be construed as exempting the operator from responsibility for compliance with all applicable component life limits, Airworthiness Limitations, or other mandatory requirements.
- The operator shall ensure that all tasks listed in the currently approved revision of this schedule are completed within the intervals specified.
- The operator shall amend the schedule as and when directed by the Minister, and shall evaluate all recommendations issued in the form of Instructions for Continued Airworthiness (ICAs) and/or publications issued by the Type Certificate (TC) holder (airframe, engine, or propeller). These instructions need to be evaluated for applicability to an air operator's program in accordance with standard 726.07 of the CARs titled Air Operator Maintenance - Evaluation Program. Where appropriate, the operator shall initiate amendment action.
- Amendments to this schedule must be approved for any change in type of operation or operating role identified overleaf and, where maximum and minimum utilization data are specified, for any variation outside the limits indicated. Approval is also required for any task deletions, increases in intervals, or other significant changes. Transport Canada approval is not required for amendments that involve only the addition of tasks or a reduction of intervals; however the operator shall notify Transport Canada of these changes within 30 days.
- The operator shall ensure that maintenance personnel are provided with such records and other documents as are necessary to enable them to determine to their satisfaction, that the aircraft is in compliance with the airworthiness requirements applicable to the work undertaken. All work required by this schedule shall be released in accordance with CAR 571.10.
- The tolerances specified in this schedule shall not apply to any Airworthiness Limitations or Airworthiness Directives. Exceptions or deviations from this maintenance schedule must be submitted into Transport Canada for approval, together with substantiating data.

Conditions générales

- Ce document, ainsi que les pages supplémentaires indiquées ici, constituent la maintenance planifiée minimale à exécuter. Rien de ce qui est contenu ou omis dans le calendrier de maintenance ne décharge l'exploitant de la responsabilité de s'assurer que l'aéronef est maintenu en état de navigabilité.
- Rien dans ce document ne doit être interprété comme une exonération de la responsabilité de l'exploitant à l'égard de la conformité à toutes les limites de la durée de vie des composants, des limitations de la navigabilité et autres exigences obligatoires.
- L'exploitant doit faire en sorte que toutes les tâches énumérées dans la révision approuvée actuelle de ce calendrier sont exécutées dans les délais fixés.
- L'exploitant doit modifier le calendrier selon les directives du ministre et évaluer toutes les recommandations contenues dans les instructions de maintien de la navigabilité ou dans les publications délivrées par le titulaire du certificat de type (cellule, moteur ou hélice). Ces instructions doivent être évaluées en fonction du programme d'un exploitant aérien conformément à la norme 726.07 du RAC - Programme d'évaluation. Le cas échéant, l'exploitant prendra des dispositions pour effectuer les modifications.
- Les modifications apportées à ce calendrier doivent être approuvées pour tout changement de type d'exploitation ou du rôle de l'aéronef indiqués au verso, lorsque les données sur l'utilisation maximale et minimales sont précisées, pour tout écart par rapport aux limites indiquées. Il faut également une approbation pour toute suppression de tâche, augmentation des intervalles ou autres changements importants. L'approbation de Transports Canada n'est pas nécessaire pour les modifications qui impliquent l'ajout de tâches ou une réduction des intervalles uniquement; toutefois, l'exploitant doit avertir Transports Canada de ces changements dans un délai de 30 jours.
- L'exploitant doit faire en sorte que le personnel de la maintenance reçoive tous les dossiers et autres documents nécessaires pour lui permettre de déterminer, à sa satisfaction, que l'aéronef est conforme aux exigences de navigabilité qui s'appliquent aux travaux effectués. Tous les travaux exigés par ce calendrier feront l'objet d'une certification après maintenance, conformément au RAC 571.10.
- Les tolérances précisées dans ce calendrier ne s'appliquent pas aux limitations de navigabilité, ni aux circulaires de navigabilité.
- Les exceptions et les écarts par rapport à ce calendrier de maintenance, ainsi que la documentation justificative, doivent être présentés à Transports Canada afin d'obtenir une approbation.

Scheduled Check Cycle Cycle de vérification prévu

The aircraft will be inspected in accordance with the check cycle specified in table 1 below. Check intervals may be varied within the tolerances specified. Detailed instructions and procedures for scheduled maintenance are contained in the attached check list (the pages of which are identified in the revision status block) or in maintenance schedule reference.....Q-0798..... rev #.....6.....

L'aéronef doit être inspecté conformément au cycle de vérification précisé au tableau 1 ci-dessous. Les intervalles de vérification peuvent varier à l'intérieur des tolérances fixées. Les instructions et les procédures détaillées relatives au calendrier de maintenance figurent dans la liste de vérification ci-jointe (les pages en sont identifiées dans le bloc sur l'état de la révision) ou dans le renvoi au calendrier de maintenanceQ-0798.....n° de rév6.....

Table 1 - Check Cycle
Tableau 1 - Cycle de vérification

Check Vérification	Scheduled inspection interval Intervalle d'inspection prévu	Window Fenêtre
100 HRS/ ANNUAL	100 HRS or 12 MONTHS	+/- 10 HRS / 1 MONTH

Notes

(Use this section if necessary, to explain the operation of the check cycle)
Utiliser cette section au besoin pour expliquer le fonctionnement du cycle de vérification)

Note 1 : Les inspections sont effectuées dans une fenêtre de plus ou moins 10 hrs selon l'intervalle du tableau ci-haut.

Note 2 : Toutes les tâches hors calendrier (tableau 3) seront synchronisées selon leur calendrier avec la prochaine inspection prévue.

Out of Phase Tasks & Equipment Maintenance Requirements Tâches hors calendrier et exigences de maintenance de l'équipement

Engine & propeller overhauls and other maintenance tasks scheduled to occur out of phase with the inspection check cycle, shall be performed as indicated in table 3 below. Where applicable, the tasks may be identified by reference to separate documents, provided the documents are listed in table 2. Any out of phase tasks not listed shall be performed at the intervals specified in STD 625, Appendix C.

Note: Reference to other documents or to STD 625, Appendix C, does not relieve the owner/operator from the responsibility for determining the applicability of the tasks and intervals concerned, nor from the responsibility for identifying any other applicable maintenance requirements not listed therein. La révision des moteurs et des hélices et autres tâches de maintenance devant être effectuées en dehors du cycle des inspections sont exécutées conformément aux indications figurant au tableau 3 ci-dessous. Le cas échéant, on peut identifier les tâches en se reportant à des documents séparés, à condition qu'ils soient indiqués au tableau 2. Toutes les tâches hors calendrier qui ne sont pas indiquées seront exécutées aux intervalles précisés dans l'appendice C de la norme 625.

Remarque : Le renvoi à d'autres documents ou à l'appendice C de la norme 625 ne décharge pas le propriétaire/exploitant de la responsabilité de déterminer l'applicabilité des tâches et des intervalles en cause, ni de la responsabilité d'identifier les autres exigences de maintenance applicables ne figurant pas ici.

**Table 2 - Reference documents
Tableau 2 - Documents de référence**

Document Name Titre de document	Reference Number N° de référence	Revision Number N° de révision

**Table 3 - Out of phase tasks
Tableau 3 - Tâches hors calendrier**

Out of phase tasks & equipment maintenance requirements ⁴ Tâches hors calendrier et exigences de maintenance de l'équipement ⁴			
Item Article	Task Tâche	Interval ⁵ Intervalle ⁵	Tolerance Tolérance
Engines* Moteurs* O-235L2C	Overhaul Révision	2400 HRS	100 HRS
Propellers* Hélices* HÉLICE À PAS FIXE	CORROSION INSPECTION	5 YEARS	3 MONTHS
ALTERNATOR	INSPECT BRUSHES LEAD AND SLIPRING	500 HRS	50 HRS AND/OR NOTE 2
ALTIMETER	TEST AND CALIBRATION AWM 571 APP B	24 MONTHS	2 MONTHS
BEACON LIGHT SWITCH	REPLACE	ON CONDITION	N/A
BRACKET AIR FILTER	INSPECT REPLACE	100 HRS 12 MONTHS	NOTE 2 1 MONTH
BRAKE SYSTEM HOSES AND O-RING (CALIPER / MASTER CYLINDER)	INSPECT REPLACE ON CONDITION	1000 HRS	100 HRS AND/OR NOTE 2
COMPASS	CALIBRATE	12 MONTHS	1 MONTH
ELT	TEST AND CERTIFIED AS PER CAR'S 571 APP. G	12 MONTHS	1 MONTH
ELT BATTERY	REPLACE	REC. DU MANUF.	1 MONTH
ENCODER	TEST AND CALIBRATION AWM 571 APP F	24 MONTHS	2 MONTHS

⁴ Include additional pages where required. Ajouter des pages supplémentaires, au besoin.

⁵ Insert interval, specifying whether in hours, cycles or calendar time
Insérer les intervalles en précisant s'il s'agit d'heures, de cycles ou de périodes déterminées.

* Completion of engine and propeller details is mandatory. If applicable, indicate "On-condition."
Il est obligatoire de fournir des détails sur les moteurs et les hélices. Le cas échéant, indiquer « en état de marche ».

Out of phase tasks & equipment maintenance requirements (continued)
Tâches hors calendrier et exigences de maintenance de l'équipement (suite)

Item Article	Task Tâche	Interval Intervalle	Tolerance Tolérance
ENGINE CONTROLS	REPLACE	4800 HRS	100 HRS AND/OR NOTE 2
ENGINE HOSES	REPLACE	10 YEARS	3 MONTHS
FIRE EXTINGUISHER	INSPECT TEST HYDROSTATIC	12 MONTHS 12 YEARS	1 MONTH 1 MONTH
FIRST AID KIT	INSPECT CONTENT IF SEAL BROKEN OR REPLACE TIME X ITEM	12 MONTHS	1 MONTH
FUEL TANK AND SCREEN	DRAIN, INTERIOR CHECK AND ATTACHEMENT	1000 HRS	100 HRS AND/OR NOTE 2
GYRO CENTRAL AIR FILTER	REPLACE	500 HRS	100 HRS AND/OR NOTE 2
LANDING LIGHT SWITCH	REPLACE	ON CONDITION	N/A
MAGNETOS (INTERNAL)	INSPECT	500 HRS	50 HRS AND/OR NOTE 2
PITOT STATIC	TEST AND CALIBRATION AWM 571 APP B	24 MONTHS	2 MONTHS
STARTER	INSPECT	500 HRS	50 HRS AND/OR NOTE 2
STC : SA01695SE DOC NUMBER 190-00673-01 REV. F	VISUAL INSPECTION ANTENNA AND MOUNTING/WHEN INSTALLED ON THE AIRCRAFT	12 MONTHS	1 MONTH
STC : SA0181WI	G5 BATTERY CAPACITY TEST/ WHEN INSTALLED ON THE AIRCRAFT	12 MONTHS	1 MONTH
TACHOMETER	ACCURACY CHECK	12 MONTHS	1 MONTH
TAXI LIGHT SWITCH	REPLACE	ON CONDITION	N/A
TRANSPONDER	TEST AND CALIBRATION AWM 571 APP F	24 MONTHS	2 MONTHS
TRIM TAB ACTUATOR	LUBRICATE	1000 HRS OR 3 YEARS	100 HRS AND/OR NOTE 2
VACUUM RELIEF VALVE FILTER	REPLACE	300 HRS	30 HRS AND/OR NOTE 2
WHEEL BEARING	REPACK AND INSPECT	500 HRS	50 HRS AND/OR NOTE 2

Application and Maintenance Schedule Description ⁶

Application et description du calendrier de maintenance⁶

Check one of the following: – Cocher une des réponses suivantes :

- ☐ As a new operator of this aircraft type, the out of phase maintenance intervals specified in STD 625 Appendix C will be used.
À titre de nouvel exploitant de ce type d'aéronef, j'utiliserai les intervalles de maintenance hors calendrier précisés dans l'appendice C de la norme 625
- ☒ As an experienced operator of this aircraft type, or similar types, the out of phase intervals specified in STD 625 Appendix C have been revised as indicated in table 3 or in the documents referenced in table 2
À titre d'exploitant expérimenté de ce type d'aéronef, ou des types semblables, les intervalles hors calendrier précisés dans l'appendice C de la norme 625 ont été révisés comme il est indiqué au tableau 3 ou dans les documents mentionnés au tableau 2

Check one of the following:

Cocher une des réponses suivantes : The maintenance schedules & interim schedules are based upon:

Les calendriers de maintenance et les calendriers provisoires sont fondés sur les textes suivants :

- ☒ STD 625 Appendix B Part 1
Norme 625, appendice B, partie 1
The following manufacturer's recommendations
- ☐ Les calendriers de maintenance et les calendriers provisoires sont fondés sur les textes suivants :

Airframe Document: Document sur la cellule : _____	Rev # N° de rév _____
Engine Document: Document sur les moteurs : _____	Rev # N° de rév _____
Propeller Document: Document sur les hélices : _____	Rev # N° de rév _____
Other Document: Autre document : _____	Rev # N° de rév _____

- ☐ Another operator's maintenance schedule
Calendrier de maintenance d'un autre exploitant

Other operator:
Autre exploitant : _____

Approval no.: _____ (attach program).
N° d'approbation : _____ (joindre le programme)

- ☒ Other data (described below):
Autres données (décrire ci-dessous) :

⁶ The data on this page is provided for information purposes only, to facilitate Transport Canada evaluation of the schedule.

Les données figurant sur cette page sont fournies à titre d'information seulement pour faciliter l'évaluation du calendrier par Transports Canada.

MODEL 152 SERIES SERVICE MANUAL

- 2-46. **INSPECTION REQUIREMENTS** : As required by Federal Aviation Regulations, all aircraft must undergo a 100 hour and/or annual **inspection**.
- 2-47. **100 HOUR AND / OR ANNUAL INSPECTIONS**: (Refer to the Inspection Charts, Column 1.) This inspection requires each item marked with a symbol • to be inspected at each 100 hours of flight time and/or each 12th month following the last inspection recorded for the aircraft.
- 2-48. **SPECIAL INSPECTIONS**: (Refer to the Inspection Charts. Column 2.) This inspection requires each item that has a numeral inserted in the column be inspected in accordance with the corresponding numeral listed in the back of the Inspection Charts.
- 2-49. **PROGRESSIVE INSPECTIONS** : N/A
- 2-50. **INSPECTION GUIDE-LINES**. The guide-lines shown, preceeding the Inspection Charts, are suggested for your use when making the detailed inspections listed in the Inspection Charts.

INSPECTION GUIDE LINES

- (a) **MOVABLE PARTS** for: lubrication, servicing, security of attachment, binding, excessive wear, safetying, proper operation, proper adjustment, correct travel, cracked fittings, security of hinges, defective bearings, cleanliness, corrosion, deformation sealing and tension.
- (b) **FLUID LINES AND HOSES** for: leaks, cracks, dents, kinks , chafing, proper radius, security, corrosion, deterioration, obstruction and foreign matter.
- (c) **METAL PARTS** for: security of attachment, cracks, metal distortion, broken spot-welds, corrosion, condition of paint and any other apparent damage.
- (d) **WIRING** for: security, chafing, burning, defective insulation, loose or broken terminals, heat deterioration and corroded terminals.
- (e) **BOLTS IN CRITICAL AREAS** for: correct torque in accordance swith torque values given in the chart in Section1, when installed or when visual inspection indicates the need for a torque check.
- (f) **FILTERS, SCREENS & FLUIDS** for: cleanliness, contamination and/or replacement at specified intervals.
- (g) **AIRCRAFT FILE**:

Miscellaneous data, information and licenses are a part of the aircraft file. Check that the following documents are up-to-date and in accordance with current Federal Aviation Regulations. Most of the items listed are required by the United States Federal Aviation Regulations. Since the regulations of other nations may require other documents and data, owners of exported aircraft should check with their own aviation officials to determine their individual requirements.

To be displayed in the aircraft at all times:

1. Aircraft Airworthiness Certificate (FAA Form 8100-2).
2. Aircraft Registration Certificate (FAA Form 8050-3).
3. Aircraft Radio Station License, if transmitter is installed (FCC Form 556).

MODEL 152 SERIES SERVICE MANUAL

To be carried in the aircraft at all times:

1. Weight and Balance and associated papers (Latest copy of the Repair and Alteration Form, FAA Form 337, if applicable).
2. Aircraft Equipment List.
3. Pilot's Operating handbook.

To be made available upon request:

1. Aircraft log Book and Engine Log Book.

(h) ENGINE RUN-UP:

Before beginning the step-by-step inspection, start, runup and shut down the engine in accordance with instructions in the Pilot's Operating Handbook. During the run-up observe the following, making note of any discrepancies or abnormalities:

1. Engine temperatures and pressures.
2. Static RPM. (Also refer to Section 11 of this manual.)
3. Magneto drop. (Also refer to Section 11 of this manual.)
4. Engine response to changes in power.
5. Any unusual engine noises.
6. Fuel shutoff valve; operate engine long enough to ensure shutoff valve functions properly.
7. Idling speed and mixture; proper idle cut-off.
8. Alternator and ammeter.
9. Suction gage.

After the inspection has been completed, an engine run-up should again be performed to determine that any discrepancies or abnormalities have been corrected.

MODEL 152 SERIES SERVICE MANUAL

INSPECTION CHARTS

IMPORTANT

READ ALL PRECEEDING PARAGRAPHS FOR INSPECTION
REQUIREMENT PRIOR TO USING THESE CHARTS

TYPE OF INSPECTION

(Refer to Para. 2-48) 2. SPECIAL

(Refer to Para. 2.47) 1. 100 HR/ANNUAL

PROPELLER

- | | |
|---------------------------|---|
| 1. Spinner..... | ● |
| 2. Spinner bulkhead | ● |
| 3. Blades | ● |
| 4. Bolts and/or nuts..... | ● |
| 5. Hub..... | ● |

ENGINE COMPARTMENT

Check for evidence of oil and fuel leaks, then clean entire engine compartement,
if needed, prior to inspection.

- | | | |
|---|---|----|
| 1. Engine oil, filler cap, dipstick, drain plug and external filter
element..... | ● | |
| 2. Oil cooler..... | ● | |
| 3. Induction air filter | ● | 1 |
| 4. Induction airbox, air valves, doors and controls | ● | |
| 5. Cold and hot air hoses..... | ● | |
| 6. Engine baffles..... | ● | |
| 7. Cylinders, rocker box covers and push rod housings | ● | |
| 8. Crankcase, oil sump, accessory section and front crankshaft
seal..... | ● | |
| 9. Hoses, metal lines and fittings | ● | 2 |
| 10. Intake and exhaust systems | ● | 3 |
| 10A Exhaust valves and guides..... | ● | 24 |
| 11. Ignition harness..... | ● | |
| 12. Spark plugs..... | ● | |
| 13. Compression check | ● | |
| 14. Crankcase and vacuum system breather lines | ● | |
| 15. Electrical wiring..... | ● | |
| 16. Vacuum pump..... | ● | |
| 17. Vacuum relief valve filter | ● | 20 |
| 18. Engine controls and linkage..... | ● | 5 |
| 19. Engine shock mounts, mount structure and ground straps | ● | |

MODEL 152 SERIES SERVICE MANUAL

TYPE OF INSPECTION

(Refer to Para. 2-48) 2. SPECIAL

(Refer to Para. 2.47) 1. 100 HR/ANNUAL

20. Cabin heat valves, doors and controls	●	
21. Starter, solenoid and electrical connections.....	●	
22. Starter brushes, brush leads and commutator	●	6
23. Alternator mounting bracket	●	
24. Alternator, belt and electrical connections.....	●	15
25. Alternator brushes, brush leads, commutator or slip ring	●	6
26. Voltage regulator mounting and electrical leads	●	
27. Magnetos (externally) and electrical connections	●	18
28. Magnetos (internally)	●	23
29. Magneto timing.....	●	7
30. Carburetor and drain plug	●	
31. Firewall.....	●	
32. Engine cowling.....	●	
33. Tappet clearance	●	14
34. Vacuum system central air filter.....	●	21

FUEL SYSTEM

1. Fuel strainer, drain valve and control	●	
2. Fuel strainer screen and bowl	●	
3. Fuel tank vents, caps and placards	●	
4. Fuel tanks, sump drains and fuel line drains	●	
5. Drain fuel and check tank interior, attachment and outlet screens	●	4
6. Fuel vent valves.....	●	
7. Fuel vent line drain.....	●	
8. Fuel shutoff valve and placards	●	
9. Fuel valve drain plug.....	●	
10. Engine primer	●	
11. For airplanes equipped with a Stewart Warner manufactured fuel quantity indicating system, perform a fuel indicating system accuracy test. Refer to Cessna Service Bulletin SEB99-18, Fuel Quantity Indicating System Inspection (or latest revision) for detailed accomplishment instructions	●	25

MODEL 152 SERIES SERVICE MANUAL

TYPE OF INSPECTION

(Refer to Para. 2-48) 2. SPECIAL

(Refer to Para. 2.47) 1. 100 HR/ANNUAL

LANDING GEAR

1. Main gear wheel and fairings.....	●	13
2. Nose gear wheel, torque links, steering rods, boots and fairing	●	13
3. Wheel bearings.....	●	8
4. Nose gear strut and shimmy dampener	●	
5. Tires	●	
6. Brake fluid, lines and hoses, linings, discs, brake assemblies and master cylinders.....	●	17
7. Parking brake system	●	
8. Main gear springs.....	●	

AIRFRAME

1. Aircraft exterior	●	
2. Aircraft structure.....	●	22
3. Windows, windshield, doors and seals	●	
4. Seat belts and shoulder harnesses.....	●	
5. Seat stops, seat rails, upholstery, structure and mounting	●	19
6. Control 'Y' bearings, sprockets, pulleys, cables, chains and turnbuckles.....	●	
7. Control lock, control wheel and control 'Y' mechanism.....	●	
8. Instruments and markings.....	●	
9. Gyros central air filter	●	9
10. Magnetic compass compensation	●	
11. Instrument wiring and plumbing	●	
12. Instrument panel, shockmounts, ground straps, cover, decals and labeling	●	
13. Defrosting, heating and ventilating systems and controls.....	●	
14. Cabin upholstery, trim, sunvisors and ash trays	●	
15. Area beneath floor, lines, hose, wires and control cables	●	
16. Lights, switches, circuit breakers, fuses and spare fuses	●	26
17. Exterior lights	●	
18. Pitot and static systems	●	
19. Stall warning system.....	●	
20. Radios, radio controls, avionics and flight instruments	●	

MODEL 152 SERIES SERVICE MANUAL

TYPE OF INSPECTION

(Refer to Para. 2-48) **2. SPECIAL**

(Refer to Para. 2.47) **1. 100 HR/ANNUAL**

21. Antennas and cables.....	●	
22. Battery, battery box and battery cables.....	●	
23. Emergency locator transmitter.....	●	10

CONTROL SYSTEMS

In addition to the items listed below, always check for correct direction of movement, correct travel and correct cable tension.

1. Cables, terminals, pulleys, pulley brackets, cable guards, turnbuckles and fairleads	●	
2. Chains, terminals, sprockets and chain guards.....	●	
3. Trim control wheels, indicators, actuator and bungee	●	
4. Travel stops	●	
5. Decals and labeling.....	●	
6. Flap control switch, flap rollers and tracks, flap indicator.....	●	
7. Flap motor, transmission, limit switches, structure, linkage, bellcranks, etc	●	
8. Elevator and trim tab hinges, tips and control rods	●	
9. Elevator trim tab actuator lubrication	●	11
10. Elevator trim tab free-play inspection.....	●	12
11. Rudder pedal assemblies and linkage.....	●	
12. Skins (external) of control surfaces and tabs	●	
13. Internal structure of control surfaces	●	
14. Balance weight attachment	●	
15. Ailerons, hinges and push-pull rods.....	●	
16. Vertical fin attach brackets.....	●	16

MODEL 152 SERIES SERVICE MANUAL

SPECIAL INSPECTION ITEMS

- 1 Replace 12 months or 50% surface contamination.
- 2 Replace engine compartment rubber hoses every 10 years. This does not include drain hoses (on condition).
- 3 Refer to Section 11 for 100 hour inspection procedures.
- 4 Each 1000 hours.
- 5 Each 100 hours for general conditions and freedom of movement. These controls are not repairable. Replace every 4800 hours.
- 6 Inspect each 500 hours.
- 7 MAGNETO-TO-ENGINE TIMING: Serials Thru 15284027 & A1520914. first 25 hours, first 50 hours, first 100 hours, and thereafter at each 100 hours: Beginning with Serials 15284028 & A1520915, first 100 hours and each 100 hours thereafter, the magneto-to-engine timing should be checked. Refer to Section 11.
- 8 Each 500 hours. More often if operated under prevailing wet or dusty conditions.
- 9 Replace each 500 hours.
- 10 Refer to Section 16 of this Manual for inspection procedure.
- 11 Lubrication of the actuator is required each 1000 hours or 3 years, whichever comes first.
- 12 Refer to Section 9 of this Manual for free-play limits, inspection, replacement and/or repair.
- 13 If aircraft is flown from surfaces with mud, snow or ice, the speed fairings should be checked that there is no accumulation which could prevent normal wheel rotation.
- 14 Refer to Avco Lycoming Service Overhaul Manual and Avco Lycoming Service Instruction No. 1068, and any applicable Service Bulletins or Service Letters, for further recommendations.
- 15 Refer to Section 16 of this Manual for inspection procedure.
- 16 Compliance with Service Letter No. SE78-62, SE79-49, and all Supplements thereto is required.
- 17 Each 1000 hours. Inspect brake system hoses (Flush Hydraulic Fluid) and O-Ring (replace Caliper/Master cylinder, On condition).
- 18 Following 800 hour replacement of original magnetos, refer to Section II of this Manual and Slick 4200/6200 Series Aircraft Magnetos Maintenance and Overhaul Instructions Bulletin, and all revisions and supplements thereto, for 500 hour inspection requirements.

MODEL 152 SERIES SERVICE MANUAL

- 19 Inspect seat rails for cracks every 100 hours. Refer to figure 3-10.
- 20 Remove and replace with new filter every 300 hours.
- 21 Inspect for damage every 200 hours; replace every 500 hours.
- 22 Vertical fin attachment each annual or 100 hour inspection. However, it is recommended nutplates used to attach vertical fin be inspected after each 100 operational hours. Refer to paragraph 4-14A for detailed instructions.
- 23 Each 500 hours. Inspect contact points. Inspect carbon brush, high tension lead, and distributor block. Inspect impulse, coupling, and pawls. Replace as required. Inspect and lubricate bearings and contact point cam. Refer to Slick 4300/6300 Series Aircraft Maintenance and Overhaul Instructions Bulletin and all revisions and supplements thereto.
- 24 Each 400 hours. Refer to Textron Lycoming Mandatory Service Bulletin No. 388C, Procedure to Determine Exhaust Valve and Guide Condition, and all revisions and supplements thereto, for 400-hour inspection requirement.
- 25 Fuel quantity indicating system accuracy test is required every 12 months. Refer to Cessna Service Bulletin SEB99-18, Fuel quantity Indicating System inspection (or latest revision) for detailed accomplishment instructions.
- 26 On condition