

Date : 3rd - Nov- 2020

Morning Session : 9am – 11.00 PM


By ~ Rohan Kumar

Topics: Computer Networks - 2

OSI Model

- OSI stands for **Open System Interconnection** is a reference model that describes how information from a software application in one computer moves through a physical medium to the software application in another computer.
- OSI consists of seven layers, and each layer performs a particular network function.
- The OSI model was developed by the International Organization for Standardization (ISO) in 1984, and it is now considered as an architectural model for inter-computer communications.
- The OSI model divides the whole task into seven smaller and manageable tasks. Each layer is assigned a particular task.
- Each layer is self-contained, so that tasks assigned to each layer can be performed independently.

Characteristics of OSI Model:




- The OSI model is divided into two layers: upper layers and lower layers.
- The upper layer of the OSI model mainly deals with the application related issues, and they are implemented only in the software. The application layer is closest to the end user. Both the end user and the application layer interact with the software applications. An upper layer refers to the layer just above another layer.
- The lower layer of the OSI model deals with the data transport issues. The data link layer and the physical layer are implemented in hardware and software. The physical layer is the lowest layer of the OSI model and is closest to the physical medium. The physical layer is mainly responsible for placing the information on the physical medium.


Functions of the OSI Layers

There are the seven OSI layers. Each layer has different functions. A list of seven layers are given below:

1. Physical Layer
2. Data-Link Layer
3. Network Layer
4. Transport Layer
5. Session Layer
6. Presentation Layer
7. Application Layer



Physical layer :




- The main functionality of the physical layer is to transmit the individual bits from one node to another node.
- It is the lowest layer of the OSI model.
- It establishes, maintains and deactivates the physical connection.
- It specifies the mechanical, electrical and procedural network interface specifications.

Functions of a Physical layer:

- **Line Configuration:** It defines the way how two or more devices can be connected physically.
- **Data Transmission:** It defines the transmission mode whether it is simplex, half-duplex or full-duplex mode between the two devices on the network.
- **Topology:** It defines the way network devices are arranged.
- **Signals:** It determines the type of the signal used for transmitting the information.

Data-Link Layer :



- This layer is responsible for the error-free transfer of data frames.
- It defines the format of the data on the network.
- It provides a reliable and efficient communication between two or more devices.

- It is mainly responsible for the unique identification of each device that resides on a local network.
- It contains two sub-layers:
 - **Logical Link Control Layer**
 - It is responsible for transferring the packets to the Network layer of the receiver that is receiving.
 - It identifies the address of the network layer protocol from the header.
 - It also provides flow control.
 - **Media Access Control Layer**
 - A Media access control layer is a link between the Logical Link Control layer and the network's physical layer.
 - It is used for transferring the packets over the network.

Functions of the Data-link layer:

- **Framing:** The data link layer translates the physical's raw bit stream into packets known as Frames. The Data link layer adds the header and trailer to the frame. The header which is added to the frame contains the hardware destination and source address.




- **Physical Addressing:** The Data link layer adds a header to the frame that contains a destination address. The frame is transmitted to the destination address mentioned in the header.
- **Flow Control:** Flow control is the main functionality of the Data-link layer. It is the technique through which the constant data rate is maintained on both the sides so that no data get corrupted. It ensures that the transmitting station such as a server with higher processing speed does not exceed the receiving station, with lower processing speed.
- **Error Control:** Error control is achieved by adding a calculated value CRC (Cyclic Redundancy Check) that is placed to the Data link layer's trailer which is added to the

message frame before it is sent to the physical layer. If any error seems to occur, then the receiver sends the acknowledgment for the retransmission of the corrupted frames.

- **Access Control:** When two or more devices are connected to the same communication channel, then the data link layer protocols are used to determine which device has control over the link at a given time.

Network Layer :




- It is a layer 3 that manages device addressing, tracks the location of devices on the network.
- It determines the best path to move data from source to the destination based on the network conditions, the priority of service, and other factors.
- The Data link layer is responsible for routing and forwarding the packets.
- Routers are the layer 3 devices, they are specified in this layer and used to provide the routing services within an internetwork.
- The protocols used to route the network traffic are known as Network layer protocols. Examples of protocols are IP and Ipv6.

Functions of Network Layer:

- **Internetworking:** An internetworking is the main responsibility of the network layer. It provides a logical connection between different devices.
- **Addressing:** A Network layer adds the source and destination address to the header of the frame. Addressing is used to identify the device on the internet.
- **Routing:** Routing is the major component of the network layer, and it determines the best optimal path out of the multiple paths from source to the destination.
- **Packetizing:** A Network Layer receives the packets from the upper layer and converts them into packets. This process is known as Packetizing. It is achieved by internet protocol (IP).

Transport Layer :



- The Transport layer is a Layer 4 ensures that messages are transmitted in the order in which they are sent and there is no duplication of data.
- The main responsibility of the transport layer is to transfer the data completely.

- It receives the data from the upper layer and converts them into smaller units known as segments.
- This layer can be termed as an end-to-end layer as it provides a point-to-point connection between source and destination to deliver the data reliably.

The two protocols used in this layer are:

- **Transmission Control Protocol**
 - It is a standard protocol that allows the systems to communicate over the internet.
 - It establishes and maintains a connection between hosts.
 - When data is sent over the TCP connection, then the TCP protocol divides the data into smaller units known as segments. Each segment travels over the internet using multiple routes, and they arrive in different orders at the destination. The transmission control protocol reorders the packets in the correct order at the receiving end.
- **User Datagram Protocol**
 - User Datagram Protocol is a transport layer protocol.
 - It is an unreliable transport protocol as in this case the receiver does not send any acknowledgement when the packet is received, the sender does not wait for any acknowledgment. Therefore, this makes a protocol unreliable.


Functions of Transport Layer:

- **Service-point addressing:** Computers run several programs simultaneously due to this reason, the transmission of data from source to the destination not only from one computer to another computer but also from one process to another process. The transport layer adds the header that contains the address known as a service-point address or port address. The responsibility of the network layer is to transmit the data from one computer to another computer and the responsibility of the transport layer is to transmit the message to the correct process.
- **Segmentation and reassembly:** When the transport layer receives the message from the upper layer, it divides the message into multiple segments, and each segment is assigned with a sequence number that uniquely identifies each segment. When the message has arrived at

the destination, then the transport layer reassembles the message based on their sequence numbers.

- **Connection control:** Transport layer provides two services Connection-oriented service and connectionless service. A connectionless service treats each segment as an individual packet, and they all travel in different routes to reach the destination. A connection-oriented service makes a connection with the transport layer at the destination machine before delivering the packets. In connection-oriented service, all the packets travel in the single route.
- **Flow control:** The transport layer is also responsible for flow control but it is performed end-to-end rather than across a single link.
- **Error control:** The transport layer is also responsible for Error control. Error control is performed end-to-end rather than across the single link. The sender transport layer ensures that messages reach the destination without any error.

Session Layer :




- It is a layer 3 in the OSI model.
- The Session layer is used to establish, maintain and synchronizes the interaction between communicating devices.

Functions of Session layer:

- **Dialog control:** Session layer acts as a dialog controller that creates a dialog between two processes or we can say that it allows the communication between two processes which can be either half-duplex or full-duplex.
- **Synchronization:** Session layer adds some checkpoints when transmitting the data in a sequence. If some error occurs in the middle of the transmission of data, then the transmission will take place again from the checkpoint. This process is known as Synchronization and recovery.

Presentation Layer :




- A Presentation layer is mainly concerned with the syntax and semantics of the information exchanged between the two systems.
- It acts as a data translator for a network.
- This layer is a part of the operating system that converts the data from one presentation format to another format.
- The Presentation layer is also known as the syntax layer.

Functions of Presentation layer:

- **Translation:** The processes in two systems exchange the information in the form of character strings, numbers and so on. Different computers use different encoding methods, the presentation layer handles the interoperability between the different encoding methods. It converts the data from sender-dependent format into a common format and changes the common format into receiver-dependent format at the receiving end.
- **Encryption:** Encryption is needed to maintain privacy. Encryption is a process of converting the sender-transmitted information into another form and sends the resulting message over the network.
- **Compression:** Data compression is a process of compressing the data, i.e., it reduces the number of bits to be transmitted. Data compression is very important in multimedia such as text, audio, video.

Application Layer :



- An application layer serves as a window for users and application processes to access network service.
- It handles issues such as network transparency, resource allocation, etc.
- An application layer is not an application, but it performs the application layer functions.
- This layer provides the network services to the end-users.

Functions of Application layer:

- File transfer, access, and management (FTAM): An application layer allows a user to access the files in a remote computer, to retrieve the files from a computer and to manage the files in a remote computer.
- Mail services: An application layer provides the facility for email forwarding and storage.
- Directory services: An application provides the distributed database sources and is used to provide that global information about various objects.

DNS

next → ← prev

DNS

An application layer protocol defines how the application processes running on different systems, pass the messages to each other.

- DNS stands for Domain Name System.
- DNS is a directory service that provides a mapping between the name of a host on the network and its numerical address.
- DNS is required for the functioning of the internet.
- Each node in a tree has a domain name, and a full domain name is a sequence of symbols specified by dots.
- DNS is a service that translates the domain name into IP addresses. This allows the users of networks to utilize user-friendly names when looking for other hosts instead of remembering the IP addresses.
- For example, suppose the FTP site at EduSoft had an IP address of 132.147.165.50, most people would reach this site by specifying ftp.EduSoft.com. Therefore, the domain name is more reliable than an IP address.

DNS is a TCP/IP protocol used on different platforms. The domain name space is divided into three different sections: generic domains, country domains, and inverse domains.

Working of DNS

- DNS is a client/server network communication protocol. DNS clients send requests to the server while DNS servers send responses to the client.
- Client requests contain a name which is converted into an IP address known as a forward DNS lookups while requests containing an IP address which is converted into a name known as reverse DNS lookups.
- DNS implements a distributed database to store the name of all the hosts available on the internet.
- If a client like a web browser sends a request containing a hostname, then a piece of software such as **DNS resolver** sends a request to the DNS server to obtain the IP address of a hostname. If a DNS server does not contain the IP address associated with a hostname, then it forwards the request to another DNS server. If the IP address has arrived at the resolver, which in turn completes the request over the internet protocol.

There are two types of IP addresses:

- IPv4
- IPv6

What is IPv4?

IPv4 is a version 4 of IP. It is a current version and the most commonly used IP address. It is a 32-bit address written in four numbers separated by 'dot', i.e., periods. This address is unique for each device.

For example, **66.94.29.13**

The above example represents the IP address in which each group of numbers separated by periods is called an Octet. Each number in an octet is in the range from 0-255. This address can produce 4,294,967,296 possible unique addresses.

In today's computer network world, computers do not understand the IP addresses in the standard numeric format as the computers understand the numbers in binary form only. The binary number can be either 1 or 0. The IPv4 consists of four sets, and these sets represent the octet. The bits in each octet represent a number.

Each bit in an octet can be either 1 or 0. If the bit is 1, then the number it represents will count, and if the bit is 0, then the number it represents does not count.

Representation of 8 Bit Octet

128	64	32	16	8	4	2	1
-----	----	----	----	---	---	---	---

The above representation shows the structure of 8-bit octet.

Now, we will see how to obtain the binary representation of the above IP address, i.e., 66.94.29.13

Step 1: First, we find the binary number of 66.

128	64	32	16	8	4	2	1
0	1	0	0	0	0	1	0

To obtain 66, we put 1 under 64 and 2 as the sum of 64 and 2 is equal to 66 ($64+2=66$), and the remaining bits will be zero, as shown above. Therefore, the binary bit version of 66 is 01000010.

Step 2: Now, we calculate the binary number of 94.

128	64	32	16	8	4	2	1
0	1	0	1	1	1	1	0

To obtain 94, we put 1 under 64, 16, 8, 4, and 2 as the sum of these numbers is equal to 94, and the remaining bits will be zero. Therefore, the binary bit version of 94 is 01011110.

Step 3: The next number is 29.

128	64	32	16	8	4	2	1
0	0	0	1	1	1	0	0

To obtain 29, we put 1 under 16, 8, 4, and 1 as the sum of these numbers is equal to 29, and the remaining bits will be zero. Therefore, the binary bit version of 29 is 00011101.

Step 4: The last number is 13.

128	64	32	16	8	4	2	1
0	0	0	0	1	1	0	1

To obtain 13, we put 1 under 8, 4, and 1 as the sum of these numbers is equal to 13, and the remaining bits will be zero. Therefore, the binary bit version of 13 is 00001101.

Drawback of IPv4

Currently, the population of the world is 7.6 billion. Every user is having more than one device connected with the internet, and private companies also rely on the internet. As we know that IPv4 produces 4 billion addresses, which are not enough for each device connected to the internet on a planet. Although the various techniques were invented, such as variable-length mask, network address translation, port address translation, classes, inter-domain translation, to conserve the bandwidth of IP address and slow down the depletion of an IP address. In these techniques, public IP is converted into a private IP due to which the user having public IP can also use the internet. But still, this was not so efficient, so it gave rise to the development of the next generation of IP addresses, i.e., IPv6.

What is IPv6?

IPv4 produces 4 billion addresses, and the developers think that these addresses are enough, but they were wrong. IPv6 is the next generation of IP addresses. The main difference between IPv4 and IPv6 is the address size of IP addresses. The IPv4 is a 32-bit address, whereas IPv6 is a 128-bit hexadecimal address. IPv6 provides a large address space, and it contains a simple header as compared to IPv4.

It provides transition strategies that convert IPv4 into IPv6, and these strategies are as follows:


- **Dual stacking:** It allows us to have both the versions, i.e., IPv4 and IPv6, on the same device.
- **Tunneling:** In this approach, all the users have IPv6 communicates with an IPv4 network to reach IPv6.
- **Network Address Translation:** The translation allows the communication between the hosts having a different version of IP.

This hexadecimal address contains both numbers and alphabets. Due to the usage of both the numbers and alphabets, IPv6 is capable of producing over 340 undecillion (3.4×10^{38}) addresses.

IPv6 is a 128-bit hexadecimal address made up of 8 sets of 16 bits each, and these 8 sets are separated by a colon. In IPv6, each hexadecimal character represents 4 bits. So, we need to convert 4 bits to a hexadecimal number at a time

Address format

The address format of IPv4:



The address format of IPv6:



The above diagram shows the address format of IPv4 and IPv6. An IPv4 is a 32-bit decimal address. It contains 4 octets or fields separated by 'dot', and each field is 8-bit in size. The number that each field contains should be in the range of 0-255. Whereas an IPv6 is a 128-bit hexadecimal address. It contains 8 fields separated by a colon, and each field is 16-bit in size.

World Wide Web (WWW)

The **World Wide Web** abbreviated as WWW and commonly known as the web.

Working of WWW:

The World Wide Web is based on several different technologies : Web browsers, Hypertext Markup Language (HTML) and Hypertext Transfer Protocol (HTTP).

An Web browser is used to access webpages. Web browsers can be defined as programs which display text, data, pictures, animation and video on the Internet. Hyperlinked resources on the World Wide Web can be accessed using software interface provided by Web browsers. Initially Web browsers were used only for surfing the Web but now they have become more universal. Web browsers can be used for several tasks including conducting searches, mailing, transferring files, and much more. Some of the commonly used browsers are Internet Explorer, Opera Mini, Google Chrome.

Features of WWW:

- HyperText Information System
- Cross-Platform
- Distributed
- Open Standards and Open Source
- Uses Web Browsers to provide a single interface for many services

- Dynamic, Interactive and Evolving.
- “Web 2.0”

Components of Web

There are 3 components of web:

1. **Uniform Resource Locator (URL)**: serves as a system for resources on the web.
2. **HyperText Transfer Protocol (HTTP)**: specifies communication of browser and server.
3. **Hyper Text Markup Language (HTML)**: defines structure, organisation and content of webpage.

CDN (Content Delivery Network)

<https://web.dev/content-delivery-networks/>

1. Transport layer aggregates data from different applications into a single stream before passing it to _____
 - a) network layer
 - b) data link layer
 - c) application layer
 - d) physical layer

Answer: A

2. Which of the following are transport layer protocols used in networking?

- a) TCP and FTP
- b) UDP and HTTP
- c) TCP and UDP
- d) HTTP and FTP

Answer: C

3. The network layer protocol for internet is _____

- a) ethernet
- b) internet protocol
- c) hypertext transfer protocol
- d) file transfer protocol

Answer: B

4. The network layer is concerned with _____ of data.

- a) bits
- b) frames
- c) packets
- d) bytes

Answer: C

