PHYSICS WALLAH

MECHANICS OF SOLIDS

STRAIN

01 Longitudinal strain $= \frac{\Delta L}{L} = \frac{\text{Change in length}}{\text{Original length}}$

02 Volumetric strain $= \frac{\Delta V}{V} = \frac{\text{Change in volume}}{\text{Original volume}}$

03 Shearing strain $= \phi = \frac{\Delta x}{L}$

LONGITUDINAL STRESS

Longitudinal/Tensile stress causes increase in length

Longitudinal stress $= \frac{F}{A}$ unit N/m^2

Tensile stress in wire

$T.S = \frac{Fm}{(M+m)/A}$

$T.S = T = \frac{m(g+a)}{A}$

$T.S_1 = \frac{T_1}{A} = \frac{6\ mg}{A}$

$T.S_2 = \frac{T_2}{A} = \frac{5\ mg}{A}$

$T.S_3 = \frac{T_3}{A} = \frac{3\ mg}{A}$

VOLUME STRESS

- Same as pressure
- Causes change in volume

volume stress $= \frac{F}{A}$ = pressure

here, F = normal force (or thrust)

SHEARING STRESS

- Causes change in shape

shearing stress $= \frac{F_t}{A}$

F_t = tangential force

HOOKE' S LAW

$E = \frac{\text{Stress}}{\text{Strain}}$

(E= modulus of elasticity)

$\tan\theta$ = modulus of elasticity



1. For rigid body E = infinity
2. Steel is more elastic than rubber
3. Depends on :-
   (a) Nature of metal
   (b) Temperature
4. Independent of dimensions

risid body

Young's modulus

E

Bulk Modulus

Modulus of rigidity

STRESS STRAIN CURVE



OA - Hooke's law obeyed

A - Proportional limit

AB - stress is not proportional to strain but body regains it's original shape and size regains load is removed

B - Yield point

B to D - Body doesn't regain it's original dimension. Beyond B is plastic region.

D - Ultimate stress point

Beyond D - large strain is produced even for a small applied force.

E - Fracture occurs



Plastic region is large for ductile materials and smaller for brittle materials

BREAKING STRESS

Breaking Force= breaking stress x area, $B.F \propto A$

$\frac{F_1}{A_1} = \frac{F_2}{A_2} \Rightarrow (B.S)_1 = (B.S)_2$

BREAKING OF WIRE UNDER IT'S OWN WEIGHT

B.S X A =T= mg

B.S X A = $V \times \rho x g = A\, L_{max}\, \rho\, g$

$L_{max} = \frac{B.S}{\rho g}$

RATIO OF DENSITY OF BODY TO THAT OF LIQUID IN WHICH BODY IS IMMERSED

$mg = Kl_a$

$mg\left(1-\frac{\rho}{\sigma}\right) = Kl_b$

$\left(1-\frac{\rho}{\sigma}\right) = \frac{l_b}{l_a}$

$\frac{\rho}{\sigma} = \frac{l_a - l_b}{l_a}$

$\frac{\sigma}{\rho} = \frac{l_a}{l_a - l_b}$

Liquid of density ρ

here, l_a and l_b are extensions in the rod in the two cases.

YOUNG'S MODULUS

$Y = \frac{\text{Longitudnal stress}}{\text{Longitudnal strain}} = \frac{FL}{A\Delta L}$

Comparing with a spring of force constant K

$Y = \frac{FL}{Ax}$ $\quad F = \frac{AYx}{L} = kx$ $\quad k = \frac{AY}{L}$

POISSON'S RATIO

$\sigma = \frac{\text{Lateral strain}}{\text{Longitudinal strain}}$ $\quad \sigma = \frac{(-dr/r)}{\left(\frac{dL}{L}\right)} = \frac{-\frac{\Delta r}{r}}{\frac{\Delta l}{l}} = \frac{-\frac{\Delta D}{D}}{\frac{\Delta l}{l}}$

Theoretical value :- $-1 < \sigma < 0.5$

Practical value :- $0 < \sigma < 0.5$

ELASTIC POTENTIAL ENERGY AND ENERGY DENSITY

$E.PE = \frac{1}{2}kx^2 = \frac{F^2}{2k} = \frac{1}{2}Fx$

$= \frac{1}{2}\left(\frac{YA}{L}\right)x^2$

$= \frac{1}{2} \times \frac{\text{Stress}}{\text{Strain}} \times \text{volume} \times \text{strain}^2$

$= \frac{1}{2} \times \text{Stress} \times \text{strain} \times \text{volume}$

Energy Density $= \frac{EPE}{\text{volume}}$

$\Rightarrow e = \frac{1}{2} \times \text{Stress} \times \text{strain}$

INCREASE IN LENGTH DUE TO IT'S OWN WEIGHT

$F = kx$

$mg = \frac{YA}{\frac{L}{2}}x$

$x = \frac{mgL}{2YA}$

$P.E = \frac{F^2}{2k}$

$= \frac{m^2 g^2}{2\frac{YA}{\frac{L}{2}}} = \frac{1}{4}\frac{m^2 g^2 L}{YA}$

RATIO OF EXTENSION

$T=3mg$, $T=2mg$

$\frac{x_1}{x_2} = \frac{\frac{F_1}{k_1}}{\frac{F_2}{k_2}} = \frac{\frac{3mg \times L_1}{Y_1 \times A_1}}{\frac{2mg \times L_2}{Y_2 \times A_2}} = \frac{3l}{2yd^2}$

where $l = \frac{L_1}{L_2}$ $\quad y = \frac{Y_1}{Y_2}$ $\quad d = \frac{D_1}{D_2}$

BULK MODULUS

Bulk modulus, $B = \frac{\text{Volumetric stress}}{\text{Volumetric strain}} = \frac{\Delta P}{-\frac{\Delta V}{V}}$

$K = \frac{1}{B}$ = compressibility

$B_{isothermal} = P$, $\quad B_{adibatic} = \gamma P$, $\quad B_{isotropic} = xP$

MODULUS OF RIGIDITY

$\eta = \frac{\text{shear stress}}{\text{shear strain}} = \frac{F}{A\phi} = \frac{Fl}{Ax}$