Bridge API Docs

auth

o > read

| GET | /auth/o/{provider}/   ⇄ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
provider `required`	

o > create

| POST | /auth/o/{provider}/   ⇄ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
provider `required`	

token > create > create

| POST | /auth/token/create/   ⇄ INTERACT

Use this endpoint to obtain user authentication token.

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description

password	
email	

token > destroy > create

`POST` `/auth/token/destroy/`
Use this endpoint to logout user (remove user authentication token).

token > login > create

`POST` `/auth/token/login/`
Use this endpoint to obtain user authentication token.

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
password	
email	

token > logout > create

`POST` `/auth/token/logout/`
Use this endpoint to logout user (remove user authentication token).

event-categories

list

`GET` `/event-categories/`
Returns the tree of all event categories via GET. Allows any.

read

`GET` `/event-categories/{id}/`
Returns a particular branch of event categories via GET. Allows any.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	

events

list

GET /events/ ⇄ INTERACT

Returns a list of all events via GET. Authenticated only.

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
page	A page number within the paginated result set.
page_size	Number of results to return per page.
search	
event_category	
day	
month	
year	
featured	
subscribed_to	
interested_in	
show_past	
ordering	

create

POST /events/ ⇄ INTERACT

Create a new event via POST. Host admins only.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
title required	
hosts_id required	
category_id required	
start_time	
end_time	
location	
description	
image	
image_ppoi	
open_to_id required	

read

⇄ INTERACT

GET /events/{id}/

Returns the given event via GET. Authenticated only.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
search	
event_category	
day	
month	

year	
featured	
subscribed_to	
interested_in	
show_past	
ordering	

update

`PUT` `/events/{id}/`

⇄ INTERACT

Update an event via PUT. Host admins only.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
search	
event_category	
day	
month	
year	
featured	
subscribed_to	
interested_in	
show_past	
ordering	

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
`title` **required**	
`hosts_id` **required**	
`category_id` **required**	
`start_time`	
`end_time`	
`location`	
`description`	
`image`	
`image_ppoi`	
`open_to_id` **required**	

partial_update

⇄ INTERACT

`PATCH` `/events/{id}/`

Partially update an event via PATCH. Host admins only.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
`id` **required**	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
`search`	
`event_category`	
`day`	

month	
year	
featured	
subscribed_to	
interested_in	
show_past	
ordering	

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
title	
hosts_id	
category_id	
start_time	
end_time	
location	
description	
image	
image_ppoi	
open_to_id	

delete

⇄ INTERACT

`DELETE` `/events/{id}/`

Deletes event via DELETE. Host admins only.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description

id **required**		

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
search	
event_category	
day	
month	
year	
featured	
subscribed_to	
interested_in	
show_past	
ordering	

host-categories

list

| GET | /host-categories/ | ⇌ INTERACT |

Returns the tree of all host categories via GET. Allows any.

read

| GET | /host-categories/{id}/ | ⇌ INTERACT |

Returns a particular branch of host categories via GET. Allows any.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id **required**	

hosts

list

GET /hosts/

Return a list of all hosts via GET. Authenticated only.

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
page	A page number within the paginated result set.
page_size	Number of results to return per page.
search	
host_category	
ordering	

create

POST /hosts/

Create a new host via POST. Authenticated only.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name required	
category_id required	
admins_id required	
description	
website	
image	
image_ppoi required	
logo	

`logo_ppoi` **required**	
`open_to_id` **required**	

read

`GET`   `/hosts/{id}/`   ⇄ **INTERACT**

Return the given host via GET. Authenticated only. If user is an admin of that host, an extra 'admins' field is shown.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
`id` **required**	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
`search`	
`host_category`	
`ordering`	

update

`PUT`   `/hosts/{id}/`   ⇄ **INTERACT**

Update a host via PUT. Host admins only.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
`id` **required**	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description

Parameter	
search	
host_category	
ordering	

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
name `required`	
category_id `required`	
admins_id `required`	
description	
website	
image	
image_ppoi `required`	
logo	
logo_ppoi `required`	
open_to_id `required`	

partial_update

`PATCH` `/hosts/{id}/`   ⇄ INTERACT

Partially update a host via PATCH. Host admins only.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id `required`	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description

search	
host_category	
ordering	

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
name	
category_id	
admins_id	
description	
website	
image	
image_ppoi	
logo	
logo_ppoi	
open_to_id	

delete

⇄ INTERACT

`DELETE` `/hosts/{id}/`

Deletes host via DELETE. Host admins only.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id `required`	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description

search	
host_category	
ordering	

add_admin

| POST | /hosts/{id}/add_admin/ |

⇄ **INTERACT**

Accepts an email address, validates it, and if a corresponding user can be found, adds that user as an admin to the host.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id `required`	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
email `required`	

password

create

| POST | /password/ |

⇄ **INTERACT**

Use this endpoint to change user password.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
new_password `required`	
current_password `required`	

reset > create

`POST` `/password/reset/`

Use this endpoint to send email to user with password reset link.

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
`email` **required**	

reset > confirm > create

`POST` `/password/reset/confirm/`

Use this endpoint to finish reset password process.

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
`uid` **required**	
`token` **required**	
`new_password` **required**	

user-categories

list

`GET` `/user-categories/`

Returns the tree of all user categories via GET. Allows any.

read

`GET` `/user-categories/{id}/`

Returns a particular branch of user categories via GET. Allows any.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description

| id required | |

users

list

`GET` `/users/` ⇄ **INTERACT**

Returns a list of all events via GET. Superuser only.

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
page	A page number within the paginated result set.
page_size	Number of results to return per page.

create

`POST` `/users/` ⇄ **INTERACT**

Create a new event via POST. Allows any.

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
email required	
password required	
user_category	

change_username

`POST` `/users/change_username/` ⇄ **INTERACT**

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
current_password required	

`new_email` required	

confirm

`POST` `/users/confirm/`

Overrides the confirm custom action defined in djoser.views.UserViewSet. Takes a unique user identifier (UUID) and a token, both given by the inherited create action, and activates the user's account. Returns a login token.

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
`uid` required	
`token` required	

read

`GET` `/users/{id}/`

Returns the given user via GET. Only the associated user is permitted.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
`id` required	A unique integer value identifying this User.

update

`PUT` `/users/{id}/`

Update an event via PUT. Only the associated user is permitted.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
`id` required	A unique integer value identifying this User.

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
`user_category_id`	
`subscribed_to_id`	
`add_interested_in`	
`remove_interested_in`	

partial_update

`PATCH` `/users/{id}/`

Partially update an event via PATCH. Only the associated user is permitted.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
`id` required	A unique integer value identifying this User.

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
`user_category_id`	
`subscribed_to_id`	
`add_interested_in`	
`remove_interested_in`	

delete

`DELETE` `/users/{id}/`

Deletes event via DELETE. Only the associated user is permitted.

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
`id` required	A unique integer value identifying this User.

me > read

GET `/users/me/`

me > update

PUT `/users/me/`

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
`user_category_id`	
`subscribed_to_id`	
`add_interested_in`	
`remove_interested_in`	

me > partial_update

PATCH `/users/me/`

Request Body

The request body should be a `"application/json"` encoded object, containing the following items.

Parameter	Description
`user_category_id`	
`subscribed_to_id`	
`add_interested_in`	
`remove_interested_in`	

me > delete

DELETE `/users/me/`