

Configuration Writing Sample

Disclaimer: I adapted this sample from work I created for a previous employer. I removed all proprietary, confidential, and identifying information, and I rewrote portions of the content to ensure it is neutral and appropriate for public use. The original material belongs to that company. I provide this sample solely to demonstrate my writing ability.

All company names, product names, and scenarios in this sample are fictional and used solely for demonstration purposes.

This configuration sample showcases my ability to explain setup options and guide users through technical choices in a clear, structured way.

Outbound data transmission settings

Institutions use outbound transmission settings to control how GivingBridge sends information to external systems. These settings define how GivingBridge authenticates, formats, and delivers data, and they ensure consistent communication between platforms. Administrators configure these values during initial setup or when integration requirements change.

Settings and descriptions

Setting	Description
Transmission Mode	Determines how GivingBridge sends data to the external system. Options include Immediate (send data as soon as staff save a record) or Scheduled (send data during a defined transmission window).
Endpoint URL	Specifies the destination address for outbound data. GivingBridge sends all outbound messages to this location. Administrators must update this value if the external system changes its endpoint.
Authentication Method	Defines the security method GivingBridge uses to authenticate with the external system. Supported methods include API key, token-based authentication, or institution-defined credentials.
API Key or Token	Stores the credential required to authenticate outbound requests. GivingBridge includes this value in each transmission to verify the institution's identity.
Batch Size	Controls the maximum number of records GivingBridge includes in a single outbound batch. Larger batch sizes reduce the number of transmissions but may increase processing time.

Retry Interval	Specifies the number of minutes GivingBridge waits before it attempts to resend data after a failed transmission.
----------------	---
