



Télécom ParisTech  
Promotion 2017  
Sylvain DASSIER

## RAPPORT DE STAGE

### Étude de l'apport du protocol MPTCP dans l'optimisation du trafic

Département : *Département d'Informatique*  
Option : *INFRES*  
Encadrants : *M. Luigi IANNONE, M. Antoine FRESSANCOURT*  
Dates : *18/07/2016 - 17/01/2017*  
Adresse : *Télécom ParisTech, 23 Avenue d'Italie,  
75013 Paris*

# Declaration d'intégrité relative au plagiat

*Je soussigné DASSIER Sylvain certifie sur l'honneur :*

1. Que les résultats décrits dans ce rapport sont l'aboutissement de mon travail.
2. Que je suis l'auteur de ce rapport.
3. Que je n'ai pas utilisé des sources ou résultats tiers sans clairement les citer et les référencer selon les règles bibliographiques préconisées.

*Je déclare que ce travail ne peut être suspecté de plagiat.*

17 janvier 2017

Signature :



# *Abstract*

English

# *Résumé*

Français

# Table des matières

<b>1</b>	<b>Introduction</b>	<b>6</b>
1.1	Context . . . . .	6
1.2	Document Outline . . . . .	6
<b>2</b>	<b>Setting up a debugging environment for MPTCP :</b>	<b>7</b>
<b>3</b>	<b>An Enhanced socket API for Multipath TCP :</b>	<b>10</b>
3.1	Implementation . . . . .	10
<b>4</b>	<b>Netcat with MPTCP (netcat-mptcp) :</b>	<b>12</b>
4.1	Setup and structure . . . . .	12
4.2	Configure Addresses and Routing . . . . .	13
4.3	Client and Server . . . . .	13
4.4	Routers . . . . .	14
4.5	Code simplification, addition and function calls at the correct place . . . . .	14
<b>5</b>	<b>Results, Statistics and Utility</b>	<b>16</b>
5.1	Results . . . . .	16
5.2	Statistics . . . . .	19
5.2.1	IPv4/All Addresses packet distribution . . . . .	19
5.2.2	Round Trip Time . . . . .	19
5.2.3	Cumulative Bytes . . . . .	21
5.2.4	MPTCP Close . . . . .	21
<b>6</b>	<b>Conclusion</b>	<b>22</b>
<b>7</b>	<b>Further developments</b>	<b>22</b>
<b>8</b>	<b>Acknowledgements</b>	<b>23</b>
<b>9</b>	<b>Bibliography</b>	<b>24</b>
<b>10</b>	<b>Appendix</b>	<b>25</b>
10.1	Client side address assignment with the following script : . . . . .	25
10.2	Server side address assignment with the following script : . . . . .	25
10.3	Client side routing : . . . . .	26
10.4	Client routing output : . . . . .	26
10.5	Server side routing : . . . . .	27
10.6	Server routing output : . . . . .	27

10.7 Router R1 :	28
10.8 Router R1 routing output :	28
10.9 Router R2 :	28
10.10 Router R2 routing output :	29
10.11 Router R3 :	29
10.12 Router R3 routing output :	30
10.13 Makefile.am :	30
10.14 Makefile.in :	30
10.15 netcat.h :	30
10.16 netcat.c :	31
10.17 core.h :	31
10.18 core.c :	32
10.19 config.conf :	35

# 1 Introduction

## 1.1 Context

Today, connected vehicles make use of 2G, 3G or 4G networks in order to connect to the internet while in motion. Whether it be for GPS, simple browsing or music, every consumer has his/her own needs.

Apart from the usual connection glitches, such connectivity is rather expensive with limited bandwidth. Even though workarounds have been implemented, most of them are either inefficient or are not completely transparent. These limitations stand in the way of development of connected vehicles.

MultiPath TCP (MPTCP) is an effort towards enabling the simultaneous use of several IP-addresses/interfaces by a modification of TCP. It presents a regular TCP interface to applications, while in fact spreading data across several sub-flows. Benefits of this include better resource utilisation, better throughput and smoother reaction to failures. The project CarFi, aims to exploit these advantages of MPTCP. A potential add-on would be the usage of the WiFi network when available. Most urban areas are covered via Mobile Network Operator or ISP WiFi hotspots. One may envisage a scenario where the default connection is established over WiFi and when it is no longer available, the communication carries on over 3G.

## 1.2 Document Outline

This document is divided into two main parts comprising different sections. The first part involves section 2 where we describe how to set up a *debugging environment for MPTCP*. This will help us to follow the different system calls during the establishment of a flow or a sub-flow. The next sections form the other part, dealing with the new socket API that enables us to control the MPTCP stack from user space. Section 3 gives a description of the socket API along with some details on its implementation. Section 4 elaborates a use case of this API, in our case a **Netcat** with **MPTCP**. Section 5 summarises our results 5.1, elucidates certain statistics 5.2 and emphasises on the utility 5.3 of our work.

# PART I

## 2 Setting up a debugging environment for MPTCP :

In order to understand the different stages of running of the MPTCP linux kernel, we have put in place a debugging environment. This has been done with [1, LibOS] (an MPTCP version of the library operating system of the linux kernel) and [2, DCE] (Direct Code Execution). Everything was done on a XUbuntu 14.04 64bit virtual machine with DCE 1.8. The following illustrates how :

### 1. Install the dependencies :

```
sudo apt-get install vim git mercurial gcc g++ python python-dev qt4-dev-tools libqt4-dev bsr cmake libc6-dev libc6-dev-i386 g++-multilib gdb valgrind gsl-bin libgsl0-dev libgsl0ldbl flex bison libfl-dev tcpdump sqlite sqlite3 libsqlite3-dev libxml2 libxml2-dev libgtk2.0-0 libgtk2.0-dev vtun lxc uncrustify doxygen graphviz imagemagick texlive texlive-extra-utils texlive-latex-extra texlive-font-utils dvipng python-sphinx dia python-pygraphviz python-kiwi python-pygoocanvas libgoocanvas-dev ipython libboost-signals-dev libboost-filesystem-dev openmpi-bin openmpi-common openmpi-doc libopenmpi-dev libncurses5-dev libncursesw5-dev unrar unrar-free p7zip-full autoconf libpcap-dev cvs libssl-dev wireshark
```

### 2. Build DCE using bake :

- (a) hg clone <http://code.nsnam.org/bake> bake
- (b) export BAKE\_HOME='pwd'/bake
- (c) export PATH=\$PATH :\$BAKE\_HOME
- (d) export PYTHONPATH=\$PYTHONPATH :\$BAKE\_HOME
- (e) mkdir dce
- (f) cd dce
- (g) bake.py configure -e dce-ns3-1.8
- (h) bake.py download
- (i) bake.py build

### 3. Build the *mptcp\_trunk\_libos* branch of *net-next-nuse*

- (a) git clone -b mptcp\_trunk\_libos <https://github.com/libos-nuse/net-next-nuse.git>
- (b) cd net-next-nuse

- (c) make menuconfig ARCH=lib
- (d) make library ARCH=lib
- (e) Since DCE by default, calls the library *liblinux.so* (not exactly the correct one), and that the correct library is *libsim-linux.so* found at *\$HOME/net-next-nuse/arch/lib/tools* we rename the existing *liblinux.so* to *liblinux0.so* and create a symbolic link for the correct library as follows :  
`ln -s $HOME/net-next-nuse/arch/lib/tools/libsim-linux.so $HOME/net-next-nuse/liblinux.so.` This will “mislead” DCE into loading the correct library.

#### 4. Build *iproute2* version 2.6.38

- (a) Download the compressed source code from  
`https://kernel.googlesource.com/pub/scm/linux/kernel/git/shemminger/iproute2/+archive/fcae78992cab7bd267785b392b438306c621e583.tar.gz`, extract it and rename the folder to *iproute2-2.6.38*.
- (b) cd iproute2-2.6.38
- (c) patch -p1 -i .../ns-3-dce/utils/iproute-2.6.38-fix-01.patch
- (d) *\$(KERNEL\_INCLUDE)* should point to the *liblinux.so* directory ( for me it is *\$HOME/net-next-nuse* )

Hence I modified the following part in the Makefile :

*Config :*

```
sh configure /home/lawrence/net-next-nuse
# sh configure $(KERNEL_MODULE)
```

- (e) LDFLAGS=-pie make CCOPTS=-fpic -D\_GNU\_SOURCE -O0 -U\_FORTIFY\_SOURCE'

#### 5. Set the *DCE\_PATH*

```
export DCE_PATH=$HOME/net-next-nuse:$HOME/iproute2-2.6.38/ip
```

#### 6. Build *ns-3-dce*

- (a) hg clone <http://code.nsnam.org/ns-3-dce> -r dce-1.8
- (b) cd ns-3-dce
- (c) ./waf configure --with-ns3=\$HOME/dce/build --enable-kernel-stack=\$HOME/net-next-nuse/arch --prefix=\$HOME/dce/build
- (d) ./waf build

#### 7. Run *dce-ipperf-mptcp* with or without *GDB*

- (a) cd ns-3-dce

- (b) Without *GDB* : `./waf -run dce-ipperf-mptcp`
- (c) With *GDB* : `./waf -run dce-ipperf-mptcp -command-template="gdb -args %s"`

Once we enter the *GDB* prompt we must put a breakpoint at one of the functions in the *mptcp* folder to stop there. Kindly refer to the files found at `$HOME/net-next-nuse/net/mptcp` to choose the function to define as a breakpoint.

An example :

Suppose we would like to stop the execution at the function `mptcp_set_default_path_manager()` found at `$HOME/net-next-nuse/net/mptcp/mptcp_pm.c`, then we give the following command at the *GDB* prompt :

`b mptcp_set_default_path_manager`

*GDB* will ask the following :

*Function "mptcp\_set\_default\_path\_manager" not defined.*

*Make breakpoint available on future shared library load ? (y or [n])*

Type in **y** and press enter. We may run the program by typing **r** and then pressing enter. *GDB* will pause at the necessary breakpoint.

## PART II

### 3 An Enhanced socket API for Multipath TCP :

In our project CarFi, we would like to control the MPTCP kernel stack from the application layer i.e. manage(open/close) sub flows according to the kind of application that uses it. For example, for a streaming application it is preferable to communicate over the Wifi channel. In the current Linux Kernel implementation of MPTCP, the path managers may not be fit for all kinds of applications. For optimum usage, advanced applications may want to know the number of sub flows available or the state of the active sub flows. When the application possesses such information it may want to create a new sub flow, terminate an existing one, change a sub flow's priority etc.

#### 3.1 Implementation

The enhanced socket API has been implemented over the existing *getsockopt()* and *setsockopt()* system calls. The following figure illustrates the MPTCP socket structure [3] :




FIGURE 1 – MPTCP socket structure

From the application's point of view, no other socket other than the **Meta Socket**

is visible. Underneath the **Meta Socket** lie several subsockets, each representing a sub flow. The structure **mptcp\_cb** points towards the head of the subflow list. The structure **mptcp\_sk** hence points indirectly towards the next subflow. Till now there is no way for the application to know what hides beyond the **Meta Socket**. This is where the socket options come into play. The enhanced socket API lists the following socket options for the user [3] :

Name	Input	Output	Description
MPTCP_GET_SUB_IDS	-	subflow list	Get the current list of subflows viewed by the kernel
MPTCP_GET_SUB_TUPLE	id	sub tuple	Get the ip and ports used by the subflow identified by id
MPTCP_OPEN_SUB_TUPLE	tuple	-	Request a new subflow with pair of ip and ports
MPTCP_CLOSE_SUB_ID	id	-	Close the subflow identified by id
MPTCP_SUB_GETSOCKOPT	id, sock opt	sock ret	Redirects the getsockopt given in input to the subflow identified by id and return the value returned by the operation
MPTCP_SUB_SETSOCKOPT	id, sock opt	-	Redirects the setsockopt given in input to the subflow identified by id

TABLE 1 – Implemented MPTCP socket options

The following example shows how we may use the socket option

**MPTCP\_OPEN\_SUB\_TUPLE** and **getsockopt()** to open a sub flow [3] :

First we introduce the **mptcp\_sub\_tuple** structure which represents the subflow :

---

```
struct mptcp_sub_tuple {
    _u8 id;           // this is an output signifying the ‘‘id’’ of the subflow
    _u8 prio;         // this field determines if the sub flow is backup or not
    _u8 addrs[0];    // pair array of size two depicting (source, destination)
}
```

---

Now we use this structure to open a sub flow as follows :

---

```
unsigned int optlen;
struct mptcp_sub_tuple *sub_tuple;
struct sockaddr_in *addr;
optlen = 42;

int error;

optlen = sizeof(struct mptcp_sub_tuple) + 2 * sizeof(struct sockaddr_in);
sub_tuple = malloc(optlen);

sub_tuple->id = 0;
sub_tuple->prio = 0;
```

---

---

```

addr = (struct sockaddr_in*) &sub_tuple->addrs[0];

// source address
addr->sin_family = AF_INET; // address family IPv4
addr->sin_port = htons(12345); // source port
inet_pton(AF_INET, "10.0.0.1", &addr->sin_addr); // source IP

addr++;

// destination address
addr->sin_family = AF_INET; // address family IPv4
addr->sin_port = htons(1234); // destination port
inet_pton(AF_INET, "10.1.0.1", &addr->sin_addr); // destination IP

error = getsockopt(sockfd, IPPROTO_TCP, MPTCP_OPEN_SUB_TUPLE,
                   sub_tuple, &optlen); // establishment of sub flow using getsockopt()

```

---

## 4 Netcat with MPTCP (netcat-mptcp) :

In order to have a concrete testbed for the enhanced socket API, we have thought of a usecase involving **Netcat**. **Netcat** or **nc** is a featured networking utility which reads and writes data across network connections, using the TCP/IP protocol [4]. It will serve as our application that will establish multiple subflows.

### 4.1 Setup and structure

Usually with **Netcat**, there is only one flow between a client and a server. Our objective is to have multiple interfaces on the client side which will connect to the same or multiple interfaces on the server side. For simplicity we have envisaged a scenario where the client has three interfaces (viz. default, wifi and cellular) and the server has three (however for demonstration purposes we need to connect to only one of them). The way the client connects to the server is changed. In fact, with our modifications in the source code, we are able to pass three additional arguments in the netcat command :

1. **-a** : Find all the remaining interfaces on the client side and establish sub flows to the server.
2. **-W** : Read the configuration file, extract the IP corresponding to the wifi interface and establish a sub flow using this interface to the server.
3. **-C** : Read the configuration file, extract the IP corresponding to the cellular interface and establish a sub flow using this interface to the server.

What happens is, the client usually connects to the server via the default interface. Then according to the option passed in the **Netcat** command, it either opens subflows

on a single interface or on all available interfaces. This is done using the function `getsockopt()` in the source code just after the TCP `connect()` system call.

The following diagram depicts the setup along with the addresses :




FIGURE 2 – Testbed topology for netcat-mptcp

Here is an example of the **Netcat** command :

On the server side, it listens on its default interface **10.0.4.7** on port **64000** with the help of the following command :

**nc -l -p 64000**

On the client side, we use our own **Netcat** executable to establish a flow / multiple flows as follows :

```
-a :      ./netcat-mptcp/src/netcat -a 10.0.4.7 64000
-W :      ./netcat-mptcp/src/netcat -W 10.0.4.7 64000
-C :      ./netcat-mptcp/src/netcat -C 10.0.4.7 64000
```

## 4.2 Configure Addresses and Routing

For the testbed, have set up the above topology on **GNS3** using the Cisco Router **c3745** and the virtual machine enabled with the enhanced Multipath TCP API.

## 4.3 Client and Server

The following command example assigns the address **10.0.1.6** to the interface **eth0** :

*Client side :*

---

```
ip addr add 10.0.1.6/24 dev eth0
```

---

Appendix 10.1 and 10.2 illustrate the scripts that are run to assign addresses on the client side and the server side.

With multiple addresses defined on several interfaces, we would also like to tell the kernel to use specific interfaces and gateways and not the default ones according to the source addresses. This has been achieved by configuring one routing table per outgoing interface, each routing table being identified by a number. The route selection process then happens in two phases : First the kernel does a lookup in the policy table (that we need to configure with *ip rules*). The policies in our case, will be that for so and so source prefix, go to so and so routing table (the routing table indicated by a number). The corresponding routing table is examined to select the gateway based on the destination addresses [5].

Appendix 10.3 and 10.5 illustrate the scripts that are run to manually configure the routing policies on the client side and the server side.

Appendix 10.4 and 10.6 illustrate the outputs for the different commands for showing the routing policies.

#### 4.4 Routers

In figure 2 the three routes need to be configured to properly deliver packets to the correct destination. We have connected to the routers via telnet to configure them. Appendix 10.7, 10.9 and 10.11 illustrate the commands that must be given to the routers **R1**, **R2** and **R3** respectively.

Appendix 10.8, 10.10 and 10.12 illustrate the outputs for the **sh ip route** command.

#### 4.5 Code simplification, addition and function calls at the correct place

The above code involving opening a sub flow may appear complex. During our participation at the **IETF'97 Hackathon** at **École Polytechnique de Louvain**, one of my fellow participants had simplified the usage of the **getsockopt()** function by deploying simpler function calls. Our aim was to find in the source code of **Netcat** where the **connect()** system call was being made. Once the the exact place found, we were to simply use the sunflow opening code in the simplified form and establish the desired subflows. We have added three different scenarios for the establishment of subflows as described in the section [Setup and structure](#).

Besides the classes **makeaddr.c**, **subinfo.c**, **submanip.c** and **suboption.c** and the header files **makeaddr.h**, **subinfo.h**, **submanip.h** and **suboption.h** which are available at the **src** folder of the github repository : [6,

[https://github.com/lawrenceFR/netcat-mptcp\]](https://github.com/lawrenceFR/netcat-mptcp), the following addition of code was also necessary for the proper functioning of **netcat-mptcp** :

1. In *netcat-mptcp/src/Makefile.am* line **28 - 39** : Appendix [Makefile.am](#)
2. In *netcat-mptcp/src/Makefile.in* line **153 - 164** and **183 - 186** : Appendix [Makefile.in](#)
3. In *netcat-mptcp/src/netcat.h* line **203 - 205** : Appendix [netcat.h](#)
4. In *netcat-mptcp/src/netcat.c* line **58 - 60, 192, 194, 222, 227, 233 - 235, 239 - 241, 357 - 359** : Appendix [netcat.c](#)
5. In *netcat-mptcp/src/core.h* line **1 - 37** : Appendix [core.h](#)
6. In *netcat-mptcp/src/core.c* line **394 - 405** and **535 - 688** : Appendix [core.c](#)

Finally, a file **config.conf** is placed in **netcat-mptcp/src** so as to indicate the addresses of the available interfaces. The format of the config file is shown in Appendix [config.conf](#).

## 5 Results, Statistics and Utility

This section analyses packet captures (captured with the help of wireshark) to verify if the manipulation of **Netcat** was successful. It depicts the establishment of the different sub flows along with the details of the **TCP options** to prove that the **MP\_CAPABLE** option is actually passed. It also gives an idea of the distribution of packets sent from the three interfaces available on the client's side, keeping in mind that the **path\_manager** used is “**default**” (i.e. the kernel will not establish supplementary sub flows on its own).

### 5.1 Results

Figure 3 is a screenshot of a packet capture showing that the kernel successfully establishes the second and third sub flows when we use the option **-a** as explained previously. First, we see the **3 way handshake** from the client address **10.0.1.6** to the server address **10.0.4.7**. Next due to our manipulation in the **Netcat** source code we have the two other **3 way handshakes** from the client addresses **10.0.2.6** and **10.0.3.6**. This is in accordance with the function of the option **-a** in the **Netcat** command defined by us (i.e. establish supplementary sub flows on all the remaining available interfaces of the client).

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	10.0.1.6	10.0.4.7	MPTCP	86	55379 → 64000 [SYN]
2	0.000261	10.0.4.7	10.0.1.6	MPTCP	86	64000 → 55379 [SYN,
3	0.020193	10.0.1.6	10.0.4.7	MPTCP	94	55379 → 64000 [ACK]
4	0.030264	10.0.1.6	10.0.4.7	MPTCP	1110	55379 → 64000 [PSH,
5	0.030460	10.0.4.7	10.0.1.6	MPTCP	74	64000 → 55379 [ACK]
6	0.040387	10.0.1.6	10.0.4.7	MPTCP	1514	55379 → 64000 [ACK]
7	0.040714	10.0.4.7	10.0.1.6	MPTCP	74	64000 → 55379 [ACK]
8	0.050499	10.0.2.6	10.0.4.7	MPTCP	86	55380 → 64000 [SYN]
9	0.050658	10.0.4.7	10.0.2.6	MPTCP	90	64000 → 55380 [SYN,
10	0.060617	10.0.1.6	10.0.4.7	MPTCP	1514	55379 → 64000 [ACK]
11	0.060784	10.0.4.7	10.0.1.6	MPTCP	74	64000 → 55379 [ACK]
12	0.070733	10.0.1.6	10.0.4.7	MPTCP	1514	55379 → 64000 [ACK]
13	0.071080	10.0.4.7	10.0.1.6	MPTCP	74	64000 → 55379 [ACK]
14	0.080847	10.0.1.6	10.0.4.7	MPTCP	1514	55379 → 64000 [ACK]
15	0.081139	10.0.4.7	10.0.1.6	MPTCP	74	64000 → 55379 [ACK]
16	0.090965	10.0.1.6	10.0.4.7	MPTCP	1514	55379 → 64000 [ACK]
17	0.091332	10.0.4.7	10.0.1.6	MPTCP	74	64000 → 55379 [ACK]
18	0.101088	10.0.1.6	10.0.4.7	MPTCP	1514	55379 → 64000 [ACK]
19	0.101250	10.0.4.7	10.0.1.6	MPTCP	74	64000 → 55379 [ACK]
20	0.111206	10.0.1.6	10.0.4.7	MPTCP	1514	55379 → 64000 [ACK]
21	0.111414	10.0.4.7	10.0.1.6	MPTCP	74	64000 → 55379 [ACK]
22	0.121326	10.0.1.6	10.0.4.7	MPTCP	1514	55379 → 64000 [ACK]
23	0.121490	10.0.4.7	10.0.1.6	MPTCP	74	64000 → 55379 [ACK]
24	0.131445	10.0.1.6	10.0.4.7	MPTCP	1514	55379 → 64000 [ACK]
25	0.131611	10.0.4.7	10.0.1.6	MPTCP	74	64000 → 55379 [ACK]
26	0.141564	10.0.3.6	10.0.4.7	MPTCP	86	55381 → 64000 [SYN]
27	0.141749	10.0.4.7	10.0.3.6	MPTCP	90	64000 → 55381 [SYN,
28	0.151682	10.0.1.6	10.0.4.7	MPTCP	1514	55379 → 64000 [ACK]
29	0.151858	10.0.4.7	10.0.1.6	MPTCP	74	64000 → 55379 [ACK]

FIGURE 3 – Subflow establishment

The following figures give the details of the **TCP options** for the first sub flow established. We see the **Multipath Capable** option that is passed :

No.	Time	Source	Destination	Protocol
1	0.000000	10.0.1.6	10.0.4.7	MPTCP
2	0.000261	10.0.4.7	10.0.1.6	MPTCP
3	0.020193	10.0.1.6	10.0.4.7	MPTCP
4	0.038264	10.0.1.6	10.0.4.7	MPTCP
5	0.039460	10.0.4.7	10.0.1.6	MPTCP
6	0.040387	10.0.1.6	10.0.4.7	MPTCP
7	0.040714	10.0.4.7	10.0.1.6	MPTCP
► Frame 1: 86 bytes on wire (688 bits), 86 bytes captured (688 bits) o				
► Ethernet II, Src: CadmusCo:f6:f1:f7 (08:00:27:f6:f1:f7), Dst: Cadmus (08:00:27:f6:f1:f7)				
► Internet Protocol Version 4, Src: 10.0.1.6, Dst: 10.0.4.7				
▼ Transmission Control Protocol, Src Port: 55379 (55379), Dst Port: 64000				
Source Port: 55379 Destination Port: 64000 [Stream index: 0] [TCP Segment Len: 0] Sequence number: 0 (relative sequence number) Acknowledgment number: 0 Header Length: 52 bytes				
► Flags: 0x002 (SYN)				
Window size value: 29200 [Calculated window size: 29200]				
► Checksum: 0x5581 [validation disabled]				
Urgent pointer: 0				
► Options: (32 bytes), Maximum segment size, SACK permitted, Timestamps: 843565, TSectr 0				
► Maximum segment size: 1460 bytes				
► TCP SACK Permitted Option: True				
► Timestamps: Tsval 843761, TSectr 843565				
► No-Operation (NOP)				
► Window scale: 7 (multiply by 128)				
▼ Multipath TCP: Multipath Capable				
Kind: Multipath TCP (30) Length: 12 0000 .... = Multipath TCP subtype: Multipath Capable (0) .... 0000 = Multipath TCP version: 0				
▼ Multipath TCP flags: 0x81				
1.... .... = Checksum required: 1 .0.... .... = Extensibility: 0 .... .1 = Use HMAC-SHA1: 1 .... 0000. = Reserved: 0x00				
Sender's Key: 5718685676031498307 [Subflow token generated from key: 2013417082] [Subflow expected IDSN: 4246710274791923459 (64bits version)				
▼ [MPTCP analysis]				
[Master flow: master is tcp stream 0] [Stream index: 0] [TCP subflow stream id(s): 2 1 0]				
► [SEQ/ACK analysis]				
[Master flow: master is tcp stream 0] [Stream index: 0] [TCP subflow stream id(s): 2 1 0]				

(a) First subflow SYN

(b) First subflow SYN + ACK

FIGURE 4 – First subflow details

No.	Time	Source	Destination	Protocol
1	0.000000	10.0.1.6	10.0.4.7	MPTCP
2	0.000261	10.0.4.7	10.0.1.6	MPTCP
3	0.020193	10.0.1.6	10.0.4.7	MPTCP
4	0.038264	10.0.1.6	10.0.4.7	MPTCP
5	0.039460	10.0.4.7	10.0.1.6	MPTCP
6	0.040387	10.0.1.6	10.0.4.7	MPTCP
7	0.040714	10.0.4.7	10.0.1.6	MPTCP
Window size value: 229 [Calculated window size: 29312] [Window size scaling factor: 128]				
► Checksum: 0xb9d0 [validation disabled]				
Urgent pointer: 0				
► Options: (40 bytes), No-Operation (NOP), No-Operation (NOP), Timestamps: 843562, TSectr 843761				
► No-Operation (NOP)				
► No-Operation (NOP)				
► Timestamps: Tsval 843562, TSectr 843761				
▼ Multipath TCP: Multipath Capable				
Kind: Multipath TCP (30) Length: 20 0000 .... = Multipath TCP subtype: Multipath Capable (0) .... 0000 = Multipath TCP version: 0				
▼ Multipath TCP flags: 0x81				
1.... .... = Checksum required: 1 .0.... .... = Extensibility: 0 .... .1 = Use HMAC-SHA1: 1 .... 0000. = Reserved: 0x00				
Sender's Key: 5718685676031498307 [Subflow token generated from key: 2013417082] [Subflow expected IDSN: 4246710274791923459 (64bits version)				
▼ Multipath TCP: Data Sequence Signal				
Kind: Multipath TCP (30) Length: 8 0010 .... = Multipath TCP subtype: Data Sequence Signal (2)				
▼ Multipath TCP flags: 0x01				
....0 .... = DATA_FIN: 0 .... 0... = Date Sequence Number is 8 octets: 0 .... .0.. = Date Sequence Number, Subflow Sequence Number, .... .0. = Data ACK is 8 octets: 0 .... .1 = Data ACK is present: 1				
Original MPTCP Data ACK: 510268443 [Multipath TCP Data ACK: 1 (Relative)]				

FIGURE 5 – First subflow ACK

No.	Time	Source	Destination	Protocol
7	0.040714	10.0.4.7	10.0.1.6	MPTCP
8	0.050409	10.0.4.7	10.0.4.7	MPTCP
9	0.050658	10.0.4.7	10.0.2.6	MPTCP
10	0.060617	10.0.1.6	10.0.4.7	MPTCP
11	0.060784	10.0.4.7	10.0.1.6	MPTCP
12	0.070733	10.0.1.6	10.0.4.7	MPTCP
13	0.071080	10.0.4.7	10.0.1.6	MPTCP
▶ Frame 8: 86 bytes on wire (688 bits), 86 bytes captured (688 bits) o				
▶ Ethernet II, Src: CadmusCo_f6:f1:f7 (08:00:27:f6:f1:f7), Dst: Cadmus				
▶ Internet Protocol Version 4, Src: 10.0.2.6, Dst: 10.0.4.7				
▼ Transmission Control Protocol, Src Port: 55380 (55380), Dst Port: 64				
Source Port: 55380				
Destination Port: 64000				
[Stream index: 1]				
[TCP Segment Len: 0]				
Sequence number: 0 (relative sequence number)				
Acknowledgment number: 0				
Header Length: 52 bytes				
▶ Flags: 0x002 (SYN)				
Window size value: 29200				
[Calculated window size: 29200]				
Checksum: 0x15f9 [validation disabled]				
Urgent pointer: 0				
▶ Options: (32 bytes), Maximum segment size, SACK permitted, Timestamps				
▶ Maximum segment size: 1460 bytes				
▶ TCP SACK Permitted Option: True				
▶ Timestamps: TSval 843562, TSecr 0				
▶ No-Operation (NOP)				
▶ Window scale: 7 (multiply by 128)				
▼ Multipath TCP: Join Connection				
Kind: Multipath TCP (30)				
Length: 12				
0001 .... = Multipath TCP subtype: Join Connection (1)				
...1 .... = Backup flag: 1				
Address ID: 38				
Receiver's Token: 984124602				
Sender's Random Number: 1395616132				
▼ [MPTCP analysis]				
[Master flow: master is tcp stream 0]				
[Stream index: 0]				
[TCP subflow stream id(s): 2 1 0]				
▶ [SEQ/ACK analysis]				
[Master flow: master is tcp stream 0]				
[Stream index: 0]				
[TCP subflow stream id(s): 2 1 0]				
▶ [MPTCP analysis]				
[Master flow: master is tcp stream 0]				
[Stream index: 0]				
[TCP subflow stream id(s): 2 1 0]				

(a) Second subflow SYN

8	0.050499	10.0.2.6	10.0.4.7	MPTCP
9	0.050658	10.0.4.7	10.0.2.6	MPTCP
10	0.060617	10.0.1.6	10.0.4.7	MPTCP
11	0.060784	10.0.4.7	10.0.1.6	MPTCP
12	0.070733	10.0.1.6	10.0.4.7	MPTCP
13	0.071080	10.0.4.7	10.0.1.6	MPTCP
▶ Frame 9: 90 bytes on wire (720 bits), 90 bytes captured (720 bits) o				
▶ Ethernet II, Src: CadmusCo_f6:f1:f7 (08:00:27:f6:f1:f7), Dst: c4:01:				
▶ Internet Protocol Version 4, Src: 10.0.2.6, Dst: 10.0.4.7				
▼ Transmission Control Protocol, Src Port: 64000 (64000), Dst Port: 55				
Source Port: 64000				
Destination Port: 55380				
[Stream index: 1]				
[TCP Segment Len: 0]				
Sequence number: 0 (relative sequence number)				
Acknowledgment number: 1 (relative ack number)				
Header Length: 56 bytes				
▶ Flags: 0x012 (SYN, ACK)				
Window size value: 28560				
[Calculated window size: 28560]				
Checksum: 0x3efc [validation disabled]				
Urgent pointer: 0				
▼ Options: (36 bytes), Maximum segment size, SACK permitted, Timestamps				
▶ Maximum segment size: 1460 bytes				
▶ TCP SACK Permitted Option: True				
▶ Timestamps: TSval 843773, TSecr 843562				
▶ No-Operation (NOP)				
▶ Window scale: 7 (multiply by 128)				
▼ Multipath TCP: Join Connection				
Kind: Multipath TCP (30)				
Length: 16				
0001 .... = Multipath TCP subtype: Join Connection (1)				
...1 .... = Backup flag: 1				
Address ID: 4096				
Sender's Truncated HMAC: 9686157918380891650				
Sender's Random Number: 1351991970				
▶ [SEQ/ACK analysis]				
▶ [MPTCP analysis]				
[Master flow: master is tcp stream 0]				
[Stream index: 0]				
[TCP subflow stream id(s): 2 1 0]				

(b) Second subflow SYN + ACK

FIGURE 6 – Second subflow details

25	0.131611	10.0.4.7	10.0.1.6	MPTCP
26	0.141564	10.0.3.6	10.0.4.7	MPTCP
27	0.141749	10.0.4.7	10.0.3.6	MPTCP
28	0.151682	10.0.1.6	10.0.4.7	MPTCP
29	0.151858	10.0.4.7	10.0.1.6	MPTCP
30	0.161817	10.0.1.6	10.0.4.7	MPTCP
31	0.162177	10.0.4.7	10.0.1.6	MPTCP
▶ Frame 27: 86 bytes on wire (688 bits), 86 bytes captured (688 bits) o				
▶ Ethernet II, Src: CadmusCo_f6:f1:f7 (08:00:27:f6:f1:f7), Dst: c4:01:				
▶ Internet Protocol Version 4, Src: 10.0.3.6, Dst: 10.0.4.7				
▼ Transmission Control Protocol, Src Port: 64000 (64000), Dst Port: 55				
Source Port: 64000				
Destination Port: 55381				
[Stream index: 2]				
[TCP Segment Len: 0]				
Sequence number: 0 (relative sequence number)				
Acknowledgment number: 1 (relative ack number)				
Header Length: 56 bytes				
▶ Flags: 0x012 (SYN, ACK)				
Window size value: 28560				
[Calculated window size: 28560]				
Checksum: 0x47a2 [validation disabled]				
Urgent pointer: 0				
▼ Options: (36 bytes), Maximum segment size, SACK permitted, Timestamps				
▶ Maximum segment size: 1460 bytes				
▶ TCP SACK Permitted Option: True				
▶ Timestamps: TSval 843796, TSecr 843563				
▶ No-Operation (NOP)				
▶ Window scale: 7 (multiply by 128)				
▼ Multipath TCP: Join Connection				
Kind: Multipath TCP (30)				
Length: 16				
0001 .... = Multipath TCP subtype: Join Connection (1)				
...1 .... = Backup flag: 1				
Address ID: 4096				
Sender's Truncated HMAC: 1633078839550135316				
Sender's Random Number: 3444375393				
▶ [SEQ/ACK analysis]				
▶ [MPTCP analysis]				
[Master flow: master is tcp stream 0]				
[Stream index: 0]				
[TCP subflow stream id(s): 2 1 0]				

(a) Third subflow SYN

(b) Third subflow SYN + ACK

FIGURE 7 – Third subflow details

## 5.2 Statistics

This section mentions a few statistics regarding the performance of **MPTCP** once the supplementary subflows are established.

### 5.2.1 IPv4/All Addresses packet distribution

Our first look is at the **IPv4/All Addresses** packet distribution which indicates the percentage contribution of each interface in the exchange of data. We have tried to send a fixed amount of random data (10MB) at bulks of 1MB for 10 counts. Command on the client side :

```
dd if=/dev/zero bs=1M count=10 | ./netcat-mptcp/src/netcat -a 10.0.4.7  
64000
```

IP	Count	Rate(ms)	Percent	Burst rate	Burst start
10.0.4.7	14076	0.1870	100.00%	0.2200	64.072
10.0.3.6	3331	0.0442	23.66%	0.2000	0.890
10.0.2.6	5021	0.0667	35.67%	0.2000	0.516
10.0.1.6	5724	0.0760	40.66%	0.2000	0.223

TABLE 2 – Packet distribution per IPv4 address

The table may seem to show that the distribution of packets is not equal. The interface **10.0.1.6** seems to send more packets than the others. This is probably due the fact that the packet emission from the second and third interfaces start a little later only after the establishment of the corresponding sub flows. Hence the kernel gets to be aware of the other sub flows later given that the **path\_manager** used is the “**default**” one. This is not the case for “**fullmesh**” **path\_manager** as the kernel knows from beforehand that it needs to use all the interfaces available for sending packets. Hence for the “**fullmesh**” **path\_manager** we have an almost equal distribution of packet emission for all the three interfaces.

### 5.2.2 Round Trip Time

This section shows the round trip time for the three interfaces.

We see that they are almost the same for the three interfaces (a small exception for the third interface around sequence number 2000000). This shows if the three interfaces are homogeneous in terms of updating their receiving windows and hence the reception and emission of packets. However, when we compare this to the round trip time in the “**fullmesh**” **path\_manager** there is hardly any anomaly in the sense that the round trip time very rarely crosses the **1800** mark.




FIGURE 8 – RTT for 10.0.1.6




FIGURE 9 – RTT for 10.0.2.6




FIGURE 10 – RTT for 10.0.3.6

### 5.2.3 Cumulative Bytes

This section illustrates the comparison of the number of bytes sent in due course of time for the three interfaces of the client. On the Y-axis we have the cumulative number of bytes. This figure shows that the interfaces **10.0.1.6** and **10.0.2.6** run almost parallel to one another, which means that their throughput is similar. The offset is attributed to the fact that the second interface starts to send packets later. For the third interface **10.0.3.6** the throughput seems to be less compared to the other two.




FIGURE 11 – Cumulative of bytes sent for the three interfaces

### 5.2.4 MPTCP Close

This section we talk about another anomaly when the **MPTCP** connection is closed. Figure 12 refers to the “**fullmesh**” **path\_manager**. We see that the connection is neatly closed with the 3 **MPTCP [FIN, ACK]** for each interface. On the other hand, figure 13 refers to the “**default**” **path\_manager** where we initiate the supplementary flows. Here we observe only one **MPTCP [FIN, ACK]** and in some other simulations we don’t see even a single one.

14148	212.361616	10.0.1.6	10.0.4.7	MPTCP	86 55380 → 64000 [FIN, ACK]
14149	212.362391	10.0.4.7	10.0.1.6	MPTCP	86 64000 → 55380 [FIN, ACK]
14150	212.371713	10.0.1.6	10.0.4.7	MPTCP	74 55380 → 64000 [RST, ACK]
14151	212.372071	10.0.4.7	10.0.2.6	MPTCP	86 64000 → 51867 [FIN, ACK]
14152	212.381834	10.0.2.6	10.0.4.7	MPTCP	74 51867 → 64000 [RST, ACK]
14153	212.392347	10.0.1.6	10.0.4.7	TCP	54 55380 → 64000 [RST] Seq=
14154	212.402083	10.0.3.6	10.0.4.7	MPTCP	78 [TCP Dup ACK 99#1] 36452
14155	212.402750	10.0.4.7	10.0.3.6	MPTCP	74 64000 → 36452 [RST, ACK]
14156	212.412196	10.0.2.6	10.0.4.7	TCP	54 51867 → 64000 [RST] Seq=

FIGURE 12 – MPTCP fullmesh close

13894	81.699475	10.0.4.7	10.0.3.6	MPTCP	74	64000 → 55383	[RST, ACK]	S
13895	81.699506	10.0.4.7	10.0.2.6	MPTCP	74	64000 → 55382	[RST, ACK]	S
13896	81.699525	10.0.4.7	10.0.1.6	MPTCP	74	64000 → 55381	[RST, ACK]	S
13897	81.709533	10.0.2.6	10.0.4.7	MPTCP	86	55382 → 64000	[FIN, ACK]	S
13898	81.709695	10.0.4.7	10.0.2.6	TCP	60	64000 → 55382	[RST] Seq=1	S
13899	81.719447	10.0.2.6	10.0.4.7	MPTCP	74	55382 → 64000	[RST, ACK]	S
13900	81.729522	10.0.3.6	10.0.4.7	MPTCP	74	55383 → 64000	[RST, ACK]	S

FIGURE 13 – MPTCP default close

## 6 Conclusion

This work is the first step towards the usage of the **Enhanced Socket API for Multipath TCP**. Our objective was to have a first functional prototype for the manipulation of subflows from the **Application Layer**. With **Netcat** as our application and the changes in its source code we have been successful in developing a versatile **netcat-mptcp**. Of course, this is a very preliminary. However the versatility and simplicity of **netcat-mptcp** will make it easy to bring in any kind of development of new features and further manipulation.

## 7 Further developments

As mentioned in section [Statistics](#), we have certain underperformances and anomalies that need to be addressed. To list a few of them :

1. **Equitable packet distribution from the three interfaces of the client** : In **netcat-mptcp** it is not as fair as in the case of ordinary **MPTCP** with the “fullmesh” **path\_manager**
2. **Round Trip Time** : Netcat-mptcp registered some **RTTs** to be quite large as compared to the “fullmesh” **path\_manager** which showed very little variation.
3. **Cumulative Bytes for the individual interfaces** : In **netcat-mptcp** we found that the third interface had a lower throughout. This is contrary to the traditional “fullmesh” **path\_manager**.
4. **Closing the MPTCP connection** : For **netcat-mptcp**, the closing of a connection does not respect the procedure as described in the **RFC** of **Multipath TCP**.

There might be other glitches which may come up in the course of further development of **netcat-mptcp**. However, the current version is functional and attains the objective of manipulation of **MPTCP** subflows from the **Application Layer**.

## **8 Acknowledgements**

Acknowledgement

## 9 Bibliography

### Références

- [1] Hajime Tazaki. libos-nuse : net-next-nuse.  
<https://github.com/libos-nuse/net-next-nuse>.
- [2] Ns-3 : Direct code execution.  
<https://www.nsnam.org/overview/projects/direct-code-execution>.
- [3] Olivier Bonaventure Benjamin Hesmans. An enhanced socket api for multipath tcp.
- [4] Netcat. <http://netcat.sourceforge.net/>. Accessed : 20/12/2016.
- [5] Configure routing : Manual configuration.  
<http://multipath-tcp.org/pmwiki.php/Users/ConfigureRouting/>. Accessed : 20/12/2016.
- [6] netcat-mptcp. <https://github.com/lawrenceFR/netcat-mptcp/>. Accessed : 20/12/2016.

## 10 Appendix

Here we have the different additional information, notably the code and the scripts used in the proper functioning of our testbed.

### 10.1 Client side address assignment with the following script :

---

```
#!/bin/sh

# flush all ip addresses
ip addr flush dev eth0
ip addr flush dev eth1
ip addr flush dev eth2

# bring all the interfaces down
ip link set dev eth0 down
ip link set dev eth1 down
ip link set dev eth2 down

# bring all the interfaces up
ip link set dev eth0 up
ip link set dev eth1 up
ip link set dev eth2 up

# assign addresses to the interfaces
ip addr add 10.0.1.6/24 dev eth0
ip addr add 10.0.2.6/24 dev eth1
ip addr add 10.0.3.6/24 dev eth2
```

---

### 10.2 Server side address assignment with the following script :

---

```
#!/bin/sh

# flush all ip addresses
ip addr flush dev eth0
ip addr flush dev eth1
ip addr flush dev eth2

# bring all the interfaces down
ip link set dev eth0 down
ip link set dev eth1 down
ip link set dev eth2 down

# bring all the interfaces up
ip link set dev eth0 up
ip link set dev eth1 up
ip link set dev eth2 up

# assign addresses to the interfaces
ip addr add 10.0.4.7/24 dev eth0
ip addr add 10.0.5.7/24 dev eth1
ip addr add 10.0.6.7/24 dev eth2
```

---

### 10.3 Client side routing :

---

```
#!/bin/sh

# this rule creates three different routing tables that we use based on the
# source addresses
ip rule add from 10.0.1.6 table 1
ip rule add from 10.0.2.6 table 2
ip rule add from 10.0.3.6 table 3

# configure the three different routing tables
ip route add 10.0.1.0/24 dev eth0 scope link table 1
ip route add default via 10.0.1.1 dev eth0 table 1

ip route add 10.0.2.0/24 dev eth1 scope link table 2
ip route add default via 10.0.2.1 dev eth1 table 2

ip route add 10.0.3.0/24 dev eth2 scope link table 3
ip route add default via 10.0.3.1 dev eth2 table 3

# default route for the selection process of normal internet-traffic
ip route add default scope global nexthop via 10.0.1.1 dev eth0
```

---

### 10.4 Client routing output :

---

```
mininet@mininet-vm:~$ ip rule show
0 :      from all liiokup local
32763 : from 10.0.3.6 lookup 3
32764 : from 10.0.2.6 lookup 2
32765 : from 10.0.1.6 lookup 1
32766 : from all lookup main
32767 : from all lookup default

mininet@mininet-vm:~$ ip route
default via 10.0.1.1 dev eth0
10.0.1.0/24 dev eth0 proto kernel scope link src 10.0.1.6
10.0.2.0/24 dev eth1 proto kernel scope link src 10.0.2.6
10.0.3.0/24 dev eth2 proto kernel scope link src 10.0.3.6

mininet@mininet-vm:~$ ip route show table 1
default via 10.0.1.1 dev eth0
10.0.1.0/24 dev eth0 scope link

mininet@mininet-vm:~$ ip route show table 2
default via 10.0.2.1 dev eth1
10.0.2.0/24 dev eth0 scope link

mininet@mininet-vm:~$ ip route show table 3
default via 10.0.3.1 dev eth2
10.0.3.0/24 dev eth0 scope link
```

---

## 10.5 Server side routing :

---

```
#!/bin/sh

# this rule creates three different routing tables that we use based on the
# source addresses
ip rule add from 10.0.4.7 table 1
ip rule add from 10.0.5.7 table 2
ip rule add from 10.0.6.7 table 3

# configure the three different routing tables
ip route add 10.0.4.0/24 dev eth0 scope link table 1
ip route add default via 10.0.4.1 dev eth0 table 1

ip route add 10.0.5.0/24 dev eth1 scope link table 2
ip route add default via 10.0.5.1 dev eth1 table 2

ip route add 10.0.6.0/24 dev eth2 scope link table 3
ip route add default via 10.0.6.1 dev eth2 table 3

# default route for the selection process of normal internet-traffic
ip route add default scope global nexthop via 10.0.4.1 dev eth0
```

---

## 10.6 Server routing output :

---

```
mininet@mininet-vm:~$ ip rule show
0 :      from all liiokup local
32763 : from 10.0.6.7 lookup 3
32764 : from 10.0.5.7 lookup 2
32765 : from 10.0.4.7 lookup 1
32766 : from all lookup main
32767 : from all lookup default

mininet@mininet-vm:~$ ip route
default via 10.0.4.1 dev eth0
10.0.4.0/24 dev eth0 proto kernel scope link src 10.0.4.7
10.0.5.0/24 dev eth1 proto kernel scope link src 10.0.5.7
10.0.6.0/24 dev eth2 proto kernel scope link src 10.0.6.7

mininet@mininet-vm:~$ ip route show table 1
default via 10.0.4.1 dev eth0
10.0.4.0/24 dev eth0 scope link

mininet@mininet-vm:~$ ip route show table 2
default via 10.0.5.1 dev eth1
10.0.5.0/24 dev eth0 scope link

mininet@mininet-vm:~$ ip route show table 3
default via 10.0.6.1 dev eth2
10.0.6.0/24 dev eth0 scope link
```

---

### **10.7 Router R1 :**

---

```
enable
conf t
interface fastEthernet0/0
ip address 10.0.1.1 255.255.255.0
no shut
exit
interface fastEthernet0/1
ip address 10.0.4.1 255.255.255.0
no shut
exit
interface fastEthernet1/0
ip address 10.0.7.1 255.255.255.0
no shut
exit

ip route 10.0.1.0 255.255.255.0 fastEthernet0/0
ip route 10.0.4.0 255.255.255.0 fastEthernet0/1
ip route 0.0.0.0 0.0.0.0 fastEthernet1/0
exit
write
sh ip route
```

---

### **10.8 Router R1 routing output :**

---

```
10.0.0.0/24 is subnetted, 3 subnets
C      10.0.1.0 is directly connected, FastEthernet0/0
C      10.0.7.0 is directly connected, FastEthernet1/0
C      10.0.4.0 is directly connected, FastEthernet0/1
S*    0.0.0.0/0 is directly connected, FastEthernet1/0
```

---

### **10.9 Router R2 :**

---

```
enable
conf t
interface fastEthernet0/0
ip address 10.0.2.1 255.255.255.0
no shut
exit
interface fastEthernet0/1
ip address 10.0.5.1 255.255.255.0
no shut
exit
interface fastEthernet1/0
ip address 10.0.7.2 255.255.255.0
no shut
exit
interface fastEthernet2/0
ip address 10.0.8.2 255.255.255.0
no shut
```

```
exit

ip route 10.0.1.0 255.255.255.0 fastEthernet1/0
ip route 10.0.2.0 255.255.255.0 fastEthernet0/0
ip route 10.0.3.0 255.255.255.0 fastEthernet2/0
ip route 10.0.4.0 255.255.255.0 fastEthernet1/0
ip route 10.0.5.0 255.255.255.0 fastEthernet0/1
ip route 10.0.6.0 255.255.255.0 fastEthernet2/0
ip route 0.0.0.0 0.0.0.0 fastEthernet1/0
exit
write
sh ip route
```

---

## 10.10 Router R2 routing output :

---

```
10.0.0.0/24 is subnetted, 8 subnets
C      10.0.8.0 is directly connected, FastEthernet2/0
C      10.0.2.0 is directly connected, FastEthernet0/0
S      10.0.3.0 is directly connected, FastEthernet2/0
S      10.0.1.0 is directly connected, FastEthernet1/0
S      10.0.6.0 is directly connected, FastEthernet2/0
C      10.0.7.0 is directly connected, FastEthernet1/0
S      10.0.4.0 is directly connected, FastEthernet1/0
C      10.0.5.0 is directly connected, FastEthernet0/1
S*    0.0.0.0/0 is directly connected, FastEthernet1/0
```

---

## 10.11 Router R3 :

---

```
enable
conf t
interface fastEthernet0/0
ip address 10.0.3.1 255.255.255.0
no shut
exit
interface fastEthernet0/1
ip address 10.0.6.1 255.255.255.0
no shut
exit
interface fastEthernet1/0
ip address 10.0.8.1 255.255.255.0
no shut
exit

ip route 10.0.3.0 255.255.255.0 fastEthernet0/0
ip route 10.0.6.0 255.255.255.0 fastEthernet0/1
ip route 0.0.0.0 0.0.0.0 fastEthernet1/0
exit
write
sh ip route
```

---

## 10.12 Router R3 routing output :

---

```
10.0.0.0/24 is subnetted, 3 subnets
C      10.0.8.0 is directly connected, FastEthernet1/0
C      10.0.3.0 is directly connected, FastEthernet0/0
C      10.0.6.0 is directly connected, FastEthernet0/1
S*    0.0.0.0/0 is directly connected, FastEthernet1/0
```

---

## 10.13 Makefile.am :

---

```
28 netcat_SOURCES = \
29   core.c \
30   flagset.c \
31   misc.c \
32   netcat.c \
33   network.c \
34   telnet.c \
35   udphelper.c \
36   makeaddr.c \
37   subinfo.c \
38   submanip.c \
39   suboption.c
```

---

## 10.14 Makefile.in :

---

```
153 netcat_SOURCES = \
154   core.c \
155   flagset.c \
156   misc.c \
157   netcat.c \
158   network.c \
159   telnet.c \
160   udphelper.c \
161   makeaddr.c \
162   subinfo.c \
163   submanip.c \
164   suboption.c

.

.

.

183 am_netcat_OBJECTS = core.$(OBJEXT) flagset.$(OBJEXT) misc.$(OBJEXT) \
184   netcat.$(OBJEXT) network.$(OBJEXT) telnet.$(OBJEXT) \
185   makeaddr.$(OBJEXT) subinfo.$(OBJEXT) submanip.$(OBJEXT) \
186   suboption.$(OBJEXT)
```

---

## 10.15 netcat.h :

---

---

```
203 extern bool opt_addAllSubflows; /* option to add all the remaining subflows
204 extern bool opt_addWifi; // option to add the wifi subflow only
205 extern bool opt_addCellular; // option to add the cellular subflow only
```

---

### 10.16 netcat.c :

---

```
58 bool opt_addAllSubflows = FALSE; /* option to ad all the supplementary
                                     subflows */
59 bool opt_addWifi = FALSE; /* option to add the Wifi subflow */
60 bool opt_addCellular = FALSE; /* option to add the Cellular subflow */

.

.

.

192 { “all”,      no_argument,      NULL, ‘a’ },
.

.

.

194 { “cellular”, no_argument,      NULL, ‘C’ },
.

.

.

222 { “wifi”,     no_argument,      NULL, ‘W’ },
.

.

.

227 c = getopt_long(argc, argv, “acCde:g:G:hi:lL:no:p:P:rs:S:tTuvVxw:Wz”,
228                      long_options, &option_index);
.

.

.

233 case ‘a’ :
234     opt_addAllSubflows = TRUE; /* enable MPTCP all subflows */
235     break;
.

.

.

239 case ‘C’ :
240     opt_addCellular = TRUE; /* enable MPTCP Cellular subflow */
241     break;
.

.

.

357 case ‘W’ :
358     opt_addWifi = TRUE; /*enable MPTCP Wifi subflow */
359     break;
```

---

### 10.17 core.h :

---

```
21 #include<stdio.h>
22 #include<stdlib.h>
```

---

```

23 #include<string.h>
24
25 #define FILENAME "config.conf"
26 #define MAXBUF 1024
27 #define DELIM "="
28
29 struct config {
30     char wifi[MAXBUF];
31     char cellular[MAXBUF];
32 };
33
34 struct config readConfig();
35
36 void addAllSubflows(int);
37 void addSubflow(int, char[]);

```

---

### 10.18 core.c :

```

394 if(opt_addWifi) {
395     printf("\nEntering Wifi\n");
396     struct config configstruct = readConfig();
397     addSubflow(sock, configstruct.wifi);
398 } else if(opt_addCellular) {
399     struct config configstruct = readConfig();
400     addSubflow(sock, configstruct.cellular);
401 } else if(opt_addAllSubflows) {
402     addAllSubflows(sock);
403 }else {
404     printf("\nNo supplementary flow initiation asked\n");
405 }

.

.

.

535 /* ... */
536
537
538 void addAllSubflows(int sock) {
539
540     // structure to store the list of subflows
541     struct mptcp_sub_tuple_list *list;
542
543     // d'abord trouver les interfaces disponible, puis etablir les sous
544     // flux
545
546     // get the subflow list
547     if(mptcp_get_sub_list(sock, &list) != 0) {
548         printf("\nError getting the list of subflows !");
549     }
550     // structure to store the subflow src dst ip port
551     struct mptcp_sub_tuple_info struc;
552     // get the structure mptcp_sub_tuple_info
553     if(mptcp_get_sub_tuple(sock, list->subid, &struc) != 0) {

```

```

553         printf("\nError getting the structure mptcp_sub_tuple_info !");
554     }
555     // char array storing the client interface addresses
556     char client_addr[4096];
557     int client_port = struc.sourceP;
558     int server_port = struc.destP;
559
560     // structures and variables for getting the characteristics of the
561     // other interfaces
562     struct ifaddrs *ifaddr, *ifa;
563     int family;
564
565     if(getifaddrs(&ifaddr) != 0) {
566         printf("\nError getting the interface addresses !");
567     }
568     for(ifa = ifaddr; ifa != NULL; ifa = ifa->ifa_next) {
569         if(ifa->ifa_addr == NULL) {
570             continue;
571         }
572         family = ifa->ifa_addr->sa_family;
573         if(family == AF_INET) {
574             inet_ntop(AF_INET, &(*ifa->ifa_addr)->sin_addr, client_addr, INET_ADDRSTRLEN);
575             if((strcmp(client_addr, struc.sourceH) != 0) &&
576                 (strcmp(client_addr, "127.0.0.1") != 0)) {
577                 if(mptcp_add_subflow(sock, AF_INET, client_addr,
578                     ++client_port, struc.destH, server_port) != 0) {
579                     printf("\nError adding a subflow !");
580                 }
581             } else {
582                 //inet_ntop(AF_INET6, &(*ifa->ifa_addr)->sin6_addr, client_addr, INET6_ADDRSTRLEN);
583                 //if((strcmp(client_addr, struc.sourceH) != 0) &&
584                 //    (strcmp(client_addr, "::1") != 0)) {
585                     // if(mptcp_add_subflow(sockfd, AF_INET6, client_addr,
586                     // struc.sourceP, struc.destH, struc.destP) != 0) {
587                         //     printf("\nError adding a subflow !");
588                     // }
589                 //}
590             }
591         }
592
593         /* display subflows */
594
595         if(mptcp_get_sub_list(sock, &list) != 0) {
596             printf("\nError getting the list of subflows !");
597         }
598         while(list != NULL){
599             mptcp_get_sub_tuple(sock, list->subid, &struc);

```

```

600         printf("(%s %d) -> (%s %d)\n", struc.sourceH, struc.sourceP,
601             struc.destH, struc.destP);
602         list = list->next;
603     }
604
605
606
607 }
608 /* ... */
609
610 void addSubflow(int sock, char ip[]) {
611     /*
612     printf("\nRes = %d\n", mptcp_add_subflow(sock, AF_INET, "10.0.5.7",
613         64101, 10.0.4.7, 64000, 1));
614     */
615     printf("\nIP address read is %s\n", ip);
616     // structure to store the list of subflows
617     struct mptcp_sub_tuple_list *list;
618
619     // get the subflow list
620     if(mptcp_get_sub_list(sock, &list) != 0) {
621         printf("\nError getting the list of subflows !");
622     }
623     // structure to store the subflow src dst ip port
624     struct mptcp_sub_tuple_info struc;
625     // get the structure mptcp_sub_tuple_info
626     if(mptcp_get_sub_tuple(sock, list->subid, &struc) != 0) {
627         printf("\nError getting the structure mptcp_sub_tuple_info !");
628     }
629     // char array storing the client interface addresses
630     char client_addr[4096];
631     int client_port = struc.sourceP;
632     int server_port = struc.destP;
633     int resultat;
634     if((resultat = mptcp_add_subflow(sock, AF_INET, ip, ++client_port,
635         struc.destH, server_port)) != 0) {
636         printf("\nError adding a subflow ! Result = %d\n",
637             resultat);
638     }
639     /* display subflows */
640
641     if(mptcp_get_sub_list(sock, &list) != 0) {
642         printf("\nError getting the list of subflows !");
643     }
644     while(list != NULL){
645         mptcp_get_sub_tuple(sock, list->subid, &struc);
646         printf("(%s %d) -> (%s %d)\n", struc.sourceH, struc.sourceP,
647             struc.destH, struc.destP);
648         list = list->next;
649     }
650

```

```

651 }
652
653
654 /* ... */
655
656 struct config readConfig() {
657     struct config configstruct;
658     printf("\nReading config file\n");
659     FILE *file = fopen("/home/mininet/netcat-mptcp/src/config.conf", "r");
660
661     if(file != NULL) {
662         char line[MAXBUF];
663         int i = 0;
664
665         while(fgets(line, sizeof(line), file) != NULL) {
666             char *cpline;
667             cpline = strstr((char *)line, DELIM);
668             cpline = cpline + strlen(DELIM);
669
670             if(i == 0) {
671                 memcpy(configstruct.wifi, cpline, strlen(cpline));
672                 printf("\nWifi ip address is %s\n", configstruct.wifi);
673             } else if(i == 1) {
674                 memcpy(configstruct.cellular, cpline, strlen(cpline));
675                 printf("\nCellular ip address is %s\n",
676                     configstruct.cellular);
677             } else {
678                 printf("\nNo more lines\n");
679             }
680             i++;
681         }
682         fclose(file);
683     }
684     return configstruct;
685 }
686
687
688 /* ... */

```

---

### 10.19 config.conf :

---

```

WIFI=10.0.2.6
CELLULAR=10.0.3.6

```

---