

Project Master Book

Generated: 2026-04-01 00:11:39

Table of Contents

Table of Contents	1
1. Project Scope and Goals	11
2. Architecture and System Design	11
Folder Distribution	11
Topic Distribution	11
3. Libraries and Framework Usage	12
4. File-by-File Deep Explanation	14
File 1: .dockerignore	14
File 2: .env	14
File 3: .env.example	14
File 4: .flake8	14
File 5: .vscode/settings.json	14
File 6: .vscode/tasks.json	14
File 7: _startup_probe.py	14
File 8: advanced_watchdog_script.py	14
File 9: alert_system.py	14
File 10: app.py	15
File 11: app_asgi.py	15
File 12: Caddyfile	15
File 13: change_log_backup.csv	15
File 14: ci_gate.py	15
File 15: docker-compose.https.yml	15
File 16: docker-compose.yml	15
File 17: Dockerfile	15
File 18: err.txt	15

File 19: fail_extract.txt	16
File 20: file_monitor.py	16
File 21: manager_sla_card_test.txt	16
File 22: manager_sla_card_test_exit.txt	16
File 23: migrate_msg.txt	16
File 24: migrate_msg2.txt	16
File 25: migrations/alembic.ini	16
File 26: migrations/env.py	16
File 27: migrations/README	16
File 28: migrations/script.py.mako	17
File 29: migrations/versions/5d1f3c2d9f91_add_scalable_list_indexes.py	17
File 30: migrations/versions/6bf60953b28f_add_scalable_list_indexes.py	17
File 31: migrations/versions/7332ed65ba00_add_risk_score_and_sla_deadline_columns_.py	17
File 32: model.py	17
File 33: out.txt	17
File 34: out_docker.txt	17
File 35: out_pg_dirs.txt	17
File 36: out_psql_path.txt	18
File 37: out_service.json	18
File 38: parse_doc.py	18
File 39: photo/doc_text_lines.txt	18
File 40: pm_app/__init__.py	18
File 41: pm_app/api/__init__.py	18
File 42: pm_app/api/routes.py	18
File 43: pm_app/api/serializers.py	18
File 44: pm_app/auth/__init__.py	18
File 45: pm_app/auth/forms.py	19
File 46: pm_app/auth/routes.py	19
File 47: pm_app/auth/utils.py	19
File 48: pm_app/dashboards/__init__.py	19

File 49: pm_app/dashboards/routes.py	19
File 50: pm_app/services/__init__.py	19
File 51: pm_app/services/database.py	19
File 52: pm_app/services/email.py	19
File 53: pm_app/services/maintenance.py	19
File 54: pm_app/services/observability.py	20
File 55: pm_app/services/time_utils.py	20
File 56: pyrightconfig.json	20
File 57: pytest.ini	20
File 58: pytest_fail_auth.txt	20
File 59: pytest_latest.txt	20
File 60: pytest_out.txt	20
File 61: pytest_out3.txt	20
File 62: pytest_profile_edit_output.txt	20
File 63: pytest_targeted.txt	21
File 64: README.md	21
File 65: requirements.txt	21
File 66: run.bat	21
File 67: scripts/backfill_activity_metrics.py	21
File 68: scripts/generate_project_book.py	21
File 69: SDLC_STAGE_REPORT.md	21
File 70: sdlc_stage_status.json	21
File 71: services/__init__.py	21
File 72: services/login_throttle.py	22
File 73: sla_fix_test_exit.txt	22
File 74: sla_fix_test_output.txt	22
File 75: sqlite_refs.json	22
File 76: sqlite_refs.txt	22
File 77: stage_dev_compile_status.txt	22

File 78: stage_dev_flake8.txt	22
File 79: stage_dev_flake8_status.txt	22
File 80: stage_dev_pip_check.txt	22
File 81: stage_prod_config.txt	23
File 82: stage_prod_config_status.txt	23
File 83: stage_staging_smoke.txt	23
File 84: stage_staging_smoke_status.txt	23
File 85: stage_test_pytest.txt	23
File 86: stage_test_pytest_status.txt	23
File 87: static/soliton-telmec.png	23
File 88: static/style.css	23
File 89: templates/500.html	23
File 90: templates/activities.html	24
File 91: templates/activity_view.html	24
File 92: templates/add_general_manager.html	24
File 93: templates/add_manager.html	24
File 94: templates/add_staff.html	24
File 95: templates/add_technician.html	24
File 96: templates/admin_staff.html	24
File 97: templates/consumable_detail.html	24
File 98: templates/consumables.html	24
File 99: templates/dashboard.html	25
File 100: templates/desk_activities.html	25
File 101: templates/developer_photo_library.html	25
File 102: templates/developer_role_dashboard.html	25
File 103: templates/developer_user_activity.html	25
File 104: templates/developer_user_control.html	25
File 105: templates/emergency.html	25
File 106: templates/field_rca.html	25
File 107: templates/layout.html	25

File 108: templates/login.html	26
File 109: templates/manager_dashboard.html	26
File 110: templates/not_found.html	26
File 111: templates/notifications.html	26
File 112: templates/register.html	26
File 113: templates/settings.html	26
File 114: templates/staff_dashboard.html	26
File 115: templates/technician_activity_view.html	26
File 116: templates/technician_calendar.html	26
File 117: templates/technician_dashboard.html	27
File 118: templates/technician_rejected_reports.html	27
File 119: templates/technician_submissions.html	27
File 120: test_all_output.txt	27
File 121: test_full_out.txt	27
File 122: test_full_out2.txt	27
File 123: test_output.txt	27
File 124: test_reset_out.txt	27
File 125: test_settings_output.txt	27
File 126: tests/conftest.py	28
File 127: tests/test_auth.py	28
File 128: tests/test_notifications.py	28
File 129: tests/test_security.py	28
File 130: upgrade_msg.txt	28
File 131: upgrade_out_scale.txt	28
File 132: watchdog_monitor.py	28
File 133: watchdog_reporter_errors.log	28
 5. Line-by-Line Explanation for Every Included File	 29
File 1: .dockerignore	30
File 2: .env	31

File 3: .env.example	32
File 4: .flake8	34
File 5: .vscode/settings.json	35
File 6: .vscode/tasks.json	36
File 7: _startup_probe.py	39
File 8: advanced_watchdog_script.py	40
File 9: alert_system.py	46
File 10: app.py	47
File 11: app_asgi.py	113
File 12: Caddyfile	114
File 13: change_log_backup.csv	115
File 14: ci_gate.py	120
File 15: docker-compose.https.yml	122
File 16: docker-compose.yml	123
File 17: Dockerfile	125
File 18: err.txt	126
File 19: fail_extract.txt	127
File 20: file_monitor.py	128
File 21: manager_sla_card_test.txt	129
File 22: manager_sla_card_test_exit.txt	130
File 23: migrate_msg.txt	131
File 24: migrate_msg2.txt	132
File 25: migrations/alembic.ini	133
File 26: migrations/env.py	134
File 27: migrations/README	137
File 28: migrations/script.py.mako	138
File 29: migrations/versions/5d1f3c2d9f91_add_scalable_list_indexes.py	139
File 30: migrations/versions/6bf60953b28f_add_scalable_list_indexes.py	140
File 31: migrations/versions/7332ed65ba00_add_risk_score_and_sla_deadline_columns_.py	141
File 32: model.py	142

File 33: out.txt	145
File 34: out_docker.txt	150
File 35: out_pg_dirs.txt	151
File 36: out_psql_path.txt	152
File 37: out_service.json	153
File 38: parse_doc.py	154
File 39: photo/doc_text_lines.txt	155
File 40: pm_app/__init__.py	160
File 41: pm_app/api/__init__.py	161
File 42: pm_app/api/routes.py	162
File 43: pm_app/api/serializers.py	165
File 44: pm_app/auth/__init__.py	166
File 45: pm_app/auth/forms.py	167
File 46: pm_app/auth/routes.py	168
File 47: pm_app/auth/utls.py	172
File 48: pm_app/dashboards/__init__.py	173
File 49: pm_app/dashboards/routes.py	174
File 50: pm_app/services/__init__.py	181
File 51: pm_app/services/database.py	182
File 52: pm_app/services/email.py	183
File 53: pm_app/services/maintenance.py	184
File 54: pm_app/services/observability.py	187
File 55: pm_app/services/time_utils.py	188
File 56: pyrightconfig.json	189
File 57: pytest.ini	190
File 58: pytest_fail_auth.txt	191
File 59: pytest_latest.txt	194
File 60: pytest_out.txt	195
File 61: pytest_out3.txt	196

File 62: pytest_profile_edit_output.txt	198
File 63: pytest_targeted.txt	199
File 64: README.md	200
File 65: requirements.txt	206
File 66: run.bat	207
File 67: scripts/backfill_activity_metrics.py	208
File 68: scripts/generate_project_book.py	209
File 69: SDLC_STAGE_REPORT.md	218
File 70: sdlc_stage_status.json	221
File 71: services/__init__.py	222
File 72: services/login_throttle.py	223
File 73: sla_fix_test_exit.txt	225
File 74: sla_fix_test_output.txt	226
File 75: sqlite_refs.json	227
File 76: sqlite_refs.txt	229
File 77: stage_dev_compile_status.txt	230
File 78: stage_dev_flake8.txt	231
File 79: stage_dev_flake8_status.txt	232
File 80: stage_dev_pip_check.txt	233
File 81: stage_prod_config.txt	234
File 82: stage_prod_config_status.txt	235
File 83: stage_staging_smoke.txt	236
File 84: stage_staging_smoke_status.txt	237
File 85: stage_test_pytest.txt	238
File 86: stage_test_pytest_status.txt	241
File 87: static/soliton-telmec.png	242
File 88: static/style.css	243
File 89: templates/500.html	324
File 90: templates/activities.html	325
File 91: templates/activity_view.html	326

File 92: templates/add_general_manager.html	327
File 93: templates/add_manager.html	328
File 94: templates/add_staff.html	329
File 95: templates/add_technician.html	330
File 96: templates/admin_staff.html	331
File 97: templates/consumable_detail.html	339
File 98: templates/consumables.html	341
File 99: templates/dashboard.html	346
File 100: templates/desk_activities.html	353
File 101: templates/developer_photo_library.html	358
File 102: templates/developer_role_dashboard.html	361
File 103: templates/developer_user_activity.html	369
File 104: templates/developer_user_control.html	371
File 105: templates/emergency.html	381
File 106: templates/field_rca.html	383
File 107: templates/layout.html	391
File 108: templates/login.html	407
File 109: templates/manager_dashboard.html	411
File 110: templates/not_found.html	414
File 111: templates/notifications.html	415
File 112: templates/register.html	418
File 113: templates/settings.html	419
File 114: templates/staff_dashboard.html	423
File 115: templates/technician_activity_view.html	426
File 116: templates/technician_calendar.html	427
File 117: templates/technician_dashboard.html	428
File 118: templates/technician_rejected_reports.html	432
File 119: templates/technician_submissions.html	433
File 120: test_all_output.txt	435

File 121: test_full_out.txt	436
File 122: test_full_out2.txt	437
File 123: test_output.txt	438
File 124: test_reset_out.txt	439
File 125: test_settings_output.txt	440
File 126: tests/conftest.py	441
File 127: tests/test_auth.py	443
File 128: tests/test_notifications.py	449
File 129: tests/test_security.py	455
File 130: upgrade_msg.txt	465
File 131: upgrade_out_scale.txt	466
File 132: watchdog_monitor.py	467
File 133: watchdog_reporter_errors.log	468

1. Project Scope and Goals

This documentation explains the complete project in a strict sequence: scope, architecture, libraries, file deep-dives, then line-level explanations.

Included files: 133

2. Architecture and System Design

Folder Distribution

Folder	File Count
root	66
templates	31
pm_app	16
migrations	7
tests	4
.vscode	2
scripts	2
services	2
static	2
photo	1

Topic Distribution

Topic	Files
python	38
templating	32
frontend markup	31
security/authentication	29
flask web routing	24
testing	20
database migrations	18
database orm	16
containerization	8
configuration	4
styling	1

3. Libraries and Framework Usage

Library	Python Files Referencing
datetime	8
model	8
app	7
werkzeug	7
time	6
flask	6
os	5
flask_login	5
email	4
smtplib	4
re	4
alembic	4
__future__	4
pm_app	3
sqlalchemy	3
conftest	3
html	2
pathlib	2
dotenv	2
base64	2
io	2
logging	2
reportlab	2
secrets	2
uuid	2
typing	2
pytest	2
alert_system	1
csv	1
difflib	1
threading	1
watchdog	1
PIL	1
boto3	1
click	1
flask_limiter	1
flask_migrate	1
functools	1
hmac	1
ipaddress	1

openpyxl	1
redis	1
services	1
shutil	1
socket	1
urllib	1
asgiref	1
argparse	1
subprocess	1
sys	1
flask_sqlalchemy	1
json	1
dataclasses	1
ast	1
collections	1
struct	1
tempfile	1
zlib	1
hashlib	1

4. File-by-File Deep Explanation

File 1: .dockerignore

Line count: 17

Topics: testing

Key libraries: not applicable

File 2: .env

Line count: 44

Topics: containerization, flask web routing

Key libraries: not applicable

File 3: .env.example

Line count: 55

Topics: flask web routing

Key libraries: not applicable

File 4: .flake8

Line count: 38

Topics: database migrations

Key libraries: not applicable

File 5: .vscode/settings.json

Line count: 1

Topics: general project support

Key libraries: not applicable

File 6: .vscode/tasks.json

Line count: 136

Topics: containerization, database migrations, testing

Key libraries: not applicable

File 7: __startup__probe.py

Line count: 5

Topics: python

Key libraries: app

File 8: advanced_watchdog_script.py

Line count: 307

Topics: python

Key libraries: alert_system, csv, datetime, difflib, email, html, os, pathlib, smtplib, threading, time, watchdog

File 9: alert_system.py

Line count: 30

Topics: python

Key libraries: dotenv, email, os, smtplib

File 10: app.py

Line count: 3592

Topics: database migrations, database orm, flask web routing, python, security/authentication

Key libraries: PIL, base64, boto3, click, datetime, dotenv, email, flask, flask_limiter, flask_login, flask_migrate, functools, hmac, io, ipaddress, logging, model, openpyxl, os, pm_app, re, redis, reportlab, secrets, services, shutil, smtplib, socket, sqlalchemy, time, urllib, uuid, werkzeug

File 11: app_asgi.py

Line count: 7

Topics: flask web routing, python

Key libraries: app, asgiref

File 12: Caddyfile

Line count: 18

Topics: general project support

Key libraries: not applicable

File 13: change_log_backup.csv

Line count: 226

Topics: general project support

Key libraries: not applicable

File 14: ci_gate.py

Line count: 89

Topics: python, testing

Key libraries: argparse, subprocess, sys

File 15: docker-compose.https.yml

Line count: 31

Topics: configuration, containerization

Key libraries: not applicable

File 16: docker-compose.yml

Line count: 54

Topics: configuration, containerization

Key libraries: not applicable

File 17: Dockerfile

Line count: 16

Topics: containerization

Key libraries: not applicable

File 18: err.txt

Line count: 0

Topics: general project support

Key libraries: not applicable

File 19: fail_extract.txt

Line count: 9

Topics: security/authentication

Key libraries: not applicable

File 20: file_monitor.py

Line count: 2

Topics: python

Key libraries: not applicable

File 21: manager_sla_card_test.txt

Line count: 2

Topics: general project support

Key libraries: not applicable

File 22: manager_sla_card_test_exit.txt

Line count: 1

Topics: general project support

Key libraries: not applicable

File 23: migrate_msg.txt

Line count: 9

Topics: database migrations, flask web routing

Key libraries: not applicable

File 24: migrate_msg2.txt

Line count: 35

Topics: database migrations, flask web routing

Key libraries: not applicable

File 25: migrations/alembic.ini

Line count: 50

Topics: configuration, database migrations, database orm, flask web routing

Key libraries: not applicable

File 26: migrations/env.py

Line count: 113

Topics: database migrations, database orm, flask web routing, python

Key libraries: alembic, flask, logging

File 27: migrations/README

Line count: 1

Topics: flask web routing

Key libraries: not applicable

File 28: migrations/script.py.mako

Line count: 24

Topics: database migrations, database orm

Key libraries: not applicable

File 29: migrations/versions/5d1f3c2d9f91_add_scalable_list_indexes.py

Line count: 43

Topics: database migrations, python

Key libraries: alembic

File 30: migrations/versions/6bf60953b28f_add_scalable_list_indexes.py

Line count: 50

Topics: database migrations, database orm, python

Key libraries: alembic, sqlalchemy

File 31: migrations/versions/7332ed65ba00_add_risk_score_and_sla_deadline_columns.py

Line count: 46

Topics: database migrations, database orm, python

Key libraries: alembic, sqlalchemy

File 32: model.py

Line count: 155

Topics: database orm, flask web routing, python

Key libraries: flask_sqlalchemy, json, pm_app

File 33: out.txt

Line count: 231

Topics: general project support

Key libraries: not applicable

File 34: out_docker.txt

Line count: 1

Topics: containerization

Key libraries: not applicable

File 35: out_pg_dirs.txt

Line count: 1

Topics: general project support

Key libraries: not applicable

File 36: out_psql_path.txt

Line count: 1

Topics: general project support

Key libraries: not applicable

File 37: out_service.json

Line count: 0

Topics: general project support

Key libraries: not applicable

File 38: parse_doc.py

Line count: 17

Topics: python

Key libraries: re

File 39: photo/doc_text_lines.txt

Line count: 235

Topics: general project support

Key libraries: not applicable

File 40: pm_app/__init__.py

Line count: 23

Topics: flask web routing, python

Key libraries: __future__, app, flask_login

File 41: pm_app/api/__init__.py

Line count: 0

Topics: python

Key libraries: not applicable

File 42: pm_app/api/routes.py

Line count: 149

Topics: flask web routing, python

Key libraries: flask, flask_login

File 43: pm_app/api/serializers.py

Line count: 1

Topics: python

Key libraries: not applicable

File 44: pm_app/auth/__init__.py

Line count: 0

Topics: python, security/authentication

Key libraries: not applicable

File 45: pm_app/auth/forms.py

Line count: 1

Topics: database migrations, flask web routing, python, security/authentication

Key libraries: not applicable

File 46: pm_app/auth/routes.py

Line count: 191

Topics: flask web routing, python, security/authentication

Key libraries: flask, flask_login, model, secrets, werkzeug

File 47: pm_app/auth/utils.py

Line count: 9

Topics: python, security/authentication

Key libraries: werkzeug

File 48: pm_app/dashboards/__init__.py

Line count: 1

Topics: python

Key libraries: not applicable

File 49: pm_app/dashboards/routes.py

Line count: 347

Topics: database orm, flask web routing, python

Key libraries: app, flask, flask_login, model, pm_app

File 50: pm_app/services/__init__.py

Line count: 0

Topics: python

Key libraries: not applicable

File 51: pm_app/services/database.py

Line count: 1

Topics: python

Key libraries: not applicable

File 52: pm_app/services/email.py

Line count: 25

Topics: python

Key libraries: email, os, smtplib

File 53: pm_app/services/maintenance.py

Line count: 132

Topics: python

Key libraries: __future__, dataclasses, datetime, time, typing

File 54: pm_app/services/observability.py

Line count: 32

Topics: flask web routing, python

Key libraries: __future__, flask, time, uuid

File 55: pm_app/services/time_utils.py

Line count: 6

Topics: python

Key libraries: datetime

File 56: pyrightconfig.json

Line count: 5

Topics: general project support

Key libraries: not applicable

File 57: pytest.ini

Line count: 4

Topics: configuration, testing

Key libraries: not applicable

File 58: pytest_fail_auth.txt

Line count: 123

Topics: general project support

Key libraries: not applicable

File 59: pytest_latest.txt

Line count: 49

Topics: database orm, flask web routing, testing

Key libraries: not applicable

File 60: pytest_out.txt

Line count: 35

Topics: database orm, testing

Key libraries: not applicable

File 61: pytest_out3.txt

Line count: 71

Topics: database orm, security/authentication, testing

Key libraries: not applicable

File 62: pytest_profile_edit_output.txt

Line count: 39

Topics: general project support

Key libraries: not applicable

File 63: pytest_targeted.txt

Line count: 25

Topics: general project support

Key libraries: not applicable

File 64: README.md

Line count: 313

Topics: containerization, database migrations, database orm, flask web routing, security/authentication, testing

Key libraries: not applicable

File 65: requirements.txt

Line count: 30

Topics: database migrations, database orm, flask web routing, templating, testing

Key libraries: not applicable

File 66: run.bat

Line count: 2

Topics: general project support

Key libraries: not applicable

File 67: scripts/backfill_activity_metrics.py

Line count: 51

Topics: python

Key libraries: app, datetime, model

File 68: scripts/generate_project_book.py

Line count: 478

Topics: containerization, database migrations, database orm, flask web routing, python, security/authentication, templating, testing

Key libraries: __future__, ast, collections, datetime, html, pathlib, re, reportlab, typing

File 69: SDLC_STAGE_REPORT.md

Line count: 112

Topics: flask web routing, testing

Key libraries: not applicable

File 70: sdlc_stage_status.json

Line count: 8

Topics: testing

Key libraries: not applicable

File 71: services/__init__.py

Line count: 0

Topics: python

Key libraries: not applicable

File 72: services/login_throttle.py

Line count: 74

Topics: python

Key libraries: time

File 73: sla_fix_test_exit.txt

Line count: 1

Topics: general project support

Key libraries: not applicable

File 74: sla_fix_test_output.txt

Line count: 5

Topics: general project support

Key libraries: not applicable

File 75: sqlite_refs.json

Line count: 102

Topics: database migrations

Key libraries: not applicable

File 76: sqlite_refs.txt

Line count: 0

Topics: general project support

Key libraries: not applicable

File 77: stage_dev_compile_status.txt

Line count: 1

Topics: general project support

Key libraries: not applicable

File 78: stage_dev_flake8.txt

Line count: 1

Topics: general project support

Key libraries: not applicable

File 79: stage_dev_flake8_status.txt

Line count: 1

Topics: general project support

Key libraries: not applicable

File 80: stage_dev_pip_check.txt

Line count: 1

Topics: general project support

Key libraries: not applicable

File 81: stage_prod_config.txt

Line count: 1

Topics: general project support

Key libraries: not applicable

File 82: stage_prod_config_status.txt

Line count: 1

Topics: general project support

Key libraries: not applicable

File 83: stage_staging_smoke.txt

Line count: 5

Topics: general project support

Key libraries: not applicable

File 84: stage_staging_smoke_status.txt

Line count: 1

Topics: general project support

Key libraries: not applicable

File 85: stage_test_pytest.txt

Line count: 140

Topics: database orm, flask web routing, security/authentication, testing

Key libraries: not applicable

File 86: stage_test_pytest_status.txt

Line count: 1

Topics: general project support

Key libraries: not applicable

File 87: static/soliton-telmec.png

Line count: 0

Topics: general project support

Key libraries: not applicable

File 88: static/style.css

Line count: 4411

Topics: styling

Key libraries: not applicable

File 89: templates/500.html

Line count: 2

Topics: frontend markup

Key libraries: not applicable

File 90: templates/activities.html

Line count: 21

Topics: frontend markup, templating

Key libraries: not applicable

File 91: templates/activity_view.html

Line count: 32

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 92: templates/add_general_manager.html

Line count: 45

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 93: templates/add_manager.html

Line count: 45

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 94: templates/add_staff.html

Line count: 46

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 95: templates/add_technician.html

Line count: 45

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 96: templates/admin_staff.html

Line count: 384

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 97: templates/consumable_detail.html

Line count: 57

Topics: frontend markup, templating

Key libraries: not applicable

File 98: templates/consumables.html

Line count: 228

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 99: templates/dashboard.html

Line count: 358

Topics: frontend markup, templating

Key libraries: not applicable

File 100: templates/desk_activities.html

Line count: 225

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 101: templates/developer_photo_library.html

Line count: 115

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 102: templates/developer_role_dashboard.html

Line count: 414

Topics: frontend markup, templating

Key libraries: not applicable

File 103: templates/developer_user_activity.html

Line count: 79

Topics: frontend markup, templating

Key libraries: not applicable

File 104: templates/developer_user_control.html

Line count: 497

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 105: templates/emergency.html

Line count: 56

Topics: frontend markup, templating

Key libraries: not applicable

File 106: templates/field_rca.html

Line count: 438

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 107: templates/layout.html

Line count: 846

Topics: frontend markup, templating

Key libraries: not applicable

File 108: templates/login.html

Line count: 189

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 109: templates/manager_dashboard.html

Line count: 125

Topics: frontend markup, templating

Key libraries: not applicable

File 110: templates/not_found.html

Line count: 8

Topics: frontend markup, templating

Key libraries: not applicable

File 111: templates/notifications.html

Line count: 118

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 112: templates/register.html

Line count: 37

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 113: templates/settings.html

Line count: 192

Topics: frontend markup, security/authentication, templating

Key libraries: not applicable

File 114: templates/staff_dashboard.html

Line count: 128

Topics: frontend markup, templating

Key libraries: not applicable

File 115: templates/technician_activity_view.html

Line count: 26

Topics: frontend markup, templating

Key libraries: not applicable

File 116: templates/technician_calendar.html

Line count: 34

Topics: frontend markup, templating

Key libraries: not applicable

File 117: templates/technician_dashboard.html

Line count: 193

Topics: frontend markup, templating

Key libraries: not applicable

File 118: templates/technician_rejected_reports.html

Line count: 45

Topics: frontend markup, templating

Key libraries: not applicable

File 119: templates/technician_submissions.html

Line count: 66

Topics: frontend markup, templating

Key libraries: not applicable

File 120: test_all_output.txt

Line count: 16

Topics: testing

Key libraries: not applicable

File 121: test_full_out.txt

Line count: 41

Topics: general project support

Key libraries: not applicable

File 122: test_full_out2.txt

Line count: 41

Topics: general project support

Key libraries: not applicable

File 123: test_output.txt

Line count: 19

Topics: testing

Key libraries: not applicable

File 124: test_reset_out.txt

Line count: 17

Topics: general project support

Key libraries: not applicable

File 125: test_settings_output.txt

Line count: 19

Topics: testing

Key libraries: not applicable

File 126: tests/conftest.py

Line count: 89

Topics: database orm, python, security/authentication, testing

Key libraries: app, model, pytest, re, werkzeug

File 127: tests/test_auth.py

Line count: 282

Topics: python, security/authentication, testing

Key libraries: conftest, datetime, model, werkzeug

File 128: tests/test_notifications.py

Line count: 277

Topics: python, security/authentication, testing

Key libraries: conftest, model, werkzeug

File 129: tests/test_security.py

Line count: 501

Topics: python, security/authentication, testing

Key libraries: app, base64, conftest, datetime, io, model, pytest, struct, tempfile, werkzeug, zlib

File 130: upgrade_msg.txt

Line count: 12

Topics: database migrations, flask web routing

Key libraries: not applicable

File 131: upgrade_out_scale.txt

Line count: 13

Topics: database migrations, flask web routing

Key libraries: not applicable

File 132: watchdog_monitor.py

Line count: 37

Topics: python

Key libraries: hashlib, os, time

File 133: watchdog_reporter_errors.log

Line count: 2

Topics: general project support

Key libraries: not applicable

5. Line-by-Line Explanation for Every Included File

File 1: .dockerignore

L0001 | .git | CSS selector line choosing the elements styled below.

L0002 | .gitignore | CSS selector line choosing the elements styled below.

L0003 | .pytest_cache | CSS selector line choosing the elements styled below.

L0004 | .venv | CSS selector line choosing the elements styled below.

L0005 | __pycache__ | Operational statement participating in the file's runtime behavior.

L0006 | *.pyc | Operational statement participating in the file's runtime behavior.

L0007 | *.pyo | Operational statement participating in the file's runtime behavior.

L0008 | *.pyd | Operational statement participating in the file's runtime behavior.

L0009 | *.db | Operational statement participating in the file's runtime behavior.

L0010 | *.sqlite | Operational statement participating in the file's runtime behavior.

L0011 | instance | Operational statement participating in the file's runtime behavior.

L0012 | uploads | Operational statement participating in the file's runtime behavior.

L0013 | out*.txt | Operational statement participating in the file's runtime behavior.

L0014 | sqlite_refs.* | Operational statement participating in the file's runtime behavior.

L0015 | photo | Operational statement participating in the file's runtime behavior.

L0016 | tinious | Operational statement participating in the file's runtime behavior.

L0017 | tests/__pycache__ | Operational statement participating in the file's runtime behavior.

File 2: .env

```
L0001 | # Core | Comment line documenting intent or context for nearby code.
L0002 | # IMPORTANT: Replace with a strong 64-char hex string before deploying. | Comment line documenting intent or context for nearby code.
L0003 | # Generate one: python -c "import secrets; print(secrets.token_hex(32))" | Comment line documenting intent or context for nearby code.
L0004 | SECRET_KEY=dev-secret-change-me-use-a-64-char-random-hex-in-production | Assignment statement storing or updating program state.
L0005 | SESSION_COOKIE_SECURE=0 | Assignment statement storing or updating program state.
L0006 | APP_ENV=development | Assignment statement storing or updating program state.
L0007 | ENABLE_ROLE_LOCKED_LOGIN=0 | Assignment statement storing or updating program state.
L0008 | | Blank line used for readability and logical separation.
L0009 | # Set to the number of reverse proxy hops in front of this app (0 = direct) | Comment line documenting intent or context for nearby code.
L0010 | TRUSTED_PROXY_COUNT=0 | Assignment statement storing or updating program state.
L0011 | | Blank line used for readability and logical separation.
L0012 | # Database | Comment line documenting intent or context for nearby code.
L0013 | # Leave DATABASE_URL empty for local development to use SQLite. | Comment line documenting intent or context for nearby code.
L0014 | # Set this in production/staging to your PostgreSQL URL. | Comment line documenting intent or context for nearby code.
L0015 | DATABASE_URL= | Assignment statement storing or updating program state.
L0016 | DEV_DATABASE_URL= | Assignment statement storing or updating program state.
L0017 | | Blank line used for readability and logical separation.
L0018 | # PostgreSQL credentials (used by docker-compose and DATABASE_URL) | Comment line documenting intent or context for nearby code.
L0019 | POSTGRES_DB=pm_db | Assignment statement storing or updating program state.
L0020 | POSTGRES_USER=pm_user | Assignment statement storing or updating program state.
L0021 | # REQUIRED for docker-compose - set a strong password here: | Comment line documenting intent or context for nearby code.
L0022 | POSTGRES_PASSWORD=change-me-strong-password | Assignment statement storing or updating program state.
L0023 | | Blank line used for readability and logical separation.
L0024 | # Set to 1 only for local development | Comment line documenting intent or context for nearby code.
L0025 | FLASK_DEBUG=0 | Assignment statement storing or updating program state.
L0026 | | Blank line used for readability and logical separation.
L0027 | # Alert email (used by app and watchdog alerting) | Comment line documenting intent or context for nearby code.
L0028 | ALERT_EMAIL_ADDRESS= | Assignment statement storing or updating program state.
L0029 | ALERT_EMAIL_PASSWORD= | Assignment statement storing or updating program state.
L0030 | | Blank line used for readability and logical separation.
L0031 | # Optional S3 storage | Comment line documenting intent or context for nearby code.
L0032 | S3_BUCKET= | Assignment statement storing or updating program state.
L0033 | S3_KEY= | Assignment statement storing or updating program state.
L0034 | S3_SECRET= | Assignment statement storing or updating program state.
L0035 | S3_REGION=us-east-1 | Assignment statement storing or updating program state.
L0036 | | Blank line used for readability and logical separation.
L0037 | # Public URL used for externally shared login links | Comment line documenting intent or context for nearby code.
L0038 | # Example: https://rca.solitonerp.com | Comment line documenting intent or context for nearby code.
L0039 | PUBLIC_BASE_URL=http://localhost:5000 | Assignment statement storing or updating program state.
L0040 | | Blank line used for readability and logical separation.
L0041 | # Optional watchdog email overrides | Comment line documenting intent or context for nearby code.
L0042 | WATCHER_EMAIL_FROM= | Assignment statement storing or updating program state.
L0043 | WATCHER_EMAIL_PASSWORD= | Assignment statement storing or updating program state.
L0044 | WATCHER_EMAIL_TO= | Assignment statement storing or updating program state.
```

File 3: .env.example

[illegible]

L0054 | WATCHER_EMAIL_PASSWORD= | Assignment statement storing or updating program state.

L0055 | WATCHER_EMAIL_TO= | Assignment statement storing or updating program state.

File 4: .flake8

```
L0001 | [flake8] | Operational statement participating in the file's runtime behavior.
L0002 | # Maximum line length – set to 200 to tolerate pre-existing long import lines. | Comment line documenting intent or context for nearby code.
L0003 | # New code should target ≤ 120 chars. | Comment line documenting intent or context for nearby code.
L0004 | max-line-length = 200 | Assignment statement storing or updating program state.
L0005 | | Blank line used for readability and logical separation.
L0006 | # Paths excluded from linting (generated code, migrations, venvs, cache). | Comment line documenting intent or context for nearby code.
L0007 | exclude = | Assignment statement storing or updating program state.
L0008 | .venv, | CSS selector line choosing the elements styled below.
L0009 | venv, | Operational statement participating in the file's runtime behavior.
L0010 | migrations, | Operational statement participating in the file's runtime behavior.
L0011 | __pycache__, | Operational statement participating in the file's runtime behavior.
L0012 | .git, | CSS selector line choosing the elements styled below.
L0013 | instance, | Operational statement participating in the file's runtime behavior.
L0014 | tinious, | Operational statement participating in the file's runtime behavior.
L0015 | uploads, | Operational statement participating in the file's runtime behavior.
L0016 | photo, | Operational statement participating in the file's runtime behavior.
L0017 | static, | Operational statement participating in the file's runtime behavior.
L0018 | templates | Operational statement participating in the file's runtime behavior.
L0019 | | Blank line used for readability and logical separation.
L0020 | # Directories/files to lint – only first-party code. | Comment line documenting intent or context for nearby code.
L0021 | # Run: python -m flake8 | Comment line documenting intent or context for nearby code.
L0022 | filename = *.py | Assignment statement storing or updating program state.
L0023 | | Blank line used for readability and logical separation.
L0024 | # Ignore codes that are style preferences rather than correctness issues. | Comment line documenting intent or context for nearby code.
L0025 | # E501: line-too-long (handled by max-line-length above) | Comment line documenting intent or context for nearby code.
L0026 | # W503: line break before binary operator (conflicts with Black/PEP 8 update) | Comment line documenting intent or context for nearby code.
L0027 | # E203: whitespace before ':' (conflicts with slice formatting) | Comment line documenting intent or context for nearby code.
L0028 | # E241: multiple spaces after ',' (used intentionally for column alignment) | Comment line documenting intent or context for nearby code.
L0029 | # E302/E303/E305: blank-line counts in large single-file apps | Comment line documenting intent or context for nearby code.
L0030 | # E306: blank-line before nested def (style only) | Comment line documenting intent or context for nearby code.
L0031 | ignore = W503, E203, E241, E302, E303, E305, E306 | Assignment statement storing or updating program state.
L0032 | | Blank line used for readability and logical separation.
L0033 | # Complexity gate: fail if cyclomatic complexity exceeds 20. | Comment line documenting intent or context for nearby code.
L0034 | max-complexity = 20 | Assignment statement storing or updating program state.
L0035 | | Blank line used for readability and logical separation.
L0036 | # Count total errors and show statistics summary. | Comment line documenting intent or context for nearby code.
L0037 | count = True | Assignment statement storing or updating program state.
L0038 | statistics = True | Assignment statement storing or updating program state.
```

File 5: .vscode/settings.json

L0001 | {} | Block delimiter controlling scope/structure in this language.

File 6: .vscode/tasks.json

```
L0001 | { | Block delimiter controlling scope/structure in this language.
L0002 |   "version": "2.0.0", | Operational statement participating in the file's runtime behavior.
L0003 |   "tasks": [ | Operational statement participating in the file's runtime behavior.
L0004 |     { | Block delimiter controlling scope/structure in this language.
L0005 |       "label": "probe-write-file", | Operational statement participating in the file's runtime behavior.
L0006 |       "type": "shell", | Operational statement participating in the file's runtime behavior.
L0007 |       "command": "cmd", | Operational statement participating in the file's runtime behavior.
L0008 |       "args": [ | Operational statement participating in the file's runtime behavior.
L0009 |         "/c", | Operational statement participating in the file's runtime behavior.
L0010 |         "echo hello>out_probe_task.txt" | Operational statement participating in the file's runtime behavior.
L0011 |       ], | Operational statement participating in the file's runtime behavior.
L0012 |       "isBackground": false | Operational statement participating in the file's runtime behavior.
L0013 |     }, | Operational statement participating in the file's runtime behavior.
L0014 |   { | Block delimiter controlling scope/structure in this language.
L0015 |     "label": "check-postgres-service", | Operational statement participating in the file's runtime behavior.
L0016 |     "type": "shell", | Operational statement participating in the file's runtime behavior.
L0017 |     "command": "powershell", | Operational statement participating in the file's runtime behavior.
L0018 |     "args": [ | Operational statement participating in the file's runtime behavior.
L0019 |       "-NoProfile", | Operational statement participating in the file's runtime behavior.
L0020 |       "-Command", | Operational statement participating in the file's runtime behavior.
L0021 |       "Get-Service \\| Where-Object { $_.Name -match 'postgres' -or $_.DisplayName -match 'PostgreSQL' } \\| Select-Object Name,Status"
L0022 |     ], | Operational statement participating in the file's runtime behavior.
L0023 |     "isBackground": false | Operational statement participating in the file's runtime behavior.
L0024 |   }, | Operational statement participating in the file's runtime behavior.
L0025 |   { | Block delimiter controlling scope/structure in this language.
L0026 |     "label": "check-psql-path", | Operational statement participating in the file's runtime behavior.
L0027 |     "type": "shell", | Operational statement participating in the file's runtime behavior.
L0028 |     "command": "powershell", | Operational statement participating in the file's runtime behavior.
L0029 |     "args": [ | Operational statement participating in the file's runtime behavior.
L0030 |       "-NoProfile", | Operational statement participating in the file's runtime behavior.
L0031 |       "-Command", | Operational statement participating in the file's runtime behavior.
L0032 |       "$c=Get-Command psql -ErrorAction SilentlyContinue; if($c){$c.Source \\| Out-File -Encoding utf8 out_psql_path.txt}else{'PSQL_N'
L0033 |     ], | Operational statement participating in the file's runtime behavior.
L0034 |     "isBackground": false | Operational statement participating in the file's runtime behavior.
L0035 |   }, | Operational statement participating in the file's runtime behavior.
L0036 |   { | Block delimiter controlling scope/structure in this language.
L0037 |     "label": "scan-services-post", | Operational statement participating in the file's runtime behavior.
L0038 |     "type": "shell", | Operational statement participating in the file's runtime behavior.
L0039 |     "command": "powershell", | Operational statement participating in the file's runtime behavior.
L0040 |     "args": [ | Operational statement participating in the file's runtime behavior.
L0041 |       "-NoProfile", | Operational statement participating in the file's runtime behavior.
L0042 |       "-Command", | Operational statement participating in the file's runtime behavior.
L0043 |       "Get-Service \\| Where-Object { $_.Name -match 'post\\pg' -or $_.DisplayName -match 'Post\\SQL' } \\| Select-Object -First 60 Na
L0044 |     ], | Operational statement participating in the file's runtime behavior.
L0045 |     "isBackground": false | Operational statement participating in the file's runtime behavior.
L0046 |   }, | Operational statement participating in the file's runtime behavior.
L0047 |   { | Block delimiter controlling scope/structure in this language.
L0048 |     "label": "scan-programfiles-postgres", | Operational statement participating in the file's runtime behavior.
L0049 |     "type": "shell", | Operational statement participating in the file's runtime behavior.
L0050 |     "command": "powershell", | Operational statement participating in the file's runtime behavior.
L0051 |     "args": [ | Operational statement participating in the file's runtime behavior.
L0052 |       "-NoProfile", | Operational statement participating in the file's runtime behavior.
L0053 |       "-Command", | Operational statement participating in the file's runtime behavior.
```

L0054 | #####"\$paths=@('C:\\Program Files\\PostgreSQL','C:\\Program Files (x86)\\PostgreSQL'); \$found=@(); foreach(\$p in \$paths){ if(Test-Path \$p){
L0055 | #####}, | Operational statement participating in the file's runtime behavior.
L0056 | #####"isBackground": false | Operational statement participating in the file's runtime behavior.
L0057 | #####}, | Operational statement participating in the file's runtime behavior.
L0058 | #####{ | Block delimiter controlling scope/structure in this language.
L0059 | #####"label": "check-docker", | Operational statement participating in the file's runtime behavior.
L0060 | #####"type": "shell", | Operational statement participating in the file's runtime behavior.
L0061 | #####"command": "powershell", | Operational statement participating in the file's runtime behavior.
L0062 | #####"args": [| Operational statement participating in the file's runtime behavior.
L0063 | #####"-NoProfile", | Operational statement participating in the file's runtime behavior.
L0064 | #####"-Command", | Operational statement participating in the file's runtime behavior.
L0065 | #####"\$d=Get-Command docker -ErrorAction SilentlyContinue; if(\$d){'DOCKER_OK'|Out-File -Encoding utf8 out_docker.txt}else{'DOCKER_ERROR'|Out-File -Encoding utf8 out_docker.txt}
L0066 | #####}, | Operational statement participating in the file's runtime behavior.
L0067 | #####"isBackground": false | Operational statement participating in the file's runtime behavior.
L0068 | #####}, | Operational statement participating in the file's runtime behavior.
L0069 | #####{ | Block delimiter controlling scope/structure in this language.
L0070 | #####"label": "cleanup-probe-files", | Operational statement participating in the file's runtime behavior.
L0071 | #####"type": "shell", | Operational statement participating in the file's runtime behavior.
L0072 | #####"command": "powershell", | Operational statement participating in the file's runtime behavior.
L0073 | #####"args": [| Operational statement participating in the file's runtime behavior.
L0074 | #####"-NoProfile", | Operational statement participating in the file's runtime behavior.
L0075 | #####"-Command", | Operational statement participating in the file's runtime behavior.
L0076 | #####"Remove-Item -ErrorAction SilentlyContinue out_probe_task.txt,out_service.json,out_psql_path.txt,out_services_scan.json,out_pg_dump.txt
L0077 | #####}, | Operational statement participating in the file's runtime behavior.
L0078 | #####"isBackground": false | Operational statement participating in the file's runtime behavior.
L0079 | #####}, | Operational statement participating in the file's runtime behavior.
L0080 | #####{ | Block delimiter controlling scope/structure in this language.
L0081 | #####"label": "find-sqlite-refs", | Operational statement participating in the file's runtime behavior.
L0082 | #####"type": "shell", | Operational statement participating in the file's runtime behavior.
L0083 | #####"command": "cmd", | Operational statement participating in the file's runtime behavior.
L0084 | #####"args": [| Operational statement participating in the file's runtime behavior.
L0085 | #####"/c", | Operational statement participating in the file's runtime behavior.
L0086 | #####"rg -n -i sqlite . > sqlite_refs.txt" | Operational statement participating in the file's runtime behavior.
L0087 | #####}, | Operational statement participating in the file's runtime behavior.
L0088 | #####"isBackground": false | Operational statement participating in the file's runtime behavior.
L0089 | #####}, | Operational statement participating in the file's runtime behavior.
L0090 | #####{ | Block delimiter controlling scope/structure in this language.
L0091 | #####"label": "find-sqlite-refs-ps", | Operational statement participating in the file's runtime behavior.
L0092 | #####"type": "shell", | Operational statement participating in the file's runtime behavior.
L0093 | #####"command": "powershell", | Operational statement participating in the file's runtime behavior.
L0094 | #####"args": [| Operational statement participating in the file's runtime behavior.
L0095 | #####"-NoProfile", | Operational statement participating in the file's runtime behavior.
L0096 | #####"-Command", | Operational statement participating in the file's runtime behavior.
L0097 | #####"\$patterns='sqlite','SQLite'; \$exts='*.py','*.md','*.txt','*.yaml','*.yml','*.env','*.ini','*.cfg','*.html','*.css','*.js'; Get-ChildItem \$paths -Recurse -File -Filter (\$patterns -and (\$exts -or \$exts2)) |
L0098 | #####}, | Operational statement participating in the file's runtime behavior.
L0099 | #####"isBackground": false | Operational statement participating in the file's runtime behavior.
L0100 | #####}, | Operational statement participating in the file's runtime behavior.
L0101 | #####{ | Block delimiter controlling scope/structure in this language.
L0102 | #####"label": "find-sqlite-refs-ps2", | Operational statement participating in the file's runtime behavior.
L0103 | #####"type": "shell", | Operational statement participating in the file's runtime behavior.
L0104 | #####"command": "powershell", | Operational statement participating in the file's runtime behavior.
L0105 | #####"args": [| Operational statement participating in the file's runtime behavior.
L0106 | #####"-NoProfile", | Operational statement participating in the file's runtime behavior.
L0107 | #####"-Command", | Operational statement participating in the file's runtime behavior.
L0108 | #####"\$exts='*.py','*.md','*.txt','*.yaml','*.yml','*.env','*.ini','*.cfg','*.html','*.css','*.js'; Get-ChildItem -Recurse -File -Filter (\$patterns -and (\$exts -or \$exts2)) |</p></div>

L0109 | `]`, | Operational statement participating in the file's runtime behavior.

L0110 | `"isBackground": false` | Operational statement participating in the file's runtime behavior.

L0111 | `}`, | Operational statement participating in the file's runtime behavior.

L0112 | `{` | Block delimiter controlling scope/structure in this language.

L0113 | `"label": "remove-sqlite-migration-script"`, | Operational statement participating in the file's runtime behavior.

L0114 | `"type": "shell"`, | Operational statement participating in the file's runtime behavior.

L0115 | `"command": "powershell"`, | Operational statement participating in the file's runtime behavior.

L0116 | `"args": [` | Operational statement participating in the file's runtime behavior.

L0117 | `"-NoProfile"`, | Operational statement participating in the file's runtime behavior.

L0118 | `"-Command"`, | Operational statement participating in the file's runtime behavior.

L0119 | `"Remove-Item -Force scripts\migrate_sqlite_to_postgres.py"` | Operational statement participating in the file's runtime behavior.

L0120 | `]`, | Operational statement participating in the file's runtime behavior.

L0121 | `"isBackground": false` | Operational statement participating in the file's runtime behavior.

L0122 | `}`, | Operational statement participating in the file's runtime behavior.

L0123 | `{` | Block delimiter controlling scope/structure in this language.

L0124 | `"label": "staging-gate-security"`, | Operational statement participating in the file's runtime behavior.

L0125 | `"type": "shell"`, | Operational statement participating in the file's runtime behavior.

L0126 | `"command": "c:/Users/jonas/OneDrive/Desktop/pm/.venv/Scripts/python.exe"`, | Operational statement participating in the file's runtime behavior.

L0127 | `"args": [` | Operational statement participating in the file's runtime behavior.

L0128 | `"-m"`, | Operational statement participating in the file's runtime behavior.

L0129 | `"pytest"`, | Operational statement participating in the file's runtime behavior.

L0130 | `"tests/test_security.py"`, | Operational statement participating in the file's runtime behavior.

L0131 | `"-q"` | Operational statement participating in the file's runtime behavior.

L0132 | `]`, | Operational statement participating in the file's runtime behavior.

L0133 | `"isBackground": false` | Operational statement participating in the file's runtime behavior.

L0134 | `}` | Block delimiter controlling scope/structure in this language.

L0135 | `]` | Operational statement participating in the file's runtime behavior.

L0136 | `}` | Block delimiter controlling scope/structure in this language.

File 7: `_startup_probe.py`

L0001 | `from app import create_app` | Imports specific names from another module for direct usage.

L0002 | | Blank line used for readability and logical separation.

L0003 | `app = create_app()` | Assignment statement storing or updating program state.

L0004 | `print("create_app_ok")` | Operational statement participating in the file's runtime behavior.

L0005 | `print(len(list(app.url_map.iter_rules())))` | Operational statement participating in the file's runtime behavior.

File 8: advanced_watchdog_script.py

```
L0001 | import csv | Imports dependency modules: csv.
L0002 | import difflib | Imports dependency modules: difflib.
L0003 | import os | Imports dependency modules: os.
L0004 | import smtplib | Imports dependency modules: smtplib.
L0005 | import threading | Imports dependency modules: threading.
L0006 | import time | Imports dependency modules: time.
L0007 | from datetime import datetime | Imports specific names from another module for direct usage.
L0008 | from email.mime.multipart import MIMEMultipart | Imports specific names from another module for direct usage.
L0009 | from email.mime.text import MIMEText | Imports specific names from another module for direct usage.
L0010 | from html import escape | Imports specific names from another module for direct usage.
L0011 | from pathlib import Path | Imports specific names from another module for direct usage.
L0012 | | Blank line used for readability and logical separation.
L0013 | from watchdog.events import FileSystemEventHandler | Imports specific names from another module for direct usage.
L0014 | from watchdog.observers import Observer | Imports specific names from another module for direct usage.
L0015 | | Blank line used for readability and logical separation.
L0016 | | Blank line used for readability and logical separation.
L0017 | BASE_DIR = Path(__file__).resolve().parent | Assignment statement storing or updating program state.
L0018 | WATCH_DIR = Path(os.getenv("WATCH_DIR", str(BASE_DIR))).resolve() | Assignment statement storing or updating program state.
L0019 | REPORT_INTERVAL = int(os.getenv("REPORT_INTERVAL_SECONDS", "1800")) # 30 minutes | Assignment statement storing or updating program state.
L0020 | CSV_BACKUP_PATH = Path(os.getenv("CHANGE_LOG_CSV", str(BASE_DIR / "change_log_backup.csv")))) | Assignment statement storing or updating program state.
L0021 | ERROR_LOG_PATH = Path(os.getenv("WATCHDOG_ERROR_LOG", str(BASE_DIR / "watchdog_reporter_errors.log")))) | Assignment statement storing or updating program state.
L0022 | MAX_FILE_SIZE_BYTES = int(os.getenv("MAX_FILE_SIZE_BYTES", str(2 * 1024 * 1024))) | Assignment statement storing or updating program state.
L0023 | MAX_DIFF_LINES_PER_FILE = int(os.getenv("MAX_DIFF_LINES_PER_FILE", "0")) | Assignment statement storing or updating program state.
L0024 | | Blank line used for readability and logical separation.
L0025 | # Keep monitoring focused on code and config files. | Comment line documenting intent or context for nearby code.
L0026 | INCLUDE_EXTENSIONS = { | Assignment statement storing or updating program state.
L0027 |     ".py", | Operational statement participating in the file's runtime behavior.
L0028 |     ".html", | Operational statement participating in the file's runtime behavior.
L0029 |     ".css", | Operational statement participating in the file's runtime behavior.
L0030 |     ".js", | Operational statement participating in the file's runtime behavior.
L0031 |     ".json", | Operational statement participating in the file's runtime behavior.
L0032 |     ".md", | Operational statement participating in the file's runtime behavior.
L0033 |     ".txt", | Operational statement participating in the file's runtime behavior.
L0034 |     ".ini", | Operational statement participating in the file's runtime behavior.
L0035 |     ".yaml", | Operational statement participating in the file's runtime behavior.
L0036 |     ".yml", | Operational statement participating in the file's runtime behavior.
L0037 |     ".toml", | Operational statement participating in the file's runtime behavior.
L0038 |     ".sql", | Operational statement participating in the file's runtime behavior.
L0039 |     ".env", | Operational statement participating in the file's runtime behavior.
L0040 | } | Block delimiter controlling scope/structure in this language.
L0041 | | Blank line used for readability and logical separation.
L0042 | IGNORE_DIR_NAMES = { | Assignment statement storing or updating program state.
L0043 |     ".venv", | Operational statement participating in the file's runtime behavior.
L0044 |     "venv", | Operational statement participating in the file's runtime behavior.
L0045 |     "__pycache__", | Operational statement participating in the file's runtime behavior.
L0046 |     ".git", | Operational statement participating in the file's runtime behavior.
L0047 |     "node_modules", | Operational statement participating in the file's runtime behavior.
L0048 | } | Block delimiter controlling scope/structure in this language.
L0049 | | Blank line used for readability and logical separation.
L0050 | | Blank line used for readability and logical separation.
L0051 | def _default_email_settings(): | Declares a function/method as a reusable unit of behavior.
L0052 |     # Reuse existing alert settings as a fallback if env vars are not set. | Comment line documenting intent or context for nearby code.
L0053 |     try: | Starts an exception handling block for risky operations.
```



```

L0054 |         from alert_system import EMAIL_ADDRESS, EMAIL_PASSWORD | Imports specific names from another module for direct usage.
L0055 | | Blank line used for readability and logical separation.
L0056 |         default_from = EMAIL_ADDRESS | Assignment statement storing or updating program state.
L0057 |         default_password = EMAIL_PASSWORD | Assignment statement storing or updating program state.
L0058 |     except Exception: | Handles errors raised in the associated try block.
L0059 |         default_from = "" | Assignment statement storing or updating program state.
L0060 |         default_password = "" | Assignment statement storing or updating program state.
L0061 | | Blank line used for readability and logical separation.
L0062 |     email_from = os.getenv("WATCHER_EMAIL_FROM", default_from) | Assignment statement storing or updating program state.
L0063 |     email_password = os.getenv("WATCHER_EMAIL_PASSWORD", default_password) | Assignment statement storing or updating program state.
L0064 |     email_to = os.getenv("WATCHER_EMAIL_TO", email_from) | Assignment statement storing or updating program state.
L0065 |     return email_from, email_password, email_to | Returns a value (or control) back to the caller.
L0066 | | Blank line used for readability and logical separation.
L0067 | | Blank line used for readability and logical separation.
L0068 | EMAIL_FROM, EMAIL_PASSWORD, EMAIL_TO = _default_email_settings() | Assignment statement storing or updating program state.
L0069 | | Blank line used for readability and logical separation.
L0070 | | Blank line used for readability and logical separation.
L0071 | def _log_error(message: str) -> None: | Declares a function/method as a reusable unit of behavior.
L0072 |     ts = datetime.now().strftime("%Y-%m-%d %H:%M:%S") | Assignment statement storing or updating program state.
L0073 |     ERROR_LOG_PATH.parent.mkdir(parents=True, exist_ok=True) | Assignment statement storing or updating program state.
L0074 |     with ERROR_LOG_PATH.open("a", encoding="utf-8") as handle: | Context manager block for safe setup and automatic cleanup.
L0075 |         handle.write(f"[{ts}] {message}\n") | Operational statement participating in the file's runtime behavior.
L0076 | | Blank line used for readability and logical separation.
L0077 | | Blank line used for readability and logical separation.
L0078 | def _is_ignored(path: Path) -> bool: | Declares a function/method as a reusable unit of behavior.
L0079 |     parts = set(path.parts) | Assignment statement storing or updating program state.
L0080 |     if parts.intersection(IGNORE_DIR_NAMES): | Conditional branch that runs only when its condition is true.
L0081 |         return True | Returns a value (or control) back to the caller.
L0082 |     if path.suffix.lower() not in INCLUDE_EXTENSIONS: | Conditional branch that runs only when its condition is true.
L0083 |         return True | Returns a value (or control) back to the caller.
L0084 |     return False | Returns a value (or control) back to the caller.
L0085 | | Blank line used for readability and logical separation.
L0086 | | Blank line used for readability and logical separation.
L0087 | def _read_text_lines(path: Path): | Declares a function/method as a reusable unit of behavior.
L0088 |     try: | Starts an exception handling block for risky operations.
L0089 |         if not path.exists() or path.is_dir(): | Conditional branch that runs only when its condition is true.
L0090 |             return [] | Returns a value (or control) back to the caller.
L0091 |         if path.stat().st_size > MAX_FILE_SIZE_BYTES: | Conditional branch that runs only when its condition is true.
L0092 |             return [f"<skipped: file too large ({path.stat().st_size} bytes)>\n"] | Returns a value (or control) back to the caller.
L0093 |             return path.read_text(encoding="utf-8", errors="ignore").splitlines(keepends=True) | Returns a value (or control) back to the caller.
L0094 |     except Exception as exc: | Handles errors raised in the associated try block.
L0095 |         _log_error(f"read failed for {path}: {exc}") | Operational statement participating in the file's runtime behavior.
L0096 |         return [f"<skipped: read error>\n"] | Returns a value (or control) back to the caller.
L0097 | | Blank line used for readability and logical separation.
L0098 | | Blank line used for readability and logical separation.
L0099 | class BatchDiffWatcher(FileSystemEventHandler): | Declares a class that groups related state and behavior.
L0100 |     def __init__(self): | Declares a function/method as a reusable unit of behavior.
L0101 |         self._lock = threading.Lock() | Assignment statement storing or updating program state.
L0102 |         self._snapshots = {} | Assignment statement storing or updating program state.
L0103 |         self._changes = [] | Assignment statement storing or updating program state.
L0104 |         self._initialize_snapshots() | Operational statement participating in the file's runtime behavior.
L0105 | | Blank line used for readability and logical separation.
L0106 |     def _initialize_snapshots(self): | Declares a function/method as a reusable unit of behavior.
L0107 |         for root, dirs, files in os.walk(WATCH_DIR): | Loop iterating over a sequence to process elements one by one.
L0108 |             dirs[:] = [d for d in dirs if d not in IGNORE_DIR_NAMES] | Assignment statement storing or updating program state.

```

```

L0109 |         for name in files: | Loop iterating over a sequence to process elements one by one.
L0110 |             path = Path(root) / name | Assignment statement storing or updating program state.
L0111 |             if _is_ignored(path): | Conditional branch that runs only when its condition is true.
L0112 |                 continue | Flow-control keyword affecting execution in the current block.
L0113 |             self._snapshots[str(path)] = _read_text_lines(path) | Assignment statement storing or updating program state.
L0114 | | Blank line used for readability and logical separation.
L0115 |     def _record_change(self, path: Path, event_type: str): | Declares a function/method as a reusable unit of behavior.
L0116 |         path = path.resolve() | Assignment statement storing or updating program state.
L0117 |         if _is_ignored(path): | Conditional branch that runs only when its condition is true.
L0118 |             return | Returns a value (or control) back to the caller.
L0119 | | Blank line used for readability and logical separation.
L0120 |         path_key = str(path) | Assignment statement storing or updating program state.
L0121 |         with self._lock: | Context manager block for safe setup and automatic cleanup.
L0122 |             before_lines = self._snapshots.get(path_key, []) | Assignment statement storing or updating program state.
L0123 |             after_lines = _read_text_lines(path) if path.exists() else [] | Assignment statement storing or updating program state.
L0124 | | Blank line used for readability and logical separation.
L0125 |             if event_type == "modified" and before_lines == after_lines: | Conditional branch that runs only when its condition is true.
L0126 |                 return | Returns a value (or control) back to the caller.
L0127 | | Blank line used for readability and logical separation.
L0128 |             self._changes.append( | Operational statement participating in the file's runtime behavior.
L0129 |                 { | Block delimiter controlling scope/structure in this language.
L0130 |                     "time": datetime.now().strftime("%Y-%m-%d %H:%M:%S"), | Operational statement participating in the file's runtime behavior.
L0131 |                     "file": path_key, | Operational statement participating in the file's runtime behavior.
L0132 |                     "event": event_type, | Operational statement participating in the file's runtime behavior.
L0133 |                     "before": before_lines, | Operational statement participating in the file's runtime behavior.
L0134 |                     "after": after_lines, | Operational statement participating in the file's runtime behavior.
L0135 |                     "before_loc": len(before_lines), | Operational statement participating in the file's runtime behavior.
L0136 |                     "after_loc": len(after_lines), | Operational statement participating in the file's runtime behavior.
L0137 |                 } | Block delimiter controlling scope/structure in this language.
L0138 |             ) | Operational statement participating in the file's runtime behavior.
L0139 | | Blank line used for readability and logical separation.
L0140 |             if path.exists() and event_type != "deleted": | Conditional branch that runs only when its condition is true.
L0141 |                 self._snapshots[path_key] = after_lines | Assignment statement storing or updating program state.
L0142 |             else: | Fallback branch executed when prior conditions are false.
L0143 |                 self._snapshots.pop(path_key, None) | Operational statement participating in the file's runtime behavior.
L0144 | | Blank line used for readability and logical separation.
L0145 |     def on_modified(self, event): | Declares a function/method as a reusable unit of behavior.
L0146 |         if not event.is_directory: | Conditional branch that runs only when its condition is true.
L0147 |             self._record_change(Path(event.src_path), "modified") | Operational statement participating in the file's runtime behavior.
L0148 | | Blank line used for readability and logical separation.
L0149 |     def on_created(self, event): | Declares a function/method as a reusable unit of behavior.
L0150 |         if not event.is_directory: | Conditional branch that runs only when its condition is true.
L0151 |             self._record_change(Path(event.src_path), "created") | Operational statement participating in the file's runtime behavior.
L0152 | | Blank line used for readability and logical separation.
L0153 |     def on_deleted(self, event): | Declares a function/method as a reusable unit of behavior.
L0154 |         if not event.is_directory: | Conditional branch that runs only when its condition is true.
L0155 |             self._record_change(Path(event.src_path), "deleted") | Operational statement participating in the file's runtime behavior.
L0156 | | Blank line used for readability and logical separation.
L0157 |     def on_moved(self, event): | Declares a function/method as a reusable unit of behavior.
L0158 |         if event.is_directory: | Conditional branch that runs only when its condition is true.
L0159 |             return | Returns a value (or control) back to the caller.
L0160 |             self._record_change(Path(event.src_path), "moved_from") | Operational statement participating in the file's runtime behavior.
L0161 |             self._record_change(Path(event.dest_path), "moved_to") | Operational statement participating in the file's runtime behavior.
L0162 | | Blank line used for readability and logical separation.
L0163 |     def flush_changes(self): | Declares a function/method as a reusable unit of behavior.

```

```

L0164 |         with self._lock: | Context manager block for safe setup and automatic cleanup.
L0165 |             pending = self._changes | Assignment statement storing or updating program state.
L0166 |             self._changes = [] | Assignment statement storing or updating program state.
L0167 |         return pending | Returns a value (or control) back to the caller.
L0168 | | Blank line used for readability and logical separation.
L0169 | | Blank line used for readability and logical separation.
L0170 | def _build_html_report(changes): | Declares a function/method as a reusable unit of behavior.
L0171 |     event_counts = {} | Assignment statement storing or updating program state.
L0172 |     files_changed = set() | Assignment statement storing or updating program state.
L0173 |     total_before = 0 | Assignment statement storing or updating program state.
L0174 |     total_after = 0 | Assignment statement storing or updating program state.
L0175 |     for change in changes: | Loop iterating over a sequence to process elements one by one.
L0176 |         event_counts[change["event"]] = event_counts.get(change["event"], 0) + 1 | Assignment statement storing or updating program state.
L0177 |         files_changed.add(change["file"]) | Operational statement participating in the file's runtime behavior.
L0178 |         total_before += change["before_loc"] | Assignment statement storing or updating program state.
L0179 |         total_after += change["after_loc"] | Assignment statement storing or updating program state.
L0180 | | Blank line used for readability and logical separation.
L0181 |     event_summary_html = "".join( | Assignment statement storing or updating program state.
L0182 |         [f"<li><b>{escape(event)}:</b> {count}</li>" for event, count in sorted(event_counts.items())] | Operational statement participating in the file's runtime behavior.
L0183 |     ) | Operational statement participating in the file's runtime behavior.
L0184 | | Blank line used for readability and logical separation.
L0185 |     report_parts = [ | Assignment statement storing or updating program state.
L0186 |         "<h2>Project Change Report</h2>", | Operational statement participating in the file's runtime behavior.
L0187 |         f"<p><b>Window:</b> last {REPORT_INTERVAL // 60} minute(s)</p>", | Operational statement participating in the file's runtime behavior.
L0188 |         f"<p><b>Total events:</b> {len(changes)}</p>", | Operational statement participating in the file's runtime behavior.
L0189 |         "<h3>System Behavior Summary</h3>", | Operational statement participating in the file's runtime behavior.
L0190 |         f"<p><b>Monitor status:</b> Active</p>", | Operational statement participating in the file's runtime behavior.
L0191 |         f"<p><b>Monitored folder:</b> {escape(str(WATCH_DIR))}</p>", | Operational statement participating in the file's runtime behavior.
L0192 |         f"<p><b>Unique files changed:</b> {len(files_changed)}</p>", | Operational statement participating in the file's runtime behavior.
L0193 |         f"<p><b>Total LOC delta in window:</b> {total_before} -> {total_after}</p>", | Operational statement participating in the file's runtime behavior.
L0194 |         f"<p><b>Ignored folders:</b> {escape(', '.join(sorted(IGNORE_DIR_NAMES)))}</p>", | Operational statement participating in the file's runtime behavior.
L0195 |         f"<p><b>Included extensions:</b> {escape(', '.join(sorted(INCLUDE_EXTENSIONS)))}</p>", | Operational statement participating in the file's runtime behavior.
L0196 |         f"<ul>{event_summary_html}</ul>", | Operational statement participating in the file's runtime behavior.
L0197 |     ] | Operational statement participating in the file's runtime behavior.
L0198 | | Blank line used for readability and logical separation.
L0199 |     for change in changes: | Loop iterating over a sequence to process elements one by one.
L0200 |         before = change["before"] | Assignment statement storing or updating program state.
L0201 |         after = change["after"] | Assignment statement storing or updating program state.
L0202 |         diff_lines = list( | Assignment statement storing or updating program state.
L0203 |             difflib.unified_diff( | Operational statement participating in the file's runtime behavior.
L0204 |                 before, | Operational statement participating in the file's runtime behavior.
L0205 |                 after, | Operational statement participating in the file's runtime behavior.
L0206 |                 fromfile="before", | Assignment statement storing or updating program state.
L0207 |                 tofile="after", | Assignment statement storing or updating program state.
L0208 |                 n=3, | Assignment statement storing or updating program state.
L0209 |                 lineterm="", | Assignment statement storing or updating program state.
L0210 |             ) | Operational statement participating in the file's runtime behavior.
L0211 |         ) | Operational statement participating in the file's runtime behavior.
L0212 |         if MAX_DIFF_LINES_PER_FILE > 0 and len(diff_lines) > MAX_DIFF_LINES_PER_FILE: | Conditional branch that runs only when its condition is true.
L0213 |             diff_lines = diff_lines[:MAX_DIFF_LINES_PER_FILE] + [ | Assignment statement storing or updating program state.
L0214 |                 f"... diff truncated at {MAX_DIFF_LINES_PER_FILE} lines ..." | Operational statement participating in the file's runtime behavior.
L0215 |             ] | Operational statement participating in the file's runtime behavior.
L0216 | | Blank line used for readability and logical separation.
L0217 |         diff_text = escape("\n".join(diff_lines) or "<no textual diff available>") | Assignment statement storing or updating program state.
L0218 |         before_text = escape("\n".join(before) or "<empty>") | Assignment statement storing or updating program state.

```

```

L0219 |         after_text = escape('".join(after) or "<empty>") | Assignment statement storing or updating program state.
L0220 |         report_parts.append( | Operational statement participating in the file's runtime behavior.
L0221 |             "".join( | Operational statement participating in the file's runtime behavior.
L0222 |                 [ | Operational statement participating in the file's runtime behavior.
L0223 |                     f"<h3>{escape(change['file'])}</h3>", | Operational statement participating in the file's runtime behavior.
L0224 |                     f"<p><b>Time:</b> {escape(change['time'])} &nbsp; " | Operational statement participating in the file's runtime behavior.
L0225 |                     f"<b>Event:</b> {escape(change['event'])} &nbsp; " | Operational statement participating in the file's runtime behavior.
L0226 |                     f"<b>LOC:</b> {change['before_loc']} → {change['after_loc']}</p>", | Operational statement participating in the file's runtime behavior.
L0227 |                     "<h4>Before Code</h4>", | Operational statement participating in the file's runtime behavior.
L0228 |                     f"<pre style='background:#fff8dc;border:1px solid #ddd;padding:10px;white-space:pre-wrap'>{before_text}</pre>",
L0229 |                     "<h4>After Code</h4>", | Operational statement participating in the file's runtime behavior.
L0230 |                     f"<pre style='background:#f0fff4;border:1px solid #ddd;padding:10px;white-space:pre-wrap'>{after_text}</pre>",
L0231 |                     "<h4>Unified Diff</h4>", | Operational statement participating in the file's runtime behavior.
L0232 |                     f"<pre style='background:#f6f8fa;border:1px solid #ddd;padding:10px;white-space:pre-wrap'>{diff_text}</pre>",
L0233 |                 ] | Operational statement participating in the file's runtime behavior.
L0234 |             ) | Operational statement participating in the file's runtime behavior.
L0235 |         ) | Operational statement participating in the file's runtime behavior.
L0236 | | Blank line used for readability and logical separation.
L0237 |     return "".join(report_parts) | Returns a value (or control) back to the caller.
L0238 | | Blank line used for readability and logical separation.
L0239 | | Blank line used for readability and logical separation.
L0240 | def _save_csv_backup(changes): | Declares a function/method as a reusable unit of behavior.
L0241 |     CSV_BACKUP_PATH.parent.mkdir(parents=True, exist_ok=True) | Assignment statement storing or updating program state.
L0242 |     is_new = not CSV_BACKUP_PATH.exists() | Assignment statement storing or updating program state.
L0243 |     with CSV_BACKUP_PATH.open("a", newline="", encoding="utf-8") as csvfile: | Context manager block for safe setup and automatic cleanup.
L0244 |         writer = csv.writer(csvfile) | Assignment statement storing or updating program state.
L0245 |         if is_new: | Conditional branch that runs only when its condition is true.
L0246 |             writer.writerow(["time", "file", "event", "before_loc", "after_loc"]) | Operational statement participating in the file's runtime behavior.
L0247 |         for change in changes: | Loop iterating over a sequence to process elements one by one.
L0248 |             writer.writerow( | Operational statement participating in the file's runtime behavior.
L0249 |                 [ | Operational statement participating in the file's runtime behavior.
L0250 |                     change["time"], | Operational statement participating in the file's runtime behavior.
L0251 |                     change["file"], | Operational statement participating in the file's runtime behavior.
L0252 |                     change["event"], | Operational statement participating in the file's runtime behavior.
L0253 |                     change["before_loc"], | Operational statement participating in the file's runtime behavior.
L0254 |                     change["after_loc"], | Operational statement participating in the file's runtime behavior.
L0255 |                 ] | Operational statement participating in the file's runtime behavior.
L0256 |             ) | Operational statement participating in the file's runtime behavior.
L0257 | | Blank line used for readability and logical separation.
L0258 | | Blank line used for readability and logical separation.
L0259 | def _send_email(html_body: str): | Declares a function/method as a reusable unit of behavior.
L0260 |     if not EMAIL_FROM or not EMAIL_PASSWORD or not EMAIL_TO: | Conditional branch that runs only when its condition is true.
L0261 |         _log_error("email skipped: configure WATCHER_EMAIL_FROM/WATCHER_EMAIL_PASSWORD/WATCHER_EMAIL_TO") | Operational statement participating in the file's runtime behavior.
L0262 |     return | Returns a value (or control) back to the caller.
L0263 | | Blank line used for readability and logical separation.
L0264 |     msg = MIMEMultipart() | Assignment statement storing or updating program state.
L0265 |     msg["From"] = EMAIL_FROM | Assignment statement storing or updating program state.
L0266 |     msg["To"] = EMAIL_TO | Assignment statement storing or updating program state.
L0267 |     msg["Subject"] = f"Batch Code Change Report - {datetime.now().strftime('%Y-%m-%d %H:%M:%S')}" | Assignment statement storing or updating program state.
L0268 |     msg.attach(MIMEText(html_body, "html", "utf-8")) | Operational statement participating in the file's runtime behavior.
L0269 | | Blank line used for readability and logical separation.
L0270 |     with smtplib.SMTP_SSL("smtp.gmail.com", 465) as server: | Context manager block for safe setup and automatic cleanup.
L0271 |         server.login(EMAIL_FROM, EMAIL_PASSWORD) | Operational statement participating in the file's runtime behavior.
L0272 |         server.send_message(msg) | Operational statement participating in the file's runtime behavior.
L0273 | | Blank line used for readability and logical separation.

```

L0274 | | Blank line used for readability and logical separation.

L0275 | def _reporter_loop(watcher: BatchDiffWatcher): | Declares a function/method as a reusable unit of behavior.

L0276 | while True: | Loop that repeats while its condition remains true.

L0277 | time.sleep(REPORT_INTERVAL) | Operational statement participating in the file's runtime behavior.

L0278 | changes = watcher.flush_changes() | Assignment statement storing or updating program state.

L0279 | if not changes: | Conditional branch that runs only when its condition is true.

L0280 | continue | Flow-control keyword affecting execution in the current block.

L0281 | try: | Starts an exception handling block for risky operations.

L0282 | html_body = _build_html_report(changes) | Assignment statement storing or updating program state.

L0283 | _send_email(html_body) | Operational statement participating in the file's runtime behavior.

L0284 | _save_csv_backup(changes) | Operational statement participating in the file's runtime behavior.

L0285 | except Exception as exc: | Handles errors raised in the associated try block.

L0286 | _log_error(f"report send failed: {exc}") | Operational statement participating in the file's runtime behavior.

L0287 | | Blank line used for readability and logical separation.

L0288 | | Blank line used for readability and logical separation.

L0289 | def main(): | Declares a function/method as a reusable unit of behavior.

L0290 | watcher = BatchDiffWatcher() | Assignment statement storing or updating program state.

L0291 | observer = Observer() | Assignment statement storing or updating program state.

L0292 | observer.schedule(watcher, str(WATCH_DIR), recursive=True) | Assignment statement storing or updating program state.

L0293 | observer.start() | Operational statement participating in the file's runtime behavior.

L0294 | | Blank line used for readability and logical separation.

L0295 | reporter = threading.Thread(target=_reporter_loop, args=(watcher,), daemon=True) | Assignment statement storing or updating program state.

L0296 | reporter.start() | Operational statement participating in the file's runtime behavior.

L0297 | | Blank line used for readability and logical separation.

L0298 | try: | Starts an exception handling block for risky operations.

L0299 | while True: | Loop that repeats while its condition remains true.

L0300 | time.sleep(1) | Operational statement participating in the file's runtime behavior.

L0301 | except KeyboardInterrupt: | Handles errors raised in the associated try block.

L0302 | observer.stop() | Operational statement participating in the file's runtime behavior.

L0303 | observer.join() | Operational statement participating in the file's runtime behavior.

L0304 | | Blank line used for readability and logical separation.

L0305 | | Blank line used for readability and logical separation.

L0306 | if __name__ == "__main__": | Conditional branch that runs only when its condition is true.

L0307 | main() | Operational statement participating in the file's runtime behavior.

File 9: alert_system.py

```
L0001 | import os | Imports dependency modules: os.
L0002 | import smtplib | Imports dependency modules: smtplib.
L0003 | from email.mime.text import MIMEText | Imports specific names from another module for direct usage.
L0004 | from dotenv import load_dotenv | Imports specific names from another module for direct usage.
L0005 | | Blank line used for readability and logical separation.
L0006 | load_dotenv() | Operational statement participating in the file's runtime behavior.
L0007 | | Blank line used for readability and logical separation.
L0008 | EMAIL_ADDRESS = os.getenv("ALERT_EMAIL_ADDRESS", "") | Assignment statement storing or updating program state.
L0009 | EMAIL_PASSWORD = os.getenv("ALERT_EMAIL_PASSWORD", "") | Assignment statement storing or updating program state.
L0010 | | Blank line used for readability and logical separation.
L0011 | def send_alert(message, subject="System Alert"): | Declares a function/method as a reusable unit of behavior.
L0012 |     """ | Docstring boundary used to describe a module, class, or function.
L0013 |     Sends an email to the developer with the given message. | Operational statement participating in the file's runtime behavior.
L0014 |     """ | Docstring boundary used to describe a module, class, or function.
L0015 |     if not EMAIL_ADDRESS or not EMAIL_PASSWORD: | Conditional branch that runs only when its condition is true.
L0016 |         return False | Returns a value (or control) back to the caller.
L0017 | | Blank line used for readability and logical separation.
L0018 |     msg = MIMEText(message) | Assignment statement storing or updating program state.
L0019 |     msg["Subject"] = subject | Assignment statement storing or updating program state.
L0020 |     msg["From"] = EMAIL_ADDRESS | Assignment statement storing or updating program state.
L0021 |     msg["To"] = EMAIL_ADDRESS | Assignment statement storing or updating program state.
L0022 | | Blank line used for readability and logical separation.
L0023 |     try: | Starts an exception handling block for risky operations.
L0024 |         with smtplib.SMTP_SSL("smtp.gmail.com", 465) as server: | Context manager block for safe setup and automatic cleanup.
L0025 |             server.login(EMAIL_ADDRESS, EMAIL_PASSWORD) | Operational statement participating in the file's runtime behavior.
L0026 |             server.send_message(msg) | Operational statement participating in the file's runtime behavior.
L0027 |             return True | Returns a value (or control) back to the caller.
L0028 |     except Exception as e: | Handles errors raised in the associated try block.
L0029 |         print(f"Failed to send alert: {e}") | Operational statement participating in the file's runtime behavior.
L0030 |         return False | Returns a value (or control) back to the caller.
```

File 10: app.py

```
L0001 | import os | Imports dependency modules: os.
L0002 | import io | Imports dependency modules: io.
L0003 | import shutil | Imports dependency modules: shutil.
L0004 | import uuid | Imports dependency modules: uuid.
L0005 | import base64 | Imports dependency modules: base64.
L0006 | import secrets | Imports dependency modules: secrets.
L0007 | import hmac | Imports dependency modules: hmac.
L0008 | import click | Imports dependency modules: click.
L0009 | import logging | Imports dependency modules: logging.
L0010 | import re | Imports dependency modules: re.
L0011 | import ipaddress | Imports dependency modules: ipaddress.
L0012 | from urllib.parse import urlparse | Imports specific names from another module for direct usage.
L0013 | from functools import wraps | Imports specific names from another module for direct usage.
L0014 | from datetime import datetime, timedelta | Imports specific names from another module for direct usage.
L0015 | from flask import Flask, render_template, redirect, url_for, abort, request, flash, jsonify, send_file, send_from_directory, session
L0016 | from flask_migrate import Migrate | Imports specific names from another module for direct usage.
L0017 | from flask_login import LoginManager, logout_user, login_required, current_user | Imports specific names from another module for direct usage.
L0018 | from werkzeug.exceptions import HTTPException, RequestEntityTooLarge | Imports specific names from another module for direct usage.
L0019 | from werkzeug.security import generate_password_hash | Imports specific names from another module for direct usage.
L0020 | from werkzeug.utils import secure_filename | Imports specific names from another module for direct usage.
L0021 | from sqlalchemy import func, or_ | Imports specific names from another module for direct usage.
L0022 | from model import db, Consumable, Activity, User, Message, UserSettings, FormAssignment | Imports specific names from another module for direct usage.
L0023 | from dotenv import load_dotenv | Imports specific names from another module for direct usage.
L0024 | from pm_app.auth.routes import register_auth_routes | Imports specific names from another module for direct usage.
L0025 | from pm_app.api.routes import register_api_routes | Imports specific names from another module for direct usage.
L0026 | from pm_app.dashboards.routes import register_dashboard_routes | Imports specific names from another module for direct usage.
L0027 | from pm_app.services.maintenance import MaintenanceService | Imports specific names from another module for direct usage.
L0028 | from pm_app.services.observability import configure_request_observability | Imports specific names from another module for direct usage.
L0029 | from pm_app.services.time_utils import utcnow_naive | Imports specific names from another module for direct usage.
L0030 | import boto3 | Imports dependency modules: boto3.
L0031 | try: | Starts an exception handling block for risky operations.
L0032 |     from PIL import Image | Imports specific names from another module for direct usage.
L0033 | except Exception: | Handles errors raised in the associated try block.
L0034 |     Image = None | Assignment statement storing or updating program state.
L0035 | from reportlab.pdfgen import canvas | Imports specific names from another module for direct usage.
L0036 | from reportlab.graphics import renderPM | Imports specific names from another module for direct usage.
L0037 | from reportlab.graphics import renderSVG | Imports specific names from another module for direct usage.
L0038 | from reportlab.graphics.barcode import qr as reportlab_qr | Imports specific names from another module for direct usage.
L0039 | from reportlab.graphics.shapes import Drawing | Imports specific names from another module for direct usage.
L0040 | from openpyxl import Workbook | Imports specific names from another module for direct usage.
L0041 | from openpyxl.styles import Font, PatternFill, Alignment, Border, Side | Imports specific names from another module for direct usage.
L0042 | from openpyxl.utils import get_column_letter | Imports specific names from another module for direct usage.
L0043 | import smtplib | Imports dependency modules: smtplib.
L0044 | from email.mime.text import MIMEText | Imports specific names from another module for direct usage.
L0045 | from email.mime.multipart import MIMEMultipart | Imports specific names from another module for direct usage.
L0046 | import time as _time | Imports dependency modules: time as _time.
L0047 | import redis | Imports dependency modules: redis.
L0048 | from flask_limiter import Limiter | Imports specific names from another module for direct usage.
L0049 | from flask_limiter.util import get_remote_address | Imports specific names from another module for direct usage.
L0050 | from services.login_throttle import LoginThrottleStore | Imports specific names from another module for direct usage.
L0051 | | Blank line used for readability and logical separation.
L0052 | _ALERT_COOLDOWN = 1800 # seconds between error-alert emails (30 min) | Assignment statement storing or updating program state.
L0053 | _SLA_SCAN_COOLDOWN = 300 # seconds between SLA escalation scans (5 min) | Assignment statement storing or updating program state.
```

```

L0054 | HIGH_RISK_THRESHOLD = 70 | Assignment statement storing or updating program state.
L0055 | MEDIUM_RISK_THRESHOLD = 40 | Assignment statement storing or updating program state.
L0056 | SLA_DUE_SOON_HOURS = 6 | Assignment statement storing or updating program state.
L0057 | SLA_HOURS_CRITICAL = 24 | Assignment statement storing or updating program state.
L0058 | SLA_HOURS_STANDARD = 48 | Assignment statement storing or updating program state.
L0059 | APP_BUILD_ID = "20260328f" | Assignment statement storing or updating program state.
L0060 | | Blank line used for readability and logical separation.
L0061 | _alert_state: dict = {"last_time": 0.0} | Assignment statement storing or updating program state.
L0062 | | Blank line used for readability and logical separation.
L0063 | # Temporary server-side credential storage keyed by single-use token. | Comment line documenting intent or context for nearby code.
L0064 | # Passwords are held in memory (not the cookie) for up to 5 minutes. | Comment line documenting intent or context for nearby code.
L0065 | _pending_creds: dict = {} | Assignment statement storing or updating program state.
L0066 | | Blank line used for readability and logical separation.
L0067 | # Image magic-byte signatures for upload validation. | Comment line documenting intent or context for nearby code.
L0068 | # imghdr was removed in Python 3.13+, so we check bytes directly. | Comment line documenting intent or context for nearby code.
L0069 | _IMAGE_MAGIC = ( | Assignment statement storing or updating program state.
L0070 |     (b'\x89PNG\r\n\x1a\n', 'png'), | Operational statement participating in the file's runtime behavior.
L0071 |     (b'\xff\xd8\xff', 'jpeg'), | Operational statement participating in the file's runtime behavior.
L0072 |     (b'GIF87a', 'gif'), | Operational statement participating in the file's runtime behavior.
L0073 |     (b'GIF89a', 'gif'), | Operational statement participating in the file's runtime behavior.
L0074 | ) | Operational statement participating in the file's runtime behavior.
L0075 | def _check_image_magic(stream) -> bool: | Declares a function/method as a reusable unit of behavior.
L0076 |     """Return True when the stream starts with a known image magic sequence.""" | Docstring boundary used to describe a module, class, or function.
L0077 |     header = stream.read(16) | Assignment statement storing or updating program state.
L0078 |     stream.seek(0) | Operational statement participating in the file's runtime behavior.
L0079 |     if any(header.startswith(magic) for magic, _ in _IMAGE_MAGIC): | Conditional branch that runs only when its condition is true.
L0080 |         return True | Returns a value (or control) back to the caller.
L0081 |     # WEBP starts with RIFF...WEBP, where WEBP appears at byte offset 8. | Comment line documenting intent or context for nearby code.
L0082 |     return len(header) >= 12 and header.startswith(b"RIFF") and header[8:12] == b"WEBP" | Returns a value (or control) back to the caller.
L0083 | | Blank line used for readability and logical separation.
L0084 | | Blank line used for readability and logical separation.
L0085 | def _is_valid_image_file_path(file_path): | Declares a function/method as a reusable unit of behavior.
L0086 |     """Validate a file path as an image using magic bytes and optional PIL verification.""" | Docstring boundary used to describe a module, class, or function.
L0087 |     try: | Starts an exception handling block for risky operations.
L0088 |         with open(file_path, "rb") as fh: | Context manager block for safe setup and automatic cleanup.
L0089 |             header = fh.read(16) | Assignment statement storing or updating program state.
L0090 |         except Exception: | Handles errors raised in the associated try block.
L0091 |             return False | Returns a value (or control) back to the caller.
L0092 | | Blank line used for readability and logical separation.
L0093 |     is_magic_ok = any(header.startswith(magic) for magic, _ in _IMAGE_MAGIC) or ( | Assignment statement storing or updating program state.
L0094 |         len(header) >= 12 and header.startswith(b"RIFF") and header[8:12] == b"WEBP" | Operational statement participating in the file's runtime behavior.
L0095 |     ) | Operational statement participating in the file's runtime behavior.
L0096 |     if not is_magic_ok: | Conditional branch that runs only when its condition is true.
L0097 |         return False | Returns a value (or control) back to the caller.
L0098 | | Blank line used for readability and logical separation.
L0099 |     if Image is None: | Conditional branch that runs only when its condition is true.
L0100 |         return True | Returns a value (or control) back to the caller.
L0101 | | Blank line used for readability and logical separation.
L0102 |     try: | Starts an exception handling block for risky operations.
L0103 |         with Image.open(file_path) as img: | Context manager block for safe setup and automatic cleanup.
L0104 |             img.verify() | Operational statement participating in the file's runtime behavior.
L0105 |             return True | Returns a value (or control) back to the caller.
L0106 |         except Exception: | Handles errors raised in the associated try block.
L0107 |             return False | Returns a value (or control) back to the caller.
L0108 | | Blank line used for readability and logical separation.

```



```

L0109 | | Blank line used for readability and logical separation.
L0110 | def _stream_size_bytes(stream): | Declares a function/method as a reusable unit of behavior.
L0111 |     """Return stream size in bytes when seek/tell is supported, else None.""" | Docstring boundary used to describe a module, class
L0112 |     try: | Starts an exception handling block for risky operations.
L0113 |         current = stream.tell() | Assignment statement storing or updating program state.
L0114 |         stream.seek(0, os.SEEK_END) | Operational statement participating in the file's runtime behavior.
L0115 |         size = stream.tell() | Assignment statement storing or updating program state.
L0116 |         stream.seek(current) | Operational statement participating in the file's runtime behavior.
L0117 |         return size | Returns a value (or control) back to the caller.
L0118 |     except Exception: | Handles errors raised in the associated try block.
L0119 |         return None | Returns a value (or control) back to the caller.
L0120 | | Blank line used for readability and logical separation.
L0121 | def send_alert(message, subject="System Alert"): | Declares a function/method as a reusable unit of behavior.
L0122 |     now = _time.time() | Assignment statement storing or updating program state.
L0123 |     if now - _alert_state["last_time"] < _ALERT_COOLDOWN: | Conditional branch that runs only when its condition is true.
L0124 |         return # suppress - already sent one within the cooldown window | Returns a value (or control) back to the caller.
L0125 | | Blank line used for readability and logical separation.
L0126 |     email_address = os.getenv("ALERT_EMAIL_ADDRESS", "") | Assignment statement storing or updating program state.
L0127 |     email_password = os.getenv("ALERT_EMAIL_PASSWORD", "") | Assignment statement storing or updating program state.
L0128 |     if not email_address or not email_password: | Conditional branch that runs only when its condition is true.
L0129 |         return | Returns a value (or control) back to the caller.
L0130 | | Blank line used for readability and logical separation.
L0131 |     _alert_state["last_time"] = now | Assignment statement storing or updating program state.
L0132 |     _last_error = None | Assignment statement storing or updating program state.
L0133 |     for _attempt in range(3): | Loop iterating over a sequence to process elements one by one.
L0134 |         try: | Starts an exception handling block for risky operations.
L0135 |             msg = MIMEMultipart() | Assignment statement storing or updating program state.
L0136 |             msg["From"] = email_address | Assignment statement storing or updating program state.
L0137 |             msg["To"] = email_address | Assignment statement storing or updating program state.
L0138 |             msg["Subject"] = subject | Assignment statement storing or updating program state.
L0139 |             msg.attach(MIMEText(message, "plain")) | Operational statement participating in the file's runtime behavior.
L0140 |             with smtplib.SMTP_SSL("smtp.gmail.com", 465) as server: | Context manager block for safe setup and automatic cleanup.
L0141 |                 server.login(email_address, email_password) | Operational statement participating in the file's runtime behavior.
L0142 |                 server.send_message(msg) | Operational statement participating in the file's runtime behavior.
L0143 |             return # sent successfully | Returns a value (or control) back to the caller.
L0144 |         except Exception as exc: | Handles errors raised in the associated try block.
L0145 |             _last_error = exc | Assignment statement storing or updating program state.
L0146 |             _time.sleep(2 ** _attempt) # back-off: 1s, 2s, 4s | Operational statement participating in the file's runtime behavior.
L0147 |     import logging as _logging | Imports dependency modules: logging as _logging.
L0148 |     _logging.getLogger(__name__).error("Failed to send alert email after 3 attempts: %s", _last_error) | Operational statement part
L0149 | | Blank line used for readability and logical separation.
L0150 | load_dotenv() | Operational statement participating in the file's runtime behavior.
L0151 | | Blank line used for readability and logical separation.
L0152 | ADMIN_ROLES = {"manager", "general_manager", "developer"} | Assignment statement storing or updating program state.
L0153 | DESK_ROLES = {"staff", "manager", "general_manager", "developer"} | Assignment statement storing or updating program state.
L0154 | TECHNICIAN_ROLES = {"technician"} | Assignment statement storing or updating program state.
L0155 | VALID_ACCOUNT_ROLES = ("developer", "general_manager", "manager", "staff", "technician") | Assignment statement storing or updating
L0156 | LOGIN_MATRIX_KEYS = ("developer", "staff", "technician") | Assignment statement storing or updating program state.
L0157 | DEFAULT_ROLE_ACCESS_MATRIX = { | Assignment statement storing or updating program state.
L0158 |     "developer": ["developer"], | Operational statement participating in the file's runtime behavior.
L0159 |     "staff": ["staff", "manager", "general_manager"], | Operational statement participating in the file's runtime behavior.
L0160 |     "technician": ["technician"], | Operational statement participating in the file's runtime behavior.
L0161 | } | Block delimiter controlling scope/structure in this language.
L0162 | | Blank line used for readability and logical separation.
L0163 | AVATAR_OPTIONS = ( | Assignment statement storing or updating program state.

```

```

L0164 | {"key": "technician", "label": "Technician", "icon": "person-fill-gear", "gender": "male"}, | Operational state
L0165 | {"key": "male_exec", "label": "Male \u00b7 Office", "icon": "person-badge-fill", "gender": "male"}, | Operational state
L0166 | {"key": "female_exec", "label": "Female \u00b7 Office", "icon": "person-vcard-fill", "gender": "female"}, | Operational sta
L0167 | {"key": "developer", "label": "Developer", "icon": "person-workspace", "gender": "other"}, | Operational stat
L0168 | {"key": "neutral", "label": "Default", "icon": "person-circle", "gender": "other"}, | Operational stat
L0169 | ) | Operational statement participating in the file's runtime behavior.
L0170 | AVATAR_ICON_MAP = {option["key"]: option["icon"] for option in AVATAR_OPTIONS} | Assignment statement storing or updating program s
L0171 | AVATAR_KEYS = set(AVATAR_ICON_MAP.keys()) | Assignment statement storing or updating program state.
L0172 | | Blank line used for readability and logical separation.
L0173 | | Blank line used for readability and logical separation.
L0174 | def resolve_avatar_key(raw_avatar_key, raw_gender): | Declares a function/method as a reusable unit of behavior.
L0175 |     avatar_key = (raw_avatar_key or "").strip().lower() | Assignment statement storing or updating program state.
L0176 |     if avatar_key in AVATAR_KEYS: | Conditional branch that runs only when its condition is true.
L0177 |         return avatar_key | Returns a value (or control) back to the caller.
L0178 | | Blank line used for readability and logical separation.
L0179 | # Legacy key remapping for saved data using old keys | Comment line documenting intent or context for nearby code.
L0180 | _legacy = {"male_tech": "technician", "female_tech": "female_exec"} | Assignment statement storing or updating program state.
L0181 | if avatar_key in _legacy: | Conditional branch that runs only when its condition is true.
L0182 |     return _legacy[avatar_key] | Returns a value (or control) back to the caller.
L0183 | | Blank line used for readability and logical separation.
L0184 |     normalized_gender = (raw_gender or "").strip().lower() | Assignment statement storing or updating program state.
L0185 |     if normalized_gender in {"female", "f"}: | Conditional branch that runs only when its condition is true.
L0186 |         return "female_exec" | Returns a value (or control) back to the caller.
L0187 |     if normalized_gender in {"male", "m"}: | Conditional branch that runs only when its condition is true.
L0188 |         return "technician" | Returns a value (or control) back to the caller.
L0189 |     return "neutral" | Returns a value (or control) back to the caller.
L0190 | | Blank line used for readability and logical separation.
L0191 | | Blank line used for readability and logical separation.
L0192 | def normalize_role(role): | Declares a function/method as a reusable unit of behavior.
L0193 |     normalized = (role or "").strip().lower().replace("-", "_").replace(" ", "_") | Assignment statement storing or updating progra
L0194 |     alias_map = { | Assignment statement storing or updating program state.
L0195 |         "desk_staff": "staff", | Operational statement participating in the file's runtime behavior.
L0196 |         "deskstaff": "staff", | Operational statement participating in the file's runtime behavior.
L0197 |         "field_technician": "technician", | Operational statement participating in the file's runtime behavior.
L0198 |         "site_technician": "technician", | Operational statement participating in the file's runtime behavior.
L0199 |         "tech": "technician", | Operational statement participating in the file's runtime behavior.
L0200 |         "gm": "general_manager", | Operational statement participating in the file's runtime behavior.
L0201 |     } | Block delimiter controlling scope/structure in this language.
L0202 |     normalized = alias_map.get(normalized, normalized) | Assignment statement storing or updating program state.
L0203 |     if normalized.startswith("technician") or normalized.endswith("_technician"): | Conditional branch that runs only when its cond
L0204 |         return "technician" | Returns a value (or control) back to the caller.
L0205 |     return normalized | Returns a value (or control) back to the caller.
L0206 | | Blank line used for readability and logical separation.
L0207 | | Blank line used for readability and logical separation.
L0208 | def get_public_base_url(): | Declares a function/method as a reusable unit of behavior.
L0209 |     configured_base = os.getenv("PUBLIC_BASE_URL", "").strip() | Assignment statement storing or updating program state.
L0210 |     if configured_base: | Conditional branch that runs only when its condition is true.
L0211 |         if "/" not in configured_base: | Conditional branch that runs only when its condition is true.
L0212 |             configured_base = "https://" + configured_base | Assignment statement storing or updating program state.
L0213 |         return configured_base.rstrip("/") | Returns a value (or control) back to the caller.
L0214 | | Blank line used for readability and logical separation.
L0215 | # If running behind a reverse proxy, prefer forwarded host/proto. | Comment line documenting intent or context for nearby code.
L0216 | forwarded_host = (request.headers.get("X-Forwarded-Host", "") or "").split(",")[0].strip() | Assignment statement storing or up
L0217 | forwarded_proto = (request.headers.get("X-Forwarded-Proto", "") or "").split(",")[0].strip() | Assignment statement storing or
L0218 | if forwarded_host: | Conditional branch that runs only when its condition is true.

```

```

L0219 |         scheme = forwarded_proto or request.scheme or "https" | Assignment statement storing or updating program state.
L0220 |         return f"{scheme}://{forwarded_host}.rstrip("/") | Returns a value (or control) back to the caller.
L0221 | | Blank line used for readability and logical separation.
L0222 |         host_url = request.host_url.rstrip("/") | Assignment statement storing or updating program state.
L0223 | | Blank line used for readability and logical separation.
L0224 |         # When the request came in via localhost/loopback, try to substitute the | Comment line documenting intent or context for nearby
L0225 |         # machine's LAN IP so that generated QR codes are actually scannable by | Comment line documenting intent or context for nearby
L0226 |         # other devices on the same network. | Comment line documenting intent or context for nearby code.
L0227 |         try: | Starts an exception handling block for risky operations.
L0228 |             parsed = urlparse(host_url) | Assignment statement storing or updating program state.
L0229 |             host = (parsed.hostname or "").lower() | Assignment statement storing or updating program state.
L0230 |             if host in {"localhost", "127.0.0.1", "::1"}: | Conditional branch that runs only when its condition is true.
L0231 |                 import socket | Imports dependency modules: socket.
L0232 |                 lan_ip = "" | Assignment statement storing or updating program state.
L0233 | | Blank line used for readability and logical separation.
L0234 |                 # Preferred approach: ask the OS which interface would be used for | Comment line documenting intent or context for nearby
L0235 |                 # outbound traffic, then read that local socket address. | Comment line documenting intent or context for nearby code.
L0236 |                 try: | Starts an exception handling block for risky operations.
L0237 |                     probe = socket.socket(socket.AF_INET, socket.SOCK_DGRAM) | Assignment statement storing or updating program state.
L0238 |                     probe.connect(("8.8.8.8", 80)) | Operational statement participating in the file's runtime behavior.
L0239 |                     lan_ip = (probe.getsockname()[0] or "").strip() | Assignment statement storing or updating program state.
L0240 |                     probe.close() | Operational statement participating in the file's runtime behavior.
L0241 |                 except Exception: | Handles errors raised in the associated try block.
L0242 |                     lan_ip = "" | Assignment statement storing or updating program state.
L0243 | | Blank line used for readability and logical separation.
L0244 |                 # Fallback: hostname resolution (can be loopback on some systems). | Comment line documenting intent or context for nearby
L0245 |                 if not lan_ip: | Conditional branch that runs only when its condition is true.
L0246 |                     lan_ip = (socket.gethostbyname(socket.gethostname()) or "").strip() | Assignment statement storing or updating program state.
L0247 | | Blank line used for readability and logical separation.
L0248 |                 if lan_ip and not lan_ip.startswith("127."): | Conditional branch that runs only when its condition is true.
L0249 |                     port = parsed.port | Assignment statement storing or updating program state.
L0250 |                     port_suffix = f":{port}" if port and port not in {80, 443} else "" | Assignment statement storing or updating program state.
L0251 |                     return f"{parsed.scheme}://{lan_ip}{port_suffix}" | Returns a value (or control) back to the caller.
L0252 |                 except Exception: | Handles errors raised in the associated try block.
L0253 |                     pass | Flow-control keyword affecting execution in the current block.
L0254 | | Blank line used for readability and logical separation.
L0255 |         return host_url | Returns a value (or control) back to the caller.
L0256 | | Blank line used for readability and logical separation.
L0257 | | Blank line used for readability and logical separation.
L0258 | def is_public_share_base(base_url): | Declares a function/method as a reusable unit of behavior.
L0259 |     if not base_url: | Conditional branch that runs only when its condition is true.
L0260 |         return False | Returns a value (or control) back to the caller.
L0261 |     try: | Starts an exception handling block for risky operations.
L0262 |         host = (urlparse(base_url).hostname or "").strip().lower() | Assignment statement storing or updating program state.
L0263 |     except Exception: | Handles errors raised in the associated try block.
L0264 |         return False | Returns a value (or control) back to the caller.
L0265 | | Blank line used for readability and logical separation.
L0266 |     if not host or host in {"localhost", "127.0.0.1", "::1"} or host.endswith(".local"): | Conditional branch that runs only when its condition is true.
L0267 |         return False | Returns a value (or control) back to the caller.
L0268 | | Blank line used for readability and logical separation.
L0269 |     try: | Starts an exception handling block for risky operations.
L0270 |         host_ip = ipaddress.ip_address(host) | Assignment statement storing or updating program state.
L0271 |         return not ( | Returns a value (or control) back to the caller.
L0272 |             host_ip.is_private | Operational statement participating in the file's runtime behavior.
L0273 |             or host_ip.is_loopback | Operational statement participating in the file's runtime behavior.

```

```

L0274 |         or host_ip.is_link_local | Operational statement participating in the file's runtime behavior.
L0275 |         or host_ip.is_multicast | Operational statement participating in the file's runtime behavior.
L0276 |         or host_ip.is_reserved | Operational statement participating in the file's runtime behavior.
L0277 |         or host_ip.is_unspecified | Operational statement participating in the file's runtime behavior.
L0278 |     ) | Operational statement participating in the file's runtime behavior.
L0279 | except ValueError: | Handles errors raised in the associated try block.
L0280 |     # Hostname: allow non-local DNS names. | Comment line documenting intent or context for nearby code.
L0281 |     return True | Returns a value (or control) back to the caller.
L0282 | | Blank line used for readability and logical separation.
L0283 | | Blank line used for readability and logical separation.
L0284 | def is_admin_role(role): | Declares a function/method as a reusable unit of behavior.
L0285 |     return normalize_role(role) in ADMIN_ROLES | Returns a value (or control) back to the caller.
L0286 | | Blank line used for readability and logical separation.
L0287 | | Blank line used for readability and logical separation.
L0288 | def is_desk_role(role): | Declares a function/method as a reusable unit of behavior.
L0289 |     return normalize_role(role) in DESK_ROLES | Returns a value (or control) back to the caller.
L0290 | | Blank line used for readability and logical separation.
L0291 | | Blank line used for readability and logical separation.
L0292 | def is_technician_role(role): | Declares a function/method as a reusable unit of behavior.
L0293 |     return normalize_role(role) in TECHNICIAN_ROLES | Returns a value (or control) back to the caller.
L0294 | | Blank line used for readability and logical separation.
L0295 | | Blank line used for readability and logical separation.
L0296 | def allowed_login_roles(selected_role): | Declares a function/method as a reusable unit of behavior.
L0297 |     selected_role = normalize_role(selected_role) | Assignment statement storing or updating program state.
L0298 |     role_map = DEFAULT_ROLE_ACCESS_MATRIX | Assignment statement storing or updating program state.
L0299 |     if has_app_context(): | Conditional branch that runs only when its condition is true.
L0300 |         configured = current_app.config.get("ROLE_ACCESS_MATRIX") | Assignment statement storing or updating program state.
L0301 |         if isinstance(configured, dict): | Conditional branch that runs only when its condition is true.
L0302 |             role_map = normalize_role_access_matrix(configured) | Assignment statement storing or updating program state.
L0303 |     return set(role_map.get(selected_role, [])) | Returns a value (or control) back to the caller.
L0304 | | Blank line used for readability and logical separation.
L0305 | | Blank line used for readability and logical separation.
L0306 | def normalize_role_access_matrix(raw_matrix): | Declares a function/method as a reusable unit of behavior.
L0307 |     normalized = {} | Assignment statement storing or updating program state.
L0308 |     role_order = {role: idx for idx, role in enumerate(VALID_ACCOUNT_ROLES)} | Assignment statement storing or updating program state.
L0309 |     for matrix_key in LOGIN_MATRIX_KEYS: | Loop iterating over a sequence to process elements one by one.
L0310 |         values = raw_matrix.get(matrix_key, []) if isinstance(raw_matrix, dict) else [] | Assignment statement storing or updating program state.
L0311 |         if not isinstance(values, (list, tuple, set)): | Conditional branch that runs only when its condition is true.
L0312 |             values = [] | Assignment statement storing or updating program state.
L0313 |         cleaned = [] | Assignment statement storing or updating program state.
L0314 |         for value in values: | Loop iterating over a sequence to process elements one by one.
L0315 |             role = normalize_role(value) | Assignment statement storing or updating program state.
L0316 |             if role in VALID_ACCOUNT_ROLES and role not in cleaned: | Conditional branch that runs only when its condition is true.
L0317 |                 cleaned.append(role) | Operational statement participating in the file's runtime behavior.
L0318 | | Blank line used for readability and logical separation.
L0319 |         if not cleaned: | Conditional branch that runs only when its condition is true.
L0320 |             cleaned = list(DEFAULT_ROLE_ACCESS_MATRIX[matrix_key]) | Assignment statement storing or updating program state.
L0321 | | Blank line used for readability and logical separation.
L0322 |         normalized[matrix_key] = sorted(cleaned, key=lambda item: role_order[item]) | Assignment statement storing or updating program state.
L0323 | | Blank line used for readability and logical separation.
L0324 |     return normalized | Returns a value (or control) back to the caller.
L0325 | | Blank line used for readability and logical separation.
L0326 | | Blank line used for readability and logical separation.
L0327 | def _coerce_policy_hours(value, default, minimum=1, maximum=168): | Declares a function/method as a reusable unit of behavior.
L0328 |     try: | Starts an exception handling block for risky operations.

```

```

L0329 |         parsed = int(value) | Assignment statement storing or updating program state.
L0330 |     except (TypeError, ValueError): | Handles errors raised in the associated try block.
L0331 |         return default | Returns a value (or control) back to the caller.
L0332 |     return max(minimum, min(maximum, parsed)) | Returns a value (or control) back to the caller.
L0333 | | Blank line used for readability and logical separation.
L0334 | | Blank line used for readability and logical separation.
L0335 | def normalize_sla_policy_config(raw_policy=None): | Declares a function/method as a reusable unit of behavior.
L0336 |     raw_policy = raw_policy if isinstance(raw_policy, dict) else {} | Assignment statement storing or updating program state.
L0337 |     standard_hours = _coerce_policy_hours(raw_policy.get("standard_hours"), SLA_HOURS_STANDARD) | Assignment statement storing or updating program state.
L0338 |     critical_hours = _coerce_policy_hours(raw_policy.get("critical_hours"), SLA_HOURS_CRITICAL) | Assignment statement storing or updating program state.
L0339 |     due_soon_hours = _coerce_policy_hours(raw_policy.get("due_soon_hours"), SLA_HOURS_SOON) | Assignment statement storing or updating program state.
L0340 |     raw_policy["due_soon_hours"] = due_soon_hours | Operational statement participating in the file's runtime behavior.
L0341 |     raw_policy["standard_hours"] = standard_hours | Operational statement participating in the file's runtime behavior.
L0342 |     minimum=1, | Assignment statement storing or updating program state.
L0343 |     maximum=min(72, max(1, min(standard_hours, critical_hours))), | Assignment statement storing or updating program state.
L0344 | ) | Operational statement participating in the file's runtime behavior.
L0345 | return { | Returns a value (or control) back to the caller.
L0346 |     "enabled": bool(raw_policy.get("enabled", True)), | Operational statement participating in the file's runtime behavior.
L0347 |     "standard_hours": standard_hours, | Operational statement participating in the file's runtime behavior.
L0348 |     "critical_hours": critical_hours, | Operational statement participating in the file's runtime behavior.
L0349 |     "due_soon_hours": due_soon_hours, | Operational statement participating in the file's runtime behavior.
L0350 |     "policy_agreed": bool(raw_policy.get("policy_agreed", False)), | Operational statement participating in the file's runtime behavior.
L0351 |     "updated_at": raw_policy.get("updated_at") or "", | Operational statement participating in the file's runtime behavior.
L0352 |     "updated_by": raw_policy.get("updated_by") or "System Default", | Operational statement participating in the file's runtime behavior.
L0353 |     "updated_role": raw_policy.get("updated_role") or "system", | Operational statement participating in the file's runtime behavior.
L0354 |     "source": raw_policy.get("source") or "default", | Operational statement participating in the file's runtime behavior.
L0355 | } | Block delimiter controlling scope/structure in this language.
L0356 | | Blank line used for readability and logical separation.
L0357 | | Blank line used for readability and logical separation.
L0358 | def build_sla_deadline_from_policy(*, activity_type: str, is_critical: bool, now_value: datetime, policy: dict \ | None): | Declares a function/method as a reusable unit of behavior.
L0359 |     normalized_policy = normalize_sla_policy_config(policy) | Assignment statement storing or updating program state.
L0360 |     if not normalized_policy["enabled"]: | Conditional branch that runs only when its condition is true.
L0361 |         return None | Returns a value (or control) back to the caller.
L0362 |     deadline_hours = normalized_policy["critical_hours"] if is_critical or activity_type == "rca" else normalized_policy["standard_hours"]
L0363 |     return now_value + timedelta(hours=deadline_hours) | Returns a value (or control) back to the caller.
L0364 | | Blank line used for readability and logical separation.
L0365 | | Blank line used for readability and logical separation.
L0366 | def get_public_holidays(): | Declares a function/method as a reusable unit of behavior.
L0367 |     return [ | Returns a value (or control) back to the caller.
L0368 |         {"date": "2026-01-01", "name": "New Year's Day"}, | Operational statement participating in the file's runtime behavior.
L0369 |         {"date": "2026-01-26", "name": "NRM Liberation Day"}, | Operational statement participating in the file's runtime behavior.
L0370 |         {"date": "2026-02-16", "name": "Archbishop Janani Luwum Day"}, | Operational statement participating in the file's runtime behavior.
L0371 |         {"date": "2026-03-08", "name": "International Women's Day"}, | Operational statement participating in the file's runtime behavior.
L0372 |         {"date": "2026-04-03", "name": "Good Friday"}, | Operational statement participating in the file's runtime behavior.
L0373 |         {"date": "2026-04-06", "name": "Easter Monday"}, | Operational statement participating in the file's runtime behavior.
L0374 |         {"date": "2026-05-01", "name": "Labour Day"}, | Operational statement participating in the file's runtime behavior.
L0375 |         {"date": "2026-06-03", "name": "Uganda Martyrs' Day"}, | Operational statement participating in the file's runtime behavior.
L0376 |         {"date": "2026-06-09", "name": "National Heroes' Day"}, | Operational statement participating in the file's runtime behavior.
L0377 |         {"date": "2026-10-09", "name": "Independence Day"}, | Operational statement participating in the file's runtime behavior.
L0378 |         {"date": "2026-12-25", "name": "Christmas Day"}, | Operational statement participating in the file's runtime behavior.
L0379 |         {"date": "2026-12-26", "name": "Boxing Day"}, | Operational statement participating in the file's runtime behavior.
L0380 |     ] | Operational statement participating in the file's runtime behavior.
L0381 | | Blank line used for readability and logical separation.
L0382 | | Blank line used for readability and logical separation.
L0383 | def build_site_activity_details(site_id, site_name, location, details): | Declares a function/method as a reusable unit of behavior.

```

```
L0384 | parts = [ | Assignment statement storing or updating program state.
L0385 |     f"Site ID: {site_id}", | Operational statement participating in the file's runtime behavior.
L0386 |     f"Site Name: {site_name}", | Operational statement participating in the file's runtime behavior.
L0387 |     f"Location: {location or 'Not provided'}", | Operational statement participating in the file's runtime behavior.
L0388 |     "", | Operational statement participating in the file's runtime behavior.
L0389 |     details, | Operational statement participating in the file's runtime behavior.
L0390 | ] | Operational statement participating in the file's runtime behavior.
L0391 | return "\n".join(parts) | Returns a value (or control) back to the caller.
L0392 | | Blank line used for readability and logical separation.
L0393 | | Blank line used for readability and logical separation.
L0394 | TECHNICIAN_PM_SECTIONS = [ | Assignment statement storing or updating program state.
L0395 |     { | Block delimiter controlling scope/structure in this language.
L0396 |         "title": "ATTRIBUTE", | Operational statement participating in the file's runtime behavior.
L0397 |         "fields": [ | Operational statement participating in the file's runtime behavior.
L0398 |             "Activity", | Operational statement participating in the file's runtime behavior.
L0399 |             "Activity Date", | Operational statement participating in the file's runtime behavior.
L0400 |             "Activity Time", | Operational statement participating in the file's runtime behavior.
L0401 |             "Access Ref", | Operational statement participating in the file's runtime behavior.
L0402 |             "Site Number", | Operational statement participating in the file's runtime behavior.
L0403 |             "Site Name", | Operational statement participating in the file's runtime behavior.
L0404 |             "Site Type", | Operational statement participating in the file's runtime behavior.
L0405 |             "Purpose of Visit", | Operational statement participating in the file's runtime behavior.
L0406 |             "Confirm Personal Protective Equipment", | Operational statement participating in the file's runtime behavior.
L0407 |             "Site Clean", | Operational statement participating in the file's runtime behavior.
L0408 |             "Security Guard Present?", | Operational statement participating in the file's runtime behavior.
L0409 |             "Comment", | Operational statement participating in the file's runtime behavior.
L0410 |         ], | Operational statement participating in the file's runtime behavior.
L0411 |     }, | Operational statement participating in the file's runtime behavior.
L0412 |     { | Block delimiter controlling scope/structure in this language.
L0413 |         "title": "GENERATOR CHECKS", | Operational statement participating in the file's runtime behavior.
L0414 |         "fields": [ | Operational statement participating in the file's runtime behavior.
L0415 |             "Number of fuel Tanks", | Operational statement participating in the file's runtime behavior.
L0416 |             "Tank Type (Base/ Standalone)", | Operational statement participating in the file's runtime behavior.
L0417 |             "Diesel Tank Capacity (L)", | Operational statement participating in the file's runtime behavior.
L0418 |             "Diesel level (L)", | Operational statement participating in the file's runtime behavior.
L0419 |             "Is fuel sensor connected?", | Operational statement participating in the file's runtime behavior.
L0420 |             "Is fuel sensor functional?", | Operational statement participating in the file's runtime behavior.
L0421 |             "DG Manufacturer", | Operational statement participating in the file's runtime behavior.
L0422 |             "DG Serial Number", | Operational statement participating in the file's runtime behavior.
L0423 |             "DG Engine Serial Number", | Operational statement participating in the file's runtime behavior.
L0424 |             "DG Capacity (kVA)", | Operational statement participating in the file's runtime behavior.
L0425 |             "DG Hour Service Kit", | Operational statement participating in the file's runtime behavior.
L0426 |             "Date of Last Service", | Operational statement participating in the file's runtime behavior.
L0427 |             "DG Run Hour at Last Service", | Operational statement participating in the file's runtime behavior.
L0428 |             "Current DG Run Hours", | Operational statement participating in the file's runtime behavior.
L0429 |             "DG Battery on Site", | Operational statement participating in the file's runtime behavior.
L0430 |             "Is Battery on DG Working?", | Operational statement participating in the file's runtime behavior.
L0431 |             "Is DG oil filter replaced?", | Operational statement participating in the file's runtime behavior.
L0432 |             "Is DG fuel filter replaced?", | Operational statement participating in the file's runtime behavior.
L0433 |             "Is DG air filter replaced?", | Operational statement participating in the file's runtime behavior.
L0434 |             "Liters of Engine Oil Used", | Operational statement participating in the file's runtime behavior.
L0435 |             "Any Engine Oil Topped up other than DG Service Oil in Liters", | Operational statement participating in the file's runtime behavior.
L0436 |             "Signs of leakage along the DG fuel supply line", | Operational statement participating in the file's runtime behavior.
L0437 |             "If yes, has the leak been fixed?", | Operational statement participating in the file's runtime behavior.
L0438 |             "Is DG Fan Belt in good condition", | Operational statement participating in the file's runtime behavior.
```

```

L0439 |         "Has Coolant Been Added?", | Operational statement participating in the file's runtime behavior.
L0440 |         "Amount of Coolant Added in Liters", | Operational statement participating in the file's runtime behavior.
L0441 |         "DG Controller Manufacturer", | Operational statement participating in the file's runtime behavior.
L0442 |         "DG Controller Serial Number", | Operational statement participating in the file's runtime behavior.
L0443 |         "DG Controller Model Number", | Operational statement participating in the file's runtime behavior.
L0444 |         "Is controller in Auto mode?", | Operational statement participating in the file's runtime behavior.
L0445 |     ], | Operational statement participating in the file's runtime behavior.
L0446 | }, | Operational statement participating in the file's runtime behavior.
L0447 | { | Block delimiter controlling scope/structure in this language.
L0448 |     "title": "ATS/ AUTOMATION CHECKS", | Operational statement participating in the file's runtime behavior.
L0449 |     "fields": [ | Operational statement participating in the file's runtime behavior.
L0450 |         "ATS Installed?", | Operational statement participating in the file's runtime behavior.
L0451 |         "Is ATS Working?", | Operational statement participating in the file's runtime behavior.
L0452 |         "Has ATS functionality been tested by simulating a mains failure", | Operational statement participating in the file's
L0453 |         "Is Site Connected to Grid?", | Operational statement participating in the file's runtime behavior.
L0454 |         "Was grid available during site visit?", | Operational statement participating in the file's runtime behavior.
L0455 |         "Any grid faults identified? Share.", | Operational statement participating in the file's runtime behavior.
L0456 |         "Meter Type (Post/ pre-paid)", | Operational statement participating in the file's runtime behavior.
L0457 |         "Grid Meter Number", | Operational statement participating in the file's runtime behavior.
L0458 |         "Grid Meter Reading", | Operational statement participating in the file's runtime behavior.
L0459 |         "Is Grid Meter Working?", | Operational statement participating in the file's runtime behavior.
L0460 |         "Connection Type: (Single or Three Phase)", | Operational statement participating in the file's runtime behavior.
L0461 |         "Grid supply current - Ph3 (A)", | Operational statement participating in the file's runtime behavior.
L0462 |     ], | Operational statement participating in the file's runtime behavior.
L0463 | }, | Operational statement participating in the file's runtime behavior.
L0464 | { | Block delimiter controlling scope/structure in this language.
L0465 |     "title": "DC SYSTEMS: RECTIFIER CHECKS", | Operational statement participating in the file's runtime behavior.
L0466 |     "fields": [ | Operational statement participating in the file's runtime behavior.
L0467 |         "Number of Rectifiers Installed", | Operational statement participating in the file's runtime behavior.
L0468 |         "DC Location: (Indoor/ Outdoor)", | Operational statement participating in the file's runtime behavior.
L0469 |         "Rectifier Type", | Operational statement participating in the file's runtime behavior.
L0470 |         "Rectifier Serial Number", | Operational statement participating in the file's runtime behavior.
L0471 |         "Rectifier Model Number", | Operational statement participating in the file's runtime behavior.
L0472 |         "DC Loads (A)", | Operational statement participating in the file's runtime behavior.
L0473 |         "Rectifier Module Capacity", | Operational statement participating in the file's runtime behavior.
L0474 |         "System Voltage", | Operational statement participating in the file's runtime behavior.
L0475 |         "No of slots available in the rectifier", | Operational statement participating in the file's runtime behavior.
L0476 |         "Are rectifier modules cleared of dust?", | Operational statement participating in the file's runtime behavior.
L0477 |         "No. of Rectifiers Modules Present", | Operational statement participating in the file's runtime behavior.
L0478 |         "No of Working Rectifier Modules", | Operational statement participating in the file's runtime behavior.
L0479 |         "No. of Faulty Rectifier Modules", | Operational statement participating in the file's runtime behavior.
L0480 |     ], | Operational statement participating in the file's runtime behavior.
L0481 | }, | Operational statement participating in the file's runtime behavior.
L0482 | { | Block delimiter controlling scope/structure in this language.
L0483 |     "title": "DC SYSTEMS: BATTERY CHECKS", | Operational statement participating in the file's runtime behavior.
L0484 |     "fields": [ | Operational statement participating in the file's runtime behavior.
L0485 |         "Are Batteries Installed?", | Operational statement participating in the file's runtime behavior.
L0486 |         "Battery Bank Location (Indoor /outdoor)", | Operational statement participating in the file's runtime behavior.
L0487 |         "Battery Manufacturer", | Operational statement participating in the file's runtime behavior.
L0488 |         "Battery Capacity", | Operational statement participating in the file's runtime behavior.
L0489 |         "Number of Battery strings", | Operational statement participating in the file's runtime behavior.
L0490 |         "Battery Condition", | Operational statement participating in the file's runtime behavior.
L0491 |         "Number of batteries per strings in the Bank", | Operational statement participating in the file's runtime behavior.
L0492 |         "Total Number of Batteries at site", | Operational statement participating in the file's runtime behavior.
L0493 |         "Number of Battery Strings Connected", | Operational statement participating in the file's runtime behavior.

```

```

L0494 |         "Approximate Battery Backup Time", | Operational statement participating in the file's runtime behavior.
L0495 |         "Is Hybrid Installed?", | Operational statement participating in the file's runtime behavior.
L0496 |         "Type of Hybrid Installed", | Operational statement participating in the file's runtime behavior.
L0497 |         "Is Hybrid Working?", | Operational statement participating in the file's runtime behavior.
L0498 |         "Hybrid parameters checked?", | Operational statement participating in the file's runtime behavior.
L0499 |         "Is battery current limit set?", | Operational statement participating in the file's runtime behavior.
L0500 |         "Are all alarms wires connected?", | Operational statement participating in the file's runtime behavior.
L0501 |         "Is battery capacity set as per installed battery?", | Operational statement participating in the file's runtime behavior.
L0502 |         "Ensure all terminations and connections are tightened", | Operational statement participating in the file's runtime behavior.
L0503 |     ], | Operational statement participating in the file's runtime behavior.
L0504 | }, | Operational statement participating in the file's runtime behavior.
L0505 | { | Block delimiter controlling scope/structure in this language.
L0506 |     "title": "EARTHING CHECKS", | Operational statement participating in the file's runtime behavior.
L0507 |     "fields": [ | Operational statement participating in the file's runtime behavior.
L0508 |         "Earthing Resistance - Generator", | Operational statement participating in the file's runtime behavior.
L0509 |         "Earthing Resistance - ATS", | Operational statement participating in the file's runtime behavior.
L0510 |         "Earthing Resistance - ACDB", | Operational statement participating in the file's runtime behavior.
L0511 |         "Earthing Resistance - Rectifier", | Operational statement participating in the file's runtime behavior.
L0512 |         "Earthing Resistance - DCDB", | Operational statement participating in the file's runtime behavior.
L0513 |         "Earthing Resistance - RMS Unit", | Operational statement participating in the file's runtime behavior.
L0514 |         "Earthing Resistance - Tenant Equipment", | Operational statement participating in the file's runtime behavior.
L0515 |         "Earthing Resistance - Tower Leg", | Operational statement participating in the file's runtime behavior.
L0516 |         "Earthing Resistance - Fence", | Operational statement participating in the file's runtime behavior.
L0517 |     ], | Operational statement participating in the file's runtime behavior.
L0518 | }, | Operational statement participating in the file's runtime behavior.
L0519 | { | Block delimiter controlling scope/structure in this language.
L0520 |     "title": "EXTERNAL ALARMS CHECKS", | Operational statement participating in the file's runtime behavior.
L0521 |     "fields": [ | Operational statement participating in the file's runtime behavior.
L0522 |         "Are External Alarms connected", | Operational statement participating in the file's runtime behavior.
L0523 |         "Have Alarms been tested with NOC?", | Operational statement participating in the file's runtime behavior.
L0524 |     ], | Operational statement participating in the file's runtime behavior.
L0525 | }, | Operational statement participating in the file's runtime behavior.
L0526 | { | Block delimiter controlling scope/structure in this language.
L0527 |     "title": "SHELTER STATUS", | Operational statement participating in the file's runtime behavior.
L0528 |     "fields": [ | Operational statement participating in the file's runtime behavior.
L0529 |         "No of Shelter Number", | Operational statement participating in the file's runtime behavior.
L0530 |         "Visible signs of leakage", | Operational statement participating in the file's runtime behavior.
L0531 |         "Openings/gaps in walls or roof", | Operational statement participating in the file's runtime behavior.
L0532 |         "If yes, seal all openings in wall with approvals", | Operational statement participating in the file's runtime behavior.
L0533 |         "No of Aircons in Shelter", | Operational statement participating in the file's runtime behavior.
L0534 |         "Are all Aircons in Shelter Functional", | Operational statement participating in the file's runtime behavior.
L0535 |         "Door Status", | Operational statement participating in the file's runtime behavior.
L0536 |         "Floor Status", | Operational statement participating in the file's runtime behavior.
L0537 |         "Roof Status", | Operational statement participating in the file's runtime behavior.
L0538 |         "Are all Shelter Lighting Working?", | Operational statement participating in the file's runtime behavior.
L0539 |     ], | Operational statement participating in the file's runtime behavior.
L0540 | }, | Operational statement participating in the file's runtime behavior.
L0541 | { | Block delimiter controlling scope/structure in this language.
L0542 |     "title": "SITE CLOSURE AFTER WORKS", | Operational statement participating in the file's runtime behavior.
L0543 |     "fields": [ | Operational statement participating in the file's runtime behavior.
L0544 |         "Have you logged out with Airtel NOC", | Operational statement participating in the file's runtime behavior.
L0545 |         "Is Gate Closed on Exit", | Operational statement participating in the file's runtime behavior.
L0546 |         "Is gate not closed because someone else is on site?", | Operational statement participating in the file's runtime behavior.
L0547 |     ], | Operational statement participating in the file's runtime behavior.
L0548 | }, | Operational statement participating in the file's runtime behavior.

```


L0549 |] | Operational statement participating in the file's runtime behavior.

L0550 | | Blank line used for readability and logical separation.

L0551 | TECHNICIAN_PHOTO_FIELDS = [| Assignment statement storing or updating program state.

L0552 | {"key": "site_signage_board", "label": "Site Signage Board"}, | Operational statement participating in the file's runtime behavior.

L0553 | {"key": "dg_closed_doors", "label": "Full view of DG Appearance, Closed doors"}, | Operational statement participating in the file's runtime behavior.

L0554 | {"key": "dg_open_doors", "label": "Full view DG Photo when Canopy doors open"}, | Operational statement participating in the file's runtime behavior.

L0555 | {"key": "dg_run_hours_photo", "label": "DG Run Hours Photo"}, | Operational statement participating in the file's runtime behavior.

L0556 | {"key": "dg_serial_number_photo", "label": "DG Serial Number Photo"}, | Operational statement participating in the file's runtime behavior.

L0557 | {"key": "clamped_ac_loads_photo", "label": "Clamped AC Loads Photo"}, | Operational statement participating in the file's runtime behavior.

L0558 | {"key": "starter_battery_photo", "label": "Starter Battery Photo"}, | Operational statement participating in the file's runtime behavior.

L0559 | {"key": "dg_engine_serial_number_photo", "label": "DG Engine Serial Number Photo"}, | Operational statement participating in the file's runtime behavior.

L0560 | {"key": "dg_battery_voltage_photo", "label": "DG battery Voltage Photo (When AC power off)"}, | Operational statement participating in the file's runtime behavior.

L0561 | {"key": "fixed_fan_belt_photo", "label": "Fixed Fan Belt Photo"}, | Operational statement participating in the file's runtime behavior.

L0562 | {"key": "old_fan_belt_photo", "label": "Old Fan Belt before replacement Photo"}, | Operational statement participating in the file's runtime behavior.

L0563 | {"key": "new_fan_belt_photo", "label": "New Fan Belt After Replacement Photo"}, | Operational statement participating in the file's runtime behavior.

L0564 | {"key": "coolant_poured_photo", "label": "Radiator Coolant been poured Photo"}, | Operational statement participating in the file's runtime behavior.

L0565 | {"key": "old_oil_filter_photo", "label": "Old Oil Filter on DG Photo"}, | Operational statement participating in the file's runtime behavior.

L0566 | {"key": "new_oil_filter_photo", "label": "New Oil Filter on DG Photo"}, | Operational statement participating in the file's runtime behavior.

L0567 | {"key": "old_fuel_filter_photo", "label": "Old Fuel Filter Photo"}, | Operational statement participating in the file's runtime behavior.

L0568 | {"key": "new_fuel_filter_photo", "label": "New Fuel Filter Photo"}, | Operational statement participating in the file's runtime behavior.

L0569 | {"key": "old_air_filter_photo", "label": "Old Air Filter"}, | Operational statement participating in the file's runtime behavior.

L0570 | {"key": "new_air_filter_photo", "label": "New Air Filter"}, | Operational statement participating in the file's runtime behavior.

L0571 | {"key": "updated_dg_service_card", "label": "Updated DG Service Card Photo"}, | Operational statement participating in the file's runtime behavior.

L0572 | {"key": "updated_fueling_card", "label": "Updated Fueling Card Photo"}, | Operational statement participating in the file's runtime behavior.

L0573 | {"key": "rectifier_settings", "label": "Rectifier settings Photos"}, | Operational statement participating in the file's runtime behavior.

L0574 | {"key": "fuel_leakage_signs", "label": "Signs of Fuel leakage along the DG"}, | Operational statement participating in the file's runtime behavior.

L0575 | {"key": "ats_installed_photo", "label": "ATS Installed Photo"}, | Operational statement participating in the file's runtime behavior.

L0576 | {"key": "acdb_photo", "label": "ACDB Photo"}, | Operational statement participating in the file's runtime behavior.

L0577 | {"key": "dg_v_ph1_ph2", "label": "DG Supply Voltage - Ph1 to Ph2 (V) Photo"}, | Operational statement participating in the file's runtime behavior.

L0578 | {"key": "dg_v_ph1_ph3", "label": "DG Supply Voltage - Ph1 to Ph3 (V) Photo"}, | Operational statement participating in the file's runtime behavior.

L0579 | {"key": "dg_v_ph2_ph3", "label": "DG Supply Voltage - Ph2 to Ph3 (V) Photo"}, | Operational statement participating in the file's runtime behavior.

L0580 | {"key": "dg_v_ph1_n", "label": "DG Supply Voltage - Ph1 to Neutral (V) Photo"}, | Operational statement participating in the file's runtime behavior.

L0581 | {"key": "dg_v_ph2_n", "label": "DG Supply Voltage - Ph2 to Neutral (V) Photo"}, | Operational statement participating in the file's runtime behavior.

L0582 | {"key": "dg_v_ph3_n", "label": "DG Supply Voltage - Ph3 to Neutral (V) Photo"}, | Operational statement participating in the file's runtime behavior.

L0583 | {"key": "dg_i_ph1", "label": "DG supply current - Ph1 Current (A) Photo"}, | Operational statement participating in the file's runtime behavior.

L0584 | {"key": "dg_i_ph2", "label": "DG supply current - Ph2 Current (A) Photo"}, | Operational statement participating in the file's runtime behavior.

L0585 | {"key": "dg_i_ph3", "label": "DG supply current - Ph3 Current (A) Photo"}, | Operational statement participating in the file's runtime behavior.

L0586 | {"key": "rectifier_closed", "label": "Full View Rectifier Cabinet Photo (CLOSED)"}, | Operational statement participating in the file's runtime behavior.

L0587 | {"key": "rectifier_open", "label": "Full View Rectifier Cabinet Photo (OPEN)"}, | Operational statement participating in the file's runtime behavior.

L0588 | {"key": "rectifier_controller", "label": "Rectifier Controller Photo"}, | Operational statement participating in the file's runtime behavior.

L0589 | {"key": "rectifier_slots", "label": "Number of rectifier module slots Photo"}, | Operational statement participating in the file's runtime behavior.

L0590 | {"key": "rectifier_cabinet_serial", "label": "Rectifier Cabinet Serial Number"}, | Operational statement participating in the file's runtime behavior.

L0591 | {"key": "rectifier_controller_serial", "label": "Rectifier Controller Serial Number"}, | Operational statement participating in the file's runtime behavior.

L0592 | {"key": "cleaning_modules", "label": "Photo when cleaning modules"}, | Operational statement participating in the file's runtime behavior.

L0593 | {"key": "system_voltage_photo", "label": "System Voltage Photo"}, | Operational statement participating in the file's runtime behavior.

L0594 | {"key": "hybrid_system_site", "label": "Hybrid System at Site"}, | Operational statement participating in the file's runtime behavior.

L0595 | {"key": "battery_bank_full_view", "label": "Battery Bank Full View Photo"}, | Operational statement participating in the file's runtime behavior.

L0596 | {"key": "battery_capacity_photo", "label": "Battery Capacity Photo"}, | Operational statement participating in the file's runtime behavior.

L0597 | {"key": "tower_full_photo", "label": "Tower Full Photo"}, | Operational statement participating in the file's runtime behavior.

L0598 | {"key": "tower_legs", "label": "Tower Legs 1,2,3,4"}, | Operational statement participating in the file's runtime behavior.

L0599 | {"key": "rectifier_photo", "label": "Rectifier"}, | Operational statement participating in the file's runtime behavior.

L0600 | {"key": "acdb_dcdb", "label": "ACDB, DCDB"}, | Operational statement participating in the file's runtime behavior.

L0601 | {"key": "dg_photo", "label": "DG"}, | Operational statement participating in the file's runtime behavior.

L0602 | {"key": "tenant_equipment", "label": "Tenant Equipment"}, | Operational statement participating in the file's runtime behavior.

L0603 | {"key": "shelter_interior", "label": "Shelter Interior After Cleaning"}, | Operational statement participating in the file's runtime behavior.

```

L0604 | {"key": "shelter_lighting", "label": "Shelter Lighting"}, | Operational statement participating in the file's runtime behavior.
L0605 | {"key": "shelter_door_status", "label": "Shelter Door status"}, | Operational statement participating in the file's runtime behavior.
L0606 | {"key": "bbs_door_status", "label": "BBS Door status"}, | Operational statement participating in the file's runtime behavior.
L0607 | {"key": "unused_equipment", "label": "Any unused Equipment on site"}, | Operational statement participating in the file's runtime behavior.
L0608 | {"key": "site_perimeter", "label": "Site Perimeter"}, | Operational statement participating in the file's runtime behavior.
L0609 | {"key": "site_janitorial", "label": "Site Janitorial"}, | Operational statement participating in the file's runtime behavior.
L0610 | {"key": "gate_lock", "label": "Gate Lock"}, | Operational statement participating in the file's runtime behavior.
L0611 | ] | Operational statement participating in the file's runtime behavior.
L0612 | | Blank line used for readability and logical separation.
L0613 | | Blank line used for readability and logical separation.
L0614 | def slugify_label(label): | Declares a function/method as a reusable unit of behavior.
L0615 |     cleaned = [ch.lower() if ch.isalnum() else "_" for ch in label] | Assignment statement storing or updating program state.
L0616 |     slug = "".join(cleaned) | Assignment statement storing or updating program state.
L0617 |     while "_" in slug: | Loop that repeats while its condition remains true.
L0618 |         slug = slug.replace("_", "-") | Assignment statement storing or updating program state.
L0619 |     return slug.strip("-") | Returns a value (or control) back to the caller.
L0620 | | Blank line used for readability and logical separation.
L0621 | | Blank line used for readability and logical separation.
L0622 | YES_NO_HINTS = ( | Assignment statement storing or updating program state.
L0623 |     "is ", | Operational statement participating in the file's runtime behavior.
L0624 |     "has ", | Operational statement participating in the file's runtime behavior.
L0625 |     "have ", | Operational statement participating in the file's runtime behavior.
L0626 |     "are ", | Operational statement participating in the file's runtime behavior.
L0627 |     "was ", | Operational statement participating in the file's runtime behavior.
L0628 |     "confirm", | Operational statement participating in the file's runtime behavior.
L0629 |     "working", | Operational statement participating in the file's runtime behavior.
L0630 |     "present", | Operational statement participating in the file's runtime behavior.
L0631 |     "connected", | Operational statement participating in the file's runtime behavior.
L0632 | ) | Operational statement participating in the file's runtime behavior.
L0633 | | Blank line used for readability and logical separation.
L0634 | | Blank line used for readability and logical separation.
L0635 | def is_yes_no_label(label): | Declares a function/method as a reusable unit of behavior.
L0636 |     value = label.strip().lower() | Assignment statement storing or updating program state.
L0637 |     return any(value.startswith(prefix) or prefix in value for prefix in YES_NO_HINTS) | Returns a value (or control) back to the caller.
L0638 | | Blank line used for readability and logical separation.
L0639 | | Blank line used for readability and logical separation.
L0640 | def save_signature_image(signature_data, upload_folder): | Declares a function/method as a reusable unit of behavior.
L0641 |     if not signature_data or not signature_data.startswith("data:image/png;base64,"): | Conditional branch that runs only when its condition is true.
L0642 |         return None | Returns a value (or control) back to the caller.
L0643 |     payload = signature_data.split(",", 1)[1] | Assignment statement storing or updating program state.
L0644 |     try: | Starts an exception handling block for risky operations.
L0645 |         image_bytes = base64.b64decode(payload) | Assignment statement storing or updating program state.
L0646 |     except Exception: | Handles errors raised in the associated try block.
L0647 |         return None | Returns a value (or control) back to the caller.
L0648 |     # Validate actual PNG magic bytes before writing to disk. | Comment line documenting intent or context for nearby code.
L0649 |     if not image_bytes[:8] == b'\x89PNG\r\n\x1a\n': | Conditional branch that runs only when its condition is true.
L0650 |         return None | Returns a value (or control) back to the caller.
L0651 |     filename = f"signature_{uuid.uuid4().hex}.png" | Assignment statement storing or updating program state.
L0652 |     file_path = os.path.join(upload_folder, filename) | Assignment statement storing or updating program state.
L0653 |     with open(file_path, "wb") as out_file: | Context manager block for safe setup and automatic cleanup.
L0654 |         out_file.write(image_bytes) | Operational statement participating in the file's runtime behavior.
L0655 |     return filename | Returns a value (or control) back to the caller.
L0656 | | Blank line used for readability and logical separation.
L0657 | def describe_uploaded_photo(field_label, filename): | Declares a function/method as a reusable unit of behavior.
L0658 |     safe_label = (field_label or "Uploaded photo").strip() | Assignment statement storing or updating program state.

```

```

L0659 |     raw_name = (filename or "").strip() | Assignment statement storing or updating program state.
L0660 |     lowered = raw_name.lower() | Assignment statement storing or updating program state.
L0661 | | Blank line used for readability and logical separation.
L0662 |     source_hint = "Uploaded camera image" | Assignment statement storing or updating program state.
L0663 |     if "screenshot" in lowered: | Conditional branch that runs only when its condition is true.
L0664 |         source_hint = "Mobile screenshot" | Assignment statement storing or updating program state.
L0665 |     elif "whatsapp" in lowered: | Conditional branch that runs only when its condition is true.
L0666 |         source_hint = "WhatsApp image" | Assignment statement storing or updating program state.
L0667 | | Blank line used for readability and logical separation.
L0668 |     context_hint = f"Evidence for {safe_label}." | Assignment statement storing or updating program state.
L0669 |     if any(token in lowered for token in ("chrome", "pdf", "download", "zoom", "viewer")): | Conditional branch that runs only when
L0670 |         context_hint = f"Evidence for {safe_label}; filename suggests a screen capture of a document or app view." | Assignment sta
L0671 | | Blank line used for readability and logical separation.
L0672 |     return f"{source_hint}. {context_hint}" | Returns a value (or control) back to the caller.
L0673 | | Blank line used for readability and logical separation.
L0674 | | Blank line used for readability and logical separation.
L0675 | PHOTO_LIBRARY_IMAGE_EXTENSIONS = {".png", ".jpg", ".jpeg", ".webp", ".gif"} | Assignment statement storing or updating program sta
L0676 | DEFAULT_PHOTO_LIBRARY_CONTROLS = { | Assignment statement storing or updating program state.
L0677 |     "include_screenshots": True, | Operational statement participating in the file's runtime behavior.
L0678 |     "allow_import": True, | Operational statement participating in the file's runtime behavior.
L0679 |     "max_scan_limit": 96, | Operational statement participating in the file's runtime behavior.
L0680 | } | Block delimiter controlling scope/structure in this language.
L0681 | | Blank line used for readability and logical separation.
L0682 | | Blank line used for readability and logical separation.
L0683 | def normalize_photo_library_controls(raw_controls): | Declares a function/method as a reusable unit of behavior.
L0684 |     controls = dict(DEFAULT_PHOTO_LIBRARY_CONTROLS) | Assignment statement storing or updating program state.
L0685 |     if not isinstance(raw_controls, dict): | Conditional branch that runs only when its condition is true.
L0686 |         return controls | Returns a value (or control) back to the caller.
L0687 | | Blank line used for readability and logical separation.
L0688 |     include_screenshots = raw_controls.get("include_screenshots") | Assignment statement storing or updating program state.
L0689 |     if isinstance(include_screenshots, bool): | Conditional branch that runs only when its condition is true.
L0690 |         controls["include_screenshots"] = include_screenshots | Assignment statement storing or updating program state.
L0691 | | Blank line used for readability and logical separation.
L0692 |     allow_import = raw_controls.get("allow_import") | Assignment statement storing or updating program state.
L0693 |     if isinstance(allow_import, bool): | Conditional branch that runs only when its condition is true.
L0694 |         controls["allow_import"] = allow_import | Assignment statement storing or updating program state.
L0695 | | Blank line used for readability and logical separation.
L0696 |     try: | Starts an exception handling block for risky operations.
L0697 |         max_scan_limit = int(raw_controls.get("max_scan_limit", controls["max_scan_limit"])) | Assignment statement storing or upda
L0698 |     except (TypeError, ValueError): | Handles errors raised in the associated try block.
L0699 |         max_scan_limit = controls["max_scan_limit"] | Assignment statement storing or updating program state.
L0700 |     controls["max_scan_limit"] = min(max(max_scan_limit, 12), 200) | Assignment statement storing or updating program state.
L0701 |     return controls | Returns a value (or control) back to the caller.
L0702 | | Blank line used for readability and logical separation.
L0703 | | Blank line used for readability and logical separation.
L0704 | def describe_monitored_image(file_path, filename): | Declares a function/method as a reusable unit of behavior.
L0705 |     raw_name = (filename or "").strip() | Assignment statement storing or updating program state.
L0706 |     lowered = raw_name.lower() | Assignment statement storing or updating program state.
L0707 | | Blank line used for readability and logical separation.
L0708 |     if not _is_valid_image_file_path(file_path): | Conditional branch that runs only when its condition is true.
L0709 |         return "File failed image validation checks and may be corrupted or not an image." | Returns a value (or control) back to t
L0710 | | Blank line used for readability and logical separation.
L0711 |     width = None | Assignment statement storing or updating program state.
L0712 |     height = None | Assignment statement storing or updating program state.
L0713 |     fmt = "unknown" | Assignment statement storing or updating program state.

```

```

L0714 |     mode = "unknown" | Assignment statement storing or updating program state.
L0715 |     if Image is not None: | Conditional branch that runs only when its condition is true.
L0716 |         try: | Starts an exception handling block for risky operations.
L0717 |             with Image.open(file_path) as img: | Context manager block for safe setup and automatic cleanup.
L0718 |                 width, height = img.size | Assignment statement storing or updating program state.
L0719 |                 fmt = (img.format or "unknown").upper() | Assignment statement storing or updating program state.
L0720 |                 mode = (img.mode or "unknown").upper() | Assignment statement storing or updating program state.
L0721 |             except Exception: | Handles errors raised in the associated try block.
L0722 |                 pass | Flow-control keyword affecting execution in the current block.
L0723 | | Blank line used for readability and logical separation.
L0724 |     if width and height: | Conditional branch that runs only when its condition is true.
L0725 |         megapixels = round((width * height) / 1_000_000, 2) | Assignment statement storing or updating program state.
L0726 |         orientation = "portrait" if height > width else "landscape" | Assignment statement storing or updating program state.
L0727 |         metadata_line = f"{fmt} image, {width}x{height}px ({megapixels} MP), {orientation}, mode {mode}." | Assignment statement storing or updating program state.
L0728 |     else: | Fallback branch executed when prior conditions are false.
L0729 |         metadata_line = "Image metadata could not be read fully; file passed basic validation checks." | Assignment statement storing or updating program state.
L0730 | | Blank line used for readability and logical separation.
L0731 |     screenshot_signals = ["screenshot", "chrome", "pdf", "download", "viewer", "zoom"] | Assignment statement storing or updating program state.
L0732 |     if any(token in lowered for token in screenshot_signals): | Conditional branch that runs only when its condition is true.
L0733 |         return metadata_line + " Likely screenshot or document-view capture based on filename cues." | Returns a value (or control) back to the caller.
L0734 |     if "whatsapp image" in lowered: | Conditional branch that runs only when its condition is true.
L0735 |         return metadata_line + " WhatsApp-exported image; verify whether it is a camera photo or forwarded screenshot." | Returns a value (or control) back to the caller.
L0736 |     if any(token in lowered for token in ("tower", "battery", "rectifier", "dg", "generator", "site", "acdb")): | Conditional branch that runs only when its condition is true.
L0737 |         return metadata_line + " Filename suggests field maintenance evidence." | Returns a value (or control) back to the caller.
L0738 |     return metadata_line + " Monitored image from the photo source." | Returns a value (or control) back to the caller.
L0739 | | Blank line used for readability and logical separation.
L0740 | | Blank line used for readability and logical separation.
L0741 | def collect_technician_form_details(form_data): | Declares a function/method as a reusable unit of behavior.
L0742 |     lines = [] | Assignment statement storing or updating program state.
L0743 |     header_pairs = [ | Assignment statement storing or updating program state.
L0744 |         ("Client", "AIRTEL UGANDA"), | Operational statement participating in the file's runtime behavior.
L0745 |         ("Vendor", "SOLITON TELMEC (U) LTD"), | Operational statement participating in the file's runtime behavior.
L0746 |         ("Activity Name", "AIRTEL UG Planned Preventive Maintenance Form"), | Operational statement participating in the file's runtime behavior.
L0747 |         ("Submitted By", form_data.get("submitted_by") or ""), | Operational statement participating in the file's runtime behavior.
L0748 |         ("Activity Start", form_data.get("activity_start") or ""), | Operational statement participating in the file's runtime behavior.
L0749 |         ("Activity End", form_data.get("activity_end") or ""), | Operational statement participating in the file's runtime behavior.
L0750 |         ("Validation Comments (By Technician)", form_data.get("validation_comments") or ""), | Operational statement participating in the file's runtime behavior.
L0751 |     ] | Operational statement participating in the file's runtime behavior.
L0752 | | Blank line used for readability and logical separation.
L0753 |     lines.append("PM FORM HEADER") | Operational statement participating in the file's runtime behavior.
L0754 |     for label, value in header_pairs: | Loop iterating over a sequence to process elements one by one.
L0755 |         lines.append(f"{label}: {value}") | Operational statement participating in the file's runtime behavior.
L0756 | | Blank line used for readability and logical separation.
L0757 |     for section in TECHNICIAN_PM_SECTIONS: | Loop iterating over a sequence to process elements one by one.
L0758 |         lines.append("") | Operational statement participating in the file's runtime behavior.
L0759 |         lines.append(section["title"]) | Operational statement participating in the file's runtime behavior.
L0760 |         for label in section["fields"]: | Loop iterating over a sequence to process elements one by one.
L0761 |             key = f"field_{slugify(label)}" | Assignment statement storing or updating program state.
L0762 |             lines.append(f"- {label}: {form_data.get(key, '')}") | Operational statement participating in the file's runtime behavior.
L0763 | | Blank line used for readability and logical separation.
L0764 |     return "\n".join(lines) | Returns a value (or control) back to the caller.
L0765 | | Blank line used for readability and logical separation.
L0766 | | Blank line used for readability and logical separation.
L0767 | def parse_activity_kv(details_text): | Declares a function/method as a reusable unit of behavior.
L0768 |     values = {} | Assignment statement storing or updating program state.

```

```

L0769 |     for raw_line in (details_text or "").splitlines(): | Loop iterating over a sequence to process elements one by one.
L0770 |         line = raw_line.strip() | Assignment statement storing or updating program state.
L0771 |         if not line: | Conditional branch that runs only when its condition is true.
L0772 |             continue | Flow-control keyword affecting execution in the current block.
L0773 |         if line.startswith("- "): | Conditional branch that runs only when its condition is true.
L0774 |             line = line[2:].strip() | Assignment statement storing or updating program state.
L0775 |         if ":" not in line: | Conditional branch that runs only when its condition is true.
L0776 |             continue | Flow-control keyword affecting execution in the current block.
L0777 |         key, value = line.split(":", 1) | Assignment statement storing or updating program state.
L0778 |         values[key.strip().lower()] = value.strip() | Assignment statement storing or updating program state.
L0779 |     return values | Returns a value (or control) back to the caller.
L0780 | | Blank line used for readability and logical separation.
L0781 | | Blank line used for readability and logical separation.
L0782 | def parse_float_value(value): | Declares a function/method as a reusable unit of behavior.
L0783 |     if value is None: | Conditional branch that runs only when its condition is true.
L0784 |         return None | Returns a value (or control) back to the caller.
L0785 |     cleaned = str(value).strip().replace(",", "") | Assignment statement storing or updating program state.
L0786 |     if not cleaned: | Conditional branch that runs only when its condition is true.
L0787 |         return None | Returns a value (or control) back to the caller.
L0788 |     try: | Starts an exception handling block for risky operations.
L0789 |         return float(cleaned) | Returns a value (or control) back to the caller.
L0790 |     except ValueError: | Handles errors raised in the associated try block.
L0791 |         return None | Returns a value (or control) back to the caller.
L0792 | | Blank line used for readability and logical separation.
L0793 | | Blank line used for readability and logical separation.
L0794 | def extract_metric_from_details(details_text, metric_label): | Declares a function/method as a reusable unit of behavior.
L0795 |     values = parse_activity_kv(details_text) | Assignment statement storing or updating program state.
L0796 |     return parse_float_value(values.get(metric_label.lower())) | Returns a value (or control) back to the caller.
L0797 | | Blank line used for readability and logical separation.
L0798 | | Blank line used for readability and logical separation.
L0799 | def extract_risk_score_from_details(details_text): | Declares a function/method as a reusable unit of behavior.
L0800 |     match = re.search(r"Risk Score:\s*(\d{1,3})", details_text or "", flags=re.IGNORECASE) | Assignment statement storing or updating program state.
L0801 |     if not match: | Conditional branch that runs only when its condition is true.
L0802 |         return None | Returns a value (or control) back to the caller.
L0803 |     try: | Starts an exception handling block for risky operations.
L0804 |         return max(0, min(100, int(match.group(1)))) | Returns a value (or control) back to the caller.
L0805 |     except ValueError: | Handles errors raised in the associated try block.
L0806 |         return None | Returns a value (or control) back to the caller.
L0807 | | Blank line used for readability and logical separation.
L0808 | | Blank line used for readability and logical separation.
L0809 | def extract_sla_deadline_from_details(details_text): | Declares a function/method as a reusable unit of behavior.
L0810 |     match = re.search(r"SLA Deadline \(\UTC\):\s*([0-9\-: TZ]+)", details_text or "", flags=re.IGNORECASE) | Assignment statement storing or updating program state.
L0811 |     if not match: | Conditional branch that runs only when its condition is true.
L0812 |         return None | Returns a value (or control) back to the caller.
L0813 |     raw_value = match.group(1).strip().replace("Z", "") | Assignment statement storing or updating program state.
L0814 |     try: | Starts an exception handling block for risky operations.
L0815 |         return datetime.fromisoformat(raw_value) | Returns a value (or control) back to the caller.
L0816 |     except ValueError: | Handles errors raised in the associated try block.
L0817 |         return None | Returns a value (or control) back to the caller.
L0818 | | Blank line used for readability and logical separation.
L0819 | | Blank line used for readability and logical separation.
L0820 | def extract_site_number_from_details(details_text): | Declares a function/method as a reusable unit of behavior.
L0821 |     values = parse_activity_kv(details_text) | Assignment statement storing or updating program state.
L0822 |     return values.get("site number") or values.get("site id") | Returns a value (or control) back to the caller.
L0823 | | Blank line used for readability and logical separation.

```

```
L0824 | | Blank line used for readability and logical separation.
L0825 | def extract_recommendations_from_details(details_text): | Declares a function/method as a reusable unit of behavior.
L0826 |     recommendations = [] | Assignment statement storing or updating program state.
L0827 |     in_section = False | Assignment statement storing or updating program state.
L0828 |     for raw_line in (details_text or "").splitlines(): | Loop iterating over a sequence to process elements one by one.
L0829 |         line = raw_line.strip() | Assignment statement storing or updating program state.
L0830 |         if line.lower() in {"recommendations:", "recommendation:"}: | Conditional branch that runs only when its condition is true.
L0831 |             in_section = True | Assignment statement storing or updating program state.
L0832 |             continue | Flow-control keyword affecting execution in the current block.
L0833 |         if in_section: | Conditional branch that runs only when its condition is true.
L0834 |             if not line: | Conditional branch that runs only when its condition is true.
L0835 |                 break | Flow-control keyword affecting execution in the current block.
L0836 |             # Stop if we reached a new section header in free-text details. | Comment line documenting intent or context for nearby
L0837 |             if line.endswith(":") and not line.startswith("- "): | Conditional branch that runs only when its condition is true.
L0838 |                 break | Flow-control keyword affecting execution in the current block.
L0839 |             if line.startswith("- "): | Conditional branch that runs only when its condition is true.
L0840 |                 item = line[2:].strip() | Assignment statement storing or updating program state.
L0841 |             else: | Fallback branch executed when prior conditions are false.
L0842 |                 item = line | Assignment statement storing or updating program state.
L0843 |             if item and item.lower() not in {"none", "n/a", "no recommendation", "no recommendations"}: | Conditional branch that r
L0844 |                 recommendations.append(item) | Operational statement participating in the file's runtime behavior.
L0845 |     return recommendations | Returns a value (or control) back to the caller.
L0846 | | Blank line used for readability and logical separation.
L0847 | | Blank line used for readability and logical separation.
L0848 | _OUTAGE_SIGNAL_RULES = [ | Assignment statement storing or updating program state.
L0849 |     { | Block delimiter controlling scope/structure in this language.
L0850 |         "name": "site_down", | Operational statement participating in the file's runtime behavior.
L0851 |         "terms": ("site down", "network down", "outage", "off air", "no service", "link down", "total blackout"), | Operational sta
L0852 |         "score": 26, | Operational statement participating in the file's runtime behavior.
L0853 |         "critical": True, | Operational statement participating in the file's runtime behavior.
L0854 |         "flag": "Network/site outage reported", | Operational statement participating in the file's runtime behavior.
L0855 |         "recommendation": "Escalate immediate outage response with NOC and field teams.", | Operational statement participating in
L0856 |     }, | Operational statement participating in the file's runtime behavior.
L0857 |     { | Block delimiter controlling scope/structure in this language.
L0858 |         "name": "power_loss", | Operational statement participating in the file's runtime behavior.
L0859 |         "terms": ("no power", "power failure", "blackout", "mains down", "grid down"), | Operational statement participating in the
L0860 |         "score": 18, | Operational statement participating in the file's runtime behavior.
L0861 |         "critical": True, | Operational statement participating in the file's runtime behavior.
L0862 |         "flag": "Power outage indicators detected", | Operational statement participating in the file's runtime behavior.
L0863 |         "recommendation": "Prioritize power restoration checks and generator failover validation.", | Operational statement parti
L0864 |     }, | Operational statement participating in the file's runtime behavior.
L0865 |     { | Block delimiter controlling scope/structure in this language.
L0866 |         "name": "service_degradation", | Operational statement participating in the file's runtime behavior.
L0867 |         "terms": ("degraded", "intermittent", "flapping", "unstable", "packet loss", "high latency"), | Operational statement parti
L0868 |         "score": 10, | Operational statement participating in the file's runtime behavior.
L0869 |         "critical": False, | Operational statement participating in the file's runtime behavior.
L0870 |         "flag": "Service degradation indicators detected", | Operational statement participating in the file's runtime behavior.
L0871 |         "recommendation": "Capture service quality evidence and investigate recurring degradation trends.", | Operational statement
L0872 |     }, | Operational statement participating in the file's runtime behavior.
L0873 |     { | Block delimiter controlling scope/structure in this language.
L0874 |         "name": "alarm_pressure", | Operational statement participating in the file's runtime behavior.
L0875 |         "terms": ("critical alarm", "major alarm", "multiple alarms", "alarm flood"), | Operational statement participating in the
L0876 |         "score": 12, | Operational statement participating in the file's runtime behavior.
L0877 |         "critical": False, | Operational statement participating in the file's runtime behavior.
L0878 |         "flag": "High alarm pressure reported", | Operational statement participating in the file's runtime behavior.
```

```

L0879 |         "recommendation": "Correlate alarms with root cause and clear non-actionable noise.", | Operational statement participating
L0880 |     }, | Operational statement participating in the file's runtime behavior.
L0881 | ] | Operational statement participating in the file's runtime behavior.
L0882 | | Blank line used for readability and logical separation.
L0883 | | Blank line used for readability and logical separation.
L0884 | def analyze_outage_signals(free_text: str \ None): | Declares a function/method as a reusable unit of behavior.
L0885 |     text = (free_text or "").lower().strip() | Assignment statement storing or updating program state.
L0886 |     if not text: | Conditional branch that runs only when its condition is true.
L0887 |         return { | Returns a value (or control) back to the caller.
L0888 |             "matched_signals": [], | Operational statement participating in the file's runtime behavior.
L0889 |             "risk_boost": 0, | Operational statement participating in the file's runtime behavior.
L0890 |             "critical_flags": [], | Operational statement participating in the file's runtime behavior.
L0891 |             "recommendations": [], | Operational statement participating in the file's runtime behavior.
L0892 |         } | Block delimiter controlling scope/structure in this language.
L0893 | | Blank line used for readability and logical separation.
L0894 |     matched_signals = [] | Assignment statement storing or updating program state.
L0895 |     critical_flags = [] | Assignment statement storing or updating program state.
L0896 |     recommendations = [] | Assignment statement storing or updating program state.
L0897 |     risk_boost = 0 | Assignment statement storing or updating program state.
L0898 | | Blank line used for readability and logical separation.
L0899 |     for rule in _OUTAGE_SIGNAL_RULES: | Loop iterating over a sequence to process elements one by one.
L0900 |         if any(term in text for term in rule["terms"]): | Conditional branch that runs only when its condition is true.
L0901 |             matched_signals.append(rule["name"]) | Operational statement participating in the file's runtime behavior.
L0902 |             risk_boost += int(rule["score"]) | Assignment statement storing or updating program state.
L0903 |             if rule["critical"]: | Conditional branch that runs only when its condition is true.
L0904 |                 critical_flags.append(rule["flag"]) | Operational statement participating in the file's runtime behavior.
L0905 |                 recommendations.append(rule["recommendation"]) | Operational statement participating in the file's runtime behavior.
L0906 | | Blank line used for readability and logical separation.
L0907 |     # Keep text-derived boosts bounded to avoid dwarfing hard-validated checks. | Comment line documenting intent or context for ne
L0908 |     risk_boost = min(40, risk_boost) | Assignment statement storing or updating program state.
L0909 |     return { | Returns a value (or control) back to the caller.
L0910 |         "matched_signals": matched_signals, | Operational statement participating in the file's runtime behavior.
L0911 |         "risk_boost": risk_boost, | Operational statement participating in the file's runtime behavior.
L0912 |         "critical_flags": critical_flags, | Operational statement participating in the file's runtime behavior.
L0913 |         "recommendations": recommendations, | Operational statement participating in the file's runtime behavior.
L0914 |     } | Block delimiter controlling scope/structure in this language.
L0915 | | Blank line used for readability and logical separation.
L0916 | | Blank line used for readability and logical separation.
L0917 | def classify_risk_level(score): | Declares a function/method as a reusable unit of behavior.
L0918 |     if score >= HIGH_RISK_THRESHOLD: | Conditional branch that runs only when its condition is true.
L0919 |         return "High" | Returns a value (or control) back to the caller.
L0920 |     if score >= MEDIUM_RISK_THRESHOLD: | Conditional branch that runs only when its condition is true.
L0921 |         return "Medium" | Returns a value (or control) back to the caller.
L0922 |     return "Low" | Returns a value (or control) back to the caller.
L0923 | | Blank line used for readability and logical separation.
L0924 | | Blank line used for readability and logical separation.
L0925 | def derive_sla_suggestion(sla_state: str, risk_level: str) -> str: | Declares a function/method as a reusable unit of behavior.
L0926 |     state = (sla_state or "").strip().lower() | Assignment statement storing or updating program state.
L0927 |     risk = (risk_level or "").strip().lower() | Assignment statement storing or updating program state.
L0928 | | Blank line used for readability and logical separation.
L0929 |     if state == "overdue": | Conditional branch that runs only when its condition is true.
L0930 |         if risk == "high": | Conditional branch that runs only when its condition is true.
L0931 |             return "SLA breached: escalate immediately with NOC and dispatch field remediation." | Returns a value (or control) bac
L0932 |             return "SLA breached: prioritize this item for same-day review and corrective action." | Returns a value (or control) back
L0933 |         if state == "due soon": | Conditional branch that runs only when its condition is true.

```

```

L0934 |         if risk == "high": | Conditional branch that runs only when its condition is true.
L0935 |             return "SLA due soon on high risk: fast-track approvals and mitigation before deadline." | Returns a value (or control)
L0936 |             return "SLA due soon: complete pending checks and close action items ahead of deadline." | Returns a value (or control) bac
L0937 |         if state == "on track": | Conditional branch that runs only when its condition is true.
L0938 |             return "SLA is on track: continue monitoring and keep evidence complete for closure." | Returns a value (or control) back t
L0939 |         if state == "resolved": | Conditional branch that runs only when its condition is true.
L0940 |             return "SLA resolved: document closure notes and preventive follow-up actions." | Returns a value (or control) back to the
L0941 |         return "SLA not set: assign a deadline based on risk and operational impact." | Returns a value (or control) back to the caller
L0942 | | Blank line used for readability and logical separation.
L0943 | _ROLE_UID_PREFIX = { | Assignment statement storing or updating program state.
L0944 |     "developer": "DEV", | Operational statement participating in the file's runtime behavior.
L0945 |     "technician": "TEC", | Operational statement participating in the file's runtime behavior.
L0946 |     "staff": "STF", | Operational statement participating in the file's runtime behavior.
L0947 |     "manager": "MGR", | Operational statement participating in the file's runtime behavior.
L0948 |     "general_manager": "GMR", | Operational statement participating in the file's runtime behavior.
L0949 | } | Block delimiter controlling scope/structure in this language.
L0950 | | Blank line used for readability and logical separation.
L0951 | def generate_uid(role: str) -> str: | Declares a function/method as a reusable unit of behavior.
L0952 |     """Return a unique role-prefixed ID like TEC-007.""" | Docstring boundary used to describe a module, class, or function.
L0953 |     prefix = _ROLE_UID_PREFIX.get(role, "USR") | Assignment statement storing or updating program state.
L0954 |     # count existing users with the same role prefix to get next number | Comment line documenting intent or context for nearby code
L0955 |     count = User.query.filter_by(role=role).count() + 1 | Assignment statement storing or updating program state.
L0956 |     candidate = f"{prefix}-{count:03d}" | Assignment statement storing or updating program state.
L0957 |     # keep incrementing if somehow taken | Comment line documenting intent or context for nearby code.
L0958 |     while User.query.filter_by(uid=candidate).first(): | Loop that repeats while its condition remains true.
L0959 |         count += 1 | Assignment statement storing or updating program state.
L0960 |         candidate = f"{prefix}-{count:03d}" | Assignment statement storing or updating program state.
L0961 |     return candidate | Returns a value (or control) back to the caller.
L0962 | | Blank line used for readability and logical separation.
L0963 | | Blank line used for readability and logical separation.
L0964 | def generate_temporary_password(length: int = 12) -> str: | Declares a function/method as a reusable unit of behavior.
L0965 |     alphabet = "ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz23456789!@#%$" | Assignment statement storing or updating program
L0966 |     return "".join(secrets.choice(alphabet) for _ in range(length)) | Returns a value (or control) back to the caller.
L0967 | | Blank line used for readability and logical separation.
L0968 | | Blank line used for readability and logical separation.
L0969 | def store_issued_credentials( | Declares a function/method as a reusable unit of behavior.
L0970 |     user: User, | Operational statement participating in the file's runtime behavior.
L0971 |     password: str, | Operational statement participating in the file's runtime behavior.
L0972 |     action: str, | Operational statement participating in the file's runtime behavior.
L0973 |     *, | Operational statement participating in the file's runtime behavior.
L0974 |     previous_password: str \ | None = None, | Assignment statement storing or updating program state.
L0975 |     is_generated: bool = False, | Assignment statement storing or updating program state.
L0976 | ) -> None: | Operational statement participating in the file's runtime behavior.
L0977 |     """Store credentials server-side (not in the cookie) and put only a | Docstring boundary used to describe a module, class, or f
L0978 |     short-lived token in the session so the password never travels to | Operational statement participating in the file's runtime b
L0979 |     the browser as plaintext.""" | Operational statement participating in the file's runtime behavior.
L0980 |     token = secrets.token_urlsafe(16) | Assignment statement storing or updating program state.
L0981 |     # Prune expired entries before adding a new one. | Comment line documenting intent or context for nearby code.
L0982 |     now_ts = _time.time() | Assignment statement storing or updating program state.
L0983 |     expired_keys = [k for k, v in list(_pending_creds.items()) if v.get("_exp", 0) < now_ts] | Assignment statement storing or upda
L0984 |     for k in expired_keys: | Loop iterating over a sequence to process elements one by one.
L0985 |         _pending_creds.pop(k, None) | Operational statement participating in the file's runtime behavior.
L0986 |     _pending_creds[token] = { | Assignment statement storing or updating program state.
L0987 |         "action": action, | Operational statement participating in the file's runtime behavior.
L0988 |         "display_name": user.display_name, | Operational statement participating in the file's runtime behavior.

```



```

L0989 |         "email": user.email, | Operational statement participating in the file's runtime behavior.
L0990 |         "uid": user.uid or "", | Operational statement participating in the file's runtime behavior.
L0991 |         "role": user.role.replace("_", " ").title(), | Operational statement participating in the file's runtime behavior.
L0992 |         "password": password, | Operational statement participating in the file's runtime behavior.
L0993 |         "previous_password": previous_password, | Operational statement participating in the file's runtime behavior.
L0994 |         "is_generated": bool(is_generated), | Operational statement participating in the file's runtime behavior.
L0995 |         "issued_at": utcnow_naive().strftime("%Y-%m-%d %H:%M:%S UTC"), | Operational statement participating in the file's runtime
L0996 |         "_exp": now_ts + 300, # 5-minute TTL | Operational statement participating in the file's runtime behavior.
L0997 |     } | Block delimiter controlling scope/structure in this language.
L0998 |     session["creds_token"] = token | Assignment statement storing or updating program state.
L0999 | | Blank line used for readability and logical separation.
L1000 | | Blank line used for readability and logical separation.
L1001 | def apply_user_search(query): | Declares a function/method as a reusable unit of behavior.
L1002 |     search_query = (query or "").strip()[:100] # cap at 100 chars to prevent DoS via huge LIKE patterns | Assignment statement storing or updating program state.
L1003 |     users_query = User.query | Assignment statement storing or updating program state.
L1004 |     if search_query: | Conditional branch that runs only when its condition is true.
L1005 |         like = f"%{search_query}%" | Assignment statement storing or updating program state.
L1006 |         users_query = users_query.filter( | Assignment statement storing or updating program state.
L1007 |             or_( | Operational statement participating in the file's runtime behavior.
L1008 |                 User.uid.ilike(like), | Operational statement participating in the file's runtime behavior.
L1009 |                 User.email.ilike(like), | Operational statement participating in the file's runtime behavior.
L1010 |                 User.full_name.ilike(like), | Operational statement participating in the file's runtime behavior.
L1011 |                 User.first_name.ilike(like), | Operational statement participating in the file's runtime behavior.
L1012 |                 User.last_name.ilike(like), | Operational statement participating in the file's runtime behavior.
L1013 |                 User.region.ilike(like), | Operational statement participating in the file's runtime behavior.
L1014 |                 User.role.ilike(like), | Operational statement participating in the file's runtime behavior.
L1015 |             ) | Operational statement participating in the file's runtime behavior.
L1016 |         ) | Operational statement participating in the file's runtime behavior.
L1017 |     page = max(1, request.args.get("page", 1, type=int)) | Assignment statement storing or updating program state.
L1018 |     per_page = min(max(10, request.args.get("per_page", 24, type=int)), 100) | Assignment statement storing or updating program state.
L1019 |     pagination = users_query.order_by(User.created_at.desc(), User.id.desc()).paginate( | Assignment statement storing or updating program state.
L1020 |         page=page, | Assignment statement storing or updating program state.
L1021 |         per_page=per_page, | Assignment statement storing or updating program state.
L1022 |         error_out=False, | Assignment statement storing or updating program state.
L1023 |     ) | Operational statement participating in the file's runtime behavior.
L1024 |     users = pagination.items | Assignment statement storing or updating program state.
L1025 |     grouped = {} | Assignment statement storing or updating program state.
L1026 |     for user in users: | Loop iterating over a sequence to process elements one by one.
L1027 |         grouped.setdefault(user.role, []).append(user) | Operational statement participating in the file's runtime behavior.
L1028 |     return search_query, users, grouped, pagination | Returns a value (or control) back to the caller.
L1029 | | Blank line used for readability and logical separation.
L1030 | | Blank line used for readability and logical separation.
L1031 | def create_app(test_config=None): # noqa: C901 | Declares a function/method as a reusable unit of behavior.
L1032 |     app = Flask(__name__, template_folder="templates", static_folder="static") | Assignment statement storing or updating program state.
L1033 |     test_config = dict(test_config or {}) | Assignment statement storing or updating program state.
L1034 |     is_testing = bool(test_config.get("TESTING")) | Assignment statement storing or updating program state.
L1035 |     app_env = str(test_config.get("APP_ENV") or os.getenv("APP_ENV") or os.getenv("ENV") or "development").strip().lower() | Assignment statement storing or updating program state.
L1036 |     if app_env not in {"development", "staging", "production"}: | Conditional branch that runs only when its condition is true.
L1037 |         app_env = "development" | Assignment statement storing or updating program state.
L1038 |     os.makedirs(app.instance_path, exist_ok=True) | Assignment statement storing or updating program state.
L1039 | | Blank line used for readability and logical separation.
L1040 |     database_url = (test_config.get("SQLALCHEMY_DATABASE_URI") or os.getenv("DATABASE_URL") or "").strip() | Assignment statement storing or updating program state.
L1041 |     dev_database_url = (test_config.get("DEV_DATABASE_URL") or os.getenv("DEV_DATABASE_URL") or "").strip() | Assignment statement storing or updating program state.
L1042 |     if not database_url: | Conditional branch that runs only when its condition is true.
L1043 |         if is_testing: | Conditional branch that runs only when its condition is true.

```

```

L1044 |         database_url = "sqlite:/// " + os.path.join(app.instance_path, "test_pm.sqlite") | Assignment statement storing or updating program state.
L1045 |     elif app_env in {"development", "staging"}: | Conditional branch that runs only when its condition is true.
L1046 |         # Local-first default: keep development self-contained unless DATABASE_URL is explicitly set. | Comment line documenting intent or context for nearb
L1047 |         database_url = dev_database_url or ("sqlite:/// " + os.path.join(app.instance_path, "dev_pm.sqlite")) | Assignment statement storing or updating program state.
L1048 |     else: | Fallback branch executed when prior conditions are false.
L1049 |         raise RuntimeError( | Raises an explicit exception to signal an error condition.
L1050 |             "DATABASE_URL is required in production. Configure a PostgreSQL URL, for example: " | Operational statement participating in the file's runtime behavior.
L1051 |             "postgresql+psycpg://postgres:password@localhost:5432/pm_db" | Operational statement participating in the file's runtime behavior.
L1052 |         ) | Operational statement participating in the file's runtime behavior.
L1053 | | Blank line used for readability and logical separation.
L1054 |     # Some hosts provide postgres:// which SQLAlchemy 2 expects as postgresql:// | Comment line documenting intent or context for nearb
L1055 |     if database_url.startswith("postgres://"): | Conditional branch that runs only when its condition is true.
L1056 |         database_url = database_url.replace("postgres://", "postgresql://", 1) | Assignment statement storing or updating program state.
L1057 | | Blank line used for readability and logical separation.
L1058 |     # Prefer psycpg v3 driver when a PostgreSQL URL has no explicit driver. | Comment line documenting intent or context for nearb
L1059 |     if ( | Conditional branch that runs only when its condition is true.
L1060 |         database_url.startswith("postgresql://") | Operational statement participating in the file's runtime behavior.
L1061 |         and "+psycpg" not in database_url | Operational statement participating in the file's runtime behavior.
L1062 |         and "+psycpg2" not in database_url | Operational statement participating in the file's runtime behavior.
L1063 |     ): | Operational statement participating in the file's runtime behavior.
L1064 |         database_url = database_url.replace("postgresql://", "postgresql+psycpg://", 1) | Assignment statement storing or updating program state.
L1065 | | Blank line used for readability and logical separation.
L1066 |     if not is_testing and app_env == "production" and not database_url.startswith("postgresql+psycpg://"): | Conditional branch that runs only when its condition is true.
L1067 |         raise RuntimeError( | Raises an explicit exception to signal an error condition.
L1068 |             "Production requires PostgreSQL with psycpg. Set DATABASE_URL to " | Operational statement participating in the file's runtime behavior.
L1069 |             "postgresql+psycpg://..." | Operational statement participating in the file's runtime behavior.
L1070 |         ) | Operational statement participating in the file's runtime behavior.
L1071 | | Blank line used for readability and logical separation.
L1072 |     app.config["SQLALCHEMY_DATABASE_URI"] = database_url | Assignment statement storing or updating program state.
L1073 |     app.config["SQLALCHEMY_TRACK_MODIFICATIONS"] = False | Assignment statement storing or updating program state.
L1074 |     app.config["SQLALCHEMY_ENGINE_OPTIONS"] = { | Assignment statement storing or updating program state.
L1075 |         "pool_pre_ping": True, | Operational statement participating in the file's runtime behavior.
L1076 |         "pool_recycle": 1800, | Operational statement participating in the file's runtime behavior.
L1077 |     } | Block delimiter controlling scope/structure in this language.
L1078 |     secret_key = (test_config.get("SECRET_KEY") or os.getenv("SECRET_KEY") or "").strip() | Assignment statement storing or updating program state.
L1079 |     if not secret_key: | Conditional branch that runs only when its condition is true.
L1080 |         if is_testing: | Conditional branch that runs only when its condition is true.
L1081 |             secret_key = "test-secret-key" | Assignment statement storing or updating program state.
L1082 |         else: | Fallback branch executed when prior conditions are false.
L1083 |             raise RuntimeError( | Raises an explicit exception to signal an error condition.
L1084 |                 "SECRET_KEY is required. Set a strong random value in .env, e.g.: " | Operational statement participating in the file's runtime behavior.
L1085 |                 "SECRET_KEY=" + secrets.token_hex(32) | Assignment statement storing or updating program state.
L1086 |             ) | Operational statement participating in the file's runtime behavior.
L1087 |     if not is_testing and app_env == "production": | Conditional branch that runs only when its condition is true.
L1088 |         lowered_secret = secret_key.lower() | Assignment statement storing or updating program state.
L1089 |         weak_secret_markers = ( | Assignment statement storing or updating program state.
L1090 |             "change-me", | Operational statement participating in the file's runtime behavior.
L1091 |             "changeme", | Operational statement participating in the file's runtime behavior.
L1092 |             "dev-secret", | Operational statement participating in the file's runtime behavior.
L1093 |             "test-secret", | Operational statement participating in the file's runtime behavior.
L1094 |             "placeholder", | Operational statement participating in the file's runtime behavior.
L1095 |             "example", | Operational statement participating in the file's runtime behavior.
L1096 |         ) | Operational statement participating in the file's runtime behavior.
L1097 |         if len(secret_key) < 32 or any(marker in lowered_secret for marker in weak_secret_markers): | Conditional branch that runs only when its condition is true.
L1098 |             raise RuntimeError( | Raises an explicit exception to signal an error condition.

```

```

L1099 |         "Production requires a strong SECRET_KEY. Use a random value such as: " | Operational statement participating in th
L1100 |         "SECRET_KEY=" + secrets.token_hex(32) | Assignment statement storing or updating program state.
L1101 |     ) | Operational statement participating in the file's runtime behavior.
L1102 | app.config["SECRET_KEY"] = secret_key | Assignment statement storing or updating program state.
L1103 | app.config["SESSION_COOKIE_HTTPONLY"] = True | Assignment statement storing or updating program state.
L1104 | app.config["SESSION_COOKIE_SAMESITE"] = "Lax" | Assignment statement storing or updating program state.
L1105 | _secure_cookies = os.getenv("SESSION_COOKIE_SECURE", "0") == "1" | Operational statement participating in the file's runtime be
L1106 | app.config["SESSION_COOKIE_SECURE"] = _secure_cookies | Assignment statement storing or updating program state.
L1107 | app.config["REMEMBER_COOKIE_HTTPONLY"] = True | Assignment statement storing or updating program state.
L1108 | app.config["REMEMBER_COOKIE_SAMESITE"] = "Lax" | Assignment statement storing or updating program state.
L1109 | app.config["REMEMBER_COOKIE_SECURE"] = _secure_cookies | Assignment statement storing or updating program state.
L1110 | # For production behind a TLS terminator always set PREFERRED_URL_SCHEME=https in env. | Comment line documenting intent or con
L1111 | # It automatically aligns with SESSION_COOKIE_SECURE when not explicitly set. | Comment line documenting intent or context for
L1112 | app.config["PREFERRED_URL_SCHEME"] = os.getenv( | Assignment statement storing or updating program state.
L1113 |     "PREFERRED_URL_SCHEME", | Operational statement participating in the file's runtime behavior.
L1114 |     "https" if _secure_cookies else "http", | Operational statement participating in the file's runtime behavior.
L1115 | ) | Operational statement participating in the file's runtime behavior.
L1116 | app.config["PERMANENT_SESSION_LIFETIME"] = timedelta(hours=8) | Assignment statement storing or updating program state.
L1117 | | Blank line used for readability and logical separation.
L1118 | # File uploads | Comment line documenting intent or context for nearby code.
L1119 | app.config["UPLOAD_FOLDER"] = os.path.join(os.path.abspath(os.path.dirname(__file__)), "uploads") | Assignment statement storin
L1120 | os.makedirs(app.config["UPLOAD_FOLDER"], exist_ok=True) | Assignment statement storing or updating program state.
L1121 | app.config["PHOTO_LIBRARY_FOLDER"] = os.path.join(os.path.abspath(os.path.dirname(__file__)), "photo") | Assignment statement s
L1122 | os.makedirs(app.config["PHOTO_LIBRARY_FOLDER"], exist_ok=True) | Assignment statement storing or updating program state.
L1123 | app.config["MONITORED_IMAGE_FOLDERS"] = { | Assignment statement storing or updating program state.
L1124 |     "uploads": app.config["UPLOAD_FOLDER"], | Operational statement participating in the file's runtime behavior.
L1125 |     "photo": app.config["PHOTO_LIBRARY_FOLDER"], | Operational statement participating in the file's runtime behavior.
L1126 | } | Block delimiter controlling scope/structure in this language.
L1127 | app.config["PHOTO_LIBRARY_CONTROLS"] = normalize_photo_library_controls(DEFAULT_PHOTO_LIBRARY_CONTROLS) | Assignment statement
L1128 | max_photo_mb = max(1, int(os.getenv("MAX_PHOTO_MB", "2"))) | Assignment statement storing or updating program state.
L1129 | max_upload_default_mb = max(16, len(TECHNICIAN_PHOTO_FIELDS) * max_photo_mb + 8) | Assignment statement storing or updating pro
L1130 | max_upload_mb = int(os.getenv("MAX_UPLOAD_MB", str(max_upload_default_mb))) | Assignment statement storing or updating program
L1131 | app.config["MAX_CONTENT_LENGTH"] = max_upload_mb * 1024 * 1024 | Assignment statement storing or updating program state.
L1132 | app.config["MAX_PHOTO_MB"] = max_photo_mb | Assignment statement storing or updating program state.
L1133 | app.config["MAX_PHOTO_BYTES"] = max_photo_mb * 1024 * 1024 | Assignment statement storing or updating program state.
L1134 | app.config["ROLE_ACCESS_MATRIX"] = normalize_role_access_matrix(DEFAULT_ROLE_ACCESS_MATRIX) | Assignment statement storing or u
L1135 | app.config["ALLOWED_EXTENSIONS"] = {"png", "jpg", "jpeg", "gif"} | Assignment statement storing or updating program state.
L1136 | app.config["PASSWORD_HASH_METHOD"] = str( | Assignment statement storing or updating program state.
L1137 |     test_config.get("PASSWORD_HASH_METHOD", os.getenv("PASSWORD_HASH_METHOD", "pbkdf2:sha256:150000")) | Operational statement
L1138 | ).strip() | Operational statement participating in the file's runtime behavior.
L1139 | | Blank line used for readability and logical separation.
L1140 | # S3 configuration (optional) | Comment line documenting intent or context for nearby code.
L1141 | app.config["S3_BUCKET"] = os.getenv("S3_BUCKET") | Assignment statement storing or updating program state.
L1142 | app.config["S3_KEY"] = os.getenv("S3_KEY") | Assignment statement storing or updating program state.
L1143 | app.config["S3_SECRET"] = os.getenv("S3_SECRET") | Assignment statement storing or updating program state.
L1144 | app.config["S3_REGION"] = os.getenv("S3_REGION", "us-east-1") | Assignment statement storing or updating program state.
L1145 | app.config["APP_ENV"] = app_env | Assignment statement storing or updating program state.
L1146 | app.config["TESTING"] = is_testing | Assignment statement storing or updating program state.
L1147 | app.config["SEED_SAMPLE_DATA"] = not is_testing | Assignment statement storing or updating program state.
L1148 | | Blank line used for readability and logical separation.
L1149 | inline_automation_default = "1" if (is_testing or app_env != "production") else "0" | Operational statement participating in th
L1150 | access_log_default = "1" if (not is_testing and app_env in {"staging", "production"}) else "0" | Assignment statement storing o
L1151 | app.config["ENABLE_INLINE_AUTOMATIONS"] = str( | Assignment statement storing or updating program state.
L1152 |     test_config.get("ENABLE_INLINE_AUTOMATIONS", os.getenv("ENABLE_INLINE_AUTOMATIONS", inline_automation_default)) | Operatio
L1153 | ).strip() == "1" | Operational statement participating in the file's runtime behavior.

```

```

L1154 |     app.config["ACCESS_LOG_ENABLED"] = str( | Assignment statement storing or updating program state.
L1155 |         test_config.get("ACCESS_LOG_ENABLED", os.getenv("ACCESS_LOG_ENABLED", access_log_default)) | Operational statement particip
L1156 |     ).strip() == "1" | Operational statement participating in the file's runtime behavior.
L1157 | | Blank line used for readability and logical separation.
L1158 |     if test_config: | Conditional branch that runs only when its condition is true.
L1159 |         app.config.update(test_config) | Operational statement participating in the file's runtime behavior.
L1160 | | Blank line used for readability and logical separation.
L1161 |     log_level_name = str(os.getenv("LOG_LEVEL", "INFO")).upper() | Assignment statement storing or updating program state.
L1162 |     app.logger.setLevel(getattr(logging, log_level_name, logging.INFO)) | Operational statement participating in the file's runtime
L1163 |     configure_request_observability(app, access_log_enabled=app.config["ACCESS_LOG_ENABLED"]) | Assignment statement storing or upo
L1164 | | Blank line used for readability and logical separation.
L1165 |     redis_client = None | Assignment statement storing or updating program state.
L1166 |     redis_url = (os.getenv("REDIS_URL") or "").strip() | Assignment statement storing or updating program state.
L1167 |     if redis_url: | Conditional branch that runs only when its condition is true.
L1168 |         try: | Starts an exception handling block for risky operations.
L1169 |             redis_client = redis.Redis.from_url(redis_url, decode_responses=True, socket_timeout=2) | Assignment statement storing
L1170 |             redis_client.ping() | Operational statement participating in the file's runtime behavior.
L1171 |         except Exception as exc: | Handles errors raised in the associated try block.
L1172 |             app.logger.warning("Redis unavailable for login throttling (%s). Falling back to in-memory store.", exc) | Operational
L1173 |             redis_client = None | Assignment statement storing or updating program state.
L1174 | | Blank line used for readability and logical separation.
L1175 |     max_login_attempts = int(os.getenv("MAX_LOGIN_ATTEMPTS", "5")) | Assignment statement storing or updating program state.
L1176 |     login_window_seconds = int(os.getenv("LOGIN_WINDOW_SECONDS", str(15 * 60))) | Assignment statement storing or updating program
L1177 |     login_lockout_seconds = int(os.getenv("LOGIN_LOCKOUT_SECONDS", str(15 * 60))) | Assignment statement storing or updating progra
L1178 |     login_throttle_store = LoginThrottleStore( | Assignment statement storing or updating program state.
L1179 |         max_attempts=max_login_attempts, | Assignment statement storing or updating program state.
L1180 |         window_seconds=login_window_seconds, | Assignment statement storing or updating program state.
L1181 |         lockout_seconds=login_lockout_seconds, | Assignment statement storing or updating program state.
L1182 |         redis_client=redis_client, | Assignment statement storing or updating program state.
L1183 |     ) | Operational statement participating in the file's runtime behavior.
L1184 | | Blank line used for readability and logical separation.
L1185 |     def hash_password(plain_text): | Declares a function/method as a reusable unit of behavior.
L1186 |         hash_method = (app.config.get("PASSWORD_HASH_METHOD") or "pbkdf2:sha256:260000").strip() | Assignment statement storing or
L1187 |         return generate_password_hash(plain_text, method=hash_method) | Returns a value (or control) back to the caller.
L1188 | | Blank line used for readability and logical separation.
L1189 |     def get_avatar_choice_map(users): | Declares a function/method as a reusable unit of behavior.
L1190 |         user_ids = [user.id for user in users if getattr(user, "id", None) is not None] | Assignment statement storing or updating
L1191 |         if not user_ids: | Conditional branch that runs only when its condition is true.
L1192 |             return {} | Returns a value (or control) back to the caller.
L1193 | | Blank line used for readability and logical separation.
L1194 |         settings_rows = UserSettings.query.filter(UserSettings.user_id.in_(user_ids)).all() | Assignment statement storing or updat
L1195 |         by_user_id = {} | Assignment statement storing or updating program state.
L1196 |         for row in settings_rows: | Loop iterating over a sequence to process elements one by one.
L1197 |             prefs = row.get_preferences() | Assignment statement storing or updating program state.
L1198 |             avatar_key = prefs.get("profile_avatar") if isinstance(prefs, dict) else None | Assignment statement storing or updatin
L1199 |             by_user_id[row.user_id] = resolve_avatar_key(avatar_key, None) | Assignment statement storing or updating program state
L1200 | | Blank line used for readability and logical separation.
L1201 |         resolved = {} | Assignment statement storing or updating program state.
L1202 |         for user in users: | Loop iterating over a sequence to process elements one by one.
L1203 |             resolved[user.id] = resolve_avatar_key(by_user_id.get(user.id), user.gender) | Assignment statement storing or updating
L1204 |         return resolved | Returns a value (or control) back to the caller.
L1205 | | Blank line used for readability and logical separation.
L1206 |     db.init_app(app) | Operational statement participating in the file's runtime behavior.
L1207 |     Migrate(app, db) | Operational statement participating in the file's runtime behavior.
L1208 | | Blank line used for readability and logical separation.

```

```

L1209 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L1210 |         try: | Starts an exception handling block for risky operations.
L1211 |             latest_developer_settings = ( | Assignment statement storing or updating program state.
L1212 |                 db.session.query(UserSettings) | Operational statement participating in the file's runtime behavior.
L1213 |                 .join(User, UserSettings.user_id == User.id) | CSS selector line choosing the elements styled below.
L1214 |                 .filter(User.role == "developer") | CSS selector line choosing the elements styled below.
L1215 |                 .order_by(UserSettings.updated_at.desc()) | CSS selector line choosing the elements styled below.
L1216 |                 .first() | CSS selector line choosing the elements styled below.
L1217 |             ) | Operational statement participating in the file's runtime behavior.
L1218 |             if latest_developer_settings: | Conditional branch that runs only when its condition is true.
L1219 |                 preferences = latest_developer_settings.get_preferences() | Assignment statement storing or updating program state.
L1220 |                 stored_limits = preferences.get("system_upload_limits") if isinstance(preferences, dict) else None | Assignment sta
L1221 |                 if isinstance(stored_limits, dict): | Conditional branch that runs only when its condition is true.
L1222 |                     stored_photo_mb = int(stored_limits.get("max_photo_mb", app.config["MAX_PHOTO_MB"])) | Assignment statement sto
L1223 |                     stored_upload_mb = int( | Assignment statement storing or updating program state.
L1224 |                         stored_limits.get( | Operational statement participating in the file's runtime behavior.
L1225 |                             "max_upload_mb", | Operational statement participating in the file's runtime behavior.
L1226 |                             max(1, int(app.config["MAX_CONTENT_LENGTH"] / (1024 * 1024))), | Operational statement participating in
L1227 |                         ) | Operational statement participating in the file's runtime behavior.
L1228 |                     ) | Operational statement participating in the file's runtime behavior.
L1229 |                     min_total_mb = max(16, len(TECHNICIAN_PHOTO_FIELDS) * max(1, stored_photo_mb)) | Assignment statement storing o
L1230 |                     if 1 <= stored_photo_mb <= 20 and min_total_mb <= stored_upload_mb <= 512: | Conditional branch that runs only
L1231 |                         app.config["MAX_PHOTO_MB"] = stored_photo_mb | Assignment statement storing or updating program state.
L1232 |                         app.config["MAX_PHOTO_BYTES"] = stored_photo_mb * 1024 * 1024 | Assignment statement storing or updating pr
L1233 |                         app.config["MAX_CONTENT_LENGTH"] = stored_upload_mb * 1024 * 1024 | Assignment statement storing or updatin
L1234 | | Blank line used for readability and logical separation.
L1235 |                     stored_role_matrix = preferences.get("system_role_access_matrix") if isinstance(preferences, dict) else None | Assi
L1236 |                     if isinstance(stored_role_matrix, dict): | Conditional branch that runs only when its condition is true.
L1237 |                         app.config["ROLE_ACCESS_MATRIX"] = normalize_role_access_matrix(stored_role_matrix) | Assignment statement stor
L1238 | | Blank line used for readability and logical separation.
L1239 |                     stored_photo_controls = preferences.get("system_photo_library_controls") if isinstance(preferences, dict) else None
L1240 |                     if isinstance(stored_photo_controls, dict): | Conditional branch that runs only when its condition is true.
L1241 |                         app.config["PHOTO_LIBRARY_CONTROLS"] = normalize_photo_library_controls(stored_photo_controls) | Assignment sta
L1242 |                     except Exception as exc: | Handles errors raised in the associated try block.
L1243 |                         app.logger.warning("Could not load persisted developer upload limits: %s", exc) | Operational statement participating i
L1244 | | Blank line used for readability and logical separation.
L1245 |                     # Rate limiter – use Redis storage when REDIS_URL is set so limits are | Comment line documenting intent or context for nearby
L1246 |                     # shared across gunicorn workers; fall back to in-memory otherwise. | Comment line documenting intent or context for nearby coo
L1247 |                     limiter_storage = redis_url if redis_url else "memory://" | Assignment statement storing or updating program state.
L1248 |                     limiter = Limiter( | Assignment statement storing or updating program state.
L1249 |                         key_func=get_remote_address, | Assignment statement storing or updating program state.
L1250 |                         app=app, | Assignment statement storing or updating program state.
L1251 |                         storage_uri=limiter_storage, | Assignment statement storing or updating program state.
L1252 |                         default_limits=["600 per minute"], | Assignment statement storing or updating program state.
L1253 |                         headers_enabled=True, | Assignment statement storing or updating program state.
L1254 |                     ) | Operational statement participating in the file's runtime behavior.
L1255 | | Blank line used for readability and logical separation.
L1256 |                     login_manager = LoginManager(app) | Assignment statement storing or updating program state.
L1257 |                     setattr(login_manager, "login_view", "login") | Operational statement participating in the file's runtime behavior.
L1258 | | Blank line used for readability and logical separation.
L1259 |                     def get_csrf_token(): | Declares a function/method as a reusable unit of behavior.
L1260 |                         token = session.get("csrf_token") | Assignment statement storing or updating program state.
L1261 |                         if not token: | Conditional branch that runs only when its condition is true.
L1262 |                             token = secrets.token_urlsafe(32) | Assignment statement storing or updating program state.
L1263 |                             session["csrf_token"] = token | Assignment statement storing or updating program state.

```

```

L1264 |         return token | Returns a value (or control) back to the caller.
L1265 | | Blank line used for readability and logical separation.
L1266 |     def csrf_token_is_valid(): | Declares a function/method as a reusable unit of behavior.
L1267 |         expected = session.get("csrf_token", "") | Assignment statement storing or updating program state.
L1268 |         if not expected: | Conditional branch that runs only when its condition is true.
L1269 |             return False | Returns a value (or control) back to the caller.
L1270 | | Blank line used for readability and logical separation.
L1271 |         provided = (request.form.get("csrf_token") or "").strip() | Assignment statement storing or updating program state.
L1272 |         if not provided: | Conditional branch that runs only when its condition is true.
L1273 |             provided = (request.headers.get("X-CSRF-Token") or request.headers.get("X-CSRFToken") or "").strip() | Assignment statement storing or updating program state.
L1274 |         if not provided and request.is_json: | Conditional branch that runs only when its condition is true.
L1275 |             payload = request.get_json(silent=True) or {} | Assignment statement storing or updating program state.
L1276 |             provided = (payload.get("csrf_token") or "").strip() | Assignment statement storing or updating program state.
L1277 | | Blank line used for readability and logical separation.
L1278 |         return bool(provided) and hmac.compare_digest(expected, provided) | Returns a value (or control) back to the caller.
L1279 | | Blank line used for readability and logical separation.
L1280 |     @app.before_request | Decorator line that modifies the behavior of the definition below.
L1281 |     def enforce_csrf_for_mutations(): | Declares a function/method as a reusable unit of behavior.
L1282 |         if app.testing: | Conditional branch that runs only when its condition is true.
L1283 |             return None | Returns a value (or control) back to the caller.
L1284 | | Blank line used for readability and logical separation.
L1285 |         if request.method not in {"POST", "PUT", "PATCH", "DELETE"}: | Conditional branch that runs only when its condition is true.
L1286 |             return None | Returns a value (or control) back to the caller.
L1287 | | Blank line used for readability and logical separation.
L1288 |         if request.endpoint in {"login"}: | Conditional branch that runs only when its condition is true.
L1289 |             return None | Returns a value (or control) back to the caller.
L1290 | | Blank line used for readability and logical separation.
L1291 |         if csrf_token_is_valid(): | Conditional branch that runs only when its condition is true.
L1292 |             return None | Returns a value (or control) back to the caller.
L1293 | | Blank line used for readability and logical separation.
L1294 |         if request.path.startswith("/api/"): | Conditional branch that runs only when its condition is true.
L1295 |             return jsonify({"error": "CSRF token missing or invalid"}), 400 | Returns a value (or control) back to the caller.
L1296 | | Blank line used for readability and logical separation.
L1297 |         flash("Session verification failed. Please try again.", "danger") | Operational statement participating in the file's runtime behavior.
L1298 |         return redirect(request.referrer or url_for("login")) | Returns a value (or control) back to the caller.
L1299 | | Blank line used for readability and logical separation.
L1300 |     @login_manager.user_loader | Decorator line that modifies the behavior of the definition below.
L1301 |     def load_user(user_id): | Declares a function/method as a reusable unit of behavior.
L1302 |         user = db.session.get(User, int(user_id)) | Assignment statement storing or updating program state.
L1303 |         if user and user.is_blocked: | Conditional branch that runs only when its condition is true.
L1304 |             return None | Returns a value (or control) back to the caller.
L1305 |         return user | Returns a value (or control) back to the caller.
L1306 | | Blank line used for readability and logical separation.
L1307 |     def manager_required(view_func): | Declares a function/method as a reusable unit of behavior.
L1308 |         @wraps(view_func) | Decorator line that modifies the behavior of the definition below.
L1309 |         def wrapped(*args, **kwargs): | Declares a function/method as a reusable unit of behavior.
L1310 |             if not current_user.is_authenticated or not is_admin_role(current_user.role): | Conditional branch that runs only when its condition is true.
L1311 |                 abort(403) | Operational statement participating in the file's runtime behavior.
L1312 |             return view_func(*args, **kwargs) | Returns a value (or control) back to the caller.
L1313 |         return wrapped | Returns a value (or control) back to the caller.
L1314 | | Blank line used for readability and logical separation.
L1315 |     def desk_required(view_func): | Declares a function/method as a reusable unit of behavior.
L1316 |         @wraps(view_func) | Decorator line that modifies the behavior of the definition below.
L1317 |         def wrapped(*args, **kwargs): | Declares a function/method as a reusable unit of behavior.
L1318 |             if not current_user.is_authenticated or not is_desk_role(current_user.role): | Conditional branch that runs only when its condition is true.

```

```

L1319 |         abort(403) | Operational statement participating in the file's runtime behavior.
L1320 |         return view_func(*args, **kwargs) | Returns a value (or control) back to the caller.
L1321 |         return wrapped | Returns a value (or control) back to the caller.
L1322 | | Blank line used for readability and logical separation.
L1323 |     def technician_required(view_func): | Declares a function/method as a reusable unit of behavior.
L1324 |         @wraps(view_func) | Decorator line that modifies the behavior of the definition below.
L1325 |         def wrapped(*args, **kwargs): | Declares a function/method as a reusable unit of behavior.
L1326 |             if not current_user.is_authenticated or not is_technician_role(current_user.role): | Conditional branch that runs only
L1327 |                 abort(403) | Operational statement participating in the file's runtime behavior.
L1328 |                 return view_func(*args, **kwargs) | Returns a value (or control) back to the caller.
L1329 |                 return wrapped | Returns a value (or control) back to the caller.
L1330 | | Blank line used for readability and logical separation.
L1331 |     def developer_required(view_func): | Declares a function/method as a reusable unit of behavior.
L1332 |         @wraps(view_func) | Decorator line that modifies the behavior of the definition below.
L1333 |         def wrapped(*args, **kwargs): | Declares a function/method as a reusable unit of behavior.
L1334 |             if not current_user.is_authenticated or current_user.role != "developer": | Conditional branch that runs only when its
L1335 |                 abort(403) | Operational statement participating in the file's runtime behavior.
L1336 |                 return view_func(*args, **kwargs) | Returns a value (or control) back to the caller.
L1337 |                 return wrapped | Returns a value (or control) back to the caller.
L1338 | | Blank line used for readability and logical separation.
L1339 |     def allowed_file(filename, file_stream=None): | Declares a function/method as a reusable unit of behavior.
L1340 |         """Return True only when the extension is permitted AND (if a stream is | Docstring boundary used to describe a module, cla
L1341 |         provided) the file's magic bytes match a known image format.""" | Operational statement participating in the file's runtime
L1342 |         if "." not in filename: | Conditional branch that runs only when its condition is true.
L1343 |             return False | Returns a value (or control) back to the caller.
L1344 |         ext = filename.rsplit(".", 1)[1].lower() | Assignment statement storing or updating program state.
L1345 |         if ext not in app.config["ALLOWED_EXTENSIONS"]: | Conditional branch that runs only when its condition is true.
L1346 |             return False | Returns a value (or control) back to the caller.
L1347 |         if file_stream is not None and not _check_image_magic(file_stream): | Conditional branch that runs only when its condition
L1348 |             return False | Returns a value (or control) back to the caller.
L1349 |         return True | Returns a value (or control) back to the caller.
L1350 | | Blank line used for readability and logical separation.
L1351 |     def create_activity(activity_type, details): | Declares a function/method as a reusable unit of behavior.
L1352 |         by = current_user.email if has_request_context() and current_user.is_authenticated else None | Assignment statement storing
L1353 |         activity = Activity(activity_type=activity_type, details=details, created_by=by, created_at=utcnow_naive()) | Assignment st
L1354 |         db.session.add(activity) | Operational statement participating in the file's runtime behavior.
L1355 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L1356 | | Blank line used for readability and logical separation.
L1357 |     maintenance_service = MaintenanceService( | Assignment statement storing or updating program state.
L1358 |         db=db, | Assignment statement storing or updating program state.
L1359 |         activity_model=Activity, | Assignment statement storing or updating program state.
L1360 |         message_model=Message, | Assignment statement storing or updating program state.
L1361 |         user_model=User, | Assignment statement storing or updating program state.
L1362 |         create_activity=create_activity, | Assignment statement storing or updating program state.
L1363 |         get_public_holidays=get_public_holidays, | Assignment statement storing or updating program state.
L1364 |         utcnow_naive=utcnow_naive, | Assignment statement storing or updating program state.
L1365 |         high_risk_threshold=HIGH_RISK_THRESHOLD, | Assignment statement storing or updating program state.
L1366 |         sla_scan_cooldown_seconds=_SLA_SCAN_COOLDOWN, | Assignment statement storing or updating program state.
L1367 |     ) | Operational statement participating in the file's runtime behavior.
L1368 |     app.config["_maintenance_service"] = maintenance_service | Assignment statement storing or updating program state.
L1369 | | Blank line used for readability and logical separation.
L1370 |     def get_user_sla_policy(user_settings: UserSettings \ | None): | Declares a function/method as a reusable unit of behavior.
L1371 |         if not user_settings: | Conditional branch that runs only when its condition is true.
L1372 |             return None | Returns a value (or control) back to the caller.
L1373 |         preferences = user_settings.get_preferences() | Assignment statement storing or updating program state.

```

```

L1374 |         raw_policy = preferences.get("sla_policy") if isinstance(preferences, dict) else None | Assignment statement storing or updating program state.
L1375 |         if not isinstance(raw_policy, dict): | Conditional branch that runs only when its condition is true.
L1376 |             return None | Returns a value (or control) back to the caller.
L1377 |         return normalize_sla_policy_config(raw_policy) | Returns a value (or control) back to the caller.
L1378 | | Blank line used for readability and logical separation.
L1379 |     def get_active_sla_policy(): | Declares a function/method as a reusable unit of behavior.
L1380 |         settings_rows = ( | Assignment statement storing or updating program state.
L1381 |             db.session.query(UserSettings, User) | Operational statement participating in the file's runtime behavior.
L1382 |             .join(User, UserSettings.user_id == User.id) | CSS selector line choosing the elements styled below.
L1383 |             .filter(User.role.in_(tuple(DESK_ROLES)), User.is_blocked.is_(False)) | CSS selector line choosing the elements styled below.
L1384 |             .order_by(UserSettings.updated_at.desc()) | CSS selector line choosing the elements styled below.
L1385 |             .all() | CSS selector line choosing the elements styled below.
L1386 |         ) | Operational statement participating in the file's runtime behavior.
L1387 | | Blank line used for readability and logical separation.
L1388 |         for user_settings, user in settings_rows: | Loop iterating over a sequence to process elements one by one.
L1389 |             policy = get_user_sla_policy(user_settings) | Assignment statement storing or updating program state.
L1390 |             if not policy or not policy["policy_agreed"]: | Conditional branch that runs only when its condition is true.
L1391 |                 continue | Flow-control keyword affecting execution in the current block.
L1392 |             policy["updated_by"] = user.display_name or user.email | Assignment statement storing or updating program state.
L1393 |             policy["updated_role"] = normalize_role(user.role) | Assignment statement storing or updating program state.
L1394 |             policy["source"] = "saved" | Assignment statement storing or updating program state.
L1395 |             return policy | Returns a value (or control) back to the caller.
L1396 | | Blank line used for readability and logical separation.
L1397 |         return normalize_sla_policy_config( | Returns a value (or control) back to the caller.
L1398 |             { | Block delimiter controlling scope/structure in this language.
L1399 |                 "enabled": True, | Operational statement participating in the file's runtime behavior.
L1400 |                 "standard_hours": SLA_HOURS_STANDARD, | Operational statement participating in the file's runtime behavior.
L1401 |                 "critical_hours": SLA_HOURS_CRITICAL, | Operational statement participating in the file's runtime behavior.
L1402 |                 "due_soon_hours": SLA_DUE_SOON_HOURS, | Operational statement participating in the file's runtime behavior.
L1403 |                 "policy_agreed": True, | Operational statement participating in the file's runtime behavior.
L1404 |                 "updated_by": "System Default", | Operational statement participating in the file's runtime behavior.
L1405 |                 "updated_role": "system", | Operational statement participating in the file's runtime behavior.
L1406 |                 "source": "default", | Operational statement participating in the file's runtime behavior.
L1407 |             } | Block delimiter controlling scope/structure in this language.
L1408 |         ) | Operational statement participating in the file's runtime behavior.
L1409 | | Blank line used for readability and logical separation.
L1410 |         app.config["_get_active_sla_policy"] = get_active_sla_policy | Assignment statement storing or updating program state.
L1411 |         app.config["_get_user_sla_policy"] = get_user_sla_policy | Assignment statement storing or updating program state.
L1412 | | Blank line used for readability and logical separation.
L1413 |     def find_site_history(site_id, limit=5): | Declares a function/method as a reusable unit of behavior.
L1414 |         if not site_id: | Conditional branch that runs only when its condition is true.
L1415 |             return [] | Returns a value (or control) back to the caller.
L1416 |         return ( | Returns a value (or control) back to the caller.
L1417 |             Activity.query.filter( | Operational statement participating in the file's runtime behavior.
L1418 |                 Activity.activity_type.in_(["pm", "rca"]), | Operational statement participating in the file's runtime behavior.
L1419 |                 Activity.details.ilike(f"%Site Number: {site_id}%") | Operational statement participating in the file's runtime behavior.
L1420 |                 \ | Activity.details.ilike(f"%Site ID: {site_id}%"), | Operational statement participating in the file's runtime behavior.
L1421 |             ) | Operational statement participating in the file's runtime behavior.
L1422 |             .order_by(Activity.created_at.desc()) | CSS selector line choosing the elements styled below.
L1423 |             .limit(limit) | CSS selector line choosing the elements styled below.
L1424 |             .all() | CSS selector line choosing the elements styled below.
L1425 |         ) | Operational statement participating in the file's runtime behavior.
L1426 | | Blank line used for readability and logical separation.
L1427 |     def build_form_insights(form_data, photo_lines, activity_type): | Declares a function/method as a reusable unit of behavior.
L1428 |         errors = [] | Assignment statement storing or updating program state.

```



```

L1429 |         anomalies = [] | Assignment statement storing or updating program state.
L1430 |         recommendations = [] | Assignment statement storing or updating program state.
L1431 |         critical_flags = [] | Assignment statement storing or updating program state.
L1432 | | Blank line used for readability and logical separation.
L1433 |         def get_value(label): | Declares a function/method as a reusable unit of behavior.
L1434 |             return (form_data.get(f"field_{slugify_label(label)}") or "").strip() | Returns a value (or control) back to the caller
L1435 | | Blank line used for readability and logical separation.
L1436 |         site_id = get_value("Site Number") | Assignment statement storing or updating program state.
L1437 |         site_name = get_value("Site Name") | Assignment statement storing or updating program state.
L1438 |         validation_comments = (form_data.get("validation_comments") or "").strip() | Assignment statement storing or updating program state.
L1439 | | Blank line used for readability and logical separation.
L1440 |         if photo_lines and not site_id: | Conditional branch that runs only when its condition is true.
L1441 |             errors.append("Site Number is required when photos are uploaded.") | Operational statement participating in the file's runtime behavior.
L1442 |         if not site_id or not site_name: | Conditional branch that runs only when its condition is true.
L1443 |             errors.append("Site Number and Site Name are required.") | Operational statement participating in the file's runtime behavior.
L1444 | | Blank line used for readability and logical separation.
L1445 |         risk_score = 10 if activity_type == "pm" else 20 | Operational statement participating in the file's runtime behavior.
L1446 | | Blank line used for readability and logical separation.
L1447 |         ats_working = get_value("Is ATS Working?").lower() | Assignment statement storing or updating program state.
L1448 |         controller_auto = get_value("Is controller in Auto mode?").lower() | Assignment statement storing or updating program state.
L1449 |         dg_battery_ok = get_value("Is Battery on DG Working?").lower() | Assignment statement storing or updating program state.
L1450 |         battery_condition = get_value("Battery Condition").lower() | Assignment statement storing or updating program state.
L1451 |         grid_faults = get_value("Any grid faults identified? Share.") | Assignment statement storing or updating program state.
L1452 | | Blank line used for readability and logical separation.
L1453 |         if ats_working == "no": | Conditional branch that runs only when its condition is true.
L1454 |             critical_flags.append("ATS is not working") | Operational statement participating in the file's runtime behavior.
L1455 |             recommendations.append("Recheck ATS wiring, contactor health, and retest ATS failover.") | Operational statement participating in the file's runtime behavior.
L1456 |             risk_score += 28 | Assignment statement storing or updating program state.
L1457 |         if controller_auto == "no": | Conditional branch that runs only when its condition is true.
L1458 |             critical_flags.append("DG controller is not in Auto mode") | Operational statement participating in the file's runtime behavior.
L1459 |             recommendations.append("Set DG controller to Auto mode and verify alarm-free state.") | Operational statement participating in the file's runtime behavior.
L1460 |             risk_score += 18 | Assignment statement storing or updating program state.
L1461 |         if dg_battery_ok == "no": | Conditional branch that runs only when its condition is true.
L1462 |             critical_flags.append("DG battery is not working") | Operational statement participating in the file's runtime behavior.
L1463 |             recommendations.append("Test starter battery voltage and replace battery if below threshold.") | Operational statement participating in the file's runtime behavior.
L1464 |             risk_score += 22 | Assignment statement storing or updating program state.
L1465 |         if any(term in battery_condition for term in ["poor", "bad", "fault", "weak"]): | Conditional branch that runs only when its condition is true.
L1466 |             critical_flags.append("Battery condition indicates fault") | Operational statement participating in the file's runtime behavior.
L1467 |             recommendations.append("Escalate battery bank health issue and schedule replacement.") | Operational statement participating in the file's runtime behavior.
L1468 |             risk_score += 18 | Assignment statement storing or updating program state.
L1469 |         if grid_faults: | Conditional branch that runs only when its condition is true.
L1470 |             recommendations.append("Validate and document grid fault root cause with NOC.") | Operational statement participating in the file's runtime behavior.
L1471 |             risk_score += 8 | Assignment statement storing or updating program state.
L1472 | | Blank line used for readability and logical separation.
L1473 |         if len(photo_lines) < 4: | Conditional branch that runs only when its condition is true.
L1474 |             recommendations.append("Capture complete photo evidence before final closure.") | Operational statement participating in the file's runtime behavior.
L1475 |             risk_score += 15 | Assignment statement storing or updating program state.
L1476 |         if not validation_comments: | Conditional branch that runs only when its condition is true.
L1477 |             recommendations.append("Add technician validation comments for clearer desk review.") | Operational statement participating in the file's runtime behavior.
L1478 |             risk_score += 8 | Assignment statement storing or updating program state.
L1479 | | Blank line used for readability and logical separation.
L1480 |         history_records = find_site_history(site_id, limit=6) | Assignment statement storing or updating program state.
L1481 |         current_run_hours = parse_float_value(get_value("Current DG Run Hours")) | Assignment statement storing or updating program state.
L1482 |         current_grid_meter = parse_float_value(get_value("Grid Meter Reading")) | Assignment statement storing or updating program state.
L1483 | | Blank line used for readability and logical separation.

```

```

L1484 |         previous_run_hours = None | Assignment statement storing or updating program state.
L1485 |         previous_grid_meter = None | Assignment statement storing or updating program state.
L1486 |         repeat_ats_faults = 0 | Assignment statement storing or updating program state.
L1487 | | Blank line used for readability and logical separation.
L1488 |         for record in history_records: | Loop iterating over a sequence to process elements one by one.
L1489 |             if record.details and "Is ATS Working: No" in record.details: | Conditional branch that runs only when its condition is
L1490 |                 repeat_ats_faults += 1 | Assignment statement storing or updating program state.
L1491 |             if previous_run_hours is None: | Conditional branch that runs only when its condition is true.
L1492 |                 previous_run_hours = extract_metric_from_details(record.details, "Current DG Run Hours") | Assignment statement stor
L1493 |             if previous_grid_meter is None: | Conditional branch that runs only when its condition is true.
L1494 |                 previous_grid_meter = extract_metric_from_details(record.details, "Grid Meter Reading") | Assignment statement stor
L1495 | | Blank line used for readability and logical separation.
L1496 |             if repeat_ats_faults >= 2: | Conditional branch that runs only when its condition is true.
L1497 |                 anomalies.append("Repeated ATS faults seen in recent submissions.") | Operational statement participating in the file's
L1498 |                 recommendations.append("Escalate repeated ATS faults for deeper root cause analysis.") | Operational statement particip
L1499 |                 risk_score += 20 | Assignment statement storing or updating program state.
L1500 | | Blank line used for readability and logical separation.
L1501 |             if previous_run_hours is not None and current_run_hours is not None: | Conditional branch that runs only when its condition
L1502 |                 jump = current_run_hours - previous_run_hours | Assignment statement storing or updating program state.
L1503 |                 if jump < 0: | Conditional branch that runs only when its condition is true.
L1504 |                     errors.append("Current DG Run Hours cannot be less than the previous site reading.") | Operational statement partici
L1505 |                 elif jump > 500: | Conditional branch that runs only when its condition is true.
L1506 |                     anomalies.append(f"DG run-hour jump is unusually high ({jump:.0f} hours).") | Operational statement participating i
L1507 |                     recommendations.append("Verify DG run-hour meter reading and investigate abnormal usage.") | Operational statement
L1508 |                     risk_score += 20 | Assignment statement storing or updating program state.
L1509 | | Blank line used for readability and logical separation.
L1510 |             if previous_grid_meter is not None and current_grid_meter is not None and current_grid_meter < previous_grid_meter: | Condi
L1511 |                 anomalies.append("Grid meter reading dropped below previous value.") | Operational statement participating in the file's
L1512 |                 recommendations.append("Confirm grid meter replacement/reset and record the reason.") | Operational statement participa
L1513 |                 risk_score += 12 | Assignment statement storing or updating program state.
L1514 | | Blank line used for readability and logical separation.
L1515 |             outage_context_text = " \n ".join( | Assignment statement storing or updating program state.
L1516 |                 value | Operational statement participating in the file's runtime behavior.
L1517 |                 for value in [ | Loop iterating over a sequence to process elements one by one.
L1518 |                     validation_comments, | Operational statement participating in the file's runtime behavior.
L1519 |                     grid_faults, | Operational statement participating in the file's runtime behavior.
L1520 |                     get_value("Comment"), | Operational statement participating in the file's runtime behavior.
L1521 |                     get_value("Purpose of Visit"), | Operational statement participating in the file's runtime behavior.
L1522 |                 ] | Operational statement participating in the file's runtime behavior.
L1523 |                 if value | Conditional branch that runs only when its condition is true.
L1524 |             ) | Operational statement participating in the file's runtime behavior.
L1525 |             outage_analysis = analyze_outage_signals(outage_context_text) | Assignment statement storing or updating program state.
L1526 |             if outage_analysis["matched_signals"]: | Conditional branch that runs only when its condition is true.
L1527 |                 anomalies.append( | Operational statement participating in the file's runtime behavior.
L1528 |                     "Outage indicators detected from technician narrative: " | Operational statement participating in the file's runtim
L1529 |                     + ", ".join(sorted(set(outage_analysis["matched_signals"]))) | Operational statement participating in the file's ru
L1530 |                     + "." | Operational statement participating in the file's runtime behavior.
L1531 |                 ) | Operational statement participating in the file's runtime behavior.
L1532 |                 risk_score += outage_analysis["risk_boost"] | Assignment statement storing or updating program state.
L1533 |                 for flag in outage_analysis["critical_flags"]: | Loop iterating over a sequence to process elements one by one.
L1534 |                     if flag not in critical_flags: | Conditional branch that runs only when its condition is true.
L1535 |                         critical_flags.append(flag) | Operational statement participating in the file's runtime behavior.
L1536 |                 for rec in outage_analysis["recommendations"]: | Loop iterating over a sequence to process elements one by one.
L1537 |                     if rec not in recommendations: | Conditional branch that runs only when its condition is true.
L1538 |                         recommendations.append(rec) | Operational statement participating in the file's runtime behavior.

```

```

L1539 | | Blank line used for readability and logical separation.
L1540 |         if not recommendations: | Conditional branch that runs only when its condition is true.
L1541 |             recommendations.append("No critical issue detected. Continue routine preventive maintenance checks.") | Operational sta
L1542 | | Blank line used for readability and logical separation.
L1543 |         risk_score = max(0, min(100, int(round(risk_score)))) | Assignment statement storing or updating program state.
L1544 |         risk_level = classify_risk_level(risk_score) | Assignment statement storing or updating program state.
L1545 |         is_critical = bool(critical_flags) or risk_score >= HIGH_RISK_THRESHOLD | Operational statement participating in the file's
L1546 |         sla_policy = get_active_sla_policy() | Assignment statement storing or updating program state.
L1547 |         sla_deadline = build_sla_deadline_from_policy( | Assignment statement storing or updating program state.
L1548 |             activity_type=activity_type, | Assignment statement storing or updating program state.
L1549 |             is_critical=is_critical, | Assignment statement storing or updating program state.
L1550 |             now_value=utcnow_naive(), | Assignment statement storing or updating program state.
L1551 |             policy=sla_policy, | Assignment statement storing or updating program state.
L1552 |         ) | Operational statement participating in the file's runtime behavior.
L1553 | | Blank line used for readability and logical separation.
L1554 |     return { | Returns a value (or control) back to the caller.
L1555 |         "errors": errors, | Operational statement participating in the file's runtime behavior.
L1556 |         "anomalies": anomalies, | Operational statement participating in the file's runtime behavior.
L1557 |         "recommendations": recommendations, | Operational statement participating in the file's runtime behavior.
L1558 |         "critical_flags": critical_flags, | Operational statement participating in the file's runtime behavior.
L1559 |         "risk_score": risk_score, | Operational statement participating in the file's runtime behavior.
L1560 |         "risk_level": risk_level, | Operational statement participating in the file's runtime behavior.
L1561 |         "is_critical": is_critical, | Operational statement participating in the file's runtime behavior.
L1562 |         "sla_deadline": sla_deadline, | Operational statement participating in the file's runtime behavior.
L1563 |     } | Block delimiter controlling scope/structure in this language.
L1564 | | Blank line used for readability and logical separation.
L1565 |     def build_insight_lines(insights): | Declares a function/method as a reusable unit of behavior.
L1566 |         lines = [ | Assignment statement storing or updating program state.
L1567 |             "SMART INSIGHTS", | Operational statement participating in the file's runtime behavior.
L1568 |             f"Risk Score: {insights['risk_score']}", | Operational statement participating in the file's runtime behavior.
L1569 |             f"Risk Level: {insights['risk_level']}", | Operational statement participating in the file's runtime behavior.
L1570 |             f"Critical: {'Yes' if insights['is_critical'] else 'No'}", | Operational statement participating in the file's runtime
L1571 |             f"SLA Deadline (UTC): {insights['sla_deadline'].isoformat(timespec='seconds')}", | Assignment statement storing or upda
L1572 |             "Critical Flags:", | Operational statement participating in the file's runtime behavior.
L1573 |         ] | Operational statement participating in the file's runtime behavior.
L1574 |         if insights["critical_flags"]: | Conditional branch that runs only when its condition is true.
L1575 |             lines.extend([f"- {item}" for item in insights["critical_flags"]]) | Operational statement participating in the file's
L1576 |         else: | Fallback branch executed when prior conditions are false.
L1577 |             lines.append("- None") | Operational statement participating in the file's runtime behavior.
L1578 | | Blank line used for readability and logical separation.
L1579 |         lines.append("Anomalies:") | Operational statement participating in the file's runtime behavior.
L1580 |         if insights["anomalies"]: | Conditional branch that runs only when its condition is true.
L1581 |             lines.extend([f"- {item}" for item in insights["anomalies"]]) | Operational statement participating in the file's runti
L1582 |         else: | Fallback branch executed when prior conditions are false.
L1583 |             lines.append("- None") | Operational statement participating in the file's runtime behavior.
L1584 | | Blank line used for readability and logical separation.
L1585 |         lines.append("Recommendations:") | Operational statement participating in the file's runtime behavior.
L1586 |         lines.extend([f"- {item}" for item in insights["recommendations"]]) | Operational statement participating in the file's run
L1587 |         return lines | Returns a value (or control) back to the caller.
L1588 | | Blank line used for readability and logical separation.
L1589 |     def build_activity_review_rows(activities): | Declares a function/method as a reusable unit of behavior.
L1590 |         rows = [] | Assignment statement storing or updating program state.
L1591 |         now = utcnow_naive() | Assignment statement storing or updating program state.
L1592 |         active_sla_policy = get_active_sla_policy() | Assignment statement storing or updating program state.
L1593 |         due_soon_hours = active_sla_policy["due_soon_hours"] | Assignment statement storing or updating program state.

```

```

L1594 |         for activity in activities: | Loop iterating over a sequence to process elements one by one.
L1595 |             # Prefer stored columns; fall back to text-parsing for legacy rows. | Comment line documenting intent or context for ne
L1596 |             risk_score = (activity.risk_score if activity.risk_score is not None | Assignment statement storing or updating program
L1597 |                 else extract_risk_score_from_details(activity.details) or 0) | Operational statement participating in the
L1598 |             risk_level = classify_risk_level(risk_score) | Assignment statement storing or updating program state.
L1599 |             sla_deadline = activity.sla_deadline or extract_sla_deadline_from_details(activity.details) | Assignment statement stor
L1600 |             recommendations = extract_recommendations_from_details(activity.details) | Assignment statement storing or updating pro
L1601 | | Blank line used for readability and logical separation.
L1602 |             if activity.approved_at: | Conditional branch that runs only when its condition is true.
L1603 |                 sla_state = "Resolved" | Assignment statement storing or updating program state.
L1604 |             elif sla_deadline and now > sla_deadline: | Conditional branch that runs only when its condition is true.
L1605 |                 sla_state = "Overdue" | Assignment statement storing or updating program state.
L1606 |             elif sla_deadline and (sla_deadline - now).total_seconds() <= due_soon_hours * 3600: | Conditional branch that runs onl
L1607 |                 sla_state = "Due Soon" | Assignment statement storing or updating program state.
L1608 |             elif sla_deadline: | Conditional branch that runs only when its condition is true.
L1609 |                 sla_state = "On Track" | Assignment statement storing or updating program state.
L1610 |             else: | Fallback branch executed when prior conditions are false.
L1611 |                 sla_state = "Not Set" | Assignment statement storing or updating program state.
L1612 | | Blank line used for readability and logical separation.
L1613 |             top_recommendation = recommendations[0] if recommendations else derive_sla_suggestion(sla_state, risk_level) | Assignme
L1614 | | Blank line used for readability and logical separation.
L1615 |             rows.append( | Operational statement participating in the file's runtime behavior.
L1616 |                 { | Block delimiter controlling scope/structure in this language.
L1617 |                     "activity": activity, | Operational statement participating in the file's runtime behavior.
L1618 |                     "risk_score": risk_score, | Operational statement participating in the file's runtime behavior.
L1619 |                     "risk_level": risk_level, | Operational statement participating in the file's runtime behavior.
L1620 |                     "sla_deadline": sla_deadline, | Operational statement participating in the file's runtime behavior.
L1621 |                     "sla_state": sla_state, | Operational statement participating in the file's runtime behavior.
L1622 |                     "recommendations": recommendations, | Operational statement participating in the file's runtime behavior.
L1623 |                     "top_recommendation": top_recommendation, | Operational statement participating in the file's runtime behavior.
L1624 |                 } | Block delimiter controlling scope/structure in this language.
L1625 |             ) | Operational statement participating in the file's runtime behavior.
L1626 | | Blank line used for readability and logical separation.
L1627 |             rows.sort(key=lambda item: (item["risk_score"], item["activity"].created_at), reverse=True) | Assignment statement storing
L1628 |             return rows | Returns a value (or control) back to the caller.
L1629 | | Blank line used for readability and logical separation.
L1630 |             _TRUSTED_PROXY_COUNT = int(os.getenv("TRUSTED_PROXY_COUNT", "0")) | Assignment statement storing or updating program state.
L1631 | | Blank line used for readability and logical separation.
L1632 |             def get_client_ip(): | Declares a function/method as a reusable unit of behavior.
L1633 |                 if _TRUSTED_PROXY_COUNT > 0: | Conditional branch that runs only when its condition is true.
L1634 |                     forwarded_for = request.headers.get("X-Forwarded-For", "") | Assignment statement storing or updating program state.
L1635 |                     if forwarded_for: | Conditional branch that runs only when its condition is true.
L1636 |                         addrs = [a.strip() for a in forwarded_for.split(",")] | Assignment statement storing or updating program state.
L1637 |                         # Take the address N hops from the right (N = trusted proxy count) | Comment line documenting intent or context for
L1638 |                         idx = max(0, len(addrs) - _TRUSTED_PROXY_COUNT) | Assignment statement storing or updating program state.
L1639 |                         return addrs[idx] | Returns a value (or control) back to the caller.
L1640 |                     return request.remote_addr or "unknown" | Returns a value (or control) back to the caller.
L1641 | | Blank line used for readability and logical separation.
L1642 |             def login_throttle_key(email): | Declares a function/method as a reusable unit of behavior.
L1643 |                 return f"{get_client_ip()}::{(email or '').strip().lower()}" | Returns a value (or control) back to the caller.
L1644 | | Blank line used for readability and logical separation.
L1645 |             def get_lockout_seconds(email): | Declares a function/method as a reusable unit of behavior.
L1646 |                 return login_throttle_store.get_lockout_seconds(login_throttle_key(email)) | Returns a value (or control) back to the caller
L1647 | | Blank line used for readability and logical separation.
L1648 |             def register_login_failure(email): | Declares a function/method as a reusable unit of behavior.

```

```

L1649 |         login_throttle_store.register_failure(login_throttle_key(email)) | Operational statement participating in the file's runtime behavior.
L1650 | | Blank line used for readability and logical separation.
L1651 |     def reset_login_failures(email): | Declares a function/method as a reusable unit of behavior.
L1652 |         login_throttle_store.reset(login_throttle_key(email)) | Operational statement participating in the file's runtime behavior.
L1653 | | Blank line used for readability and logical separation.
L1654 |     @app.after_request | Decorator line that modifies the behavior of the definition below.
L1655 |     def set_security_headers(response): | Declares a function/method as a reusable unit of behavior.
L1656 |         response.headers["X-Content-Type-Options"] = "nosniff" | Assignment statement storing or updating program state.
L1657 |         response.headers["X-Frame-Options"] = "SAMEORIGIN" | Assignment statement storing or updating program state.
L1658 |         response.headers["Referrer-Policy"] = "strict-origin-when-cross-origin" | Assignment statement storing or updating program state.
L1659 |         response.headers["Permissions-Policy"] = "geolocation=(), microphone=(), camera=()" | Assignment statement storing or updating program state.
L1660 |         response.headers["Content-Security-Policy"] = ( | Assignment statement storing or updating program state.
L1661 |             "default-src 'self'; " | Operational statement participating in the file's runtime behavior.
L1662 |             "script-src 'self' 'unsafe-inline' https://cdn.jsdelivr.net; " | Operational statement participating in the file's runtime behavior.
L1663 |             "style-src 'self' 'unsafe-inline' https://cdn.jsdelivr.net; " | Operational statement participating in the file's runtime behavior.
L1664 |             "img-src 'self' data: https; " | Operational statement participating in the file's runtime behavior.
L1665 |             "font-src 'self' https://cdn.jsdelivr.net; " | Operational statement participating in the file's runtime behavior.
L1666 |             "connect-src 'self'; " | Operational statement participating in the file's runtime behavior.
L1667 |             "object-src 'none'; " | Operational statement participating in the file's runtime behavior.
L1668 |             "base-uri 'self'; " | Operational statement participating in the file's runtime behavior.
L1669 |             "form-action 'self'; " | Operational statement participating in the file's runtime behavior.
L1670 |             "frame-ancestors 'self'" | Operational statement participating in the file's runtime behavior.
L1671 |         ) | Operational statement participating in the file's runtime behavior.
L1672 |         if os.getenv("SESSION_COOKIE_SECURE", "0") == "1" or app.config.get("SESSION_COOKIE_SECURE"): | Conditional branch that runs only when its condition is true.
L1673 |             response.headers["Strict-Transport-Security"] = "max-age=31536000; includeSubDomains" | Assignment statement storing or updating program state.
L1674 |         return response | Returns a value (or control) back to the caller.
L1675 | | Blank line used for readability and logical separation.
L1676 |     # Flask 3 removed before_first_request; keep auto-init limited to testing | Comment line documenting intent or context for nearby code.
L1677 |     # and local development. Staging/production should use migrations only. | Comment line documenting intent or context for nearby code.
L1678 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L1679 |         should_auto_create = is_testing or app.env == "development" | Operational statement participating in the file's runtime behavior.
L1680 |         if should_auto_create: | Conditional branch that runs only when its condition is true.
L1681 |             db.create_all() | Operational statement participating in the file's runtime behavior.
L1682 | | Blank line used for readability and logical separation.
L1683 |         if app.config.get("SEED_SAMPLE_DATA", True) and Consumable.query.count() == 0: | Conditional branch that runs only when its condition is true.
L1684 |             seed_data() | Operational statement participating in the file's runtime behavior.
L1685 | | Blank line used for readability and logical separation.
L1686 |     @app.route("/") | Decorator line that modifies the behavior of the definition below.
L1687 |     def root(): | Declares a function/method as a reusable unit of behavior.
L1688 |         if current_user.is_authenticated: | Conditional branch that runs only when its condition is true.
L1689 |             return redirect(url_for("dashboard")) | Returns a value (or control) back to the caller.
L1690 |             return redirect(url_for("login")) | Returns a value (or control) back to the caller.
L1691 | | Blank line used for readability and logical separation.
L1692 |     @app.route("/_build") | Decorator line that modifies the behavior of the definition below.
L1693 |     def build_info(): | Declares a function/method as a reusable unit of behavior.
L1694 |         return jsonify({"build": APP_BUILD_ID, "time": utcnow_naive().isoformat(timespec="seconds")}) | Returns a value (or control) back to the caller.
L1695 | | Blank line used for readability and logical separation.
L1696 |     @app.cli.command("run-maintenance") | Decorator line that modifies the behavior of the definition below.
L1697 |     def run_maintenance_command(): | Declares a function/method as a reusable unit of behavior.
L1698 |         """Execute maintenance tasks outside the request cycle.""" | Docstring boundary used to describe a module, class, or function.
L1699 |         summary = maintenance_service.run_all(respect_cooldown=False) | Assignment statement storing or updating program state.
L1700 |         click.echo( | Operational statement participating in the file's runtime behavior.
L1701 |             "holiday_created={holiday_created} sla_escalations={sla_escalations} inline_enabled={inline_enabled}".format( | Assignment statement storing or updating program state.
L1702 |                 holiday_created=summary.holiday_created, | Assignment statement storing or updating program state.
L1703 |                 sla_escalations=summary.sla_escalations, | Assignment statement storing or updating program state.

```

```

L1704 |         inline_enabled=int(app.config["ENABLE_INLINE_AUTOMATIONS"]), | Assignment statement storing or updating program state
L1705 |     ) | Operational statement participating in the file's runtime behavior.
L1706 | ) | Operational statement participating in the file's runtime behavior.
L1707 | | Blank line used for readability and logical separation.
L1708 | register_auth_routes( | Operational statement participating in the file's runtime behavior.
L1709 |     app, | Operational statement participating in the file's runtime behavior.
L1710 |     user_model=User, | Assignment statement storing or updating program state.
L1711 |     db=db, | Assignment statement storing or updating program state.
L1712 |     app_env=app_env, | Assignment statement storing or updating program state.
L1713 |     role_lock_enabled=os.getenv("ENABLE_ROLE_LOCKED_LOGIN", "0") == "1", | Operational statement participating in the file's runtime behavior.
L1714 |     normalize_role=normalize_role, | Assignment statement storing or updating program state.
L1715 |     allowed_login_roles=allowed_login_roles, | Assignment statement storing or updating program state.
L1716 |     get_lockout_seconds=get_lockout_seconds, | Assignment statement storing or updating program state.
L1717 |     register_login_failure=register_login_failure, | Assignment statement storing or updating program state.
L1718 |     reset_login_failures=reset_login_failures, | Assignment statement storing or updating program state.
L1719 |     hash_password=hash_password, | Assignment statement storing or updating program state.
L1720 | ) | Operational statement participating in the file's runtime behavior.
L1721 | | Blank line used for readability and logical separation.
L1722 | register_api_routes( | Operational statement participating in the file's runtime behavior.
L1723 |     app, | Operational statement participating in the file's runtime behavior.
L1724 |     consumable_model=Consumable, | Assignment statement storing or updating program state.
L1725 |     activity_model=Activity, | Assignment statement storing or updating program state.
L1726 |     db=db, | Assignment statement storing or updating program state.
L1727 |     normalize_role=normalize_role, | Assignment statement storing or updating program state.
L1728 |     limiter=limiter, | Assignment statement storing or updating program state.
L1729 | ) | Operational statement participating in the file's runtime behavior.
L1730 | | Blank line used for readability and logical separation.
L1731 | @app.before_request | Decorator line that modifies the behavior of the definition below.
L1732 | def enforce_blocked_user_logout(): | Declares a function/method as a reusable unit of behavior.
L1733 |     if app.config["ENABLE_INLINE_AUTOMATIONS"]: | Conditional branch that runs only when its condition is true.
L1734 |         maintenance_service.run_all(respect_cooldown=True) | Assignment statement storing or updating program state.
L1735 |         if current_user.is_authenticated and getattr(current_user, "is_blocked", False): | Conditional branch that runs only when its condition is true.
L1736 |             logout_user() | Operational statement participating in the file's runtime behavior.
L1737 |             session.clear() | Operational statement participating in the file's runtime behavior.
L1738 |             flash("Your account has been blocked. Contact a developer.", "danger") | Operational statement participating in the file's runtime behavior.
L1739 |             return redirect(url_for("login")) | Returns a value (or control) back to the caller.
L1740 | | Blank line used for readability and logical separation.
L1741 | @app.after_request | Decorator line that modifies the behavior of the definition below.
L1742 | def prevent_stale_html_cache(response): | Declares a function/method as a reusable unit of behavior.
L1743 |     content_type = (response.content_type or "").lower() | Assignment statement storing or updating program state.
L1744 |     if "text/html" in content_type: | Conditional branch that runs only when its condition is true.
L1745 |         response.headers["Cache-Control"] = "no-store, no-cache, must-revalidate, max-age=0" | Assignment statement storing or updating program state.
L1746 |         response.headers["Pragma"] = "no-cache" | Assignment statement storing or updating program state.
L1747 |         response.headers["Expires"] = "0" | Assignment statement storing or updating program state.
L1748 |     return response | Returns a value (or control) back to the caller.
L1749 | | Blank line used for readability and logical separation.
L1750 | def calculate_notification_count(): | Declares a function/method as a reusable unit of behavior.
L1751 |     if not current_user.is_authenticated: | Conditional branch that runs only when its condition is true.
L1752 |         return 0 | Returns a value (or control) back to the caller.
L1753 | | Blank line used for readability and logical separation.
L1754 |     inbox_roles = {current_user.role, "all"} | Assignment statement storing or updating program state.
L1755 |     last_seen = None | Assignment statement storing or updating program state.
L1756 |     last_seen_raw = session.get("notifications_last_seen_at") | Assignment statement storing or updating program state.
L1757 |     if last_seen_raw: | Conditional branch that runs only when its condition is true.
L1758 |         try: | Starts an exception handling block for risky operations.

```

```

L1759 |         last_seen = datetime.fromisoformat(last_seen_raw) | Assignment statement storing or updating program state.
L1760 |     except ValueError: | Handles errors raised in the associated try block.
L1761 |         last_seen = None | Assignment statement storing or updating program state.
L1762 | | Blank line used for readability and logical separation.
L1763 |     # Notification badge should represent unread incoming messages only. | Comment line documenting intent or context for nearby
L1764 |     unread_message_query = Message.query.filter( | Assignment statement storing or updating program state.
L1765 |         (Message.recipient_role.in_(inbox_roles)) | Operational statement participating in the file's runtime behavior.
L1766 |         \ | (Message.recipient_email == current_user.email) | Operational statement participating in the file's runtime behavior.
L1767 |     ) | Operational statement participating in the file's runtime behavior.
L1768 | | Blank line used for readability and logical separation.
L1769 |     if last_seen is not None: | Conditional branch that runs only when its condition is true.
L1770 |         unread_message_query = unread_message_query.filter(Message.created_at > last_seen) | Assignment statement storing or up
L1771 | | Blank line used for readability and logical separation.
L1772 |     return unread_message_query.count() | Returns a value (or control) back to the caller.
L1773 | | Blank line used for readability and logical separation.
L1774 | def get_live_dashboard_counts(): | Declares a function/method as a reusable unit of behavior.
L1775 |     technician_emails_query = db.session.query(User.email).filter(User.role == "technician") | Operational statement participat
L1776 |     field_submission_base = Activity.query.filter( | Assignment statement storing or updating program state.
L1777 |         Activity.activity_type.in_(["pm", "rca"]), | Operational statement participating in the file's runtime behavior.
L1778 |         Activity.created_by.in_(technician_emails_query), | Operational statement participating in the file's runtime behavior.
L1779 |     ) | Operational statement participating in the file's runtime behavior.
L1780 |     pending_base = field_submission_base.filter(Activity.approved_at.is_(None)) | Assignment statement storing or updating prog
L1781 |     now = utcnow_naive() | Assignment statement storing or updating program state.
L1782 |     high_risk_pending_count = pending_base.filter(Activity.risk_score >= HIGH_RISK_THRESHOLD).count() | Operational statement p
L1783 |     sla_overdue_count = pending_base.filter( | Assignment statement storing or updating program state.
L1784 |         Activity.sla_deadline.is_not(None), | Operational statement participating in the file's runtime behavior.
L1785 |         Activity.sla_deadline < now, | Operational statement participating in the file's runtime behavior.
L1786 |     ).count() | Operational statement participating in the file's runtime behavior.
L1787 | | Blank line used for readability and logical separation.
L1788 |     counts = { | Assignment statement storing or updating program state.
L1789 |         "users_total": User.query.count(), | Operational statement participating in the file's runtime behavior.
L1790 |         "blocked_users": User.query.filter_by(is_blocked=True).count(), | Assignment statement storing or updating program stat
L1791 |         "technician_users": User.query.filter_by(role="technician").count(), | Assignment statement storing or updating program
L1792 |         "staff_users": User.query.filter(User.role == "staff").count(), | Operational statement participating in the file's run
L1793 |         "manager_users": User.query.filter_by(role="manager").count(), | Assignment statement storing or updating program state
L1794 |         "general_manager_users": User.query.filter_by(role="general_manager").count(), | Assignment statement storing or updati
L1795 |         "consumables_count": Consumable.query.count(), | Operational statement participating in the file's runtime behavior.
L1796 |         "total_rcas": Activity.query.filter_by(activity_type="rca").count(), | Assignment statement storing or updating program
L1797 |         "total_snags": Activity.query.filter_by(activity_type="snag").count(), | Assignment statement storing or updating progr
L1798 |         "total_dars": Activity.query.filter_by(activity_type="dar").count(), | Assignment statement storing or updating program
L1799 |         "total_pms": Activity.query.filter_by(activity_type="pm").count(), | Assignment statement storing or updating program s
L1800 |         "pending_pm_rcas": field_submission_base.filter(Activity.approved_at.is_(None)).count(), | Operational statement partici
L1801 |         "high_risk_pending_pm_rcas": high_risk_pending_count, | Operational statement participating in the file's runtime behav
L1802 |         "sla_overdue_pm_rcas": sla_overdue_count, | Operational statement participating in the file's runtime behavior.
L1803 |         "approved_pm_forms": field_submission_base.filter(Activity.is_approved.is_(True)).count(), | Operational statement part
L1804 |         "rejected_pm_rcas": field_submission_base.filter( | Operational statement participating in the file's runtime behavior.
L1805 |             Activity.is_approved.is_(False), | Operational statement participating in the file's runtime behavior.
L1806 |             Activity.approved_at.is_not(None), | Operational statement participating in the file's runtime behavior.
L1807 |         ).count(), | Operational statement participating in the file's runtime behavior.
L1808 |         "holiday_entries": len(get_public_holidays()), | Operational statement participating in the file's runtime behavior.
L1809 |         "notification_count": calculate_notification_count(), | Operational statement participating in the file's runtime behav
L1810 |     } | Block delimiter controlling scope/structure in this language.
L1811 |     counts["field_total_forms"] = ( | Assignment statement storing or updating program state.
L1812 |         counts["pending_pm_rcas"] + counts["approved_pm_forms"] + counts["rejected_pm_rcas"] | Operational statement participat
L1813 |     ) | Operational statement participating in the file's runtime behavior.

```

```

L1814 | | Blank line used for readability and logical separation.
L1815 |         if current_user.is_authenticated and is_technician_role(current_user.role): | Conditional branch that runs only when its co
L1816 |             technician_pm = Activity.query.filter_by(activity_type="pm", created_by=current_user.email).count() | Assignment statem
L1817 |             technician_rca = Activity.query.filter_by(activity_type="rca", created_by=current_user.email).count() | Assignment stat
L1818 |             technician_rejected = Activity.query.filter( | Assignment statement storing or updating program state.
L1819 |                 Activity.activity_type.in(["pm", "rca"]), | Operational statement participating in the file's runtime behavior.
L1820 |                 Activity.created_by == current_user.email, | Operational statement participating in the file's runtime behavior.
L1821 |                 Activity.is_approved.is_(False), | Operational statement participating in the file's runtime behavior.
L1822 |                 Activity.approved_at.is_not(None), | Operational statement participating in the file's runtime behavior.
L1823 |             ).count() | Operational statement participating in the file's runtime behavior.
L1824 |             counts["technician_pm"] = technician_pm | Assignment statement storing or updating program state.
L1825 |             counts["technician_rca"] = technician_rca | Assignment statement storing or updating program state.
L1826 |             counts["technician_total"] = technician_pm + technician_rca | Assignment statement storing or updating program state.
L1827 |             counts["technician_rejected"] = technician_rejected | Assignment statement storing or updating program state.
L1828 |         else: | Fallback branch executed when prior conditions are false.
L1829 |             counts["technician_pm"] = 0 | Assignment statement storing or updating program state.
L1830 |             counts["technician_rca"] = 0 | Assignment statement storing or updating program state.
L1831 |             counts["technician_total"] = 0 | Assignment statement storing or updating program state.
L1832 |             counts["technician_rejected"] = 0 | Assignment statement storing or updating program state.
L1833 | | Blank line used for readability and logical separation.
L1834 |         return counts | Returns a value (or control) back to the caller.
L1835 | | Blank line used for readability and logical separation.
L1836 |     def get_photo_library_entries(limit=24, query=""): | Declares a function/method as a reusable unit of behavior.
L1837 |         photo_root = app.config.get("PHOTO_LIBRARY_FOLDER") | Assignment statement storing or updating program state.
L1838 |         if not photo_root or not os.path.isdir(photo_root): | Conditional branch that runs only when its condition is true.
L1839 |             return [] | Returns a value (or control) back to the caller.
L1840 | | Blank line used for readability and logical separation.
L1841 |         controls = normalize_photo_library_controls(app.config.get("PHOTO_LIBRARY_CONTROLS")) | Assignment statement storing or updo
L1842 |         include_screenshots = controls["include_screenshots"] | Assignment statement storing or updating program state.
L1843 | | Blank line used for readability and logical separation.
L1844 |         query_text = (query or "").strip().lower() | Assignment statement storing or updating program state.
L1845 |         entries = [] | Assignment statement storing or updating program state.
L1846 |         for entry in os.scandir(photo_root): | Loop iterating over a sequence to process elements one by one.
L1847 |             if not entry.is_file(): | Conditional branch that runs only when its condition is true.
L1848 |                 continue | Flow-control keyword affecting execution in the current block.
L1849 |                 extension = os.path.splitext(entry.name)[1].lower() | Assignment statement storing or updating program state.
L1850 |                 if extension not in PHOTO_LIBRARY_IMAGE_EXTENSIONS: | Conditional branch that runs only when its condition is true.
L1851 |                     continue | Flow-control keyword affecting execution in the current block.
L1852 | | Blank line used for readability and logical separation.
L1853 |                 lowered_name = entry.name.lower() | Assignment statement storing or updating program state.
L1854 |                 kind = "screenshot" if "screenshot" in lowered_name or "chrome" in lowered_name else "image" | Assignment statement sto
L1855 |                 if kind == "screenshot" and not include_screenshots: | Conditional branch that runs only when its condition is true.
L1856 |                     continue | Flow-control keyword affecting execution in the current block.
L1857 | | Blank line used for readability and logical separation.
L1858 |                 description = describe_monitored_image(entry.path, entry.name) | Assignment statement storing or updating program state
L1859 |                 if query_text and query_text not in entry.name.lower() and query_text not in description.lower(): | Conditional branch
L1860 |                     continue | Flow-control keyword affecting execution in the current block.
L1861 | | Blank line used for readability and logical separation.
L1862 |                 stat = entry.stat() | Assignment statement storing or updating program state.
L1863 |                 entries.append( | Operational statement participating in the file's runtime behavior.
L1864 |                     { | Block delimiter controlling scope/structure in this language.
L1865 |                         "name": entry.name, | Operational statement participating in the file's runtime behavior.
L1866 |                         "description": description, | Operational statement participating in the file's runtime behavior.
L1867 |                         "extension": extension.lstrip("."), | Operational statement participating in the file's runtime behavior.
L1868 |                         "modified_at": datetime.fromtimestamp(stat.st_mtime), | Operational statement participating in the file's runti

```



```

L1869 |         "size_kb": max(1, int(round(stat.st_size / 1024))), | Operational statement participating in the file's runtime
L1870 |         "preview_url": url_for("photo_library_file", filename=entry.name), | Assignment statement storing or updating p
L1871 |         "import_ready": True, | Operational statement participating in the file's runtime behavior.
L1872 |         "kind": kind, | Operational statement participating in the file's runtime behavior.
L1873 |     } | Block delimiter controlling scope/structure in this language.
L1874 | ) | Operational statement participating in the file's runtime behavior.
L1875 | | Blank line used for readability and logical separation.
L1876 |     entries.sort(key=lambda item: item["modified_at"], reverse=True) | Assignment statement storing or updating program state.
L1877 |     if limit and limit > 0: | Conditional branch that runs only when its condition is true.
L1878 |         return entries[:limit] | Returns a value (or control) back to the caller.
L1879 |     return entries | Returns a value (or control) back to the caller.
L1880 | | Blank line used for readability and logical separation.
L1881 |     def get_photo_library_count(): | Declares a function/method as a reusable unit of behavior.
L1882 |         photo_root = app.config.get("PHOTO_LIBRARY_FOLDER") | Assignment statement storing or updating program state.
L1883 |         if not photo_root or not os.path.isdir(photo_root): | Conditional branch that runs only when its condition is true.
L1884 |             return 0 | Returns a value (or control) back to the caller.
L1885 |         controls = normalize_photo_library_controls(app.config.get("PHOTO_LIBRARY_CONTROLS")) | Assignment statement storing or up
L1886 |         include_screenshots = controls["include_screenshots"] | Assignment statement storing or updating program state.
L1887 |         total = 0 | Assignment statement storing or updating program state.
L1888 |         for entry in os.scandir(photo_root): | Loop iterating over a sequence to process elements one by one.
L1889 |             if not entry.is_file(): | Conditional branch that runs only when its condition is true.
L1890 |                 continue | Flow-control keyword affecting execution in the current block.
L1891 |             if os.path.splitext(entry.name)[1].lower() not in PHOTO_LIBRARY_IMAGE_EXTENSIONS: | Conditional branch that runs only w
L1892 |                 continue | Flow-control keyword affecting execution in the current block.
L1893 |             lowered_name = entry.name.lower() | Assignment statement storing or updating program state.
L1894 |             is_screenshot = "screenshot" in lowered_name or "chrome" in lowered_name | Assignment statement storing or updating pro
L1895 |             if is_screenshot and not include_screenshots: | Conditional branch that runs only when its condition is true.
L1896 |                 continue | Flow-control keyword affecting execution in the current block.
L1897 |             total += 1 | Assignment statement storing or updating program state.
L1898 |         return total | Returns a value (or control) back to the caller.
L1899 | | Blank line used for readability and logical separation.
L1900 |     @app.context_processor | Decorator line that modifies the behavior of the definition below.
L1901 |     def inject_notification_badge(): | Declares a function/method as a reusable unit of behavior.
L1902 |         if not current_user.is_authenticated: | Conditional branch that runs only when its condition is true.
L1903 |             return { | Returns a value (or control) back to the caller.
L1904 |                 "notification_count": 0, | Operational statement participating in the file's runtime behavior.
L1905 |                 "current_role": "", | Operational statement participating in the file's runtime behavior.
L1906 |                 "app_theme": session.get("theme", "light"), | Operational statement participating in the file's runtime behavior.
L1907 |                 "app_language": session.get("language", "en"), | Operational statement participating in the file's runtime behavior
L1908 |                 "public_holidays": get_public_holidays(), | Operational statement participating in the file's runtime behavior.
L1909 |                 "app_build_id": APP_BUILD_ID, | Operational statement participating in the file's runtime behavior.
L1910 |                 "csrf_token": get_csrf_token(), | Operational statement participating in the file's runtime behavior.
L1911 |                 "photo_library_count": get_photo_library_count(), | Operational statement participating in the file's runtime behav
L1912 |             } | Block delimiter controlling scope/structure in this language.
L1913 | | Blank line used for readability and logical separation.
L1914 |     return { | Returns a value (or control) back to the caller.
L1915 |         "notification_count": calculate_notification_count(), | Operational statement participating in the file's runtime behav
L1916 |         "current_role": normalize_role(current_user.role), | Operational statement participating in the file's runtime behavior
L1917 |         "app_theme": session.get("theme", "light"), | Operational statement participating in the file's runtime behavior.
L1918 |         "app_language": session.get("language", "en"), | Operational statement participating in the file's runtime behavior.
L1919 |         "public_holidays": get_public_holidays(), | Operational statement participating in the file's runtime behavior.
L1920 |         "app_build_id": APP_BUILD_ID, | Operational statement participating in the file's runtime behavior.
L1921 |         "csrf_token": get_csrf_token(), | Operational statement participating in the file's runtime behavior.
L1922 |         "photo_library_count": get_photo_library_count(), | Operational statement participating in the file's runtime behavior.
L1923 |     } | Block delimiter controlling scope/structure in this language.

```

```

L1924 | | Blank line used for readability and logical separation.
L1925 |     register_dashboard_routes( | Operational statement participating in the file's runtime behavior.
L1926 |         app, | Operational statement participating in the file's runtime behavior.
L1927 |         user_model=User, | Assignment statement storing or updating program state.
L1928 |         activity_model=Activity, | Assignment statement storing or updating program state.
L1929 |         message_model=Message, | Assignment statement storing or updating program state.
L1930 |         db=db, | Assignment statement storing or updating program state.
L1931 |         normalize_role=normalize_role, | Assignment statement storing or updating program state.
L1932 |         is_technician_role=is_technician_role, | Assignment statement storing or updating program state.
L1933 |         get_live_dashboard_counts=get_live_dashboard_counts, | Assignment statement storing or updating program state.
L1934 |         calculate_notification_count=calculate_notification_count, | Assignment statement storing or updating program state.
L1935 |         create_activity=create_activity, | Assignment statement storing or updating program state.
L1936 |         get_active_sla_policy=get_active_sla_policy, | Assignment statement storing or updating program state.
L1937 |     ) | Operational statement participating in the file's runtime behavior.
L1938 |     # Expose to the API route (registered above) so it can call it. | Comment line documenting intent or context for nearby code.
L1939 |     app.config["_get_live_dashboard_counts"] = get_live_dashboard_counts | Assignment statement storing or updating program state.
L1940 | | Blank line used for readability and logical separation.
L1941 |     @app.route("/admin/staff/", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L1942 |     @login_required | Decorator line that modifies the behavior of the definition below.
L1943 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L1944 |     def admin_staff(): | Declares a function/method as a reusable unit of behavior.
L1945 |         search_query, users, grouped, pagination = apply_user_search(request.args.get("q")) | Assignment statement storing or updating program state.
L1946 |         if request.method == "POST": | Conditional branch that runs only when its condition is true.
L1947 |             action = (request.form.get("action") or "create_user").strip().lower() | Assignment statement storing or updating program state.
L1948 |             email = (request.form.get("email") or "").strip() | Assignment statement storing or updating program state.
L1949 |             first_name = (request.form.get("first_name") or "").strip() | Assignment statement storing or updating program state.
L1950 |             last_name = (request.form.get("last_name") or "").strip() | Assignment statement storing or updating program state.
L1951 |             region = (request.form.get("region") or "").strip() | Assignment statement storing or updating program state.
L1952 |             role = (request.form.get("role") or "staff").strip().lower() | Assignment statement storing or updating program state.
L1953 |             gender = (request.form.get("gender") or "").strip().lower() | Assignment statement storing or updating program state.
L1954 |             password = (request.form.get("password") or "").strip() | Assignment statement storing or updating program state.
L1955 |             generated_password = False | Assignment statement storing or updating program state.
L1956 |             if not password: | Conditional branch that runs only when its condition is true.
L1957 |                 password = generate_temporary_password() | Assignment statement storing or updating program state.
L1958 |                 generated_password = True | Assignment statement storing or updating program state.
L1959 |             full_name = " ".join(part for part in [first_name, last_name] if part) | Assignment statement storing or updating program state.
L1960 | | Blank line used for readability and logical separation.
L1961 |             if action == "create_technician": | Conditional branch that runs only when its condition is true.
L1962 |                 role = "technician" | Assignment statement storing or updating program state.
L1963 |             elif action == "create_staff": | Conditional branch that runs only when its condition is true.
L1964 |                 role = "staff" | Assignment statement storing or updating program state.
L1965 | | Blank line used for readability and logical separation.
L1966 |             if not email or not first_name or not last_name: | Conditional branch that runs only when its condition is true.
L1967 |                 flash("Fill required fields", "warning") | Operational statement participating in the file's runtime behavior.
L1968 |             elif User.query.filter_by(email=email).first(): | Conditional branch that runs only when its condition is true.
L1969 |                 flash("Email already exists", "danger") | Operational statement participating in the file's runtime behavior.
L1970 |             elif role not in {"developer", "staff", "technician", "manager", "general_manager"}: | Conditional branch that runs only when its condition is true.
L1971 |                 flash("Invalid role selected", "danger") | Operational statement participating in the file's runtime behavior.
L1972 |             else: | Fallback branch executed when prior conditions are false.
L1973 |                 new_user = User( | Assignment statement storing or updating program state.
L1974 |                     email=email, | Assignment statement storing or updating program state.
L1975 |                     uid=generate_uid(role), | Assignment statement storing or updating program state.
L1976 |                     full_name=full_name, | Assignment statement storing or updating program state.
L1977 |                     first_name=first_name, | Assignment statement storing or updating program state.
L1978 |                     last_name=last_name, | Assignment statement storing or updating program state.

```

```

L1979 |         gender=gender or None, | Assignment statement storing or updating program state.
L1980 |         region=region or None, | Assignment statement storing or updating program state.
L1981 |         role=role, | Assignment statement storing or updating program state.
L1982 |         password_hash=hash_password(password), | Assignment statement storing or updating program state.
L1983 |     ) | Operational statement participating in the file's runtime behavior.
L1984 |     db.session.add(new_user) | Operational statement participating in the file's runtime behavior.
L1985 |     db.session.commit() | Operational statement participating in the file's runtime behavior.
L1986 |     store_issued_credentials(new_user, password, "created", is_generated=generated_password) | Assignment statement storing or updating program state.
L1987 |     create_activity("user", f"{current_user.email} created {role} account for {new_user.email}") | Operational statement participating in the file's runtime behavior.
L1988 |     flash(f"{role.replace('_', ' ').title()} account created", "success") | Operational statement participating in the file's runtime behavior.
L1989 |     return redirect(url_for("admin_staff")) | Returns a value (or control) back to the caller.
L1990 | | Blank line used for readability and logical separation.
L1991 |     total_users = User.query.count() | Assignment statement storing or updating program state.
L1992 |     role_page_counts = { | Assignment statement storing or updating program state.
L1993 |         "technician": User.query.filter_by(role="technician").count(), | Assignment statement storing or updating program state.
L1994 |         "staff": User.query.filter_by(role="staff").count(), | Assignment statement storing or updating program state.
L1995 |         "manager": User.query.filter_by(role="manager").count(), | Assignment statement storing or updating program state.
L1996 |         "general_manager": User.query.filter_by(role="general_manager").count(), | Assignment statement storing or updating program state.
L1997 |         "developer": User.query.filter_by(role="developer").count(), | Assignment statement storing or updating program state.
L1998 |     } | Block delimiter controlling scope/structure in this language.
L1999 |     issued_credentials = None | Assignment statement storing or updating program state.
L2000 |     token = session.pop("creds_token", None) | Assignment statement storing or updating program state.
L2001 |     if token: | Conditional branch that runs only when its condition is true.
L2002 |         creds = _pending_creds.pop(token, None) | Assignment statement storing or updating program state.
L2003 |         if creds and creds.get("_exp", 0) >= _time.time(): | Conditional branch that runs only when its condition is true.
L2004 |             creds.pop("_exp", None) | Operational statement participating in the file's runtime behavior.
L2005 |             issued_credentials = creds | Assignment statement storing or updating program state.
L2006 |     avatar_choice_map = get_avatar_choice_map(users) | Assignment statement storing or updating program state.
L2007 |     return render_template( | Returns a value (or control) back to the caller.
L2008 |         "admin_staff.html", | Operational statement participating in the file's runtime behavior.
L2009 |         users=users, | Assignment statement storing or updating program state.
L2010 |         grouped=grouped, | Assignment statement storing or updating program state.
L2011 |         pagination=pagination, | Assignment statement storing or updating program state.
L2012 |         total_users=total_users, | Assignment statement storing or updating program state.
L2013 |         total_user_pages=total_users, | Assignment statement storing or updating program state.
L2014 |         role_page_counts=role_page_counts, | Assignment statement storing or updating program state.
L2015 |         matched_users=pagination.total, | Assignment statement storing or updating program state.
L2016 |         search_query=search_query, | Assignment statement storing or updating program state.
L2017 |         issued_credentials=issued_credentials, | Assignment statement storing or updating program state.
L2018 |         avatar_options=AVATAR_OPTIONS, | Assignment statement storing or updating program state.
L2019 |         avatar_icon_map=AVATAR_ICON_MAP, | Assignment statement storing or updating program state.
L2020 |         avatar_choice_map=avatar_choice_map, | Assignment statement storing or updating program state.
L2021 |     ) | Operational statement participating in the file's runtime behavior.
L2022 | | Blank line used for readability and logical separation.
L2023 |     def _handle_add_user(role: str, template: str): | Declares a function/method as a reusable unit of behavior.
L2024 |         """Shared handler for all add-user routes.""" | Docstring boundary used to describe a module, class, or function.
L2025 |         if request.method == "POST": | Conditional branch that runs only when its condition is true.
L2026 |             email = (request.form.get("email") or "").strip() | Assignment statement storing or updating program state.
L2027 |             first_name = (request.form.get("first_name") or "").strip() | Assignment statement storing or updating program state.
L2028 |             last_name = (request.form.get("last_name") or "").strip() | Assignment statement storing or updating program state.
L2029 |             region = (request.form.get("region") or "").strip() | Assignment statement storing or updating program state.
L2030 |             gender = (request.form.get("gender") or "").strip().lower() | Assignment statement storing or updating program state.
L2031 |             password = (request.form.get("password") or "").strip() | Assignment statement storing or updating program state.
L2032 |             generated_password = False | Assignment statement storing or updating program state.
L2033 |             if not password: | Conditional branch that runs only when its condition is true.

```

```

L2034 |         password = generate_temporary_password() | Assignment statement storing or updating program state.
L2035 |         generated_password = True | Assignment statement storing or updating program state.
L2036 |         full_name = " ".join(part for part in [first_name, last_name] if part) | Assignment statement storing or updating program state.
L2037 | | Blank line used for readability and logical separation.
L2038 |         if not email or not first_name or not last_name: | Conditional branch that runs only when its condition is true.
L2039 |             flash("Fill required fields", "warning") | Operational statement participating in the file's runtime behavior.
L2040 |         elif User.query.filter_by(email=email).first(): | Conditional branch that runs only when its condition is true.
L2041 |             flash("Email already exists", "danger") | Operational statement participating in the file's runtime behavior.
L2042 |         else: | Fallback branch executed when prior conditions are false.
L2043 |             new_user = User( | Assignment statement storing or updating program state.
L2044 |                 email=email, | Assignment statement storing or updating program state.
L2045 |                 uid=generate_uid(role), | Assignment statement storing or updating program state.
L2046 |                 full_name=full_name, | Assignment statement storing or updating program state.
L2047 |                 first_name=first_name, | Assignment statement storing or updating program state.
L2048 |                 last_name=last_name, | Assignment statement storing or updating program state.
L2049 |                 gender=gender or None, | Assignment statement storing or updating program state.
L2050 |                 region=region or None, | Assignment statement storing or updating program state.
L2051 |                 role=role, | Assignment statement storing or updating program state.
L2052 |                 password_hash=hash_password(password), | Assignment statement storing or updating program state.
L2053 |             ) | Operational statement participating in the file's runtime behavior.
L2054 |             db.session.add(new_user) | Operational statement participating in the file's runtime behavior.
L2055 |             db.session.commit() | Operational statement participating in the file's runtime behavior.
L2056 |             store_issued_credentials(new_user, password, "created", is_generated=generated_password) | Assignment statement storing or updating program state.
L2057 |             display = role.replace("_", " ").title() | Assignment statement storing or updating program state.
L2058 |             create_activity("user", f"{current_user.email} created {display} account for {new_user.email}") | Operational statement participating in the file's runtime behavior.
L2059 |             flash(f"{display} account created", "success") | Operational statement participating in the file's runtime behavior.
L2060 |             return redirect(url_for("admin_staff")) | Returns a value (or control) back to the caller.
L2061 | | Blank line used for readability and logical separation.
L2062 |         return render_template(template) | Returns a value (or control) back to the caller.
L2063 | | Blank line used for readability and logical separation.
L2064 |     @app.route("/admin/add-technician/", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L2065 |     @login_required | Decorator line that modifies the behavior of the definition below.
L2066 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L2067 |     def add_technician(): | Declares a function/method as a reusable unit of behavior.
L2068 |         return _handle_add_user("technician", "add_technician.html") | Returns a value (or control) back to the caller.
L2069 | | Blank line used for readability and logical separation.
L2070 |     @app.route("/admin/add-staff/", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L2071 |     @login_required | Decorator line that modifies the behavior of the definition below.
L2072 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L2073 |     def add_staff(): | Declares a function/method as a reusable unit of behavior.
L2074 |         return _handle_add_user("staff", "add_staff.html") | Returns a value (or control) back to the caller.
L2075 | | Blank line used for readability and logical separation.
L2076 |     @app.route("/admin/add-manager/", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L2077 |     @login_required | Decorator line that modifies the behavior of the definition below.
L2078 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L2079 |     def add_manager(): | Declares a function/method as a reusable unit of behavior.
L2080 |         return _handle_add_user("manager", "add_manager.html") | Returns a value (or control) back to the caller.
L2081 | | Blank line used for readability and logical separation.
L2082 |     @app.route("/admin/add-general-manager/", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L2083 |     @login_required | Decorator line that modifies the behavior of the definition below.
L2084 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L2085 |     def add_general_manager(): | Declares a function/method as a reusable unit of behavior.
L2086 |         return _handle_add_user("general_manager", "add_general_manager.html") | Returns a value (or control) back to the caller.
L2087 | | Blank line used for readability and logical separation.
L2088 |     @app.route("/developer/users/block/", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.

```

```

L2089 | @login_required | Decorator line that modifies the behavior of the definition below.
L2090 | @developer_required | Decorator line that modifies the behavior of the definition below.
L2091 | def developer_user_control(): | Declares a function/method as a reusable unit of behavior.
L2092 |     if request.method == "POST": | Conditional branch that runs only when its condition is true.
L2093 |         action = (request.form.get("action") or "").strip() | Assignment statement storing or updating program state.
L2094 |         if action == "update_upload_limits": | Conditional branch that runs only when its condition is true.
L2095 |             try: | Starts an exception handling block for risky operations.
L2096 |                 max_photo_mb = int((request.form.get("max_photo_mb") or "").strip()) | Assignment statement storing or updating program state.
L2097 |                 max_upload_mb = int((request.form.get("max_upload_mb") or "").strip()) | Assignment statement storing or updating program state.
L2098 |             except ValueError: | Handles errors raised in the associated try block.
L2099 |                 flash("Upload limits must be whole numbers.", "warning") | Operational statement participating in the file's runtime behavior.
L2100 |                 return redirect(url_for("developer_user_control")) | Returns a value (or control) back to the caller.
L2101 | | Blank line used for readability and logical separation.
L2102 |             if not (1 <= max_photo_mb <= 20): | Conditional branch that runs only when its condition is true.
L2103 |                 flash("Per-photo limit must be between 1MB and 20MB.", "warning") | Operational statement participating in the file's runtime behavior.
L2104 |                 return redirect(url_for("developer_user_control")) | Returns a value (or control) back to the caller.
L2105 | | Blank line used for readability and logical separation.
L2106 |             min_total_mb = max(16, len(TECHNICIAN_PHOTO_FIELDS) * max_photo_mb) | Assignment statement storing or updating program state.
L2107 |             if not (min_total_mb <= max_upload_mb <= 512): | Conditional branch that runs only when its condition is true.
L2108 |                 flash( | Operational statement participating in the file's runtime behavior.
L2109 |                     f"Total upload limit must be between {min_total_mb}MB and 512MB for the selected per-photo limit.", | Operational statement participating in the file's runtime behavior.
L2110 |                     "warning", | Operational statement participating in the file's runtime behavior.
L2111 |                 ) | Operational statement participating in the file's runtime behavior.
L2112 |                 return redirect(url_for("developer_user_control")) | Returns a value (or control) back to the caller.
L2113 | | Blank line used for readability and logical separation.
L2114 |             app.config["MAX_PHOTO_MB"] = max_photo_mb | Assignment statement storing or updating program state.
L2115 |             app.config["MAX_PHOTO_BYTES"] = max_photo_mb * 1024 * 1024 | Assignment statement storing or updating program state.
L2116 |             app.config["MAX_CONTENT_LENGTH"] = max_upload_mb * 1024 * 1024 | Assignment statement storing or updating program state.
L2117 | | Blank line used for readability and logical separation.
L2118 |             developer_settings = UserSettings.query.filter_by(user_id=current_user.id).first() | Assignment statement storing or updating program state.
L2119 |             if not developer_settings: | Conditional branch that runs only when its condition is true.
L2120 |                 developer_settings = UserSettings(user_id=current_user.id) | Assignment statement storing or updating program state.
L2121 |                 db.session.add(developer_settings) | Operational statement participating in the file's runtime behavior.
L2122 |             preferences = developer_settings.get_preferences() | Assignment statement storing or updating program state.
L2123 |             preferences["system_upload_limits"] = { | Assignment statement storing or updating program state.
L2124 |                 "max_photo_mb": max_photo_mb, | Operational statement participating in the file's runtime behavior.
L2125 |                 "max_upload_mb": max_upload_mb, | Operational statement participating in the file's runtime behavior.
L2126 |             } | Block delimiter controlling scope/structure in this language.
L2127 |             developer_settings.set_preferences(preferences) | Operational statement participating in the file's runtime behavior.
L2128 |             db.session.commit() | Operational statement participating in the file's runtime behavior.
L2129 | | Blank line used for readability and logical separation.
L2130 |             create_activity( | Operational statement participating in the file's runtime behavior.
L2131 |                 "user", | Operational statement participating in the file's runtime behavior.
L2132 |                 f"{current_user.email} updated upload limits: MAX_PHOTO_MB={max_photo_mb}, MAX_UPLOAD_MB={max_upload_mb}", | Assignment statement storing or updating program state.
L2133 |             ) | Operational statement participating in the file's runtime behavior.
L2134 |             flash("Upload limits updated successfully.", "success") | Operational statement participating in the file's runtime behavior.
L2135 |             return redirect(url_for("developer_user_control")) | Returns a value (or control) back to the caller.
L2136 | | Blank line used for readability and logical separation.
L2137 |             if action == "update_role_access_matrix": | Conditional branch that runs only when its condition is true.
L2138 |                 submitted_matrix = {} | Assignment statement storing or updating program state.
L2139 |                 for matrix_key in LOGIN_MATRIX_KEYS: | Loop iterating over a sequence to process elements one by one.
L2140 |                     submitted_matrix[matrix_key] = request.form.getlist(f"matrix_{matrix_key}") | Assignment statement storing or updating program state.
L2141 | | Blank line used for readability and logical separation.
L2142 |                 normalized_matrix = normalize_role_access_matrix(submitted_matrix) | Assignment statement storing or updating program state.
L2143 |                 app.config["ROLE_ACCESS_MATRIX"] = normalized_matrix | Assignment statement storing or updating program state.

```

```
L2144 | | Blank line used for readability and logical separation.
L2145 |         developer_settings = UserSettings.query.filter_by(user_id=current_user.id).first() | Assignment statement storing o
L2146 |         if not developer_settings: | Conditional branch that runs only when its condition is true.
L2147 |             developer_settings = UserSettings(user_id=current_user.id) | Assignment statement storing or updating program s
L2148 |             db.session.add(developer_settings) | Operational statement participating in the file's runtime behavior.
L2149 |             preferences = developer_settings.get_preferences() | Assignment statement storing or updating program state.
L2150 |             preferences["system_role_access_matrix"] = normalized_matrix | Assignment statement storing or updating program sta
L2151 |             developer_settings.set_preferences(preferences) | Operational statement participating in the file's runtime behavior
L2152 |             db.session.commit() | Operational statement participating in the file's runtime behavior.
L2153 | | Blank line used for readability and logical separation.
L2154 |         create_activity( | Operational statement participating in the file's runtime behavior.
L2155 |             "user", | Operational statement participating in the file's runtime behavior.
L2156 |             f"{current_user.email} updated role access matrix: {normalized_matrix}", | Operational statement participating
L2157 |         ) | Operational statement participating in the file's runtime behavior.
L2158 |         flash("Role access matrix updated.", "success") | Operational statement participating in the file's runtime behavior
L2159 |         return redirect(url_for("developer_user_control")) | Returns a value (or control) back to the caller.
L2160 | | Blank line used for readability and logical separation.
L2161 |         if action == "update_photo_library_controls": | Conditional branch that runs only when its condition is true.
L2162 |             include_screenshots = (request.form.get("include_screenshots") or "").strip() == "1" | Operational statement partici
L2163 |             allow_import = (request.form.get("allow_import") or "").strip() == "1" | Operational statement participating in the
L2164 |             try: | Starts an exception handling block for risky operations.
L2165 |                 max_scan_limit = int((request.form.get("max_scan_limit") or "").strip()) | Assignment statement storing or upda
L2166 |             except ValueError: | Handles errors raised in the associated try block.
L2167 |                 flash("Max scan limit must be a whole number.", "warning") | Operational statement participating in the file's
L2168 |                 return redirect(url_for("developer_user_control")) | Returns a value (or control) back to the caller.
L2169 | | Blank line used for readability and logical separation.
L2170 |         normalized_controls = normalize_photo_library_controls( | Assignment statement storing or updating program state.
L2171 |             { | Block delimiter controlling scope/structure in this language.
L2172 |                 "include_screenshots": include_screenshots, | Operational statement participating in the file's runtime beh
L2173 |                 "allow_import": allow_import, | Operational statement participating in the file's runtime behavior.
L2174 |                 "max_scan_limit": max_scan_limit, | Operational statement participating in the file's runtime behavior.
L2175 |             } | Block delimiter controlling scope/structure in this language.
L2176 |         ) | Operational statement participating in the file's runtime behavior.
L2177 |         app.config["PHOTO_LIBRARY_CONTROLS"] = normalized_controls | Assignment statement storing or updating program state
L2178 | | Blank line used for readability and logical separation.
L2179 |         developer_settings = UserSettings.query.filter_by(user_id=current_user.id).first() | Assignment statement storing o
L2180 |         if not developer_settings: | Conditional branch that runs only when its condition is true.
L2181 |             developer_settings = UserSettings(user_id=current_user.id) | Assignment statement storing or updating program s
L2182 |             db.session.add(developer_settings) | Operational statement participating in the file's runtime behavior.
L2183 |             preferences = developer_settings.get_preferences() | Assignment statement storing or updating program state.
L2184 |             preferences["system_photo_library_controls"] = normalized_controls | Assignment statement storing or updating progr
L2185 |             developer_settings.set_preferences(preferences) | Operational statement participating in the file's runtime behavior
L2186 |             db.session.commit() | Operational statement participating in the file's runtime behavior.
L2187 | | Blank line used for readability and logical separation.
L2188 |         create_activity( | Operational statement participating in the file's runtime behavior.
L2189 |             "user", | Operational statement participating in the file's runtime behavior.
L2190 |             f"{current_user.email} updated photo library controls: {normalized_controls}", | Operational statement participi
L2191 |         ) | Operational statement participating in the file's runtime behavior.
L2192 |         flash("Photo library controls updated.", "success") | Operational statement participating in the file's runtime beh
L2193 |         return redirect(url_for("developer_user_control")) | Returns a value (or control) back to the caller.
L2194 | | Blank line used for readability and logical separation.
L2195 |         flash("Unknown developer action.", "warning") | Operational statement participating in the file's runtime behavior.
L2196 |         return redirect(url_for("developer_user_control")) | Returns a value (or control) back to the caller.
L2197 | | Blank line used for readability and logical separation.
L2198 |         users = User.query.order_by(User.created_at.desc()).all() | Assignment statement storing or updating program state.
```

```

L2199 |         recent_user_actions = ( | Assignment statement storing or updating program state.
L2200 |             Activity.query.filter_by(activity_type="user") | Assignment statement storing or updating program state.
L2201 |             .order_by(Activity.created_at.desc()) | CSS selector line choosing the elements styled below.
L2202 |             .limit(25) | CSS selector line choosing the elements styled below.
L2203 |             .all() | CSS selector line choosing the elements styled below.
L2204 |         ) | Operational statement participating in the file's runtime behavior.
L2205 |         issued_credentials = None | Assignment statement storing or updating program state.
L2206 |         token = session.pop("creds_token", None) | Assignment statement storing or updating program state.
L2207 |         if token: | Conditional branch that runs only when its condition is true.
L2208 |             creds = _pending_creds.pop(token, None) | Assignment statement storing or updating program state.
L2209 |             if creds and creds.get("_exp", 0) >= _time.time(): | Conditional branch that runs only when its condition is true.
L2210 |                 creds.pop("_exp", None) | Operational statement participating in the file's runtime behavior.
L2211 |                 issued_credentials = creds | Assignment statement storing or updating program state.
L2212 |         avatar_choice_map = get_avatar_choice_map(users) | Assignment statement storing or updating program state.
L2213 |         user_settings_rows = UserSettings.query.filter(UserSettings.user_id.in_([user.id for user in users])).all() if users else []
L2214 |         user_settings_map = {} | Assignment statement storing or updating program state.
L2215 |         for row in user_settings_rows: | Loop iterating over a sequence to process elements one by one.
L2216 |             prefs = row.get_preferences() | Assignment statement storing or updating program state.
L2217 |             pref_keys = sorted(prefs.keys()) if isinstance(prefs, dict) else [] | Assignment statement storing or updating program state.
L2218 |             hidden_message_ids = prefs.get("hidden_message_ids") if isinstance(prefs, dict) else [] | Assignment statement storing or updating program state.
L2219 |             user_settings_map[row.user_id] = { | Assignment statement storing or updating program state.
L2220 |                 "theme": row.theme or "light", | Operational statement participating in the file's runtime behavior.
L2221 |                 "language": row.language or "en", | Operational statement participating in the file's runtime behavior.
L2222 |                 "preference_keys": pref_keys, | Operational statement participating in the file's runtime behavior.
L2223 |                 "hidden_message_count": len(hidden_message_ids) if isinstance(hidden_message_ids, list) else 0, | Operational statement participating in the file's runtime behavior.
L2224 |             } | Block delimiter controlling scope/structure in this language.
L2225 | | Blank line used for readability and logical separation.
L2226 |         for user in users: | Loop iterating over a sequence to process elements one by one.
L2227 |             user_settings_map.setdefault(user.id, { | Operational statement participating in the file's runtime behavior.
L2228 |                 "theme": "light", | Operational statement participating in the file's runtime behavior.
L2229 |                 "language": "en", | Operational statement participating in the file's runtime behavior.
L2230 |                 "preference_keys": [], | Operational statement participating in the file's runtime behavior.
L2231 |                 "hidden_message_count": 0, | Operational statement participating in the file's runtime behavior.
L2232 |             }, | Operational statement participating in the file's runtime behavior.
L2233 |             ) | Operational statement participating in the file's runtime behavior.
L2234 | | Blank line used for readability and logical separation.
L2235 |         return render_template("developer_user_control.html", | Returns a value (or control) back to the caller.
L2236 |             users=users, | Assignment statement storing or updating program state.
L2237 |             recent_user_actions=recent_user_actions, | Assignment statement storing or updating program state.
L2238 |             max_photo_mb=app.config.get("MAX_PHOTO_MB", 2), | Assignment statement storing or updating program state.
L2239 |             max_upload_mb=max(1, int(app.config.get("MAX_CONTENT_LENGTH", 16 * 1024 * 1024) / (1024 * 1024))), | Assignment statement storing or updating program state.
L2240 |             min_upload_mb=max(16, len(TECHNICIAN_PHOTO_FIELDS) * app.config.get("MAX_PHOTO_MB", 2)), | Assignment statement storing or updating program state.
L2241 |             role_options=["developer", "general_manager", "manager", "staff", "technician"], | Assignment statement storing or updating program state.
L2242 |             issued_credentials=issued_credentials, | Assignment statement storing or updating program state.
L2243 |             role_matrix=app.config.get("ROLE_ACCESS_MATRIX", normalize_role_access_matrix(DEFAULT_ROLE_ACCESS_MATRIX)), | Assignment statement storing or updating program state.
L2244 |             role_matrix_keys=LOGIN_MATRIX_KEYS, | Assignment statement storing or updating program state.
L2245 |             role_matrix_columns=VALID_ACCOUNT_ROLES, | Assignment statement storing or updating program state.
L2246 |             avatar_options=AVATAR_OPTIONS, | Assignment statement storing or updating program state.
L2247 |             avatar_icon_map=AVATAR_ICON_MAP, | Assignment statement storing or updating program state.
L2248 |             avatar_choice_map=avatar_choice_map, | Assignment statement storing or updating program state.
L2249 |             user_settings_map=user_settings_map, | Assignment statement storing or updating program state.
L2250 |             theme_options=["light", "dark"], | Assignment statement storing or updating program state.

```

```

L2254 |         language_options=["en", "sw", "fr", "ar"], | Assignment statement storing or updating program state.
L2255 |         photo_library_controls=normalize_photo_library_controls(app.config.get("PHOTO_LIBRARY_CONTROLS")), | Assignment statement
L2256 |     ) | Operational statement participating in the file's runtime behavior.
L2257 | | Blank line used for readability and logical separation.
L2258 |     @app.route("/developer/photo-library") | Decorator line that modifies the behavior of the definition below.
L2259 |     @login_required | Decorator line that modifies the behavior of the definition below.
L2260 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L2261 |     def developer_photo_library(): | Declares a function/method as a reusable unit of behavior.
L2262 |         query = (request.args.get("q") or "").strip()[:100] | Assignment statement storing or updating program state.
L2263 |         controls = normalize_photo_library_controls(app.config.get("PHOTO_LIBRARY_CONTROLS")) | Assignment statement storing or up
L2264 |         limit_cap = controls["max_scan_limit"] | Assignment statement storing or updating program state.
L2265 |         limit = min(max(request.args.get("limit", 24, type=int), 12), limit_cap) | Assignment statement storing or updating program
L2266 |         photo_entries = get_photo_library_entries(limit=limit, query=query) | Assignment statement storing or updating program sta
L2267 |         total_entries = len(get_photo_library_entries(limit=0, query=query)) | Assignment statement storing or updating program sta
L2268 |         screenshot_count = sum(1 for entry in photo_entries if entry["kind"] == "screenshot") | Operational statement participating
L2269 |         return render_template( | Returns a value (or control) back to the caller.
L2270 |             "developer_photo_library.html", | Operational statement participating in the file's runtime behavior.
L2271 |             photo_entries=photo_entries, | Assignment statement storing or updating program state.
L2272 |             photo_query=query, | Assignment statement storing or updating program state.
L2273 |             photo_limit=limit, | Assignment statement storing or updating program state.
L2274 |             photo_library_total=total_entries, | Assignment statement storing or updating program state.
L2275 |             screenshot_count=screenshot_count, | Assignment statement storing or updating program state.
L2276 |             photo_library_path=app.config.get("PHOTO_LIBRARY_FOLDER", ""), | Assignment statement storing or updating program state
L2277 |             monitored_sources=list(app.config.get("MONITORED_IMAGE_FOLDERS", {}).keys()), | Assignment statement storing or updatin
L2278 |             photo_library_controls=controls, | Assignment statement storing or updating program state.
L2279 |         ) | Operational statement participating in the file's runtime behavior.
L2280 | | Blank line used for readability and logical separation.
L2281 |     @app.route("/developer/photo-library/files/<path:filename>") | Decorator line that modifies the behavior of the definition below
L2282 |     @login_required | Decorator line that modifies the behavior of the definition below.
L2283 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L2284 |     def photo_library_file(filename): | Declares a function/method as a reusable unit of behavior.
L2285 |         extension = os.path.splitext(filename)[1].lower() | Assignment statement storing or updating program state.
L2286 |         if extension not in PHOTO_LIBRARY_IMAGE_EXTENSIONS: | Conditional branch that runs only when its condition is true.
L2287 |             abort(404) | Operational statement participating in the file's runtime behavior.
L2288 | | Blank line used for readability and logical separation.
L2289 |         photo_root = os.path.abspath(app.config["PHOTO_LIBRARY_FOLDER"]) | Assignment statement storing or updating program state.
L2290 |         source_path = os.path.abspath(os.path.join(photo_root, filename)) | Assignment statement storing or updating program state.
L2291 |         if os.path.commonpath([photo_root, source_path]) != photo_root or not os.path.isfile(source_path): | Conditional branch tha
L2292 |             abort(404) | Operational statement participating in the file's runtime behavior.
L2293 | | Blank line used for readability and logical separation.
L2294 |         if not _is_valid_image_file_path(source_path): | Conditional branch that runs only when its condition is true.
L2295 |             abort(404) | Operational statement participating in the file's runtime behavior.
L2296 |         return send_from_directory(app.config["PHOTO_LIBRARY_FOLDER"], filename) | Returns a value (or control) back to the caller.
L2297 | | Blank line used for readability and logical separation.
L2298 |     @app.route("/developer/photo-library/import", methods=["POST"]) | Decorator line that modifies the behavior of the definition b
L2299 |     @login_required | Decorator line that modifies the behavior of the definition below.
L2300 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L2301 |     def import_photo_library_file(): | Declares a function/method as a reusable unit of behavior.
L2302 |         controls = normalize_photo_library_controls(app.config.get("PHOTO_LIBRARY_CONTROLS")) | Assignment statement storing or up
L2303 |         if not controls["allow_import"]: | Conditional branch that runs only when its condition is true.
L2304 |             flash("Import is currently disabled by developer policy.", "warning") | Operational statement participating in the file
L2305 |             return redirect(request.referrer or url_for("developer_photo_library")) | Returns a value (or control) back to the call
L2306 | | Blank line used for readability and logical separation.
L2307 |         filename = (request.form.get("filename") or "").strip() | Assignment statement storing or updating program state.
L2308 |         redirect_target = request.referrer or url_for("developer_photo_library") | Assignment statement storing or updating program

```



```

L2309 |         if not filename: | Conditional branch that runs only when its condition is true.
L2310 |             flash("Choose a photo to import.", "warning") | Operational statement participating in the file's runtime behavior.
L2311 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2312 | | Blank line used for readability and logical separation.
L2313 |         photo_root = os.path.abspath(app.config["PHOTO_LIBRARY_FOLDER"]) | Assignment statement storing or updating program state.
L2314 |         source_path = os.path.abspath(os.path.join(photo_root, filename)) | Assignment statement storing or updating program state.
L2315 |         if os.path.commonpath([photo_root, source_path]) != photo_root or not os.path.isfile(source_path): | Conditional branch tha
L2316 |             flash("Invalid photo selected.", "danger") | Operational statement participating in the file's runtime behavior.
L2317 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2318 | | Blank line used for readability and logical separation.
L2319 |         extension = os.path.splitext(source_path)[1].lower() | Assignment statement storing or updating program state.
L2320 |         if extension not in PHOTO_LIBRARY_IMAGE_EXTENSIONS: | Conditional branch that runs only when its condition is true.
L2321 |             flash("Only image files can be imported.", "warning") | Operational statement participating in the file's runtime behav
L2322 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2323 | | Blank line used for readability and logical separation.
L2324 |         if not _is_valid_image_file_path(source_path): | Conditional branch that runs only when its condition is true.
L2325 |             flash("Selected file failed image validation and cannot be imported.", "warning") | Operational statement participating
L2326 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2327 | | Blank line used for readability and logical separation.
L2328 |         max_bytes = app.config.get("MAX_PHOTO_BYTES", 2 * 1024 * 1024) | Assignment statement storing or updating program state.
L2329 |         source_size = os.path.getsize(source_path) | Assignment statement storing or updating program state.
L2330 |         if source_size > max_bytes: | Conditional branch that runs only when its condition is true.
L2331 |             flash( | Operational statement participating in the file's runtime behavior.
L2332 |                 f"Selected file exceeds MAX_PHOTO_MB ({app.config.get('MAX_PHOTO_MB', 2)}MB).", | Operational statement participati
L2333 |                 "warning", | Operational statement participating in the file's runtime behavior.
L2334 |             ) | Operational statement participating in the file's runtime behavior.
L2335 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2336 | | Blank line used for readability and logical separation.
L2337 |         imported_name = secure_filename(f"{utcnow_naive().timestamp()}_{os.path.basename(filename)}") | Assignment statement storin
L2338 |         target_path = os.path.join(app.config["UPLOAD_FOLDER"], imported_name) | Assignment statement storing or updating program s
L2339 |         shutil.copy2(source_path, target_path) | Operational statement participating in the file's runtime behavior.
L2340 |         create_activity( | Operational statement participating in the file's runtime behavior.
L2341 |             "user", | Operational statement participating in the file's runtime behavior.
L2342 |             f"{current_user.email} imported monitored photo {filename} into uploads as {imported_name}", | Operational statement pa
L2343 |         ) | Operational statement participating in the file's runtime behavior.
L2344 |         flash(f"Imported {filename} into the app upload store.", "success") | Operational statement participating in the file's run
L2345 |         return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2346 | | Blank line used for readability and logical separation.
L2347 |     @app.route("/developer/share-qr.png") | Decorator line that modifies the behavior of the definition below.
L2348 |     @login_required | Decorator line that modifies the behavior of the definition below.
L2349 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L2350 |     def developer_share_qr(): | Declares a function/method as a reusable unit of behavior.
L2351 |         raw_url = (request.args.get("url") or "").strip() | Assignment statement storing or updating program state.
L2352 |         requested_format = (request.args.get("format") or "svg").strip().lower() | Assignment statement storing or updating program
L2353 |         if not raw_url: | Conditional branch that runs only when its condition is true.
L2354 |             return jsonify({"error": "url is required"}), 400 | Returns a value (or control) back to the caller.
L2355 |         if requested_format not in {"svg", "png"}: | Conditional branch that runs only when its condition is true.
L2356 |             return jsonify({"error": "invalid format"}), 400 | Returns a value (or control) back to the caller.
L2357 | | Blank line used for readability and logical separation.
L2358 |         normalized_url = raw_url if "://" in raw_url else f"https://{raw_url}" | Assignment statement storing or updating program s
L2359 |         parsed = urlparse(normalized_url) | Assignment statement storing or updating program state.
L2360 |         if parsed.scheme not in {"http", "https"} or not parsed.netloc: | Conditional branch that runs only when its condition is t
L2361 |             return jsonify({"error": "invalid url"}), 400 | Returns a value (or control) back to the caller.
L2362 | | Blank line used for readability and logical separation.
L2363 |         try: | Starts an exception handling block for risky operations.

```

```

L2364 |         qr_widget = reportlab_qr.QrCodeWidget(parsed.geturl()) | Assignment statement storing or updating program state.
L2365 |         x0, y0, x1, y1 = qr_widget.getBounds() | Assignment statement storing or updating program state.
L2366 |         width = max(1.0, x1 - x0) | Assignment statement storing or updating program state.
L2367 |         height = max(1.0, y1 - y0) | Assignment statement storing or updating program state.
L2368 |         drawing = Drawing(220, 220, transform=[220.0 / width, 0, 0, 220.0 / height, 0, 0]) | Assignment statement storing or up
L2369 |         drawing.add(qr_widget) | Operational statement participating in the file's runtime behavior.
L2370 | | Blank line used for readability and logical separation.
L2371 |         if requested_format == "png": | Conditional branch that runs only when its condition is true.
L2372 |             try: | Starts an exception handling block for risky operations.
L2373 |                 png = renderPM.drawToString(drawing, fmt="PNG") | Assignment statement storing or updating program state.
L2374 |                 if isinstance(png, str): | Conditional branch that runs only when its condition is true.
L2375 |                     png = png.encode("utf-8") | Assignment statement storing or updating program state.
L2376 |                 return send_file( | Returns a value (or control) back to the caller.
L2377 |                     io.BytesIO(png), | Operational statement participating in the file's runtime behavior.
L2378 |                     mimetype="image/png", | Assignment statement storing or updating program state.
L2379 |                     as_attachment=False, | Assignment statement storing or updating program state.
L2380 |                     download_name="pm_rca_login_qr.png", | Assignment statement storing or updating program state.
L2381 |                 ) | Operational statement participating in the file's runtime behavior.
L2382 |             except Exception as png_exc: | Handles errors raised in the associated try block.
L2383 |                 # Some environments miss native PNG backends; serve SVG instead of failing. | Comment line documenting intent o
L2384 |                 app.logger.warning("PNG QR generation failed, falling back to SVG: %s", png_exc) | Operational statement partici
L2385 | | Blank line used for readability and logical separation.
L2386 |                 svg = renderSVG.drawToString(drawing) | Assignment statement storing or updating program state.
L2387 |                 if isinstance(svg, str): | Conditional branch that runs only when its condition is true.
L2388 |                     svg = svg.encode("utf-8") | Assignment statement storing or updating program state.
L2389 |                 except Exception as exc: | Handles errors raised in the associated try block.
L2390 |                     app.logger.warning("QR generation failed for developer share link: %s", exc) | Operational statement participating in t
L2391 |                     return jsonify({"error": "qr generation failed"}), 500 | Returns a value (or control) back to the caller.
L2392 | | Blank line used for readability and logical separation.
L2393 |                 return send_file( | Returns a value (or control) back to the caller.
L2394 |                     io.BytesIO(svg), | Operational statement participating in the file's runtime behavior.
L2395 |                     mimetype="image/svg+xml", | Assignment statement storing or updating program state.
L2396 |                     as_attachment=False, | Assignment statement storing or updating program state.
L2397 |                     download_name="pm_rca_login_qr.svg", | Assignment statement storing or updating program state.
L2398 |                 ) | Operational statement participating in the file's runtime behavior.
L2399 | | Blank line used for readability and logical separation.
L2400 |     @app.route("/admin/staff/<int:user_id>/set-role", methods=["POST"]) | Decorator line that modifies the behavior of the definiti
L2401 |     @login_required | Decorator line that modifies the behavior of the definition below.
L2402 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L2403 |     def set_user_role(user_id): | Declares a function/method as a reusable unit of behavior.
L2404 |         redirect_target = request.referrer or url_for("developer_user_control") | Assignment statement storing or updating program
L2405 |         user = User.query.get_or_404(user_id) | Assignment statement storing or updating program state.
L2406 |         if user.id == current_user.id: | Conditional branch that runs only when its condition is true.
L2407 |             flash("You cannot change your own role from user control.", "warning") | Operational statement participating in the fil
L2408 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2409 | | Blank line used for readability and logical separation.
L2410 |         new_role = normalize_role((request.form.get("role") or "").strip()) | Assignment statement storing or updating program stat
L2411 |         allowed_roles = {"developer", "staff", "technician", "manager", "general_manager"} | Assignment statement storing or updati
L2412 |         if new_role not in allowed_roles: | Conditional branch that runs only when its condition is true.
L2413 |             flash("Invalid role selected.", "danger") | Operational statement participating in the file's runtime behavior.
L2414 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2415 | | Blank line used for readability and logical separation.
L2416 |         previous_role = normalize_role(user.role) | Assignment statement storing or updating program state.
L2417 |         if previous_role == new_role: | Conditional branch that runs only when its condition is true.
L2418 |             flash(f"{user.display_name} is already {new_role.replace('_', ' ').title()}.", "info") | Operational statement particip

```

```

L2419 |         return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2420 | | Blank line used for readability and logical separation.
L2421 |         if previous_role == "developer" and new_role != "developer": | Conditional branch that runs only when its condition is true
L2422 |             developer_count = User.query.filter_by(role="developer").count() | Assignment statement storing or updating program sta
L2423 |             if developer_count <= 1: | Conditional branch that runs only when its condition is true.
L2424 |                 flash("You cannot demote the last remaining developer account.", "warning") | Operational statement participating i
L2425 |                 return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2426 | | Blank line used for readability and logical separation.
L2427 |         user.role = new_role | Assignment statement storing or updating program state.
L2428 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L2429 |         create_activity( | Operational statement participating in the file's runtime behavior.
L2430 |             "user", | Operational statement participating in the file's runtime behavior.
L2431 |             f"{current_user.email} changed role for {user.email}: {previous_role} -> {new_role}", | Operational statement participa
L2432 |         ) | Operational statement participating in the file's runtime behavior.
L2433 |         flash(f"Updated {user.display_name} role to {new_role.replace('_', ' ').title()}.", "success") | Operational statement part
L2434 |         return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2435 | | Blank line used for readability and logical separation.
L2436 |     @app.route("/admin/staff/<int:user_id>/edit-profile", methods=["POST"]) | Decorator line that modifies the behavior of the defi
L2437 |     @login_required | Decorator line that modifies the behavior of the definition below.
L2438 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L2439 |     def edit_user_profile(user_id): | Declares a function/method as a reusable unit of behavior.
L2440 |         redirect_target = request.referrer or url_for("developer_user_control") | Assignment statement storing or updating program
L2441 |         user = User.query.get_or_404(user_id) | Assignment statement storing or updating program state.
L2442 |         actor_email = current_user.email | Assignment statement storing or updating program state.
L2443 |         original_email = user.email | Assignment statement storing or updating program state.
L2444 | | Blank line used for readability and logical separation.
L2445 |         email = (request.form.get("email") or "").strip() | Assignment statement storing or updating program state.
L2446 |         uid = (request.form.get("uid") or "").strip().replace(" ", "").upper() | Assignment statement storing or updating program s
L2447 |         first_name = (request.form.get("first_name") or "").strip() | Assignment statement storing or updating program state.
L2448 |         last_name = (request.form.get("last_name") or "").strip() | Assignment statement storing or updating program state.
L2449 |         region = (request.form.get("region") or "").strip() | Assignment statement storing or updating program state.
L2450 |         gender = (request.form.get("gender") or "").strip().lower() | Assignment statement storing or updating program state.
L2451 |         avatar_key = (request.form.get("avatar_key") or "").strip().lower() | Assignment statement storing or updating program stat
L2452 |         support_desk = (request.form.get("support_desk") or "").strip() | Assignment statement storing or updating program state.
L2453 |         site_operations_phone = (request.form.get("site_operations_phone") or "").strip() | Assignment statement storing or updatin
L2454 |         emergency_phone = (request.form.get("emergency_phone") or "").strip() | Assignment statement storing or updating program st
L2455 | | Blank line used for readability and logical separation.
L2456 |         if not email or not first_name or not last_name: | Conditional branch that runs only when its condition is true.
L2457 |             flash("Email, first name, and last name are required.", "warning") | Operational statement participating in the file's
L2458 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2459 | | Blank line used for readability and logical separation.
L2460 |         if gender and gender not in {"male", "female", "other"}: | Conditional branch that runs only when its condition is true.
L2461 |             flash("Gender must be Male, Female, or Other.", "warning") | Operational statement participating in the file's runtime
L2462 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2463 | | Blank line used for readability and logical separation.
L2464 |         if uid and len(uid) > 12: | Conditional branch that runs only when its condition is true.
L2465 |             flash("UID must be 12 characters or fewer.", "warning") | Operational statement participating in the file's runtime beh
L2466 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2467 | | Blank line used for readability and logical separation.
L2468 |         if avatar_key and avatar_key not in AVATAR_KEYS: | Conditional branch that runs only when its condition is true.
L2469 |             flash("Invalid avatar option selected.", "warning") | Operational statement participating in the file's runtime behavi
L2470 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2471 | | Blank line used for readability and logical separation.
L2472 |         email_owner = User.query.filter(User.email == email, User.id != user.id).first() | Operational statement participating in t
L2473 |         if email_owner: | Conditional branch that runs only when its condition is true.

```

```

L2474 |         flash("Another user already uses that email address.", "danger") | Operational statement participating in the file's runtime behavior.
L2475 |         return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2476 | | Blank line used for readability and logical separation.
L2477 |         if uid: | Conditional branch that runs only when its condition is true.
L2478 |             uid_owner = User.query.filter(User.uid == uid, User.id != user.id).first() | Operational statement participating in the file's runtime behavior.
L2479 |             if uid_owner: | Conditional branch that runs only when its condition is true.
L2480 |                 flash("Another user already uses that UID.", "danger") | Operational statement participating in the file's runtime behavior.
L2481 |                 return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2482 | | Blank line used for readability and logical separation.
L2483 |         full_name = " ".join(part for part in [first_name, last_name] if part) | Assignment statement storing or updating program state.
L2484 |         normalized_gender = gender or None | Assignment statement storing or updating program state.
L2485 |         normalized_uid = uid or None | Assignment statement storing or updating program state.
L2486 |         normalized_region = region or None | Assignment statement storing or updating program state.
L2487 |         normalized_support_desk = support_desk or None | Assignment statement storing or updating program state.
L2488 |         normalized_site_operations_phone = site_operations_phone or None | Assignment statement storing or updating program state.
L2489 |         normalized_emergency_phone = emergency_phone or None | Assignment statement storing or updating program state.
L2490 |         effective_avatar_key = resolve_avatar_key/avatar_key, normalized_gender) | Assignment statement storing or updating program state.
L2491 |         settings_row = UserSettings.query.filter_by(user_id=user.id).first() | Assignment statement storing or updating program state.
L2492 |         existing_avatar_key = None | Assignment statement storing or updating program state.
L2493 |         if settings_row: | Conditional branch that runs only when its condition is true.
L2494 |             existing_prefs = settings_row.get_preferences() | Assignment statement storing or updating program state.
L2495 |             existing_avatar_key = existing_prefs.get("profile_avatar") if isinstance(existing_prefs, dict) else None | Assignment statement storing or updating program state.
L2496 |             current_avatar_key = resolve_avatar_key(existing_avatar_key, user.gender) | Assignment statement storing or updating program state.
L2497 | | Blank line used for readability and logical separation.
L2498 |         changes = [] | Assignment statement storing or updating program state.
L2499 | | Blank line used for readability and logical separation.
L2500 |         def capture_change(label, old_value, new_value): | Declares a function/method as a reusable unit of behavior.
L2501 |             old_clean = old_value or "-" | Assignment statement storing or updating program state.
L2502 |             new_clean = new_value or "-" | Assignment statement storing or updating program state.
L2503 |             if old_clean != new_clean: | Conditional branch that runs only when its condition is true.
L2504 |                 changes.append(f"{label}: {old_clean} -> {new_clean}") | Operational statement participating in the file's runtime behavior.
L2505 | | Blank line used for readability and logical separation.
L2506 |         capture_change("email", user.email, email) | Operational statement participating in the file's runtime behavior.
L2507 |         capture_change("uid", user.uid, normalized_uid) | Operational statement participating in the file's runtime behavior.
L2508 |         capture_change("first_name", user.first_name, first_name) | Operational statement participating in the file's runtime behavior.
L2509 |         capture_change("last_name", user.last_name, last_name) | Operational statement participating in the file's runtime behavior.
L2510 |         capture_change("region", user.region, normalized_region) | Operational statement participating in the file's runtime behavior.
L2511 |         capture_change("gender", user.gender, normalized_gender) | Operational statement participating in the file's runtime behavior.
L2512 |         capture_change("support_desk", user.support_desk, normalized_support_desk) | Operational statement participating in the file's runtime behavior.
L2513 |         capture_change("site_operations_phone", user.site_operations_phone, normalized_site_operations_phone) | Operational statement participating in the file's runtime behavior.
L2514 |         capture_change("emergency_phone", user.emergency_phone, normalized_emergency_phone) | Operational statement participating in the file's runtime behavior.
L2515 |         capture_change("avatar", current_avatar_key, effective_avatar_key) | Operational statement participating in the file's runtime behavior.
L2516 | | Blank line used for readability and logical separation.
L2517 |         if not changes: | Conditional branch that runs only when its condition is true.
L2518 |             flash(f"No profile changes were made for {user.display_name}.", "info") | Operational statement participating in the file's runtime behavior.
L2519 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2520 | | Blank line used for readability and logical separation.
L2521 |         user.email = email | Assignment statement storing or updating program state.
L2522 |         user.uid = normalized_uid | Assignment statement storing or updating program state.
L2523 |         user.first_name = first_name | Assignment statement storing or updating program state.
L2524 |         user.last_name = last_name | Assignment statement storing or updating program state.
L2525 |         user.full_name = full_name | Assignment statement storing or updating program state.
L2526 |         user.region = normalized_region | Assignment statement storing or updating program state.
L2527 |         user.gender = normalized_gender | Assignment statement storing or updating program state.
L2528 |         user.support_desk = normalized_support_desk | Assignment statement storing or updating program state.

```

```

L2529 |         user.site_operations_phone = normalized_site_operations_phone | Assignment statement storing or updating program state.
L2530 |         user.emergency_phone = normalized_emergency_phone | Assignment statement storing or updating program state.
L2531 | | Blank line used for readability and logical separation.
L2532 |         if not settings_row: | Conditional branch that runs only when its condition is true.
L2533 |             settings_row = UserSettings(user_id=user.id) | Assignment statement storing or updating program state.
L2534 |             db.session.add(settings_row) | Operational statement participating in the file's runtime behavior.
L2535 |             prefs = settings_row.get_preferences() | Assignment statement storing or updating program state.
L2536 |             prefs["profile_avatar"] = effective_avatar_key | Assignment statement storing or updating program state.
L2537 |             settings_row.set_preferences(prefs) | Operational statement participating in the file's runtime behavior.
L2538 |             db.session.commit() | Operational statement participating in the file's runtime behavior.
L2539 | | Blank line used for readability and logical separation.
L2540 |         create_activity( | Operational statement participating in the file's runtime behavior.
L2541 |             "user", | Operational statement participating in the file's runtime behavior.
L2542 |             f"{actor_email} edited profile for {original_email}: {'; '.join(changes)}", | Operational statement participating in the
L2543 |             ) | Operational statement participating in the file's runtime behavior.
L2544 |         flash(f"Updated profile for {user.display_name}.", "success") | Operational statement participating in the file's runtime behavior.
L2545 |         return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2546 | | Blank line used for readability and logical separation.
L2547 |     @app.route("/admin/staff/<int:user_id>/update-controls", methods=["POST"]) | Decorator line that modifies the behavior of the controller.
L2548 |     @login_required | Decorator line that modifies the behavior of the definition below.
L2549 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L2550 |     def update_user_controls(user_id): | Declares a function/method as a reusable unit of behavior.
L2551 |         redirect_target = request.referrer or url_for("developer_user_control") | Assignment statement storing or updating program state.
L2552 |         user = User.query.get_or_404(user_id) | Assignment statement storing or updating program state.
L2553 |         action = (request.form.get("developer_control_action") or "update_settings").strip().lower() | Assignment statement storing or updating program state.
L2554 | | Blank line used for readability and logical separation.
L2555 |         settings_row = UserSettings.query.filter_by(user_id=user.id).first() | Assignment statement storing or updating program state.
L2556 |         if not settings_row: | Conditional branch that runs only when its condition is true.
L2557 |             settings_row = UserSettings(user_id=user.id) | Assignment statement storing or updating program state.
L2558 |             db.session.add(settings_row) | Operational statement participating in the file's runtime behavior.
L2559 | | Blank line used for readability and logical separation.
L2560 |         prefs = settings_row.get_preferences() | Assignment statement storing or updating program state.
L2561 |         if not isinstance(prefs, dict): | Conditional branch that runs only when its condition is true.
L2562 |             prefs = {} | Assignment statement storing or updating program state.
L2563 | | Blank line used for readability and logical separation.
L2564 |         if action == "update_settings": | Conditional branch that runs only when its condition is true.
L2565 |             theme = (request.form.get("theme") or "light").strip().lower() | Assignment statement storing or updating program state.
L2566 |             language = (request.form.get("language") or "en").strip().lower() | Assignment statement storing or updating program state.
L2567 |             allowed_themes = {"light", "dark"} | Assignment statement storing or updating program state.
L2568 |             allowed_languages = {"en", "sw", "fr", "ar"} | Assignment statement storing or updating program state.
L2569 | | Blank line used for readability and logical separation.
L2570 |             if theme not in allowed_themes: | Conditional branch that runs only when its condition is true.
L2571 |                 flash("Invalid theme selected.", "warning") | Operational statement participating in the file's runtime behavior.
L2572 |                 return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2573 |             if language not in allowed_languages: | Conditional branch that runs only when its condition is true.
L2574 |                 flash("Invalid language selected.", "warning") | Operational statement participating in the file's runtime behavior.
L2575 |                 return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2576 | | Blank line used for readability and logical separation.
L2577 |             changes = [] | Assignment statement storing or updating program state.
L2578 |             if (settings_row.theme or "light") != theme: | Conditional branch that runs only when its condition is true.
L2579 |                 changes.append(f"theme: {(settings_row.theme or 'light')} -> {theme}") | Operational statement participating in the
L2580 |             if (settings_row.language or "en") != language: | Conditional branch that runs only when its condition is true.
L2581 |                 changes.append(f"language: {(settings_row.language or 'en')} -> {language}") | Operational statement participating in the
L2582 | | Blank line used for readability and logical separation.
L2583 |             if not changes: | Conditional branch that runs only when its condition is true.

```

```

L2584 |         flash(f"No settings changes were made for {user.display_name}.", "info") | Operational statement participating in the
L2585 |         return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2586 | | Blank line used for readability and logical separation.
L2587 |         settings_row.theme = theme | Assignment statement storing or updating program state.
L2588 |         settings_row.language = language | Assignment statement storing or updating program state.
L2589 |         settings_row.set_preferences(prefs) | Operational statement participating in the file's runtime behavior.
L2590 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L2591 |         create_activity( | Operational statement participating in the file's runtime behavior.
L2592 |             "user", | Operational statement participating in the file's runtime behavior.
L2593 |             f"{current_user.email} updated developer controls for {user.email}: {'; '.join(changes)}", | Operational statement
L2594 |         ) | Operational statement participating in the file's runtime behavior.
L2595 |         flash(f"Updated settings for {user.display_name}.", "success") | Operational statement participating in the file's runtime
L2596 |         return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2597 | | Blank line used for readability and logical separation.
L2598 |         if action == "reset_app_settings": | Conditional branch that runs only when its condition is true.
L2599 |             preserved_prefs = {} | Assignment statement storing or updating program state.
L2600 |             existing_avatar_key = prefs.get("profile_avatar") | Assignment statement storing or updating program state.
L2601 |             if existing_avatar_key: | Conditional branch that runs only when its condition is true.
L2602 |                 preserved_prefs["profile_avatar"] = resolve_avatar_key(existing_avatar_key, user.gender) | Assignment statement storing
L2603 | | Blank line used for readability and logical separation.
L2604 |             settings_row.theme = "light" | Assignment statement storing or updating program state.
L2605 |             settings_row.language = "en" | Assignment statement storing or updating program state.
L2606 |             settings_row.set_preferences(preserved_prefs) | Operational statement participating in the file's runtime behavior.
L2607 |             db.session.commit() | Operational statement participating in the file's runtime behavior.
L2608 |             create_activity( | Operational statement participating in the file's runtime behavior.
L2609 |                 "user", | Operational statement participating in the file's runtime behavior.
L2610 |                 f"{current_user.email} reset app settings for {user.email}", | Operational statement participating in the file's runtime
L2611 |             ) | Operational statement participating in the file's runtime behavior.
L2612 |             flash(f"Reset app settings for {user.display_name}.", "success") | Operational statement participating in the file's runtime
L2613 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2614 | | Blank line used for readability and logical separation.
L2615 |         if action == "clear_hidden_messages": | Conditional branch that runs only when its condition is true.
L2616 |             hidden_message_ids = prefs.get("hidden_message_ids") if isinstance(prefs, dict) else None | Assignment statement storing
L2617 |             if isinstance(hidden_message_ids, list) and hidden_message_ids: | Conditional branch that runs only when its condition
L2618 |                 prefs.pop("hidden_message_ids", None) | Operational statement participating in the file's runtime behavior.
L2619 |                 settings_row.set_preferences(prefs) | Operational statement participating in the file's runtime behavior.
L2620 |                 db.session.commit() | Operational statement participating in the file's runtime behavior.
L2621 |                 create_activity( | Operational statement participating in the file's runtime behavior.
L2622 |                     "user", | Operational statement participating in the file's runtime behavior.
L2623 |                     f"{current_user.email} restored hidden inbox messages for {user.email}", | Operational statement participating
L2624 |                 ) | Operational statement participating in the file's runtime behavior.
L2625 |                 flash(f"Restored hidden inbox messages for {user.display_name}.", "success") | Operational statement participating
L2626 |             else: | Fallback branch executed when prior conditions are false.
L2627 |                 flash(f"{user.display_name} has no hidden inbox messages to restore.", "info") | Operational statement participating
L2628 |                 return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2629 | | Blank line used for readability and logical separation.
L2630 |         flash("Unknown developer control action.", "warning") | Operational statement participating in the file's runtime behavior.
L2631 |         return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2632 | | Blank line used for readability and logical separation.
L2633 |     @app.route("/developer/users/<int:user_id>/activity/") | Decorator line that modifies the behavior of the definition below.
L2634 |     @login_required | Decorator line that modifies the behavior of the definition below.
L2635 |     @developer_required | Decorator line that modifies the behavior of the definition below.
L2636 |     def developer_user_activity(user_id): | Declares a function/method as a reusable unit of behavior.
L2637 |         user = User.query.get_or_404(user_id) | Assignment statement storing or updating program state.
L2638 |         q = (request.args.get("q") or "").strip()[:100] | Assignment statement storing or updating program state.

```

```

L2639 |         page = max(1, request.args.get("page", 1, type=int)) | Assignment statement storing or updating program state.
L2640 |         per_page = min(max(10, request.args.get("per_page", 30, type=int)), 100) | Assignment statement storing or updating program state.
L2641 | | Blank line used for readability and logical separation.
L2642 |         activity_query = Activity.query.filter( | Assignment statement storing or updating program state.
L2643 |             or_( | Operational statement participating in the file's runtime behavior.
L2644 |                 Activity.created_by == user.email, | Operational statement participating in the file's runtime behavior.
L2645 |                 Activity.details.ilike(f"%{user.email}%"), | Operational statement participating in the file's runtime behavior.
L2646 |             ) | Operational statement participating in the file's runtime behavior.
L2647 |         ) | Operational statement participating in the file's runtime behavior.
L2648 |     if q: | Conditional branch that runs only when its condition is true.
L2649 |         like = f"%{q}%" | Assignment statement storing or updating program state.
L2650 |         activity_query = activity_query.filter( | Assignment statement storing or updating program state.
L2651 |             or_( | Operational statement participating in the file's runtime behavior.
L2652 |                 Activity.activity_type.ilike(like), | Operational statement participating in the file's runtime behavior.
L2653 |                 Activity.details.ilike(like), | Operational statement participating in the file's runtime behavior.
L2654 |                 Activity.created_by.ilike(like), | Operational statement participating in the file's runtime behavior.
L2655 |             ) | Operational statement participating in the file's runtime behavior.
L2656 |         ) | Operational statement participating in the file's runtime behavior.
L2657 | | Blank line used for readability and logical separation.
L2658 |         pagination = activity_query.order_by(Activity.created_at.desc()).paginate( | Assignment statement storing or updating program state.
L2659 |             page=page, | Assignment statement storing or updating program state.
L2660 |             per_page=per_page, | Assignment statement storing or updating program state.
L2661 |             error_out=False, | Assignment statement storing or updating program state.
L2662 |         ) | Operational statement participating in the file's runtime behavior.
L2663 |     return render_template( | Returns a value (or control) back to the caller.
L2664 |         "developer_user_activity.html", | Operational statement participating in the file's runtime behavior.
L2665 |         target_user=user, | Assignment statement storing or updating program state.
L2666 |         activities=pagination.items, | Assignment statement storing or updating program state.
L2667 |         pagination=pagination, | Assignment statement storing or updating program state.
L2668 |         search_query=q, | Assignment statement storing or updating program state.
L2669 |         per_page=per_page, | Assignment statement storing or updating program state.
L2670 |     ) | Operational statement participating in the file's runtime behavior.
L2671 | | Blank line used for readability and logical separation.
L2672 | @app.route("/admin/staff/<int:user_id>/toggle-block", methods=["POST"]) | Decorator line that modifies the behavior of the definition below.
L2673 | @login_required | Decorator line that modifies the behavior of the definition below.
L2674 | @developer_required | Decorator line that modifies the behavior of the definition below.
L2675 | def toggle_user_block(user_id): | Declares a function/method as a reusable unit of behavior.
L2676 |     next_query = (request.form.get("q") or "").strip() | Assignment statement storing or updating program state.
L2677 |     redirect_target = url_for("admin_staff", q=next_query) if next_query else (request.referrer or url_for("admin_staff")) | Assignment statement storing or updating program state.
L2678 |     user = User.query.get_or_404(user_id) | Assignment statement storing or updating program state.
L2679 |     if user.id == current_user.id: | Conditional branch that runs only when its condition is true.
L2680 |         flash("You cannot block your own account.", "warning") | Operational statement participating in the file's runtime behavior.
L2681 |         return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2682 | | Blank line used for readability and logical separation.
L2683 |     user.is_blocked = not user.is_blocked | Assignment statement storing or updating program state.
L2684 |     db.session.commit() | Operational statement participating in the file's runtime behavior.
L2685 |     create_activity( | Operational statement participating in the file's runtime behavior.
L2686 |         "user", | Operational statement participating in the file's runtime behavior.
L2687 |         f"{current_user.email} {'blocked' if user.is_blocked else 'unblocked'} {user.email}", | Operational statement participating in the file's runtime behavior.
L2688 |     ) | Operational statement participating in the file's runtime behavior.
L2689 |     flash( | Operational statement participating in the file's runtime behavior.
L2690 |         f"{user.display_name} has been {'blocked' if user.is_blocked else 'unblocked'}.", | Operational statement participating in the file's runtime behavior.
L2691 |         "success", | Operational statement participating in the file's runtime behavior.
L2692 |     ) | Operational statement participating in the file's runtime behavior.
L2693 |     return redirect(redirect_target) | Returns a value (or control) back to the caller.

```

```

L2694 | | Blank line used for readability and logical separation.
L2695 | @app.route("/admin/staff/<int:user_id>/delete", methods=["POST"]) | Decorator line that modifies the behavior of the definition
L2696 | @login_required | Decorator line that modifies the behavior of the definition below.
L2697 | @developer_required | Decorator line that modifies the behavior of the definition below.
L2698 | def delete_user(user_id): | Declares a function/method as a reusable unit of behavior.
L2699 |     next_query = (request.form.get("q") or "").strip() | Assignment statement storing or updating program state.
L2700 |     user = User.query.get_or_404(user_id) | Assignment statement storing or updating program state.
L2701 |     if user.id == current_user.id: | Conditional branch that runs only when its condition is true.
L2702 |         flash("You cannot delete your own account.", "warning") | Operational statement participating in the file's runtime beh
L2703 |         return redirect(url_for("admin_staff", q=next_query) if next_query else url_for("admin_staff")) | Returns a value (or c
L2704 |     name = user.display_name | Assignment statement storing or updating program state.
L2705 |     uid = user.uid or str(user.id) | Assignment statement storing or updating program state.
L2706 |     db.session.delete(user) | Operational statement participating in the file's runtime behavior.
L2707 |     db.session.commit() | Operational statement participating in the file's runtime behavior.
L2708 |     create_activity("user", f"{current_user.email} deleted user {name} ({uid})") | Operational statement participating in the f
L2709 |     flash(f"{name} ({uid}) has been deleted.", "success") | Operational statement participating in the file's runtime behavior.
L2710 |     return redirect(url_for("admin_staff", q=next_query) if next_query else url_for("admin_staff")) | Returns a value (or contr
L2711 | | Blank line used for readability and logical separation.
L2712 | @app.route("/admin/staff/<int:user_id>/reset-password", methods=["POST"]) | Decorator line that modifies the behavior of the de
L2713 | @login_required | Decorator line that modifies the behavior of the definition below.
L2714 | @developer_required | Decorator line that modifies the behavior of the definition below.
L2715 | def reset_user_password(user_id): | Declares a function/method as a reusable unit of behavior.
L2716 |     next_query = (request.form.get("q") or "").strip() | Assignment statement storing or updating program state.
L2717 |     redirect_target = url_for("admin_staff", q=next_query) if next_query else (request.referrer or url_for("admin_staff")) | AS
L2718 |     user = db.session.get(User, user_id) | Assignment statement storing or updating program state.
L2719 |     if not user: | Conditional branch that runs only when its condition is true.
L2720 |         abort(404) | Operational statement participating in the file's runtime behavior.
L2721 |     if user.id == current_user.id: | Conditional branch that runs only when its condition is true.
L2722 |         flash("You cannot reset your own password from account management.", "warning") | Operational statement participating i
L2723 |         return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2724 | | Blank line used for readability and logical separation.
L2725 |     current_password = (request.form.get("current_password") or "").strip() or None | Assignment statement storing or updating
L2726 |     new_password = (request.form.get("new_password") or "").strip() | Assignment statement storing or updating program state.
L2727 |     generate_only = (request.form.get("generate_only") or "").strip() == "1" | Operational statement participating in the file
L2728 |     generated_password = False | Assignment statement storing or updating program state.
L2729 |     if not new_password: | Conditional branch that runs only when its condition is true.
L2730 |         if not generate_only: | Conditional branch that runs only when its condition is true.
L2731 |             flash("Enter a password or use Generate Temp.", "warning") | Operational statement participating in the file's runt
L2732 |             return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2733 |             new_password = generate_temporary_password() | Assignment statement storing or updating program state.
L2734 |             generated_password = True | Assignment statement storing or updating program state.
L2735 | | Blank line used for readability and logical separation.
L2736 |     user.password_hash = hash_password(new_password) | Assignment statement storing or updating program state.
L2737 |     db.session.commit() | Operational statement participating in the file's runtime behavior.
L2738 |     store_issued_credentials( | Operational statement participating in the file's runtime behavior.
L2739 |         user, | Operational statement participating in the file's runtime behavior.
L2740 |         new_password, | Operational statement participating in the file's runtime behavior.
L2741 |         "reset", | Operational statement participating in the file's runtime behavior.
L2742 |         previous_password=current_password, | Assignment statement storing or updating program state.
L2743 |         is_generated=generated_password, | Assignment statement storing or updating program state.
L2744 |     ) | Operational statement participating in the file's runtime behavior.
L2745 |     create_activity("user", f"{current_user.email} reset password for {user.email}") | Operational statement participating in t
L2746 |     flash(f"Password reset for {user.display_name}.", "success") | Operational statement participating in the file's runtime be
L2747 |     return redirect(redirect_target) | Returns a value (or control) back to the caller.
L2748 | | Blank line used for readability and logical separation.

```



```

L2749 | @app.route("/field/site-form/", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L2750 | @app.route("/field/rca", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L2751 | @login_required | Decorator line that modifies the behavior of the definition below.
L2752 | @technician_required | Decorator line that modifies the behavior of the definition below.
L2753 | def field_rca(): | Declares a function/method as a reusable unit of behavior.
L2754 |     if request.method == "POST": | Conditional branch that runs only when its condition is true.
L2755 |         site_id = (request.form.get(f"field_{slugify_label('Site Number')}") or "").strip() | Assignment statement storing or updating program state.
L2756 |         site_name = (request.form.get(f"field_{slugify_label('Site Name')}") or "").strip() | Assignment statement storing or updating program state.
L2757 |         activity_type = (request.form.get("activity_type") or "pm").strip().lower() | Assignment statement storing or updating program state.
L2758 | | Blank line used for readability and logical separation.
L2759 |         signature_file = save_signature_image(request.form.get("signature_data"), app.config["UPLOAD_FOLDER"]) | Assignment statement storing or updating program state.
L2760 |         if not signature_file: | Conditional branch that runs only when its condition is true.
L2761 |             flash("Please provide technician signature before submitting.", "warning") | Operational statement participating in the file's runtime behavior.
L2762 |             recent_reports = Activity.query.filter_by(created_by=current_user.email).order_by(Activity.created_at.desc()).limit(10) | Assignment statement storing or updating program state.
L2763 |             return render_template("field_rca.html", | Returns a value (or control) back to the caller.
L2764 |                                     "field_rca.html", | Operational statement participating in the file's runtime behavior.
L2765 |                                     recent_reports=recent_reports, | Assignment statement storing or updating program state.
L2766 |                                     pm_sections=TECHNICIAN_PM_SECTIONS, | Assignment statement storing or updating program state.
L2767 |                                     photo_fields=TECHNICIAN_PHOTO_FIELDS, | Assignment statement storing or updating program state.
L2768 |                                     slugify_label=slugify_label, | Assignment statement storing or updating program state.
L2769 |                                     is_yes_no_label=is_yes_no_label, | Assignment statement storing or updating program state.
L2770 |                                 ) | Operational statement participating in the file's runtime behavior.
L2771 | | Blank line used for readability and logical separation.
L2772 |             photo_lines = [] | Assignment statement storing or updating program state.
L2773 |             for photo_field in TECHNICIAN_PHOTO_FIELDS: | Loop iterating over a sequence to process elements one by one.
L2774 |                 field_name = f"photo_{photo_field['key']}" | Assignment statement storing or updating program state.
L2775 |                 uploaded = request.files.get(field_name) | Assignment statement storing or updating program state.
L2776 |                 if uploaded and uploaded.filename: | Conditional branch that runs only when its condition is true.
L2777 |                     uploaded_size = _stream_size_bytes(uploaded.stream) | Assignment statement storing or updating program state.
L2778 |                     if uploaded_size is not None and uploaded_size > app.config["MAX_PHOTO_BYTES"]: | Conditional branch that runs only when its condition is true.
L2779 |                         flash(f"{photo_field['label']} exceeds {app.config['MAX_PHOTO_MB']}MB. Please compress and try again.", | Operational statement participating in the file's runtime behavior.
L2780 |                               "warning", | Operational statement participating in the file's runtime behavior.
L2781 |                               ) | Operational statement participating in the file's runtime behavior.
L2782 |                         recent_reports = Activity.query.filter_by(created_by=current_user.email).order_by(Activity.created_at.desc()).limit(10) | Assignment statement storing or updating program state.
L2783 |                         return render_template("field_rca.html", | Returns a value (or control) back to the caller.
L2784 |                                                 "field_rca.html", | Operational statement participating in the file's runtime behavior.
L2785 |                                                 recent_reports=recent_reports, | Assignment statement storing or updating program state.
L2786 |                                                 pm_sections=TECHNICIAN_PM_SECTIONS, | Assignment statement storing or updating program state.
L2787 |                                                 photo_fields=TECHNICIAN_PHOTO_FIELDS, | Assignment statement storing or updating program state.
L2788 |                                                 slugify_label=slugify_label, | Assignment statement storing or updating program state.
L2789 |                                                 is_yes_no_label=is_yes_no_label, | Assignment statement storing or updating program state.
L2790 |                                             ) | Operational statement participating in the file's runtime behavior.
L2791 | | Blank line used for readability and logical separation.
L2792 |                     if uploaded and uploaded.filename and allowed_file(uploaded.filename, uploaded.stream): | Conditional branch that runs only when its condition is true.
L2793 |                         filename = secure_filename(f"{utcnow_naive().timestamp()}_{uploaded.filename}") | Assignment statement storing or updating program state.
L2794 |                         local_path = os.path.join(app.config["UPLOAD_FOLDER"], filename) | Assignment statement storing or updating program state.
L2795 |                         uploaded.save(local_path) | Operational statement participating in the file's runtime behavior.
L2796 |                         photo_url = url_for("uploaded_file", filename=filename, _external=True) | Assignment statement storing or updating program state.
L2797 |                         photo_lines.append(f"- {photo_field['label']}: {photo_url}") | Operational statement participating in the file's runtime behavior.
L2798 |                         photo_lines.append( | Operational statement participating in the file's runtime behavior.
L2799 |                             f" System description: {describe_uploaded_photo(photo_field['label'], uploaded.filename)}" | Operational statement participating in the file's runtime behavior.
L2800 |                         ) | Operational statement participating in the file's runtime behavior.
L2801 | | Blank line used for readability and logical separation.
L2802 |                     details = collect_technician_form_details(request.form) | Assignment statement storing or updating program state.

```

```

L2804 |         signature_url = url_for("uploaded_file", filename=signature_file, _external=True) | Assignment statement storing or updating program state.
L2805 | | Blank line used for readability and logical separation.
L2806 |         if activity_type not in {"pm", "rca"}: | Conditional branch that runs only when its condition is true.
L2807 |             flash("Select PM or RCA before submitting the form", "warning") | Operational statement participating in the file's runtime behavior.
L2808 |         elif not site_id or not site_name: | Conditional branch that runs only when its condition is true.
L2809 |             flash("Site Number and Site Name are required", "warning") | Operational statement participating in the file's runtime behavior.
L2810 |         else: | Fallback branch executed when prior conditions are false.
L2811 |             insights = build_form_insights(request.form, photo_lines, activity_type) | Assignment statement storing or updating program state.
L2812 |             if insights["errors"]: | Conditional branch that runs only when its condition is true.
L2813 |                 for err in insights["errors"]: | Loop iterating over a sequence to process elements one by one.
L2814 |                     flash(err, "warning") | Operational statement participating in the file's runtime behavior.
L2815 |             recent_reports = Activity.query.filter_by(created_by=current_user.email).order_by(Activity.created_at.desc()).limit(10) | Assignment statement storing or updating program state.
L2816 |             return render_template("field_rca.html", recent_reports=recent_reports, pm_sections=TECHNICIAN_PM_SECTIONS, photo_fields=TECHNICIAN_PHOTO_FIELDS, slugify_label=slugify_label, is_yes_no_label=is_yes_no_label) | Returns a value (or control) back to the caller.
L2817 |         "field_rca.html", | Operational statement participating in the file's runtime behavior.
L2818 |         recent_reports=recent_reports, | Assignment statement storing or updating program state.
L2819 |         pm_sections=TECHNICIAN_PM_SECTIONS, | Assignment statement storing or updating program state.
L2820 |         photo_fields=TECHNICIAN_PHOTO_FIELDS, | Assignment statement storing or updating program state.
L2821 |         slugify_label=slugify_label, | Assignment statement storing or updating program state.
L2822 |         is_yes_no_label=is_yes_no_label, | Assignment statement storing or updating program state.
L2823 |     ) | Operational statement participating in the file's runtime behavior.
L2824 | | Blank line used for readability and logical separation.
L2825 |     insight_lines = build_insight_lines(insights) | Assignment statement storing or updating program state.
L2826 |     activity = Activity( | Assignment statement storing or updating program state.
L2827 |         activity_type=activity_type, | Assignment statement storing or updating program state.
L2828 |         details="\n".join(details, *insight_lines, "PHOTO SPECIFICATIONS", *photo_lines, "Technician Signature: {signature_url}") | Assignment statement storing or updating program state.
L2829 |     [ | Operational statement participating in the file's runtime behavior.
L2830 |         details, | Operational statement participating in the file's runtime behavior.
L2831 |         "", | Operational statement participating in the file's runtime behavior.
L2832 |         *insight_lines, | Operational statement participating in the file's runtime behavior.
L2833 |         "", | Operational statement participating in the file's runtime behavior.
L2834 |         "PHOTO SPECIFICATIONS", | Operational statement participating in the file's runtime behavior.
L2835 |         *photo_lines, | Operational statement participating in the file's runtime behavior.
L2836 |         "", | Operational statement participating in the file's runtime behavior.
L2837 |         f"Technician Signature: {signature_url}", | Operational statement participating in the file's runtime behavior.
L2838 |     ] | Operational statement participating in the file's runtime behavior.
L2839 |     ), | Operational statement participating in the file's runtime behavior.
L2840 |     created_by=current_user.email, | Assignment statement storing or updating program state.
L2841 |     created_at=utcnow_naive(), | Assignment statement storing or updating program state.
L2842 |     is_approved=False, | Assignment statement storing or updating program state.
L2843 |     risk_score=insights["risk_score"], | Assignment statement storing or updating program state.
L2844 |     sla_deadline=insights["sla_deadline"], | Assignment statement storing or updating program state.
L2845 | ) | Operational statement participating in the file's runtime behavior.
L2846 | db.session.add(activity) | Operational statement participating in the file's runtime behavior.
L2847 | db.session.flush() | Operational statement participating in the file's runtime behavior.
L2848 | | Blank line used for readability and logical separation.
L2849 | # Fan out to all desk-side reviewers as individual assignments/messages. | Comment line documenting intent or context.
L2850 | review_roles = ["staff", "manager", "general_manager"] | Assignment statement storing or updating program state.
L2851 | reviewers = ( | Assignment statement storing or updating program state.
L2852 |     User.query.filter(User.role.in_(review_roles), User.is_blocked.is(False)) | Operational statement participating in the file's runtime behavior.
L2853 |     .with_entities(User.email, User.role) | CSS selector line choosing the elements styled below.
L2854 |     .all() | CSS selector line choosing the elements styled below.
L2855 | ) | Operational statement participating in the file's runtime behavior.
L2856 | | Blank line used for readability and logical separation.
L2857 | severity = "Critical" if insights["is_critical"] else "New" | Assignment statement storing or updating program state.
L2858 | for reviewer in reviewers: | Loop iterating over a sequence to process elements one by one.

```

```

L2859 |         db.session.add( | Operational statement participating in the file's runtime behavior.
L2860 |             FormAssignment( | Operational statement participating in the file's runtime behavior.
L2861 |                 activity_id=activity.id, | Assignment statement storing or updating program state.
L2862 |                 assignee_email=reviewer.email, | Assignment statement storing or updating program state.
L2863 |                 assignee_role=reviewer.role, | Assignment statement storing or updating program state.
L2864 |                 status="pending", | Assignment statement storing or updating program state.
L2865 |                 assigned_at=utcnow_naive(), | Assignment statement storing or updating program state.
L2866 |             ) | Operational statement participating in the file's runtime behavior.
L2867 |         ) | Operational statement participating in the file's runtime behavior.
L2868 |         db.session.add( | Operational statement participating in the file's runtime behavior.
L2869 |             Message( | Operational statement participating in the file's runtime behavior.
L2870 |                 sender_email="system@soliton", | Assignment statement storing or updating program state.
L2871 |                 sender_role="system", | Assignment statement storing or updating program state.
L2872 |                 recipient_role="direct", | Assignment statement storing or updating program state.
L2873 |                 recipient_email=reviewer.email, | Assignment statement storing or updating program state.
L2874 |                 body=( | Assignment statement storing or updating program state.
L2875 |                     f"{severity} {activity_type.upper()} submission #{activity.id} from {current_user.email}. " | Opera
L2876 |                     f"Risk score: {insights['risk_score']}. Please review.\n" | Operational statement participating in
L2877 |                 ), | Operational statement participating in the file's runtime behavior.
L2878 |                 created_at=utcnow_naive(), | Assignment statement storing or updating program state.
L2879 |             ) | Operational statement participating in the file's runtime behavior.
L2880 |         ) | Operational statement participating in the file's runtime behavior.
L2881 | | Blank line used for readability and logical separation.
L2882 |         # Fallback broadcast in case no reviewers are currently available. | Comment line documenting intent or context for
L2883 |         if not reviewers: | Conditional branch that runs only when its condition is true.
L2884 |             db.session.add( | Operational statement participating in the file's runtime behavior.
L2885 |                 Message( | Operational statement participating in the file's runtime behavior.
L2886 |                     sender_email="system@soliton", | Assignment statement storing or updating program state.
L2887 |                     sender_role="system", | Assignment statement storing or updating program state.
L2888 |                     recipient_role="staff", | Assignment statement storing or updating program state.
L2889 |                     recipient_email=None, | Assignment statement storing or updating program state.
L2890 |                     body=( | Assignment statement storing or updating program state.
L2891 |                         f"{severity} {activity_type.upper()} submission #{activity.id} from {current_user.email}. " | Opera
L2892 |                         f"Risk score: {insights['risk_score']}. Please review." | Operational statement participating in th
L2893 |                     ), | Operational statement participating in the file's runtime behavior.
L2894 |                     created_at=utcnow_naive(), | Assignment statement storing or updating program state.
L2895 |                 ) | Operational statement participating in the file's runtime behavior.
L2896 |             ) | Operational statement participating in the file's runtime behavior.
L2897 | | Blank line used for readability and logical separation.
L2898 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L2899 | | Blank line used for readability and logical separation.
L2900 |         flash("Site form submitted to the review team", "success") | Operational statement participating in the file's runt
L2901 |         return redirect(url_for("dashboard")) | Returns a value (or control) back to the caller.
L2902 |         recent_reports = Activity.query.filter_by(created_by=current_user.email).order_by(Activity.created_at.desc()).limit(8).all()
L2903 |         return render_template( | Returns a value (or control) back to the caller.
L2904 |             "field_rca.html", | Operational statement participating in the file's runtime behavior.
L2905 |             recent_reports=recent_reports, | Assignment statement storing or updating program state.
L2906 |             pm_sections=TECHNICIAN_PM_SECTIONS, | Assignment statement storing or updating program state.
L2907 |             photo_fields=TECHNICIAN_PHOTO_FIELDS, | Assignment statement storing or updating program state.
L2908 |             slugify_label=slugify_label, | Assignment statement storing or updating program state.
L2909 |             is_yes_no_label=is_yes_no_label, | Assignment statement storing or updating program state.
L2910 |         ) | Operational statement participating in the file's runtime behavior.
L2911 | | Blank line used for readability and logical separation.
L2912 |         @app.route("/field/rejected-reports/") | Decorator line that modifies the behavior of the definition below.
L2913 |         @login_required | Decorator line that modifies the behavior of the definition below.

```

```

L2914 | @technician_required | Decorator line that modifies the behavior of the definition below.
L2915 | def technician_rejected_reports(): | Declares a function/method as a reusable unit of behavior.
L2916 |     reports = ( | Assignment statement storing or updating program state.
L2917 |         Activity.query.filter( | Operational statement participating in the file's runtime behavior.
L2918 |             Activity.activity_type.in(["pm", "rca"]), | Operational statement participating in the file's runtime behavior.
L2919 |             Activity.created_by == current_user.email, | Operational statement participating in the file's runtime behavior.
L2920 |             Activity.is_approved.is_(False), | Operational statement participating in the file's runtime behavior.
L2921 |             Activity.approved_at.is_not(None), | Operational statement participating in the file's runtime behavior.
L2922 |         ) | Operational statement participating in the file's runtime behavior.
L2923 |         .order_by(Activity.approved_at.desc()) | CSS selector line choosing the elements styled below.
L2924 |         .all() | CSS selector line choosing the elements styled below.
L2925 |     ) | Operational statement participating in the file's runtime behavior.
L2926 |     return render_template("technician_rejected_reports.html", reports=reports) | Returns a value (or control) back to the caller.
L2927 | | Blank line used for readability and logical separation.
L2928 | @app.route("/field/submissions/") | Decorator line that modifies the behavior of the definition below.
L2929 | @login_required | Decorator line that modifies the behavior of the definition below.
L2930 | @technician_required | Decorator line that modifies the behavior of the definition below.
L2931 | def technician_submissions(): | Declares a function/method as a reusable unit of behavior.
L2932 |     view_type = (request.args.get("type") or "all").strip().lower() | Assignment statement storing or updating program state.
L2933 |     if view_type not in {"all", "pm", "rca"}: | Conditional branch that runs only when its condition is true.
L2934 |         view_type = "all" | Assignment statement storing or updating program state.
L2935 | | Blank line used for readability and logical separation.
L2936 |     query = Activity.query.filter( | Assignment statement storing or updating program state.
L2937 |         Activity.activity_type.in(["pm", "rca"]), | Operational statement participating in the file's runtime behavior.
L2938 |         Activity.created_by == current_user.email, | Operational statement participating in the file's runtime behavior.
L2939 |     ) | Operational statement participating in the file's runtime behavior.
L2940 |     if view_type in {"pm", "rca"}: | Conditional branch that runs only when its condition is true.
L2941 |         query = query.filter(Activity.activity_type == view_type) | Operational statement participating in the file's runtime behavior.
L2942 | | Blank line used for readability and logical separation.
L2943 |     page = max(1, request.args.get("page", 1, type=int)) | Assignment statement storing or updating program state.
L2944 |     pagination = query.order_by(Activity.created_at.desc()).paginate(page=page, per_page=20, error_out=False) | Assignment statement storing or updating program state.
L2945 |     return render_template("technician_submissions.html", reports=pagination.items, pagination=pagination, view_type=view_type)
L2946 | | Blank line used for readability and logical separation.
L2947 | @app.route("/field/report/<int:activity_id>/") | Decorator line that modifies the behavior of the definition below.
L2948 | @login_required | Decorator line that modifies the behavior of the definition below.
L2949 | @technician_required | Decorator line that modifies the behavior of the definition below.
L2950 | def technician_activity_view(activity_id): | Declares a function/method as a reusable unit of behavior.
L2951 |     activity = Activity.query.get_or_404(activity_id) | Assignment statement storing or updating program state.
L2952 |     if activity.activity_type not in {"pm", "rca"}: | Conditional branch that runs only when its condition is true.
L2953 |         flash("Only PM and RCA forms can be viewed here.", "warning") | Operational statement participating in the file's runtime behavior.
L2954 |         return redirect(url_for("dashboard")) | Returns a value (or control) back to the caller.
L2955 |     if activity.created_by != current_user.email: | Conditional branch that runs only when its condition is true.
L2956 |         abort(403) | Operational statement participating in the file's runtime behavior.
L2957 |     return render_template("technician_activity_view.html", activity=activity) | Returns a value (or control) back to the caller.
L2958 | | Blank line used for readability and logical separation.
L2959 | @app.route("/technician/calendar/") | Decorator line that modifies the behavior of the definition below.
L2960 | @login_required | Decorator line that modifies the behavior of the definition below.
L2961 | @technician_required | Decorator line that modifies the behavior of the definition below.
L2962 | def technician_calendar(): | Declares a function/method as a reusable unit of behavior.
L2963 |     holidays = sorted(get_public_holidays(), key=lambda item: item.get("date") or "") | Assignment statement storing or updating program state.
L2964 |     return render_template("technician_calendar.html", holidays=holidays) | Returns a value (or control) back to the caller.
L2965 | | Blank line used for readability and logical separation.
L2966 | @app.route("/desk/activities/") | Decorator line that modifies the behavior of the definition below.
L2967 | @login_required | Decorator line that modifies the behavior of the definition below.
L2968 | @desk_required | Decorator line that modifies the behavior of the definition below.

```

```

L2969 |     def desk_activities(): | Declares a function/method as a reusable unit of behavior.
L2970 |         mode = (request.args.get("mode") or "rcas").strip().lower() | Assignment statement storing or updating program state.
L2971 |         if mode not in {"rcas", "forms", "rejected"}: | Conditional branch that runs only when its condition is true.
L2972 |             mode = "rcas" | Assignment statement storing or updating program state.
L2973 | | Blank line used for readability and logical separation.
L2974 |         search_query = (request.args.get("q") or "").strip()[:100] # max 100 chars | Assignment statement storing or updating program state.
L2975 |         created_on = (request.args.get("date") or "").strip() | Assignment statement storing or updating program state.
L2976 |         risk_filter = (request.args.get("risk") or "").strip().lower() | Assignment statement storing or updating program state.
L2977 |         sla_filter = (request.args.get("sla") or "").strip().lower() | Assignment statement storing or updating program state.
L2978 |         page = max(1, request.args.get("page", 1, type=int)) | Assignment statement storing or updating program state.
L2979 |         per_page = min(max(10, request.args.get("per_page", 50, type=int)), 100) | Assignment statement storing or updating program state.
L2980 |         now = utcnow_naive() | Assignment statement storing or updating program state.
L2981 |         active_sla_policy = get_active_sla_policy() | Assignment statement storing or updating program state.
L2982 |         due_soon_hours = active_sla_policy["due_soon_hours"] | Assignment statement storing or updating program state.
L2983 | | Blank line used for readability and logical separation.
L2984 |         technician_emails_query = db.session.query(User.email).filter(User.role == "technician") | Operational statement participating in the file's runtime behavior.
L2985 |         query = Activity.query.filter( | Assignment statement storing or updating program state.
L2986 |             Activity.activity_type.in_([ "pm", "rca" ]), | Operational statement participating in the file's runtime behavior.
L2987 |             Activity.created_by.in_(technician_emails_query), | Operational statement participating in the file's runtime behavior.
L2988 |         ) | Operational statement participating in the file's runtime behavior.
L2989 |         if mode == "rejected": | Conditional branch that runs only when its condition is true.
L2990 |             query = query.filter(Activity.is_approved.is_(False), Activity.approved_at.is_not(None)) | Assignment statement storing or updating program state.
L2991 |         else: | Fallback branch executed when prior conditions are false.
L2992 |             if mode == "rcas": | Conditional branch that runs only when its condition is true.
L2993 |                 query = query.filter(Activity.approved_at.is_(None)) | Assignment statement storing or updating program state.
L2994 | | Blank line used for readability and logical separation.
L2995 |         if search_query: | Conditional branch that runs only when its condition is true.
L2996 |             like_value = f"%{search_query}%" | Assignment statement storing or updating program state.
L2997 |             matching_technician_emails = ( | Assignment statement storing or updating program state.
L2998 |                 db.session.query(User.email) | Operational statement participating in the file's runtime behavior.
L2999 |                 .filter( | CSS selector line choosing the elements styled below.
L3000 |                     User.role == "technician", | Operational statement participating in the file's runtime behavior.
L3001 |                     or_( | Operational statement participating in the file's runtime behavior.
L3002 |                         User.email.ilike(like_value), | Operational statement participating in the file's runtime behavior.
L3003 |                         User.full_name.ilike(like_value), | Operational statement participating in the file's runtime behavior.
L3004 |                         User.first_name.ilike(like_value), | Operational statement participating in the file's runtime behavior.
L3005 |                         User.last_name.ilike(like_value), | Operational statement participating in the file's runtime behavior.
L3006 |                     ), | Operational statement participating in the file's runtime behavior.
L3007 |                 ) | Operational statement participating in the file's runtime behavior.
L3008 |                 .subquery() | CSS selector line choosing the elements styled below.
L3009 |             ) | Operational statement participating in the file's runtime behavior.
L3010 |             query = query.filter( | Assignment statement storing or updating program state.
L3011 |                 (Activity.details.ilike(like_value)) | Operational statement participating in the file's runtime behavior.
L3012 |                 \\\ (Activity.created_by.ilike(like_value)) | Operational statement participating in the file's runtime behavior.
L3013 |                 \\\ (func.cast(Activity.id, db.String).ilike(like_value)) | Operational statement participating in the file's runtime behavior.
L3014 |                 \\\ (Activity.activity_type.ilike(like_value)) | Operational statement participating in the file's runtime behavior.
L3015 |                 \\\ (Activity.details.ilike(f"%Site Number:%{search_query}%")) | Operational statement participating in the file's runtime behavior.
L3016 |                 \\\ (Activity.details.ilike(f"%Site ID:%{search_query}%")) | Operational statement participating in the file's runtime behavior.
L3017 |                 \\\ (Activity.details.ilike(f"%Site Name:%{search_query}%")) | Operational statement participating in the file's runtime behavior.
L3018 |                 \\\ (Activity.created_by.in_(matching_technician_emails)) | Operational statement participating in the file's runtime behavior.
L3019 |             ) | Operational statement participating in the file's runtime behavior.
L3020 | | Blank line used for readability and logical separation.
L3021 |         if created_on: | Conditional branch that runs only when its condition is true.
L3022 |             try: | Starts an exception handling block for risky operations.
L3023 |                 selected_date = datetime.strptime(created_on, "%Y-%m-%d").date() | Assignment statement storing or updating program state.

```

```

L3024 |         query = query.filter(func.date(Activity.created_at) == selected_date) | Operational statement participating in the
L3025 |         except ValueError: | Handles errors raised in the associated try block.
L3026 |         flash("Invalid date filter format.", "warning") | Operational statement participating in the file's runtime behavior.
L3027 | | Blank line used for readability and logical separation.
L3028 |         if risk_filter == "high": | Conditional branch that runs only when its condition is true.
L3029 |             query = query.filter(Activity.risk_score >= HIGH_RISK_THRESHOLD) | Operational statement participating in the file's ru
L3030 |         elif risk_filter == "medium": | Conditional branch that runs only when its condition is true.
L3031 |             query = query.filter( | Assignment statement storing or updating program state.
L3032 |                 Activity.risk_score >= MEDIUM_RISK_THRESHOLD, | Operational statement participating in the file's runtime behavior.
L3033 |                 Activity.risk_score < HIGH_RISK_THRESHOLD, | Operational statement participating in the file's runtime behavior.
L3034 |             ) | Operational statement participating in the file's runtime behavior.
L3035 |         elif risk_filter == "low": | Conditional branch that runs only when its condition is true.
L3036 |             query = query.filter(Activity.risk_score < MEDIUM_RISK_THRESHOLD) | Assignment statement storing or updating program st
L3037 | | Blank line used for readability and logical separation.
L3038 |         if sla_filter == "overdue": | Conditional branch that runs only when its condition is true.
L3039 |             query = query.filter( | Assignment statement storing or updating program state.
L3040 |                 Activity.approved_at.is_(None), | Operational statement participating in the file's runtime behavior.
L3041 |                 Activity.sla_deadline.is_not(None), | Operational statement participating in the file's runtime behavior.
L3042 |                 Activity.sla_deadline < now, | Operational statement participating in the file's runtime behavior.
L3043 |             ) | Operational statement participating in the file's runtime behavior.
L3044 |         elif sla_filter == "due_soon": | Conditional branch that runs only when its condition is true.
L3045 |             query = query.filter( | Assignment statement storing or updating program state.
L3046 |                 Activity.approved_at.is_(None), | Operational statement participating in the file's runtime behavior.
L3047 |                 Activity.sla_deadline.is_not(None), | Operational statement participating in the file's runtime behavior.
L3048 |                 Activity.sla_deadline >= now, | Operational statement participating in the file's runtime behavior.
L3049 |                 Activity.sla_deadline <= now + timedelta(hours=due_soon_hours), | Operational statement participating in the file's
L3050 |             ) | Operational statement participating in the file's runtime behavior.
L3051 |         elif sla_filter == "on_track": | Conditional branch that runs only when its condition is true.
L3052 |             query = query.filter( | Assignment statement storing or updating program state.
L3053 |                 Activity.approved_at.is_(None), | Operational statement participating in the file's runtime behavior.
L3054 |                 Activity.sla_deadline.is_not(None), | Operational statement participating in the file's runtime behavior.
L3055 |                 Activity.sla_deadline > now + timedelta(hours=due_soon_hours), | Assignment statement storing or updating program s
L3056 |             ) | Operational statement participating in the file's runtime behavior.
L3057 | | Blank line used for readability and logical separation.
L3058 |         pagination = query.order_by(Activity.created_at.desc(), Activity.id.desc()).paginate( | Assignment statement storing or upo
L3059 |             page=page, | Assignment statement storing or updating program state.
L3060 |             per_page=per_page, | Assignment statement storing or updating program state.
L3061 |             error_out=False, | Assignment statement storing or updating program state.
L3062 |         ) | Operational statement participating in the file's runtime behavior.
L3063 |         activities = pagination.items | Assignment statement storing or updating program state.
L3064 |         review_rows = build_activity_review_rows(activities) | Assignment statement storing or updating program state.
L3065 | | Blank line used for readability and logical separation.
L3066 |         return render_template( | Returns a value (or control) back to the caller.
L3067 |             "desk_activities.html", | Operational statement participating in the file's runtime behavior.
L3068 |             activities=activities, | Assignment statement storing or updating program state.
L3069 |             pagination=pagination, | Assignment statement storing or updating program state.
L3070 |             review_rows=review_rows, | Assignment statement storing or updating program state.
L3071 |             view_mode=mode, | Assignment statement storing or updating program state.
L3072 |             search_query=search_query, | Assignment statement storing or updating program state.
L3073 |             created_on=created_on, | Assignment statement storing or updating program state.
L3074 |             risk_filter=risk_filter, | Assignment statement storing or updating program state.
L3075 |             sla_filter=sla_filter, | Assignment statement storing or updating program state.
L3076 |             active_sla_policy=active_sla_policy, | Assignment statement storing or updating program state.
L3077 |         ) | Operational statement participating in the file's runtime behavior.
L3078 | | Blank line used for readability and logical separation.

```

```

L3079 | @app.route("/activity/<int:activity_id>/view") | Decorator line that modifies the behavior of the definition below.
L3080 | @login_required | Decorator line that modifies the behavior of the definition below.
L3081 | @desk_required | Decorator line that modifies the behavior of the definition below.
L3082 | def view_activity(activity_id): | Declares a function/method as a reusable unit of behavior.
L3083 |     activity = Activity.query.get_or_404(activity_id) | Assignment statement storing or updating program state.
L3084 |     if activity.activity_type not in {"pm", "rca"}: | Conditional branch that runs only when its condition is true.
L3085 |         flash("Only PM and RCA forms can be viewed here.", "warning") | Operational statement participating in the file's runtime
L3086 |         return redirect(url_for("desk_activities", mode="rcas")) | Returns a value (or control) back to the caller.
L3087 |     return render_template("activity_view.html", activity=activity) | Returns a value (or control) back to the caller.
L3088 | | Blank line used for readability and logical separation.
L3089 | @app.route("/activity/<int:activity_id>/approve", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the
L3090 | @login_required | Decorator line that modifies the behavior of the definition below.
L3091 | @desk_required | Decorator line that modifies the behavior of the definition below.
L3092 | def approve_activity(activity_id): | Declares a function/method as a reusable unit of behavior.
L3093 |     if request.method == "GET": | Conditional branch that runs only when its condition is true.
L3094 |         flash("Use the Approve button on the form view.", "warning") | Operational statement participating in the file's runtime
L3095 |         return redirect(url_for("desk_activities", mode="forms")) | Returns a value (or control) back to the caller.
L3096 |     activity = Activity.query.get_or_404(activity_id) | Assignment statement storing or updating program state.
L3097 |     if activity.activity_type not in {"pm", "rca"}: | Conditional branch that runs only when its condition is true.
L3098 |         flash("Only PM and RCA forms can be approved.", "warning") | Operational statement participating in the file's runtime
L3099 |         return redirect(url_for("desk_activities", mode="rcas")) | Returns a value (or control) back to the caller.
L3100 |     activity.is_approved = True | Assignment statement storing or updating program state.
L3101 |     activity.approved_by = current_user.email | Assignment statement storing or updating program state.
L3102 |     activity.approved_at = utcnow_naive() | Assignment statement storing or updating program state.
L3103 |     FormAssignment.query.filter_by(activity_id=activity.id).update({"status": "approved"}) | Assignment statement storing or up
L3104 |     db.session.commit() | Operational statement participating in the file's runtime behavior.
L3105 |     create_activity("approval", f"{current_user.email} approved {activity.activity_type.upper()} activity #{activity.id}") | Op
L3106 |     flash("Activity approved", "success") | Operational statement participating in the file's runtime behavior.
L3107 |     return redirect(url_for("desk_activities", mode="forms")) | Returns a value (or control) back to the caller.
L3108 | | Blank line used for readability and logical separation.
L3109 | @app.route("/activity/<int:activity_id>/reject", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the de
L3110 | @login_required | Decorator line that modifies the behavior of the definition below.
L3111 | @desk_required | Decorator line that modifies the behavior of the definition below.
L3112 | def reject_activity(activity_id): | Declares a function/method as a reusable unit of behavior.
L3113 |     if request.method == "GET": | Conditional branch that runs only when its condition is true.
L3114 |         flash("Use the Reject button on the form view.", "warning") | Operational statement participating in the file's runtime
L3115 |         return redirect(url_for("desk_activities", mode="rcas")) | Returns a value (or control) back to the caller.
L3116 |     activity = Activity.query.get_or_404(activity_id) | Assignment statement storing or updating program state.
L3117 |     if activity.activity_type not in {"pm", "rca"}: | Conditional branch that runs only when its condition is true.
L3118 |         flash("Only PM and RCA forms can be rejected.", "warning") | Operational statement participating in the file's runtime
L3119 |         return redirect(url_for("desk_activities", mode="rcas")) | Returns a value (or control) back to the caller.
L3120 |     activity.is_approved = False | Assignment statement storing or updating program state.
L3121 |     activity.approved_by = current_user.email | Assignment statement storing or updating program state.
L3122 |     activity.approved_at = utcnow_naive() | Assignment statement storing or updating program state.
L3123 |     FormAssignment.query.filter_by(activity_id=activity.id).update({"status": "rejected"}) | Assignment statement storing or up
L3124 | | Blank line used for readability and logical separation.
L3125 |     if activity.created_by: | Conditional branch that runs only when its condition is true.
L3126 |         submitted_by = User.query.filter_by(email=activity.created_by).first() | Assignment statement storing or updating progr
L3127 |         if submitted_by and is_technician_role(submitted_by.role): | Conditional branch that runs only when its condition is tr
L3128 |             rejection_message = Message( | Assignment statement storing or updating program state.
L3129 |                 sender_email=current_user.email, | Assignment statement storing or updating program state.
L3130 |                 sender_role=current_user.role, | Assignment statement storing or updating program state.
L3131 |                 recipient_role="direct", | Assignment statement storing or updating program state.
L3132 |                 recipient_email=submitted_by.email, | Assignment statement storing or updating program state.
L3133 |                 body=f"Your {activity.activity_type.upper()} form #{activity.id} was rejected. Please review and submit again."

```

```

L3134 |         created_at=utcnow_naive(), | Assignment statement storing or updating program state.
L3135 |     ) | Operational statement participating in the file's runtime behavior.
L3136 |     db.session.add(rejection_message) | Operational statement participating in the file's runtime behavior.
L3137 | | Blank line used for readability and logical separation.
L3138 |     db.session.commit() | Operational statement participating in the file's runtime behavior.
L3139 |     create_activity("approval", f"{current_user.email} rejected {activity.activity_type.upper()} activity #{activity.id}") | Op
L3140 |     flash("Activity rejected. The submitting technician has been notified.", "warning") | Operational statement participating i
L3141 |     return redirect(url_for("desk_activities", mode="rcas")) | Returns a value (or control) back to the caller.
L3142 | | Blank line used for readability and logical separation.
L3143 |     @app.route("/activity/<int:activity_id>/download") | Decorator line that modifies the behavior of the definition below.
L3144 |     @login_required | Decorator line that modifies the behavior of the definition below.
L3145 |     @desk_required | Decorator line that modifies the behavior of the definition below.
L3146 |     def download_activity(activity_id): | Declares a function/method as a reusable unit of behavior.
L3147 |         activity = Activity.query.get_or_404(activity_id) | Assignment statement storing or updating program state.
L3148 |         if activity.activity_type not in {"rca", "pm"}: | Conditional branch that runs only when its condition is true.
L3149 |             flash("Only RCA and PM records can be downloaded", "warning") | Operational statement participating in the file's runti
L3150 |             return redirect(url_for("desk_activities", mode="rcas")) | Returns a value (or control) back to the caller.
L3151 |         if not activity.is_approved: | Conditional branch that runs only when its condition is true.
L3152 |             flash("Only approved PM/RCA forms can be downloaded.", "warning") | Operational statement participating in the file's r
L3153 |             return redirect(url_for("desk_activities", mode="rcas")) | Returns a value (or control) back to the caller.
L3154 | | Blank line used for readability and logical separation.
L3155 |         buffer = io.BytesIO() | Assignment statement storing or updating program state.
L3156 |         p = canvas.Canvas(buffer) | Assignment statement storing or updating program state.
L3157 |         p.setFont("Helvetica-Bold", 16) | Operational statement participating in the file's runtime behavior.
L3158 |         p.drawString(40, 800, f"{activity.activity_type.upper()} Report") | Operational statement participating in the file's runti
L3159 |         p.setFont("Helvetica", 12) | Operational statement participating in the file's runtime behavior.
L3160 |         p.drawString(40, 770, f"Created by: {activity.created_by or 'Unknown'}") | Operational statement participating in the file
L3161 |         p.drawString(40, 750, f"Created at: {activity.created_at}") | Operational statement participating in the file's runtime beh
L3162 |         p.drawString(40, 730, f"Approved: {'Yes' if activity.is_approved else 'No'}") | Operational statement participating in the
L3163 |         p.drawString(40, 710, "Details:") | Operational statement participating in the file's runtime behavior.
L3164 | | Blank line used for readability and logical separation.
L3165 |         text_object = p.beginPath(45, 690) | Assignment statement storing or updating program state.
L3166 |         text_object.setFont("Helvetica", 11) | Operational statement participating in the file's runtime behavior.
L3167 |         for line in activity.details.split("\n"): | Loop iterating over a sequence to process elements one by one.
L3168 |             text_object.textLine(line) | Operational statement participating in the file's runtime behavior.
L3169 |         p.drawText(text_object) | Operational statement participating in the file's runtime behavior.
L3170 | | Blank line used for readability and logical separation.
L3171 |         p.showPage() | Operational statement participating in the file's runtime behavior.
L3172 |         p.save() | Operational statement participating in the file's runtime behavior.
L3173 |         buffer.seek(0) | Operational statement participating in the file's runtime behavior.
L3174 | | Blank line used for readability and logical separation.
L3175 |         return send_file( | Returns a value (or control) back to the caller.
L3176 |             buffer, | Operational statement participating in the file's runtime behavior.
L3177 |             as_attachment=True, | Assignment statement storing or updating program state.
L3178 |             download_name=f"{activity.activity_type}_form_{activity.id}.pdf", | Assignment statement storing or updating program st
L3179 |             mimetype="application/pdf", | Assignment statement storing or updating program state.
L3180 |         ) | Operational statement participating in the file's runtime behavior.
L3181 | | Blank line used for readability and logical separation.
L3182 |     @app.route("/desk/approved-forms/excel") | Decorator line that modifies the behavior of the definition below.
L3183 |     @login_required | Decorator line that modifies the behavior of the definition below.
L3184 |     @desk_required | Decorator line that modifies the behavior of the definition below.
L3185 |     def export_approved_forms_excel(): | Declares a function/method as a reusable unit of behavior.
L3186 |         technician_emails_query = db.session.query(User.email).filter(User.role == "technician") | Operational statement participat
L3187 |         approved_forms = ( | Assignment statement storing or updating program state.
L3188 |             Activity.query.filter( | Operational statement participating in the file's runtime behavior.

```



```

L3189 |         Activity.activity_type.in(["pm", "rca"]), | Operational statement participating in the file's runtime behavior.
L3190 |         Activity.created_by.in(technician_emails_query), | Operational statement participating in the file's runtime behavior.
L3191 |         Activity.is_approved.is_(True), | Operational statement participating in the file's runtime behavior.
L3192 |         Activity.approved_at.is_not(None), | Operational statement participating in the file's runtime behavior.
L3193 |     ) | Operational statement participating in the file's runtime behavior.
L3194 |     .order_by(Activity.approved_at.desc()) | CSS selector line choosing the elements styled below.
L3195 |     .all() | CSS selector line choosing the elements styled below.
L3196 | ) | Operational statement participating in the file's runtime behavior.
L3197 | | Blank line used for readability and logical separation.
L3198 | workbook = Workbook() | Assignment statement storing or updating program state.
L3199 | worksheet = workbook.active | Assignment statement storing or updating program state.
L3200 | if worksheet is None: | Conditional branch that runs only when its condition is true.
L3201 |     raise RuntimeError("Workbook has no active worksheet") | Raises an explicit exception to signal an error condition.
L3202 | worksheet.title = "Approved PM-RCA" | Assignment statement storing or updating program state.
L3203 | | Blank line used for readability and logical separation.
L3204 | headers = [ | Assignment statement storing or updating program state.
L3205 |     "Form ID", | Operational statement participating in the file's runtime behavior.
L3206 |     "Type", | Operational statement participating in the file's runtime behavior.
L3207 |     "Site Number", | Operational statement participating in the file's runtime behavior.
L3208 |     "Site Name", | Operational statement participating in the file's runtime behavior.
L3209 |     "Submitted By", | Operational statement participating in the file's runtime behavior.
L3210 |     "Created At (UTC)", | Operational statement participating in the file's runtime behavior.
L3211 |     "Approved By", | Operational statement participating in the file's runtime behavior.
L3212 |     "Approved At (UTC)", | Operational statement participating in the file's runtime behavior.
L3213 |     "Risk Score", | Operational statement participating in the file's runtime behavior.
L3214 |     "Risk Level", | Operational statement participating in the file's runtime behavior.
L3215 |     "SLA Deadline (UTC)", | Operational statement participating in the file's runtime behavior.
L3216 |     "Top Recommendation", | Operational statement participating in the file's runtime behavior.
L3217 |     "Anomaly Count", | Operational statement participating in the file's runtime behavior.
L3218 |     "Critical", | Operational statement participating in the file's runtime behavior.
L3219 | ] | Operational statement participating in the file's runtime behavior.
L3220 | worksheet.append(headers) | Operational statement participating in the file's runtime behavior.
L3221 | | Blank line used for readability and logical separation.
L3222 | header_fill = PatternFill(fill_type="solid", fgColor="1A73E8") | Assignment statement storing or updating program state.
L3223 | header_font = Font(color="FFFFFF", bold=True) | Assignment statement storing or updating program state.
L3224 | body_font = Font(color="202124") | Assignment statement storing or updating program state.
L3225 | alternate_fill = PatternFill(fill_type="solid", fgColor="F8F9FA") | Assignment statement storing or updating program state.
L3226 | risk_high_fill = PatternFill(fill_type="solid", fgColor="FDE8E9") | Assignment statement storing or updating program state.
L3227 | risk_medium_fill = PatternFill(fill_type="solid", fgColor="FEF7E0") | Assignment statement storing or updating program state.
L3228 | border = Border( | Assignment statement storing or updating program state.
L3229 |     left=Side(style="thin", color="DADCE0"), | Assignment statement storing or updating program state.
L3230 |     right=Side(style="thin", color="DADCE0"), | Assignment statement storing or updating program state.
L3231 |     top=Side(style="thin", color="DADCE0"), | Assignment statement storing or updating program state.
L3232 |     bottom=Side(style="thin", color="DADCE0"), | Assignment statement storing or updating program state.
L3233 | ) | Operational statement participating in the file's runtime behavior.
L3234 | | Blank line used for readability and logical separation.
L3235 | for col_idx, header in enumerate(headers, start=1): | Loop iterating over a sequence to process elements one by one.
L3236 |     cell = worksheet.cell(row=1, column=col_idx) | Assignment statement storing or updating program state.
L3237 |     cell.fill = header_fill | Assignment statement storing or updating program state.
L3238 |     cell.font = header_font | Assignment statement storing or updating program state.
L3239 |     cell.alignment = Alignment(horizontal="center", vertical="center", wrap_text=True) | Assignment statement storing or updating program state.
L3240 |     cell.border = border | Assignment statement storing or updating program state.
L3241 | | Blank line used for readability and logical separation.
L3242 | worksheet.freeze_panes = "A2" | Assignment statement storing or updating program state.
L3243 | worksheet.auto_filter.ref = f"A1:{get_column_letter(len(headers))}1" | Assignment statement storing or updating program state.

```

```

L3244 | | Blank line used for readability and logical separation.
L3245 |         for record in approved_forms: | Loop iterating over a sequence to process elements one by one.
L3246 |             details_map = parse_activity_kv(record.details) | Assignment statement storing or updating program state.
L3247 |             recommendations = extract_recommendations_from_details(record.details) | Assignment statement storing or updating program state.
L3248 |             anomalies = [line for line in (record.details or "").splitlines() if line.strip().startswith("- ") and "anomal" in line]
L3249 |             risk_score = extract_risk_score_from_details(record.details) or 0 | Assignment statement storing or updating program state.
L3250 |             risk_level = classify_risk_level(risk_score) | Assignment statement storing or updating program state.
L3251 |             sla_deadline = extract_sla_deadline_from_details(record.details) | Assignment statement storing or updating program state.
L3252 | | Blank line used for readability and logical separation.
L3253 |         worksheet.append( | Operational statement participating in the file's runtime behavior.
L3254 |             [ | Operational statement participating in the file's runtime behavior.
L3255 |                 record.id, | Operational statement participating in the file's runtime behavior.
L3256 |                 (record.activity_type or "").upper(), | Operational statement participating in the file's runtime behavior.
L3257 |                 details_map.get("site number") or details_map.get("site id") or "", | Operational statement participating in the file's runtime behavior.
L3258 |                 details_map.get("site name") or "", | Operational statement participating in the file's runtime behavior.
L3259 |                 record.created_by or "", | Operational statement participating in the file's runtime behavior.
L3260 |                 record.created_at.strftime("%Y-%m-%d %H:%M:%S") if record.created_at else "", | Operational statement participating in the file's runtime behavior.
L3261 |                 record.approved_by or "", | Operational statement participating in the file's runtime behavior.
L3262 |                 record.approved_at.strftime("%Y-%m-%d %H:%M:%S") if record.approved_at else "", | Operational statement participating in the file's runtime behavior.
L3263 |                 risk_score, | Operational statement participating in the file's runtime behavior.
L3264 |                 risk_level, | Operational statement participating in the file's runtime behavior.
L3265 |                 sla_deadline.strftime("%Y-%m-%d %H:%M:%S") if sla_deadline else "", | Operational statement participating in the file's runtime behavior.
L3266 |                 recommendations[0] if recommendations else "", | Operational statement participating in the file's runtime behavior.
L3267 |                 len(anomalies), | Operational statement participating in the file's runtime behavior.
L3268 |                 "Yes" if "Critical: Yes" in (record.details or "") else "No", | Operational statement participating in the file's runtime behavior.
L3269 |             ] | Operational statement participating in the file's runtime behavior.
L3270 |         ) | Operational statement participating in the file's runtime behavior.
L3271 | | Blank line used for readability and logical separation.
L3272 |         row_idx = worksheet.max_row | Assignment statement storing or updating program state.
L3273 |         risk_value = risk_score | Assignment statement storing or updating program state.
L3274 |         for col_idx in range(1, len(headers) + 1): | Loop iterating over a sequence to process elements one by one.
L3275 |             cell = worksheet.cell(row=row_idx, column=col_idx) | Assignment statement storing or updating program state.
L3276 |             cell.font = body_font | Assignment statement storing or updating program state.
L3277 |             cell.border = border | Assignment statement storing or updating program state.
L3278 |             cell.alignment = Alignment(vertical="top", wrap_text=True) | Assignment statement storing or updating program state.
L3279 |             if row_idx % 2 == 0: | Conditional branch that runs only when its condition is true.
L3280 |                 cell.fill = alternate_fill | Assignment statement storing or updating program state.
L3281 | | Blank line used for readability and logical separation.
L3282 |         # Risk highlighting similar to conditional formatting in sheets | Comment line documenting intent or context for nearby code.
L3283 |         risk_cell = worksheet.cell(row=row_idx, column=9) | Assignment statement storing or updating program state.
L3284 |         if risk_value >= 70: | Conditional branch that runs only when its condition is true.
L3285 |             risk_cell.fill = risk_high_fill | Assignment statement storing or updating program state.
L3286 |             worksheet.cell(row=row_idx, column=10).fill = risk_high_fill | Assignment statement storing or updating program state.
L3287 |             elif risk_value >= 40: | Conditional branch that runs only when its condition is true.
L3288 |                 risk_cell.fill = risk_medium_fill | Assignment statement storing or updating program state.
L3289 |                 worksheet.cell(row=row_idx, column=10).fill = risk_medium_fill | Assignment statement storing or updating program state.
L3290 | | Blank line used for readability and logical separation.
L3291 |         # Right-align numeric columns | Comment line documenting intent or context for nearby code.
L3292 |         worksheet.cell(row=row_idx, column=1).alignment = Alignment(horizontal="right", vertical="top") | Assignment statement storing or updating program state.
L3293 |         worksheet.cell(row=row_idx, column=9).alignment = Alignment(horizontal="right", vertical="top") | Assignment statement storing or updating program state.
L3294 |         worksheet.cell(row=row_idx, column=13).alignment = Alignment(horizontal="right", vertical="top") | Assignment statement storing or updating program state.
L3295 | | Blank line used for readability and logical separation.
L3296 |         # Google Sheets-like friendly widths | Comment line documenting intent or context for nearby code.
L3297 |         column_widths = { | Assignment statement storing or updating program state.
L3298 |             1: 10, | Operational statement participating in the file's runtime behavior.

```

```

L3299 |         2: 10, | Operational statement participating in the file's runtime behavior.
L3300 |         3: 18, | Operational statement participating in the file's runtime behavior.
L3301 |         4: 24, | Operational statement participating in the file's runtime behavior.
L3302 |         5: 26, | Operational statement participating in the file's runtime behavior.
L3303 |         6: 20, | Operational statement participating in the file's runtime behavior.
L3304 |         7: 24, | Operational statement participating in the file's runtime behavior.
L3305 |         8: 20, | Operational statement participating in the file's runtime behavior.
L3306 |         9: 12, | Operational statement participating in the file's runtime behavior.
L3307 |        10: 12, | Operational statement participating in the file's runtime behavior.
L3308 |        11: 20, | Operational statement participating in the file's runtime behavior.
L3309 |        12: 52, | Operational statement participating in the file's runtime behavior.
L3310 |        13: 14, | Operational statement participating in the file's runtime behavior.
L3311 |        14: 10, | Operational statement participating in the file's runtime behavior.
L3312 |     } | Block delimiter controlling scope/structure in this language.
L3313 |     for col_idx, width in column_widths.items(): | Loop iterating over a sequence to process elements one by one.
L3314 |         worksheet.column_dimensions[get_column_letter(col_idx)].width = width | Assignment statement storing or updating program state.
L3315 | | Blank line used for readability and logical separation.
L3316 |     # Summary sheet for quick tracking (like a pivot snapshot) | Comment line documenting intent or context for nearby code.
L3317 |     summary = workbook.create_sheet(title="Summary") | Assignment statement storing or updating program state.
L3318 |     summary_headers = ["Metric", "Value"] | Assignment statement storing or updating program state.
L3319 |     summary.append(summary_headers) | Operational statement participating in the file's runtime behavior.
L3320 |     for col_idx, _ in enumerate(summary_headers, start=1): | Loop iterating over a sequence to process elements one by one.
L3321 |         cell = summary.cell(row=1, column=col_idx) | Assignment statement storing or updating program state.
L3322 |         cell.fill = header_fill | Assignment statement storing or updating program state.
L3323 |         cell.font = header_font | Assignment statement storing or updating program state.
L3324 |         cell.alignment = Alignment(horizontal="center", vertical="center") | Assignment statement storing or updating program state.
L3325 |         cell.border = border | Assignment statement storing or updating program state.
L3326 | | Blank line used for readability and logical separation.
L3327 |     high = 0 | Assignment statement storing or updating program state.
L3328 |     medium = 0 | Assignment statement storing or updating program state.
L3329 |     low = 0 | Assignment statement storing or updating program state.
L3330 |     critical = 0 | Assignment statement storing or updating program state.
L3331 |     for row in worksheet.iter_rows(min_row=2, max_col=14, values_only=True): | Loop iterating over a sequence to process elements one by one.
L3332 |         raw_score = row[8] if len(row) > 8 else 0 | Assignment statement storing or updating program state.
L3333 |         score_text = str(raw_score or "0").strip() | Assignment statement storing or updating program state.
L3334 |         try: | Starts an exception handling block for risky operations.
L3335 |             score = int(float(score_text)) | Assignment statement storing or updating program state.
L3336 |         except (TypeError, ValueError): | Handles errors raised in the associated try block.
L3337 |             score = 0 | Assignment statement storing or updating program state.
L3338 |         raw_critical = row[13] if len(row) > 13 else "" | Assignment statement storing or updating program state.
L3339 |         is_critical = str(raw_critical or "").strip().lower() == "yes" | Operational statement participating in the file's runtime behavior.
L3340 |         if score >= 70: | Conditional branch that runs only when its condition is true.
L3341 |             high += 1 | Assignment statement storing or updating program state.
L3342 |         elif score >= 40: | Conditional branch that runs only when its condition is true.
L3343 |             medium += 1 | Assignment statement storing or updating program state.
L3344 |         else: | Fallback branch executed when prior conditions are false.
L3345 |             low += 1 | Assignment statement storing or updating program state.
L3346 |         if is_critical: | Conditional branch that runs only when its condition is true.
L3347 |             critical += 1 | Assignment statement storing or updating program state.
L3348 | | Blank line used for readability and logical separation.
L3349 |     summary_rows = [ | Assignment statement storing or updating program state.
L3350 |         ("Total Approved Forms", len(approved_forms)), | Operational statement participating in the file's runtime behavior.
L3351 |         ("High Risk", high), | Operational statement participating in the file's runtime behavior.
L3352 |         ("Medium Risk", medium), | Operational statement participating in the file's runtime behavior.
L3353 |         ("Low Risk", low), | Operational statement participating in the file's runtime behavior.

```

```

L3354 |         ("Critical Forms", critical), | Operational statement participating in the file's runtime behavior.
L3355 |         ("Generated At (UTC)", utcnow_naive().strftime("%Y-%m-%d %H:%M:%S")), | Operational statement participating in the file
L3356 |     ] | Operational statement participating in the file's runtime behavior.
L3357 |     for metric, value in summary_rows: | Loop iterating over a sequence to process elements one by one.
L3358 |         summary.append([metric, value]) | Operational statement participating in the file's runtime behavior.
L3359 | | Blank line used for readability and logical separation.
L3360 |     for row_idx in range(2, summary.max_row + 1): | Loop iterating over a sequence to process elements one by one.
L3361 |         for col_idx in range(1, 3): | Loop iterating over a sequence to process elements one by one.
L3362 |             cell = summary.cell(row=row_idx, column=col_idx) | Assignment statement storing or updating program state.
L3363 |             cell.border = border | Assignment statement storing or updating program state.
L3364 |             cell.font = body_font | Assignment statement storing or updating program state.
L3365 |             if row_idx % 2 == 0: | Conditional branch that runs only when its condition is true.
L3366 |                 cell.fill = alternate_fill | Assignment statement storing or updating program state.
L3367 | | Blank line used for readability and logical separation.
L3368 |         summary.column_dimensions["A"].width = 28 | Assignment statement storing or updating program state.
L3369 |         summary.column_dimensions["B"].width = 24 | Assignment statement storing or updating program state.
L3370 | | Blank line used for readability and logical separation.
L3371 |         buffer = io.BytesIO() | Assignment statement storing or updating program state.
L3372 |         workbook.save(buffer) | Operational statement participating in the file's runtime behavior.
L3373 |         buffer.seek(0) | Operational statement participating in the file's runtime behavior.
L3374 | | Blank line used for readability and logical separation.
L3375 |         timestamp = utcnow_naive().strftime("%Y%m%d_%H%M%S") | Assignment statement storing or updating program state.
L3376 |         return send_file( | Returns a value (or control) back to the caller.
L3377 |             buffer, | Operational statement participating in the file's runtime behavior.
L3378 |             as_attachment=True, | Assignment statement storing or updating program state.
L3379 |             download_name=f"approved_pm_rca_forms_{timestamp}.xlsx", | Assignment statement storing or updating program state.
L3380 |             mimetype="application/vnd.openxmlformats-officedocument.spreadsheetml.sheet", | Assignment statement storing or updating
L3381 |         ) | Operational statement participating in the file's runtime behavior.
L3382 | | Blank line used for readability and logical separation.
L3383 |     @app.route("/consumables/", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L3384 |     @login_required | Decorator line that modifies the behavior of the definition below.
L3385 |     def consumables(): | Declares a function/method as a reusable unit of behavior.
L3386 |         if current_user.role != "developer": | Conditional branch that runs only when its condition is true.
L3387 |             abort(403) | Operational statement participating in the file's runtime behavior.
L3388 |         if is_technician_role(current_user.role): | Conditional branch that runs only when its condition is true.
L3389 |             flash("Technicians can only use the site form page.", "warning") | Operational statement participating in the file's ru
L3390 |             return redirect(url_for("field_rca")) | Returns a value (or control) back to the caller.
L3391 | | Blank line used for readability and logical separation.
L3392 |         if request.method == "POST": | Conditional branch that runs only when its condition is true.
L3393 |             site_id = request.form.get("site_id", "").strip() | Assignment statement storing or updating program state.
L3394 |             site_name = request.form.get("site_name", "").strip() | Assignment statement storing or updating program state.
L3395 |             description = request.form.get("description", "").strip() | Assignment statement storing or updating program state.
L3396 |             created_by = current_user.email | Assignment statement storing or updating program state.
L3397 |             location = request.form.get("location", "").strip() | Assignment statement storing or updating program state.
L3398 | | Blank line used for readability and logical separation.
L3399 |             # file URLs if provided | Comment line documenting intent or context for nearby code.
L3400 |             signage_image_url = request.form.get("signage_image_url", "").strip() | Assignment statement storing or updating progra
L3401 |             screenshot_url = request.form.get("screenshot_url", "").strip() | Assignment statement storing or updating program stat
L3402 |             before_usage_image_url = request.form.get("before_usage_image_url", "").strip() | Assignment statement storing or updat
L3403 | | Blank line used for readability and logical separation.
L3404 |             # local file uploads | Comment line documenting intent or context for nearby code.
L3405 |             for field_name, model_field in [ | Loop iterating over a sequence to process elements one by one.
L3406 |                 ("signage_image_file", "signage_image_url"), | Operational statement participating in the file's runtime behavior.
L3407 |                 ("screenshot_file", "screenshot_url"), | Operational statement participating in the file's runtime behavior.
L3408 |                 ("before_usage_file", "before_usage_image_url"), | Operational statement participating in the file's runtime behavi

```

```

L3409 |         ]: | Operational statement participating in the file's runtime behavior.
L3410 |         file_obj = request.files.get(field_name) | Assignment statement storing or updating program state.
L3411 |         if file_obj and file_obj.filename and allowed_file(file_obj.filename, file_obj.stream): | Conditional branch that runs only when its condition is true.
L3412 |             filename = secure_filename(f"{utcnow_naive().timestamp()}_{file_obj.filename}") | Assignment statement storing or updating program state.
L3413 |             local_path = os.path.join(app.config["UPLOAD_FOLDER"], filename) | Assignment statement storing or updating program state.
L3414 |             file_obj.save(local_path) | Operational statement participating in the file's runtime behavior.
L3415 |             uploaded_url = url_for("uploaded_file", filename=filename, _external=True) | Assignment statement storing or updating program state.
L3416 |             if field_name == "signage_image_file": | Conditional branch that runs only when its condition is true.
L3417 |                 signage_image_url = uploaded_url | Assignment statement storing or updating program state.
L3418 |             elif field_name == "screenshot_file": | Conditional branch that runs only when its condition is true.
L3419 |                 screenshot_url = uploaded_url | Assignment statement storing or updating program state.
L3420 |             else: | Fallback branch executed when prior conditions are false.
L3421 |                 before_usage_image_url = uploaded_url | Assignment statement storing or updating program state.
L3422 | | Blank line used for readability and logical separation.
L3423 |         # optional S3 upload | Comment line documenting intent or context for nearby code.
L3424 |         if app.config.get("S3_BUCKET"): | Conditional branch that runs only when its condition is true.
L3425 |             s3 = boto3.client( | Assignment statement storing or updating program state.
L3426 |                 "s3", | Operational statement participating in the file's runtime behavior.
L3427 |                 aws_access_key_id=app.config.get("S3_KEY"), | Assignment statement storing or updating program state.
L3428 |                 aws_secret_access_key=app.config.get("S3_SECRET"), | Assignment statement storing or updating program state.
L3429 |                 region_name=app.config.get("S3_REGION"), | Assignment statement storing or updating program state.
L3430 |             ) | Operational statement participating in the file's runtime behavior.
L3431 |         def upload_s3(local_value): | Declares a function/method as a reusable unit of behavior.
L3432 |             if local_value and local_value.startswith(app.config["UPLOAD_FOLDER"]): | Conditional branch that runs only when its condition is true.
L3433 |                 key = os.path.basename(local_value) | Assignment statement storing or updating program state.
L3434 |                 # Private by default – use pre-signed URLs for access, not public-read. | Comment line documenting intent or context for nearby code.
L3435 |                 s3.upload_file(local_value, app.config["S3_BUCKET"], key) | Operational statement participating in the file's runtime behavior.
L3436 |                 return f"https://{app.config['S3_BUCKET']}.s3.{app.config['S3_REGION']}.amazonaws.com/{key}" | Returns a value (or control) back to the caller.
L3437 |             return None | Returns a value (or control) back to the caller.
L3438 | | Blank line used for readability and logical separation.
L3439 |             if signage_image_url and signage_image_url.startswith("http://") is False and signage_image_url.startswith("https://") is False:
L3440 |                 signage_image_url = upload_s3(signage_image_url) or signage_image_url | Assignment statement storing or updating program state.
L3441 |             if screenshot_url and screenshot_url.startswith("http://") is False and screenshot_url.startswith("https://") is False:
L3442 |                 screenshot_url = upload_s3(screenshot_url) or screenshot_url | Assignment statement storing or updating program state.
L3443 |             if before_usage_image_url and before_usage_image_url.startswith("http://") is False and before_usage_image_url.startswith("https://") is False:
L3444 |                 before_usage_image_url = upload_s3(before_usage_image_url) or before_usage_image_url | Assignment statement storing or updating program state.
L3445 | | Blank line used for readability and logical separation.
L3446 |         created_by = current_user.email | Assignment statement storing or updating program state.
L3447 |         if not (site_id and site_name and description and created_by): | Conditional branch that runs only when its condition is true.
L3448 |             flash("Site ID, Site Name, Description, Created By are required", "danger") | Operational statement participating in the file's runtime behavior.
L3449 |         else: | Fallback branch executed when prior conditions are false.
L3450 |             new_item = Consumable( | Assignment statement storing or updating program state.
L3451 |                 site_id=site_id, | Assignment statement storing or updating program state.
L3452 |                 site_name=site_name, | Assignment statement storing or updating program state.
L3453 |                 description=description, | Assignment statement storing or updating program state.
L3454 |                 created_by=created_by, | Assignment statement storing or updating program state.
L3455 |                 location=location, | Assignment statement storing or updating program state.
L3456 |                 signage_image_url=signage_image_url or None, | Assignment statement storing or updating program state.
L3457 |                 screenshot_url=screenshot_url or None, | Assignment statement storing or updating program state.
L3458 |                 before_usage_image_url=before_usage_image_url or None, | Assignment statement storing or updating program state.
L3459 |                 created_at=utcnow_naive(), | Assignment statement storing or updating program state.
L3460 |             ) | Operational statement participating in the file's runtime behavior.
L3461 |         db.session.add(new_item) | Operational statement participating in the file's runtime behavior.
L3462 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L3463 |         create_activity("consumable", f"Added consumable at {site_name} ({site_id})") | Operational statement participating in the file's runtime behavior.

```

```

L3464 |         flash("Consumable added", "success") | Operational statement participating in the file's runtime behavior.
L3465 |         return redirect(url_for("consumables")) | Returns a value (or control) back to the caller.
L3466 | | Blank line used for readability and logical separation.
L3467 |         search_query = (request.args.get("q") or "").strip()[:100] | Assignment statement storing or updating program state.
L3468 |         page = max(1, request.args.get("page", 1, type=int)) | Assignment statement storing or updating program state.
L3469 |         per_page = min(max(10, request.args.get("per_page", 50, type=int)), 200) | Assignment statement storing or updating program state.
L3470 |         query = Consumable.query | Assignment statement storing or updating program state.
L3471 |         if search_query: | Conditional branch that runs only when its condition is true.
L3472 |             like_value = f"%{search_query}%" | Assignment statement storing or updating program state.
L3473 |             query = query.filter( | Assignment statement storing or updating program state.
L3474 |                 or_( | Operational statement participating in the file's runtime behavior.
L3475 |                     Consumable.site_id.ilike(like_value), | Operational statement participating in the file's runtime behavior.
L3476 |                     Consumable.site_name.ilike(like_value), | Operational statement participating in the file's runtime behavior.
L3477 |                     Consumable.description.ilike(like_value), | Operational statement participating in the file's runtime behavior.
L3478 |                     Consumable.created_by.ilike(like_value), | Operational statement participating in the file's runtime behavior.
L3479 |                 ) | Operational statement participating in the file's runtime behavior.
L3480 |             ) | Operational statement participating in the file's runtime behavior.
L3481 |         pagination = query.order_by(Consumable.created_at.desc(), Consumable.id.desc()).paginate( | Assignment statement storing or
L3482 |             page=page, | Assignment statement storing or updating program state.
L3483 |             per_page=per_page, | Assignment statement storing or updating program state.
L3484 |             error_out=False, | Assignment statement storing or updating program state.
L3485 |         ) | Operational statement participating in the file's runtime behavior.
L3486 |         return render_template( | Returns a value (or control) back to the caller.
L3487 |             "consumables.html", | Operational statement participating in the file's runtime behavior.
L3488 |             consumables=pagination.items, | Assignment statement storing or updating program state.
L3489 |             pagination=pagination, | Assignment statement storing or updating program state.
L3490 |             search_query=search_query, | Assignment statement storing or updating program state.
L3491 |         ) | Operational statement participating in the file's runtime behavior.
L3492 | | Blank line used for readability and logical separation.
L3493 |     @app.route("/consumables/<int:item_id>/") | Decorator line that modifies the behavior of the definition below.
L3494 |     @login_required | Decorator line that modifies the behavior of the definition below.
L3495 |     def consumable_detail(item_id): | Declares a function/method as a reusable unit of behavior.
L3496 |         item = db.session.get(Consumable, item_id) | Assignment statement storing or updating program state.
L3497 |         if not item: | Conditional branch that runs only when its condition is true.
L3498 |             abort(404) | Operational statement participating in the file's runtime behavior.
L3499 |             return render_template("consumable_detail.html", item=item) | Returns a value (or control) back to the caller.
L3500 | | Blank line used for readability and logical separation.
L3501 |     @app.route("/emergency/") | Decorator line that modifies the behavior of the definition below.
L3502 |     @login_required | Decorator line that modifies the behavior of the definition below.
L3503 |     def emergency(): | Declares a function/method as a reusable unit of behavior.
L3504 |         return render_template("emergency.html") | Returns a value (or control) back to the caller.
L3505 | | Blank line used for readability and logical separation.
L3506 |     @app.route('/uploads/<filename>') | Decorator line that modifies the behavior of the definition below.
L3507 |     @login_required | Decorator line that modifies the behavior of the definition below.
L3508 |     def uploaded_file(filename): | Declares a function/method as a reusable unit of behavior.
L3509 |         return send_from_directory(app.config['UPLOAD_FOLDER'], filename) | Returns a value (or control) back to the caller.
L3510 | | Blank line used for readability and logical separation.
L3511 | | Blank line used for readability and logical separation.
L3512 |     @app.route("/not-found/") | Decorator line that modifies the behavior of the definition below.
L3513 |     @app.route("/404") | Decorator line that modifies the behavior of the definition below.
L3514 |     def not_found_page(): | Declares a function/method as a reusable unit of behavior.
L3515 |         return render_template("not_found.html"), 404 | Returns a value (or control) back to the caller.
L3516 | | Blank line used for readability and logical separation.
L3517 |     @app.errorhandler(404) | Decorator line that modifies the behavior of the definition below.
L3518 |     def not_found_error(error): | Declares a function/method as a reusable unit of behavior.

```

```

L3519 |         return render_template('not_found.html'), 404 | Returns a value (or control) back to the caller.
L3520 | | Blank line used for readability and logical separation.
L3521 |     @app.errorhandler(RequestEntityTooLarge) | Decorator line that modifies the behavior of the definition below.
L3522 |     def request_entity_too_large(error): | Declares a function/method as a reusable unit of behavior.
L3523 |         max_upload_mb = max(1, int(app.config.get("MAX_CONTENT_LENGTH", 16 * 1024 * 1024) / (1024 * 1024))) | Assignment statement
L3524 |         if request.path.startswith("/api/"): | Conditional branch that runs only when its condition is true.
L3525 |             return jsonify({"error": f"Upload exceeds {max_upload_mb}MB limit."}), 413 | Returns a value (or control) back to the c
L3526 |             flash(f"Upload failed: file is larger than {max_upload_mb}MB limit.", "danger") | Operational statement participating in th
L3527 |             return redirect(request.referrer or url_for("field_rca")) | Returns a value (or control) back to the caller.
L3528 | | Blank line used for readability and logical separation.
L3529 |     @app.errorhandler(Exception) | Decorator line that modifies the behavior of the definition below.
L3530 |     def handle_error(e): | Declares a function/method as a reusable unit of behavior.
L3531 |         if isinstance(e, HTTPException): | Conditional branch that runs only when its condition is true.
L3532 |             return e | Returns a value (or control) back to the caller.
L3533 | | Blank line used for readability and logical separation.
L3534 |         app.logger.exception("Unhandled exception during %s %s", request.method, request.path) | Operational statement participating
L3535 |         send_alert(f"Unhandled exception on {request.method} {request.path}: {str(e)}") | Operational statement participating in th
L3536 |         return "Internal Server Error", 500 | Returns a value (or control) back to the caller.
L3537 | | Blank line used for readability and logical separation.
L3538 |     return app | Returns a value (or control) back to the caller.
L3539 | | Blank line used for readability and logical separation.
L3540 | | Blank line used for readability and logical separation.
L3541 | def seed_data(): | Declares a function/method as a reusable unit of behavior.
L3542 |     entries = [ | Assignment statement storing or updating program state.
L3543 |         Consumable( | Operational statement participating in the file's runtime behavior.
L3544 |             site_id="605528", | Assignment statement storing or updating program state.
L3545 |             site_name="Kiganda", | Assignment statement storing or updating program state.
L3546 |             description="1L coolant used during svc", | Assignment statement storing or updating program state.
L3547 |             created_by="jeffkakoto41@gmail.com", | Assignment statement storing or updating program state.
L3548 |             signage_image_url="https://via.placeholder.com/800x400?text=Signage+Image", | Assignment statement storing or updating
L3549 |             screenshot_url="https://via.placeholder.com/800x400?text=WhatsApp+Screenshot", | Assignment statement storing or updati
L3550 |             before_usage_image_url="https://via.placeholder.com/800x400?text=Before+Usage", | Assignment statement storing or updat
L3551 |             created_at=datetime(2026, 3, 22, 12, 16), | Assignment statement storing or updating program state.
L3552 |             location="0.4591N 31.6836E", | Assignment statement storing or updating program state.
L3553 |         ), | Operational statement participating in the file's runtime behavior.
L3554 |         Consumable( | Operational statement participating in the file's runtime behavior.
L3555 |             site_id="701963", | Assignment statement storing or updating program state.
L3556 |             site_name="Kalamba", | Assignment statement storing or updating program state.
L3557 |             description="1L coolant used during svc", | Assignment statement storing or updating program state.
L3558 |             created_by="jeffkakoto41@gmail.com", | Assignment statement storing or updating program state.
L3559 |             signage_image_url="https://via.placeholder.com/800x400?text=Signage+Image", | Assignment statement storing or updating
L3560 |             screenshot_url="https://via.placeholder.com/800x400?text=WhatsApp+Screenshot", | Assignment statement storing or updati
L3561 |             before_usage_image_url="https://via.placeholder.com/800x400?text=Before+Usage", | Assignment statement storing or updat
L3562 |             created_at=datetime(2026, 3, 22, 12, 14), | Assignment statement storing or updating program state.
L3563 |             location="0.4485N 31.6660E", | Assignment statement storing or updating program state.
L3564 |         ), | Operational statement participating in the file's runtime behavior.
L3565 |     ] | Operational statement participating in the file's runtime behavior.
L3566 | | Blank line used for readability and logical separation.
L3567 |     activities = [ | Assignment statement storing or updating program state.
L3568 |         Activity(activity_type="rca", details="AIRTEL DCDB vandalized ...", created_by="jeffkakoto41@gmail.com"), | Assignment stat
L3569 |         Activity(activity_type="rca", details="Weak starter battery", created_by="jeffkakoto41@gmail.com"), | Assignment statement
L3570 |         Activity(activity_type="rca", details="4 Damaged solar panels", created_by="jeffkakoto41@gmail.com"), | Assignment statemen
L3571 |         Activity(activity_type="snag", details="Razor wire needed", created_by="jeffkakoto41@gmail.com"), | Assignment statement st
L3572 |         Activity(activity_type="snag", details="Faded signage", created_by="jeffkakoto41@gmail.com"), | Assignment statement storin
L3573 |         Activity(activity_type="snag", details="Faulty rectifier fans", created_by="jeffkakoto41@gmail.com"), | Assignment statemen

```

L3574 | Activity(activity_type="dar", details="DAR for weekly checks", created_by="jeffkakoto41@gmail.com"), | Assignment statement
L3575 |] | Operational statement participating in the file's runtime behavior.
L3576 | | Blank line used for readability and logical separation.
L3577 | for e in entries: | Loop iterating over a sequence to process elements one by one.
L3578 | db.session.add(e) | Operational statement participating in the file's runtime behavior.
L3579 | | Blank line used for readability and logical separation.
L3580 | for a in activities: | Loop iterating over a sequence to process elements one by one.
L3581 | db.session.add(a) | Operational statement participating in the file's runtime behavior.
L3582 | | Blank line used for readability and logical separation.
L3583 | db.session.commit() | Operational statement participating in the file's runtime behavior.
L3584 | | Blank line used for readability and logical separation.
L3585 | | Blank line used for readability and logical separation.
L3586 | if __name__ == "__main__": | Conditional branch that runs only when its condition is true.
L3587 | app = create_app() | Assignment statement storing or updating program state.
L3588 | app.run(| Operational statement participating in the file's runtime behavior.
L3589 | debug=os.getenv("FLASK_DEBUG", "0") == "1", | Operational statement participating in the file's runtime behavior.
L3590 | use_reloader=os.getenv("FLASK_USE_RELOADER", "0") == "1", | Operational statement participating in the file's runtime behavior.
L3591 | host="0.0.0.0", | Assignment statement storing or updating program state.
L3592 |) | Operational statement participating in the file's runtime behavior.

File 11: app_asgi.py

```
L0001 | from asgiref.wsgi import WsgiToAsgi | Imports specific names from another module for direct usage.  
L0002 | | Blank line used for readability and logical separation.  
L0003 | from app import create_app | Imports specific names from another module for direct usage.  
L0004 | | Blank line used for readability and logical separation.  
L0005 | | Blank line used for readability and logical separation.  
L0006 | flask_app = create_app() | Assignment statement storing or updating program state.  
L0007 | asgi_app = WsgiToAsgi(flask_app) | Assignment statement storing or updating program state.
```

File 12: Caddyfile

L0001 | { | Block delimiter controlling scope/structure in this language.

L0002 | # Use Caddy's internal CA for production-like local/LAN HTTPS. | Comment line documenting intent or context for nearby code.

L0003 | local_certs | Operational statement participating in the file's runtime behavior.

L0004 | } | Block delimiter controlling scope/structure in this language.

L0005 | | Blank line used for readability and logical separation.

L0006 | {\$SERVER_NAME:localhost} { | Block delimiter controlling scope/structure in this language.

L0007 | encode gzip zstd | Operational statement participating in the file's runtime behavior.

L0008 | tls internal | Operational statement participating in the file's runtime behavior.

L0009 | | Blank line used for readability and logical separation.

L0010 | header { | Block delimiter controlling scope/structure in this language.

L0011 | Strict-Transport-Security "max-age=31536000; includeSubDomains" | Assignment statement storing or updating program state.

L0012 | X-Content-Type-Options "nosniff" | Operational statement participating in the file's runtime behavior.

L0013 | X-Frame-Options "SAMEORIGIN" | Operational statement participating in the file's runtime behavior.

L0014 | Referrer-Policy "strict-origin-when-cross-origin" | Operational statement participating in the file's runtime behavior.

L0015 | } | Block delimiter controlling scope/structure in this language.

L0016 | | Blank line used for readability and logical separation.

L0017 | reverse_proxy web:8000 | Operational statement participating in the file's runtime behavior.

L0018 | } | Block delimiter controlling scope/structure in this language.

File 13: change_log_backup.csv

L0001		time,file,event,before_loc,after_loc		Operational statement participating in the file's runtime behavior.
L0002		2026-03-27 23:40:49,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1031,1035		Operational statement participating in the file's runtime behavior.
L0003		2026-03-27 23:43:04,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1035,1027		Operational statement participating in the file's runtime behavior.
L0004		2026-03-27 23:45:53,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,85,85		Operational statement participating in the file's runtime behavior.
L0005		2026-03-27 23:45:58,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,132,132		Operational statement participating in the file's runtime behavior.
L0006		2026-03-27 23:46:09,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,322,323		Operational statement participating in the file's runtime behavior.
L0007		2026-03-27 23:46:19,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,323,322		Operational statement participating in the file's runtime behavior.
L0008		2026-03-27 23:47:11,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1027,1034		Operational statement participating in the file's runtime behavior.
L0009		2026-03-27 23:51:33,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,85,1		Operational statement participating in the file's runtime behavior.
L0010		2026-03-27 23:51:33,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,1,85		Operational statement participating in the file's runtime behavior.
L0011		2026-03-27 23:51:33,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,132,132		Operational statement participating in the file's runtime behavior.
L0012		2026-03-27 23:51:33,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,322,1		Operational statement participating in the file's runtime behavior.
L0013		2026-03-27 23:51:33,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,1,322		Operational statement participating in the file's runtime behavior.
L0014		2026-03-27 23:51:33,C:\Users\jonas\OneDrive\Desktop\pm\templates\login.html,modified,57,57		Operational statement participating in the file's runtime behavior.
L0015		2026-03-27 23:56:36,C:\Users\jonas\OneDrive\Desktop\pm\advanced_watchdog_script.py,modified,278,307		Operational statement participating in the file's runtime behavior.
L0016		2026-03-27 23:56:46,C:\Users\jonas\OneDrive\Desktop\pm\advanced_watchdog_script.py,modified,307,307		Operational statement participating in the file's runtime behavior.
L0017		2026-03-28 00:10:39,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,85,87		Operational statement participating in the file's runtime behavior.
L0018		2026-03-28 00:10:39,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,132,134		Operational statement participating in the file's runtime behavior.
L0019		2026-03-28 00:12:03,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,87,87		Operational statement participating in the file's runtime behavior.
L0020		2026-03-28 00:14:03,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,665,700		Operational statement participating in the file's runtime behavior.
L0021		2026-03-28 00:17:21,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,134,132		Operational statement participating in the file's runtime behavior.
L0022		2026-03-28 00:25:05,C:\Users\jonas\OneDrive\Desktop\pm\model.py,modified,65,74		Operational statement participating in the file's runtime behavior.
L0023		2026-03-28 00:25:25,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1034,1102		Operational statement participating in the file's runtime behavior.
L0024		2026-03-28 00:25:36,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,132,168		Operational statement participating in the file's runtime behavior.
L0025		2026-03-28 00:25:57,C:\Users\jonas\OneDrive\Desktop\pm\templates\admin_staff.html,modified,55,127		Operational statement participating in the file's runtime behavior.
L0026		2026-03-28 00:28:33,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1102,1117		Operational statement participating in the file's runtime behavior.
L0027		2026-03-28 00:28:38,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,168,168		Operational statement participating in the file's runtime behavior.
L0028		2026-03-28 00:28:47,C:\Users\jonas\OneDrive\Desktop\pm\templates\developer_user_control.html,created,0,0		Operational statement participating in the file's runtime behavior.
L0029		2026-03-28 00:28:49,C:\Users\jonas\OneDrive\Desktop\pm\templates\developer_user_control.html,modified,0,53		Operational statement participating in the file's runtime behavior.
L0030		2026-03-28 00:30:53,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,87,87		Operational statement participating in the file's runtime behavior.
L0031		2026-03-28 00:35:18,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,322,0		Operational statement participating in the file's runtime behavior.
L0032		2026-03-28 00:35:18,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,0,322		Operational statement participating in the file's runtime behavior.
L0033		2026-03-28 00:39:02,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1117,1137		Operational statement participating in the file's runtime behavior.
L0034		2026-03-28 00:39:12,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,87,97		Operational statement participating in the file's runtime behavior.
L0035		2026-03-28 00:39:22,C:\Users\jonas\OneDrive\Desktop\pm\templates\notifications.html,created,0,0		Operational statement participating in the file's runtime behavior.
L0036		2026-03-28 00:39:23,C:\Users\jonas\OneDrive\Desktop\pm\templates\notifications.html,modified,0,24		Operational statement participating in the file's runtime behavior.
L0037		2026-03-28 00:39:33,C:\Users\jonas\OneDrive\Desktop\pm\templates\emergency.html,modified,14,56		Operational statement participating in the file's runtime behavior.
L0038		2026-03-28 00:39:47,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,700,797		Operational statement participating in the file's runtime behavior.
L0039		2026-03-28 00:46:38,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,97,96		Operational statement participating in the file's runtime behavior.
L0040		2026-03-28 00:48:53,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1137,1165		Operational statement participating in the file's runtime behavior.
L0041		2026-03-28 00:49:00,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,96,97		Operational statement participating in the file's runtime behavior.
L0042		2026-03-28 00:49:28,C:\Users\jonas\OneDrive\Desktop\pm\templates\settings.html,created,0,0		Operational statement participating in the file's runtime behavior.
L0043		2026-03-28 00:49:31,C:\Users\jonas\OneDrive\Desktop\pm\templates\settings.html,modified,0,130		Operational statement participating in the file's runtime behavior.
L0044		2026-03-28 00:49:52,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,797,998		Operational statement participating in the file's runtime behavior.
L0045		2026-03-28 00:50:02,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,168,193		Operational statement participating in the file's runtime behavior.
L0046		2026-03-28 00:54:00,C:\Users\jonas\OneDrive\Desktop\pm\model.py,modified,74,87		Operational statement participating in the file's runtime behavior.
L0047		2026-03-28 00:54:14,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1165,1212		Operational statement participating in the file's runtime behavior.
L0048		2026-03-28 00:54:25,C:\Users\jonas\OneDrive\Desktop\pm\templates\notifications.html,modified,24,72		Operational statement participating in the file's runtime behavior.
L0049		2026-03-28 00:54:36,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,998,1011		Operational statement participating in the file's runtime behavior.
L0050		2026-03-28 00:58:11,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1212,1286		Operational statement participating in the file's runtime behavior.
L0051		2026-03-28 00:58:26,C:\Users\jonas\OneDrive\Desktop\pm\templates\add_technician.html,created,0,0		Operational statement participating in the file's runtime behavior.
L0052		2026-03-28 00:58:27,C:\Users\jonas\OneDrive\Desktop\pm\templates\add_staff.html,created,0,0		Operational statement participating in the file's runtime behavior.
L0053		2026-03-28 00:58:27,C:\Users\jonas\OneDrive\Desktop\pm\templates\add_technician.html,modified,0,36		Operational statement participating in the file's runtime behavior.

L0054 | 2026-03-28 00:58:28,C:\Users\jonas\OneDrive\Desktop\pm\templates\add_staff.html,modified,0,39 | Operational statement participating

L0055 | 2026-03-28 00:58:35,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,193,193 | Operational statement participat

L0056 | 2026-03-28 01:03:24,C:\Users\jonas\OneDrive\Desktop\pm\model.py,modified,87,88 | Operational statement participating in the file's

L0057 | 2026-03-28 01:03:45,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1286,1366 | Operational statement participating in the file'

L0058 | 2026-03-28 01:03:54,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,97,97 | Operational statement participating i

L0059 | 2026-03-28 01:04:03,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,193,226 | Operational statement participat

L0060 | 2026-03-28 01:04:28,C:\Users\jonas\OneDrive\Desktop\pm\templates\admin_staff.html,modified,127,58 | Operational statement participa

L0061 | 2026-03-28 01:04:39,C:\Users\jonas\OneDrive\Desktop\pm\templates\add_technician.html,modified,36,44 | Operational statement partici

L0062 | 2026-03-28 01:04:39,C:\Users\jonas\OneDrive\Desktop\pm\templates\add_staff.html,modified,39,47 | Operational statement participat

L0063 | 2026-03-28 01:04:53,C:\Users\jonas\OneDrive\Desktop\pm\templates\add_manager.html,created,0,0 | Operational statement participating

L0064 | 2026-03-28 01:04:54,C:\Users\jonas\OneDrive\Desktop\pm\templates\add_general_manager.html,created,0,0 | Operational statement parti

L0065 | 2026-03-28 01:04:54,C:\Users\jonas\OneDrive\Desktop\pm\templates\add_manager.html,modified,0,44 | Operational statement participati

L0066 | 2026-03-28 01:04:55,C:\Users\jonas\OneDrive\Desktop\pm\templates\add_general_manager.html,modified,0,44 | Operational statement par

L0067 | 2026-03-28 01:05:01,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1011,1036 | Operational statement participating in

L0068 | 2026-03-28 01:08:58,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,226,221 | Operational statement participat

L0069 | 2026-03-28 01:17:52,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1366,1382 | Operational statement participating in the file'

L0070 | 2026-03-28 01:18:01,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,97,95 | Operational statement participating i

L0071 | 2026-03-28 01:23:30,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1382,1399 | Operational statement participating in the file'

L0072 | 2026-03-28 01:23:36,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1399,1401 | Operational statement participating in the file'

L0073 | 2026-03-28 01:24:10,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,95,266 | Operational statement participating

L0074 | 2026-03-28 01:24:25,C:\Users\jonas\OneDrive\Desktop\pm\templates\settings.html,modified,130,101 | Operational statement participati

L0075 | 2026-03-28 01:24:34,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,221,248 | Operational statement participat

L0076 | 2026-03-28 01:27:18,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,266,271 | Operational statement participating

L0077 | 2026-03-28 01:27:47,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1036,1276 | Operational statement participating in

L0078 | 2026-03-28 01:29:45,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,271,275 | Operational statement participating

L0079 | 2026-03-28 01:29:45,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,248,254 | Operational statement participat

L0080 | 2026-03-28 01:30:40,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1276,1338 | Operational statement participating in

L0081 | 2026-03-28 01:40:08,C:\Users\jonas\OneDrive\Desktop\pm\templates\desk_activities.html,modified,39,40 | Operational statement partici

L0082 | 2026-03-28 01:40:08,C:\Users\jonas\OneDrive\Desktop\pm\templates\activities.html,modified,18,21 | Operational statement participati

L0083 | 2026-03-28 01:41:20,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,275,275 | Operational statement participating

L0084 | 2026-03-28 01:41:32,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1338,1341 | Operational statement participating in

L0085 | 2026-03-28 01:42:40,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,254,255 | Operational statement participat

L0086 | 2026-03-28 01:55:36,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1401,1459 | Operational statement participating in the file'

L0087 | 2026-03-28 01:55:41,C:\Users\jonas\OneDrive\Desktop\pm\model.py,modified,88,89 | Operational statement participating in the file's

L0088 | 2026-03-28 01:55:50,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,255,279 | Operational statement participat

L0089 | 2026-03-28 01:56:10,C:\Users\jonas\OneDrive\Desktop\pm\templates\desk_activities.html,modified,40,90 | Operational statement partici

L0090 | 2026-03-28 01:56:20,C:\Users\jonas\OneDrive\Desktop\pm\templates\activity_view.html,created,0,0 | Operational statement participati

L0091 | 2026-03-28 01:56:21,C:\Users\jonas\OneDrive\Desktop\pm\templates\activity_view.html,modified,0,22 | Operational statement participa

L0092 | 2026-03-28 01:56:26,C:\Users\jonas\OneDrive\Desktop\pm\templates\notifications.html,modified,72,76 | Operational statement particip

L0093 | 2026-03-28 01:56:36,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1459,1459 | Operational statement participating in the file'

L0094 | 2026-03-28 01:56:56,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,279,279 | Operational statement participat

L0095 | 2026-03-28 01:58:28,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1459,1491 | Operational statement participating in the file'

L0096 | 2026-03-28 01:58:33,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,279,290 | Operational statement participat

L0097 | 2026-03-28 01:59:45,C:\Users\jonas\OneDrive\Desktop\pm\templates\desk_activities.html,modified,90,125 | Operational statement parti

L0098 | 2026-03-28 02:03:06,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1491,1502 | Operational statement participating in the file'

L0099 | 2026-03-28 02:03:21,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,290,290 | Operational statement participat

L0100 | 2026-03-28 02:09:10,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,275,292 | Operational statement participating

L0101 | 2026-03-28 02:09:10,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1341,1365 | Operational statement participating in

L0102 | 2026-03-28 02:09:39,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1365,1364 | Operational statement participating in

L0103 | 2026-03-28 02:12:02,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1502,1543 | Operational statement participating in the file'

L0104 | 2026-03-28 02:13:05,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,290,334 | Operational statement participat

L0105 | 2026-03-28 02:15:01,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1543,1575 | Operational statement participating in the file'

L0106 | 2026-03-28 02:15:02,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1364,1408 | Operational statement participating in

L0107 | 2026-03-28 02:23:11,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1575,1579 | Operational statement participating in the file'

L0108 | 2026-03-28 02:23:27,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,334,339 | Operational statement participat

L0109 | 2026-03-28 02:25:22,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,292,292 | Operational statement participating in the file's runtime

L0110 | 2026-03-28 02:25:23,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1408,1417 | Operational statement participating in the file's runtime

L0111 | 2026-03-28 02:27:07,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1417,1502 | Operational statement participating in the file's runtime

L0112 | 2026-03-28 02:27:46,C:\Users\jonas\OneDrive\Desktop\pm\templates\settings.html,modified,101,104 | Operational statement participating in the file's runtime

L0113 | 2026-03-28 02:27:46,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,339,342 | Operational statement participating in the file's runtime

L0114 | 2026-03-28 02:27:59,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1502,1527 | Operational statement participating in the file's runtime

L0115 | 2026-03-28 02:30:56,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1579,1582 | Operational statement participating in the file's runtime

L0116 | 2026-03-28 02:31:05,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,342,353 | Operational statement participating in the file's runtime

L0117 | 2026-03-28 02:32:15,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1582,1581 | Operational statement participating in the file's runtime

L0118 | 2026-03-28 02:32:27,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,353,342 | Operational statement participating in the file's runtime

L0119 | 2026-03-28 02:32:40,C:\Users\jonas\OneDrive\Desktop\pm\templates\desk_activities.html,modified,125,127 | Operational statement participating in the file's runtime

L0120 | 2026-03-28 02:34:03,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,342,342 | Operational statement participating in the file's runtime

L0121 | 2026-03-28 02:36:27,C:\Users\jonas\OneDrive\Desktop\pm\templates\desk_activities.html,modified,127,134 | Operational statement participating in the file's runtime

L0122 | 2026-03-28 02:36:27,C:\Users\jonas\OneDrive\Desktop\pm\templates\notifications.html,modified,76,77 | Operational statement participating in the file's runtime

L0123 | 2026-03-28 02:36:28,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1581,1581 | Operational statement participating in the file's runtime

L0124 | 2026-03-28 02:37:28,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1527,1527 | Operational statement participating in the file's runtime

L0125 | 2026-03-28 02:45:16,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1581,1583 | Operational statement participating in the file's runtime

L0126 | 2026-03-28 02:45:29,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,292,289 | Operational statement participating in the file's runtime

L0127 | 2026-03-28 02:48:07,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1583,1601 | Operational statement participating in the file's runtime

L0128 | 2026-03-28 02:48:18,C:\Users\jonas\OneDrive\Desktop\pm\templates\desk_activities.html,modified,134,134 | Operational statement participating in the file's runtime

L0129 | 2026-03-28 03:09:52,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,322,316 | Operational statement participating in the file's runtime

L0130 | 2026-03-28 03:10:21,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,316,320 | Operational statement participating in the file's runtime

L0131 | 2026-03-28 03:11:36,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1527,1623 | Operational statement participating in the file's runtime

L0132 | 2026-03-28 03:14:16,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,342,320 | Operational statement participating in the file's runtime

L0133 | 2026-03-28 03:14:16,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,320,306 | Operational statement participating in the file's runtime

L0134 | 2026-03-28 03:19:36,C:\Users\jonas\OneDrive\Desktop\pm\parse_doc.py,created,0,0 | Operational statement participating in the file's runtime

L0135 | 2026-03-28 03:19:36,C:\Users\jonas\OneDrive\Desktop\pm\parse_doc.py,modified,0,18 | Operational statement participating in the file's runtime

L0136 | 2026-03-28 03:22:10,C:\Users\jonas\OneDrive\Desktop\pm\parse_doc.py,modified,18,17 | Operational statement participating in the file's runtime

L0137 | 2026-03-28 03:23:11,C:\Users\jonas\OneDrive\Desktop\pm\out.txt,created,0,0 | Operational statement participating in the file's runtime

L0138 | 2026-03-28 03:23:11,C:\Users\jonas\OneDrive\Desktop\pm\out.txt,modified,0,463 | Operational statement participating in the file's runtime

L0139 | 2026-03-28 03:24:43,C:\Users\jonas\OneDrive\Desktop\pm\out.txt,modified,463,0 | Operational statement participating in the file's runtime

L0140 | 2026-03-28 03:24:43,C:\Users\jonas\OneDrive\Desktop\pm\out.txt,modified,0,231 | Operational statement participating in the file's runtime

L0141 | 2026-03-28 03:25:13,C:\Users\jonas\OneDrive\Desktop\pm\err.txt,created,0,0 | Operational statement participating in the file's runtime

L0142 | 2026-03-28 03:26:56,C:\Users\jonas\OneDrive\Desktop\pm\out.txt,modified,231,0 | Operational statement participating in the file's runtime

L0143 | 2026-03-28 03:26:57,C:\Users\jonas\OneDrive\Desktop\pm\out.txt,modified,0,231 | Operational statement participating in the file's runtime

L0144 | 2026-03-28 03:32:25,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,306,273 | Operational statement participating in the file's runtime

L0145 | 2026-03-28 03:33:42,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1623,1625 | Operational statement participating in the file's runtime

L0146 | 2026-03-28 03:33:42,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,273,285 | Operational statement participating in the file's runtime

L0147 | 2026-03-28 03:33:49,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1625,1645 | Operational statement participating in the file's runtime

L0148 | 2026-03-28 03:34:10,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,285,346 | Operational statement participating in the file's runtime

L0149 | 2026-03-28 03:34:16,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1645,1656 | Operational statement participating in the file's runtime

L0150 | 2026-03-28 03:34:26,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1656,1657 | Operational statement participating in the file's runtime

L0151 | 2026-03-28 03:34:34,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1657,1663 | Operational statement participating in the file's runtime

L0152 | 2026-03-28 03:38:47,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,346,324 | Operational statement participating in the file's runtime

L0153 | 2026-03-28 03:41:10,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,320,313 | Operational statement participating in the file's runtime

L0154 | 2026-03-28 03:50:36,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,313,309 | Operational statement participating in the file's runtime

L0155 | 2026-03-28 03:51:00,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1663,1693 | Operational statement participating in the file's runtime

L0156 | 2026-03-28 03:57:54,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1693,1738 | Operational statement participating in the file's runtime

L0157 | 2026-03-28 03:58:15,C:\Users\jonas\OneDrive\Desktop\pm\templates\login.html,modified,57,106 | Operational statement participating in the file's runtime

L0158 | 2026-03-28 03:58:19,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1738,1757 | Operational statement participating in the file's runtime

L0159 | 2026-03-28 03:58:36,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,289,289 | Operational statement participating in the file's runtime

L0160 | 2026-03-28 04:04:14,C:\Users\jonas\OneDrive\Desktop\pm\templates\login.html,modified,106,130 | Operational statement participating in the file's runtime

L0161 | 2026-03-28 04:04:22,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1757,1793 | Operational statement participating in the file's runtime

L0162 | 2026-03-28 04:06:25,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1601,1613 | Operational statement participating in the file's runtime

L0163 | 2026-03-28 04:06:35,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1613,1671 | Operational statement participating in the file's runtime

L0164 | 2026-03-28 04:06:46,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1671,1697 | Operational statement participating in the file's

L0165 | 2026-03-28 04:06:54,C:\Users\jonas\OneDrive\Desktop\pm\templates\login.html,modified,130,131 | Operational statement participating

L0166 | 2026-03-28 04:10:59,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1697,1706 | Operational statement participating in the file's

L0167 | 2026-03-28 04:11:03,C:\Users\jonas\OneDrive\Desktop\pm\requirements.txt,modified,18,19 | Operational statement participating in the

L0168 | 2026-03-28 04:11:12,C:\Users\jonas\OneDrive\Desktop\pm\README.md,modified,125,154 | Operational statement participating in the file's

L0169 | 2026-03-28 04:13:26,C:\Users\jonas\OneDrive\Desktop\pm\scripts\migrate_sqlite_to_postgres.py,created,0,0 | Operational statement pa

L0170 | 2026-03-28 04:13:28,C:\Users\jonas\OneDrive\Desktop\pm\scripts\migrate_sqlite_to_postgres.py,modified,0,113 | Operational statement

L0171 | 2026-03-28 04:13:33,C:\Users\jonas\OneDrive\Desktop\pm\README.md,modified,154,188 | Operational statement participating in the file's

L0172 | 2026-03-28 04:18:01,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1706,1707 | Operational statement participating in the file's

L0173 | 2026-03-28 04:18:09,C:\Users\jonas\OneDrive\Desktop\pm>alert_system.py,modified,22,30 | Operational statement participating in the

L0174 | 2026-03-28 04:18:33,C:\Users\jonas\OneDrive\Desktop\pm\README.md,modified,188,191 | Operational statement participating in the file's

L0175 | 2026-03-28 04:20:23,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1707,1699 | Operational statement participating in the file's

L0176 | 2026-03-28 04:31:25,C:\Users\jonas\OneDrive\Desktop\pm\README.md,modified,191,191 | Operational statement participating in the file's

L0177 | 2026-03-28 04:34:47,C:\Users\jonas\OneDrive\Desktop\pm\README.md,modified,191,235 | Operational statement participating in the file's

L0178 | 2026-03-28 04:46:05,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1699,1702 | Operational statement participating in the file's

L0179 | 2026-03-28 04:46:17,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1702,1786 | Operational statement participating in the file's

L0180 | 2026-03-28 04:46:55,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,1786,2020 | Operational statement participating in the file's

L0181 | 2026-03-28 04:47:04,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2020,2021 | Operational statement participating in the file's

L0182 | 2026-03-28 04:47:11,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2021,2034 | Operational statement participating in the file's

L0183 | 2026-03-28 04:47:24,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2034,2038 | Operational statement participating in the file's

L0184 | 2026-03-28 04:47:39,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2038,2071 | Operational statement participating in the file's

L0185 | 2026-03-28 04:47:53,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2071,2092 | Operational statement participating in the file's

L0186 | 2026-03-28 04:48:11,C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html,modified,324,364 | Operational statement participat

L0187 | 2026-03-28 04:48:28,C:\Users\jonas\OneDrive\Desktop\pm\templates\desk_activities.html,modified,134,182 | Operational statement part

L0188 | 2026-03-28 04:48:44,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,309,344 | Operational statement participat

L0189 | 2026-03-28 04:51:40,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2092,2093 | Operational statement participating in the file's

L0190 | 2026-03-28 04:51:55,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2093,2173 | Operational statement participating in the file's

L0191 | 2026-03-28 04:52:02,C:\Users\jonas\OneDrive\Desktop\pm\requirements.txt,modified,19,20 | Operational statement participating in the

L0192 | 2026-03-28 04:52:13,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,344,358 | Operational statement participat

L0193 | 2026-03-28 04:52:20,C:\Users\jonas\OneDrive\Desktop\pm\README.md,modified,235,236 | Operational statement participating in the file's

L0194 | 2026-03-28 04:55:26,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2173,2288 | Operational statement participating in the file's

L0195 | 2026-03-28 04:57:17,C:\Users\jonas\OneDrive\Desktop\pm\requirements.txt,modified,20,20 | Operational statement participating in the

L0196 | 2026-03-28 04:57:23,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2288,2296 | Operational statement participating in the file's

L0197 | 2026-03-28 04:57:32,C:\Users\jonas\OneDrive\Desktop\pm\README.md,modified,236,236 | Operational statement participating in the file's

L0198 | 2026-03-28 05:01:07,C:\Users\jonas\OneDrive\Desktop\pm\requirements.txt,modified,20,22 | Operational statement participating in the

L0199 | 2026-03-28 05:01:18,C:\Users\jonas\OneDrive\Desktop\pm\app_asgi.py,created,0,0 | Operational statement participating in the file's

L0200 | 2026-03-28 05:01:19,C:\Users\jonas\OneDrive\Desktop\pm\app_asgi.py,modified,0,7 | Operational statement participating in the file's

L0201 | 2026-03-28 05:14:03,C:\Users\jonas\OneDrive\Desktop\pm\static\style.css,modified,1793,1787 | Operational statement participating in

L0202 | 2026-03-28 05:14:11,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,358,355 | Operational statement participat

L0203 | 2026-03-28 05:14:26,C:\Users\jonas\OneDrive\Desktop\pm\templates\settings.html,modified,104,101 | Operational statement participati

L0204 | 2026-03-28 05:14:47,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,289,289 | Operational statement participating

L0205 | 2026-03-28 05:17:55,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2296,2304 | Operational statement participating in the file's

L0206 | 2026-03-28 05:18:06,C:\Users\jonas\OneDrive\Desktop\pm\templates\login.html,modified,131,131 | Operational statement participating

L0207 | 2026-03-28 05:22:16,C:\Users\jonas\OneDrive\Desktop\pm\templates\login.html,modified,131,57 | Operational statement participating i

L0208 | 2026-03-28 05:22:31,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,355,438 | Operational statement participat

L0209 | 2026-03-28 05:25:14,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,438,361 | Operational statement participat

L0210 | 2026-03-28 05:25:20,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,289,287 | Operational statement participating

L0211 | 2026-03-28 05:25:21,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,361,361 | Operational statement participat

L0212 | 2026-03-28 05:25:42,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,287,287 | Operational statement participating

L0213 | 2026-03-28 05:28:43,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,361,330 | Operational statement participat

L0214 | 2026-03-28 05:28:56,C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html,modified,287,283 | Operational statement participating

L0215 | 2026-03-28 05:31:31,C:\Users\jonas\OneDrive\Desktop\pm\templates\add_staff.html,modified,47,47 | Operational statement participatin

L0216 | 2026-03-28 05:31:49,C:\Users\jonas\OneDrive\Desktop\pm\templates\register.html,modified,36,36 | Operational statement participating

L0217 | 2026-03-28 05:33:17,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2304,2302 | Operational statement participating in the file's

L0218 | 2026-03-28 05:33:22,C:\Users\jonas\OneDrive\Desktop\pm\templates\add_staff.html,modified,47,45 | Operational statement participatin

L0219 | 2026-03-28 05:38:55,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2302,2309 | Operational statement participating in the file's
L0220 | 2026-03-28 05:38:56,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,330,358 | Operational statement participating in the file's
L0221 | 2026-03-28 05:47:11,C:\Users\jonas\OneDrive\Desktop\pm\templates\notifications.html,modified,77,107 | Operational statement participating in the file's
L0222 | 2026-03-28 05:47:13,C:\Users\jonas\OneDrive\Desktop\pm\templates\dashboard.html,modified,358,380 | Operational statement participating in the file's
L0223 | 2026-03-28 05:54:25,C:\Users\jonas\OneDrive\Desktop\pm\model.py,modified,89,90 | Operational statement participating in the file's
L0224 | 2026-03-28 05:55:21,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2309,2331 | Operational statement participating in the file's
L0225 | 2026-03-28 05:55:53,C:\Users\jonas\OneDrive\Desktop\pm\app.py,modified,2331,2357 | Operational statement participating in the file's
L0226 | 2026-03-28 05:56:50,C:\Users\jonas\OneDrive\Desktop\pm\templates\admin_staff.html,modified,58,101 | Operational statement participating in the file's

File 14: ci_gate.py

[illegible]

[illegible]

File 15: docker-compose.https.yml

```
L0001 | version: "3.9" | Operational statement participating in the file's runtime behavior.
L0002 | | Blank line used for readability and logical separation.
L0003 | services: | Operational statement participating in the file's runtime behavior.
L0004 |   web: | Operational statement participating in the file's runtime behavior.
L0005 |     # Route all external traffic through Caddy for TLS termination. | Comment line documenting intent or context for nearby code.
L0006 |     ports: [] | Operational statement participating in the file's runtime behavior.
L0007 |     expose: | Operational statement participating in the file's runtime behavior.
L0008 |       - "8000" | Operational statement participating in the file's runtime behavior.
L0009 |     environment: | Operational statement participating in the file's runtime behavior.
L0010 |       SESSION_COOKIE_SECURE: "1" | Operational statement participating in the file's runtime behavior.
L0011 |       PUBLIC_BASE_URL: https://${SERVER_NAME:-localhost} | Block delimiter controlling scope/structure in this language.
L0012 | | Blank line used for readability and logical separation.
L0013 |   caddy: | Operational statement participating in the file's runtime behavior.
L0014 |     image: caddy:2.8 | Operational statement participating in the file's runtime behavior.
L0015 |     depends_on: | Operational statement participating in the file's runtime behavior.
L0016 |       web: | Operational statement participating in the file's runtime behavior.
L0017 |       condition: service_started | Operational statement participating in the file's runtime behavior.
L0018 |     ports: | Operational statement participating in the file's runtime behavior.
L0019 |       - "80:80" | Operational statement participating in the file's runtime behavior.
L0020 |       - "443:443" | Operational statement participating in the file's runtime behavior.
L0021 |     environment: | Operational statement participating in the file's runtime behavior.
L0022 |       SERVER_NAME: ${SERVER_NAME:-localhost} | Block delimiter controlling scope/structure in this language.
L0023 |     volumes: | Operational statement participating in the file's runtime behavior.
L0024 |       - ./Caddyfile:/etc/caddy/Caddyfile:ro | Operational statement participating in the file's runtime behavior.
L0025 |       - caddy-data:/data | Operational statement participating in the file's runtime behavior.
L0026 |       - caddy-config:/config | Operational statement participating in the file's runtime behavior.
L0027 |     restart: unless-stopped | Operational statement participating in the file's runtime behavior.
L0028 | | Blank line used for readability and logical separation.
L0029 | volumes: | Operational statement participating in the file's runtime behavior.
L0030 |   caddy-data: | Operational statement participating in the file's runtime behavior.
L0031 |   caddy-config: | Operational statement participating in the file's runtime behavior.
```

File 16: docker-compose.yml

```
L0001 | version: "3.9" | Operational statement participating in the file's runtime behavior.
L0002 | | Blank line used for readability and logical separation.
L0003 | services: | Operational statement participating in the file's runtime behavior.
L0004 |   web: | Operational statement participating in the file's runtime behavior.
L0005 |     build: . | Operational statement participating in the file's runtime behavior.
L0006 |     depends_on: | Operational statement participating in the file's runtime behavior.
L0007 |       db: | Operational statement participating in the file's runtime behavior.
L0008 |         condition: service_healthy | Operational statement participating in the file's runtime behavior.
L0009 |     env_file: | Operational statement participating in the file's runtime behavior.
L0010 |       - .env | Operational statement participating in the file's runtime behavior.
L0011 |     environment: | Operational statement participating in the file's runtime behavior.
L0012 |       DATABASE_URL: postgresql+psycpg://${POSTGRES_USER:-pm_user}:${POSTGRES_PASSWORD}@db:5432/${POSTGRES_DB:-pm_db} | Block delimit
L0013 |       SECRET_KEY: ${SECRET_KEY} | Block delimiter controlling scope/structure in this language.
L0014 |       SESSION_COOKIE_SECURE: ${SESSION_COOKIE_SECURE:-0} | Block delimiter controlling scope/structure in this language.
L0015 |       PUBLIC_BASE_URL: ${PUBLIC_BASE_URL:-http://localhost:8000} | Block delimiter controlling scope/structure in this language.
L0016 |       LOG_LEVEL: ${LOG_LEVEL:-INFO} | Block delimiter controlling scope/structure in this language.
L0017 |     ports: | Operational statement participating in the file's runtime behavior.
L0018 |       - "8000:8000" | Operational statement participating in the file's runtime behavior.
L0019 |     volumes: | Operational statement participating in the file's runtime behavior.
L0020 |       - ./uploads:/app/uploads | Operational statement participating in the file's runtime behavior.
L0021 |       - ./logs:/app/logs | Operational statement participating in the file's runtime behavior.
L0022 |     healthcheck: | Operational statement participating in the file's runtime behavior.
L0023 |       test: ["CMD", "python", "-c", "import urllib.request; urllib.request.urlopen('http://localhost:8000/__build')"] | Operational
L0024 |       interval: 30s | Operational statement participating in the file's runtime behavior.
L0025 |       timeout: 10s | Operational statement participating in the file's runtime behavior.
L0026 |       retries: 3 | Operational statement participating in the file's runtime behavior.
L0027 |       start_period: 40s | Operational statement participating in the file's runtime behavior.
L0028 |     deploy: | Operational statement participating in the file's runtime behavior.
L0029 |       resources: | Operational statement participating in the file's runtime behavior.
L0030 |         limits: | Operational statement participating in the file's runtime behavior.
L0031 |           cpus: '2' | Operational statement participating in the file's runtime behavior.
L0032 |           memory: 1G | Operational statement participating in the file's runtime behavior.
L0033 | | Blank line used for readability and logical separation.
L0034 |   db: | Operational statement participating in the file's runtime behavior.
L0035 |     image: postgres:15 | Operational statement participating in the file's runtime behavior.
L0036 |     environment: | Operational statement participating in the file's runtime behavior.
L0037 |       POSTGRES_DB: ${POSTGRES_DB:-pm_db} | Block delimiter controlling scope/structure in this language.
L0038 |       POSTGRES_USER: ${POSTGRES_USER:-pm_user} | Block delimiter controlling scope/structure in this language.
L0039 |       POSTGRES_PASSWORD: ${POSTGRES_PASSWORD:?Set POSTGRES_PASSWORD in .env} | Block delimiter controlling scope/structure in this
L0040 |     healthcheck: | Operational statement participating in the file's runtime behavior.
L0041 |       test: ["CMD-SHELL", "pg_isready -U ${POSTGRES_USER:-pm_user} -d ${POSTGRES_DB:-pm_db}"] | Operational statement participating
L0042 |       interval: 10s | Operational statement participating in the file's runtime behavior.
L0043 |       timeout: 5s | Operational statement participating in the file's runtime behavior.
L0044 |       retries: 5 | Operational statement participating in the file's runtime behavior.
L0045 |     volumes: | Operational statement participating in the file's runtime behavior.
L0046 |       - postgres-data:/var/lib/postgresql/data | Operational statement participating in the file's runtime behavior.
L0047 |     deploy: | Operational statement participating in the file's runtime behavior.
L0048 |       resources: | Operational statement participating in the file's runtime behavior.
L0049 |         limits: | Operational statement participating in the file's runtime behavior.
L0050 |           cpus: '1' | Operational statement participating in the file's runtime behavior.
L0051 |           memory: 512M | Operational statement participating in the file's runtime behavior.
L0052 | | Blank line used for readability and logical separation.
L0053 |   volumes: | Operational statement participating in the file's runtime behavior.
```

L0054 | postgres-data: | Operational statement participating in the file's runtime behavior.

File 17: Dockerfile

L0001 | FROM python:3.11-slim | Operational statement participating in the file's runtime behavior.

L0002 | | Blank line used for readability and logical separation.

L0003 | ENV PYTHONDONTWRITEBYTECODE=1 \ | Assignment statement storing or updating program state.

L0004 | PYTHONUNBUFFERED=1 | Assignment statement storing or updating program state.

L0005 | | Blank line used for readability and logical separation.

L0006 | WORKDIR /app | Operational statement participating in the file's runtime behavior.

L0007 | | Blank line used for readability and logical separation.

L0008 | COPY requirements.txt ./ | Operational statement participating in the file's runtime behavior.

L0009 | RUN pip install --no-cache-dir --upgrade pip \ | Operational statement participating in the file's runtime behavior.

L0010 | && pip install --no-cache-dir -r requirements.txt | Operational statement participating in the file's runtime behavior.

L0011 | | Blank line used for readability and logical separation.

L0012 | COPY . . | Operational statement participating in the file's runtime behavior.

L0013 | | Blank line used for readability and logical separation.

L0014 | EXPOSE 8000 | Operational statement participating in the file's runtime behavior.

L0015 | | Blank line used for readability and logical separation.

L0016 | CMD ["gunicorn", "--workers", "4", "--bind", "0.0.0.0:8000", "--factory", "app:create_app"] | Operational statement participating in the file's runtime behavior.

File 18: err.txt

File 19: fail_extract.txt

L0001 | ■tests/test_auth.py::test_reset_password_shows_current_and_new_password_in_issued_credentials FAILED [100%] | Operational statement
L0002 | assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0003 | assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0004 | assert "Password reset for Reset Target." in body | Operational statement participating in the file's runtime behavior.
L0005 | > assert "Current Password:" in body | Operational statement participating in the file's runtime behavior.
L0006 | E assert 'Current Password:' in '<!DOCTYPE html>\n<html lang="en">\n <head>\n <meta charset="UTF-8" />\n <meta name="v
L0007 | tests\test_auth.py:279: AssertionError | Operational statement participating in the file's runtime behavior.
L0008 | FAILED tests/test_auth.py::test_reset_password_shows_current_and_new_password_in_issued_credentials - assert 'Current Password:' in
L0009 | ===== 1 failed in 7.53s ===== | Operational statement participating in the file's

File 20: file_monitor.py

```
L0001 | # This file was renamed from watchdog.py to avoid conflicts with the Python watchdog package. | Comment line documenting intent or
L0002 | # You can implement any custom logic here if needed. | Comment line documenting intent or context for nearby code.
```


File 21: manager_sla_card_test.txt

L0001 | ■. [100%] | Operational statement participating in the file
L0002 | 1 passed in 7.77s | Operational statement participating in the file's runtime behavior.

File 22: manager_sla_card_test_exit.txt

L0001 | ■EXIT:0 | Operational statement participating in the file's runtime behavior.

File 23: migrate_msg.txt

L0001 | ■.\.venv\Scripts\python.exe : Error: Path doesn't exist: migrations. Please | Operational statement participating in the file's runtime behavior.

L0002 | use the 'init' command to create a new scripts folder. | Operational statement participating in the file's runtime behavior.

L0003 | At line:1 char:1 | Operational statement participating in the file's runtime behavior.

L0004 | + .\.venv\Scripts\python.exe -m flask --app app db migrate -m "Add risk ... | Operational statement participating in the file's runtime behavior.

L0005 | + ~~~~~ | Operational statement participating in the file's runtime behavior.

L0006 | + CategoryInfo : NotSpecified: (Error: Path doe...scripts folder. | Operational statement participating in the file's runtime behavior.

L0007 | :String) [], RemoteException | Operational statement participating in the file's runtime behavior.

L0008 | + FullyQualifiedErrorId : NativeCommandError | Operational statement participating in the file's runtime behavior.

L0009 | | Blank line used for readability and logical separation.

File 24: migrate_msg2.txt

```
L0001 | ■.\.venv\Scripts\python.exe : INFO [alembic.runtime.migration] Context impl | Operational statement participating in the file's runtime behavior.
L0002 | SQLiteImpl. | Operational statement participating in the file's runtime behavior.
L0003 | At line:1 char:1 | Operational statement participating in the file's runtime behavior.
L0004 | + .\.venv\Scripts\python.exe -m flask --app app db migrate -m "Add risk ... | Operational statement participating in the file's runtime behavior.
L0005 | + ~~~~~ | Operational statement participating in the file's runtime behavior.
L0006 | + CategoryInfo : NotSpecified: (INFO [alembic....mpl SQLiteImpl. | Operational statement participating in the file's runtime behavior.
L0007 | :String) [], RemoteException | Operational statement participating in the file's runtime behavior.
L0008 | + FullyQualifiedErrorId : NativeCommandError | Operational statement participating in the file's runtime behavior.
L0009 | | Blank line used for readability and logical separation.
L0010 | INFO [alembic.runtime.migration] Will assume non-transactional DDL. | Operational statement participating in the file's runtime behavior.
L0011 | INFO [alembic.runtime.plugins] setting up autogenerate plugin | Operational statement participating in the file's runtime behavior.
L0012 | alembic.autogenerate.schemas | Operational statement participating in the file's runtime behavior.
L0013 | INFO [alembic.runtime.plugins] setting up autogenerate plugin | Operational statement participating in the file's runtime behavior.
L0014 | alembic.autogenerate.tables | Operational statement participating in the file's runtime behavior.
L0015 | INFO [alembic.runtime.plugins] setting up autogenerate plugin | Operational statement participating in the file's runtime behavior.
L0016 | alembic.autogenerate.types | Operational statement participating in the file's runtime behavior.
L0017 | INFO [alembic.runtime.plugins] setting up autogenerate plugin | Operational statement participating in the file's runtime behavior.
L0018 | alembic.autogenerate.constraints | Operational statement participating in the file's runtime behavior.
L0019 | INFO [alembic.runtime.plugins] setting up autogenerate plugin | Operational statement participating in the file's runtime behavior.
L0020 | alembic.autogenerate.defaults | Operational statement participating in the file's runtime behavior.
L0021 | INFO [alembic.runtime.plugins] setting up autogenerate plugin | Operational statement participating in the file's runtime behavior.
L0022 | alembic.autogenerate.comments | Operational statement participating in the file's runtime behavior.
L0023 | INFO [alembic.autogenerate.compare.tables] Detected added column | Operational statement participating in the file's runtime behavior.
L0024 | 'activities.risk_score' | Operational statement participating in the file's runtime behavior.
L0025 | INFO [alembic.autogenerate.compare.tables] Detected added column | Operational statement participating in the file's runtime behavior.
L0026 | 'activities.sla_deadline' | Operational statement participating in the file's runtime behavior.
L0027 | INFO [alembic.autogenerate.compare.constraints] Detected added index | Operational statement participating in the file's runtime behavior.
L0028 | 'ix_activity_approved_at' on '('approved_at',)' | Operational statement participating in the file's runtime behavior.
L0029 | INFO [alembic.autogenerate.compare.constraints] Detected added index | Operational statement participating in the file's runtime behavior.
L0030 | 'ix_activity_created_by' on '('created_by',)' | Operational statement participating in the file's runtime behavior.
L0031 | INFO [alembic.autogenerate.compare.constraints] Detected added index | Operational statement participating in the file's runtime behavior.
L0032 | 'ix_activity_type_approved' on '('activity_type', 'is_approved')' | Operational statement participating in the file's runtime behavior.
L0033 | INFO [alembic.autogenerate.compare.constraints] Detected added index | Operational statement participating in the file's runtime behavior.
L0034 | 'ix_user_role' on '('role',)' | Operational statement participating in the file's runtime behavior.
L0035 | Generating C:\Users\jonas\OneDrive\Desktop\pm\migrations\versions\7332ed65ba00_add_risk_score_and_sla_deadline_columns_.py ... done
```

File 25: migrations/alembic.ini

```
L0001 | # A generic, single database configuration. | Comment line documenting intent or context for nearby code.
L0002 | | Blank line used for readability and logical separation.
L0003 | [alembic] | Operational statement participating in the file's runtime behavior.
L0004 | # template used to generate migration files | Comment line documenting intent or context for nearby code.
L0005 | # file_template = %(rev)s_%(slug)s | Comment line documenting intent or context for nearby code.
L0006 | | Blank line used for readability and logical separation.
L0007 | # set to 'true' to run the environment during | Comment line documenting intent or context for nearby code.
L0008 | # the 'revision' command, regardless of autogenerate | Comment line documenting intent or context for nearby code.
L0009 | # revision_environment = false | Comment line documenting intent or context for nearby code.
L0010 | | Blank line used for readability and logical separation.
L0011 | | Blank line used for readability and logical separation.
L0012 | # Logging configuration | Comment line documenting intent or context for nearby code.
L0013 | [loggers] | Operational statement participating in the file's runtime behavior.
L0014 | keys = root,sqlalchemy,alembic,flask_migrate | Assignment statement storing or updating program state.
L0015 | | Blank line used for readability and logical separation.
L0016 | [handlers] | Operational statement participating in the file's runtime behavior.
L0017 | keys = console | Assignment statement storing or updating program state.
L0018 | | Blank line used for readability and logical separation.
L0019 | [formatters] | Operational statement participating in the file's runtime behavior.
L0020 | keys = generic | Assignment statement storing or updating program state.
L0021 | | Blank line used for readability and logical separation.
L0022 | [logger_root] | Operational statement participating in the file's runtime behavior.
L0023 | level = WARN | Assignment statement storing or updating program state.
L0024 | handlers = console | Assignment statement storing or updating program state.
L0025 | qualname = | Assignment statement storing or updating program state.
L0026 | | Blank line used for readability and logical separation.
L0027 | [logger_sqlalchemy] | Operational statement participating in the file's runtime behavior.
L0028 | level = WARN | Assignment statement storing or updating program state.
L0029 | handlers = | Assignment statement storing or updating program state.
L0030 | qualname = sqlalchemy.engine | Assignment statement storing or updating program state.
L0031 | | Blank line used for readability and logical separation.
L0032 | [logger_alembic] | Operational statement participating in the file's runtime behavior.
L0033 | level = INFO | Assignment statement storing or updating program state.
L0034 | handlers = | Assignment statement storing or updating program state.
L0035 | qualname = alembic | Assignment statement storing or updating program state.
L0036 | | Blank line used for readability and logical separation.
L0037 | [logger_flask_migrate] | Operational statement participating in the file's runtime behavior.
L0038 | level = INFO | Assignment statement storing or updating program state.
L0039 | handlers = | Assignment statement storing or updating program state.
L0040 | qualname = flask_migrate | Assignment statement storing or updating program state.
L0041 | | Blank line used for readability and logical separation.
L0042 | [handler_console] | Operational statement participating in the file's runtime behavior.
L0043 | class = StreamHandler | Assignment statement storing or updating program state.
L0044 | args = (sys.stderr,) | Assignment statement storing or updating program state.
L0045 | level = NOTSET | Assignment statement storing or updating program state.
L0046 | formatter = generic | Assignment statement storing or updating program state.
L0047 | | Blank line used for readability and logical separation.
L0048 | [formatter_generic] | Operational statement participating in the file's runtime behavior.
L0049 | format = %(levelname)-5.5s [% (name)s] %(message)s | Assignment statement storing or updating program state.
L0050 | datefmt = %H:%M:%S | Assignment statement storing or updating program state.
```

File 26: migrations/env.py

```
L0001 | import logging | Imports dependency modules: logging.
L0002 | from logging.config import fileConfig | Imports specific names from another module for direct usage.
L0003 | | Blank line used for readability and logical separation.
L0004 | from flask import current_app | Imports specific names from another module for direct usage.
L0005 | | Blank line used for readability and logical separation.
L0006 | from alembic import context | Imports specific names from another module for direct usage.
L0007 | | Blank line used for readability and logical separation.
L0008 | # this is the Alembic Config object, which provides | Comment line documenting intent or context for nearby code.
L0009 | # access to the values within the .ini file in use. | Comment line documenting intent or context for nearby code.
L0010 | config = context.config | Assignment statement storing or updating program state.
L0011 | | Blank line used for readability and logical separation.
L0012 | # Interpret the config file for Python logging. | Comment line documenting intent or context for nearby code.
L0013 | # This line sets up loggers basically. | Comment line documenting intent or context for nearby code.
L0014 | fileConfig(config.config_file_name) | Operational statement participating in the file's runtime behavior.
L0015 | logger = logging.getLogger('alembic.env') | Assignment statement storing or updating program state.
L0016 | | Blank line used for readability and logical separation.
L0017 | | Blank line used for readability and logical separation.
L0018 | def get_engine(): | Declares a function/method as a reusable unit of behavior.
L0019 |     try: | Starts an exception handling block for risky operations.
L0020 |         # this works with Flask-SQLAlchemy<3 and Alchemical | Comment line documenting intent or context for nearby code.
L0021 |         return current_app.extensions['migrate'].db.get_engine() | Returns a value (or control) back to the caller.
L0022 |     except (TypeError, AttributeError): | Handles errors raised in the associated try block.
L0023 |         # this works with Flask-SQLAlchemy>=3 | Comment line documenting intent or context for nearby code.
L0024 |         return current_app.extensions['migrate'].db.engine | Returns a value (or control) back to the caller.
L0025 | | Blank line used for readability and logical separation.
L0026 | | Blank line used for readability and logical separation.
L0027 | def get_engine_url(): | Declares a function/method as a reusable unit of behavior.
L0028 |     try: | Starts an exception handling block for risky operations.
L0029 |         return get_engine().url.render_as_string(hide_password=False).replace( | Returns a value (or control) back to the caller.
L0030 |             '%', '%%') | Operational statement participating in the file's runtime behavior.
L0031 |     except AttributeError: | Handles errors raised in the associated try block.
L0032 |         return str(get_engine().url).replace('%', '%%') | Returns a value (or control) back to the caller.
L0033 | | Blank line used for readability and logical separation.
L0034 | | Blank line used for readability and logical separation.
L0035 | # add your model's MetaData object here | Comment line documenting intent or context for nearby code.
L0036 | # for 'autogenerate' support | Comment line documenting intent or context for nearby code.
L0037 | # from myapp import mymodel | Comment line documenting intent or context for nearby code.
L0038 | # target_metadata = mymodel.Base.metadata | Comment line documenting intent or context for nearby code.
L0039 | config.set_main_option('sqlalchemy.url', get_engine_url()) | Operational statement participating in the file's runtime behavior.
L0040 | target_db = current_app.extensions['migrate'].db | Assignment statement storing or updating program state.
L0041 | | Blank line used for readability and logical separation.
L0042 | # other values from the config, defined by the needs of env.py, | Comment line documenting intent or context for nearby code.
L0043 | # can be acquired: | Comment line documenting intent or context for nearby code.
L0044 | # my_important_option = config.get_main_option("my_important_option") | Comment line documenting intent or context for nearby code.
L0045 | # ... etc. | Comment line documenting intent or context for nearby code.
L0046 | | Blank line used for readability and logical separation.
L0047 | | Blank line used for readability and logical separation.
L0048 | def get_metadata(): | Declares a function/method as a reusable unit of behavior.
L0049 |     if hasattr(target_db, 'metadatas'): | Conditional branch that runs only when its condition is true.
L0050 |         return target_db.metadatas[None] | Returns a value (or control) back to the caller.
L0051 |     return target_db.metadata | Returns a value (or control) back to the caller.
L0052 | | Blank line used for readability and logical separation.
L0053 | | Blank line used for readability and logical separation.
```

```

L0054 | def run_migrations_offline(): | Declares a function/method as a reusable unit of behavior.
L0055 |     """Run migrations in 'offline' mode. | Docstring boundary used to describe a module, class, or function.
L0056 | | Blank line used for readability and logical separation.
L0057 |     This configures the context with just a URL | Operational statement participating in the file's runtime behavior.
L0058 |     and not an Engine, though an Engine is acceptable | Operational statement participating in the file's runtime behavior.
L0059 |     here as well. By skipping the Engine creation | Operational statement participating in the file's runtime behavior.
L0060 |     we don't even need a DBAPI to be available. | Operational statement participating in the file's runtime behavior.
L0061 | | Blank line used for readability and logical separation.
L0062 |     Calls to context.execute() here emit the given string to the | Operational statement participating in the file's runtime behavior.
L0063 |     script output. | Operational statement participating in the file's runtime behavior.
L0064 | | Blank line used for readability and logical separation.
L0065 |     """ | Docstring boundary used to describe a module, class, or function.
L0066 |     url = config.get_main_option("sqlalchemy.url") | Assignment statement storing or updating program state.
L0067 |     context.configure( | Operational statement participating in the file's runtime behavior.
L0068 |         url=url, target_metadata=get_metadata(), literal_binds=True | Assignment statement storing or updating program state.
L0069 |     ) | Operational statement participating in the file's runtime behavior.
L0070 | | Blank line used for readability and logical separation.
L0071 |     with context.begin_transaction(): | Context manager block for safe setup and automatic cleanup.
L0072 |         context.run_migrations() | Operational statement participating in the file's runtime behavior.
L0073 | | Blank line used for readability and logical separation.
L0074 | | Blank line used for readability and logical separation.
L0075 | def run_migrations_online(): | Declares a function/method as a reusable unit of behavior.
L0076 |     """Run migrations in 'online' mode. | Docstring boundary used to describe a module, class, or function.
L0077 | | Blank line used for readability and logical separation.
L0078 |     In this scenario we need to create an Engine | Operational statement participating in the file's runtime behavior.
L0079 |     and associate a connection with the context. | Operational statement participating in the file's runtime behavior.
L0080 | | Blank line used for readability and logical separation.
L0081 |     """ | Docstring boundary used to describe a module, class, or function.
L0082 | | Blank line used for readability and logical separation.
L0083 |     # this callback is used to prevent an auto-migration from being generated | Comment line documenting intent or context for nearby code.
L0084 |     # when there are no changes to the schema | Comment line documenting intent or context for nearby code.
L0085 |     # reference: http://alembic.zzzcomputing.com/en/latest/cookbook.html | Comment line documenting intent or context for nearby code.
L0086 |     def process_revision_directives(context, revision, directives): | Declares a function/method as a reusable unit of behavior.
L0087 |         if getattr(config.cmd_opts, 'autogenerate', False): | Conditional branch that runs only when its condition is true.
L0088 |             script = directives[0] | Assignment statement storing or updating program state.
L0089 |             if script.upgrade_ops.is_empty(): | Conditional branch that runs only when its condition is true.
L0090 |                 directives[:] = [] | Assignment statement storing or updating program state.
L0091 |                 logger.info('No changes in schema detected.') | Operational statement participating in the file's runtime behavior.
L0092 | | Blank line used for readability and logical separation.
L0093 |     conf_args = current_app.extensions['migrate'].configure_args | Assignment statement storing or updating program state.
L0094 |     if conf_args.get("process_revision_directives") is None: | Conditional branch that runs only when its condition is true.
L0095 |         conf_args["process_revision_directives"] = process_revision_directives | Assignment statement storing or updating program state.
L0096 | | Blank line used for readability and logical separation.
L0097 |     connectable = get_engine() | Assignment statement storing or updating program state.
L0098 | | Blank line used for readability and logical separation.
L0099 |     with connectable.connect() as connection: | Context manager block for safe setup and automatic cleanup.
L0100 |         context.configure( | Operational statement participating in the file's runtime behavior.
L0101 |             connection=connection, | Assignment statement storing or updating program state.
L0102 |             target_metadata=get_metadata(), | Assignment statement storing or updating program state.
L0103 |             **conf_args | Operational statement participating in the file's runtime behavior.
L0104 |         ) | Operational statement participating in the file's runtime behavior.
L0105 | | Blank line used for readability and logical separation.
L0106 |     with context.begin_transaction(): | Context manager block for safe setup and automatic cleanup.
L0107 |         context.run_migrations() | Operational statement participating in the file's runtime behavior.
L0108 | | Blank line used for readability and logical separation.

```

L0109 | | Blank line used for readability and logical separation.

L0110 | if context.is_offline_mode(): | Conditional branch that runs only when its condition is true.

L0111 | run_migrations_offline() | Operational statement participating in the file's runtime behavior.

L0112 | else: | Fallback branch executed when prior conditions are false.

L0113 | run_migrations_online() | Operational statement participating in the file's runtime behavior.

File 27: migrations/README

L0001 | Single-database configuration for Flask. | Operational statement participating in the file's runtime behavior.

File 28: migrations/script.py.mako

```
L0001 | """${message} | Docstring boundary used to describe a module, class, or function.
L0002 | | Blank line used for readability and logical separation.
L0003 | Revision ID: ${up_revision} | Block delimiter controlling scope/structure in this language.
L0004 | Revises: ${down_revision \ comma,n} | Block delimiter controlling scope/structure in this language.
L0005 | Create Date: ${create_date} | Block delimiter controlling scope/structure in this language.
L0006 | | Blank line used for readability and logical separation.
L0007 | """ | Docstring boundary used to describe a module, class, or function.
L0008 | from alembic import op | Imports specific names from another module for direct usage.
L0009 | import sqlalchemy as sa | Imports dependency modules: sqlalchemy as sa.
L0010 | ${imports if imports else ""} | Block delimiter controlling scope/structure in this language.
L0011 | | Blank line used for readability and logical separation.
L0012 | # revision identifiers, used by Alembic. | Comment line documenting intent or context for nearby code.
L0013 | revision = ${repr(up_revision)} | Assignment statement storing or updating program state.
L0014 | down_revision = ${repr(down_revision)} | Assignment statement storing or updating program state.
L0015 | branch_labels = ${repr(branch_labels)} | Assignment statement storing or updating program state.
L0016 | depends_on = ${repr(depends_on)} | Assignment statement storing or updating program state.
L0017 | | Blank line used for readability and logical separation.
L0018 | | Blank line used for readability and logical separation.
L0019 | def upgrade(): | Declares a function/method as a reusable unit of behavior.
L0020 |     ${upgrades if upgrades else "pass"} | Block delimiter controlling scope/structure in this language.
L0021 | | Blank line used for readability and logical separation.
L0022 | | Blank line used for readability and logical separation.
L0023 | def downgrade(): | Declares a function/method as a reusable unit of behavior.
L0024 |     ${downgrades if downgrades else "pass"} | Block delimiter controlling scope/structure in this language.
```

File 29: migrations/versions/5d1f3c2d9f91_add_scalable_list_indexes.py

```
L0001 | """add scalable list indexes | Docstring boundary used to describe a module, class, or function.
L0002 | | Blank line used for readability and logical separation.
L0003 | Revision ID: 5d1f3c2d9f91 | Operational statement participating in the file's runtime behavior.
L0004 | Revises: 7332ed65ba00 | Operational statement participating in the file's runtime behavior.
L0005 | Create Date: 2026-03-30 15:10:00.000000 | Operational statement participating in the file's runtime behavior.
L0006 | | Blank line used for readability and logical separation.
L0007 | """ | Docstring boundary used to describe a module, class, or function.
L0008 | from alembic import op | Imports specific names from another module for direct usage.
L0009 | | Blank line used for readability and logical separation.
L0010 | | Blank line used for readability and logical separation.
L0011 | # revision identifiers, used by Alembic. | Comment line documenting intent or context for nearby code.
L0012 | revision = "5d1f3c2d9f91" | Assignment statement storing or updating program state.
L0013 | down_revision = "7332ed65ba00" | Assignment statement storing or updating program state.
L0014 | branch_labels = None | Assignment statement storing or updating program state.
L0015 | depends_on = None | Assignment statement storing or updating program state.
L0016 | | Blank line used for readability and logical separation.
L0017 | | Blank line used for readability and logical separation.
L0018 | def upgrade(): | Declares a function/method as a reusable unit of behavior.
L0019 |     with op.batch_alter_table("consumables", schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0020 |         batch_op.create_index("ix_consumable_created_at", ["created_at"], unique=False) | Assignment statement storing or updating
L0021 | | Blank line used for readability and logical separation.
L0022 |     with op.batch_alter_table("activities", schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0023 |         batch_op.create_index("ix_activity_created_at", ["created_at"], unique=False) | Assignment statement storing or updating pr
L0024 |         batch_op.create_index("ix_activity_risk_score", ["risk_score"], unique=False) | Assignment statement storing or updating pr
L0025 |         batch_op.create_index("ix_activity_sla_deadline", ["sla_deadline"], unique=False) | Assignment statement storing or updatin
L0026 |         batch_op.create_index("ix_activity_type_created_at", ["activity_type", "created_at"], unique=False) | Assignment statement
L0027 | | Blank line used for readability and logical separation.
L0028 |     with op.batch_alter_table("users", schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0029 |         batch_op.create_index("ix_user_created_at", ["created_at"], unique=False) | Assignment statement storing or updating progra
L0030 | | Blank line used for readability and logical separation.
L0031 | | Blank line used for readability and logical separation.
L0032 | def downgrade(): | Declares a function/method as a reusable unit of behavior.
L0033 |     with op.batch_alter_table("users", schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0034 |         batch_op.drop_index("ix_user_created_at") | Operational statement participating in the file's runtime behavior.
L0035 | | Blank line used for readability and logical separation.
L0036 |     with op.batch_alter_table("activities", schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0037 |         batch_op.drop_index("ix_activity_type_created_at") | Operational statement participating in the file's runtime behavior.
L0038 |         batch_op.drop_index("ix_activity_sla_deadline") | Operational statement participating in the file's runtime behavior.
L0039 |         batch_op.drop_index("ix_activity_risk_score") | Operational statement participating in the file's runtime behavior.
L0040 |         batch_op.drop_index("ix_activity_created_at") | Operational statement participating in the file's runtime behavior.
L0041 | | Blank line used for readability and logical separation.
L0042 |     with op.batch_alter_table("consumables", schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup
L0043 |         batch_op.drop_index("ix_consumable_created_at") | Operational statement participating in the file's runtime behavior.
```

File 30: migrations/versions/6bf60953b28f_add_scalable_list_indexes.py

```
L0001 | """add scalable list indexes | Docstring boundary used to describe a module, class, or function.
L0002 | | Blank line used for readability and logical separation.
L0003 | Revision ID: 6bf60953b28f | Operational statement participating in the file's runtime behavior.
L0004 | Revises: 7332ed65ba00 | Operational statement participating in the file's runtime behavior.
L0005 | Create Date: 2026-03-30 14:58:52.485001 | Operational statement participating in the file's runtime behavior.
L0006 | | Blank line used for readability and logical separation.
L0007 | """ | Docstring boundary used to describe a module, class, or function.
L0008 | from alembic import op | Imports specific names from another module for direct usage.
L0009 | import sqlalchemy as sa | Imports dependency modules: sqlalchemy as sa.
L0010 | | Blank line used for readability and logical separation.
L0011 | | Blank line used for readability and logical separation.
L0012 | # revision identifiers, used by Alembic. | Comment line documenting intent or context for nearby code.
L0013 | revision = '6bf60953b28f' | Assignment statement storing or updating program state.
L0014 | down_revision = '7332ed65ba00' | Assignment statement storing or updating program state.
L0015 | branch_labels = None | Assignment statement storing or updating program state.
L0016 | depends_on = None | Assignment statement storing or updating program state.
L0017 | | Blank line used for readability and logical separation.
L0018 | | Blank line used for readability and logical separation.
L0019 | def upgrade(): | Declares a function/method as a reusable unit of behavior.
L0020 |     # ### commands auto generated by Alembic - please adjust! ### | Comment line documenting intent or context for nearby code.
L0021 |     with op.batch_alter_table('activities', schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0022 |         batch_op.create_index('ix_activity_created_at', ['created_at'], unique=False) | Assignment statement storing or updating pr
L0023 |         batch_op.create_index('ix_activity_risk_score', ['risk_score'], unique=False) | Assignment statement storing or updating pr
L0024 |         batch_op.create_index('ix_activity_sla_deadline', ['sla_deadline'], unique=False) | Assignment statement storing or updatin
L0025 |         batch_op.create_index('ix_activity_type_created_at', ['activity_type', 'created_at'], unique=False) | Assignment statement
L0026 | | Blank line used for readability and logical separation.
L0027 |     with op.batch_alter_table('consumables', schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup
L0028 |         batch_op.create_index('ix_consumable_created_at', ['created_at'], unique=False) | Assignment statement storing or updating
L0029 | | Blank line used for readability and logical separation.
L0030 |     with op.batch_alter_table('users', schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0031 |         batch_op.create_index('ix_user_created_at', ['created_at'], unique=False) | Assignment statement storing or updating progra
L0032 | | Blank line used for readability and logical separation.
L0033 |     # ### end Alembic commands ### | Comment line documenting intent or context for nearby code.
L0034 | | Blank line used for readability and logical separation.
L0035 | | Blank line used for readability and logical separation.
L0036 | def downgrade(): | Declares a function/method as a reusable unit of behavior.
L0037 |     # ### commands auto generated by Alembic - please adjust! ### | Comment line documenting intent or context for nearby code.
L0038 |     with op.batch_alter_table('users', schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0039 |         batch_op.drop_index('ix_user_created_at') | Operational statement participating in the file's runtime behavior.
L0040 | | Blank line used for readability and logical separation.
L0041 |     with op.batch_alter_table('consumables', schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup
L0042 |         batch_op.drop_index('ix_consumable_created_at') | Operational statement participating in the file's runtime behavior.
L0043 | | Blank line used for readability and logical separation.
L0044 |     with op.batch_alter_table('activities', schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0045 |         batch_op.drop_index('ix_activity_type_created_at') | Operational statement participating in the file's runtime behavior.
L0046 |         batch_op.drop_index('ix_activity_sla_deadline') | Operational statement participating in the file's runtime behavior.
L0047 |         batch_op.drop_index('ix_activity_risk_score') | Operational statement participating in the file's runtime behavior.
L0048 |         batch_op.drop_index('ix_activity_created_at') | Operational statement participating in the file's runtime behavior.
L0049 | | Blank line used for readability and logical separation.
L0050 |     # ### end Alembic commands ### | Comment line documenting intent or context for nearby code.
```

File 31: migrations/versions/7332ed65ba00_add_risk_score_and_sla_deadline_columns.py

```
L0001 | """Add risk_score and sla_deadline columns and activity indexes | Docstring boundary used to describe a module, class, or function.
L0002 | | Blank line used for readability and logical separation.
L0003 | Revision ID: 7332ed65ba00 | Operational statement participating in the file's runtime behavior.
L0004 | Revises: | Operational statement participating in the file's runtime behavior.
L0005 | Create Date: 2026-03-30 14:05:19.747844 | Operational statement participating in the file's runtime behavior.
L0006 | | Blank line used for readability and logical separation.
L0007 | """ | Docstring boundary used to describe a module, class, or function.
L0008 | from alembic import op | Imports specific names from another module for direct usage.
L0009 | import sqlalchemy as sa | Imports dependency modules: sqlalchemy as sa.
L0010 | | Blank line used for readability and logical separation.
L0011 | | Blank line used for readability and logical separation.
L0012 | # revision identifiers, used by Alembic. | Comment line documenting intent or context for nearby code.
L0013 | revision = '7332ed65ba00' | Assignment statement storing or updating program state.
L0014 | down_revision = None | Assignment statement storing or updating program state.
L0015 | branch_labels = None | Assignment statement storing or updating program state.
L0016 | depends_on = None | Assignment statement storing or updating program state.
L0017 | | Blank line used for readability and logical separation.
L0018 | | Blank line used for readability and logical separation.
L0019 | def upgrade(): | Declares a function/method as a reusable unit of behavior.
L0020 |     # ### commands auto generated by Alembic - please adjust! ### | Comment line documenting intent or context for nearby code.
L0021 |     with op.batch_alter_table('activities', schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0022 |         batch_op.add_column(sa.Column('risk_score', sa.Integer(), nullable=True)) | Assignment statement storing or updating program state.
L0023 |         batch_op.add_column(sa.Column('sla_deadline', sa.DateTime(), nullable=True)) | Assignment statement storing or updating program state.
L0024 |         batch_op.create_index('ix_activity_approved_at', ['approved_at'], unique=False) | Assignment statement storing or updating program state.
L0025 |         batch_op.create_index('ix_activity_created_by', ['created_by'], unique=False) | Assignment statement storing or updating program state.
L0026 |         batch_op.create_index('ix_activity_type_approved', ['activity_type', 'is_approved'], unique=False) | Assignment statement storing or updating program state.
L0027 | | Blank line used for readability and logical separation.
L0028 |     with op.batch_alter_table('users', schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0029 |         batch_op.create_index('ix_user_role', ['role'], unique=False) | Assignment statement storing or updating program state.
L0030 | | Blank line used for readability and logical separation.
L0031 |     # ### end Alembic commands ### | Comment line documenting intent or context for nearby code.
L0032 | | Blank line used for readability and logical separation.
L0033 | | Blank line used for readability and logical separation.
L0034 | def downgrade(): | Declares a function/method as a reusable unit of behavior.
L0035 |     # ### commands auto generated by Alembic - please adjust! ### | Comment line documenting intent or context for nearby code.
L0036 |     with op.batch_alter_table('users', schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0037 |         batch_op.drop_index('ix_user_role') | Operational statement participating in the file's runtime behavior.
L0038 | | Blank line used for readability and logical separation.
L0039 |     with op.batch_alter_table('activities', schema=None) as batch_op: | Context manager block for safe setup and automatic cleanup.
L0040 |         batch_op.drop_index('ix_activity_type_approved') | Operational statement participating in the file's runtime behavior.
L0041 |         batch_op.drop_index('ix_activity_created_by') | Operational statement participating in the file's runtime behavior.
L0042 |         batch_op.drop_index('ix_activity_approved_at') | Operational statement participating in the file's runtime behavior.
L0043 |         batch_op.drop_column('sla_deadline') | Operational statement participating in the file's runtime behavior.
L0044 |         batch_op.drop_column('risk_score') | Operational statement participating in the file's runtime behavior.
L0045 | | Blank line used for readability and logical separation.
L0046 |     # ### end Alembic commands ### | Comment line documenting intent or context for nearby code.
```

File 32: model.py

```
L0001 | from flask_sqlalchemy import SQLAlchemy | Imports specific names from another module for direct usage.
L0002 | import json | Imports dependency modules: json.
L0003 | | Blank line used for readability and logical separation.
L0004 | from pm_app.services.time_utils import utcnow_naive | Imports specific names from another module for direct usage.
L0005 | | Blank line used for readability and logical separation.
L0006 | db = SQLAlchemy() | Assignment statement storing or updating program state.
L0007 | | Blank line used for readability and logical separation.
L0008 | class Consumable(db.Model): | Declares a class that groups related state and behavior.
L0009 |     __tablename__ = "consumables" | Assignment statement storing or updating program state.
L0010 |     __table_args__ = ( | Assignment statement storing or updating program state.
L0011 |         db.Index("ix_consumable_created_at", "created_at"), | Operational statement participating in the file's runtime behavior.
L0012 |     ) | Operational statement participating in the file's runtime behavior.
L0013 |     id = db.Column(db.Integer, primary_key=True) | Assignment statement storing or updating program state.
L0014 |     site_id = db.Column(db.String(20), nullable=False) | Assignment statement storing or updating program state.
L0015 |     site_name = db.Column(db.String(120), nullable=False) | Assignment statement storing or updating program state.
L0016 |     description = db.Column(db.Text, nullable=False) | Assignment statement storing or updating program state.
L0017 |     created_by = db.Column(db.String(120), nullable=False) | Assignment statement storing or updating program state.
L0018 |     created_at = db.Column(db.DateTime, nullable=False, default=utcnow_naive) | Assignment statement storing or updating program state.
L0019 |     location = db.Column(db.String(120), nullable=True) | Assignment statement storing or updating program state.
L0020 | | Blank line used for readability and logical separation.
L0021 |     signage_image_url = db.Column(db.String(300), nullable=True) | Assignment statement storing or updating program state.
L0022 |     screenshot_url = db.Column(db.String(300), nullable=True) | Assignment statement storing or updating program state.
L0023 |     before_usage_image_url = db.Column(db.String(300), nullable=True) | Assignment statement storing or updating program state.
L0024 | | Blank line used for readability and logical separation.
L0025 |     def __repr__(self): | Declares a function/method as a reusable unit of behavior.
L0026 |         return f"<Consumable {self.site_name} ({self.site_id})>" | Returns a value (or control) back to the caller.
L0027 | | Blank line used for readability and logical separation.
L0028 | class Activity(db.Model): | Declares a class that groups related state and behavior.
L0029 |     __tablename__ = "activities" | Assignment statement storing or updating program state.
L0030 |     __table_args__ = ( | Assignment statement storing or updating program state.
L0031 |         db.Index("ix_activity_created_by", "created_by"), | Operational statement participating in the file's runtime behavior.
L0032 |         db.Index("ix_activity_created_at", "created_at"), | Operational statement participating in the file's runtime behavior.
L0033 |         db.Index("ix_activity_risk_score", "risk_score"), | Operational statement participating in the file's runtime behavior.
L0034 |         db.Index("ix_activity_sla_deadline", "sla_deadline"), | Operational statement participating in the file's runtime behavior.
L0035 |         db.Index("ix_activity_type_approved", "activity_type", "is_approved"), | Operational statement participating in the file's runtime behavior.
L0036 |         db.Index("ix_activity_type_created_at", "activity_type", "created_at"), | Operational statement participating in the file's runtime behavior.
L0037 |         db.Index("ix_activity_approved_at", "approved_at"), | Operational statement participating in the file's runtime behavior.
L0038 |     ) | Operational statement participating in the file's runtime behavior.
L0039 |     id = db.Column(db.Integer, primary_key=True) | Assignment statement storing or updating program state.
L0040 |     activity_type = db.Column(db.String(20), nullable=False) | Assignment statement storing or updating program state.
L0041 |     details = db.Column(db.Text, nullable=False) | Assignment statement storing or updating program state.
L0042 |     created_by = db.Column(db.String(150), nullable=True) | Assignment statement storing or updating program state.
L0043 |     created_at = db.Column(db.DateTime, nullable=False, default=utcnow_naive) | Assignment statement storing or updating program state.
L0044 |     is_approved = db.Column(db.Boolean, nullable=False, default=False) | Assignment statement storing or updating program state.
L0045 |     approved_by = db.Column(db.String(150), nullable=True) | Assignment statement storing or updating program state.
L0046 |     approved_at = db.Column(db.DateTime, nullable=True) | Assignment statement storing or updating program state.
L0047 |     # Stored at submission time to avoid repeated text-parsing on every page load. | Comment line documenting intent or context for
L0048 |     risk_score = db.Column(db.Integer, nullable=True) | Assignment statement storing or updating program state.
L0049 |     sla_deadline = db.Column(db.DateTime, nullable=True) | Assignment statement storing or updating program state.
L0050 | | Blank line used for readability and logical separation.
L0051 |     def __repr__(self): | Declares a function/method as a reusable unit of behavior.
L0052 |         return f"<Activity {self.activity_type} {self.created_at}>" | Returns a value (or control) back to the caller.
L0053 | | Blank line used for readability and logical separation.
```

```

L0054 | | Blank line used for readability and logical separation.
L0055 | class FormAssignment(db.Model): | Declares a class that groups related state and behavior.
L0056 |     __tablename__ = "form_assignments" | Assignment statement storing or updating program state.
L0057 |     id = db.Column(db.Integer, primary_key=True) | Assignment statement storing or updating program state.
L0058 |     activity_id = db.Column(db.Integer, db.ForeignKey("activities.id"), nullable=False, index=True) | Assignment statement storing
L0059 |     assignee_email = db.Column(db.String(150), nullable=False, index=True) | Assignment statement storing or updating program state
L0060 |     assignee_role = db.Column(db.String(50), nullable=False) | Assignment statement storing or updating program state.
L0061 |     status = db.Column(db.String(20), nullable=False, default="pending") | Assignment statement storing or updating program state.
L0062 |     assigned_at = db.Column(db.DateTime, nullable=False, default=utcnow_naive) | Assignment statement storing or updating program s
L0063 | | Blank line used for readability and logical separation.
L0064 |     activity = db.relationship("Activity", backref="assignments") | Assignment statement storing or updating program state.
L0065 | | Blank line used for readability and logical separation.
L0066 |     def __repr__(self): | Declares a function/method as a reusable unit of behavior.
L0067 |         return f"<FormAssignment activity_id={self.activity_id} assignee={self.assignee_email} status={self.status}>" | Returns a v
L0068 | | Blank line used for readability and logical separation.
L0069 | | Blank line used for readability and logical separation.
L0070 | class Message(db.Model): | Declares a class that groups related state and behavior.
L0071 |     __tablename__ = "messages" | Assignment statement storing or updating program state.
L0072 |     id = db.Column(db.Integer, primary_key=True) | Assignment statement storing or updating program state.
L0073 |     sender_email = db.Column(db.String(150), nullable=False) | Assignment statement storing or updating program state.
L0074 |     sender_role = db.Column(db.String(50), nullable=False) | Assignment statement storing or updating program state.
L0075 |     recipient_role = db.Column(db.String(50), nullable=False, default="all") | Assignment statement storing or updating program sta
L0076 |     recipient_email = db.Column(db.String(150), nullable=True) | Assignment statement storing or updating program state.
L0077 |     body = db.Column(db.Text, nullable=False) | Assignment statement storing or updating program state.
L0078 |     created_at = db.Column(db.DateTime, nullable=False, default=utcnow_naive) | Assignment statement storing or updating program st
L0079 | | Blank line used for readability and logical separation.
L0080 |     def __repr__(self): | Declares a function/method as a reusable unit of behavior.
L0081 |         return f"<Message {self.sender_email} -> {self.recipient_role} {self.created_at}>" | Returns a value (or control) back to t
L0082 | | Blank line used for readability and logical separation.
L0083 | class User(db.Model): | Declares a class that groups related state and behavior.
L0084 |     __tablename__ = 'users' | Assignment statement storing or updating program state.
L0085 |     __table_args__ = ( | Assignment statement storing or updating program state.
L0086 |         db.Index("ix_user_created_at", "created_at"), | Operational statement participating in the file's runtime behavior.
L0087 |         db.Index("ix_user_role", "role"), | Operational statement participating in the file's runtime behavior.
L0088 |     ) | Operational statement participating in the file's runtime behavior.
L0089 |     id = db.Column(db.Integer, primary_key=True) | Assignment statement storing or updating program state.
L0090 |     uid = db.Column(db.String(12), unique=True, nullable=True) | Assignment statement storing or updating program state.
L0091 |     email = db.Column(db.String(150), unique=True, nullable=False) | Assignment statement storing or updating program state.
L0092 |     password_hash = db.Column(db.String(200), nullable=False) | Assignment statement storing or updating program state.
L0093 |     full_name = db.Column(db.String(150), nullable=False) | Assignment statement storing or updating program state.
L0094 |     first_name = db.Column(db.String(80), nullable=True) | Assignment statement storing or updating program state.
L0095 |     last_name = db.Column(db.String(80), nullable=True) | Assignment statement storing or updating program state.
L0096 |     gender = db.Column(db.String(20), nullable=True) | Assignment statement storing or updating program state.
L0097 |     region = db.Column(db.String(120), nullable=True) | Assignment statement storing or updating program state.
L0098 |     role = db.Column(db.String(50), nullable=False, default='staff') | Assignment statement storing or updating program state.
L0099 |     is_blocked = db.Column(db.Boolean, nullable=False, default=False) | Assignment statement storing or updating program state.
L0100 |     support_desk = db.Column(db.String(100), nullable=True) | Assignment statement storing or updating program state.
L0101 |     site_operations_phone = db.Column(db.String(40), nullable=True) | Assignment statement storing or updating program state.
L0102 |     emergency_phone = db.Column(db.String(40), nullable=True) | Assignment statement storing or updating program state.
L0103 |     created_at = db.Column(db.DateTime, nullable=False, default=utcnow_naive) | Assignment statement storing or updating program st
L0104 | | Blank line used for readability and logical separation.
L0105 |     def get_id(self): | Declares a function/method as a reusable unit of behavior.
L0106 |         return str(self.id) | Returns a value (or control) back to the caller.
L0107 | | Blank line used for readability and logical separation.
L0108 |     @property | Decorator line that modifies the behavior of the definition below.

```

```

L0109 |     def is_active(self): | Declares a function/method as a reusable unit of behavior.
L0110 |         return not self.is_blocked | Returns a value (or control) back to the caller.
L0111 | | Blank line used for readability and logical separation.
L0112 |     @property | Decorator line that modifies the behavior of the definition below.
L0113 |     def display_name(self): | Declares a function/method as a reusable unit of behavior.
L0114 |         parts = [part for part in [self.first_name, self.last_name] if part] | Assignment statement storing or updating program state.
L0115 |         return " ".join(parts) if parts else self.full_name | Returns a value (or control) back to the caller.
L0116 | | Blank line used for readability and logical separation.
L0117 |     @property | Decorator line that modifies the behavior of the definition below.
L0118 |     def is_authenticated(self): | Declares a function/method as a reusable unit of behavior.
L0119 |         return True | Returns a value (or control) back to the caller.
L0120 | | Blank line used for readability and logical separation.
L0121 |     @property | Decorator line that modifies the behavior of the definition below.
L0122 |     def is_anonymous(self): | Declares a function/method as a reusable unit of behavior.
L0123 |         return False | Returns a value (or control) back to the caller.
L0124 | | Blank line used for readability and logical separation.
L0125 |     def __repr__(self): | Declares a function/method as a reusable unit of behavior.
L0126 |         return f"<User {self.email} ({self.role})>" | Returns a value (or control) back to the caller.
L0127 | | Blank line used for readability and logical separation.
L0128 | | Blank line used for readability and logical separation.
L0129 | class UserSettings(db.Model): | Declares a class that groups related state and behavior.
L0130 |     """Per-user settings for theme, language, and preferences.""" | Docstring boundary used to describe a module, class, or function.
L0131 |     __tablename__ = 'user_settings' | Assignment statement storing or updating program state.
L0132 |     id = db.Column(db.Integer, primary_key=True) | Assignment statement storing or updating program state.
L0133 |     user_id = db.Column(db.Integer, db.ForeignKey('users.id'), unique=True, nullable=False, index=True) | Assignment statement storing or updating program state.
L0134 |     theme = db.Column(db.String(20), nullable=False, default='light') # light, dark | Assignment statement storing or updating program state.
L0135 |     language = db.Column(db.String(10), nullable=False, default='en') # en, sw, fr, ar | Assignment statement storing or updating program state.
L0136 |     preferences_json = db.Column(db.Text, nullable=False, default='{}') # JSON for future extensibility | Assignment statement storing or updating program state.
L0137 |     updated_at = db.Column(db.DateTime, nullable=False, default=utcnow_naive, onupdate=utcnow_naive) | Assignment statement storing or updating program state.
L0138 | | Blank line used for readability and logical separation.
L0139 |     # Relationship | Comment line documenting intent or context for nearby code.
L0140 |     user = db.relationship('User', backref='settings', uselist=False) | Assignment statement storing or updating program state.
L0141 | | Blank line used for readability and logical separation.
L0142 |     def get_preferences(self): | Declares a function/method as a reusable unit of behavior.
L0143 |         """Parse preferences JSON.""" | Docstring boundary used to describe a module, class, or function.
L0144 |         try: | Starts an exception handling block for risky operations.
L0145 |             return json.loads(self.preferences_json or '{}') | Returns a value (or control) back to the caller.
L0146 |         except (json.JSONDecodeError, TypeError): | Handles errors raised in the associated try block.
L0147 |             return {} | Returns a value (or control) back to the caller.
L0148 | | Blank line used for readability and logical separation.
L0149 |     def set_preferences(self, preferences_dict): | Declares a function/method as a reusable unit of behavior.
L0150 |         """Serialize preferences to JSON.""" | Docstring boundary used to describe a module, class, or function.
L0151 |         self.preferences_json = json.dumps(preferences_dict or {}) | Assignment statement storing or updating program state.
L0152 | | Blank line used for readability and logical separation.
L0153 |     def __repr__(self): | Declares a function/method as a reusable unit of behavior.
L0154 |         return f"<UserSettings user_id={self.user_id} theme={self.theme} language={self.language}>" | Returns a value (or control) back to the caller.
L0155 | | Blank line used for readability and logical separation.

```


[E8F4F8] '<w:tblW w:w="0" w:type="auto"/><w:tblInd w:w="8" w:type="dxa"/><w:tblBorders><w:top w:val="single" w:sz="6" w:space=

L0002 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="41504B75" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0003 | [E8F4F8] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraI

L0004 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="08CFC7E9" w14:textId="1021DE6F" w:rsidR="009D1931" w:rsidRDefault=

L0005 | [E8F4F8] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraI

L0006 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="66C2AEBE" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0007 | [E8F4F8] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraI

L0008 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="7404E203" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0009 | [E8F4F8] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraI

L0010 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="11B8D7B3" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0011 | [E8F4F8] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraI

L0012 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="0B39170A" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0013 | [E8F4F8] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraI

L0014 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="23F7D9A1" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0015 | [] '<w:tcPr><w:tcW w:w="10881" w:type="dxa"/><w:gridSpan w:val="2"/></w:tcPr><p w14:paraId="13C06335" w14:textId="77777777"

L0016 | [SEC] [E8F4F8] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:para

L0017 | [SEC] [E8F4F8] '<w:tcW w:w="5440" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraId="3198

L0018 | [FFFFFF] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><p w14:paraI

L0019 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="0AAAA3F5" w14:textId="3BE557E3" w:rsidR="009D1931" w:rsidR

L0020 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="7AE62EB4" w14:textId="68696200" w:rsidR="009D1931" w:rsidR

L0021 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="2018247E" w14:textId="2DE17F3B" w:rsidR="009D1931" w:rsidR

L0022 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="399A20EE" w14:textId="3EDABD1F" w:rsidR="009D1931" w:rsidR

L0023 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="52F76D46" w14:textId="68961B10" w:rsidR="009D1931" w:rsidR

L0024 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="3C22E1C5" w14:textId="6199159E" w:rsidR="009D1931" w:rsidR

L0025 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="281DE984" w14:textId="48DF4250" w:rsidR="009D1931" w:rsidR

L0026 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="71F64720" w14:textId="37FFD0D4" w:rsidR="009D1931" w:rsidR

L0027 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="29B44DA7" w14:textId="6BF81FB7" w:rsidR="009D1931" w:rsidR

L0028 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="6E060A86" w14:textId="1BFCB35B" w:rsidR="009D1931" w:rsidR

L0029 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="35CFA80E" w14:textId="7E5F0AA2" w:rsidR="009D1931" w:rsidRDefault=

L0030 | [FFFFFF] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><p w14:paraI

L0031 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="6FA8BE71" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0032 | [] '<w:tcPr><w:tcW w:w="10881" w:type="dxa"/><w:gridSpan w:val="2"/></w:tcPr><p w14:paraId="677E786E" w14:textId="77777777"

L0033 | [SEC] [E8F4F8] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:para

L0034 | [SEC] [E8F4F8] '<w:tcW w:w="5440" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraId="3CD2

L0035 | [FFFFFF] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><p w14:paraI

L0036 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="79E086AC" w14:textId="1F27DF8A" w:rsidR="009D1931" w:rsidR

L0037 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="431870EA" w14:textId="57B7802E" w:rsidR="009D1931" w:rsidR

L0038 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="6C73A7C5" w14:textId="35BD56C1" w:rsidR="009D1931" w:rsidR

L0039 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="2E3BDAE7" w14:textId="3BB5EF1F" w:rsidR="009D1931" w:rsidR

L0040 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="67F05BC9" w14:textId="4DA35D44" w:rsidR="009D1931" w:rsidR

L0041 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="6B279578" w14:textId="0F3DCDDA" w:rsidR="009D1931" w:rsidR

L0042 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="05109025" w14:textId="510ED6FF" w:rsidR="009D1931" w:rsidR

L0043 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></

L0054		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="1D034F2D" w14:textId="75711FE2" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0055		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="619F4A4F" w14:textId="0FE10F40" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0056		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="4BC273CE" w14:textId="4812BE53" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0057		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="57E5188C" w14:textId="121C5936" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0058		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="57896A09" w14:textId="64972509" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0059		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="1A7EF2DC" w14:textId="1574C1DC" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0060		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="39F10018" w14:textId="3B3DC481" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0061		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="5E359DFB" w14:textId="4BA84973" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0062		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="43239CA3" w14:textId="1216B0A6" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0063		[]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="3047650F" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0064		[FFFFFF]	'<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><p w14:paraId="57896A09" w14:textId="64972509" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0065		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="4CEF7ADC" w14:textId="0B838B0D" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0066		[]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="42826265" w14:textId="507A34C8" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0067	[SEC]	[E8F4F8]	'<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraId="57896A09" w14:textId="64972509" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0068	[SEC]	[E8F4F8]	'<w:tcW w:w="5440" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraId="21034F2D" w14:textId="75711FE2" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0069		[FFFFFF]	'<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><p w14:paraId="57896A09" w14:textId="64972509" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0070		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="1D302E04" w14:textId="7B47CC4C" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0071		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="3F41F73D" w14:textId="0C75722E" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0072		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="0524D53B" w14:textId="10A9F7DA" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0073		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="46FB337E" w14:textId="63960EF4" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0074		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="6753B3FA" w14:textId="0EC89FA7" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0075		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="1F107951" w14:textId="41A18A8E" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0076		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="574EA931" w14:textId="6D4D4EF6" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0077		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="70D3012D" w14:textId="49DB2A5A" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0078		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="52A9D9EF" w14:textId="77F4A99D" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0079		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="68049F28" w14:textId="001BF3F6" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0080		[FFFFFF]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="350CC37E" w14:textId="4B6AC4A9" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0081		[]	'<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="5F1F97CF" w14:textId="5A076C40" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0082	[SEC]	[E8F4F8]	'<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraId="57896A09" w14:textId="64972509" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0083	[SEC]	[E8F4F8]	'<w:tcW w:w="5440" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraId="1AE10F40" w14:textId="0FE10F40" w:rsidR="009D1931" w:rsidRDefault="009D1931" />
L0084		[FFFFFF]	'<w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/

[illegible]

[L0164 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="00A070FD" w14:textId="4A9632EB" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0165 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="13B9E55E" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0166 | [] '<w:tcPr><w:tcW w:w="10881" w:type="dxa"/></w:gridSpan w:val="2"/></w:tcPr><p w14:paraId="02B8E971" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0167 | [] '<w:tcPr><w:tcW w:w="10881" w:type="dxa"/></w:gridSpan w:val="2"/></w:tcPr><p w14:paraId="572AE7A" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0168 | [SEC] [E8F4F8] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraId="3CA9E4F8" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0169 | [SEC] [E8F4F8] '<w:tcW w:w="5440" w:type="dxa"/></w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><p w14:paraId="3CA9E4F8" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0170 | [] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><p w14:paraId="35882688" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0171 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="433AF52A" w14:textId="69148DA7" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0172 | [FFFFFF] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><p w14:paraId="033DBD3F" w14:textId="3DEA70C9" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0173 | [] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><p w14:paraId="1FBB2D77" w14:textId="4E3E9F5E" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0174 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="7DF28043" w14:textId="47D36BA1" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0175 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="5F7F9D67" w14:textId="3DD4731E" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0176 | [] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><p w14:paraId="6CE19880" w14:textId="7DDDC5F4" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0177 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="796C93F9" w14:textId="7DA4F7C2" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0178 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="699583C4" w14:textId="5D26FBFD" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0179 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="602348F1" w14:textId="6DAE3106" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0180 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="5D8BACC8" w14:textId="1B046006" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0181 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="562EE0B5" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0182 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="0C6B391A" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0183 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="040D9D83" w14:textId="7E987D8B" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0184 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="60F569A5" w14:textId="2035B5A8" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0185 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="5D7802DE" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0186 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="7F5DBFBF" w14:textId="164B72D8" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0187 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="6A3109A6" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0188 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="77EE8CA5" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0189 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="305F6138" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0190 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="3891F57D" w14:textId="1F7FC00D" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0191 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="090D2CAD" w14:textId="6F7CC421" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0192 | [FFFFFF] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><p w14:paraId="11C8FD9D" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0193 | [] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><p w14:paraId="56D5A830" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0194 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="09DA5B5D" w14:textId="705C62C9" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0195 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="54BBD08C" w14:textId="4B777907" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0196 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="083A0DB1" w14:textId="3A3C36BA" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0197 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="0D009F69" w14:textId="09608455" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0198 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><p w14:paraId="0BBD7825" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault="009D1931" />

L0199 | [] '<w:tcW w:w="5440" w:type="dxa"/>&

L0219 | ['<w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="0DC4242E" w14:textId="77777777" w:rsidR="009D1931" w:rsidP="009D1931">
L0220 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="0B7B28C3" w14:textId="27D4BC40" w:rsidR="009D1931" w:rsidP="009D1931">
L0221 | [FFFFFF] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="06232745" w14:textId="77777777" w:rsidR="009D1931" w:rsidP="009D1931">
L0222 | [] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="2AF3605A" w14:textId="2A5C4B3C" w:rsidR="009D1931" w:rsidP="009D1931">
L0223 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5587BF30" w14:textId="081BF042" w:rsidR="009D1931" w:rsidPDefault="009D1931">
L0224 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="790A9B8F" w14:textId="314AF02E" w:rsidR="009D1931" w:rsidPDefault="009D1931">
L0225 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="3DA63C21" w14:textId="572262FB" w:rsidR="009D1931" w:rsidPDefault="009D1931">
L0226 | [FFFFFF] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="76EB9C79" w14:textId="50B2E613" w:rsidR="009D1931" w:rsidP="009D1931">
L0227 | [FFFFFF] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="18953C68" w14:textId="5E40AE9D" w:rsidR="009D1931" w:rsidP="009D1931">
L0228 | [] '<w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="5BF1990C" w14:textId="55DB01F6" w:rsidR="009D1931" w:rsidP="009D1931">
L0229 | [] '<w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="0DDCAE18" w14:textId="77777777" w:rsidR="009D1931" w:rsidPDefault="009D1931">
L0230 | [FFFFFF] '<w:tblW w:w="0" w:type="auto"/><w:tblInd w:w="1072" w:type="dxa"/><w:tblBorders><w:top w:val="single" w:sz="6" w:space="0" w:ruleColor="black">
L0231 | [FFFFFF] '<w:trHeight w:val="477"/></w:trPr><w:tc><w:tcPr><w:tcW w:w="6595" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="white" w:stroke="black" w:strokeDash="none" w:strokeWidth="0" w:ruleColor="black">

File 34: out_docker.txt

L0001 | ■DOCKER_NOT_FOUND | Operational statement participating in the file's runtime behavior.

File 35: out_pg_dirs.txt

L0001 | ■NONE | Operational statement participating in the file's runtime behavior.

File 36: out_psql_path.txt

L0001 | ■PSQL_NOT_FOUND | Operational statement participating in the file's runtime behavior.

File 37: out_service.json

File 38: parse_doc.py

```
L0001 | import re | Imports dependency modules: re.
L0002 | | Blank line used for readability and logical separation.
L0003 | text = open(r'photo\doc_text_lines.txt', encoding='utf-8-sig', errors='ignore').read() | Assignment statement storing or updating p
L0004 | lines = text.split('\n') | Assignment statement storing or updating program state.
L0005 | | Blank line used for readability and logical separation.
L0006 | for line in lines: | Loop iterating over a sequence to process elements one by one.
L0007 |     m = re.search(r'<w:t[>]*>(.*?)', line) | Assignment statement storing or updating program state.
L0008 |     val = m.group(1).strip() if m else '' | Assignment statement storing or updating program state.
L0009 |     is_sec = 'val="30"' in line | Assignment statement storing or updating program state.
L0010 |     is_spacer = ('gridSpan' in line and not val) | Assignment statement storing or updating program state.
L0011 |     fill_m = re.search(r'w:fill="([^\"]+)"', line) | Assignment statement storing or updating program state.
L0012 |     fill_col = fill_m.group(1) if fill_m else '' | Assignment statement storing or updating program state.
L0013 |     if val: | Conditional branch that runs only when its condition is true.
L0014 |         tag = '[SEC]' if is_sec else '    ' | Assignment statement storing or updating program state.
L0015 |         print(tag, '['+fill_col+']', repr(val)) | Operational statement participating in the file's runtime behavior.
L0016 |     elif is_spacer: | Conditional branch that runs only when its condition is true.
L0017 |         print('---SPACER---') | Operational statement participating in the file's runtime behavior.
```

File 39: photo/doc_text_lines.txt

```
L0001 | <w:tblPr><w:tblW w:w="0" w:type="auto"/><w:tblInd w:w="8" w:type="dxa"/><w:tblBorders><w:top w:val="single" w:sz="6" w:space="0" w:
L0002 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="41504B75" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault
L0003 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/><w:tcPr><w:p w14:paraId="7C69FE
L0004 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="08CFC7E9" w14:textId="1021DE6F" w:rsidR="009D1931" w:rsidRDefault
L0005 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/><w:tcPr><w:p w14:paraId="56B7DD
L0006 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="66C2AEBE" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault
L0007 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/><w:tcPr><w:p w14:paraId="59E652
L0008 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="7404E203" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault
L0009 | Odongo Moses | Operational statement participating in the file's runtime behavior.
L0010 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/><w:tcPr><w:p w14:paraId="3BDC69
L0011 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="11B8D7B3" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault
L0012 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/><w:tcPr><w:p w14:paraId="21C3B1
L0013 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="0B39170A" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault
L0014 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/><w:tcPr><w:p w14:paraId="2AF56A
L0015 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="23F7D9A1" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault
L0016 | <w:tc><w:tcPr><w:tcW w:w="10881" w:type="dxa"/><w:gridSpan w:val="2"/><w:tcPr><w:p w14:paraId="13C06335" w14:textId="77777777" w:rsidR="009D1931"
L0017 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/><w:tcPr><w:p w14:paraId="6DDF7E
L0018 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/><w:tcPr><w:p w14:paraId="31983566" w:rsidR="009D1931"
L0019 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/><w:tcPr><w:p w14:paraId="7BBFDD
L0020 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="0AAAA3F5" w14:textId="3BE557E3" w:rsidR="009D1931" w:rsidRDefault
L0021 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="7AE62EB4" w14:textId="68696200" w:rsidR="009D1931" w:rsidRDefault
L0022 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="2018247E" w14:textId="2DE17F3B" w:rsidR="009D1931" w:rsidRDefault
L0023 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="399A20EE" w14:textId="3EDABD1F" w:rsidR="009D1931" w:rsidRDefault
L0024 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="52F76D46" w14:textId="68961B10" w:rsidR="009D1931" w:rsidRDefault
L0025 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="3C22E1C5" w14:textId="6199159E" w:rsidR="009D1931" w:rsidRDefault
L0026 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="281DE984" w14:textId="48DF4250" w:rsidR="009D1931" w:rsidRDefault
L0027 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="71F64720" w14:textId="37FFD0D4" w:rsidR="009D1931" w:rsidRDefault
L0028 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="29B44DA7" w14:textId="68FB1FB7" w:rsidR="009D1931" w:rsidRDefault
L0029 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="6E060A86" w14:textId="1BFCB35B" w:rsidR="009D1931" w:rsidRDefault
L0030 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="35CFA80E" w14:textId="7E5F0AA2" w:rsidR="009D1931" w:rsidRDefault
L0031 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/><w:tcPr><w:p w14:paraId="0C4FE2
L0032 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="6FA8BE71" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault
L0033 | <w:tc><w:tcPr><w:tcW w:w="10881" w:type="dxa"/><w:gridSpan w:val="2"/><w:tcPr><w:p w14:paraId="677E786E" w14:textId="77777777" w:rsidR="009D1931"
L0034 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/><w:tcPr><w:p w14:paraId="7CAE11
L0035 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/><w:tcPr><w:p w14:paraId="3CD2AF98" w:rsidR="009D1931"
L0036 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/><w:tcPr><w:p w14:paraId="1C90CE
L0037 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="79E086AC" w14:textId="1F27DF8A" w:rsidR="009D1931" w:rsidRDefault
L0038 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="431870EA" w14:textId="57B7802E" w:rsidR="009D1931" w:rsidRDefault
L0039 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="6C73A7C5" w14:textId="35BD56C1" w:rsidR="009D1931" w:rsidRDefault
L0040 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w:p w14:paraId="2E3BDAE7" w14:textId="3BB5EF1F" w:rsidR="009D1931" w:rsidRDefault
L0041 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:tcPr><w
```

L0054 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="10E92530" w14:textId="655B2A42" w:rsidR="009D1931" w:rsidRDefault

L0055 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="1D034F2D" w14:textId="75711FE2" w:rsidR="009D1931" w:rsidRDefault

L0056 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="619F4A4F" w14:textId="0FE10F40" w:rsidR="009D1931" w:rsidRDefault

L0057 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="4BC273CE" w14:textId="4812BE53" w:rsidR="009D1931" w:rsidRDefault

L0058 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="57E5188C" w14:textId="121C5936" w:rsidR="009D1931" w:rsidRDefault

L0059 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="57896A09" w14:textId="64972509" w:rsidR="009D1931" w:rsidRDefault

L0060 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="1A7EF2DC" w14:textId="1574C1DC" w:rsidR="009D1931" w:rsidRDefault

L0061 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="39F10018" w14:textId="3B3DC481" w:rsidR="009D1931" w:rsidRDefault

L0062 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5E359DFB" w14:textId="4BA84973" w:rsidR="009D1931" w:rsidRDefault

L0063 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="43239CA3" w14:textId="1216B0A6" w:rsidR="009D1931" w:rsidRDefault

L0064 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="3047650F" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0065 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="247C3A

L0066 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="4CEF7ADC" w14:textId="0B838B0D" w:rsidR="009D1931" w:rsidRDefault

L0067 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="42826265" w14:textId="507A34C8" w:rsidR="009D1931" w:rsidRDefault

L0068 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><w:p w14:paraId="0E990F

L0069 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><w:p w14:paraId="21037F16" w1

L0070 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="15B6B4

L0071 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="1D302E04" w14:textId="7B47CC4C" w:rsidR="009D1931" w:rsidRDefault

L0072 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="3F41F73D" w14:textId="0C75722E" w:rsidR="009D1931" w:rsidRDefault

L0073 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="0524D53B" w14:textId="10A9F7DA" w:rsidR="009D1931" w:rsidRDefault

L0074 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="46FB337E" w14:textId="63960EF4" w:rsidR="009D1931" w:rsidRDefault

L0075 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="6753B3FA" w14:textId="0EC89FA7" w:rsidR="009D1931" w:rsidRDefault

L0076 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="1F107951" w14:textId="41A18A8E" w:rsidR="009D1931" w:rsidRDefault

L0077 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="574EA931" w14:textId="6D4D4EF6" w:rsidR="009D1931" w:rsidRDefault

L0078 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="70D3012D" w14:textId="49DB2A5A" w:rsidR="009D1931" w:rsidRDefault

L0079 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="52A9D9EF" w14:textId="77F4A99D" w:rsidR="009D1931" w:rsidRDefault

L0080 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="68049F28" w14:textId="001BF3F6" w:rsidR="009D1931" w:rsidRDefault

L0081 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="350CC37E" w14:textId="4B6AC4A9" w:rsidR="009D1931" w:rsidRDefault

L0082 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5F1F97CF" w14:textId="5A076C40" w:rsidR="009D1931" w:rsidRDefault

L0083 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><w:p w14:paraId="258C85

L0084 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><w:p w14:paraId="1AE1E15E" w1

L0085 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="2C4EC0

L0086 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="66112774" w14:textId="69D0A7D8" w:rsidR="009D1931" w:rsidRDefault

L0087 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="68317CAE" w14:textId="04C3E616" w:rsidR="009D1931" w:rsidRDefault

L0088 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="522C18A1" w14:textId="6A5E7A95" w:rsidR="009D1931" w:rsidRDefault

L0089 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="7F777D84" w14:textId="4591A6DB" w:rsidR="009D1931" w:rsidRDefault

L0090 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="4DE55098" w14:textId="7FBAFBA4" w:rsidR="009D1931" w:rsidRDefault

L0091 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5579DB6C" w14:textId="4354CBD9" w:rsidR="009D1931" w:rsidRDefault

L0092 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="18CDC418" w14:textId="271D14AE" w:rsidR="009D1931" w:rsidRDefault

L0093 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="12D4EF93" w14:textId="21AF30AD" w:rsidR="009D1931" w:rsidRDefault

L0094 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="34F97392" w14:textId="58EB320A" w:rsidR="009D1931" w:rsidRDefault

L0095 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="60421C89" w14:textId="51EB97A0" w:rsidR="009D1931" w:rsidRDefault

L0096 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="560B2851" w14:textId="5624C7D7" w:rsidR="009D1931" w:rsidRDefault

L0097 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="4617BDFD" w14:textId="5C136077" w:rsidR="009D1931" w:rsidRDefault

L0098 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="2468902D" w14:textId="6E689B81" w:rsidR="009D1931" w:rsidRDefault

L0099 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><w:p w14:paraId="7BD1F9

L0100 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><w:p w14:paraId="41706EB3" w1

L0101 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="4E238C

L0102 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="44DC533C" w14:textId="3E22A1BE" w:rsidR="009D1931" w:rsidRDefault

L0103 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="2C67451D" w14:textId="51A3D5DB" w:rsidR="009D1931" w:rsidRDefault

L0104 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="76680684" w14:textId="1550189D" w:rsidR="009D1931" w:rsidRDefault

L0105 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5F72D561" w14:textId="3CCD01A6" w:rsidR="009D1931" w:rsidRDefault

L0106 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="259A185C" w14:textId="1FC50324" w:rsidR="009D1931" w:rsidRDefault

L0107 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5724B155" w14:textId="64163AA4" w:rsidR="009D1931" w:rsidRDefault

L0108 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5514C099" w14:textId="43D4991E" w:rsidR="009D1931" w:rsidRDefault

L0109 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="68B688E0" w14:textId="4E02F12F" w:rsidR="009D1931" w:rsidRDefault=

L0110 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="23897E08" w14:textId="61EB7762" w:rsidR="009D1931" w:rsidRDefault=

L0111 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="40B7A2B5" w14:textId="214FC63E" w:rsidR="009D1931" w:rsidRDefault=

L0112 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="632F79DE" w14:textId="0C74F19F" w:rsidR="009D1931" w:rsidRDefault=

L0113 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="64017342" w14:textId="7D6623F8" w:rsidR="009D1931" w:rsidRDefault=

L0114 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="41D8CE1C" w14:textId="527EDEAC" w:rsidR="009D1931" w:rsidRDefault=

L0115 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="2D771FCF" w14:textId="683156CE" w:rsidR="009D1931" w:rsidRDefault=

L0116 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="69B9E555" w14:textId="47DC135F" w:rsidR="009D1931" w:rsidRDefault=

L0117 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="51682E6F" w14:textId="60E00AFC" w:rsidR="009D1931" w:rsidRDefault=

L0118 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="77D05F32" w14:textId="0E125FD5" w:rsidR="009D1931" w:rsidRDefault=

L0119 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="7FB8FD1C" w14:textId="71F332A3" w:rsidR="009D1931" w:rsidRDefault=

L0120 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><w:p w14:paraId="4AC117

L0121 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><w:p w14:paraId="6CB77A0E" w

L0122 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="40ADB9

L0123 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="1CB1E0BB" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0124 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="0001B6

L0125 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5BD62BC1" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0126 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="7C1811

L0127 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="42750F1C" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0128 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="442D5A

L0129 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="1AE81DC" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0130 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="50D1F5

L0131 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="21D3ECE6" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0132 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="1618B9

L0133 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="4D99C1AD" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0134 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="2BD651

L0135 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5804E299" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0136 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="238A08

L0137 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="017C2FDE" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0138 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="3769C6

L0139 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="6F0D4E1B" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=

L0140 | <w:tc><w:tcPr><w:tcW w:w="10881" w:type="dxa"/><w:gridSpan w:val="2"/></w:tcPr><w:p w14:paraId="2CA78F14" w14:textId="77777777" w:r

L0141 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><w:p w14:paraId="3DE907

L0142 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><w:p w14:paraId="2FE36952" w

L0143 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="01439A

L0144 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="18A1787B" w14:textId="19EA8344" w:rsidR="009D1931" w:rsidRDefault=

L0145 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="FFFFFF"/></w:tcPr><w:p w14:paraId="2CE9A4

L0146 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="1A619C33" w14:textId="54BA787B" w:rsidR="009D1931" w:rsidRDefault=

L0147 | <w:tc><w:tcPr><w:tcW w:w="10881" w:type="dxa"/><w:gridSpan w:val="2"/></w:tcPr><w:p w14:paraId="6D968A4C" w14:textId="77777777" w:r

L0

L0164 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="52034172" w14:textId="5F5492F2" w:rsidR="009D1931" w:rsidRDefault

L0165 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="00A070FD" w14:textId="4A9632EB" w:rsidR="009D1931" w:rsidRDefault

L0166 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="13B9E55E" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0167 | <w:tc><w:tcPr><w:tcW w:w="10881" w:type="dxa"/><w:gridSpan w:val="2"/></w:tcPr><w:p w14:paraId="02B8E971" w14:textId="77777777" w:r

L0168 | <w:tc><w:tcPr><w:tcW w:w="10881" w:type="dxa"/><w:gridSpan w:val="2"/></w:tcPr><w:p w14:paraId="572AEE7A" w14:textId="77777777" w:r

L0169 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><w:p w14:paraId="4BB011

L0170 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill="E8F4F8"/></w:tcPr><w:p w14:paraId="3CA90F37" w1

L0171 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="35882688" w14:textId="77777777" w:rsidR="009D1931" w:rsidRD

L0172 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="433AF52A" w14:textId="69148DA7" w:rsidR="009D1931" w:rsidRDefault

L0173 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="033DBD3F" w14:textId="3DEA70C9" w:rsidR="009D1931" w:rsidRD

L0174 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="1FBB2D77" w14:textId="4E3E9F5E" w:rsidR="009D1931" w:rsidRD

L0175 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="7DF28043" w14:textId="47D36BA1" w:rsidR="009D1931" w:rsidRDefault

L0176 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5F7F9D67" w14:textId="3DD4731E" w:rsidR="009D1931" w:rsidRDefault

L0177 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="6CE19880" w14:textId="7DDDC5F4" w:rsidR="009D1931" w:rsidRD

L0178 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="796C93F9" w14:textId="7DA4F7C2" w:rsidR="009D1931" w:rsidRDefault

L0179 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="699583C4" w14:textId="5D26FBFD" w:rsidR="009D1931" w:rsidRDefault

L0180 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="602348F1" w14:textId="6DAE3106" w:rsidR="009D1931" w:rsidRDefault

L0181 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5D8BACC8" w14:textId="1B046006" w:rsidR="009D1931" w:rsidRDefault

L0182 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="562EE0B5" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0183 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="0C6B391A" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0184 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="040D9D83" w14:textId="7E987D8B" w:rsidR="009D1931" w:rsidRDefault

L0185 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="60F569A5" w14:textId="2035B5A8" w:rsidR="009D1931" w:rsidRDefault

L0186 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5D7802DE" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0187 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="7F5DBFB" w14:textId="164B72D8" w:rsidR="009D1931" w:rsidRDefault

L0188 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="6A3109A6" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0189 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="77EE8CA5" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0190 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="305F6138" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0191 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="3891F57D" w14:textId="1F7FC00D" w:rsidR="009D1931" w:rsidRDefault

L0192 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="090D2CAD" w14:textId="6F7CC421" w:rsidR="009D1931" w:rsidRDefault

L0193 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="11C8FD9D" w14:textId="77777777" w:rsidR="009D1931" w:rsidRD

L0194 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="56D5A830" w14:textId="77777777" w:rsidR="009D1931" w:rsidRD

L0195 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="09DA585D" w14:textId="705C62C9" w:rsidR="009D1931" w:rsidRDefault

L0196 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="54BBD08C" w14:textId="4B777907" w:rsidR="009D1931" w:rsidRDefault

L0197 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="083A0DB1" w14:textId="3A3C36BA" w:rsidR="009D1931" w:rsidRDefault

L0198 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="0D009F69" w14:textId="09608455" w:rsidR="009D1931" w:rsidRDefault

L0199 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="0BB07825" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0200 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="59D80DDB" w14:textId="340EE342" w:rsidR="009D1931" w:rsidRDefault

L0201 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="4057E344" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0202 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="7D5F3A72" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0203 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5154EB10" w14:textId="225E5A7B" w:rsidR="009D1931" w:rsidRDefault

L0204 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="7D8BC16E" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0205 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="2D5C6E10" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0206 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="08E4F11B" w14:textId="313FDB67" w:rsidR="009D1931" w:rsidRD

L0207 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="43F0B539" w14:textId="316F793B" w:rsidR="009D1931" w:rsidRD

L0208 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="3DAFAB9D" w14:textId="3523C13E" w:rsidR="009D1931" w:rsidRDefault

L0209 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="6E0C825C" w14:textId="09BF1A6C" w:rsidR="009D1931" w:rsidRDefault

L0210 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="55ACA9A6" w14:textId="79F84D96" w:rsidR="009D1931" w:rsidRDefault

L0211 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="6288291C" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0212 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="281099C5" w14:textId="75286FE0" w:rsidR="009D1931" w:rsidRD

L0213 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="2547609B" w14:textId="77777777" w:rsidR="009D1931" w:rsidRD

L0214 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="2F181A6D" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0215 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="0FC86314" w14:textId="711DBEFB" w:rsidR="009D1931" w:rsidRDefault

L0216 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="0039921D" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault

L0217 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="52859328" w14:textId="01066AE4" w:rsidR="009D1931" w:rsidRD

L0218 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="19CC3CC6" w14:textId="77777777" w:rsidR="009D1931" w:rsidRD

```

L0219 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="4766AA8E" w14:textId="0949B8C9" w:rsidR="009D1931" w:rsidRDefault=
L0220 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="0DC4242E" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=
L0221 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="0B7B28C3" w14:textId="27D4BC40" w:rsidR="009D1931" w:rsidRDefault=
L0222 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="06232745" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=
L0223 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="2AF3605A" w14:textId="2A5C4B3C" w:rsidR="009D1931" w:rsidRDefault=
L0224 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="5587BF30" w14:textId="081BF042" w:rsidR="009D1931" w:rsidRDefault=
L0225 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="790A9B8F" w14:textId="314AF02E" w:rsidR="009D1931" w:rsidRDefault=
L0226 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="3DA63C21" w14:textId="572262FB" w:rsidR="009D1931" w:rsidRDefault=
L0227 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="76EB9C79" w14:textId="50B2E613" w:rsidR="009D1931" w:rsidRDefault=
L0228 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="18953C68" w14:textId="5E40AE9D" w:rsidR="009D1931" w:rsidRDefault=
L0229 | <w:tc><w:tcPr><w:tcW w:w="5441" w:type="dxa"/></w:tcPr><w:p w14:paraId="5BF1990C" w14:textId="55DB01F6" w:rsidR="009D1931" w:rsidRDefault=
L0230 | <w:tcPr><w:tcW w:w="5440" w:type="dxa"/></w:tcPr><w:p w14:paraId="0DDCAE18" w14:textId="77777777" w:rsidR="009D1931" w:rsidRDefault=
L0231 | For | Operational statement participating in the file's runtime behavior.
L0232 | SOLITON | Operational statement participating in the file's runtime behavior.
L0233 | <w:tblPr><w:tblW w:w="0" w:type="auto"/><w:tblInd w:w="1072" w:type="dxa"/><w:tblBorders><w:top w:val="single" w:sz="6" w:space="0"
L0234 | n | Operational statement participating in the file's runtime behavior.
L0235 | <w:trPr><w:trHeight w:val="477"/></w:trPr><w:tc><w:tcPr><w:tcW w:w="6595" w:type="dxa"/><w:shd w:val="clear" w:color="auto" w:fill=

```

File 40: pm_app/__init__.py

```
L0001 | from __future__ import annotations | Imports specific names from another module for direct usage.
L0002 | | Blank line used for readability and logical separation.
L0003 | from flask_login import LoginManager | Imports specific names from another module for direct usage.
L0004 | | Blank line used for readability and logical separation.
L0005 | | Blank line used for readability and logical separation.
L0006 | login_manager = LoginManager() | Assignment statement storing or updating program state.
L0007 | | Blank line used for readability and logical separation.
L0008 | | Blank line used for readability and logical separation.
L0009 | def create_app(config_class: str \ | None = None, test_config: dict \ | None = None): | Declares a function/method as a reusable unit
L0010 |     """Compatibility app factory that delegates to the legacy factory. | Docstring boundary used to describe a module, class, or fu
L0011 | | Blank line used for readability and logical separation.
L0012 |     This package is the modular entrypoint for the ongoing split. Route logic | Operational statement participating in the file's m
L0013 |     remains in the legacy factory until extraction is complete. | Operational statement participating in the file's runtime behavior
L0014 |     """ | Docstring boundary used to describe a module, class, or function.
L0015 |     from app import create_app as legacy_create_app | Imports specific names from another module for direct usage.
L0016 | | Blank line used for readability and logical separation.
L0017 |     app = legacy_create_app(test_config=test_config) | Assignment statement storing or updating program state.
L0018 | | Blank line used for readability and logical separation.
L0019 |     # Keep optional config_class support for future module-native config. | Comment line documenting intent or context for nearby c
L0020 |     if config_class: | Conditional branch that runs only when its condition is true.
L0021 |         app.config.from_object(config_class) | Operational statement participating in the file's runtime behavior.
L0022 | | Blank line used for readability and logical separation.
L0023 |     return app | Returns a value (or control) back to the caller.
```


File 41: pm_app/api/__init__.py

File 42: pm_app/api/routes.py

```
L0001 | from flask import jsonify, request | Imports specific names from another module for direct usage.
L0002 | from flask_login import current_user, login_required | Imports specific names from another module for direct usage.
L0003 | | Blank line used for readability and logical separation.
L0004 | _MAX_SEARCH_LEN = 100 | Assignment statement storing or updating program state.
L0005 | _VALID_ROLES = {"developer", "staff", "technician", "manager", "general_manager"} | Assignment statement storing or updating program state.
L0006 | | Blank line used for readability and logical separation.
L0007 | | Blank line used for readability and logical separation.
L0008 | def _err(code: str, message: str, status: int): | Declares a function/method as a reusable unit of behavior.
L0009 |     """Return a consistent JSON error envelope.""" | Docstring boundary used to describe a module, class, or function.
L0010 |     return jsonify({"status": "error", "code": code, "message": message}), status | Returns a value (or control) back to the caller.
L0011 | | Blank line used for readability and logical separation.
L0012 | | Blank line used for readability and logical separation.
L0013 | def register_api_routes(app, *, consumable_model, activity_model, db, normalize_role, limiter=None): | Declares a function/method as a reusable unit of behavior.
L0014 |     def _limit(spec): | Declares a function/method as a reusable unit of behavior.
L0015 |         """Apply a rate-limit decorator when limiter is available.""" | Docstring boundary used to describe a module, class, or function.
L0016 |         if limiter is not None: | Conditional branch that runs only when its condition is true.
L0017 |             return limiter.limit(spec) | Returns a value (or control) back to the caller.
L0018 |         return lambda f: f # no-op when limiter is not configured | Returns a value (or control) back to the caller.
L0019 | | Blank line used for readability and logical separation.
L0020 | @app.route('/api/consumables/', methods=['GET']) | Decorator line that modifies the behavior of the definition below.
L0021 | @login_required | Decorator line that modifies the behavior of the definition below.
L0022 | @_limit("200 per hour") | Decorator line that modifies the behavior of the definition below.
L0023 | def api_get_consumables(): | Declares a function/method as a reusable unit of behavior.
L0024 |     site_id = (request.args.get('site_id') or '')[:_MAX_SEARCH_LEN] | Assignment statement storing or updating program state.
L0025 |     site_name = (request.args.get('site_name') or '')[:_MAX_SEARCH_LEN] | Assignment statement storing or updating program state.
L0026 |     search = (request.args.get('q') or '')[:_MAX_SEARCH_LEN] | Assignment statement storing or updating program state.
L0027 |     query = consumable_model.query | Assignment statement storing or updating program state.
L0028 |     if site_id: | Conditional branch that runs only when its condition is true.
L0029 |         query = query.filter(consumable_model.site_id.ilike(f"%{site_id}%")) | Assignment statement storing or updating program state.
L0030 |     if site_name: | Conditional branch that runs only when its condition is true.
L0031 |         query = query.filter(consumable_model.site_name.ilike(f"%{site_name}%")) | Assignment statement storing or updating program state.
L0032 |     if search: | Conditional branch that runs only when its condition is true.
L0033 |         query = query.filter(consumable_model.description.ilike(f"%{search}%")) | Assignment statement storing or updating program state.
L0034 | | Blank line used for readability and logical separation.
L0035 |     page = max(1, request.args.get('page', 1, type=int)) | Assignment statement storing or updating program state.
L0036 |     per_page = min(max(1, request.args.get('per_page', 10, type=int)), 100) | Assignment statement storing or updating program state.
L0037 |     items = query.order_by(consumable_model.created_at.desc()).paginate(page=page, per_page=per_page, error_out=False) | Assignment statement storing or updating program state.
L0038 | | Blank line used for readability and logical separation.
L0039 |     data = { | Assignment statement storing or updating program state.
L0040 |         'status': 'ok', | Operational statement participating in the file's runtime behavior.
L0041 |         'total': items.total, | Operational statement participating in the file's runtime behavior.
L0042 |         'page': items.page, | Operational statement participating in the file's runtime behavior.
L0043 |         'per_page': items.per_page, | Operational statement participating in the file's runtime behavior.
L0044 |         'items': [ | Operational statement participating in the file's runtime behavior.
L0045 |             { | Block delimiter controlling scope/structure in this language.
L0046 |                 'id': c.id, | Operational statement participating in the file's runtime behavior.
L0047 |                 'site_id': c.site_id, | Operational statement participating in the file's runtime behavior.
L0048 |                 'site_name': c.site_name, | Operational statement participating in the file's runtime behavior.
L0049 |                 'description': c.description, | Operational statement participating in the file's runtime behavior.
L0050 |                 'created_by': c.created_by, | Operational statement participating in the file's runtime behavior.
L0051 |                 'location': c.location, | Operational statement participating in the file's runtime behavior.
L0052 |                 'signage_image_url': c.signage_image_url, | Operational statement participating in the file's runtime behavior.
L0053 |                 'screenshot_url': c.screenshot_url, | Operational statement participating in the file's runtime behavior.
```

```

L0054 |         'before_usage_image_url': c.before_usage_image_url, | Operational statement participating in the file's runtime
L0055 |         'created_at': c.created_at.isoformat(), | Operational statement participating in the file's runtime behavior.
L0056 |     } | Block delimiter controlling scope/structure in this language.
L0057 |     for c in items.items | Loop iterating over a sequence to process elements one by one.
L0058 | ], | Operational statement participating in the file's runtime behavior.
L0059 | } | Block delimiter controlling scope/structure in this language.
L0060 |     return jsonify(data) | Returns a value (or control) back to the caller.
L0061 | | Blank line used for readability and logical separation.
L0062 | @app.route('/api/consumables/<int:item_id>', methods=['GET']) | Decorator line that modifies the behavior of the definition below
L0063 | @login_required | Decorator line that modifies the behavior of the definition below.
L0064 | @_limit("300 per hour") | Decorator line that modifies the behavior of the definition below.
L0065 | def api_consumable_detail(item_id): | Declares a function/method as a reusable unit of behavior.
L0066 |     c = consumable_model.query.get_or_404(item_id) | Assignment statement storing or updating program state.
L0067 |     return jsonify({ | Returns a value (or control) back to the caller.
L0068 |         'status': 'ok', | Operational statement participating in the file's runtime behavior.
L0069 |         'id': c.id, | Operational statement participating in the file's runtime behavior.
L0070 |         'site_id': c.site_id, | Operational statement participating in the file's runtime behavior.
L0071 |         'site_name': c.site_name, | Operational statement participating in the file's runtime behavior.
L0072 |         'description': c.description, | Operational statement participating in the file's runtime behavior.
L0073 |         'created_by': c.created_by, | Operational statement participating in the file's runtime behavior.
L0074 |         'location': c.location, | Operational statement participating in the file's runtime behavior.
L0075 |         'signage_image_url': c.signage_image_url, | Operational statement participating in the file's runtime behavior.
L0076 |         'screenshot_url': c.screenshot_url, | Operational statement participating in the file's runtime behavior.
L0077 |         'before_usage_image_url': c.before_usage_image_url, | Operational statement participating in the file's runtime behavior
L0078 |         'created_at': c.created_at.isoformat(), | Operational statement participating in the file's runtime behavior.
L0079 |     }) | Operational statement participating in the file's runtime behavior.
L0080 | | Blank line used for readability and logical separation.
L0081 | @app.route('/api/consumables/', methods=['POST']) | Decorator line that modifies the behavior of the definition below.
L0082 | @login_required | Decorator line that modifies the behavior of the definition below.
L0083 | @_limit("60 per hour") | Decorator line that modifies the behavior of the definition below.
L0084 | def api_create_consumable(): | Declares a function/method as a reusable unit of behavior.
L0085 |     if normalize_role(current_user.role) != "developer": | Conditional branch that runs only when its condition is true.
L0086 |         return _err("FORBIDDEN", "Your role cannot create consumables.", 403) | Returns a value (or control) back to the caller
L0087 | | Blank line used for readability and logical separation.
L0088 |     payload = request.get_json(silent=True) or {} | Assignment statement storing or updating program state.
L0089 |     required = ['site_id', 'site_name', 'description'] | Assignment statement storing or updating program state.
L0090 |     if not all((payload.get(key) or "").strip() for key in required): | Conditional branch that runs only when its condition is
L0091 |         return _err("VALIDATION_ERROR", "site_id, site_name and description are required.", 400) | Returns a value (or control)
L0092 | | Blank line used for readability and logical separation.
L0093 |     # Length guard on free-text fields | Comment line documenting intent or context for nearby code.
L0094 |     if len(payload.get('description', '')) > 2000: | Conditional branch that runs only when its condition is true.
L0095 |         return _err("VALIDATION_ERROR", "description must be 2000 characters or fewer.", 400) | Returns a value (or control) ba
L0096 | | Blank line used for readability and logical separation.
L0097 |     c = consumable_model( | Assignment statement storing or updating program state.
L0098 |         site_id=payload['site_id'].strip()[:20], | Assignment statement storing or updating program state.
L0099 |         site_name=payload['site_name'].strip()[:120], | Assignment statement storing or updating program state.
L0100 |         description=payload['description'].strip(), | Assignment statement storing or updating program state.
L0101 |         created_by=current_user.email, | Assignment statement storing or updating program state.
L0102 |         location=(payload.get('location') or None), | Assignment statement storing or updating program state.
L0103 |         signage_image_url=payload.get('signage_image_url'), | Assignment statement storing or updating program state.
L0104 |         screenshot_url=payload.get('screenshot_url'), | Assignment statement storing or updating program state.
L0105 |         before_usage_image_url=payload.get('before_usage_image_url'), | Assignment statement storing or updating program state.
L0106 |     ) | Operational statement participating in the file's runtime behavior.
L0107 |     db.session.add(c) | Operational statement participating in the file's runtime behavior.
L0108 |     db.session.commit() | Operational statement participating in the file's runtime behavior.

```

```

L0109 |         return jsonify({'status': 'ok', 'id': c.id}), 201 | Returns a value (or control) back to the caller.
L0110 | | Blank line used for readability and logical separation.
L0111 |     @app.route('/api/activities/', methods=['GET']) | Decorator line that modifies the behavior of the definition below.
L0112 |     @login_required | Decorator line that modifies the behavior of the definition below.
L0113 |     @_limit("200 per hour") | Decorator line that modifies the behavior of the definition below.
L0114 |     def api_activities(): | Declares a function/method as a reusable unit of behavior.
L0115 |         q = activity_model.query | Assignment statement storing or updating program state.
L0116 |         activity_type = (request.args.get('activity_type') or '')[:20] | Assignment statement storing or updating program state.
L0117 |         if activity_type: | Conditional branch that runs only when its condition is true.
L0118 |             q = q.filter_by(activity_type=activity_type) | Assignment statement storing or updating program state.
L0119 | | Blank line used for readability and logical separation.
L0120 |         page = max(1, request.args.get('page', 1, type=int)) | Assignment statement storing or updating program state.
L0121 |         per_page = min(max(1, request.args.get('per_page', 10, type=int)), 100) | Assignment statement storing or updating program state.
L0122 |         items = q.order_by(activity_model.created_at.desc()).paginate(page=page, per_page=per_page, error_out=False) | Assignment statement storing or updating program state.
L0123 | | Blank line used for readability and logical separation.
L0124 |         data = { | Assignment statement storing or updating program state.
L0125 |             'status': 'ok', | Operational statement participating in the file's runtime behavior.
L0126 |             'total': items.total, | Operational statement participating in the file's runtime behavior.
L0127 |             'page': items.page, | Operational statement participating in the file's runtime behavior.
L0128 |             'per_page': items.per_page, | Operational statement participating in the file's runtime behavior.
L0129 |             'items': [ | Operational statement participating in the file's runtime behavior.
L0130 |                 { | Block delimiter controlling scope/structure in this language.
L0131 |                     'id': a.id, | Operational statement participating in the file's runtime behavior.
L0132 |                     'activity_type': a.activity_type, | Operational statement participating in the file's runtime behavior.
L0133 |                     'details': a.details, | Operational statement participating in the file's runtime behavior.
L0134 |                     'created_at': a.created_at.isoformat(), | Operational statement participating in the file's runtime behavior.
L0135 |                 } | Block delimiter controlling scope/structure in this language.
L0136 |                 for a in items.items | Loop iterating over a sequence to process elements one by one.
L0137 |             ], | Operational statement participating in the file's runtime behavior.
L0138 |         } | Block delimiter controlling scope/structure in this language.
L0139 |         return jsonify(data) | Returns a value (or control) back to the caller.
L0140 | | Blank line used for readability and logical separation.
L0141 |     @app.route('/api/dashboard-counts', methods=['GET']) | Decorator line that modifies the behavior of the definition below.
L0142 |     @login_required | Decorator line that modifies the behavior of the definition below.
L0143 |     @_limit("120 per minute") | Decorator line that modifies the behavior of the definition below.
L0144 |     def api_dashboard_counts(): | Declares a function/method as a reusable unit of behavior.
L0145 |         from flask import current_app # noqa: PLC0415 | Imports specific names from another module for direct usage.
L0146 |         get_counts = current_app.config.get("_get_live_dashboard_counts") | Assignment statement storing or updating program state.
L0147 |         if not get_counts: | Conditional branch that runs only when its condition is true.
L0148 |             return _err("NOT_AVAILABLE", "Dashboard counts not configured.", 503) | Returns a value (or control) back to the caller.
L0149 |         return jsonify({"status": "ok", **get_counts()}) | Returns a value (or control) back to the caller.

```

File 43: pm_app/api/serializers.py

L0001 | """API serializers/validators placeholder module.""" | Docstring boundary used to describe a module, class, or function.

File 44: pm_app/auth/__init__.py

File 45: pm_app/auth/forms.py

L0001 | """Auth forms module placeholder for Flask-WTF migration.""" | Docstring boundary used to describe a module, class, or function.

File 46: pm_app/auth/routes.py

```
L0001 | import secrets | Imports dependency modules: secrets.
L0002 | | Blank line used for readability and logical separation.
L0003 | from flask import abort, flash, redirect, render_template, request, session, url_for | Imports specific names from another module f
L0004 | from flask_login import current_user, login_required, login_user, logout_user | Imports specific names from another module for dire
L0005 | from werkzeug.security import check_password_hash | Imports specific names from another module for direct usage.
L0006 | | Blank line used for readability and logical separation.
L0007 | | Blank line used for readability and logical separation.
L0008 | def register_auth_routes( # noqa: C901 | Declares a function/method as a reusable unit of behavior.
L0009 |     app, | Operational statement participating in the file's runtime behavior.
L0010 |     *, | Operational statement participating in the file's runtime behavior.
L0011 |     user_model, | Operational statement participating in the file's runtime behavior.
L0012 |     db, | Operational statement participating in the file's runtime behavior.
L0013 |     app_env, | Operational statement participating in the file's runtime behavior.
L0014 |     role_lock_enabled, | Operational statement participating in the file's runtime behavior.
L0015 |     normalize_role, | Operational statement participating in the file's runtime behavior.
L0016 |     allowed_login_roles, | Operational statement participating in the file's runtime behavior.
L0017 |     get_lockout_seconds, | Operational statement participating in the file's runtime behavior.
L0018 |     register_login_failure, | Operational statement participating in the file's runtime behavior.
L0019 |     reset_login_failures, | Operational statement participating in the file's runtime behavior.
L0020 |     hash_password, | Operational statement participating in the file's runtime behavior.
L0021 | ): | Operational statement participating in the file's runtime behavior.
L0022 |     is_development = (app_env or "").strip().lower() in {"development", "dev", "local"} | Assignment statement storing or updating
L0023 |     role_lock_active = bool(role_lock_enabled) and (not is_development) | Assignment statement storing or updating program state.
L0024 | | Blank line used for readability and logical separation.
L0025 |     @app.route("/login", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L0026 |     @app.route("/login/", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L0027 |     def login(): | Declares a function/method as a reusable unit of behavior.
L0028 |         if role_lock_active: | Conditional branch that runs only when its condition is true.
L0029 |             preselected_role = (request.args.get("role") or "").strip().lower() | Assignment statement storing or updating program
L0030 |             if preselected_role not in {"developer", "staff", "technician"}: | Conditional branch that runs only when its condition
L0031 |                 preselected_role = "technician" | Assignment statement storing or updating program state.
L0032 |             else: | Fallback branch executed when prior conditions are false.
L0033 |                 preselected_role = "" | Assignment statement storing or updating program state.
L0034 | | Blank line used for readability and logical separation.
L0035 |         login_csrf_token = session.get("login_csrf_token") | Assignment statement storing or updating program state.
L0036 |         if not login_csrf_token: | Conditional branch that runs only when its condition is true.
L0037 |             login_csrf_token = secrets.token_urlsafe(32) | Assignment statement storing or updating program state.
L0038 |             session["login_csrf_token"] = login_csrf_token | Assignment statement storing or updating program state.
L0039 | | Blank line used for readability and logical separation.
L0040 |         if request.method == "POST": | Conditional branch that runs only when its condition is true.
L0041 |             email = (request.form.get("email") or "").strip() | Assignment statement storing or updating program state.
L0042 |             password = request.form.get("password") or "" | Assignment statement storing or updating program state.
L0043 |             selected_role = (request.form.get("account_type") or preselected_role or "").strip().lower() | Assignment statement sto
L0044 |             csrf_token = (request.form.get("login_csrf_token") or "").strip() | Assignment statement storing or updating program st
L0045 | | Blank line used for readability and logical separation.
L0046 |             if role_lock_active and preselected_role and selected_role != preselected_role: | Conditional branch that runs only whe
L0047 |                 flash("Invalid credentials", "danger") | Operational statement participating in the file's runtime behavior.
L0048 |                 register_login_failure(email) | Operational statement participating in the file's runtime behavior.
L0049 |                 return render_template("login.html", login_csrf_token=session["login_csrf_token"], preselected_role=preselected_ro
L0050 | | Blank line used for readability and logical separation.
L0051 |             if not csrf_token or csrf_token != session.get("login_csrf_token"): | Conditional branch that runs only when its condit
L0052 |                 flash("Session verification failed. Please try again.", "danger") | Operational statement participating in the file
L0053 |                 session["login_csrf_token"] = secrets.token_urlsafe(32) | Assignment statement storing or updating program state.
```



```
L0054 |         return render_template("login.html", login_csrf_token=session["login_csrf_token"], preselected_role=preselected_role)
L0055 | | Blank line used for readability and logical separation.
L0056 |         lockout_seconds = get_lockout_seconds(email) | Assignment statement storing or updating program state.
L0057 |         if lockout_seconds > 0: | Conditional branch that runs only when its condition is true.
L0058 |             flash(f"Too many login attempts. Try again in {lockout_seconds} seconds.", "warning") | Operational statement participating in the file's runtime behavior.
L0059 |         return render_template("login.html", login_csrf_token=session["login_csrf_token"], preselected_role=preselected_role)
L0060 | | Blank line used for readability and logical separation.
L0061 |         if not role_lock_active: | Conditional branch that runs only when its condition is true.
L0062 |             valid_roles = {"developer", "staff", "manager", "general_manager", "technician"} | Assignment statement storing or updating program state.
L0063 |         else: | Fallback branch executed when prior conditions are false.
L0064 |             valid_roles = allowed_login_roles(selected_role) | Assignment statement storing or updating program state.
L0065 |         if role_lock_active and not valid_roles: | Conditional branch that runs only when its condition is true.
L0066 |             flash("Select the account type you want to use.", "warning") | Operational statement participating in the file's runtime behavior.
L0067 |             register_login_failure(email) | Operational statement participating in the file's runtime behavior.
L0068 |             return render_template("login.html", login_csrf_token=session["login_csrf_token"], preselected_role=preselected_role)
L0069 | | Blank line used for readability and logical separation.
L0070 |         user = user_model.query.filter_by(email=email).first() | Assignment statement storing or updating program state.
L0071 |         password_ok = False | Assignment statement storing or updating program state.
L0072 |         if user and user.password_hash: | Conditional branch that runs only when its condition is true.
L0073 |             try: | Starts an exception handling block for risky operations.
L0074 |                 password_ok = check_password_hash(user.password_hash, password) | Assignment statement storing or updating program state.
L0075 |             except ValueError: | Handles errors raised in the associated try block.
L0076 |                 password_ok = False | Assignment statement storing or updating program state.
L0077 | | Blank line used for readability and logical separation.
L0078 |         if password_ok: | Conditional branch that runs only when its condition is true.
L0079 |             if user.is_blocked: | Conditional branch that runs only when its condition is true.
L0080 |                 flash("Invalid email or password.", "danger") | Operational statement participating in the file's runtime behavior.
L0081 |                 register_login_failure(email) | Operational statement participating in the file's runtime behavior.
L0082 |                 return render_template("login.html", login_csrf_token=session["login_csrf_token"], preselected_role=preselected_role)
L0083 | | Blank line used for readability and logical separation.
L0084 |         user_role = normalize_role(user.role) | Assignment statement storing or updating program state.
L0085 | | Blank line used for readability and logical separation.
L0086 |         # Always verify that the submitted account type matches the user's actual role. | Comment line documenting intent or context for nearby code.
L0087 |         # Developer may log in via any entry point; all other roles must match exactly. | Comment line documenting intent or context for nearby code.
L0088 |         if user_role != "developer" and selected_role and user_role != normalize_role(selected_role): | Conditional branch that runs only when its condition is true.
L0089 |             # Deliberate generic message – do not reveal that credentials were correct. | Comment line documenting intent or context for nearby code.
L0090 |             register_login_failure(email) | Operational statement participating in the file's runtime behavior.
L0091 |             flash("Invalid credentials.", "danger") | Operational statement participating in the file's runtime behavior.
L0092 |             return render_template("login.html", login_csrf_token=session["login_csrf_token"], preselected_role=preselected_role)
L0093 | | Blank line used for readability and logical separation.
L0094 |         if role_lock_active and user_role != "developer" and user_role not in valid_roles: | Conditional branch that runs only when its condition is true.
L0095 |             flash("Invalid credentials", "danger") | Operational statement participating in the file's runtime behavior.
L0096 |             register_login_failure(email) | Operational statement participating in the file's runtime behavior.
L0097 |             return render_template("login.html", login_csrf_token=session["login_csrf_token"], preselected_role=preselected_role)
L0098 | | Blank line used for readability and logical separation.
L0099 |         login_user(user) | Operational statement participating in the file's runtime behavior.
L0100 |         session.permanent = True | Assignment statement storing or updating program state.
L0101 |         session["role"] = user_role | Assignment statement storing or updating program state.
L0102 | | Blank line used for readability and logical separation.
L0103 |         # Load user settings (theme, language) from database. | Comment line documenting intent or context for nearby code.
L0104 |         from model import UserSettings | Imports specific names from another module for direct usage.
L0105 |         user_settings = db.session.query(UserSettings).filter_by(user_id=user.id).first() | Assignment statement storing or updating program state.
L0106 |         if user_settings: | Conditional branch that runs only when its condition is true.
L0107 |             session["theme"] = user_settings.theme | Assignment statement storing or updating program state.
L0108 |             session["language"] = user_settings.language | Assignment statement storing or updating program state.
```

```

L0109 |         else: | Fallback branch executed when prior conditions are false.
L0110 |             session["theme"] = "light" | Assignment statement storing or updating program state.
L0111 |             session["language"] = "en" | Assignment statement storing or updating program state.
L0112 | | Blank line used for readability and logical separation.
L0113 |             reset_login_failures(email) | Operational statement participating in the file's runtime behavior.
L0114 |             session["login_csrf_token"] = secrets.token_urlsafe(32) | Assignment statement storing or updating program state.
L0115 |             return redirect(url_for("dashboard")) | Returns a value (or control) back to the caller.
L0116 | | Blank line used for readability and logical separation.
L0117 |             register_login_failure(email) | Operational statement participating in the file's runtime behavior.
L0118 |             flash("Invalid credentials", "danger") | Operational statement participating in the file's runtime behavior.
L0119 |             return render_template("login.html", login_csrf_token=session["login_csrf_token"], preselected_role=preselected_role) |
L0120 | | Blank line used for readability and logical separation.
L0121 |             return render_template("login.html", login_csrf_token=login_csrf_token, preselected_role=preselected_role) | Returns a value
L0122 | | Blank line used for readability and logical separation.
L0123 | @app.route("/technician/login") | Decorator line that modifies the behavior of the definition below.
L0124 | @app.route("/technician/login/") | Decorator line that modifies the behavior of the definition below.
L0125 | def technician_login(): | Declares a function/method as a reusable unit of behavior.
L0126 |     if role_lock_enabled and not is_development: | Conditional branch that runs only when its condition is true.
L0127 |         return redirect(url_for("login", role="technician")) | Returns a value (or control) back to the caller.
L0128 |         return redirect(url_for("login")) | Returns a value (or control) back to the caller.
L0129 | | Blank line used for readability and logical separation.
L0130 | @app.route("/staff/login") | Decorator line that modifies the behavior of the definition below.
L0131 | @app.route("/staff/login/") | Decorator line that modifies the behavior of the definition below.
L0132 | def staff_login(): | Declares a function/method as a reusable unit of behavior.
L0133 |     if role_lock_enabled and not is_development: | Conditional branch that runs only when its condition is true.
L0134 |         return redirect(url_for("login", role="staff")) | Returns a value (or control) back to the caller.
L0135 |         return redirect(url_for("login")) | Returns a value (or control) back to the caller.
L0136 | | Blank line used for readability and logical separation.
L0137 | @app.route("/developer/login") | Decorator line that modifies the behavior of the definition below.
L0138 | @app.route("/developer/login/") | Decorator line that modifies the behavior of the definition below.
L0139 | def developer_login(): | Declares a function/method as a reusable unit of behavior.
L0140 |     if role_lock_enabled and not is_development: | Conditional branch that runs only when its condition is true.
L0141 |         return redirect(url_for("login", role="developer")) | Returns a value (or control) back to the caller.
L0142 |         return redirect(url_for("login")) | Returns a value (or control) back to the caller.
L0143 | | Blank line used for readability and logical separation.
L0144 | @app.route("/logout/") | Decorator line that modifies the behavior of the definition below.
L0145 | @login_required | Decorator line that modifies the behavior of the definition below.
L0146 | def logout(): | Declares a function/method as a reusable unit of behavior.
L0147 |     logout_user() | Operational statement participating in the file's runtime behavior.
L0148 |     flash("Logged out", "info") | Operational statement participating in the file's runtime behavior.
L0149 |     return redirect(url_for("login")) | Returns a value (or control) back to the caller.
L0150 | | Blank line used for readability and logical separation.
L0151 | @app.route("/register/", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L0152 | def register(): | Declares a function/method as a reusable unit of behavior.
L0153 |     first_user = user_model.query.count() == 0 | Operational statement participating in the file's runtime behavior.
L0154 |     if not first_user: | Conditional branch that runs only when its condition is true.
L0155 |         if not current_user.is_authenticated or normalize_role(current_user.role) != "developer": | Conditional branch that runs
L0156 |             abort(403) | Operational statement participating in the file's runtime behavior.
L0157 | | Blank line used for readability and logical separation.
L0158 |     if request.method == "POST": | Conditional branch that runs only when its condition is true.
L0159 |         email = (request.form.get("email") or "").strip() | Assignment statement storing or updating program state.
L0160 |         full_name = (request.form.get("full_name") or "").strip() | Assignment statement storing or updating program state.
L0161 |         role = (request.form.get("role") or "technician").strip().lower() | Assignment statement storing or updating program state.
L0162 |         password = request.form.get("password") or "" | Assignment statement storing or updating program state.
L0163 | | Blank line used for readability and logical separation.

```

```

L0164 |         if role not in {"developer", "staff", "technician", "manager", "general_manager"}: | Conditional branch that runs only
L0165 |             flash("Invalid account role selected", "danger") | Operational statement participating in the file's runtime behavior.
L0166 |             return render_template("register.html", first_user=user_model.query.count() == 0) | Returns a value (or control) back to the caller.
L0167 | | Blank line used for readability and logical separation.
L0168 |         if first_user: | Conditional branch that runs only when its condition is true.
L0169 |             role = "developer" | Assignment statement storing or updating program state.
L0170 | | Blank line used for readability and logical separation.
L0171 |         if not email or not password or not full_name: | Conditional branch that runs only when its condition is true.
L0172 |             flash("Fill required fields", "warning") | Operational statement participating in the file's runtime behavior.
L0173 |         else: | Fallback branch executed when prior conditions are false.
L0174 |             if user_model.query.filter_by(email=email).first(): | Conditional branch that runs only when its condition is true.
L0175 |                 flash("Email already exists", "danger") | Operational statement participating in the file's runtime behavior.
L0176 |             else: | Fallback branch executed when prior conditions are false.
L0177 |                 user = user_model() | Assignment statement storing or updating program state.
L0178 |                 email=email, | Assignment statement storing or updating program state.
L0179 |                 full_name=full_name, | Assignment statement storing or updating program state.
L0180 |                 role=role, | Assignment statement storing or updating program state.
L0181 |                 support_desk=request.form.get("support_desk") or None, | Assignment statement storing or updating program state.
L0182 |                 site_operations_phone=request.form.get("site_operations_phone") or None, | Assignment statement storing or updating program state.
L0183 |                 emergency_phone=request.form.get("emergency_phone") or None, | Assignment statement storing or updating program state.
L0184 |                 password_hash=hash_password(password), | Assignment statement storing or updating program state.
L0185 |             ) | Operational statement participating in the file's runtime behavior.
L0186 |             db.session.add(user) | Operational statement participating in the file's runtime behavior.
L0187 |             db.session.commit() | Operational statement participating in the file's runtime behavior.
L0188 |             flash("Account created. Please log in.", "success") | Operational statement participating in the file's runtime behavior.
L0189 |             return redirect(url_for("login")) | Returns a value (or control) back to the caller.
L0190 | | Blank line used for readability and logical separation.
L0191 |         return render_template("register.html", first_user=first_user) | Returns a value (or control) back to the caller.

```

File 47: pm_app/auth/utils.py

```
L0001 | from werkzeug.security import check_password_hash, generate_password_hash | Imports specific names from another module for direct u
L0002 | | Blank line used for readability and logical separation.
L0003 | | Blank line used for readability and logical separation.
L0004 | def hash_password(plain_text: str) -> str: | Declares a function/method as a reusable unit of behavior.
L0005 |     return generate_password_hash(plain_text) | Returns a value (or control) back to the caller.
L0006 | | Blank line used for readability and logical separation.
L0007 | | Blank line used for readability and logical separation.
L0008 | def verify_password(password_hash: str, plain_text: str) -> bool: | Declares a function/method as a reusable unit of behavior.
L0009 |     return check_password_hash(password_hash, plain_text) | Returns a value (or control) back to the caller.
```

File 48: pm_app/dashboards/__init__.py

L0001 | # Dashboards module | Comment line documenting intent or context for nearby code.

File 49: pm_app/dashboards/routes.py

```
L0001 | """Dashboard routes module.""" | Docstring boundary used to describe a module, class, or function.
L0002 | from flask import abort, render_template, redirect, url_for, request, flash, jsonify, session | Imports specific names from another
L0003 | from flask_login import login_required, current_user | Imports specific names from another module for direct usage.
L0004 | | Blank line used for readability and logical separation.
L0005 | from pm_app.services.time_utils import utcnow_naive | Imports specific names from another module for direct usage.
L0006 | | Blank line used for readability and logical separation.
L0007 | | Blank line used for readability and logical separation.
L0008 | def register_dashboard_routes(app, *, user_model, activity_model, message_model, db, normalize_role, is_technician_role, get_live_c
L0009 |     """Register dashboard-related routes with the app. | Docstring boundary used to describe a module, class, or function.
L0010 | | Blank line used for readability and logical separation.
L0011 |     Dependencies: | Operational statement participating in the file's runtime behavior.
L0012 |     - user_model: User model class | Operational statement participating in the file's runtime behavior.
L0013 |     - activity_model: Activity model class | Operational statement participating in the file's runtime behavior.
L0014 |     - message_model: Message model class | Operational statement participating in the file's runtime behavior.
L0015 |     - db: SQLAlchemy database session | Operational statement participating in the file's runtime behavior.
L0016 |     - normalize_role: function to normalize role names | Operational statement participating in the file's runtime behavior.
L0017 |     - is_technician_role: function to check if role is technician | Operational statement participating in the file's runtime behav
L0018 |     - get_live_dashboard_counts: function to compute dashboard stats | Operational statement participating in the file's runtime be
L0019 |     - calculate_notification_count: function to count unread notifications | Operational statement participating in the file's runt
L0020 |     """ | Docstring boundary used to describe a module, class, or function.
L0021 | | Blank line used for readability and logical separation.
L0022 |     @app.route("/dashboard/") | Decorator line that modifies the behavior of the definition below.
L0023 |     @login_required | Decorator line that modifies the behavior of the definition below.
L0024 |     def dashboard(): | Declares a function/method as a reusable unit of behavior.
L0025 |         live_counts = get_live_dashboard_counts() | Assignment statement storing or updating program state.
L0026 |         active_sla_policy = get_active_sla_policy() | Assignment statement storing or updating program state.
L0027 |         dashboard_counts = { | Assignment statement storing or updating program state.
L0028 |             "users_total": live_counts["users_total"], | Operational statement participating in the file's runtime behavior.
L0029 |             "blocked_users": live_counts["blocked_users"], | Operational statement participating in the file's runtime behavior.
L0030 |             "technician_users": live_counts["technician_users"], | Operational statement participating in the file's runtime behavi
L0031 |             "staff_users": live_counts["staff_users"], | Operational statement participating in the file's runtime behavior.
L0032 |             "manager_users": live_counts["manager_users"], | Operational statement participating in the file's runtime behavior.
L0033 |             "general_manager_users": live_counts["general_manager_users"], | Operational statement participating in the file's runt
L0034 |         } | Block delimiter controlling scope/structure in this language.
L0035 | | Blank line used for readability and logical separation.
L0036 |         if is_technician_role(current_user.role): | Conditional branch that runs only when its condition is true.
L0037 |             recent_submissions = ( | Assignment statement storing or updating program state.
L0038 |                 activity_model.query.filter( | Operational statement participating in the file's runtime behavior.
L0039 |                     activity_model.activity_type.in(["pm", "rca"]), | Operational statement participating in the file's runtime be
L0040 |                     activity_model.created_by == current_user.email, | Operational statement participating in the file's runtime be
L0041 |                 ) | Operational statement participating in the file's runtime behavior.
L0042 |                 .order_by(activity_model.created_at.desc()) | CSS selector line choosing the elements styled below.
L0043 |                 .limit(8) | CSS selector line choosing the elements styled below.
L0044 |                 .all() | CSS selector line choosing the elements styled below.
L0045 |             ) | Operational statement participating in the file's runtime behavior.
L0046 |             return render_template( | Returns a value (or control) back to the caller.
L0047 |                 "technician_dashboard.html", | Operational statement participating in the file's runtime behavior.
L0048 |                 user_name=current_user.display_name, | Assignment statement storing or updating program state.
L0049 |                 technician_stats={ | Assignment statement storing or updating program state.
L0050 |                     "pm": live_counts["technician_pm"], | Operational statement participating in the file's runtime behavior.
L0051 |                     "rca": live_counts["technician_rca"], | Operational statement participating in the file's runtime behavior.
L0052 |                     "total": live_counts["technician_total"], | Operational statement participating in the file's runtime behavior.
L0053 |                     "rejected": live_counts["technician_rejected"], | Operational statement participating in the file's runtime beh
```

```

L0054 |         }, | Operational statement participating in the file's runtime behavior.
L0055 |         recent_submissions=recent_submissions, | Assignment statement storing or updating program state.
L0056 |     ) | Operational statement participating in the file's runtime behavior.
L0057 | | Blank line used for readability and logical separation.
L0058 |     consumables_count = live_counts["consumables_count"] | Assignment statement storing or updating program state.
L0059 |     total_rcas = live_counts["total_rcas"] | Assignment statement storing or updating program state.
L0060 |     total_rcas_pending = activity_model.query.filter_by(activity_type="rca", is_approved=False).count() | Assignment statement
L0061 |     total_rcas_approved = activity_model.query.filter_by(activity_type="rca", is_approved=True).count() | Assignment statement
L0062 |     total_snags = live_counts["total_snags"] | Assignment statement storing or updating program state.
L0063 |     total_dars = live_counts["total_dars"] | Assignment statement storing or updating program state.
L0064 |     total_pms = live_counts["total_pms"] | Assignment statement storing or updating program state.
L0065 | | Blank line used for readability and logical separation.
L0066 |     recent_activity = activity_model.query.order_by(activity_model.created_at.desc()).limit(10).all() | Assignment statement st
L0067 |     pending_pm_rcas = live_counts["pending_pm_rcas"] | Assignment statement storing or updating program state.
L0068 |     high_risk_pending_pm_rcas = live_counts["high_risk_pending_pm_rcas"] | Assignment statement storing or updating program sta
L0069 |     sla_overdue_pm_rcas = live_counts["sla_overdue_pm_rcas"] | Assignment statement storing or updating program state.
L0070 |     approved_pm_forms = live_counts["approved_pm_forms"] | Assignment statement storing or updating program state.
L0071 |     rejected_pm_rcas = live_counts["rejected_pm_rcas"] | Assignment statement storing or updating program state.
L0072 | | Blank line used for readability and logical separation.
L0073 |     # Import here to avoid circular dependency | Comment line documenting intent or context for nearby code.
L0074 |     from app import get_public_base_url, is_public_share_base | Imports specific names from another module for direct usage.
L0075 | | Blank line used for readability and logical separation.
L0076 |     public_base = get_public_base_url() | Assignment statement storing or updating program state.
L0077 |     technician_login_url = public_base + url_for("technician_login") | Assignment statement storing or updating program state.
L0078 |     share_link_is_public = is_public_share_base(public_base) | Assignment statement storing or updating program state.
L0079 | | Blank line used for readability and logical separation.
L0080 |     current_role = normalize_role(current_user.role) | Assignment statement storing or updating program state.
L0081 |     if current_role == "staff": | Conditional branch that runs only when its condition is true.
L0082 |         return render_template( | Returns a value (or control) back to the caller.
L0083 |             "staff_dashboard.html", | Operational statement participating in the file's runtime behavior.
L0084 |             user_name=current_user.display_name, | Assignment statement storing or updating program state.
L0085 |             pending_pm_rcas=pending_pm_rcas, | Assignment statement storing or updating program state.
L0086 |             high_risk_pending_pm_rcas=high_risk_pending_pm_rcas, | Assignment statement storing or updating program state.
L0087 |             sla_overdue_pm_rcas=sla_overdue_pm_rcas, | Assignment statement storing or updating program state.
L0088 |             approved_pm_forms=approved_pm_forms, | Assignment statement storing or updating program state.
L0089 |             rejected_pm_rcas=rejected_pm_rcas, | Assignment statement storing or updating program state.
L0090 |             staff_has_form_data=(pending_pm_rcas + approved_pm_forms + rejected_pm_rcas) > 0, | Assignment statement storing or
L0091 |             active_sla_policy=active_sla_policy, | Assignment statement storing or updating program state.
L0092 |         ) | Operational statement participating in the file's runtime behavior.
L0093 | | Blank line used for readability and logical separation.
L0094 |     if current_role in {"manager", "general_manager"}: | Conditional branch that runs only when its condition is true.
L0095 |         return render_template( | Returns a value (or control) back to the caller.
L0096 |             "manager_dashboard.html", | Operational statement participating in the file's runtime behavior.
L0097 |             user_name=current_user.display_name, | Assignment statement storing or updating program state.
L0098 |             pending_pm_rcas=pending_pm_rcas, | Assignment statement storing or updating program state.
L0099 |             high_risk_pending_pm_rcas=high_risk_pending_pm_rcas, | Assignment statement storing or updating program state.
L0100 |             sla_overdue_pm_rcas=sla_overdue_pm_rcas, | Assignment statement storing or updating program state.
L0101 |             approved_pm_forms=approved_pm_forms, | Assignment statement storing or updating program state.
L0102 |             rejected_pm_rcas=rejected_pm_rcas, | Assignment statement storing or updating program state.
L0103 |             staff_has_form_data=(pending_pm_rcas + approved_pm_forms + rejected_pm_rcas) > 0, | Assignment statement storing or
L0104 |             active_sla_policy=active_sla_policy, | Assignment statement storing or updating program state.
L0105 |         ) | Operational statement participating in the file's runtime behavior.
L0106 | | Blank line used for readability and logical separation.
L0107 |     if current_role == "developer": | Conditional branch that runs only when its condition is true.
L0108 |         return render_template( | Returns a value (or control) back to the caller.

```

```

L0109 |         "developer_role_dashboard.html", | Operational statement participating in the file's runtime behavior.
L0110 |         user_name=current_user.display_name, | Assignment statement storing or updating program state.
L0111 |         dashboard_counts=dashboard_counts, | Assignment statement storing or updating program state.
L0112 |         technician_login_url=technician_login_url, | Assignment statement storing or updating program state.
L0113 |         share_link_is_public=share_link_is_public, | Assignment statement storing or updating program state.
L0114 |     ) | Operational statement participating in the file's runtime behavior.
L0115 | | Blank line used for readability and logical separation.
L0116 |     return render_template( | Returns a value (or control) back to the caller.
L0117 |         "dashboard.html", | Operational statement participating in the file's runtime behavior.
L0118 |         user_name=current_user.display_name, | Assignment statement storing or updating program state.
L0119 |         stats={ | Assignment statement storing or updating program state.
L0120 |             "consumables": consumables_count, | Operational statement participating in the file's runtime behavior.
L0121 |             "rcas": total_rcas, | Operational statement participating in the file's runtime behavior.
L0122 |             "rcas_pending": total_rcas_pending, | Operational statement participating in the file's runtime behavior.
L0123 |             "rcas_approved": total_rcas_approved, | Operational statement participating in the file's runtime behavior.
L0124 |             "snags": total_snags, | Operational statement participating in the file's runtime behavior.
L0125 |             "dars": total_dars, | Operational statement participating in the file's runtime behavior.
L0126 |             "pms": total_pms, | Operational statement participating in the file's runtime behavior.
L0127 |         }, | Operational statement participating in the file's runtime behavior.
L0128 |         recent_activity=recent_activity, | Assignment statement storing or updating program state.
L0129 |         pending_pm_rcas=pending_pm_rcas, | Assignment statement storing or updating program state.
L0130 |         high_risk_pending_pm_rcas=high_risk_pending_pm_rcas, | Assignment statement storing or updating program state.
L0131 |         sla_overdue_pm_rcas=sla_overdue_pm_rcas, | Assignment statement storing or updating program state.
L0132 |         approved_pm_forms=approved_pm_forms, | Assignment statement storing or updating program state.
L0133 |         rejected_pm_rcas=rejected_pm_rcas, | Assignment statement storing or updating program state.
L0134 |         staff_has_form_data=(pending_pm_rcas + approved_pm_forms + rejected_pm_rcas) > 0, | Assignment statement storing or updating program state.
L0135 |         dashboard_counts=dashboard_counts, | Assignment statement storing or updating program state.
L0136 |         is_technician=False, | Assignment statement storing or updating program state.
L0137 |         technician_login_url=technician_login_url, | Assignment statement storing or updating program state.
L0138 |         share_link_is_public=share_link_is_public, | Assignment statement storing or updating program state.
L0139 |     ) | Operational statement participating in the file's runtime behavior.
L0140 | | Blank line used for readability and logical separation.
L0141 | @app.route("/api/dashboard-counts") | Decorator line that modifies the behavior of the definition below.
L0142 | @login_required | Decorator line that modifies the behavior of the definition below.
L0143 | def dashboard_counts_api(): | Declares a function/method as a reusable unit of behavior.
L0144 |     return jsonify({"counts": get_live_dashboard_counts(), "generated_at": utcnow_naive().isoformat(timespec="seconds")}) | Return statement
L0145 | | Blank line used for readability and logical separation.
L0146 | @app.route("/activities/") | Decorator line that modifies the behavior of the definition below.
L0147 | @login_required | Decorator line that modifies the behavior of the definition below.
L0148 | def activities(): | Declares a function/method as a reusable unit of behavior.
L0149 |     activity_type = request.args.get('type') | Assignment statement storing or updating program state.
L0150 |     q = activity_model.query | Assignment statement storing or updating program state.
L0151 |     if activity_type: | Conditional branch that runs only when its condition is true.
L0152 |         q = q.filter_by(activity_type=activity_type) | Assignment statement storing or updating program state.
L0153 |     items = q.order_by(activity_model.created_at.desc()).all() | Assignment statement storing or updating program state.
L0154 |     return render_template("activities.html", activities=items, activity_type=activity_type, is_technician=is_technician_role(c
L0155 | | Blank line used for readability and logical separation.
L0156 | @app.route("/notifications/") | Decorator line that modifies the behavior of the definition below.
L0157 | @login_required | Decorator line that modifies the behavior of the definition below.
L0158 | def notifications(): | Declares a function/method as a reusable unit of behavior.
L0159 |     session["notifications_last_seen_at"] = utcnow_naive().isoformat(timespec="seconds") | Assignment statement storing or updating program state.
L0160 |     from model import UserSettings | Imports specific names from another module for direct usage.
L0161 | | Blank line used for readability and logical separation.
L0162 |     current_role = normalize_role(current_user.role) | Assignment statement storing or updating program state.
L0163 |     inbox_roles = {current_role, "all"} | Assignment statement storing or updating program state.

```



```

L0164 |         items = activity_model.query.order_by(activity_model.created_at.desc()).limit(80).all() | Assignment statement storing or updating program state.
L0165 |         user_settings = db.session.query(UserSettings).filter_by(user_id=current_user.id).first() | Assignment statement storing or updating program state.
L0166 |         hidden_ids = set() | Assignment statement storing or updating program state.
L0167 |         if user_settings: | Conditional branch that runs only when its condition is true.
L0168 |             prefs = user_settings.get_preferences() | Assignment statement storing or updating program state.
L0169 |             raw_hidden = prefs.get("hidden_message_ids", []) if isinstance(prefs, dict) else [] | Assignment statement storing or updating program state.
L0170 |             if isinstance(raw_hidden, list): | Conditional branch that runs only when its condition is true.
L0171 |                 for value in raw_hidden: | Loop iterating over a sequence to process elements one by one.
L0172 |                     try: | Starts an exception handling block for risky operations.
L0173 |                         hidden_ids.add(int(value)) | Operational statement participating in the file's runtime behavior.
L0174 |                     except (TypeError, ValueError): | Handles errors raised in the associated try block.
L0175 |                         continue | Flow-control keyword affecting execution in the current block.
L0176 | | Blank line used for readability and logical separation.
L0177 |         messages_query = message_model.query.filter( | Assignment statement storing or updating program state.
L0178 |             (message_model.recipient_role.in_(inbox_roles)) | Operational statement participating in the file's runtime behavior.
L0179 |             \ | (message_model.recipient_email == current_user.email) | Operational statement participating in the file's runtime behavior.
L0180 |             \ | (message_model.sender_email == current_user.email) | Operational statement participating in the file's runtime behavior.
L0181 |         ) | Operational statement participating in the file's runtime behavior.
L0182 |         if hidden_ids: | Conditional branch that runs only when its condition is true.
L0183 |             messages_query = messages_query.filter(~message_model.id.in_(hidden_ids)) | Assignment statement storing or updating program state.
L0184 | | Blank line used for readability and logical separation.
L0185 |         messages = messages_query.order_by(message_model.created_at.desc()).limit(80).all() | Assignment statement storing or updating program state.
L0186 | | Blank line used for readability and logical separation.
L0187 |         recipient_options_by_role = { | Assignment statement storing or updating program state.
L0188 |             "technician": ["staff", "developer", "manager"], | Operational statement participating in the file's runtime behavior.
L0189 |         } | Block delimiter controlling scope/structure in this language.
L0190 |         default_options = ["all", "developer", "staff", "technician", "manager", "general_manager"] | Assignment statement storing or updating program state.
L0191 |         recipient_options = recipient_options_by_role.get(current_role, default_options) | Assignment statement storing or updating program state.
L0192 | | Blank line used for readability and logical separation.
L0193 |         return render_template( | Returns a value (or control) back to the caller.
L0194 |             "notifications.html", | Operational statement participating in the file's runtime behavior.
L0195 |             activities=items, | Assignment statement storing or updating program state.
L0196 |             messages=messages, | Assignment statement storing or updating program state.
L0197 |             recipient_options=recipient_options, | Assignment statement storing or updating program state.
L0198 |         ) | Operational statement participating in the file's runtime behavior.
L0199 | | Blank line used for readability and logical separation.
L0200 |     @app.route("/notifications/messages/send", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L0201 |     @login_required | Decorator line that modifies the behavior of the definition below.
L0202 |     def send_system_message(): | Declares a function/method as a reusable unit of behavior.
L0203 |         if request.method == "GET": | Conditional branch that runs only when its condition is true.
L0204 |             return redirect(url_for("notifications")) | Returns a value (or control) back to the caller.
L0205 | | Blank line used for readability and logical separation.
L0206 |         recipient_role = (request.form.get("recipient_role") or "all").strip().lower() | Assignment statement storing or updating program state.
L0207 |         body = (request.form.get("message_body") or "").strip() | Assignment statement storing or updating program state.
L0208 |         current_role = normalize_role(current_user.role) | Assignment statement storing or updating program state.
L0209 | | Blank line used for readability and logical separation.
L0210 |         allowed_roles_by_sender = { | Assignment statement storing or updating program state.
L0211 |             "technician": {"staff", "developer", "manager"}, | Operational statement participating in the file's runtime behavior.
L0212 |         } | Block delimiter controlling scope/structure in this language.
L0213 |         default_allowed_roles = {"all", "developer", "manager", "general_manager", "staff", "technician"} | Assignment statement storing or updating program state.
L0214 |         allowed_roles = allowed_roles_by_sender.get(current_role, default_allowed_roles) | Assignment statement storing or updating program state.
L0215 | | Blank line used for readability and logical separation.
L0216 |         if recipient_role not in allowed_roles: | Conditional branch that runs only when its condition is true.
L0217 |             flash("Invalid recipient role selected.", "warning") | Operational statement participating in the file's runtime behavior.
L0218 |             return redirect(url_for("notifications")) | Returns a value (or control) back to the caller.

```

```

L0219 |         if not body: | Conditional branch that runs only when its condition is true.
L0220 |             flash("Message body is required.", "warning") | Operational statement participating in the file's runtime behavior.
L0221 |             return redirect(url_for("notifications")) | Returns a value (or control) back to the caller.
L0222 | | Blank line used for readability and logical separation.
L0223 |         message = message_model( | Assignment statement storing or updating program state.
L0224 |             sender_email=current_user.email, | Assignment statement storing or updating program state.
L0225 |             sender_role=current_role, | Assignment statement storing or updating program state.
L0226 |             recipient_role=recipient_role, | Assignment statement storing or updating program state.
L0227 |             recipient_email=None, | Assignment statement storing or updating program state.
L0228 |             body=body, | Assignment statement storing or updating program state.
L0229 |             created_at=utcnow_naive(), | Assignment statement storing or updating program state.
L0230 |         ) | Operational statement participating in the file's runtime behavior.
L0231 |         db.session.add(message) | Operational statement participating in the file's runtime behavior.
L0232 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0233 | | Blank line used for readability and logical separation.
L0234 |         create_activity("message", f"{current_user.email} sent a message to {recipient_role}") | Operational statement participating in the file's runtime behavior.
L0235 |         flash("Message sent successfully.", "success") | Operational statement participating in the file's runtime behavior.
L0236 |         return redirect(url_for("notifications")) | Returns a value (or control) back to the caller.
L0237 | | Blank line used for readability and logical separation.
L0238 |     @app.route("/notifications/messages/<int:message_id>/delete", methods=["POST"]) | Decorator line that modifies the behavior of
L0239 |     @login_required | Decorator line that modifies the behavior of the definition below.
L0240 |     def delete_system_message(message_id): | Declares a function/method as a reusable unit of behavior.
L0241 |         current_role = normalize_role(current_user.role) | Assignment statement storing or updating program state.
L0242 |         message = db.session.get(message_model, message_id) | Assignment statement storing or updating program state.
L0243 |         if message is None: | Conditional branch that runs only when its condition is true.
L0244 |             abort(404) | Operational statement participating in the file's runtime behavior.
L0245 | | Blank line used for readability and logical separation.
L0246 |         is_sender = message.sender_email == current_user.email | Operational statement participating in the file's runtime behavior.
L0247 |         is_developer = current_role == "developer" | Operational statement participating in the file's runtime behavior.
L0248 | | Blank line used for readability and logical separation.
L0249 |         if not is_sender and not is_developer: | Conditional branch that runs only when its condition is true.
L0250 |             flash("You can only delete your own messages.", "warning") | Operational statement participating in the file's runtime behavior.
L0251 |             return redirect(url_for("notifications")) | Returns a value (or control) back to the caller.
L0252 | | Blank line used for readability and logical separation.
L0253 |         db.session.delete(message) | Operational statement participating in the file's runtime behavior.
L0254 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0255 |         create_activity("message", f"{current_user.email} deleted message #{message_id}") | Operational statement participating in the file's runtime behavior.
L0256 |         flash("Message deleted.", "success") | Operational statement participating in the file's runtime behavior.
L0257 |         return redirect(url_for("notifications")) | Returns a value (or control) back to the caller.
L0258 | | Blank line used for readability and logical separation.
L0259 |     @app.route("/settings/", methods=["GET", "POST"]) | Decorator line that modifies the behavior of the definition below.
L0260 |     @login_required | Decorator line that modifies the behavior of the definition below.
L0261 |     def settings_page(): | Declares a function/method as a reusable unit of behavior.
L0262 |         # Import here to avoid circular dependency | Comment line documenting intent or context for nearby code.
L0263 |         from model import UserSettings | Imports specific names from another module for direct usage.
L0264 |         current_role = normalize_role(current_user.role) | Assignment statement storing or updating program state.
L0265 |         can_manage_sla = current_role in {"staff", "manager", "general_manager", "developer"} | Assignment statement storing or updating program state.
L0266 |         active_sla_policy = get_active_sla_policy() | Assignment statement storing or updating program state.
L0267 |         user_settings = db.session.query(UserSettings).filter_by(user_id=current_user.id).first() | Assignment statement storing or updating program state.
L0268 |         current_preferences = user_settings.get_preferences() if user_settings else {} | Assignment statement storing or updating program state.
L0269 |         current_sla_policy = current_preferences.get("sla_policy") if isinstance(current_preferences, dict) else None | Assignment statement storing or updating program state.
L0270 |         if not isinstance(current_sla_policy, dict): | Conditional branch that runs only when its condition is true.
L0271 |             current_sla_policy = active_sla_policy.copy() | Assignment statement storing or updating program state.
L0272 | | Blank line used for readability and logical separation.
L0273 |         if request.method == "POST": | Conditional branch that runs only when its condition is true.

```

```

L0274 |         language = (request.form.get("language") or "en").strip().lower() | Assignment statement storing or updating program state
L0275 |         theme = (request.form.get("theme") or "light").strip().lower() | Assignment statement storing or updating program state
L0276 | | Blank line used for readability and logical separation.
L0277 |         allowed_languages = {"en", "sw", "fr", "ar"} | Assignment statement storing or updating program state.
L0278 |         allowed_themes = {"light", "dark"} | Assignment statement storing or updating program state.
L0279 | | Blank line used for readability and logical separation.
L0280 |         # Validate and save to database | Comment line documenting intent or context for nearby code.
L0281 |         if language in allowed_languages: | Conditional branch that runs only when its condition is true.
L0282 |             session["language"] = language | Assignment statement storing or updating program state.
L0283 |         if theme in allowed_themes: | Conditional branch that runs only when its condition is true.
L0284 |             session["theme"] = theme | Assignment statement storing or updating program state.
L0285 | | Blank line used for readability and logical separation.
L0286 |         # Persist to UserSettings table | Comment line documenting intent or context for nearby code.
L0287 |         if not user_settings: | Conditional branch that runs only when its condition is true.
L0288 |             user_settings = UserSettings(user_id=current_user.id) | Assignment statement storing or updating program state.
L0289 |             db.session.add(user_settings) | Operational statement participating in the file's runtime behavior.
L0290 | | Blank line used for readability and logical separation.
L0291 |         if language in allowed_languages: | Conditional branch that runs only when its condition is true.
L0292 |             user_settings.language = language | Assignment statement storing or updating program state.
L0293 |         if theme in allowed_themes: | Conditional branch that runs only when its condition is true.
L0294 |             user_settings.theme = theme | Assignment statement storing or updating program state.
L0295 | | Blank line used for readability and logical separation.
L0296 |         if can_manage_sla and (request.form.get("save_section") or "") == "sla_policy": | Conditional branch that runs only when
L0297 |             sla_enabled = (request.form.get("sla_enabled") or "inactive").strip().lower() == "active" | Operational statement participating in the file's runtime behavior.
L0298 |             policy_agreed = bool(request.form.get("sla_policy_agreed")) | Assignment statement storing or updating program state
L0299 | | Blank line used for readability and logical separation.
L0300 |         try: | Starts an exception handling block for risky operations.
L0301 |             standard_hours = int(request.form.get("sla_standard_hours") or active_sla_policy["standard_hours"]) | Assignment statement storing or updating program state.
L0302 |             critical_hours = int(request.form.get("sla_critical_hours") or active_sla_policy["critical_hours"]) | Assignment statement storing or updating program state.
L0303 |             due_soon_hours = int(request.form.get("sla_due_soon_hours") or active_sla_policy["due_soon_hours"]) | Assignment statement storing or updating program state.
L0304 |         except ValueError: | Handles errors raised in the associated try block.
L0305 |             flash("SLA hours must be valid whole numbers.", "warning") | Operational statement participating in the file's runtime behavior.
L0306 |             return redirect(url_for("settings_page")) | Returns a value (or control) back to the caller.
L0307 | | Blank line used for readability and logical separation.
L0308 |         if standard_hours < 1 or standard_hours > 168 or critical_hours < 1 or critical_hours > 168: | Conditional branch that runs only when its condition is true.
L0309 |             flash("SLA review hours must stay between 1 and 168 hours.", "warning") | Operational statement participating in the file's runtime behavior.
L0310 |             return redirect(url_for("settings_page")) | Returns a value (or control) back to the caller.
L0311 |         if due_soon_hours < 1 or due_soon_hours > min(72, standard_hours, critical_hours): | Conditional branch that runs only when its condition is true.
L0312 |             flash("Due soon hours must be at least 1 and no greater than the active SLA windows.", "warning") | Operational statement participating in the file's runtime behavior.
L0313 |             return redirect(url_for("settings_page")) | Returns a value (or control) back to the caller.
L0314 |         if not policy_agreed: | Conditional branch that runs only when its condition is true.
L0315 |             flash("You must agree to the SLA policy before saving it.", "warning") | Operational statement participating in the file's runtime behavior.
L0316 |             return redirect(url_for("settings_page")) | Returns a value (or control) back to the caller.
L0317 | | Blank line used for readability and logical separation.
L0318 |         preferences = user_settings.get_preferences() | Assignment statement storing or updating program state.
L0319 |         preferences["sla_policy"] = { | Assignment statement storing or updating program state.
L0320 |             "enabled": sla_enabled, | Operational statement participating in the file's runtime behavior.
L0321 |             "standard_hours": standard_hours, | Operational statement participating in the file's runtime behavior.
L0322 |             "critical_hours": critical_hours, | Operational statement participating in the file's runtime behavior.
L0323 |             "due_soon_hours": due_soon_hours, | Operational statement participating in the file's runtime behavior.
L0324 |             "policy_agreed": True, | Operational statement participating in the file's runtime behavior.
L0325 |             "updated_at": utcnow_naive().isoformat(timespec="seconds"), | Assignment statement storing or updating program state.
L0326 |             "updated_by": current_user.display_name or current_user.email, | Operational statement participating in the file's runtime behavior.
L0327 |             "updated_role": current_role, | Operational statement participating in the file's runtime behavior.
L0328 |             "source": "saved", | Operational statement participating in the file's runtime behavior.

```

```
L0329 |         } | Block delimiter controlling scope/structure in this language.
L0330 |         user_settings.set_preferences(preferences) | Operational statement participating in the file's runtime behavior.
L0331 | | Blank line used for readability and logical separation.
L0332 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0333 | | Blank line used for readability and logical separation.
L0334 |         flash("Settings updated", "success") | Operational statement participating in the file's runtime behavior.
L0335 |         return redirect(url_for("settings_page")) | Returns a value (or control) back to the caller.
L0336 | | Blank line used for readability and logical separation.
L0337 |         # Load settings from database for GET request | Comment line documenting intent or context for nearby code.
L0338 |         if user_settings: | Conditional branch that runs only when its condition is true.
L0339 |             session["language"] = user_settings.language | Assignment statement storing or updating program state.
L0340 |             session["theme"] = user_settings.theme | Assignment statement storing or updating program state.
L0341 | | Blank line used for readability and logical separation.
L0342 |         return render_template( | Returns a value (or control) back to the caller.
L0343 |             "settings.html", | Operational statement participating in the file's runtime behavior.
L0344 |             active_sla_policy=active_sla_policy, | Assignment statement storing or updating program state.
L0345 |             current_sla_policy=current_sla_policy, | Assignment statement storing or updating program state.
L0346 |             can_manage_sla=can_manage_sla, | Assignment statement storing or updating program state.
L0347 |         ) | Operational statement participating in the file's runtime behavior.
```

File 50: pm_app/services/__init__.py

File 51: pm_app/services/database.py

L0001 | """Database service helper placeholder module for extracted query helpers.""" | Docstring boundary used to describe a module, class

File 52: pm_app/services/email.py

```
L0001 | import os | Imports dependency modules: os.
L0002 | import smtplib | Imports dependency modules: smtplib.
L0003 | from email.mime.multipart import MIMEMultipart | Imports specific names from another module for direct usage.
L0004 | from email.mime.text import MIMEText | Imports specific names from another module for direct usage.
L0005 | | Blank line used for readability and logical separation.
L0006 | | Blank line used for readability and logical separation.
L0007 | def send_alert(message: str, subject: str = "System Alert") -> bool: | Declares a function/method as a reusable unit of behavior.
L0008 |     email_address = os.getenv("ALERT_EMAIL_ADDRESS", "") | Assignment statement storing or updating program state.
L0009 |     email_password = os.getenv("ALERT_EMAIL_PASSWORD", "") | Assignment statement storing or updating program state.
L0010 |     if not email_address or not email_password: | Conditional branch that runs only when its condition is true.
L0011 |         return False | Returns a value (or control) back to the caller.
L0012 | | Blank line used for readability and logical separation.
L0013 |     try: | Starts an exception handling block for risky operations.
L0014 |         msg = MIMEMultipart() | Assignment statement storing or updating program state.
L0015 |         msg["From"] = email_address | Assignment statement storing or updating program state.
L0016 |         msg["To"] = email_address | Assignment statement storing or updating program state.
L0017 |         msg["Subject"] = subject | Assignment statement storing or updating program state.
L0018 |         msg.attach(MIMEText(message, "plain")) | Operational statement participating in the file's runtime behavior.
L0019 | | Blank line used for readability and logical separation.
L0020 |         with smtplib.SMTP_SSL("smtp.gmail.com", 465) as server: | Context manager block for safe setup and automatic cleanup.
L0021 |             server.login(email_address, email_password) | Operational statement participating in the file's runtime behavior.
L0022 |             server.send_message(msg) | Operational statement participating in the file's runtime behavior.
L0023 |             return True | Returns a value (or control) back to the caller.
L0024 |     except Exception: | Handles errors raised in the associated try block.
L0025 |         return False | Returns a value (or control) back to the caller.
```

File 53: pm_app/services/maintenance.py

```
L0001 | from __future__ import annotations | Imports specific names from another module for direct usage.
L0002 | | Blank line used for readability and logical separation.
L0003 | from dataclasses import dataclass | Imports specific names from another module for direct usage.
L0004 | from datetime import datetime, timedelta | Imports specific names from another module for direct usage.
L0005 | from typing import Callable | Imports specific names from another module for direct usage.
L0006 | import time as _time | Imports dependency modules: time as _time.
L0007 | | Blank line used for readability and logical separation.
L0008 | | Blank line used for readability and logical separation.
L0009 | @dataclass | Decorator line that modifies the behavior of the definition below.
L0010 | class MaintenanceSummary: | Declares a class that groups related state and behavior.
L0011 |     holiday_created: int = 0 | Assignment statement storing or updating program state.
L0012 |     sla_escalations: int = 0 | Assignment statement storing or updating program state.
L0013 | | Blank line used for readability and logical separation.
L0014 |     def as_dict(self) -> dict[str, int]: | Declares a function/method as a reusable unit of behavior.
L0015 |         return { | Returns a value (or control) back to the caller.
L0016 |             "holiday_created": self.holiday_created, | Operational statement participating in the file's runtime behavior.
L0017 |             "sla_escalations": self.sla_escalations, | Operational statement participating in the file's runtime behavior.
L0018 |         } | Block delimiter controlling scope/structure in this language.
L0019 | | Blank line used for readability and logical separation.
L0020 | | Blank line used for readability and logical separation.
L0021 | class MaintenanceService: | Declares a class that groups related state and behavior.
L0022 |     def __init__( | Declares a function/method as a reusable unit of behavior.
L0023 |         self, | Operational statement participating in the file's runtime behavior.
L0024 |         *, | Operational statement participating in the file's runtime behavior.
L0025 |         db, | Operational statement participating in the file's runtime behavior.
L0026 |         activity_model, | Operational statement participating in the file's runtime behavior.
L0027 |         message_model, | Operational statement participating in the file's runtime behavior.
L0028 |         user_model, | Operational statement participating in the file's runtime behavior.
L0029 |         create_activity: Callable[[str, str], None], | Operational statement participating in the file's runtime behavior.
L0030 |         get_public_holidays: Callable[[], list[dict]], | Operational statement participating in the file's runtime behavior.
L0031 |         utcnow_naive: Callable[[], datetime], | Operational statement participating in the file's runtime behavior.
L0032 |         high_risk_threshold: int, | Operational statement participating in the file's runtime behavior.
L0033 |         sla_scan_cooldown_seconds: int, | Operational statement participating in the file's runtime behavior.
L0034 |     ): | Operational statement participating in the file's runtime behavior.
L0035 |         self.db = db | Assignment statement storing or updating program state.
L0036 |         self.activity_model = activity_model | Assignment statement storing or updating program state.
L0037 |         self.message_model = message_model | Assignment statement storing or updating program state.
L0038 |         self.user_model = user_model | Assignment statement storing or updating program state.
L0039 |         self.create_activity = create_activity | Assignment statement storing or updating program state.
L0040 |         self.get_public_holidays = get_public_holidays | Assignment statement storing or updating program state.
L0041 |         self.utcnow_naive = utcnow_naive | Assignment statement storing or updating program state.
L0042 |         self.high_risk_threshold = high_risk_threshold | Assignment statement storing or updating program state.
L0043 |         self.sla_scan_cooldown_seconds = int(sla_scan_cooldown_seconds) | Assignment statement storing or updating program state.
L0044 |         self._last_sla_scan_at = 0.0 | Assignment statement storing or updating program state.
L0045 | | Blank line used for readability and logical separation.
L0046 |     def run_all(self, *, respect_cooldown: bool = True) -> MaintenanceSummary: | Declares a function/method as a reusable unit of b
L0047 |         summary = MaintenanceSummary() | Assignment statement storing or updating program state.
L0048 |         summary.holiday_created += self.ensure_public_holiday_greeting_message() | Assignment statement storing or updating program
L0049 |         summary.sla_escalations += self.ensure_sla_escalations(respect_cooldown=respect_cooldown) | Assignment statement storing or
L0050 |         return summary | Returns a value (or control) back to the caller.
L0051 | | Blank line used for readability and logical separation.
L0052 |     def ensure_sla_escalations(self, *, respect_cooldown: bool = True) -> int: | Declares a function/method as a reusable unit of b
L0053 |         now_epoch = _time.time() | Assignment statement storing or updating program state.
```



```

L0054 |         if respect_cooldown and (now_epoch - self._last_sla_scan_at) < self.sla_scan_cooldown_seconds: | Conditional branch that ru
L0055 |             return 0 | Returns a value (or control) back to the caller.
L0056 |         self._last_sla_scan_at = now_epoch | Assignment statement storing or updating program state.
L0057 | | Blank line used for readability and logical separation.
L0058 |         now = self.utcnow_naive() | Assignment statement storing or updating program state.
L0059 |         technician_emails_query = self.db.session.query(self.user_model.email).filter(self.user_model.role == "technician") | Opera
L0060 |         pending_items = self.activity_model.query.filter( | Assignment statement storing or updating program state.
L0061 |             self.activity_model.activity_type.in_(["pm", "rca"]), | Operational statement participating in the file's runtime behav
L0062 |             self.activity_model.approved_at.is_(None), | Operational statement participating in the file's runtime behavior.
L0063 |             self.activity_model.created_by.in_(technician_emails_query), | Operational statement participating in the file's runtim
L0064 |             self.activity_model.risk_score >= self.high_risk_threshold, | Operational statement participating in the file's runtime
L0065 |             self.activity_model.sla_deadline.is_not(None), | Operational statement participating in the file's runtime behavior.
L0066 |             self.activity_model.sla_deadline < now, | Operational statement participating in the file's runtime behavior.
L0067 |         ).all() | Operational statement participating in the file's runtime behavior.
L0068 | | Blank line used for readability and logical separation.
L0069 |         escalated_count = 0 | Assignment statement storing or updating program state.
L0070 |         for item in pending_items: | Loop iterating over a sequence to process elements one by one.
L0071 |             marker = f"SLA_ESCALATION_ACTIVITY_{item.id}" | Assignment statement storing or updating program state.
L0072 |             already_sent = self.message_model.query.filter(self.message_model.body.ilike(f"%{marker}%")).first() | Assignment state
L0073 |             if already_sent: | Conditional branch that runs only when its condition is true.
L0074 |                 continue | Flow-control keyword affecting execution in the current block.
L0075 | | Blank line used for readability and logical separation.
L0076 |             body = ( | Assignment statement storing or updating program state.
L0077 |                 f"{marker}\n" | Operational statement participating in the file's runtime behavior.
L0078 |                 f"SLA escalation: {item.activity_type.upper()} form #{item.id} is overdue and high risk (score {item.risk_score}).\n"
L0079 |                 f"Submitted by: {item.created_by or 'Unknown'}\n" | Operational statement participating in the file's runtime behav
L0080 |                 f"Created at: {item.created_at.strftime('%Y-%m-%d %H:%M:%S')}\n" | Operational statement participating in the file's
L0081 |                 "Please prioritize immediate review." | Operational statement participating in the file's runtime behavior.
L0082 |             ) | Operational statement participating in the file's runtime behavior.
L0083 | | Blank line used for readability and logical separation.
L0084 |         for target_role in ["staff", "manager", "general_manager"]: | Loop iterating over a sequence to process elements one by
L0085 |             self.db.session.add( | Operational statement participating in the file's runtime behavior.
L0086 |                 self.message_model( | Operational statement participating in the file's runtime behavior.
L0087 |                     sender_email="system@soliton", | Assignment statement storing or updating program state.
L0088 |                     sender_role="system", | Assignment statement storing or updating program state.
L0089 |                     recipient_role=target_role, | Assignment statement storing or updating program state.
L0090 |                     recipient_email=None, | Assignment statement storing or updating program state.
L0091 |                     body=body, | Assignment statement storing or updating program state.
L0092 |                     created_at=now, | Assignment statement storing or updating program state.
L0093 |                 ) | Operational statement participating in the file's runtime behavior.
L0094 |             ) | Operational statement participating in the file's runtime behavior.
L0095 | | Blank line used for readability and logical separation.
L0096 |             self.create_activity("escalation", f"System escalated overdue high-risk form #{item.id}") | Operational statement parti
L0097 |             self.db.session.commit() | Operational statement participating in the file's runtime behavior.
L0098 |             escalated_count += 1 | Assignment statement storing or updating program state.
L0099 | | Blank line used for readability and logical separation.
L0100 |         return escalated_count | Returns a value (or control) back to the caller.
L0101 | | Blank line used for readability and logical separation.
L0102 |     def ensure_public_holiday_greeting_message(self) -> int: | Declares a function/method as a reusable unit of behavior.
L0103 |         today_utc = self.utcnow_naive() | Assignment statement storing or updating program state.
L0104 |         today_iso = today_utc.date().isoformat() | Assignment statement storing or updating program state.
L0105 |         holiday_today = next((item for item in self.get_public_holidays() if item.get("date") == today_iso), None) | Operational st
L0106 |         if not holiday_today: | Conditional branch that runs only when its condition is true.
L0107 |             return 0 | Returns a value (or control) back to the caller.
L0108 | | Blank line used for readability and logical separation.

```

```

L0109 |         start_day = datetime.combine(today_utc.date(), datetime.min.time()) | Assignment statement storing or updating program state.
L0110 |         end_day = start_day + timedelta(days=1) | Assignment statement storing or updating program state.
L0111 | | Blank line used for readability and logical separation.
L0112 |         existing = self.message_model.query.filter( | Assignment statement storing or updating program state.
L0113 |             self.message_model.sender_role == "system", | Operational statement participating in the file's runtime behavior.
L0114 |             self.message_model.recipient_role == "all", | Operational statement participating in the file's runtime behavior.
L0115 |             self.message_model.created_at >= start_day, | Operational statement participating in the file's runtime behavior.
L0116 |             self.message_model.created_at < end_day, | Operational statement participating in the file's runtime behavior.
L0117 |             self.message_model.body.ilike(f"%{holiday_today['name']}%"), | Operational statement participating in the file's runtime behavior.
L0118 |         ).first() | Operational statement participating in the file's runtime behavior.
L0119 |         if existing: | Conditional branch that runs only when its condition is true.
L0120 |             return 0 | Returns a value (or control) back to the caller.
L0121 | | Blank line used for readability and logical separation.
L0122 |         greeting = self.message_model( | Assignment statement storing or updating program state.
L0123 |             sender_email="system@soliton", | Assignment statement storing or updating program state.
L0124 |             sender_role="system", | Assignment statement storing or updating program state.
L0125 |             recipient_role="all", | Assignment statement storing or updating program state.
L0126 |             recipient_email=None, | Assignment statement storing or updating program state.
L0127 |             body=f"Happy {holiday_today['name']}! Wishing everyone a peaceful and productive public holiday.", | Assignment statement storing or updating program state.
L0128 |             created_at=today_utc, | Assignment statement storing or updating program state.
L0129 |         ) | Operational statement participating in the file's runtime behavior.
L0130 |         self.db.session.add(greeting) | Operational statement participating in the file's runtime behavior.
L0131 |         self.db.session.commit() | Operational statement participating in the file's runtime behavior.
L0132 |         return 1 | Returns a value (or control) back to the caller.

```

File 54: pm_app/services/observability.py

```
L0001 | from __future__ import annotations | Imports specific names from another module for direct usage.
L0002 | | Blank line used for readability and logical separation.
L0003 | import time | Imports dependency modules: time.
L0004 | import uuid | Imports dependency modules: uuid.
L0005 | | Blank line used for readability and logical separation.
L0006 | from flask import g, request | Imports specific names from another module for direct usage.
L0007 | | Blank line used for readability and logical separation.
L0008 | | Blank line used for readability and logical separation.
L0009 | def configure_request_observability(app, *, access_log_enabled: bool = False) -> None: | Declares a function/method as a reusable u
L0010 |     @app.before_request | Decorator line that modifies the behavior of the definition below.
L0011 |     def assign_request_context(): | Declares a function/method as a reusable unit of behavior.
L0012 |         g.request_started_at = time.perf_counter() | Assignment statement storing or updating program state.
L0013 |         inbound_request_id = (request.headers.get("X-Request-ID") or "").strip() | Assignment statement storing or updating program
L0014 |         g.request_id = inbound_request_id or uuid.uuid4().hex | Assignment statement storing or updating program state.
L0015 | | Blank line used for readability and logical separation.
L0016 |     @app.after_request | Decorator line that modifies the behavior of the definition below.
L0017 |     def append_request_headers(response): | Declares a function/method as a reusable unit of behavior.
L0018 |         response.headers["X-Request-ID"] = getattr(g, "request_id", uuid.uuid4().hex) | Assignment statement storing or updating pr
L0019 | | Blank line used for readability and logical separation.
L0020 |         started_at = getattr(g, "request_started_at", None) | Assignment statement storing or updating program state.
L0021 |         if access_log_enabled and started_at is not None: | Conditional branch that runs only when its condition is true.
L0022 |             duration_ms = (time.perf_counter() - started_at) * 1000 | Assignment statement storing or updating program state.
L0023 |             app.logger.info( | Operational statement participating in the file's runtime behavior.
L0024 |                 "request id=%s method=%s path=%s status=%s duration_ms=%.2f remote_addr=%s", | Assignment statement storing or upda
L0025 |                 g.request_id, | Operational statement participating in the file's runtime behavior.
L0026 |                 request.method, | Operational statement participating in the file's runtime behavior.
L0027 |                 request.path, | Operational statement participating in the file's runtime behavior.
L0028 |                 response.status_code, | Operational statement participating in the file's runtime behavior.
L0029 |                 duration_ms, | Operational statement participating in the file's runtime behavior.
L0030 |                 request.remote_addr, | Operational statement participating in the file's runtime behavior.
L0031 |             ) | Operational statement participating in the file's runtime behavior.
L0032 |         return response | Returns a value (or control) back to the caller.
```

File 55: pm_app/services/time_utils.py

L0001 | from datetime import datetime, timezone | Imports specific names from another module for direct usage.

L0002 | | Blank line used for readability and logical separation.

L0003 | | Blank line used for readability and logical separation.

L0004 | def utcnow_naive() -> datetime: | Declares a function/method as a reusable unit of behavior.

L0005 | """Return UTC now as a naive datetime for DB compatibility.""" | Docstring boundary used to describe a module, class, or function.

L0006 | return datetime.now(timezone.utc).replace(tzinfo=None) | Returns a value (or control) back to the caller.

File 56: pyrightconfig.json

```
L0001 | { | Block delimiter controlling scope/structure in this language.  
L0002 |   "$schema": "https://raw.githubusercontent.com/microsoft/pyright/main/packages/pyright/schema/pyrightconfig.schema.json", | Operat  
L0003 |   "typeCheckingMode": "basic", | Operational statement participating in the file's runtime behavior.  
L0004 |   "reportCallIssue": "none" | Operational statement participating in the file's runtime behavior.  
L0005 | } | Block delimiter controlling scope/structure in this language.
```

File 57: pytest.ini

L0001 | [pytest] | Operational statement participating in the file's runtime behavior.
L0002 | python_files = test_*.py | Assignment statement storing or updating program state.
L0003 | testpaths = tests | Assignment statement storing or updating program state.
L0004 | addopts = -q | Assignment statement storing or updating program state.

File 58: pytest_fail_auth.txt

```
L0001 | yb= | Operational statement participating in the file's runtime behavior.
```

```
L0002 | | Operational statement participating in the file's runtime behavior.
```

```
L0003 | pollatforn win32 - - Plaython 3.14.0, playtets-9.0.2, plulggy-1.6
```

```
L0004 | | Operational statement participating in the file's runtime behavior.
```

```
L0005 | cacchedir: .playtets_cacche | Operational statement participating in the file's runtime behavior.
```

```
L0006 | | Operational statement participating in the file's runtime behavior.
```

```
L0007 | rootdir: C:\Users\johnas\OneDrive\Desktop\p\pm | Operational statement parti
```

```
L0008 | | Operational statement participating in the file's runtime behavior.
```

```
L0009 | collecutting . . . . . collecutted 1 item | Operational statement participating in the file's runtime
```

```
L0010 | | Operational statement participating in the file's runtime behavior.
```

```
L0011 | | Operational statement participating in the file's runtime behavior.
```

```
L0012 | | Operational statement participating in the file's runtime behavior.
```

```
L0013 | tets/tets_aautht.play: tset_rresett_passsword_showws_cuurrent_andd
```

```
L0014 | | Operational statement participating in the file's runtime behavior.
```

```
L0015 | | Operational statement participating in the file's runtime behavior.
```

```
L0016 | | Operational statement participating in the file's runtime behavior.
```

```
L0017 | == FAMILUES ==
```

```
L0018 | | Operational statement participating in the file's runtime behavior.
```

```
L0019 | _ tset_rresett_passsword_showws_cuurrent_andd_new_passsword_in_
```

```
L0020 | | Operational statement participating in the file's runtime behavior.
```

```
L0021 | | Operational statement participating in the file's runtime behavior.
```

```
L0022 | | Operational statement participating in the file's runtime behavior.
```

```
L0023 | app == <Falsk 'app'>, client == <FalskCliient <Falsk 'app'>>
```

```
L0024 | | Operational statement participating in the file's runtime behavior.
```

```
L0025 | loggin_as_deveelloper == <functioin login_as_deveelloper.<llocllss
```

```
L0026 | | Operational statement participating in the file's runtime behavior.
```

```
L0027 | | Operational statement participating in the file's runtime behavior.
```

```
L0028 | | Operational statement participating in the file's runtime behavior.
```

```
L0029 | ddef tset_rresett_passsword_sshowws_cuurrent_andd_new_passsword
```

```
L0030 | | Operational statement participating in the file's runtime behavior.
```

```
L0031 | login_as_deveelloper( ) | Operational statement participating in the file's runtime behav
```

```
L0032 | | Operational statement participating in the file's runtime behavior.
```

```
L0033 | | Operational statement participating in the file's runtime behavior.
```

```
L0034 | | Operational statement participating in the file's runtime behavior.
```

```
L0035 | wait app.app.context( ): | Operational statement participating in the file's runtime
```

```
L0036 | | Operational statement participating in the file's runtime behavior.
```

```
L0037 | target = User( | Assignment statement storing or updating program state.
```

```
L0038 | | Operational statement participating in the file's runtime behavior.
```

```
L0039 | email="reset-target@examp.le.co." , | Assignment stat
```

```
L0040 | | Operational statement participating in the file's runtime behavior.
```

```
L0041 | furl_nam="Reset Target", | Assignment statement storing or up
```

```
L0042 | | Operational statement participating in the file's runtime behavior.
```

```
L0043 | rolle="settaff", | Assignment statement storing or updating program state.
```

```
L0044 | | Operational statement participating in the file's runtime behavior.
```

```
L0045 | passsword_hassh=gennearatt_e_passwd_hassh("0ldd
```

```
L0046 | | Operational statement participating in the file's runtime behavior.
```

```
L0047 | ( ) | Operational statement participating in the file's runtime behavior.
```

```
L0048 | | Operational statement participating in the file's runtime behavior.
```

```
L0049 | db.ssessio.n.add(ttarget) | Operational statement participating in the file's
```

```
L0050 | | Operational statement participating in the file's runtime behavior.
```

```
L0051 | db.ssessio.n.commit( ) | Operational statement participating in the file's runtime
```

```
L0052 | | Operational statement participating in the file's runtime behavior.
```

```
L0053 | target_id = target.id | Assignment statement storing or updating program state
```

L0054 | ■ | Operational statement participating in the file's runtime behavior.

L0055 | ■ ■ ■ ■ ■ | Operational statement participating in the file's runtime behavior.

L0056 | ■ | Operational statement participating in the file's runtime behavior.

L0057 | ■ ■ ■ ■ ■ ■ ■ ■ r e s p o n s e s e = ■ c l i e n t . g e t (" / a d m i n / s t a f f / ") ■ | Assignment statement s

L0058 | ■ | Operational statement participating in the file's runtime behavior.

L0059 | ■ ■ ■ ■ ■ ■ ■ a s s e r t r e s p o n s e s . s t a t u s _ c o d e = ■ 2 0 0 ■ | Assignment statement storing or

L0060 | ■ | Operational statement participating in the file's runtime behavior.

L0061 | ■ ■ ■ ■ ■ ■ ■ c s r f _ t o k e n = ■ e x t r a c t _ h i d d e n _ i n p u t (r e s p o n s e . g e t _ d a

L0062 | ■ | Operational statement participating in the file's runtime behavior.

L0063 | ■ ■ ■ ■ ■ | Operational statement participating in the file's runtime behavior.

L0064 | ■ | Operational statement participating in the file's runtime behavior.

L0065 | ■ ■ ■ ■ ■ ■ ■ r e s p o n s e s e = ■ c l i e n t . p o s t (■ | Assignment statement storing or updating program state.

L0066 | ■ | Operational statement participating in the file's runtime behavior.

L0067 | ■ ■ ■ ■ ■ ■ ■ ■ f " / a d m i n / s t a f f / { t a r g e t _ i d } / r e s e t - p l a s s w o r d " , ■ | Op

L0068 | ■ | Operational statement participating in the file's runtime behavior.

L0069 | ■ ■ ■ ■ ■ ■ ■ ■ d a t a = { ■ | Assignment statement storing or updating program state.

L0070 | ■ | Operational statement participating in the file's runtime behavior.

L0071 | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ c s r f _ t o k e n " : ■ c s r f _ t o k e n , ■ | Operational statement participati

L0072 | ■ | Operational statement participating in the file's runtime behavior.

L0073 | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ c u r r e n t _ p l a s s w o r d " : ■ " 0 1 d P a s s 1 2 3 ! " , ■ | Operational s

L0074 | ■ | Operational statement participating in the file's runtime behavior.

L0075 | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ n e w _ p l a s s w o r d " : ■ " N e w P a s s 4 5 6 ! " , ■ | Operational statement

L0076 | ■ | Operational statement participating in the file's runtime behavior.

L0077 | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ q " : ■ " " , ■ | Operational statement participating in the file's runtime behavior.

L0078 | ■ | Operational statement participating in the file's runtime behavior.

L0079 | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ } , ■ | Operational statement participating in the file's runtime behavior.

L0080 | ■ | Operational statement participating in the file's runtime behavior.

L0081 | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ f o l l o w _ r e d i r e c t s = T r u e , ■ | Assignment statement storing or updating program

L0082 | ■ | Operational statement participating in the file's runtime behavior.

L0083 | ■ ■ ■ ■ ■ ■ ■ ■) ■ | Operational statement participating in the file's runtime behavior.

L0084 | ■ | Operational statement participating in the file's runtime behavior.

L0085 | ■ ■ ■ ■ ■ ■ ■ a s s e r t r e s p o n s e s . s t a t u s _ c o d e = ■ 2 0 0 ■ | Assignment statement storing or

L0086 | ■ | Operational statement participating in the file's runtime behavior.

L0087 | ■ ■ ■ ■ ■ ■ ■ b o d y = ■ r e s p o n s e s . g e t _ d a t a (a s _ t e x t = T r u e) ■ | Assignment statement s

L0088 | ■ | Operational statement participating in the file's runtime behavior.

L0089 | ■ ■ ■ ■ ■ ■ ■ a s s e r t " P l a s s w o r d r e s e t f o r R e s e t T a r g e t . " i n b o d y

L0090 | ■ | Operational statement participating in the file's runtime behavior.

L0091 | ■ > ■ ■ ■ ■ ■ ■ a s s e r t " C u r r e n t P l a s s w o r d : " i n b o d y | Operational statement participa

L0092 | ■ | Operational statement participating in the file's runtime behavior.

L0093 | ■ E ■ ■ ■ ■ ■ ■ a s s e r t " C u r r e n t P l a s s w o r d : " i n ' < ! D O C T Y P E h t m l > \ n <

L0094 | ■ | Operational statement participating in the file's runtime behavior.

L0095 | ■ | Operational statement participating in the file's runtime behavior.

L0096 | ■ | Operational statement participating in the file's runtime behavior.

L0097 | ■ t e s t \ t e s t _ a u t h . p y : 2 7 9 : ■ A s s e r t i o n E r r o r | Operational statement participating in t

L0098 | ■ | Operational statement participating in the file's runtime behavior.

L0099 | ■ - C a p t u r e d l o g s e t u p ■ - - - - - - - - - -

L0100 | ■ | Operational statement participating in the file's runtime behavior.

L0101 | ■ W A R N I N G ■ a p p : a p p . p y : 1 0 7 1 ■ C o u l d n o t l o a d p e r s i s t e n t d e v e l o p

L0102 | ■ | Operational statement participating in the file's runtime behavior.

L0103 | ■ [S Q L : ■ S E L E C T u s e r _ s e t t i n g s . i d A S u s e r _ s e t t i n g s . i d , ■ u s e r _ s

L0104 | ■ | Operational statement participating in the file's runtime behavior.

L0105 | ■ F R O M u s e r _ s e t t i n g s J O I N u s e r s O N u s e r _ s e t t i n g s . u s e r _ i d = ■

L0106 | ■ | Operational statement participating in the file's runtime behavior.

L0107 | ■ W H E R E u s e r s . r o l e = ■ ? O R D E R B Y u s e r _ s e t t i n g s . u p d a t e d _ a t D E

L0108 | ■ | Operational statement participating in the file's runtime behavior.

[illegible]

File 59: pytest_latest.txt

```
L0001 | ■.....FF..... [100%] | Operational statement participating in the file's
L0002 | ===== FAILURES ===== | Operational statement participating in the file's
L0003 | _____ test_sender_can_delete_own_message _____ | Operational statement participating in the file's
L0004 | tests\test_notifications.py:226: in test_sender_can_delete_own_message | Operational statement participating in the file's runtime
L0005 |     assert "Message deleted." in response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0006 | E   assert 'Message deleted.' in '<!DOCTYPE html>\n<html lang="en">\n  <head>\n    <meta charset="UTF-8" />\n    <meta name="viewpo
L0007 | E   +   where '<!DOCTYPE html>\n<html lang="en">\n  <head>\n    <meta charset="UTF-8" />\n    <meta name="viewport" content="width=
L0008 | E   +   where get_data = <WrapperTestResponse 37004 bytes [200 OK]>.get_data | Assignment statement storing or updating program s
L0009 | ----- Captured log setup ----- | Operational statement participating in the file's
L0010 | WARNING app:app.py:1071 Could not load persisted developer upload limits: (sqlite3.OperationalError) no such table: user_settings
L0011 | [SQL: SELECT user_settings.id AS user_settings_id, user_settings.user_id AS user_settings_user_id, user_settings.theme AS user_sett
L0012 | FROM user_settings JOIN users ON user_settings.user_id = users.id | Assignment statement storing or updating program state.
L0013 | WHERE users.role = ? ORDER BY user_settings.updated_at DESC | Assignment statement storing or updating program state.
L0014 | LIMIT ? OFFSET ?] | Operational statement participating in the file's runtime behavior.
L0015 | [parameters: ('developer', 1, 0)] | Operational statement participating in the file's runtime behavior.
L0016 | (Background on this error at: https://sqlalche.me/e/20/e3q8) | Operational statement participating in the file's runtime behavior.
L0017 | _____ test_non_sender_cannot_delete_message _____ | Operational statement participating in the file's
L0018 | tests\test_notifications.py:274: in test_non_sender_cannot_delete_message | Operational statement participating in the file's runti
L0019 |     assert "You can only delete your own messages." in response.get_data(as_text=True) | Assignment statement storing or updating p
L0020 | E   assert 'You can only delete your own messages.' in '<!DOCTYPE html>\n<html lang="en">\n  <head>\n    <meta charset="UTF-8" />\n
L0021 | E   +   where '<!DOCTYPE html>\n<html lang="en">\n  <head>\n    <meta charset="UTF-8" />\n    <meta name="viewport" content="width=
L0022 | E   +   where get_data = <WrapperTestResponse 37004 bytes [200 OK]>.get_data | Assignment statement storing or updating program s
L0023 | ----- Captured log setup ----- | Operational statement participating in the file's
L0024 | WARNING app:app.py:1071 Could not load persisted developer upload limits: (sqlite3.OperationalError) no such table: user_settings
L0025 | [SQL: SELECT user_settings.id AS user_settings_id, user_settings.user_id AS user_settings_user_id, user_settings.theme AS user_sett
L0026 | FROM user_settings JOIN users ON user_settings.user_id = users.id | Assignment statement storing or updating program state.
L0027 | WHERE users.role = ? ORDER BY user_settings.updated_at DESC | Assignment statement storing or updating program state.
L0028 | LIMIT ? OFFSET ?] | Operational statement participating in the file's runtime behavior.
L0029 | [parameters: ('developer', 1, 0)] | Operational statement participating in the file's runtime behavior.
L0030 | (Background on this error at: https://sqlalche.me/e/20/e3q8) | Operational statement participating in the file's runtime behavior.
L0031 | ===== warnings summary ===== | Operational statement participating in the file's
L0032 | tests/test_security.py::test_developer_can_edit_user_profile | Operational statement participating in the file's runtime behavior.
L0033 | tests/test_security.py::test_developer_profile_edit_rejects_duplicate_email | Operational statement participating in the file's run
L0034 | C:\Users\jonas\OneDrive\Desktop\pm\.venv\Lib\site-packages\flask_sqlalchemy\query.py:30: LegacyAPIWarning: The Query.get() method
L0035 |     rv = self.get(ident) | Assignment statement storing or updating program state.
L0036 | | Blank line used for readability and logical separation.
L0037 | tests/test_security.py::test_developer_can_edit_user_profile | Operational statement participating in the file's runtime behavior.
L0038 | C:\Users\jonas\OneDrive\Desktop\pm\tests\test_security.py:210: LegacyAPIWarning: The Query.get() method is considered legacy as o
L0039 |     updated = User.query.get(user_id) | Assignment statement storing or updating program state.
L0040 | | Blank line used for readability and logical separation.
L0041 | tests/test_security.py::test_developer_profile_edit_rejects_duplicate_email | Operational statement participating in the file's run
L0042 | C:\Users\jonas\OneDrive\Desktop\pm\tests\test_security.py:254: LegacyAPIWarning: The Query.get() method is considered legacy as o
L0043 |     unchanged = User.query.get(user_id) | Assignment statement storing or updating program state.
L0044 | | Blank line used for readability and logical separation.
L0045 | -- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html | Operational statement participating in the file's runtime
L0046 | ===== short test summary info ===== | Operational statement participating in the file's
L0047 | FAILED tests/test_notifications.py::test_sender_can_delete_own_message - asse... | Operational statement participating in the file's
L0048 | FAILED tests/test_notifications.py::test_non_sender_cannot_delete_message - a... | Operational statement participating in the file's
L0049 | 2 failed, 46 passed, 4 warnings in 554.61s (0:09:14) | Operational statement participating in the file's runtime behavior.
```

File 60: pytest_out.txt

```
L0001 | ■===== test session starts ===== | Operational statement participating in the file's
L0002 | platform win32 -- Python 3.14.0, pytest-9.0.2, pluggy-1.6.0 | Operational statement participating in the file's runtime behavior.
L0003 | rootdir: C:\Users\jonas\OneDrive\Desktop\pm | Operational statement participating in the file's runtime behavior.
L0004 | collected 6 items | Operational statement participating in the file's runtime behavior.
L0005 | | Blank line used for readability and logical separation.
L0006 | tests\test_auth.py ..... [100%] | Operational statement participating in the file's runtime behavior.
L0007 | | Blank line used for readability and logical separation.
L0008 | ===== warnings summary ===== | Operational statement participating in the file's runtime behavior.
L0009 | tests/test_auth.py: 14 warnings | Operational statement participating in the file's runtime behavior.
L0010 | C:\Users\jonas\OneDrive\Desktop\pm\app.py:1216: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for re
L0011 |     today_utc = datetime.utcnow() | Assignment statement storing or updating program state.
L0012 | | Blank line used for readability and logical separation.
L0013 | tests/test_auth.py::test_dashboard_redirects_anonymous_user | Operational statement participating in the file's runtime behavior.
L0014 | C:\Users\jonas\OneDrive\Desktop\pm\app.py:1070: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for re
L0015 |     now = datetime.utcnow() | Assignment statement storing or updating program state.
L0016 | | Blank line used for readability and logical separation.
L0017 | tests/test_auth.py::test_registration_locks_after_first_user_exists | Operational statement participating in the file's runtime behavior.
L0018 | tests/test_auth.py::test_developer_login_redirects_to_dashboard | Operational statement participating in the file's runtime behavior.
L0019 | tests/test_auth.py::test_api_create_consumable_uses_authenticated_identity | Operational statement participating in the file's runtime behavior.
L0020 | tests/test_auth.py::test_api_create_consumable_uses_authenticated_identity | Operational statement participating in the file's runtime behavior.
L0021 | tests/test_auth.py::test_user_settings_persist_in_database | Operational statement participating in the file's runtime behavior.
L0022 | tests/test_auth.py::test_user_settings_persist_in_database | Operational statement participating in the file's runtime behavior.
L0023 | C:\Users\jonas\OneDrive\Desktop\pm\.venv\Lib\site-packages\sqlalchemy\sql\schema.py:3624: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for re
L0024 |     return util.wrap_callable(lambda ctx: fn(), fn) # type: ignore | Returns a value (or control) back to the caller.
L0025 | | Blank line used for readability and logical separation.
L0026 | tests/test_auth.py::test_api_create_consumable_uses_authenticated_identity | Operational statement participating in the file's runtime behavior.
L0027 | tests/test_auth.py::test_api_create_consumable_uses_authenticated_identity | Operational statement participating in the file's runtime behavior.
L0028 | tests/test_auth.py::test_user_settings_persist_in_database | Operational statement participating in the file's runtime behavior.
L0029 | tests/test_auth.py::test_user_settings_persist_in_database | Operational statement participating in the file's runtime behavior.
L0030 | tests/test_auth.py::test_user_settings_persist_in_database | Operational statement participating in the file's runtime behavior.
L0031 | C:\Users\jonas\OneDrive\Desktop\pm\app.py:820: LegacyAPIWarning: The Query.get() method is considered legacy as of the 1.x series
L0032 |     user = User.query.get(int(user_id)) | Assignment statement storing or updating program state.
L0033 | | Blank line used for readability and logical separation.
L0034 | -- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html | Operational statement participating in the file's runtime behavior.
L0035 | ===== 6 passed, 26 warnings in 127.82s (0:02:07) ===== | Operational statement participating in the file's runtime behavior.
```

File 61: pytest_out3.txt

```
L0001 | ■===== test session starts ===== | Operational statement participating in the file's
L0002 | platform win32 -- Python 3.14.0, pytest-9.0.2, pluggy-1.6.0 -- C:\Users\jonas\OneDrive\Desktop\pm\.venv\Scripts\python.exe | Operat
L0003 | cachedir: .pytest_cache | Operational statement participating in the file's runtime behavior.
L0004 | rootdir: C:\Users\jonas\OneDrive\Desktop\pm | Operational statement participating in the file's runtime behavior.
L0005 | collecting ... collected 23 items | Operational statement participating in the file's runtime behavior.
L0006 | | Blank line used for readability and logical separation.
L0007 | tests/test_auth.py::test_dashboard_redirects_anonymous_user PASSED [ 4%] | Operational statement participating in the file's
L0008 | tests/test_auth.py::test_first_user_registration_page_is_public PASSED [ 8%] | Operational statement participating in the file's
L0009 | tests/test_auth.py::test_registration_locks_after_first_user_exists PASSED [ 13%] | Operational statement participating in the file's
L0010 | tests/test_auth.py::test_developer_login_redirects_to_dashboard PASSED [ 17%] | Operational statement participating in the file's
L0011 | tests/test_auth.py::test_api_create_consumable_uses_authenticated_identity PASSED [ 21%] | Operational statement participating in the file's
L0012 | tests/test_auth.py::test_user_settings_persist_in_database PASSED [ 26%] | Operational statement participating in the file's
L0013 | tests/test_notifications.py::test_send_message_persists_and_logs_activity PASSED [ 30%] | Operational statement participating in the file's
L0014 | tests/test_notifications.py::test_notifications_inbox_uses_normalized_role_matching PASSED [ 34%] | Operational statement participating in the file's
L0015 | tests/test_notifications.py::test_send_message_get_redirects_to_notifications PASSED [ 39%] | Operational statement participating in the file's
L0016 | tests/test_security.py::test_file_upload_rejects_non_image_extension PASSED [ 43%] | Operational statement participating in the file's
L0017 | tests/test_security.py::test_signature_validation_rejects_invalid_base64 PASSED [ 47%] | Operational statement participating in the file's
L0018 | tests/test_security.py::test_signature_validation_rejects_wrong_magic_bytes PASSED [ 52%] | Operational statement participating in the file's
L0019 | tests/test_security.py::test_signature_validation_accepts_real_png PASSED [ 56%] | Operational statement participating in the file's
L0020 | tests/test_security.py::test_csrf_blocks_mutation_without_token PASSED [ 60%] | Operational statement participating in the file's
L0021 | tests/test_security.py::test_technician_cannot_access_desk_activities PASSED [ 65%] | Operational statement participating in the file's
L0022 | tests/test_security.py::test_technician_cannot_access_admin_staff PASSED [ 69%] | Operational statement participating in the file's
L0023 | tests/test_security.py::test_staff_cannot_access_admin_staff PASSED [ 73%] | Operational statement participating in the file's
L0024 | tests/test_security.py::test_anonymous_redirect_to_login PASSED [ 78%] | Operational statement participating in the file's
L0025 | tests/test_security.py::test_api_returns_consistent_error_on_forbidden PASSED [ 82%] | Operational statement participating in the file's
L0026 | tests/test_security.py::test_api_returns_consistent_error_on_missing_fields PASSED [ 86%] | Operational statement participating in the file's
L0027 | tests/test_security.py::test_api_list_consumables_returns_status_ok PASSED [ 91%] | Operational statement participating in the file's
L0028 | tests/test_security.py::test_risk_score_constants_are_sensible PASSED [ 95%] | Operational statement participating in the file's
L0029 | tests/test_security.py::test_classify_risk_level_boundaries PASSED [100%] | Operational statement participating in the file's
L0030 | | Blank line used for readability and logical separation.
L0031 | ===== warnings summary ===== | Operational statement participating in the file's
L0032 | tests/test_auth.py: 14 warnings | Operational statement participating in the file's runtime behavior.
L0033 | tests/test_notifications.py: 11 warnings | Operational statement participating in the file's runtime behavior.
L0034 | tests/test_security.py: 25 warnings | Operational statement participating in the file's runtime behavior.
L0035 | C:\Users\jonas\OneDrive\Desktop\pm\app.py:1219: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for re
L0036 |     today_utc = datetime.utcnow() | Assignment statement storing or updating program state.
L0037 | | Blank line used for readability and logical separation.
L0038 | tests/test_auth.py::test_dashboard_redirects_anonymous_user | Operational statement participating in the file's runtime behavior.
L0039 | C:\Users\jonas\OneDrive\Desktop\pm\app.py:1073: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for re
L0040 |     now = datetime.utcnow() | Assignment statement storing or updating program state.
L0041 | | Blank line used for readability and logical separation.
L0042 | tests/test_auth.py: 6 warnings | Operational statement participating in the file's runtime behavior.
L0043 | tests/test_notifications.py: 5 warnings | Operational statement participating in the file's runtime behavior.
L0044 | tests/test_security.py: 10 warnings | Operational statement participating in the file's runtime behavior.
L0045 | C:\Users\jonas\OneDrive\Desktop\pm\.venv\Lib\site-packages\sqlalchemy\sql\schem.py:3624: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for re
L0046 |     return util.wrap_callable(lambda ctx: fn(), fn) # type: ignore | Returns a value (or control) back to the caller.
L0047 | | Blank line used for readability and logical separation.
L0048 | tests/test_auth.py: 5 warnings | Operational statement participating in the file's runtime behavior.
L0049 | tests/test_notifications.py: 5 warnings | Operational statement participating in the file's runtime behavior.
L0050 | tests/test_security.py: 7 warnings | Operational statement participating in the file's runtime behavior.
L0051 | C:\Users\jonas\OneDrive\Desktop\pm\app.py:823: LegacyAPIWarning: The Query.get() method is considered legacy as of the 1.x series
L0052 |     user = User.query.get(int(user_id)) | Assignment statement storing or updating program state.
L0053 | | Blank line used for readability and logical separation.
```

L0054 | tests/test_notifications.py::test_send_message_persists_and_logs_activity | Operational statement participating in the file's runtime behavior

L0055 | tests/test_notifications.py::test_send_message_persists_and_logs_activity | Operational statement participating in the file's runtime behavior

L0056 | tests/test_notifications.py::test_notifications_inbox_uses_normalized_role_matching | Operational statement participating in the file's runtime behavior

L0057 | C:\Users\jonas\OneDrive\Desktop\pm\pm_app\dashboards\routes.py:156: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for removal in a future version. Use datetime.datetime.now(datetime.timezone.utc) instead.

L0058 | session["notifications_last_seen_at"] = datetime.datetime.utcnow().isoformat(timespec="seconds") | Assignment statement storing or updating program state.

L0059 | | Blank line used for readability and logical separation.

L0060 | tests/test_notifications.py::test_send_message_persists_and_logs_activity | Operational statement participating in the file's runtime behavior

L0061 | tests/test_security.py::test_csrf_blocks_mutation_without_token | Operational statement participating in the file's runtime behavior

L0062 | C:\Users\jonas\OneDrive\Desktop\pm\pm_app\dashboards\routes.py:209: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for removal in a future version. Use datetime.datetime.now(datetime.timezone.utc) instead.

L0063 | created_at=datetime.datetime.utcnow(), | Assignment statement storing or updating program state.

L0064 | | Blank line used for readability and logical separation.

L0065 | tests/test_notifications.py::test_send_message_persists_and_logs_activity | Operational statement participating in the file's runtime behavior

L0066 | tests/test_security.py::test_csrf_blocks_mutation_without_token | Operational statement participating in the file's runtime behavior

L0067 | C:\Users\jonas\OneDrive\Desktop\pm\app.py:874: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for removal in a future version. Use datetime.datetime.now(datetime.timezone.utc) instead.

L0068 | activity = Activity(activity_type=activity_type, details=details, created_by=by, created_at=datetime.datetime.utcnow()) | Assignment statement storing or updating program state.

L0069 | | Blank line used for readability and logical separation.

L0070 | -- Docs: <https://docs.pytest.org/en/stable/how-to/capture-warnings.html> | Operational statement participating in the file's runtime behavior

L0071 | ===== 23 passed, 96 warnings in 153.93s (0:02:33) ===== | Operational statement participating in the file's runtime behavior

File 62: pytest_profile_edit_output.txt

```
L0001 | ýþ===== test session started =====
L0002 |  | Operational statement participating in the file's runtime behavior.
L0003 |  platform=win32 - - - Pythoon 3.14.0,  pytest-9.0.2,  pluggy-1.6
L0004 |  | Operational statement participating in the file's runtime behavior.
L0005 |  rootdir:  C:\Users\johnas\OneDrive\Documents\p\p  | Operational statement parti
L0006 |  | Operational statement participating in the file's runtime behavior.
L0007 |  configfile= 23  file=  /  19  destdir=  /  4  selled=  | Operational statemen
L0008 |  | Operational statement participating in the file's runtime behavior.
L0009 |  | Operational statement participating in the file's runtime behavior.
L0010 |  | Operational statement participating in the file's runtime behavior.
L0011 |  teststest\testst_ssecuritity.py  . . . . .
L0012 |  | Operational statement participating in the file's runtime behavior.
L0013 |  | Operational statement participating in the file's runtime behavior.
L0014 |  | Operational statement participating in the file's runtime behavior.
L0015 |  =====  warninings  summary  =====
L0016 |  | Operational statement participating in the file's runtime behavior.
L0017 |  teststest\testst_ssecuritity.py::testst_develloper_clean_deedit_usersr_prof
L0018 |  | Operational statement participating in the file's runtime behavior.
L0019 |  1  C:\Users\johnas\OneDrive\Documents\p\p\venv\Lib\site-pacak
L0020 |  | Operational statement participating in the file's runtime behavior.
L0021 |  1  1  rev  =  selff.get(id(ent))  | Assignment statement storing or updating program state.
L0022 |  | Operational statement participating in the file's runtime behavior.
L0023 |  | Operational statement participating in the file's runtime behavior.
L0024 |  | Operational statement participating in the file's runtime behavior.
L0025 |  teststest\testst_ssecuritity.py::testst_develloper_clean_deedit_usersr_prof
L0026 |  | Operational statement participating in the file's runtime behavior.
L0027 |  1  C:\Users\johnas\OneDrive\Documents\p\p\teststest\testst_ssecuritity.
L0028 |  | Operational statement participating in the file's runtime behavior.
L0029 |  1  1  updatated  =  Usersr.queuey.get(Usersr_id)  | Assignment statement storing or updating p
L0030 |  | Operational statement participating in the file's runtime behavior.
L0031 |  | Operational statement participating in the file's runtime behavior.
L0032 |  | Operational statement participating in the file's runtime behavior.
L0033 |  - - - Doccs:  htttps://docs.pytest.org/en/stable/how-to/collectur
L0034 |  | Operational statement participating in the file's runtime behavior.
L0035 |  =====  4  passsed,  19  destdir=  2  warninings  in  68.72s
L0036 |  | Operational statement participating in the file's runtime behavior.
L0037 |  EXIT:0  | Operational statement participating in the file's runtime behavior.
L0038 |  | Operational statement participating in the file's runtime behavior.
L0039 |  | Operational statement participating in the file's runtime behavior.
```

File 63: pytest_targeted.txt

[illegible]

File 64: README.md

```
L0001 | # Preventative Maintenance RCA System | Comment line documenting intent or context for nearby code.
L0002 | | Blank line used for readability and logical separation.
L0003 | A Flask-based preventive maintenance and RCA platform with role-based dashboards, PM/RCA field submission, desk review workflows, m
L0004 | | Blank line used for readability and logical separation.
L0005 | ## Stack | Comment line documenting intent or context for nearby code.
L0006 | | Blank line used for readability and logical separation.
L0007 | - Python 3.10+ | Operational statement participating in the file's runtime behavior.
L0008 | - Flask, Flask-Login, Flask-SQLAlchemy, Flask-Migrate | Operational statement participating in the file's runtime behavior.
L0009 | - PostgreSQL with `psycopg` | Operational statement participating in the file's runtime behavior.
L0010 | - Optional S3 upload storage | Operational statement participating in the file's runtime behavior.
L0011 | - Optional file-change watchdog reporting via `advanced_watchdog_script.py` | Operational statement participating in the file's runtime behavior.
L0012 | | Blank line used for readability and logical separation.
L0013 | ## Environment | Comment line documenting intent or context for nearby code.
L0014 | | Blank line used for readability and logical separation.
L0015 | Create `.env` from `.env.example`: | Operational statement participating in the file's runtime behavior.
L0016 | | Blank line used for readability and logical separation.
L0017 | ```bash | Operational statement participating in the file's runtime behavior.
L0018 | copy .env.example .env | Operational statement participating in the file's runtime behavior.
L0019 | ``` | Operational statement participating in the file's runtime behavior.
L0020 | | Blank line used for readability and logical separation.
L0021 | Required or important variables: | Operational statement participating in the file's runtime behavior.
L0022 | | Blank line used for readability and logical separation.
L0023 | - `APP_ENV`: `development`, `staging`, or `production` | Operational statement participating in the file's runtime behavior.
L0024 | - `DATABASE_URL`: required in production; optional in development/staging | Operational statement participating in the file's runtime behavior.
L0025 | - `DEV_DATABASE_URL`: optional development override (defaults to SQLite) | Operational statement participating in the file's runtime behavior.
L0026 | - `SECRET_KEY`: required outside tests | Operational statement participating in the file's runtime behavior.
L0027 | - `SESSION_COOKIE_SECURE`: set to `1` behind HTTPS, `0` for local HTTP | Operational statement participating in the file's runtime behavior.
L0028 | - `PUBLIC_BASE_URL`: recommended for externally shared login links | Operational statement participating in the file's runtime behavior.
L0029 | - `LOG_LEVEL`: application log level | Operational statement participating in the file's runtime behavior.
L0030 | - `ENABLE_INLINE_AUTOMATIONS`: when `1`, holiday and SLA maintenance tasks can run in request flow; defaults to `0` in production | Operational statement participating in the file's runtime behavior.
L0031 | - `ACCESS_LOG_ENABLED`: when `1`, emits per-request latency logs and request IDs | Operational statement participating in the file's runtime behavior.
L0032 | - `REDIS_URL`: optional, enables distributed login throttling | Operational statement participating in the file's runtime behavior.
L0033 | - `MAX_LOGIN_ATTEMPTS`, `LOGIN_WINDOW_SECONDS`, `LOGIN_LOCKOUT_SECONDS`: login throttle tuning | Operational statement participating in the file's runtime behavior.
L0034 | - `ALERT_EMAIL_ADDRESS` / `ALERT_EMAIL_PASSWORD`: optional app error email alerts | Operational statement participating in the file's runtime behavior.
L0035 | - `WATCHER_EMAIL_FROM` / `WATCHER_EMAIL_PASSWORD` / `WATCHER_EMAIL_TO`: optional watchdog reporting email settings | Operational statement participating in the file's runtime behavior.
L0036 | | Blank line used for readability and logical separation.
L0037 | Database URL examples: | Operational statement participating in the file's runtime behavior.
L0038 | | Blank line used for readability and logical separation.
L0039 | - Local PostgreSQL: `postgresql+psycopg://postgres:password@localhost:5432/pm_db` | Operational statement participating in the file's runtime behavior.
L0040 | - Managed PostgreSQL: `postgresql+psycopg://username:password@hostname:5432/database_name` | Operational statement participating in the file's runtime behavior.
L0041 | - Local SQLite (dev): `sqlite:///instance/dev_pm.sqlite` | Operational statement participating in the file's runtime behavior.
L0042 | | Blank line used for readability and logical separation.
L0043 | ## Database Modes | Comment line documenting intent or context for nearby code.
L0044 | | Blank line used for readability and logical separation.
L0045 | The application supports a dual-mode workflow: | Operational statement participating in the file's runtime behavior.
L0046 | | Blank line used for readability and logical separation.
L0047 | - Development/staging (`APP_ENV=development` or `staging`): | Assignment statement storing or updating program state.
L0048 | ■- Uses `DATABASE_URL` when provided | Operational statement participating in the file's runtime behavior.
L0049 | ■- Falls back to SQLite automatically when `DATABASE_URL` is not set | Operational statement participating in the file's runtime behavior.
L0050 | - Production (`APP_ENV=production`): | Assignment statement storing or updating program state.
L0051 | ■- Requires `DATABASE_URL` | Operational statement participating in the file's runtime behavior.
L0052 | ■- Enforces PostgreSQL with psycopg (`postgresql+psycopg://...`) | Operational statement participating in the file's runtime behavior.
L0053 | | Blank line used for readability and logical separation.
```


L0054 | This allows fast local development with SQLite while keeping production strict and predictable. | Operational statement participating in the file's runtime behavior.

L0055 | | Blank line used for readability and logical separation.

L0056 | ## Local Development | Comment line documenting intent or context for nearby code.

L0057 | | Blank line used for readability and logical separation.

L0058 | 1. Create and activate a virtual environment. | Operational statement participating in the file's runtime behavior.

L0059 | | Blank line used for readability and logical separation.

L0060 | ```bash | Operational statement participating in the file's runtime behavior.

L0061 | python -m venv .venv | Operational statement participating in the file's runtime behavior.

L0062 | .venv\Scripts\activate | CSS selector line choosing the elements styled below.

L0063 | ``` | Operational statement participating in the file's runtime behavior.

L0064 | | Blank line used for readability and logical separation.

L0065 | 2. Install dependencies. | Operational statement participating in the file's runtime behavior.

L0066 | | Blank line used for readability and logical separation.

L0067 | ```bash | Operational statement participating in the file's runtime behavior.

L0068 | pip install -r requirements.txt | Operational statement participating in the file's runtime behavior.

L0069 | ``` | Operational statement participating in the file's runtime behavior.

L0070 | | Blank line used for readability and logical separation.

L0071 | 3. Set up PostgreSQL and update `.env`. | Operational statement participating in the file's runtime behavior.

L0072 | | Blank line used for readability and logical separation.

L0073 | 4. Run migrations if you are managing schema changes through Flask-Migrate. | Operational statement participating in the file's runtime behavior.

L0074 | | Blank line used for readability and logical separation.

L0075 | ```bash | Operational statement participating in the file's runtime behavior.

L0076 | flask db upgrade | Operational statement participating in the file's runtime behavior.

L0077 | ``` | Operational statement participating in the file's runtime behavior.

L0078 | | Blank line used for readability and logical separation.

L0079 | 5. Start the app. | Operational statement participating in the file's runtime behavior.

L0080 | | Blank line used for readability and logical separation.

L0081 | ```bash | Operational statement participating in the file's runtime behavior.

L0082 | python app.py | Operational statement participating in the file's runtime behavior.

L0083 | ``` | Operational statement participating in the file's runtime behavior.

L0084 | | Blank line used for readability and logical separation.

L0085 | Alternative local run: | Operational statement participating in the file's runtime behavior.

L0086 | | Blank line used for readability and logical separation.

L0087 | ```bash | Operational statement participating in the file's runtime behavior.

L0088 | flask --app app.py run --host 0.0.0.0 --port 5000 | Operational statement participating in the file's runtime behavior.

L0089 | ``` | Operational statement participating in the file's runtime behavior.

L0090 | | Blank line used for readability and logical separation.

L0091 | 6. Open `http://127.0.0.1:5000/login/`. | Operational statement participating in the file's runtime behavior.

L0092 | | Blank line used for readability and logical separation.

L0093 | If you do not set `DATABASE\_URL` in development, the app will use SQLite automatically. | Operational statement participating in the file's runtime behavior.

L0094 | | Blank line used for readability and logical separation.

L0095 | ## Bootstrap Registration | Comment line documenting intent or context for nearby code.

L0096 | | Blank line used for readability and logical separation.

L0097 | - The first user can be created via `/register/` and is forced to the `developer` role. | Operational statement participating in the file's runtime behavior.

L0098 | - After the first account exists, `/register/` is locked down to authenticated developers only. | Operational statement participating in the file's runtime behavior.

L0099 | - Developers create additional staff, technician, manager, and general manager accounts from the account management UI. | Operational statement participating in the file's runtime behavior.

L0100 | | Blank line used for readability and logical separation.

L0101 | ## Testing | Comment line documenting intent or context for nearby code.

L0102 | | Blank line used for readability and logical separation.

L0103 | The smoke suite lives under `tests/` and uses a temporary SQLite database only when `TESTING=True`. Production and normal development use PostgreSQL. | Operational statement participating in the file's runtime behavior.

L0104 | | Blank line used for readability and logical separation.

L0105 | Run tests with: | Operational statement participating in the file's runtime behavior.

L0106 | | Blank line used for readability and logical separation.

L0107 | ```bash | Operational statement participating in the file's runtime behavior.

L0108 | pytest | Operational statement participating in the file's runtime behavior.

L0109 | ``` | Operational statement participating in the file's runtime behavior.

L0110 | | Blank line used for readability and logical separation.

L0111 | Current smoke coverage includes: | Operational statement participating in the file's runtime behavior.

L0112 | | Blank line used for readability and logical separation.

L0113 | - anonymous redirect for protected dashboard access | Operational statement participating in the file's runtime behavior.

L0114 | - first-user registration bootstrap behavior | Operational statement participating in the file's runtime behavior.

L0115 | - registration lock-down after bootstrap | Operational statement participating in the file's runtime behavior.

L0116 | - CSRF-aware developer login | Operational statement participating in the file's runtime behavior.

L0117 | - authenticated consumable API create flow using server-side identity | Operational statement participating in the file's runtime behavior.

L0118 | | Blank line used for readability and logical separation.

L0119 | ## Quick Validation | Comment line documenting intent or context for nearby code.

L0120 | | Blank line used for readability and logical separation.

L0121 | Syntax check: | Operational statement participating in the file's runtime behavior.

L0122 | | Blank line used for readability and logical separation.

L0123 | ```bash | Operational statement participating in the file's runtime behavior.

L0124 | python -m compileall -q . | Operational statement participating in the file's runtime behavior.

L0125 | ``` | Operational statement participating in the file's runtime behavior.

L0126 | | Blank line used for readability and logical separation.

L0127 | List routes: | Operational statement participating in the file's runtime behavior.

L0128 | | Blank line used for readability and logical separation.

L0129 | ```bash | Operational statement participating in the file's runtime behavior.

L0130 | flask --app app.py routes | Operational statement participating in the file's runtime behavior.

L0131 | ``` | Operational statement participating in the file's runtime behavior.

L0132 | | Blank line used for readability and logical separation.

L0133 | Run maintenance tasks outside the request cycle: | Operational statement participating in the file's runtime behavior.

L0134 | | Blank line used for readability and logical separation.

L0135 | ```bash | Operational statement participating in the file's runtime behavior.

L0136 | flask --app app.py run-maintenance | Operational statement participating in the file's runtime behavior.

L0137 | ``` | Operational statement participating in the file's runtime behavior.

L0138 | | Blank line used for readability and logical separation.

L0139 | ## Docker Deployment | Comment line documenting intent or context for nearby code.

L0140 | | Blank line used for readability and logical separation.

L0141 | This repository now includes a `Dockerfile`, `.dockerignore`, and `docker-compose.yml`. | Operational statement participating in the file's runtime behavior.

L0142 | | Blank line used for readability and logical separation.

L0143 | Start the stack: | Operational statement participating in the file's runtime behavior.

L0144 | | Blank line used for readability and logical separation.

L0145 | ```bash | Operational statement participating in the file's runtime behavior.

L0146 | docker compose up --build | Operational statement participating in the file's runtime behavior.

L0147 | ``` | Operational statement participating in the file's runtime behavior.

L0148 | | Blank line used for readability and logical separation.

L0149 | Services: | Operational statement participating in the file's runtime behavior.

L0150 | | Blank line used for readability and logical separation.

L0151 | - Web app: `http://localhost:8000` | Operational statement participating in the file's runtime behavior.

L0152 | - PostgreSQL: `localhost:5432` | Operational statement participating in the file's runtime behavior.

L0153 | | Blank line used for readability and logical separation.

L0154 | Compose notes: | Operational statement participating in the file's runtime behavior.

L0155 | | Blank line used for readability and logical separation.

L0156 | - The app container runs with `unicorn --factory app:create\_app` | Operational statement participating in the file's runtime behavior.

L0157 | - Compose overrides `DATABASE\_URL` to point at the `db` service | Operational statement participating in the file's runtime behavior.

L0158 | - Uploaded files are persisted through the `./uploads` bind mount | Operational statement participating in the file's runtime behavior.

L0159 | - PostgreSQL data is persisted in the `postgres-data` volume | Operational statement participating in the file's runtime behavior.

L0160 | | Blank line used for readability and logical separation.

L0161 | ### Production-Like HTTPS (Recommended Path) | Comment line documenting intent or context for nearby code.

L0162 | | Blank line used for readability and logical separation.

L0163 | This project includes an HTTPS overlay using Caddy as a reverse proxy in front of Unicorn. | Operational statement participating in the file's runtime behavior.

L0164 | | Blank line used for readability and logical separation.

L0165 | Files: | Operational statement participating in the file's runtime behavior.

L0166 | | Blank line used for readability and logical separation.

L0167 | - `Caddyfile` | Operational statement participating in the file's runtime behavior.

L0168 | - `docker-compose.https.yml` | Operational statement participating in the file's runtime behavior.

L0169 | | Blank line used for readability and logical separation.

L0170 | What this gives you: | Operational statement participating in the file's runtime behavior.

L0171 | | Blank line used for readability and logical separation.

L0172 | - TLS termination at the edge (port 443) | Operational statement participating in the file's runtime behavior.

L0173 | - HTTP -> HTTPS redirection | Operational statement participating in the file's runtime behavior.

L0174 | - `SESSION\_COOKIE\_SECURE=1` for secure cookies | Assignment statement storing or updating program state.

L0175 | - App still runs behind Gunicorn (`web:8000`) and is not exposed directly | Operational statement participating in the file's runtime behavior.

L0176 | | Blank line used for readability and logical separation.

L0177 | 1. Set your host name or LAN IP in `.env`: | Operational statement participating in the file's runtime behavior.

L0178 | | Blank line used for readability and logical separation.

L0179 | ```bash | Operational statement participating in the file's runtime behavior.

L0180 | set SERVER_NAME=localhost | Assignment statement storing or updating program state.

L0181 | ``` | Operational statement participating in the file's runtime behavior.

L0182 | | Blank line used for readability and logical separation.

L0183 | For LAN testing from other devices, use your host IP instead: | Operational statement participating in the file's runtime behavior.

L0184 | | Blank line used for readability and logical separation.

L0185 | ```bash | Operational statement participating in the file's runtime behavior.

L0186 | set SERVER_NAME=172.16.0.62 | Assignment statement storing or updating program state.

L0187 | ``` | Operational statement participating in the file's runtime behavior.

L0188 | | Blank line used for readability and logical separation.

L0189 | 2. Start the base stack plus HTTPS overlay: | Operational statement participating in the file's runtime behavior.

L0190 | | Blank line used for readability and logical separation.

L0191 | ```bash | Operational statement participating in the file's runtime behavior.

L0192 | docker compose -f docker-compose.yml -f docker-compose.https.yml up --build -d | Operational statement participating in the file's runtime behavior.

L0193 | ``` | Operational statement participating in the file's runtime behavior.

L0194 | | Blank line used for readability and logical separation.

L0195 | 3. Open the app over HTTPS: | Operational statement participating in the file's runtime behavior.

L0196 | | Blank line used for readability and logical separation.

L0197 | ```text | Operational statement participating in the file's runtime behavior.

L0198 | https://localhost | Operational statement participating in the file's runtime behavior.

L0199 | ``` | Operational statement participating in the file's runtime behavior.

L0200 | | Blank line used for readability and logical separation.

L0201 | or | Operational statement participating in the file's runtime behavior.

L0202 | | Blank line used for readability and logical separation.

L0203 | ```text | Operational statement participating in the file's runtime behavior.

L0204 | https://172.16.0.62 | Operational statement participating in the file's runtime behavior.

L0205 | ``` | Operational statement participating in the file's runtime behavior.

L0206 | | Blank line used for readability and logical separation.

L0207 | 4. Stop the HTTPS stack: | Operational statement participating in the file's runtime behavior.

L0208 | | Blank line used for readability and logical separation.

L0209 | ```bash | Operational statement participating in the file's runtime behavior.

L0210 | docker compose -f docker-compose.yml -f docker-compose.https.yml down | Operational statement participating in the file's runtime behavior.

L0211 | ``` | Operational statement participating in the file's runtime behavior.

L0212 | | Blank line used for readability and logical separation.

L0213 | Notes: | Operational statement participating in the file's runtime behavior.

L0214 | | Blank line used for readability and logical separation.

L0215 | - Caddy is configured with internal certificates (`tls internal`), which is ideal for production-like local/LAN testing. | Operational statement participating in the file's runtime behavior.

L0216 | - Browsers may warn until the local CA is trusted on each client device. | Operational statement participating in the file's runtime behavior.

L0217 | - In true public production, switch to a real domain and publicly trusted certificates. | Operational statement participating in the file's runtime behavior.

L0218 | | Blank line used for readability and logical separation.

L0219 | ## Watchdog Reporting | Comment line documenting intent or context for nearby code.

L0220 | | Blank line used for readability and logical separation.

L0221 | Use only `advanced\_watchdog\_script.py` for file-change reporting. | Operational statement participating in the file's runtime behavior.

L0222 | | Blank line used for readability and logical separation.

L0223 | The older watchdog variants were removed because they contained unsafe embedded credentials. Configure reporting through environment variables.

L0224 | | Blank line used for readability and logical separation.

L0225 | - `WATCHER\_EMAIL\_FROM` | Operational statement participating in the file's runtime behavior.

L0226 | - `WATCHER\_EMAIL\_PASSWORD` | Operational statement participating in the file's runtime behavior.

L0227 | - `WATCHER\_EMAIL\_TO` | Operational statement participating in the file's runtime behavior.

L0228 | | Blank line used for readability and logical separation.

L0229 | Run the watcher manually if needed: | Operational statement participating in the file's runtime behavior.

L0230 | | Blank line used for readability and logical separation.

L0231 | ```bash | Operational statement participating in the file's runtime behavior.

L0232 | python advanced_watchdog_script.py | Operational statement participating in the file's runtime behavior.

L0233 | ``` | Operational statement participating in the file's runtime behavior.

L0234 | | Blank line used for readability and logical separation.

L0235 | ## Storage and Uploads | Comment line documenting intent or context for nearby code.

L0236 | | Blank line used for readability and logical separation.

L0237 | - Local uploads are stored under `uploads/` | Operational statement participating in the file's runtime behavior.

L0238 | - Upload size limit is 16 MB | Operational statement participating in the file's runtime behavior.

L0239 | - Allowed file extensions are image types configured in the app | Operational statement participating in the file's runtime behavior.

L0240 | - If `S3\_BUCKET` is set, the app can upload files to S3 | Operational statement participating in the file's runtime behavior.

L0241 | | Blank line used for readability and logical separation.

L0242 | ## Main Routes | Comment line documenting intent or context for nearby code.

L0243 | | Blank line used for readability and logical separation.

L0244 | - `/login/` | Operational statement participating in the file's runtime behavior.

L0245 | - `/dashboard/` | Operational statement participating in the file's runtime behavior.

L0246 | - `/field/site-form/` | Operational statement participating in the file's runtime behavior.

L0247 | - `/desk/activities/` | Operational statement participating in the file's runtime behavior.

L0248 | - `/consumables/` | Operational statement participating in the file's runtime behavior.

L0249 | - `/notifications/` | Operational statement participating in the file's runtime behavior.

L0250 | - `/settings/` | Operational statement participating in the file's runtime behavior.

L0251 | - `/desk/approved-forms/excel` | Operational statement participating in the file's runtime behavior.

L0252 | | Blank line used for readability and logical separation.

L0253 | ## REST API | Comment line documenting intent or context for nearby code.

L0254 | | Blank line used for readability and logical separation.

L0255 | - `GET /api/dashboard-counts` | Operational statement participating in the file's runtime behavior.

L0256 | - `GET /api/consumables/` | Operational statement participating in the file's runtime behavior.

L0257 | - `GET /api/consumables/<id>/` | Operational statement participating in the file's runtime behavior.

L0258 | - `POST /api/consumables/` | Operational statement participating in the file's runtime behavior.

L0259 | - `GET /api/activities/` | Operational statement participating in the file's runtime behavior.

L0260 | | Blank line used for readability and logical separation.

L0261 | Notes: | Operational statement participating in the file's runtime behavior.

L0262 | | Blank line used for readability and logical separation.

L0263 | - API routes require authentication | Operational statement participating in the file's runtime behavior.

L0264 | - Mutating requests are CSRF-protected | Operational statement participating in the file's runtime behavior.

L0265 | - Consumable creation uses the authenticated user identity on the server side | Operational statement participating in the file's runtime behavior.

L0266 | | Blank line used for readability and logical separation.

L0267 | ## Production Notes | Comment line documenting intent or context for nearby code.

L0268 | | Blank line used for readability and logical separation.

L0269 | - Set a strong `SECRET\_KEY` | Operational statement participating in the file's runtime behavior.

L0270 | - Set `APP\_ENV=production` | Assignment statement storing or updating program state.

L0271 | - Set `SESSION\_COOKIE\_SECURE=1` behind HTTPS | Assignment statement storing or updating program state.

L0272 | - Point `PUBLIC\_BASE\_URL` at the public domain used for login links | Operational statement participating in the file's runtime behavior.

L0273 | - Set `REDIS\_URL` in multi-instance deployments so login throttling is shared across workers | Operational statement participating in the file's runtime behavior.

L0274 | - Prefer `ENABLE\_INLINE\_AUTOMATIONS=0` in production and execute `flask --app app.py run-maintenance` from a scheduler | Assignment statement participating in the file's runtime behavior.

L0275 | - Set `ACCESS\_LOG\_ENABLED=1` to emit request IDs and latency logs for incident investigation | Assignment statement storing or updating program state.

L0276 | - Rotate any credentials that were previously committed before deploying | Operational statement participating in the file's runtime behavior.

L0277 | - Prefer structured logging and external monitoring for production incidents | Operational statement participating in the file's runtime behavior.

L0278 | - Use PostgreSQL backups such as `pg\_dump` / `pg\_restore` for disaster recovery | Operational statement participating in the file's runtime behavior.

L0279 | | Blank line used for readability and logical separation.

L0280 | ## Migration Path: SQLite to PostgreSQL | Comment line documenting intent or context for nearby code.

L0281 | | Blank line used for readability and logical separation.

L0282 | Use this flow when development is complete: | Operational statement participating in the file's runtime behavior.

L0283 | | Blank line used for readability and logical separation.

L0284 | 1. Set production-style environment values: | Operational statement participating in the file's runtime behavior.

L0285 | | Blank line used for readability and logical separation.

L0286 | ```bash | Operational statement participating in the file's runtime behavior.

L0287 | set APP_ENV=production | Assignment statement storing or updating program state.

L0288 | set DATABASE_URL=postgresql+psycopg://username:password@hostname:5432/pm_db | Assignment statement storing or updating program state.

L0289 | ``` | Operational statement participating in the file's runtime behavior.

L0290 | | Blank line used for readability and logical separation.

L0291 | 2. Run schema migrations: | Operational statement participating in the file's runtime behavior.

L0292 | | Blank line used for readability and logical separation.

L0293 | ```bash | Operational statement participating in the file's runtime behavior.

L0294 | flask db upgrade | Operational statement participating in the file's runtime behavior.

L0295 | ``` | Operational statement participating in the file's runtime behavior.

L0296 | | Blank line used for readability and logical separation.

L0297 | 3. Run smoke tests against the app and key routes. | Operational statement participating in the file's runtime behavior.

L0298 | | Blank line used for readability and logical separation.

L0299 | 4. Keep SQLite for local feature work, but validate PostgreSQL before every release. | Operational statement participating in the file's runtime behavior.

L0300 | | Blank line used for readability and logical separation.

L0301 | ## Backup and Restore | Comment line documenting intent or context for nearby code.

L0302 | | Blank line used for readability and logical separation.

L0303 | Backup: | Operational statement participating in the file's runtime behavior.

L0304 | | Blank line used for readability and logical separation.

L0305 | ```bash | Operational statement participating in the file's runtime behavior.

L0306 | pg_dump --format=custom --file=pm_backup.dump postgresql://postgres:password@localhost:5432/pm_db | Assignment statement storing or updating program state.

L0307 | ``` | Operational statement participating in the file's runtime behavior.

L0308 | | Blank line used for readability and logical separation.

L0309 | Restore: | Operational statement participating in the file's runtime behavior.

L0310 | | Blank line used for readability and logical separation.

L0311 | ```bash | Operational statement participating in the file's runtime behavior.

L0312 | pg_restore --clean --if-exists --no-owner --dbname=postgresql://postgres:password@localhost:5432/pm_db pm_backup.dump | Assignment statement storing or updating program state.

L0313 | ``` | Operational statement participating in the file's runtime behavior.

File 65: requirements.txt

L0001 | alembic==1.18.4 | Operational statement participating in the file's runtime behavior.
L0002 | asgiref==3.8.1 | Operational statement participating in the file's runtime behavior.
L0003 | blinker==1.9.0 | Operational statement participating in the file's runtime behavior.
L0004 | boto3==1.40.56 | Operational statement participating in the file's runtime behavior.
L0005 | click==8.3.1 | Operational statement participating in the file's runtime behavior.
L0006 | colorama==0.4.6 | Operational statement participating in the file's runtime behavior.
L0007 | Flask==3.1.3 | Operational statement participating in the file's runtime behavior.
L0008 | Flask-Limiter==4.1.1 | Operational statement participating in the file's runtime behavior.
L0009 | Flask-Login==0.6.3 | Operational statement participating in the file's runtime behavior.
L0010 | Flask-Migrate==4.1.0 | Operational statement participating in the file's runtime behavior.
L0011 | Flask-SQLAlchemy==3.1.1 | Operational statement participating in the file's runtime behavior.
L0012 | flake8==7.3.0 | Operational statement participating in the file's runtime behavior.
L0013 | greenlet==3.3.2 | Operational statement participating in the file's runtime behavior.
L0014 | gunicorn==23.0.0 | Operational statement participating in the file's runtime behavior.
L0015 | itsdangerous==2.2.0 | Operational statement participating in the file's runtime behavior.
L0016 | Jinja2==3.1.6 | Operational statement participating in the file's runtime behavior.
L0017 | Mako==1.3.10 | Operational statement participating in the file's runtime behavior.
L0018 | MarkupSafe==3.0.3 | Operational statement participating in the file's runtime behavior.
L0019 | pytest==8.4.2 | Operational statement participating in the file's runtime behavior.
L0020 | python-dotenv==1.2.2 | Operational statement participating in the file's runtime behavior.
L0021 | redis==6.4.0 | Operational statement participating in the file's runtime behavior.
L0022 | openpyxl==3.1.5 | Operational statement participating in the file's runtime behavior.
L0023 | Pillow==11.3.0 | Operational statement participating in the file's runtime behavior.
L0024 | pycogp[binary]==3.2.1 | Operational statement participating in the file's runtime behavior.
L0025 | reportlab==4.4.3 | Operational statement participating in the file's runtime behavior.
L0026 | SQLAlchemy==2.0.48 | Operational statement participating in the file's runtime behavior.
L0027 | typing_extensions==4.15.0 | Operational statement participating in the file's runtime behavior.
L0028 | uvicorn==0.31.1 | Operational statement participating in the file's runtime behavior.
L0029 | watchdog==6.0.0 | Operational statement participating in the file's runtime behavior.
L0030 | Werkzeug==3.1.7 | Operational statement participating in the file's runtime behavior.

File 66: run.bat

L0001 | @echo off | Decorator line that modifies the behavior of the definition below.

L0002 | "%~dp0.venv\Scripts\python.exe" "%~dp0app.py" %* | Operational statement participating in the file's runtime behavior.

File 67: scripts/backfill_activity_metrics.py

```
L0001 | from datetime import timedelta | Imports specific names from another module for direct usage.
L0002 | | Blank line used for readability and logical separation.
L0003 | from app import ( | Imports specific names from another module for direct usage.
L0004 |     SLA_HOURS_CRITICAL, | Operational statement participating in the file's runtime behavior.
L0005 |     SLA_HOURS_STANDARD, | Operational statement participating in the file's runtime behavior.
L0006 |     create_app, | Operational statement participating in the file's runtime behavior.
L0007 |     extract_risk_score_from_details, | Operational statement participating in the file's runtime behavior.
L0008 |     extract_sla_deadline_from_details, | Operational statement participating in the file's runtime behavior.
L0009 | ) | Operational statement participating in the file's runtime behavior.
L0010 | from model import Activity, db | Imports specific names from another module for direct usage.
L0011 | | Blank line used for readability and logical separation.
L0012 | | Blank line used for readability and logical separation.
L0013 | def main(): | Declares a function/method as a reusable unit of behavior.
L0014 |     app = create_app({"SEED_SAMPLE_DATA": False}) | Assignment statement storing or updating program state.
L0015 | | Blank line used for readability and logical separation.
L0016 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0017 |         query = Activity.query.filter( | Assignment statement storing or updating program state.
L0018 |             (Activity.risk_score.is_(None)) \ | (Activity.sla_deadline.is_(None)) | Operational statement participating in the file's
L0019 |             ) | Operational statement participating in the file's runtime behavior.
L0020 | | Blank line used for readability and logical separation.
L0021 |         updated = 0 | Assignment statement storing or updating program state.
L0022 |         scanned = 0 | Assignment statement storing or updating program state.
L0023 |         for activity in query.yield_per(500): | Loop iterating over a sequence to process elements one by one.
L0024 |             scanned += 1 | Assignment statement storing or updating program state.
L0025 |             changed = False | Assignment statement storing or updating program state.
L0026 | | Blank line used for readability and logical separation.
L0027 |             if activity.risk_score is None: | Conditional branch that runs only when its condition is true.
L0028 |                 risk_score = extract_risk_score_from_details(activity.details) | Assignment statement storing or updating program state.
L0029 |                 if risk_score is not None: | Conditional branch that runs only when its condition is true.
L0030 |                     activity.risk_score = risk_score | Assignment statement storing or updating program state.
L0031 |                     changed = True | Assignment statement storing or updating program state.
L0032 | | Blank line used for readability and logical separation.
L0033 |             if activity.sla_deadline is None and activity.activity_type in {"pm", "rca"}: | Conditional branch that runs only when
L0034 |                 sla_deadline = extract_sla_deadline_from_details(activity.details) | Assignment statement storing or updating program state.
L0035 |                 if sla_deadline is None: | Conditional branch that runs only when its condition is true.
L0036 |                     default_hours = SLA_HOURS_CRITICAL if activity.activity_type == "rca" else SLA_HOURS_STANDARD | Operational statement
L0037 |                     sla_deadline = activity.created_at + timedelta(hours=default_hours) | Assignment statement storing or updating program state.
L0038 |                     activity.sla_deadline = sla_deadline | Assignment statement storing or updating program state.
L0039 |                     changed = True | Assignment statement storing or updating program state.
L0040 | | Blank line used for readability and logical separation.
L0041 |             if changed: | Conditional branch that runs only when its condition is true.
L0042 |                 updated += 1 | Assignment statement storing or updating program state.
L0043 | | Blank line used for readability and logical separation.
L0044 |             if updated: | Conditional branch that runs only when its condition is true.
L0045 |                 db.session.commit() | Operational statement participating in the file's runtime behavior.
L0046 | | Blank line used for readability and logical separation.
L0047 |             print(f"Scanned {scanned} activities; updated {updated} rows.") | Operational statement participating in the file's runtime behavior.
L0048 | | Blank line used for readability and logical separation.
L0049 | | Blank line used for readability and logical separation.
L0050 | if __name__ == "__main__": | Conditional branch that runs only when its condition is true.
L0051 |     main() | Operational statement participating in the file's runtime behavior.
```


File 68: scripts/generate_project_book.py

```
L0001 | from __future__ import annotations | Imports specific names from another module for direct usage.
L0002 | | Blank line used for readability and logical separation.
L0003 | import ast | Imports dependency modules: ast.
L0004 | import html | Imports dependency modules: html.
L0005 | import re | Imports dependency modules: re.
L0006 | from collections import Counter, defaultdict | Imports specific names from another module for direct usage.
L0007 | from datetime import datetime | Imports specific names from another module for direct usage.
L0008 | from pathlib import Path | Imports specific names from another module for direct usage.
L0009 | from typing import Iterable | Imports specific names from another module for direct usage.
L0010 | | Blank line used for readability and logical separation.
L0011 | from reportlab.lib import colors | Imports specific names from another module for direct usage.
L0012 | from reportlab.lib.pagesizes import A4 | Imports specific names from another module for direct usage.
L0013 | from reportlab.lib.styles import ParagraphStyle, getSampleStyleSheet | Imports specific names from another module for direct usage.
L0014 | from reportlab.platypus import ( | Imports specific names from another module for direct usage.
L0015 |     PageBreak, | Operational statement participating in the file's runtime behavior.
L0016 |     Paragraph, | Operational statement participating in the file's runtime behavior.
L0017 |     Preformatted, | Operational statement participating in the file's runtime behavior.
L0018 |     SimpleDocTemplate, | Operational statement participating in the file's runtime behavior.
L0019 |     Spacer, | Operational statement participating in the file's runtime behavior.
L0020 |     Table, | Operational statement participating in the file's runtime behavior.
L0021 |     TableStyle, | Operational statement participating in the file's runtime behavior.
L0022 | ) | Operational statement participating in the file's runtime behavior.
L0023 | from reportlab.platypus.tableofcontents import TableOfContents | Imports specific names from another module for direct usage.
L0024 | | Blank line used for readability and logical separation.
L0025 | | Blank line used for readability and logical separation.
L0026 | ROOT = Path(__file__).resolve().parents[1] | Assignment statement storing or updating program state.
L0027 | DOCS_DIR = ROOT / "docs" | Assignment statement storing or updating program state.
L0028 | MARKDOWN_OUT = DOCS_DIR / "PROJECT_BOOK.md" | Assignment statement storing or updating program state.
L0029 | PDF_OUT = DOCS_DIR / "PROJECT_BOOK.pdf" | Assignment statement storing or updating program state.
L0030 | | Blank line used for readability and logical separation.
L0031 | IGNORE_DIRS = { | Assignment statement storing or updating program state.
L0032 |     ".git", | Operational statement participating in the file's runtime behavior.
L0033 |     ".venv", | Operational statement participating in the file's runtime behavior.
L0034 |     "venv", | Operational statement participating in the file's runtime behavior.
L0035 |     "__pycache__", | Operational statement participating in the file's runtime behavior.
L0036 |     ".mypy_cache", | Operational statement participating in the file's runtime behavior.
L0037 |     ".pytest_cache", | Operational statement participating in the file's runtime behavior.
L0038 |     "node_modules", | Operational statement participating in the file's runtime behavior.
L0039 |     "uploads", | Operational statement participating in the file's runtime behavior.
L0040 |     "tinious", | Operational statement participating in the file's runtime behavior.
L0041 |     "photo\\_doc_extract", | Operational statement participating in the file's runtime behavior.
L0042 |     "docs", | Operational statement participating in the file's runtime behavior.
L0043 | } | Block delimiter controlling scope/structure in this language.
L0044 | | Blank line used for readability and logical separation.
L0045 | TEXT_EXTENSIONS = { | Assignment statement storing or updating program state.
L0046 |     ".py", | Operational statement participating in the file's runtime behavior.
L0047 |     ".md", | Operational statement participating in the file's runtime behavior.
L0048 |     ".txt", | Operational statement participating in the file's runtime behavior.
L0049 |     ".json", | Operational statement participating in the file's runtime behavior.
L0050 |     ".yaml", | Operational statement participating in the file's runtime behavior.
L0051 |     ".yml", | Operational statement participating in the file's runtime behavior.
L0052 |     ".ini", | Operational statement participating in the file's runtime behavior.
L0053 |     ".cfg", | Operational statement participating in the file's runtime behavior.
```

```

L0054 |     ".toml", | Operational statement participating in the file's runtime behavior.
L0055 |     ".html", | Operational statement participating in the file's runtime behavior.
L0056 |     ".css", | Operational statement participating in the file's runtime behavior.
L0057 |     ".js", | Operational statement participating in the file's runtime behavior.
L0058 |     ".bat", | Operational statement participating in the file's runtime behavior.
L0059 |     ".sql", | Operational statement participating in the file's runtime behavior.
L0060 |     ".csv", | Operational statement participating in the file's runtime behavior.
L0061 |     ".mako", | Operational statement participating in the file's runtime behavior.
L0062 |     ".env", | Operational statement participating in the file's runtime behavior.
L0063 | } | Block delimiter controlling scope/structure in this language.
L0064 | | Blank line used for readability and logical separation.
L0065 | | Blank line used for readability and logical separation.
L0066 | def normalize_dir_name(p: Path) -> str: | Declares a function/method as a reusable unit of behavior.
L0067 |     return str(p).replace("/", "\\").lower() | Returns a value (or control) back to the caller.
L0068 | | Blank line used for readability and logical separation.
L0069 | | Blank line used for readability and logical separation.
L0070 | def should_skip_dir(path: Path) -> bool: | Declares a function/method as a reusable unit of behavior.
L0071 |     norm = normalize_dir_name(path) | Assignment statement storing or updating program state.
L0072 |     for ignored in IGNORE_DIRS: | Loop iterating over a sequence to process elements one by one.
L0073 |         if ignored.lower() in norm: | Conditional branch that runs only when its condition is true.
L0074 |             return True | Returns a value (or control) back to the caller.
L0075 |     return False | Returns a value (or control) back to the caller.
L0076 | | Blank line used for readability and logical separation.
L0077 | | Blank line used for readability and logical separation.
L0078 | def is_probably_text_file(path: Path) -> bool: | Declares a function/method as a reusable unit of behavior.
L0079 |     if path.suffix.lower() in TEXT_EXTENSIONS: | Conditional branch that runs only when its condition is true.
L0080 |         return True | Returns a value (or control) back to the caller.
L0081 |     try: | Starts an exception handling block for risky operations.
L0082 |         chunk = path.read_bytes()[:4096] | Assignment statement storing or updating program state.
L0083 |     except OSError: | Handles errors raised in the associated try block.
L0084 |         return False | Returns a value (or control) back to the caller.
L0085 |     return b"\x00" not in chunk | Returns a value (or control) back to the caller.
L0086 | | Blank line used for readability and logical separation.
L0087 | | Blank line used for readability and logical separation.
L0088 | def iter_project_files(root: Path) -> Iterable[Path]: | Declares a function/method as a reusable unit of behavior.
L0089 |     for p in sorted(root.rglob("*")): | Loop iterating over a sequence to process elements one by one.
L0090 |         if not p.is_file(): | Conditional branch that runs only when its condition is true.
L0091 |             continue | Flow-control keyword affecting execution in the current block.
L0092 |         rel = p.relative_to(root) | Assignment statement storing or updating program state.
L0093 |         if should_skip_dir(rel.parent): | Conditional branch that runs only when its condition is true.
L0094 |             continue | Flow-control keyword affecting execution in the current block.
L0095 |         if p.name in {"PROJECT_BOOK.md", "PROJECT_BOOK.pdf"}: | Conditional branch that runs only when its condition is true.
L0096 |             continue | Flow-control keyword affecting execution in the current block.
L0097 |         if not is_probably_text_file(p): | Conditional branch that runs only when its condition is true.
L0098 |             continue | Flow-control keyword affecting execution in the current block.
L0099 |         yield p | Operational statement participating in the file's runtime behavior.
L0100 | | Blank line used for readability and logical separation.
L0101 | | Blank line used for readability and logical separation.
L0102 | def read_text_file(path: Path) -> list[str]: | Declares a function/method as a reusable unit of behavior.
L0103 |     for encoding in ("utf-8", "utf-8-sig", "latin-1"): | Loop iterating over a sequence to process elements one by one.
L0104 |         try: | Starts an exception handling block for risky operations.
L0105 |             return path.read_text(encoding=encoding).splitlines() | Returns a value (or control) back to the caller.
L0106 |         except UnicodeDecodeError: | Handles errors raised in the associated try block.
L0107 |             continue | Flow-control keyword affecting execution in the current block.
L0108 |     return ["<unreadable text file>"] | Returns a value (or control) back to the caller.

```

```

L0109 | | Blank line used for readability and logical separation.
L0110 | | Blank line used for readability and logical separation.
L0111 | def infer_file_topics(path: Path, lines: list[str]) -> list[str]: | Declares a function/method as a reusable unit of behavior.
L0112 |     content = "\n".join(lines).lower() | Assignment statement storing or updating program state.
L0113 |     topics = [] | Assignment statement storing or updating program state.
L0114 |     if path.suffix == ".py": | Conditional branch that runs only when its condition is true.
L0115 |         topics.append("python") | Operational statement participating in the file's runtime behavior.
L0116 |     if "flask" in content: | Conditional branch that runs only when its condition is true.
L0117 |         topics.append("flask web routing") | Operational statement participating in the file's runtime behavior.
L0118 |     if "sqlalchemy" in content: | Conditional branch that runs only when its condition is true.
L0119 |         topics.append("database orm") | Operational statement participating in the file's runtime behavior.
L0120 |     if "alembic" in content or "migration" in content: | Conditional branch that runs only when its condition is true.
L0121 |         topics.append("database migrations") | Operational statement participating in the file's runtime behavior.
L0122 |     if "jinja" in content or "{%" in content: | Conditional branch that runs only when its condition is true.
L0123 |         topics.append("templating") | Operational statement participating in the file's runtime behavior.
L0124 |     if path.suffix == ".html": | Conditional branch that runs only when its condition is true.
L0125 |         topics.append("frontend markup") | Operational statement participating in the file's runtime behavior.
L0126 |     if path.suffix == ".css": | Conditional branch that runs only when its condition is true.
L0127 |         topics.append("styling") | Operational statement participating in the file's runtime behavior.
L0128 |     if "pytest" in content or "def test_" in content: | Conditional branch that runs only when its condition is true.
L0129 |         topics.append("testing") | Operational statement participating in the file's runtime behavior.
L0130 |     if path.suffix in {".yaml", ".yml", ".ini", ".cfg", ".toml", ".env"}: | Conditional branch that runs only when its condition is true.
L0131 |         topics.append("configuration") | Operational statement participating in the file's runtime behavior.
L0132 |     if path.name.lower().startswith("docker") or "docker" in content: | Conditional branch that runs only when its condition is true.
L0133 |         topics.append("containerization") | Operational statement participating in the file's runtime behavior.
L0134 |     if "csrf" in content or "auth" in path.parts: | Conditional branch that runs only when its condition is true.
L0135 |         topics.append("security/authentication") | Operational statement participating in the file's runtime behavior.
L0136 |     return sorted(set(topics)) | Returns a value (or control) back to the caller.
L0137 | | Blank line used for readability and logical separation.
L0138 | | Blank line used for readability and logical separation.
L0139 | def extract_python_imports(source: str) -> list[str]: | Declares a function/method as a reusable unit of behavior.
L0140 |     imports: list[str] = [] | Assignment statement storing or updating program state.
L0141 |     try: | Starts an exception handling block for risky operations.
L0142 |         tree = ast.parse(source) | Assignment statement storing or updating program state.
L0143 |     except SyntaxError: | Handles errors raised in the associated try block.
L0144 |         return imports | Returns a value (or control) back to the caller.
L0145 |     for node in ast.walk(tree): | Loop iterating over a sequence to process elements one by one.
L0146 |         if isinstance(node, ast.Import): | Conditional branch that runs only when its condition is true.
L0147 |             for name in node.names: | Loop iterating over a sequence to process elements one by one.
L0148 |                 imports.append(name.name.split(".")[0]) | Operational statement participating in the file's runtime behavior.
L0149 |             elif isinstance(node, ast.ImportFrom) and node.module: | Conditional branch that runs only when its condition is true.
L0150 |                 imports.append(node.module.split(".")[0]) | Operational statement participating in the file's runtime behavior.
L0151 |     return sorted(set(imports)) | Returns a value (or control) back to the caller.
L0152 | | Blank line used for readability and logical separation.
L0153 | | Blank line used for readability and logical separation.
L0154 | def explain_line(line: str) -> str: | Declares a function/method as a reusable unit of behavior.
L0155 |     stripped = line.strip() | Assignment statement storing or updating program state.
L0156 |     if not stripped: | Conditional branch that runs only when its condition is true.
L0157 |         return "Blank line used for readability and logical separation." | Returns a value (or control) back to the caller.
L0158 |     if stripped.startswith("#"): | Conditional branch that runs only when its condition is true.
L0159 |         return "Comment line documenting intent or context for nearby code." | Returns a value (or control) back to the caller.
L0160 |     if stripped.startswith('"""') or stripped.startswith('\'\'\''): | Conditional branch that runs only when its condition is true.
L0161 |         return "Docstring boundary used to describe a module, class, or function." | Returns a value (or control) back to the caller.
L0162 |     if stripped.startswith("import "): | Conditional branch that runs only when its condition is true.
L0163 |         modules = stripped.replace("import", "", 1).strip() | Assignment statement storing or updating program state.

```

```

L0164 |         return f"Imports dependency modules: {modules}." | Returns a value (or control) back to the caller.
L0165 |     if stripped.startswith("from "): | Conditional branch that runs only when its condition is true.
L0166 |         return "Imports specific names from another module for direct usage." | Returns a value (or control) back to the caller.
L0167 |     if stripped.startswith("@"): | Conditional branch that runs only when its condition is true.
L0168 |         return "Decorator line that modifies the behavior of the definition below." | Returns a value (or control) back to the caller.
L0169 |     if re.match(r"^class\s+\w+", stripped): | Conditional branch that runs only when its condition is true.
L0170 |         return "Declares a class that groups related state and behavior." | Returns a value (or control) back to the caller.
L0171 |     if re.match(r"^def\s+\w+", stripped) or re.match(r"^async\s+def\s+\w+", stripped): | Conditional branch that runs only when its condition is true.
L0172 |         return "Declares a function/method as a reusable unit of behavior." | Returns a value (or control) back to the caller.
L0173 |     if stripped.startswith(("if ", "elif ")): | Conditional branch that runs only when its condition is true.
L0174 |         return "Conditional branch that runs only when its condition is true." | Returns a value (or control) back to the caller.
L0175 |     if stripped == "else:": | Conditional branch that runs only when its condition is true.
L0176 |         return "Fallback branch executed when prior conditions are false." | Returns a value (or control) back to the caller.
L0177 |     if stripped.startswith("for "): | Conditional branch that runs only when its condition is true.
L0178 |         return "Loop iterating over a sequence to process elements one by one." | Returns a value (or control) back to the caller.
L0179 |     if stripped.startswith("while "): | Conditional branch that runs only when its condition is true.
L0180 |         return "Loop that repeats while its condition remains true." | Returns a value (or control) back to the caller.
L0181 |     if stripped.startswith("try:"): | Conditional branch that runs only when its condition is true.
L0182 |         return "Starts an exception handling block for risky operations." | Returns a value (or control) back to the caller.
L0183 |     if stripped.startswith("except"): | Conditional branch that runs only when its condition is true.
L0184 |         return "Handles errors raised in the associated try block." | Returns a value (or control) back to the caller.
L0185 |     if stripped.startswith("finally:"): | Conditional branch that runs only when its condition is true.
L0186 |         return "Runs cleanup logic regardless of success or failure." | Returns a value (or control) back to the caller.
L0187 |     if stripped.startswith("with "): | Conditional branch that runs only when its condition is true.
L0188 |         return "Context manager block for safe setup and automatic cleanup." | Returns a value (or control) back to the caller.
L0189 |     if stripped.startswith("return"): | Conditional branch that runs only when its condition is true.
L0190 |         return "Returns a value (or control) back to the caller." | Returns a value (or control) back to the caller.
L0191 |     if stripped.startswith("raise "): | Conditional branch that runs only when its condition is true.
L0192 |         return "Raises an explicit exception to signal an error condition." | Returns a value (or control) back to the caller.
L0193 |     if stripped in {"pass", "continue", "break"}: | Conditional branch that runs only when its condition is true.
L0194 |         return "Flow-control keyword affecting execution in the current block." | Returns a value (or control) back to the caller.
L0195 |     if "=" in stripped and not any(op in stripped for op in ["==", "!=", ">=", "<="]): | Conditional branch that runs only when its condition is true.
L0196 |         return "Assignment statement storing or updating program state." | Returns a value (or control) back to the caller.
L0197 |     if stripped.startswith("<") and stripped.endswith(">"): | Conditional branch that runs only when its condition is true.
L0198 |         return "Markup line defining structure in an HTML-like template file." | Returns a value (or control) back to the caller.
L0199 |     if stripped.startswith(".") or stripped.startswith("#"): | Conditional branch that runs only when its condition is true.
L0200 |         return "CSS selector line choosing the elements styled below." | Returns a value (or control) back to the caller.
L0201 |     if stripped.endswith("{") or stripped.endswith("}"): | Conditional branch that runs only when its condition is true.
L0202 |         return "Block delimiter controlling scope/structure in this language." | Returns a value (or control) back to the caller.
L0203 |     return "Operational statement participating in the file's runtime behavior." | Returns a value (or control) back to the caller.
L0204 | | Blank line used for readability and logical separation.
L0205 | | Blank line used for readability and logical separation.
L0206 | def build_file_record(path: Path) -> dict: | Declares a function/method as a reusable unit of behavior.
L0207 |     rel = path.relative_to(ROOT) | Assignment statement storing or updating program state.
L0208 |     lines = read_text_file(path) | Assignment statement storing or updating program state.
L0209 |     text = "\n".join(lines) | Assignment statement storing or updating program state.
L0210 |     topics = infer_file_topics(rel, lines) | Assignment statement storing or updating program state.
L0211 | | Blank line used for readability and logical separation.
L0212 |     imports: list[str] = [] | Assignment statement storing or updating program state.
L0213 |     if rel.suffix == ".py": | Conditional branch that runs only when its condition is true.
L0214 |         imports = extract_python_imports(text) | Assignment statement storing or updating program state.
L0215 | | Blank line used for readability and logical separation.
L0216 |     line_entries = [] | Assignment statement storing or updating program state.
L0217 |     for idx, line in enumerate(lines, start=1): | Loop iterating over a sequence to process elements one by one.
L0218 |         code = line.replace("\n", "\\n") | Assignment statement storing or updating program state.

```

```

L0219 |         explanation = explain_line(line).replace("\|", "\\|") | Assignment statement storing or updating program state.
L0220 |         line_entries.append((idx, code, explanation)) | Operational statement participating in the file's runtime behavior.
L0221 | | Blank line used for readability and logical separation.
L0222 |     return { | Returns a value (or control) back to the caller.
L0223 |         "path": str(rel).replace("\\", "/"), | Operational statement participating in the file's runtime behavior.
L0224 |         "line_count": len(lines), | Operational statement participating in the file's runtime behavior.
L0225 |         "topics": topics, | Operational statement participating in the file's runtime behavior.
L0226 |         "imports": imports, | Operational statement participating in the file's runtime behavior.
L0227 |         "line_entries": line_entries, | Operational statement participating in the file's runtime behavior.
L0228 |     } | Block delimiter controlling scope/structure in this language.
L0229 | | Blank line used for readability and logical separation.
L0230 | | Blank line used for readability and logical separation.
L0231 | def summarize_architecture(records: list[dict]) -> dict: | Declares a function/method as a reusable unit of behavior.
L0232 |     by_top_folder = Counter() | Assignment statement storing or updating program state.
L0233 |     all_topics = Counter() | Assignment statement storing or updating program state.
L0234 |     all_imports = Counter() | Assignment statement storing or updating program state.
L0235 | | Blank line used for readability and logical separation.
L0236 |     for rec in records: | Loop iterating over a sequence to process elements one by one.
L0237 |         path = rec["path"] | Assignment statement storing or updating program state.
L0238 |         top = path.split("/")[0] if "/" in path else "root" | Assignment statement storing or updating program state.
L0239 |         by_top_folder[top] += 1 | Assignment statement storing or updating program state.
L0240 |         for t in rec["topics"]: | Loop iterating over a sequence to process elements one by one.
L0241 |             all_topics[t] += 1 | Assignment statement storing or updating program state.
L0242 |         for imp in rec["imports"]: | Loop iterating over a sequence to process elements one by one.
L0243 |             all_imports[imp] += 1 | Assignment statement storing or updating program state.
L0244 | | Blank line used for readability and logical separation.
L0245 |     return { | Returns a value (or control) back to the caller.
L0246 |         "folders": by_top_folder, | Operational statement participating in the file's runtime behavior.
L0247 |         "topics": all_topics, | Operational statement participating in the file's runtime behavior.
L0248 |         "imports": all_imports, | Operational statement participating in the file's runtime behavior.
L0249 |     } | Block delimiter controlling scope/structure in this language.
L0250 | | Blank line used for readability and logical separation.
L0251 | | Blank line used for readability and logical separation.
L0252 | def write_markdown(records: list[dict], architecture: dict) -> None: | Declares a function/method as a reusable unit of behavior.
L0253 |     lines: list[str] = [] | Assignment statement storing or updating program state.
L0254 |     generated = datetime.now().strftime("%Y-%m-%d %H:%M:%S") | Assignment statement storing or updating program state.
L0255 | | Blank line used for readability and logical separation.
L0256 |     lines.append("# Project Master Book") | Operational statement participating in the file's runtime behavior.
L0257 |     lines.append("") | Operational statement participating in the file's runtime behavior.
L0258 |     lines.append(f"Generated: {generated}") | Operational statement participating in the file's runtime behavior.
L0259 |     lines.append("") | Operational statement participating in the file's runtime behavior.
L0260 |     lines.append("## Table of Contents") | Operational statement participating in the file's runtime behavior.
L0261 |     lines.append("") | Operational statement participating in the file's runtime behavior.
L0262 |     lines.append("1. Project Scope and Goals") | Operational statement participating in the file's runtime behavior.
L0263 |     lines.append("2. Architecture and System Design") | Operational statement participating in the file's runtime behavior.
L0264 |     lines.append("3. Libraries and Framework Usage") | Operational statement participating in the file's runtime behavior.
L0265 |     lines.append("4. File-by-File Deep Explanation") | Operational statement participating in the file's runtime behavior.
L0266 |     lines.append("5. Line-by-Line Explanation for Every Included File") | Operational statement participating in the file's runtime behavior.
L0267 |     lines.append("") | Operational statement participating in the file's runtime behavior.
L0268 | | Blank line used for readability and logical separation.
L0269 |     lines.append("## 1. Project Scope and Goals") | Operational statement participating in the file's runtime behavior.
L0270 |     lines.append("") | Operational statement participating in the file's runtime behavior.
L0271 |     lines.append( | Operational statement participating in the file's runtime behavior.
L0272 |         "This book explains the project in a strict sequence: high-level goals, architecture, libraries, " | Operational statement
L0273 |         "then every file with line-by-line detail." | Operational statement participating in the file's runtime behavior.

```

```

L0274 | ) | Operational statement participating in the file's runtime behavior.
L0275 | lines.append(f"Total included text files: {len(records)}") | Operational statement participating in the file's runtime behavior.
L0276 | lines.append("") | Operational statement participating in the file's runtime behavior.
L0277 | | Blank line used for readability and logical separation.
L0278 | lines.append("## 2. Architecture and System Design") | Operational statement participating in the file's runtime behavior.
L0279 | lines.append("") | Operational statement participating in the file's runtime behavior.
L0280 | lines.append("### Folder Distribution") | Operational statement participating in the file's runtime behavior.
L0281 | for folder, count in architecture["folders"].most_common(): | Loop iterating over a sequence to process elements one by one.
L0282 |     lines.append(f"- {folder}: {count} files") | Operational statement participating in the file's runtime behavior.
L0283 | lines.append("") | Operational statement participating in the file's runtime behavior.
L0284 | | Blank line used for readability and logical separation.
L0285 | lines.append("### Topic Distribution") | Operational statement participating in the file's runtime behavior.
L0286 | for topic, count in architecture["topics"].most_common(): | Loop iterating over a sequence to process elements one by one.
L0287 |     lines.append(f"- {topic}: {count} files") | Operational statement participating in the file's runtime behavior.
L0288 | lines.append("") | Operational statement participating in the file's runtime behavior.
L0289 | | Blank line used for readability and logical separation.
L0290 | lines.append("## 3. Libraries and Framework Usage") | Operational statement participating in the file's runtime behavior.
L0291 | lines.append("") | Operational statement participating in the file's runtime behavior.
L0292 | lines.append("### Python Imports Observed") | Operational statement participating in the file's runtime behavior.
L0293 | for lib, count in architecture["imports"].most_common(): | Loop iterating over a sequence to process elements one by one.
L0294 |     lines.append(f"- {lib}: referenced in {count} Python files") | Operational statement participating in the file's runtime behavior.
L0295 | lines.append("") | Operational statement participating in the file's runtime behavior.
L0296 | | Blank line used for readability and logical separation.
L0297 | lines.append("## 4. File-by-File Deep Explanation") | Operational statement participating in the file's runtime behavior.
L0298 | lines.append("") | Operational statement participating in the file's runtime behavior.
L0299 | for idx, rec in enumerate(records, start=1): | Loop iterating over a sequence to process elements one by one.
L0300 |     lines.append(f"### File {idx}: {rec['path']}") | Operational statement participating in the file's runtime behavior.
L0301 |     lines.append(f"- Line count: {rec['line_count']}") | Operational statement participating in the file's runtime behavior.
L0302 |     lines.append( | Operational statement participating in the file's runtime behavior.
L0303 |         "- Topics: " + (" ".join(rec["topics"]) if rec["topics"] else "general project support") | Operational statement parti
L0304 |     ) | Operational statement participating in the file's runtime behavior.
L0305 |     lines.append( | Operational statement participating in the file's runtime behavior.
L0306 |         "- Key libraries: " + (" ".join(rec["imports"]) if rec["imports"] else "not applicable") | Operational statement parti
L0307 |     ) | Operational statement participating in the file's runtime behavior.
L0308 |     lines.append("") | Operational statement participating in the file's runtime behavior.
L0309 | | Blank line used for readability and logical separation.
L0310 | lines.append("## 5. Line-by-Line Explanation for Every Included File") | Operational statement participating in the file's runtime
L0311 | lines.append("") | Operational statement participating in the file's runtime behavior.
L0312 | | Blank line used for readability and logical separation.
L0313 | for idx, rec in enumerate(records, start=1): | Loop iterating over a sequence to process elements one by one.
L0314 |     lines.append(f"### File {idx}: {rec['path']}") | Operational statement participating in the file's runtime behavior.
L0315 |     lines.append("") | Operational statement participating in the file's runtime behavior.
L0316 |     lines.append("\ Line \ Code \ Explanation \") | Operational statement participating in the file's runtime behavior.
L0317 |     lines.append("\---\---\---\") | Operational statement participating in the file's runtime behavior.
L0318 |     for line_no, code, explanation in rec["line_entries"]: | Loop iterating over a sequence to process elements one by one.
L0319 |         safe_code = code if len(code) <= 240 else f"{code[:237]}..." | Operational statement participating in the file's runtime
L0320 |         lines.append(f"\ {line_no} \ {safe_code} \ {explanation} \") | Operational statement participating in the file's runtime
L0321 |     lines.append("") | Operational statement participating in the file's runtime behavior.
L0322 | | Blank line used for readability and logical separation.
L0323 | DOCS_DIR.mkdir(parents=True, exist_ok=True) | Assignment statement storing or updating program state.
L0324 | MARKDOWN_OUT.write_text("\n".join(lines), encoding="utf-8") | Assignment statement storing or updating program state.
L0325 | | Blank line used for readability and logical separation.
L0326 | | Blank line used for readability and logical separation.
L0327 | class BookTemplate(SimpleDocTemplate): | Declares a class that groups related state and behavior.
L0328 |     def afterFlowable(self, flowable): | Declares a function/method as a reusable unit of behavior.

```

```

L0329 |         if isinstance(flowable, Paragraph): | Conditional branch that runs only when its condition is true.
L0330 |             style_name = flowable.style.name | Assignment statement storing or updating program state.
L0331 |             if style_name in {"Heading1", "Heading2", "Heading3"}: | Conditional branch that runs only when its condition is true.
L0332 |                 level = {"Heading1": 0, "Heading2": 1, "Heading3": 2}[style_name] | Assignment statement storing or updating program state.
L0333 |                 text = flowable.getPlainText() | Assignment statement storing or updating program state.
L0334 |                 self.notify("TOCEntry", (level, text, self.page)) | Operational statement participating in the file's runtime behavior.
L0335 | | Blank line used for readability and logical separation.
L0336 | | Blank line used for readability and logical separation.
L0337 | def write_pdf(records: list[dict], architecture: dict) -> None: | Declares a function/method as a reusable unit of behavior.
L0338 |     DOCS_DIR.mkdir(parents=True, exist_ok=True) | Assignment statement storing or updating program state.
L0339 |     styles = getSampleStyleSheet() | Assignment statement storing or updating program state.
L0340 | | Blank line used for readability and logical separation.
L0341 |     code_style = ParagraphStyle( | Assignment statement storing or updating program state.
L0342 |         "CodeLine", | Operational statement participating in the file's runtime behavior.
L0343 |         parent=styles["BodyText"], | Assignment statement storing or updating program state.
L0344 |         fontName="Courier", | Assignment statement storing or updating program state.
L0345 |         fontSize=6.7, | Assignment statement storing or updating program state.
L0346 |         leading=8, | Assignment statement storing or updating program state.
L0347 |     ) | Operational statement participating in the file's runtime behavior.
L0348 | | Blank line used for readability and logical separation.
L0349 |     body_style = ParagraphStyle( | Assignment statement storing or updating program state.
L0350 |         "DenseBody", | Operational statement participating in the file's runtime behavior.
L0351 |         parent=styles["BodyText"], | Assignment statement storing or updating program state.
L0352 |         fontSize=9, | Assignment statement storing or updating program state.
L0353 |         leading=11, | Assignment statement storing or updating program state.
L0354 |     ) | Operational statement participating in the file's runtime behavior.
L0355 | | Blank line used for readability and logical separation.
L0356 |     toc = TableOfContents() | Assignment statement storing or updating program state.
L0357 |     toc.levelStyles = [ | Assignment statement storing or updating program state.
L0358 |         ParagraphStyle(fontSize=10, name="TOCLevel1", leftIndent=20, firstLineIndent=-12, spaceBefore=4), | Assignment statement storing or updating program state.
L0359 |         ParagraphStyle(fontSize=9, name="TOCLevel2", leftIndent=36, firstLineIndent=-12, spaceBefore=2), | Assignment statement storing or updating program state.
L0360 |         ParagraphStyle(fontSize=8, name="TOCLevel3", leftIndent=52, firstLineIndent=-12, spaceBefore=1), | Assignment statement storing or updating program state.
L0361 |     ] | Operational statement participating in the file's runtime behavior.
L0362 | | Blank line used for readability and logical separation.
L0363 |     story = [] | Assignment statement storing or updating program state.
L0364 |     generated = datetime.now().strftime("%Y-%m-%d %H:%M:%S") | Assignment statement storing or updating program state.
L0365 | | Blank line used for readability and logical separation.
L0366 |     story.append(Paragraph("Project Master Book", styles["Title"])) | Operational statement participating in the file's runtime behavior.
L0367 |     story.append(Spacer(1, 8)) | Operational statement participating in the file's runtime behavior.
L0368 |     story.append(Paragraph(f"Generated: {generated}", body_style)) | Operational statement participating in the file's runtime behavior.
L0369 |     story.append(Spacer(1, 12)) | Operational statement participating in the file's runtime behavior.
L0370 | | Blank line used for readability and logical separation.
L0371 |     story.append(Paragraph("Table of Contents", styles["Heading1"])) | Operational statement participating in the file's runtime behavior.
L0372 |     story.append(toc) | Operational statement participating in the file's runtime behavior.
L0373 |     story.append(PageBreak()) | Operational statement participating in the file's runtime behavior.
L0374 | | Blank line used for readability and logical separation.
L0375 |     story.append(Paragraph("1. Project Scope and Goals", styles["Heading1"])) | Operational statement participating in the file's runtime behavior.
L0376 |     story.append( | Operational statement participating in the file's runtime behavior.
L0377 |         Paragraph( | Operational statement participating in the file's runtime behavior.
L0378 |             "This documentation explains the complete project in a strict sequence: " | Operational statement participating in the file's runtime behavior.
L0379 |             "scope, architecture, libraries, file deep-dives, then line-level explanations.", | Operational statement participating in the file's runtime behavior.
L0380 |             body_style, | Operational statement participating in the file's runtime behavior.
L0381 |         ) | Operational statement participating in the file's runtime behavior.
L0382 |     ) | Operational statement participating in the file's runtime behavior.
L0383 |     story.append(Paragraph(f"Included files: {len(records)}", body_style)) | Operational statement participating in the file's runtime behavior.

```

```

L0384 |     story.append(Spacer(1, 12)) | Operational statement participating in the file's runtime behavior.
L0385 | | Blank line used for readability and logical separation.
L0386 |     story.append(Paragraph("2. Architecture and System Design", styles["Heading1"])) | Operational statement participating in the f
L0387 |     story.append(Paragraph("Folder Distribution", styles["Heading2"])) | Operational statement participating in the file's runtime
L0388 |     folder_table_data = [{"Folder", "File Count"}] | Assignment statement storing or updating program state.
L0389 |     for folder, count in architecture["folders"].most_common(): | Loop iterating over a sequence to process elements one by one.
L0390 |         folder_table_data.append([folder, str(count)]) | Operational statement participating in the file's runtime behavior.
L0391 |     folder_table = Table(folder_table_data, colWidths=[260, 100]) | Assignment statement storing or updating program state.
L0392 |     folder_table.setStyle( | Operational statement participating in the file's runtime behavior.
L0393 |         TableStyle( | Operational statement participating in the file's runtime behavior.
L0394 |             [ | Operational statement participating in the file's runtime behavior.
L0395 |                 ("BACKGROUND", (0, 0), (-1, 0), colors.lightgrey), | Operational statement participating in the file's runtime beha
L0396 |                 ("GRID", (0, 0), (-1, -1), 0.25, colors.grey), | Operational statement participating in the file's runtime behavior
L0397 |                 ("FONTNAME", (0, 0), (-1, 0), "Helvetica-Bold"), | Operational statement participating in the file's runtime behavi
L0398 |                 ("FONTSIZE", (0, 0), (-1, -1), 8), | Operational statement participating in the file's runtime behavior.
L0399 |             ] | Operational statement participating in the file's runtime behavior.
L0400 |         ) | Operational statement participating in the file's runtime behavior.
L0401 |     ) | Operational statement participating in the file's runtime behavior.
L0402 |     story.append(folder_table) | Operational statement participating in the file's runtime behavior.
L0403 |     story.append(Spacer(1, 10)) | Operational statement participating in the file's runtime behavior.
L0404 | | Blank line used for readability and logical separation.
L0405 |     story.append(Paragraph("Topic Distribution", styles["Heading2"])) | Operational statement participating in the file's runtime b
L0406 |     topic_table_data = [{"Topic", "Files"}] | Assignment statement storing or updating program state.
L0407 |     for topic, count in architecture["topics"].most_common(): | Loop iterating over a sequence to process elements one by one.
L0408 |         topic_table_data.append([topic, str(count)]) | Operational statement participating in the file's runtime behavior.
L0409 |     topic_table = Table(topic_table_data, colWidths=[260, 100]) | Assignment statement storing or updating program state.
L0410 |     topic_table.setStyle( | Operational statement participating in the file's runtime behavior.
L0411 |         TableStyle( | Operational statement participating in the file's runtime behavior.
L0412 |             [ | Operational statement participating in the file's runtime behavior.
L0413 |                 ("BACKGROUND", (0, 0), (-1, 0), colors.lightgrey), | Operational statement participating in the file's runtime beha
L0414 |                 ("GRID", (0, 0), (-1, -1), 0.25, colors.grey), | Operational statement participating in the file's runtime behavior
L0415 |                 ("FONTNAME", (0, 0), (-1, 0), "Helvetica-Bold"), | Operational statement participating in the file's runtime behavi
L0416 |                 ("FONTSIZE", (0, 0), (-1, -1), 8), | Operational statement participating in the file's runtime behavior.
L0417 |             ] | Operational statement participating in the file's runtime behavior.
L0418 |         ) | Operational statement participating in the file's runtime behavior.
L0419 |     ) | Operational statement participating in the file's runtime behavior.
L0420 |     story.append(topic_table) | Operational statement participating in the file's runtime behavior.
L0421 |     story.append(PageBreak()) | Operational statement participating in the file's runtime behavior.
L0422 | | Blank line used for readability and logical separation.
L0423 |     story.append(Paragraph("3. Libraries and Framework Usage", styles["Heading1"])) | Operational statement participating in the fi
L0424 |     imports_table_data = [{"Library", "Python Files Referencing"}] | Assignment statement storing or updating program state.
L0425 |     for lib, count in architecture["imports"].most_common(): | Loop iterating over a sequence to process elements one by one.
L0426 |         imports_table_data.append([lib, str(count)]) | Operational statement participating in the file's runtime behavior.
L0427 |     imports_table = Table(imports_table_data, colWidths=[260, 100]) | Assignment statement storing or updating program state.
L0428 |     imports_table.setStyle( | Operational statement participating in the file's runtime behavior.
L0429 |         TableStyle( | Operational statement participating in the file's runtime behavior.
L0430 |             [ | Operational statement participating in the file's runtime behavior.
L0431 |                 ("BACKGROUND", (0, 0), (-1, 0), colors.lightgrey), | Operational statement participating in the file's runtime beha
L0432 |                 ("GRID", (0, 0), (-1, -1), 0.25, colors.grey), | Operational statement participating in the file's runtime behavior
L0433 |                 ("FONTNAME", (0, 0), (-1, 0), "Helvetica-Bold"), | Operational statement participating in the file's runtime behavi
L0434 |                 ("FONTSIZE", (0, 0), (-1, -1), 8), | Operational statement participating in the file's runtime behavior.
L0435 |             ] | Operational statement participating in the file's runtime behavior.
L0436 |         ) | Operational statement participating in the file's runtime behavior.
L0437 |     ) | Operational statement participating in the file's runtime behavior.
L0438 |     story.append(imports_table) | Operational statement participating in the file's runtime behavior.

```



```

L0439 |     story.append(PageBreak()) | Operational statement participating in the file's runtime behavior.
L0440 | | Blank line used for readability and logical separation.
L0441 |     story.append(Paragraph("4. File-by-File Deep Explanation", styles["Heading1"])) | Operational statement participating in the fi
L0442 |     for idx, rec in enumerate(records, start=1): | Loop iterating over a sequence to process elements one by one.
L0443 |         story.append(Paragraph(f"File {idx}: {html.escape(rec['path'])}", styles["Heading2"])) | Operational statement participatin
L0444 |         story.append(Paragraph(f"Line count: {rec['line_count']}", body_style)) | Operational statement participating in the file's
L0445 |         topics = ", ".join(rec["topics"]) if rec["topics"] else "general project support" | Assignment statement storing or updatin
L0446 |         imports = ", ".join(rec["imports"]) if rec["imports"] else "not applicable" | Assignment statement storing or updating prog
L0447 |         story.append(Paragraph(f"Topics: {html.escape(topics)}", body_style)) | Operational statement participating in the file's
L0448 |         story.append(Paragraph(f"Key libraries: {html.escape(imports)}", body_style)) | Operational statement participating in the
L0449 |         story.append(Spacer(1, 5)) | Operational statement participating in the file's runtime behavior.
L0450 | | Blank line used for readability and logical separation.
L0451 |     story.append(PageBreak()) | Operational statement participating in the file's runtime behavior.
L0452 |     story.append(Paragraph("5. Line-by-Line Explanation for Every Included File", styles["Heading1"])) | Operational statement part
L0453 | | Blank line used for readability and logical separation.
L0454 |     for idx, rec in enumerate(records, start=1): | Loop iterating over a sequence to process elements one by one.
L0455 |         story.append(PageBreak()) | Operational statement participating in the file's runtime behavior.
L0456 |         story.append(Paragraph(f"File {idx}: {html.escape(rec['path'])}", styles["Heading2"])) | Operational statement participatin
L0457 |         story.append(Spacer(1, 4)) | Operational statement participating in the file's runtime behavior.
L0458 |         for line_no, code, explanation in rec["line_entries"]: | Loop iterating over a sequence to process elements one by one.
L0459 |             safe_code = code if len(code) <= 180 else f"{code[:177]}..." | Operational statement participating in the file's runtim
L0460 |             item = f"L{line_no:04d} \ | {safe_code} \ | {explanation}" | Assignment statement storing or updating program state.
L0461 |             story.append(Preformatted(item, code_style)) | Operational statement participating in the file's runtime behavior.
L0462 | | Blank line used for readability and logical separation.
L0463 |     doc = BookTemplate(str(PDF_OUT), pagesize=A4, leftMargin=32, rightMargin=32, topMargin=28, bottomMargin=28) | Assignment statem
L0464 |     doc.multiBuild(story) | Operational statement participating in the file's runtime behavior.
L0465 | | Blank line used for readability and logical separation.
L0466 | | Blank line used for readability and logical separation.
L0467 | def main() -> None: | Declares a function/method as a reusable unit of behavior.
L0468 |     files = [build_file_record(path) for path in iter_project_files(ROOT)] | Assignment statement storing or updating program state
L0469 |     architecture = summarize_architecture(files) | Assignment statement storing or updating program state.
L0470 |     write_markdown(files, architecture) | Operational statement participating in the file's runtime behavior.
L0471 |     write_pdf(files, architecture) | Operational statement participating in the file's runtime behavior.
L0472 |     print(f"Generated: {MARKDOWN_OUT}") | Operational statement participating in the file's runtime behavior.
L0473 |     print(f"Generated: {PDF_OUT}") | Operational statement participating in the file's runtime behavior.
L0474 |     print(f"Included files: {len(files)}") | Operational statement participating in the file's runtime behavior.
L0475 | | Blank line used for readability and logical separation.
L0476 | | Blank line used for readability and logical separation.
L0477 | if __name__ == "__main__": | Conditional branch that runs only when its condition is true.
L0478 |     main() | Operational statement participating in the file's runtime behavior.

```

File 69: SDLC_STAGE_REPORT.md

```
L0001 | # SDLC Stage Report (Development, Testing, Staging, Production) | Comment line documenting intent or context for nearby code.
L0002 | | Blank line used for readability and logical separation.
L0003 | ## Scope | Comment line documenting intent or context for nearby code.
L0004 | This report summarizes an execution-based readiness check across four stages: | Operational statement participating in the file's runtime behavior.
L0005 | 1. Development | Operational statement participating in the file's runtime behavior.
L0006 | 2. Testing | Operational statement participating in the file's runtime behavior.
L0007 | 3. Staging | Operational statement participating in the file's runtime behavior.
L0008 | 4. Production | Operational statement participating in the file's runtime behavior.
L0009 | | Blank line used for readability and logical separation.
L0010 | ## Stage 1: Development | Comment line documenting intent or context for nearby code.
L0011 | | Blank line used for readability and logical separation.
L0012 | ### Checks run | Comment line documenting intent or context for nearby code.
L0013 | - Dependency consistency (`pip check`) | Operational statement participating in the file's runtime behavior.
L0014 | - Lint availability/execution (`python -m flake8 app.py pm_app tests`) | Operational statement participating in the file's runtime behavior.
L0015 | - Bytecode compile sanity (`python -m compileall -q app.py pm_app tests`) | Operational statement participating in the file's runtime behavior.
L0016 | | Blank line used for readability and logical separation.
L0017 | ### Evidence | Comment line documenting intent or context for nearby code.
L0018 | - `No broken requirements found.` from `stage_dev_pip_check.txt` | Operational statement participating in the file's runtime behavior.
L0019 | - `No module named flake8` from `stage_dev_flake8.txt` | Operational statement participating in the file's runtime behavior.
L0020 | - Compile status `PASS` from `stage_dev_compile_status.txt` | Operational statement participating in the file's runtime behavior.
L0021 | | Blank line used for readability and logical separation.
L0022 | ### Status | Comment line documenting intent or context for nearby code.
L0023 | - **Conditional pass** | Operational statement participating in the file's runtime behavior.
L0024 | | Blank line used for readability and logical separation.
L0025 | ### Findings | Comment line documenting intent or context for nearby code.
L0026 | - Dependencies are internally consistent. | Operational statement participating in the file's runtime behavior.
L0027 | - Code compiles successfully. | Operational statement participating in the file's runtime behavior.
L0028 | - Lint gate is currently blocked because `flake8` is not installed in the active virtual environment. | Operational statement participating in the file's runtime behavior.
L0029 | | Blank line used for readability and logical separation.
L0030 | ## Stage 2: Testing | Comment line documenting intent or context for nearby code.
L0031 | | Blank line used for readability and logical separation.
L0032 | ### Checks run | Comment line documenting intent or context for nearby code.
L0033 | - Full regression evidence (existing run): `pytest_latest.txt` | Operational statement participating in the file's runtime behavior.
L0034 | - Fresh targeted spot check: `python -m pytest tests/test_auth.py -q --maxfail=1` | Assignment statement storing or updating program state.
L0035 | | Blank line used for readability and logical separation.
L0036 | ### Evidence | Comment line documenting intent or context for nearby code.
L0037 | - `2 failed, 46 passed, 4 warnings` in `pytest_latest.txt` | Operational statement participating in the file's runtime behavior.
L0038 | - Failures: `tests/test_notifications.py::test_sender_can_delete_own_message` and `tests/test_notifications.py::test_non_sender_cannot_delete` | Operational statement participating in the file's runtime behavior.
L0039 | - Fresh run shows teardown instability after test execution: | Operational statement participating in the file's runtime behavior.
L0040 | - `KeyboardInterrupt` | Operational statement participating in the file's runtime behavior.
L0041 | - final exception in teardown path: `KeyError` from `_pytest/tmpdir.py` stash handling | Operational statement participating in the file's runtime behavior.
L0042 | | Blank line used for readability and logical separation.
L0043 | ### Status | Comment line documenting intent or context for nearby code.
L0044 | - **Fail** | Operational statement participating in the file's runtime behavior.
L0045 | | Blank line used for readability and logical separation.
L0046 | ### Findings | Comment line documenting intent or context for nearby code.
L0047 | - Functional regressions exist in notification delete-message behavior. | Operational statement participating in the file's runtime behavior.
L0048 | - Test environment/tooling is unstable during teardown, reducing confidence in deterministic CI outcomes. | Operational statement participating in the file's runtime behavior.
L0049 | | Blank line used for readability and logical separation.
L0050 | ## Stage 3: Staging | Comment line documenting intent or context for nearby code.
L0051 | | Blank line used for readability and logical separation.
L0052 | ### Checks run | Comment line documenting intent or context for nearby code.
L0053 | - Flask app smoke checks via test client (programmatic run): | Operational statement participating in the file's runtime behavior.
```

L0054 | - `GET /login` | Operational statement participating in the file's runtime behavior.

L0055 | - `GET /` | Operational statement participating in the file's runtime behavior.

L0056 | - `GET /this-route-should-not-exist` | Operational statement participating in the file's runtime behavior.

L0057 | - security header probe (`X-Content-Type-Options`) | Operational statement participating in the file's runtime behavior.

L0058 | | Blank line used for readability and logical separation.

L0059 | ### Evidence | Comment line documenting intent or context for nearby code.

L0060 | - Output: `{ "login\_status": 200, "root\_status": 302, "missing\_status": 404, "x\_content\_type\_options\_login": "nosniff"}` | Operational statement participating in the file's runtime behavior.

L0061 | | Blank line used for readability and logical separation.

L0062 | ### Status | Comment line documenting intent or context for nearby code.

L0063 | - **Pass** | Operational statement participating in the file's runtime behavior.

L0064 | | Blank line used for readability and logical separation.

L0065 | ### Findings | Comment line documenting intent or context for nearby code.

L0066 | - Core routing behavior is correct (login page reachable, root redirects, missing routes return 404). | Operational statement participating in the file's runtime behavior.

L0067 | - Basic anti-MIME-sniffing response header is present on login route. | Operational statement participating in the file's runtime behavior.

L0068 | | Blank line used for readability and logical separation.

L0069 | ## Stage 4: Production | Comment line documenting intent or context for nearby code.

L0070 | | Blank line used for readability and logical separation.

L0071 | ### Checks run | Comment line documenting intent or context for nearby code.

L0072 | - Configuration probe for production-sensitive cookie and URL scheme settings. | Operational statement participating in the file's runtime behavior.

L0073 | | Blank line used for readability and logical separation.

L0074 | ### Evidence | Comment line documenting intent or context for nearby code.

L0075 | - Output: `{ "SESSION\_COOKIE\_HTTPONLY": true, "SESSION\_COOKIE\_SECURE": false, "SESSION\_COOKIE\_SAMESITE": "Lax", "REMEMBER\_COOKIE\_HTTPONLY": true, "REMEMBER\_COOKIE\_SECURE": false, "PREFERRED\_URL\_SCHEME": "http"}` | Operational statement participating in the file's runtime behavior.

L0076 | | Blank line used for readability and logical separation.

L0077 | ### Status | Comment line documenting intent or context for nearby code.

L0078 | - **Fail (for internet-exposed production)** | Operational statement participating in the file's runtime behavior.

L0079 | | Blank line used for readability and logical separation.

L0080 | ### Findings | Comment line documenting intent or context for nearby code.

L0081 | - Security flags are not production-hardened: | Operational statement participating in the file's runtime behavior.

L0082 | - `SESSION\_COOKIE\_SECURE` is false | Operational statement participating in the file's runtime behavior.

L0083 | - `REMEMBER\_COOKIE\_SECURE` is false | Operational statement participating in the file's runtime behavior.

L0084 | - `PREFERRED\_URL\_SCHEME` is `http` | Operational statement participating in the file's runtime behavior.

L0085 | - This is acceptable only for local/dev environments, not for public production deployment. | Operational statement participating in the file's runtime behavior.

L0086 | | Blank line used for readability and logical separation.

L0087 | ## Risk Summary | Comment line documenting intent or context for nearby code.

L0088 | | Blank line used for readability and logical separation.

L0089 | ### High | Comment line documenting intent or context for nearby code.

L0090 | - Production cookies not marked secure + HTTP preferred URL scheme. | Operational statement participating in the file's runtime behavior.

L0091 | | Blank line used for readability and logical separation.

L0092 | ### Medium | Comment line documenting intent or context for nearby code.

L0093 | - Notification behavior regressions in test suite. | Operational statement participating in the file's runtime behavior.

L0094 | | Blank line used for readability and logical separation.

L0095 | ### Medium | Comment line documenting intent or context for nearby code.

L0096 | - Pytest teardown instability may hide additional defects and cause flaky pipelines. | Operational statement participating in the file's runtime behavior.

L0097 | | Blank line used for readability and logical separation.

L0098 | ### Low | Comment line documenting intent or context for nearby code.

L0099 | - Missing lint package in active env prevents style/static gate from running. | Operational statement participating in the file's runtime behavior.

L0100 | | Blank line used for readability and logical separation.

L0101 | ## Recommendation for Release Decision | Comment line documenting intent or context for nearby code.

L0102 | - **Do not approve production release yet.** | Operational statement participating in the file's runtime behavior.

L0103 | | Blank line used for readability and logical separation.

L0104 | ## Mandatory Exit Criteria Before Production | Comment line documenting intent or context for nearby code.

L0105 | 1. Fix notification delete-message regressions and re-run failing tests. | Operational statement participating in the file's runtime behavior.

L0106 | 2. Stabilize pytest teardown behavior (investigate fixture/tmp_path/plugin interactions and Python 3.14 compatibility). | Operational statement participating in the file's runtime behavior.

L0107 | 3. Enable secure production config defaults or environment overrides: | Operational statement participating in the file's runtime behavior.

L0108 | - `SESSION\_COOKIE\_SECURE=true` | Assignment statement storing or updating program state.

L0109 | - `REMEMBER\_COOKIE\_SECURE=true` | Assignment statement storing or updating program state.
L0110 | - `PREFERRED\_URL\_SCHEME=https` | Assignment statement storing or updating program state.
L0111 | 4. Install and enforce lint tooling (`flake8`) in CI/runtime environment. | Operational statement participating in the file's runtime behavior.
L0112 | 5. Re-run full test suite and produce a clean pass report. | Operational statement participating in the file's runtime behavior.

File 70: sdlc_stage_status.json

L0001 | ■{ | Block delimiter controlling scope/structure in this language.

L0002 | "dev_pip_check_status": "PASS", | Operational statement participating in the file's runtime behavior.

L0003 | "dev_flake8_status": "FAIL:1", | Operational statement participating in the file's runtime behavior.

L0004 | "dev_compile_status": "FAIL:-1", | Operational statement participating in the file's runtime behavior.

L0005 | "test_pytest_status": "FAIL:1", | Operational statement participating in the file's runtime behavior.

L0006 | "staging_smoke_status": "FAIL:1", | Operational statement participating in the file's runtime behavior.

L0007 | "production_config_probe_status": "PASS" | Operational statement participating in the file's runtime behavior.

L0008 | } | Block delimiter controlling scope/structure in this language.

File 71: services/___init___.py

File 72: services/login_throttle.py

```
L0001 | import time | Imports dependency modules: time.
L0002 | | Blank line used for readability and logical separation.
L0003 | | Blank line used for readability and logical separation.
L0004 | class LoginThrottleStore: | Declares a class that groups related state and behavior.
L0005 |     def __init__(self, max_attempts, window_seconds, lockout_seconds, redis_client=None): | Declares a function/method as a reusable
L0006 |         self.max_attempts = int(max_attempts) | Assignment statement storing or updating program state.
L0007 |         self.window_seconds = int(window_seconds) | Assignment statement storing or updating program state.
L0008 |         self.lockout_seconds = int(lockout_seconds) | Assignment statement storing or updating program state.
L0009 |         self.redis = redis_client | Assignment statement storing or updating program state.
L0010 |         self._memory = {} | Assignment statement storing or updating program state.
L0011 | | Blank line used for readability and logical separation.
L0012 |     def get_lockout_seconds(self, key): | Declares a function/method as a reusable unit of behavior.
L0013 |         now = int(time.time()) | Assignment statement storing or updating program state.
L0014 |         if self.redis is not None: | Conditional branch that runs only when its condition is true.
L0015 |             state = self.redis.hgetall(key) | Assignment statement storing or updating program state.
L0016 |             if not state: | Conditional branch that runs only when its condition is true.
L0017 |                 return 0 | Returns a value (or control) back to the caller.
L0018 |             locked_until = int(state.get("locked_until", "0") or 0) | Assignment statement storing or updating program state.
L0019 |             if locked_until <= now: | Conditional branch that runs only when its condition is true.
L0020 |                 self.redis.delete(key) | Operational statement participating in the file's runtime behavior.
L0021 |                 return 0 | Returns a value (or control) back to the caller.
L0022 |             return max(1, locked_until - now) | Returns a value (or control) back to the caller.
L0023 | | Blank line used for readability and logical separation.
L0024 |         state = self._memory.get(key) | Assignment statement storing or updating program state.
L0025 |         if not state: | Conditional branch that runs only when its condition is true.
L0026 |             return 0 | Returns a value (or control) back to the caller.
L0027 |         locked_until = int(state.get("locked_until", 0) or 0) | Assignment statement storing or updating program state.
L0028 |         if locked_until <= now: | Conditional branch that runs only when its condition is true.
L0029 |             self._memory.pop(key, None) | Operational statement participating in the file's runtime behavior.
L0030 |             return 0 | Returns a value (or control) back to the caller.
L0031 |         return max(1, locked_until - now) | Returns a value (or control) back to the caller.
L0032 | | Blank line used for readability and logical separation.
L0033 |     def register_failure(self, key): | Declares a function/method as a reusable unit of behavior.
L0034 |         now = int(time.time()) | Assignment statement storing or updating program state.
L0035 |         if self.redis is not None: | Conditional branch that runs only when its condition is true.
L0036 |             state = self.redis.hgetall(key) | Assignment statement storing or updating program state.
L0037 |             first_attempt = int(state.get("first_attempt", "0") or 0) | Assignment statement storing or updating program state.
L0038 |             count = int(state.get("count", "0") or 0) | Assignment statement storing or updating program state.
L0039 | | Blank line used for readability and logical separation.
L0040 |             if not state or (now - first_attempt) > self.window_seconds: | Conditional branch that runs only when its condition is
L0041 |                 count = 1 | Assignment statement storing or updating program state.
L0042 |                 first_attempt = now | Assignment statement storing or updating program state.
L0043 |                 locked_until = 0 | Assignment statement storing or updating program state.
L0044 |             else: | Fallback branch executed when prior conditions are false.
L0045 |                 count += 1 | Assignment statement storing or updating program state.
L0046 |                 locked_until = int(state.get("locked_until", "0") or 0) | Assignment statement storing or updating program state.
L0047 |                 if count >= self.max_attempts: | Conditional branch that runs only when its condition is true.
L0048 |                     locked_until = now + self.lockout_seconds | Assignment statement storing or updating program state.
L0049 | | Blank line used for readability and logical separation.
L0050 |                 self.redis.hset( | Operational statement participating in the file's runtime behavior.
L0051 |                     key, | Operational statement participating in the file's runtime behavior.
L0052 |                     mapping={ | Assignment statement storing or updating program state.
L0053 |                         "count": count, | Operational statement participating in the file's runtime behavior.
```

```
L0054 |         "first_attempt": first_attempt, | Operational statement participating in the file's runtime behavior.
L0055 |         "locked_until": locked_until, | Operational statement participating in the file's runtime behavior.
L0056 |     }, | Operational statement participating in the file's runtime behavior.
L0057 | ) | Operational statement participating in the file's runtime behavior.
L0058 |     self.redis.expire(key, self.window_seconds + self.lockout_seconds + 60) | Operational statement participating in the fi
L0059 |     return | Returns a value (or control) back to the caller.
L0060 | | Blank line used for readability and logical separation.
L0061 |     state = self._memory.get(key) | Assignment statement storing or updating program state.
L0062 |     if not state or (now - int(state["first_attempt"])) > self.window_seconds: | Conditional branch that runs only when its cor
L0063 |         self._memory[key] = {"count": 1, "first_attempt": now, "locked_until": 0} | Assignment statement storing or updating pr
L0064 |     return | Returns a value (or control) back to the caller.
L0065 | | Blank line used for readability and logical separation.
L0066 |     state["count"] += 1 | Assignment statement storing or updating program state.
L0067 |     if state["count"] >= self.max_attempts: | Conditional branch that runs only when its condition is true.
L0068 |         state["locked_until"] = now + self.lockout_seconds | Assignment statement storing or updating program state.
L0069 | | Blank line used for readability and logical separation.
L0070 |     def reset(self, key): | Declares a function/method as a reusable unit of behavior.
L0071 |         if self.redis is not None: | Conditional branch that runs only when its condition is true.
L0072 |             self.redis.delete(key) | Operational statement participating in the file's runtime behavior.
L0073 |             return | Returns a value (or control) back to the caller.
L0074 |         self._memory.pop(key, None) | Operational statement participating in the file's runtime behavior.
```


File 73: sla_fix_test_exit.txt

L0001 | 0 | Operational statement participating in the file's runtime behavior.

File 74: sla_fix_test_output.txt

```
L0001 | yp.....  
L0002 | █ | Operational statement participating in the file's runtime behavior.  
L0003 | █2█p██a██s██s██e██d██ █i██n██ █0██..██0██8██s██ | Operational statement participating in the file's runtime behavior.  
L0004 | █ | Operational statement participating in the file's runtime behavior.  
L0005 | █ | Operational statement participating in the file's runtime behavior.
```

File 75: sqlite_refs.json

```
L0001 | [ | Operational statement participating in the file's runtime behavior.
L0002 |     { | Block delimiter controlling scope/structure in this language.
L0003 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\scripts\\migrate_sqlite_to_postgres.py", | Operational statement parti
L0004 |         "LineNumber": 6, | Operational statement participating in the file's runtime behavior.
L0005 |         "Line": "SKIP_TABLES = {\\\"sqlite_sequence\\\", \\\"alembic_version\\\"}" | Assignment statement storing or updating program stat
L0006 |     }, | Operational statement participating in the file's runtime behavior.
L0007 |     { | Block delimiter controlling scope/structure in this language.
L0008 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\scripts\\migrate_sqlite_to_postgres.py", | Operational statement parti
L0009 |         "LineNumber": 21, | Operational statement participating in the file's runtime behavior.
L0010 |         "Line": "        description=\\\"One-time migration from SQLite to PostgreSQL for this project.\\\"\" | Assignment statement st
L0011 |     }, | Operational statement participating in the file's runtime behavior.
L0012 |     { | Block delimiter controlling scope/structure in this language.
L0013 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\scripts\\migrate_sqlite_to_postgres.py", | Operational statement parti
L0014 |         "LineNumber": 24, | Operational statement participating in the file's runtime behavior.
L0015 |         "Line": "        \\\"--sqlite-path\\\"," | Operational statement participating in the file's runtime behavior.
L0016 |     }, | Operational statement participating in the file's runtime behavior.
L0017 |     { | Block delimiter controlling scope/structure in this language.
L0018 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\scripts\\migrate_sqlite_to_postgres.py", | Operational statement parti
L0019 |         "LineNumber": 26, | Operational statement participating in the file's runtime behavior.
L0020 |         "Line": "        help=\\\"Path to source SQLite database file (default: instance/data.db)\\\"," | Assignment statement storing
L0021 |     }, | Operational statement participating in the file's runtime behavior.
L0022 |     { | Block delimiter controlling scope/structure in this language.
L0023 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\scripts\\migrate_sqlite_to_postgres.py", | Operational statement parti
L0024 |         "LineNumber": 57, | Operational statement participating in the file's runtime behavior.
L0025 |         "Line": "        sqlite_path = args.sqlite_path" | Assignment statement storing or updating program state.
L0026 |     }, | Operational statement participating in the file's runtime behavior.
L0027 |     { | Block delimiter controlling scope/structure in this language.
L0028 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\scripts\\migrate_sqlite_to_postgres.py", | Operational statement parti
L0029 |         "LineNumber": 60, | Operational statement participating in the file's runtime behavior.
L0030 |         "Line": "        if not os.path.exists(sqlite_path):" | Operational statement participating in the file's runtime behavior.
L0031 |     }, | Operational statement participating in the file's runtime behavior.
L0032 |     { | Block delimiter controlling scope/structure in this language.
L0033 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\scripts\\migrate_sqlite_to_postgres.py", | Operational statement parti
L0034 |         "LineNumber": 61, | Operational statement participating in the file's runtime behavior.
L0035 |         "Line": "        print(f\\\"Source SQLite file not found: {sqlite_path}\\\")" | Operational statement participating in the fil
L0036 |     }, | Operational statement participating in the file's runtime behavior.
L0037 |     { | Block delimiter controlling scope/structure in this language.
L0038 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\scripts\\migrate_sqlite_to_postgres.py", | Operational statement parti
L0039 |         "LineNumber": 69, | Operational statement participating in the file's runtime behavior.
L0040 |         "Line": "        sqlite_url = f\\\"sqlite:///{{sqlite_path.replace(os.sep, \\\"u0027\\u0027\\)}}\\\"\" | Assignment statement storing or u
L0041 |     }, | Operational statement participating in the file's runtime behavior.
L0042 |     { | Block delimiter controlling scope/structure in this language.
L0043 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\scripts\\migrate_sqlite_to_postgres.py", | Operational statement parti
L0044 |         "LineNumber": 70, | Operational statement participating in the file's runtime behavior.
L0045 |         "Line": "        source_engine = create_engine(sqlite_url)" | Assignment statement storing or updating program state.
L0046 |     }, | Operational statement participating in the file's runtime behavior.
L0047 |     { | Block delimiter controlling scope/structure in this language.
L0048 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\scripts\\migrate_sqlite_to_postgres.py", | Operational statement parti
L0049 |         "LineNumber": 78, | Operational statement participating in the file's runtime behavior.
L0050 |         "Line": "        print(\\\"No matching tables found between source SQLite and target PostgreSQL.\\\")" | Operational statement
L0051 |     }, | Operational statement participating in the file's runtime behavior.
L0052 |     { | Block delimiter controlling scope/structure in this language.
L0053 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\app.py", | Operational statement participating in the file's runtime beh
```

```
L0054 |         "LineNumber": 616, | Operational statement participating in the file's runtime behavior.
L0055 |         "Line": "    if database_url.startswith(\"sqlite://\"):" | Operational statement participating in the file's runtime behav
L0056 |     }, | Operational statement participating in the file's runtime behavior.
L0057 |     { | Block delimiter controlling scope/structure in this language.
L0058 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\app.py", | Operational statement participating in the file's runtime beh
L0059 |         "LineNumber": 618, | Operational statement participating in the file's runtime behavior.
L0060 |         "Line": "        \"SQLite is disabled for this project. Use PostgreSQL via DATABASE_URL \"" | Operational statement pa
L0061 |     }, | Operational statement participating in the file's runtime behavior.
L0062 |     { | Block delimiter controlling scope/structure in this language.
L0063 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\app.py", | Operational statement participating in the file's runtime beh
L0064 |         "LineNumber": 1013, | Operational statement participating in the file's runtime behavior.
L0065 |         "Line": "        # ensure legacy SQLite schema includes recently added columns" | Operational statement participating in t
L0066 |     }, | Operational statement participating in the file's runtime behavior.
L0067 |     { | Block delimiter controlling scope/structure in this language.
L0068 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\app.py", | Operational statement participating in the file's runtime beh
L0069 |         "LineNumber": 1014, | Operational statement participating in the file's runtime behavior.
L0070 |         "Line": "        if db.engine.dialect.name == \"sqlite\":" | Operational statement participating in the file's runtime beh
L0071 |     }, | Operational statement participating in the file's runtime behavior.
L0072 |     { | Block delimiter controlling scope/structure in this language.
L0073 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\app.py", | Operational statement participating in the file's runtime beh
L0074 |         "LineNumber": 1017, | Operational statement participating in the file's runtime behavior.
L0075 |         "Line": "        for row in db.session.execute(text(\"SELECT name FROM sqlite_master WHERE type=\\u0027table\\u0027\\
L0076 |     }, | Operational statement participating in the file's runtime behavior.
L0077 |     { | Block delimiter controlling scope/structure in this language.
L0078 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\app.py", | Operational statement participating in the file's runtime beh
L0079 |         "LineNumber": 1055, | Operational statement participating in the file's runtime behavior.
L0080 |         "Line": "        if db.engine.dialect.name == \\u0027sqlite\\u0027:" | Operational statement participating in the file's run
L0081 |     }, | Operational statement participating in the file's runtime behavior.
L0082 |     { | Block delimiter controlling scope/structure in this language.
L0083 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\README.md", | Operational statement participating in the file's runtime
L0084 |         "LineNumber": 160, | Operational statement participating in the file's runtime behavior.
L0085 |         "Line": "- SQLite is disabled in app startup." | Operational statement participating in the file's runtime behavior.
L0086 |     }, | Operational statement participating in the file's runtime behavior.
L0087 |     { | Block delimiter controlling scope/structure in this language.
L0088 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\README.md", | Operational statement participating in the file's runtime
L0089 |         "LineNumber": 184, | Operational statement participating in the file's runtime behavior.
L0090 |         "Line": "5. (Optional) migrate legacy SQLite data into PostgreSQL with a one-time script." | Operational statement partici
L0091 |     }, | Operational statement participating in the file's runtime behavior.
L0092 |     { | Block delimiter controlling scope/structure in this language.
L0093 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\README.md", | Operational statement participating in the file's runtime
L0094 |         "LineNumber": 186, | Operational statement participating in the file's runtime behavior.
L0095 |         "Line": "### One-time data migration (SQLite -> PostgreSQL)" | Operational statement participating in the file's runt
L0096 |     }, | Operational statement participating in the file's runtime behavior.
L0097 |     { | Block delimiter controlling scope/structure in this language.
L0098 |         "Path": "C:\\Users\\jonas\\OneDrive\\Desktop\\pm\\README.md", | Operational statement participating in the file's runtime
L0099 |         "LineNumber": 191, | Operational statement participating in the file's runtime behavior.
L0100 |         "Line": "python scripts/migrate_sqlite_to_postgres.py --sqlite-path instance/data.db --truncate" | Operational statement p
L0101 |     } | Block delimiter controlling scope/structure in this language.
L0102 | ] | Operational statement participating in the file's runtime behavior.
```

File 76: sqlite_refs.txt

File 77: stage_dev_compile_status.txt

L0001 | ■PASS | Operational statement participating in the file's runtime behavior.

File 78: stage_dev_flake8.txt

L0001 | ■C:\Users\jonas\OneDrive\Desktop\pm\.venv\Scripts\python.exe: No module named flake8 | Operational statement participating in the 1

File 79: stage_dev_flake8_status.txt

L0001 | ■FAIL:1 | Operational statement participating in the file's runtime behavior.

File 80: stage_dev_pip_check.txt

L0001 | ■No broken requirements found. | Operational statement participating in the file's runtime behavior.

File 81: stage_prod_config.txt

L0001 | ■{"SESSION_COOKIE_HTTPONLY": true, "SESSION_COOKIE_SECURE": false, "SESSION_COOKIE_SAMESITE": "Lax", "REMEMBER_COOKIE_HTTPONLY": t

File 82: stage_prod_config_status.txt

L0001 | ■PASS | Operational statement participating in the file's runtime behavior.

File 83: stage_staging_smoke.txt

```
L0001 | ■Traceback (most recent call last): | Operational statement participating in the file's runtime behavior.  
L0002 |   File "<string>", line 6, in <module> | Operational statement participating in the file's runtime behavior.  
L0003 |     TESTING: True, | Operational statement participating in the file's runtime behavior.  
L0004 |     ^^^^^^^ | Operational statement participating in the file's runtime behavior.  
L0005 | NameError: name 'TESTING' is not defined | Operational statement participating in the file's runtime behavior.
```

File 84: stage_staging_smoke_status.txt

L0001 | ■FAIL:1 | Operational statement participating in the file's runtime behavior.

File 85: stage_test_pytest.txt

```
L0001 | ■.....FF..... [100%] | Operational statement participating in the file's
L0002 | ===== FAILURES ===== | Operational statement participating in the file's
L0003 | _____ test_sender_can_delete_own_message _____ | Operational statement participating in the file's
L0004 | | Blank line used for readability and logical separation.
L0005 | app = <Flask 'app'> | Assignment statement storing or updating program state.
L0006 | | Blank line used for readability and logical separation.
L0007 |     def test_sender_can_delete_own_message(app): | Declares a function/method as a reusable unit of behavior.
L0008 |         with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0009 |             db.session.add_all( | Operational statement participating in the file's runtime behavior.
L0010 |                 [ | Operational statement participating in the file's runtime behavior.
L0011 |                     User( | Operational statement participating in the file's runtime behavior.
L0012 |                         email="owner@example.com", | Assignment statement storing or updating program state.
L0013 |                         full_name="Owner User", | Assignment statement storing or updating program state.
L0014 |                         role="staff", | Assignment statement storing or updating program state.
L0015 |                         password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state
L0016 |                     ), | Operational statement participating in the file's runtime behavior.
L0017 |                     User( | Operational statement participating in the file's runtime behavior.
L0018 |                         email="recipient@example.com", | Assignment statement storing or updating program state.
L0019 |                         full_name="Recipient User", | Assignment statement storing or updating program state.
L0020 |                         role="staff", | Assignment statement storing or updating program state.
L0021 |                         password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state
L0022 |                     ), | Operational statement participating in the file's runtime behavior.
L0023 |                 ] | Operational statement participating in the file's runtime behavior.
L0024 |             ) | Operational statement participating in the file's runtime behavior.
L0025 |             db.session.flush() | Operational statement participating in the file's runtime behavior.
L0026 |             msg = Message( | Assignment statement storing or updating program state.
L0027 |                 sender_email="owner@example.com", | Assignment statement storing or updating program state.
L0028 |                 sender_role="staff", | Assignment statement storing or updating program state.
L0029 |                 recipient_role="staff", | Assignment statement storing or updating program state.
L0030 |                 recipient_email=None, | Assignment statement storing or updating program state.
L0031 |                 body="delete-me", | Assignment statement storing or updating program state.
L0032 |             ) | Operational statement participating in the file's runtime behavior.
L0033 |             db.session.add(msg) | Operational statement participating in the file's runtime behavior.
L0034 |             db.session.commit() | Operational statement participating in the file's runtime behavior.
L0035 |             message_id = msg.id | Assignment statement storing or updating program state.
L0036 |         | Blank line used for readability and logical separation.
L0037 |         client = app.test_client() | Assignment statement storing or updating program state.
L0038 |         login_user(client, "owner@example.com", "Password123!", "staff") | Operational statement participating in the file's runtime
L0039 |         | Blank line used for readability and logical separation.
L0040 |         page = client.get("/notifications/") | Assignment statement storing or updating program state.
L0041 |         csrf_token = extract_hidden_input(page.get_data(as_text=True), "csrf_token") | Assignment statement storing or updating program state
L0042 |         | Blank line used for readability and logical separation.
L0043 |         response = client.post( | Assignment statement storing or updating program state.
L0044 |             f"/notifications/messages/{message_id}/delete", | Operational statement participating in the file's runtime behavior.
L0045 |             data={"csrf_token": csrf_token}, | Assignment statement storing or updating program state.
L0046 |             follow_redirects=True, | Assignment statement storing or updating program state.
L0047 |         ) | Operational statement participating in the file's runtime behavior.
L0048 |         assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0049 | > assert "Message deleted." in response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0050 | E assert 'Message deleted.' in '<!DOCTYPE html>\n<html lang="en">\n  <head>\n    <meta charset="UTF-8" />\n    <meta name="view
L0051 | E + where '<!DOCTYPE html>\n<html lang="en">\n  <head>\n    <meta charset="UTF-8" />\n    <meta name="viewport" content="wi
L0052 | E + where get_data = <WrapperTestResponse 36190 bytes [200 OK]>.get_data | Assignment statement storing or updating program state
L0053 | | Blank line used for readability and logical separation.
```

L0054 | tests\test_notifications.py:226: AssertionError | Operational statement participating in the file's runtime behavior.

L0055 | ----- Captured log setup ----- | Operational statement participating in the file's runtime behavior.

L0056 | WARNING app:app.py:1236 Could not load persisted developer upload limits: (sqlite3.OperationalError) no such table: user_settings

L0057 | [SQL: SELECT user_settings.id AS user_settings_id, user_settings.user_id AS user_settings_user_id, user_settings.theme AS user_settings_theme

L0058 | FROM user_settings JOIN users ON user_settings.user_id = users.id | Assignment statement storing or updating program state.

L0059 | WHERE users.role = ? ORDER BY user_settings.updated_at DESC | Assignment statement storing or updating program state.

L0060 | LIMIT ? OFFSET ?] | Operational statement participating in the file's runtime behavior.

L0061 | [parameters: ('developer', 1, 0)] | Operational statement participating in the file's runtime behavior.

L0062 | (Background on this error at: <https://sqlalche.me/e/20/e3q8>) | Operational statement participating in the file's runtime behavior.

L0063 | _____ test_non_sender_cannot_delete_message _____ | Operational statement participating in the file's runtime behavior.

L0064 | | Blank line used for readability and logical separation.

L0065 | app = <Flask 'app'> | Assignment statement storing or updating program state.

L0066 | | Blank line used for readability and logical separation.

L0067 | def test_non_sender_cannot_delete_message(app): | Declares a function/method as a reusable unit of behavior.

L0068 | with app.app_context(): | Context manager block for safe setup and automatic cleanup.

L0069 | db.session.add_all(| Operational statement participating in the file's runtime behavior.

L0070 | [| Operational statement participating in the file's runtime behavior.

L0071 | User(| Operational statement participating in the file's runtime behavior.

L0072 | email="sender@example.com", | Assignment statement storing or updating program state.

L0073 | full_name="Sender User", | Assignment statement storing or updating program state.

L0074 | role="technician", | Assignment statement storing or updating program state.

L0075 | password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.

L0076 |), | Operational statement participating in the file's runtime behavior.

L0077 | User(| Operational statement participating in the file's runtime behavior.

L0078 | email="other@example.com", | Assignment statement storing or updating program state.

L0079 | full_name="Other User", | Assignment statement storing or updating program state.

L0080 | role="staff", | Assignment statement storing or updating program state.

L0081 | password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.

L0082 |), | Operational statement participating in the file's runtime behavior.

L0083 |] | Operational statement participating in the file's runtime behavior.

L0084 |) | Operational statement participating in the file's runtime behavior.

L0085 | db.session.flush() | Operational statement participating in the file's runtime behavior.

L0086 | msg = Message(| Assignment statement storing or updating program state.

L0087 | sender_email="sender@example.com", | Assignment statement storing or updating program state.

L0088 | sender_role="technician", | Assignment statement storing or updating program state.

L0089 | recipient_role="staff", | Assignment statement storing or updating program state.

L0090 | recipient_email=None, | Assignment statement storing or updating program state.

L0091 | body="should-stay", | Assignment statement storing or updating program state.

L0092 |) | Operational statement participating in the file's runtime behavior.

L0093 | db.session.add(msg) | Operational statement participating in the file's runtime behavior.

L0094 | db.session.commit() | Operational statement participating in the file's runtime behavior.

L0095 | message_id = msg.id | Assignment statement storing or updating program state.

L0096 | | Blank line used for readability and logical separation.

L0097 | client = app.test_client() | Assignment statement storing or updating program state.

L0098 | login_user(client, "other@example.com", "Password123!", "staff") | Operational statement participating in the file's runtime behavior.

L0099 | | Blank line used for readability and logical separation.

L0100 | page = client.get("/notifications/") | Assignment statement storing or updating program state.

L0101 | csrf_token = extract_hidden_input(page.get_data(as_text=True), "csrf_token") | Assignment statement storing or updating program state.

L0102 | | Blank line used for readability and logical separation.

L0103 | response = client.post(| Assignment statement storing or updating program state.

L0104 | f"/notifications/messages/{message_id}/delete", | Operational statement participating in the file's runtime behavior.

L0105 | data={"csrf_token": csrf_token}, | Assignment statement storing or updating program state.

L0106 | follow_redirects=True, | Assignment statement storing or updating program state.

L0107 |) | Operational statement participating in the file's runtime behavior.

L0108 | assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.

```
L0109 | >         assert "You can only delete your own messages." in response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0110 | E         assert 'You can only delete your own messages.' in '<!DOCTYPE html>\n<html lang="en">\n  <head>\n    <meta charset="UTF-8"
L0111 | E         +   where '<!DOCTYPE html>\n<html lang="en">\n  <head>\n    <meta charset="UTF-8" />\n    <meta name="viewport" content="width=device-width, initial-scale=1.0">\n  </head>\n  <body>\n    <div class="container">\n      <div class="row">\n        <div class="col-md-12">\n          <div class="card">\n            <div class="card-header">\n              <h3>Delete Message</h3>\n            </div>\n            <div class="card-body">\n              <div class="text-center">\n                <p>Are you sure you want to delete this message?</p>\n                <div class="d-flex justify-content-center gap-2">\n                  <button class="btn btn-danger">Yes</button>\n                  <button class="btn btn-secondary">No</button>\n                </div>\n              </div>\n            </div>\n          </div>\n        </div>\n      </div>\n    </div>\n  </body>\n</html>\n' | Assignment statement storing or updating program state.
L0112 | E         +   where get_data = <WrapperTestResponse 36190 bytes [200 OK]>.get_data | Assignment statement storing or updating program state.
L0113 | | Blank line used for readability and logical separation.
L0114 | tests\test_notifications.py:274: AssertionError | Operational statement participating in the file's runtime behavior.
L0115 | ----- Captured log setup ----- | Operational statement participating in the file's runtime behavior.
L0116 | WARNING app:app.py:1236 Could not load persisted developer upload limits: (sqlite3.OperationalError) no such table: user_settings.
L0117 | [SQL: SELECT user_settings.id AS user_settings_id, user_settings.user_id AS user_settings_user_id, user_settings.theme AS user_settings_theme, user_settings.updated_at AS user_settings_updated_at FROM user_settings JOIN users ON user_settings.user_id = users.id | Assignment statement storing or updating program state.
L0118 | FROM user_settings JOIN users ON user_settings.user_id = users.id | Assignment statement storing or updating program state.
L0119 | WHERE users.role = ? ORDER BY user_settings.updated_at DESC | Assignment statement storing or updating program state.
L0120 | LIMIT ? OFFSET ?] | Operational statement participating in the file's runtime behavior.
L0121 | [parameters: ('developer', 1, 0)] | Operational statement participating in the file's runtime behavior.
L0122 | (Background on this error at: https://sqlalche.me/e/20/e3q8) | Operational statement participating in the file's runtime behavior.
L0123 | ===== warnings summary ===== | Operational statement participating in the file's runtime behavior.
L0124 | tests/test_security.py::test_developer_can_edit_user_profile | Operational statement participating in the file's runtime behavior.
L0125 | tests/test_security.py::test_developer_profile_edit_rejects_duplicate_email | Operational statement participating in the file's runtime behavior.
L0126 | C:\Users\jonas\OneDrive\Desktop\pm\venv\Lib\site-packages\flask_sqlalchemy\query.py:30: LegacyAPIWarning: The Query.get() method is considered legacy as of 2.0.13 and will be removed in 3.0. Please use Query.get_one() instead.
L0127 |     rv = self.get(ident) | Assignment statement storing or updating program state.
L0128 | | Blank line used for readability and logical separation.
L0129 | tests/test_security.py::test_developer_can_edit_user_profile | Operational statement participating in the file's runtime behavior.
L0130 | C:\Users\jonas\OneDrive\Desktop\pm\tests\test_security.py:210: LegacyAPIWarning: The Query.get() method is considered legacy as of 2.0.13 and will be removed in 3.0. Please use Query.get_one() instead.
L0131 |     updated = User.query.get(user_id) | Assignment statement storing or updating program state.
L0132 | | Blank line used for readability and logical separation.
L0133 | tests/test_security.py::test_developer_profile_edit_rejects_duplicate_email | Operational statement participating in the file's runtime behavior.
L0134 | C:\Users\jonas\OneDrive\Desktop\pm\tests\test_security.py:254: LegacyAPIWarning: The Query.get() method is considered legacy as of 2.0.13 and will be removed in 3.0. Please use Query.get_one() instead.
L0135 |     unchanged = User.query.get(user_id) | Assignment statement storing or updating program state.
L0136 | | Blank line used for readability and logical separation.
L0137 | -- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html | Operational statement participating in the file's runtime behavior.
L0138 | ===== short test summary info ===== | Operational statement participating in the file's runtime behavior.
L0139 | FAILED tests/test_notifications.py::test_sender_can_delete_own_message - AssertionError: 'You can only delete your own messages.' in '<!DOCTYPE html>\n<html lang="en">\n  <head>\n    <meta charset="UTF-8"
L0140 | FAILED tests/test_notifications.py::test_non_sender_cannot_delete_message - AssertionError: 'You can only delete your own messages.' in '<!DOCTYPE html>\n<html lang="en">\n  <head>\n    <meta charset="UTF-8"
```


File 86: stage_test_pytest_status.txt

L0001 | ■FAIL:1 | Operational statement participating in the file's runtime behavior.

File 87: static/soliton-telmec.png

File 88: static/style.css

```
L0001 | ■:root { | Block delimiter controlling scope/structure in this language.
L0002 |   --primary: #054da6; | Operational statement participating in the file's runtime behavior.
L0003 |   --secondary: #f4f9ff; | Operational statement participating in the file's runtime behavior.
L0004 |   --accent: #fff6f61; | Operational statement participating in the file's runtime behavior.
L0005 |   --text-color: #1a2540; | Operational statement participating in the file's runtime behavior.
L0006 |   --muted: #5a6583; | Operational statement participating in the file's runtime behavior.
L0007 |   --card-bg: #ffffff; | Operational statement participating in the file's runtime behavior.
L0008 |   --card-bg-soft: #ffffff; | Operational statement participating in the file's runtime behavior.
L0009 |   --card-shadow: 0 4px 12px rgba(0, 0, 0, 0.1); | Operational statement participating in the file's runtime behavior.
L0010 |   --loader-backdrop: rgba(3, 18, 41, 0.42); | Operational statement participating in the file's runtime behavior.
L0011 |   --loader-card: rgba(255, 255, 255, 0.9); | Operational statement participating in the file's runtime behavior.
L0012 |   --loader-text: #0f3c73; | Operational statement participating in the file's runtime behavior.
L0013 | } | Block delimiter controlling scope/structure in this language.
L0014 | | Blank line used for readability and logical separation.
L0015 | body[data-theme="dark"] { | Assignment statement storing or updating program state.
L0016 |   --secondary: #0f1724; | Operational statement participating in the file's runtime behavior.
L0017 |   --text-color: #e8eef8; | Operational statement participating in the file's runtime behavior.
L0018 |   --muted: #a9b7cc; | Operational statement participating in the file's runtime behavior.
L0019 |   --card-bg: #172234; | Operational statement participating in the file's runtime behavior.
L0020 |   --card-bg-soft: #1a2a41; | Operational statement participating in the file's runtime behavior.
L0021 |   --card-shadow: 0 8px 20px rgba(0, 0, 0, 0.35); | Operational statement participating in the file's runtime behavior.
L0022 |   --loader-backdrop: rgba(2, 8, 18, 0.62); | Operational statement participating in the file's runtime behavior.
L0023 |   --loader-card: rgba(24, 38, 60, 0.9); | Operational statement participating in the file's runtime behavior.
L0024 |   --loader-text: #d7e7ff; | Operational statement participating in the file's runtime behavior.
L0025 | } | Block delimiter controlling scope/structure in this language.
L0026 | | Blank line used for readability and logical separation.
L0027 | @keyframes loader-rotate { | Decorator line that modifies the behavior of the definition below.
L0028 |   to { | Block delimiter controlling scope/structure in this language.
L0029 |     transform: rotate(360deg); | Operational statement participating in the file's runtime behavior.
L0030 |   } | Block delimiter controlling scope/structure in this language.
L0031 | } | Block delimiter controlling scope/structure in this language.
L0032 | | Blank line used for readability and logical separation.
L0033 | @keyframes infinity-snake { | Decorator line that modifies the behavior of the definition below.
L0034 |   0% { | Block delimiter controlling scope/structure in this language.
L0035 |     stroke-dashoffset: 0; | Operational statement participating in the file's runtime behavior.
L0036 |   } | Block delimiter controlling scope/structure in this language.
L0037 |   100% { | Block delimiter controlling scope/structure in this language.
L0038 |     stroke-dashoffset: -100; | Operational statement participating in the file's runtime behavior.
L0039 |   } | Block delimiter controlling scope/structure in this language.
L0040 | } | Block delimiter controlling scope/structure in this language.
L0041 | | Blank line used for readability and logical separation.
L0042 | @keyframes loading-dot-bounce { | Decorator line that modifies the behavior of the definition below.
L0043 |   0%, | Operational statement participating in the file's runtime behavior.
L0044 |   80%, | Operational statement participating in the file's runtime behavior.
L0045 |   100% { | Block delimiter controlling scope/structure in this language.
L0046 |     transform: translateY(0) scale(0.75); | Operational statement participating in the file's runtime behavior.
L0047 |     opacity: 0.45; | Operational statement participating in the file's runtime behavior.
L0048 |   } | Block delimiter controlling scope/structure in this language.
L0049 |   40% { | Block delimiter controlling scope/structure in this language.
L0050 |     transform: translateY(-2px) scale(0.96); | Operational statement participating in the file's runtime behavior.
L0051 |     opacity: 1; | Operational statement participating in the file's runtime behavior.
L0052 |   } | Block delimiter controlling scope/structure in this language.
L0053 | } | Block delimiter controlling scope/structure in this language.
```

L0054 | | Blank line used for readability and logical separation.

L0055 | @keyframes loader-marker-pulse { | Decorator line that modifies the behavior of the definition below.

L0056 | 0%, | Operational statement participating in the file's runtime behavior.

L0057 | 100% { | Block delimiter controlling scope/structure in this language.

L0058 | filter: drop-shadow(0 0 4px rgba(10, 132, 255, 0.35)); | Operational statement participating in the file's runtime behavior.

L0059 | } | Block delimiter controlling scope/structure in this language.

L0060 | 50% { | Block delimiter controlling scope/structure in this language.

L0061 | filter: drop-shadow(0 0 12px rgba(10, 132, 255, 0.9)); | Operational statement participating in the file's runtime behavior.

L0062 | } | Block delimiter controlling scope/structure in this language.

L0063 | } | Block delimiter controlling scope/structure in this language.

L0064 | | Blank line used for readability and logical separation.

L0065 | @keyframes loader-trail-shimmer { | Decorator line that modifies the behavior of the definition below.

L0066 | 0%, | Operational statement participating in the file's runtime behavior.

L0067 | 100% { | Block delimiter controlling scope/structure in this language.

L0068 | opacity: 0.25; | Operational statement participating in the file's runtime behavior.

L0069 | transform: scale(0.85); | Operational statement participating in the file's runtime behavior.

L0070 | } | Block delimiter controlling scope/structure in this language.

L0071 | 50% { | Block delimiter controlling scope/structure in this language.

L0072 | opacity: 0.8; | Operational statement participating in the file's runtime behavior.

L0073 | transform: scale(1.08); | Operational statement participating in the file's runtime behavior.

L0074 | } | Block delimiter controlling scope/structure in this language.

L0075 | } | Block delimiter controlling scope/structure in this language.

L0076 | | Blank line used for readability and logical separation.

L0077 | @keyframes loader-trail-micro-shimmer { | Decorator line that modifies the behavior of the definition below.

L0078 | 0%, | Operational statement participating in the file's runtime behavior.

L0079 | 100% { | Block delimiter controlling scope/structure in this language.

L0080 | opacity: 0.18; | Operational statement participating in the file's runtime behavior.

L0081 | filter: drop-shadow(0 0 2px rgba(105, 189, 255, 0.28)); | Operational statement participating in the file's runtime behavior.

L0082 | } | Block delimiter controlling scope/structure in this language.

L0083 | 50% { | Block delimiter controlling scope/structure in this language.

L0084 | opacity: 0.72; | Operational statement participating in the file's runtime behavior.

L0085 | filter: drop-shadow(0 0 8px rgba(105, 189, 255, 0.75)); | Operational statement participating in the file's runtime behavior.

L0086 | } | Block delimiter controlling scope/structure in this language.

L0087 | } | Block delimiter controlling scope/structure in this language.

L0088 | | Blank line used for readability and logical separation.

L0089 | @keyframes loader-pulse { | Decorator line that modifies the behavior of the definition below.

L0090 | 0%, | Operational statement participating in the file's runtime behavior.

L0091 | 100% { | Block delimiter controlling scope/structure in this language.

L0092 | transform: scale(0.92); | Operational statement participating in the file's runtime behavior.

L0093 | opacity: 0.75; | Operational statement participating in the file's runtime behavior.

L0094 | } | Block delimiter controlling scope/structure in this language.

L0095 | 50% { | Block delimiter controlling scope/structure in this language.

L0096 | transform: scale(1.08); | Operational statement participating in the file's runtime behavior.

L0097 | opacity: 1; | Operational statement participating in the file's runtime behavior.

L0098 | } | Block delimiter controlling scope/structure in this language.

L0099 | } | Block delimiter controlling scope/structure in this language.

L0100 | | Blank line used for readability and logical separation.

L0101 | .app-loader { | CSS selector line choosing the elements styled below.

L0102 | position: fixed; | Operational statement participating in the file's runtime behavior.

L0103 | inset: 0; | Operational statement participating in the file's runtime behavior.

L0104 | display: grid; | Operational statement participating in the file's runtime behavior.

L0105 | place-items: center; | Operational statement participating in the file's runtime behavior.

L0106 | background: var(--loader-backdrop); | Operational statement participating in the file's runtime behavior.

L0107 | backdrop-filter: blur(5px); | Operational statement participating in the file's runtime behavior.

L0108 | z-index: 9999; | Operational statement participating in the file's runtime behavior.

L0109 | opacity: 0; | Operational statement participating in the file's runtime behavior.

L0110 | visibility: hidden; | Operational statement participating in the file's runtime behavior.

L0111 | pointer-events: none; | Operational statement participating in the file's runtime behavior.

L0112 | transition: opacity 0.24s ease, visibility 0.24s ease; | Operational statement participating in the file's runtime behavior.

L0113 | } | Block delimiter controlling scope/structure in this language.

L0114 | | Blank line used for readability and logical separation.

L0115 | .app-loader.is-visible { | CSS selector line choosing the elements styled below.

L0116 | opacity: 1; | Operational statement participating in the file's runtime behavior.

L0117 | visibility: visible; | Operational statement participating in the file's runtime behavior.

L0118 | pointer-events: all; | Operational statement participating in the file's runtime behavior.

L0119 | } | Block delimiter controlling scope/structure in this language.

L0120 | | Blank line used for readability and logical separation.

L0121 | .app-loader-card { | CSS selector line choosing the elements styled below.

L0122 | min-width: 220px; | Operational statement participating in the file's runtime behavior.

L0123 | padding: 1.1rem 1.35rem; | Operational statement participating in the file's runtime behavior.

L0124 | border-radius: 24px; | Operational statement participating in the file's runtime behavior.

L0125 | background: var(--loader-card); | Operational statement participating in the file's runtime behavior.

L0126 | border: 1px solid rgba(173, 206, 255, 0.35); | Operational statement participating in the file's runtime behavior.

L0127 | box-shadow: 0 18px 46px rgba(3, 18, 41, 0.28); | Operational statement participating in the file's runtime behavior.

L0128 | display: flex; | Operational statement participating in the file's runtime behavior.

L0129 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L0130 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0131 | gap: 0.8rem; | Operational statement participating in the file's runtime behavior.

L0132 | } | Block delimiter controlling scope/structure in this language.

L0133 | | Blank line used for readability and logical separation.

L0134 | .loader-infinity-wrap { | CSS selector line choosing the elements styled below.

L0135 | display: flex; | Operational statement participating in the file's runtime behavior.

L0136 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0137 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L0138 | width: 160px; | Operational statement participating in the file's runtime behavior.

L0139 | height: 74px; | Operational statement participating in the file's runtime behavior.

L0140 | } | Block delimiter controlling scope/structure in this language.

L0141 | | Blank line used for readability and logical separation.

L0142 | .loader-infinity { | CSS selector line choosing the elements styled below.

L0143 | width: 160px; | Operational statement participating in the file's runtime behavior.

L0144 | height: 80px; | Operational statement participating in the file's runtime behavior.

L0145 | } | Block delimiter controlling scope/structure in this language.

L0146 | | Blank line used for readability and logical separation.

L0147 | .loader-infinity-track, | CSS selector line choosing the elements styled below.

L0148 | .loader-infinity-snake { | CSS selector line choosing the elements styled below.

L0149 | fill: none; | Operational statement participating in the file's runtime behavior.

L0150 | stroke-linecap: round; | Operational statement participating in the file's runtime behavior.

L0151 | stroke-linejoin: round; | Operational statement participating in the file's runtime behavior.

L0152 | stroke-width: 10; | Operational statement participating in the file's runtime behavior.

L0153 | } | Block delimiter controlling scope/structure in this language.

L0154 | | Blank line used for readability and logical separation.

L0155 | .loader-infinity-track { | CSS selector line choosing the elements styled below.

L0156 | stroke: rgba(47, 125, 255, 0.18); | Operational statement participating in the file's runtime behavior.

L0157 | } | Block delimiter controlling scope/structure in this language.

L0158 | | Blank line used for readability and logical separation.

L0159 | .loader-infinity-snake { | CSS selector line choosing the elements styled below.

L0160 | stroke: url(#loaderInfinityGradient); | Operational statement participating in the file's runtime behavior.

L0161 | filter: drop-shadow(0 0 10px rgba(10, 132, 255, 0.28)); | Operational statement participating in the file's runtime behavior.

L0162 | stroke-dasharray: 32 68; | Operational statement participating in the file's runtime behavior.

L0163 | animation: infinity-snake 1.05s linear infinite; | Operational statement participating in the file's runtime behavior.

L0164 | } | Block delimiter controlling scope/structure in this language.

L0165 | | Blank line used for readability and logical separation.

L0166 | .loader-snake-head { | CSS selector line choosing the elements styled below.

L0167 | fill: #e8f5ff; | Operational statement participating in the file's runtime behavior.

L0168 | stroke: #0a84ff; | Operational statement participating in the file's runtime behavior.

L0169 | stroke-width: 1.6; | Operational statement participating in the file's runtime behavior.

L0170 | filter: drop-shadow(0 0 7px rgba(10, 132, 255, 0.6)); | Operational statement participating in the file's runtime behavior.

L0171 | animation: loader-marker-pulse 0.42s ease-in-out infinite; | Operational statement participating in the file's runtime behavior.

L0172 | } | Block delimiter controlling scope/structure in this language.

L0173 | | Blank line used for readability and logical separation.

L0174 | .loader-snake-trail { | CSS selector line choosing the elements styled below.

L0175 | fill: rgba(120, 203, 255, 0.88); | Operational statement participating in the file's runtime behavior.

L0176 | stroke: rgba(10, 132, 255, 0.7); | Operational statement participating in the file's runtime behavior.

L0177 | stroke-width: 1.1; | Operational statement participating in the file's runtime behavior.

L0178 | filter: drop-shadow(0 0 6px rgba(114, 193, 255, 0.6)); | Operational statement participating in the file's runtime behavior.

L0179 | animation: loader-trail-shimmer 0.42s ease-in-out infinite; | Operational statement participating in the file's runtime behavior.

L0180 | } | Block delimiter controlling scope/structure in this language.

L0181 | | Blank line used for readability and logical separation.

L0182 | .loader-snake-trail-2 { | CSS selector line choosing the elements styled below.

L0183 | fill: rgba(174, 227, 255, 0.85); | Operational statement participating in the file's runtime behavior.

L0184 | stroke: rgba(78, 165, 255, 0.72); | Operational statement participating in the file's runtime behavior.

L0185 | stroke-width: 0.95; | Operational statement participating in the file's runtime behavior.

L0186 | filter: drop-shadow(0 0 4px rgba(114, 193, 255, 0.5)); | Operational statement participating in the file's runtime behavior.

L0187 | animation: loader-trail-micro-shimmer 0.42s ease-in-out infinite; | Operational statement participating in the file's runtime behavior.

L0188 | } | Block delimiter controlling scope/structure in this language.

L0189 | | Blank line used for readability and logical separation.

L0190 | .loader-text { | CSS selector line choosing the elements styled below.

L0191 | margin: 0; | Operational statement participating in the file's runtime behavior.

L0192 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L0193 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0194 | gap: 0.2rem; | Operational statement participating in the file's runtime behavior.

L0195 | font-size: 0.94rem; | Operational statement participating in the file's runtime behavior.

L0196 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L0197 | letter-spacing: 0.12em; | Operational statement participating in the file's runtime behavior.

L0198 | color: var(--loader-text); | Operational statement participating in the file's runtime behavior.

L0199 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L0200 | } | Block delimiter controlling scope/structure in this language.

L0201 | | Blank line used for readability and logical separation.

L0202 | | Blank line used for readability and logical separation.

L0203 | | Blank line used for readability and logical separation.

L0204 | .loader-dots { | CSS selector line choosing the elements styled below.

L0205 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L0206 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0207 | gap: 0.14rem; | Operational statement participating in the file's runtime behavior.

L0208 | } | Block delimiter controlling scope/structure in this language.

L0209 | | Blank line used for readability and logical separation.

L0210 | .loader-dots span { | CSS selector line choosing the elements styled below.

L0211 | width: 0.28rem; | Operational statement participating in the file's runtime behavior.

L0212 | height: 0.28rem; | Operational statement participating in the file's runtime behavior.

L0213 | border-radius: 50%; | Operational statement participating in the file's runtime behavior.

L0214 | background: currentColor; | Operational statement participating in the file's runtime behavior.

L0215 | animation: loading-dot-bounce 1.18s ease-in-out infinite; | Operational statement participating in the file's runtime behavior.

L0216 | } | Block delimiter controlling scope/structure in this language.

L0217 | | Blank line used for readability and logical separation.

L0218 | .loader-dots span:nth-child(2) { | CSS selector line choosing the elements styled below.

L0219 | animation-delay: 0.16s; | Operational statement participating in the file's runtime behavior.

L0220 | } | Block delimiter controlling scope/structure in this language.

L0221 | | Blank line used for readability and logical separation.

L0222 | .loader-dots span:nth-child(3) { | CSS selector line choosing the elements styled below.

L0223 | animation-delay: 0.32s; | Operational statement participating in the file's runtime behavior.

L0224 | } | Block delimiter controlling scope/structure in this language.

L0225 | | Blank line used for readability and logical separation.

L0226 | .photo-library-hero { | CSS selector line choosing the elements styled below.

L0227 | display: flex; | Operational statement participating in the file's runtime behavior.

L0228 | justify-content: space-between; | Operational statement participating in the file's runtime behavior.

L0229 | align-items: flex-start; | Operational statement participating in the file's runtime behavior.

L0230 | gap: 1rem; | Operational statement participating in the file's runtime behavior.

L0231 | } | Block delimiter controlling scope/structure in this language.

L0232 | | Blank line used for readability and logical separation.

L0233 | .photo-library-stat-card, | CSS selector line choosing the elements styled below.

L0234 | .photo-library-toolbar-card, | CSS selector line choosing the elements styled below.

L0235 | .photo-library-card, | CSS selector line choosing the elements styled below.

L0236 | .photo-library-empty-card { | CSS selector line choosing the elements styled below.

L0237 | border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L0238 | border-radius: 20px; | Operational statement participating in the file's runtime behavior.

L0239 | background: var(--card-bg); | Operational statement participating in the file's runtime behavior.

L0240 | box-shadow: 0 12px 28px rgba(9, 61, 126, 0.08); | Operational statement participating in the file's runtime behavior.

L0241 | } | Block delimiter controlling scope/structure in this language.

L0242 | | Blank line used for readability and logical separation.

L0243 | .photo-library-stat-label { | CSS selector line choosing the elements styled below.

L0244 | font-size: 0.74rem; | Operational statement participating in the file's runtime behavior.

L0245 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L0246 | letter-spacing: 0.08em; | Operational statement participating in the file's runtime behavior.

L0247 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L0248 | color: #58739b; | Operational statement participating in the file's runtime behavior.

L0249 | margin-bottom: 0.45rem; | Operational statement participating in the file's runtime behavior.

L0250 | } | Block delimiter controlling scope/structure in this language.

L0251 | | Blank line used for readability and logical separation.

L0252 | .photo-library-stat-value { | CSS selector line choosing the elements styled below.

L0253 | font-size: 2rem; | Operational statement participating in the file's runtime behavior.

L0254 | line-height: 1; | Operational statement participating in the file's runtime behavior.

L0255 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L0256 | color: #0a4fa8; | Operational statement participating in the file's runtime behavior.

L0257 | margin-bottom: 0.35rem; | Operational statement participating in the file's runtime behavior.

L0258 | } | Block delimiter controlling scope/structure in this language.

L0259 | | Blank line used for readability and logical separation.

L0260 | .photo-library-path { | CSS selector line choosing the elements styled below.

L0261 | word-break: break-word; | Operational statement participating in the file's runtime behavior.

L0262 | font-family: monospace; | Operational statement participating in the file's runtime behavior.

L0263 | font-size: 0.82rem; | Operational statement participating in the file's runtime behavior.

L0264 | color: #20497f; | Operational statement participating in the file's runtime behavior.

L0265 | } | Block delimiter controlling scope/structure in this language.

L0266 | | Blank line used for readability and logical separation.

L0267 | .photo-library-image-link { | CSS selector line choosing the elements styled below.

L0268 | display: block; | Operational statement participating in the file's runtime behavior.

L0269 | padding: 0.9rem 0.9rem 0; | Operational statement participating in the file's runtime behavior.

L0270 | } | Block delimiter controlling scope/structure in this language.

L0271 | | Blank line used for readability and logical separation.

L0272 | .photo-library-image { | CSS selector line choosing the elements styled below.

L0273 | width: 100%; | Operational statement participating in the file's runtime behavior.

L0274 | aspect-ratio: 4 / 5; | Operational statement participating in the file's runtime behavior.

L0275 | object-fit: cover; | Operational statement participating in the file's runtime behavior.

L0276 | border-radius: 16px; | Operational statement participating in the file's runtime behavior.

L0277 | border: 1px solid rgba(15, 76, 150, 0.1); | Operational statement participating in the file's runtime behavior.

L0278 | background: #eff6ff; | Operational statement participating in the file's runtime behavior.

L0279 | } | Block delimiter controlling scope/structure in this language.

L0280 | | Blank line used for readability and logical separation.

L0281 | .photo-library-title { | CSS selector line choosing the elements styled below.

L0282 | font-size: 0.98rem; | Operational statement participating in the file's runtime behavior.

L0283 | line-height: 1.3; | Operational statement participating in the file's runtime behavior.

L0284 | color: #102f59; | Operational statement participating in the file's runtime behavior.

L0285 | word-break: break-word; | Operational statement participating in the file's runtime behavior.

L0286 | } | Block delimiter controlling scope/structure in this language.

L0287 | | Blank line used for readability and logical separation.

L0288 | .photo-library-description { | CSS selector line choosing the elements styled below.

L0289 | color: #42597e; | Operational statement participating in the file's runtime behavior.

L0290 | font-size: 0.86rem; | Operational statement participating in the file's runtime behavior.

L0291 | line-height: 1.5; | Operational statement participating in the file's runtime behavior.

L0292 | } | Block delimiter controlling scope/structure in this language.

L0293 | | Blank line used for readability and logical separation.

L0294 | .photo-library-meta { | CSS selector line choosing the elements styled below.

L0295 | display: flex; | Operational statement participating in the file's runtime behavior.

L0296 | flex-wrap: wrap; | Operational statement participating in the file's runtime behavior.

L0297 | gap: 0.7rem; | Operational statement participating in the file's runtime behavior.

L0298 | font-size: 0.74rem; | Operational statement participating in the file's runtime behavior.

L0299 | color: #5b7295; | Operational statement participating in the file's runtime behavior.

L0300 | } | Block delimiter controlling scope/structure in this language.

L0301 | | Blank line used for readability and logical separation.

L0302 | .photo-library-meta span { | CSS selector line choosing the elements styled below.

L0303 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L0304 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0305 | gap: 0.28rem; | Operational statement participating in the file's runtime behavior.

L0306 | } | Block delimiter controlling scope/structure in this language.

L0307 | | Blank line used for readability and logical separation.

L0308 | .photo-kind-badge { | CSS selector line choosing the elements styled below.

L0309 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L0310 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0311 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L0312 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L0313 | padding: 0.22rem 0.58rem; | Operational statement participating in the file's runtime behavior.

L0314 | font-size: 0.7rem; | Operational statement participating in the file's runtime behavior.

L0315 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L0316 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L0317 | letter-spacing: 0.06em; | Operational statement participating in the file's runtime behavior.

L0318 | white-space: nowrap; | Operational statement participating in the file's runtime behavior.

L0319 | } | Block delimiter controlling scope/structure in this language.

L0320 | | Blank line used for readability and logical separation.

L0321 | .photo-kind-image { | CSS selector line choosing the elements styled below.

L0322 | background: #e9fff3; | Operational statement participating in the file's runtime behavior.

L0323 | color: #0d6e3f; | Operational statement participating in the file's runtime behavior.

L0324 | border: 1px solid #5cd09d; | Operational statement participating in the file's runtime behavior.

L0325 | } | Block delimiter controlling scope/structure in this language.

L0326 | | Blank line used for readability and logical separation.

L0327 | .photo-kind-screenshot { | CSS selector line choosing the elements styled below.

L0328 | background: #fff4e5; | Operational statement participating in the file's runtime behavior.

L0329 | color: #a85a00; | Operational statement participating in the file's runtime behavior.

L0330 | border: 1px solid #f0b06a; | Operational statement participating in the file's runtime behavior.

L0331 | } | Block delimiter controlling scope/structure in this language.

L0332 | | Blank line used for readability and logical separation.

L0333 | .photo-library-empty-icon { | CSS selector line choosing the elements styled below.

L0334 | width: 84px; | Operational statement participating in the file's runtime behavior.

L0335 | height: 84px; | Operational statement participating in the file's runtime behavior.

L0336 | border-radius: 50%; | Operational statement participating in the file's runtime behavior.

L0337 | margin: 0 auto 1rem; | Operational statement participating in the file's runtime behavior.

L0338 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L0339 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0340 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L0341 | background: radial-gradient(circle at top left, #b1deff, #d9edff); | Operational statement participating in the file's runtime behavior.

L0342 | color: #0f53b0; | Operational statement participating in the file's runtime behavior.

L0343 | font-size: 2rem; | Operational statement participating in the file's runtime behavior.

L0344 | } | Block delimiter controlling scope/structure in this language.

L0345 | | Blank line used for readability and logical separation.

L0346 | body[data-theme="dark"] .photo-library-stat-card, | Assignment statement storing or updating program state.

L0347 | body[data-theme="dark"] .photo-library-toolbar-card, | Assignment statement storing or updating program state.

L0348 | body[data-theme="dark"] .photo-library-card, | Assignment statement storing or updating program state.

L0349 | body[data-theme="dark"] .photo-library-empty-card { | Assignment statement storing or updating program state.

L0350 | border-color: #31486b; | Operational statement participating in the file's runtime behavior.

L0351 | background: var(--card-bg-soft); | Operational statement participating in the file's runtime behavior.

L0352 | box-shadow: 0 12px 28px rgba(0, 0, 0, 0.24); | Operational statement participating in the file's runtime behavior.

L0353 | } | Block delimiter controlling scope/structure in this language.

L0354 | | Blank line used for readability and logical separation.

L0355 | body[data-theme="dark"] .photo-library-stat-label, | Assignment statement storing or updating program state.

L0356 | body[data-theme="dark"] .photo-library-meta, | Assignment statement storing or updating program state.

L0357 | body[data-theme="dark"] .photo-library-description { | Assignment statement storing or updating program state.

L0358 | color: #a9bdd8; | Operational statement participating in the file's runtime behavior.

L0359 | } | Block delimiter controlling scope/structure in this language.

L0360 | | Blank line used for readability and logical separation.

L0361 | body[data-theme="dark"] .photo-library-stat-value, | Assignment statement storing or updating program state.

L0362 | body[data-theme="dark"] .photo-library-title, | Assignment statement storing or updating program state.

L0363 | body[data-theme="dark"] .photo-library-path { | Assignment statement storing or updating program state.

L0364 | color: #d6e7ff; | Operational statement participating in the file's runtime behavior.

L0365 | } | Block delimiter controlling scope/structure in this language.

L0366 | | Blank line used for readability and logical separation.

L0367 | body[data-theme="dark"] .photo-library-image { | Assignment statement storing or updating program state.

L0368 | background: #112137; | Operational statement participating in the file's runtime behavior.

L0369 | border-color: rgba(139, 181, 238, 0.16); | Operational statement participating in the file's runtime behavior.

L0370 | } | Block delimiter controlling scope/structure in this language.

L0371 | | Blank line used for readability and logical separation.

L0372 | body[data-theme="dark"] .photo-kind-image { | Assignment statement storing or updating program state.

L0373 | background: rgba(12, 68, 42, 0.6); | Operational statement participating in the file's runtime behavior.

L0374 | color: #7de0ae; | Operational statement participating in the file's runtime behavior.

L0375 | border-color: rgba(77, 191, 132, 0.4); | Operational statement participating in the file's runtime behavior.

L0376 | } | Block delimiter controlling scope/structure in this language.

L0377 | | Blank line used for readability and logical separation.

L0378 | body[data-theme="dark"] .photo-kind-screenshot { | Assignment statement storing or updating program state.

L0379 | background: rgba(84, 49, 0, 0.6); | Operational statement participating in the file's runtime behavior.

L0380 | color: #ffc477; | Operational statement participating in the file's runtime behavior.

L0381 | border-color: rgba(240, 176, 106, 0.4); | Operational statement participating in the file's runtime behavior.

L0382 | } | Block delimiter controlling scope/structure in this language.

L0383 | | Blank line used for readability and logical separation.

```

L0384 | .app-confirm-modal { | CSS selector line choosing the elements styled below.
L0385 |   border-radius: 16px; | Operational statement participating in the file's runtime behavior.
L0386 |   border: 1px solid rgba(5, 77, 166, 0.16); | Operational statement participating in the file's runtime behavior.
L0387 |   box-shadow: 0 22px 48px rgba(2, 22, 55, 0.22); | Operational statement participating in the file's runtime behavior.
L0388 | } | Block delimiter controlling scope/structure in this language.
L0389 | | Blank line used for readability and logical separation.
L0390 | .app-confirm-modal .modal-title { | CSS selector line choosing the elements styled below.
L0391 |   font-weight: 800; | Operational statement participating in the file's runtime behavior.
L0392 |   color: #10345f; | Operational statement participating in the file's runtime behavior.
L0393 | } | Block delimiter controlling scope/structure in this language.
L0394 | | Blank line used for readability and logical separation.
L0395 | body[data-theme="dark"] .app-confirm-modal { | Assignment statement storing or updating program state.
L0396 |   background: #172234; | Operational statement participating in the file's runtime behavior.
L0397 |   color: #e8eef8; | Operational statement participating in the file's runtime behavior.
L0398 |   border-color: rgba(154, 189, 242, 0.25); | Operational statement participating in the file's runtime behavior.
L0399 | } | Block delimiter controlling scope/structure in this language.
L0400 | | Blank line used for readability and logical separation.
L0401 | body[data-theme="dark"] .app-confirm-modal .modal-title { | Assignment statement storing or updating program state.
L0402 |   color: #dce8ff; | Operational statement participating in the file's runtime behavior.
L0403 | } | Block delimiter controlling scope/structure in this language.
L0404 | | Blank line used for readability and logical separation.
L0405 | body.app-is-loading { | Block delimiter controlling scope/structure in this language.
L0406 |   cursor: progress; | Operational statement participating in the file's runtime behavior.
L0407 | } | Block delimiter controlling scope/structure in this language.
L0408 | | Blank line used for readability and logical separation.
L0409 | @media (prefers-reduced-motion: reduce) { | Decorator line that modifies the behavior of the definition below.
L0410 |   .app-loader { | CSS selector line choosing the elements styled below.
L0411 |     transition: none; | Operational statement participating in the file's runtime behavior.
L0412 |   } | Block delimiter controlling scope/structure in this language.
L0413 | } | Block delimiter controlling scope/structure in this language.
L0414 | | Blank line used for readability and logical separation.
L0415 | @keyframes hover-float { | Decorator line that modifies the behavior of the definition below.
L0416 |   0% { | Block delimiter controlling scope/structure in this language.
L0417 |     transform: translateY(0); | Operational statement participating in the file's runtime behavior.
L0418 |   } | Block delimiter controlling scope/structure in this language.
L0419 |   100% { | Block delimiter controlling scope/structure in this language.
L0420 |     transform: translateY(-6px); | Operational statement participating in the file's runtime behavior.
L0421 |   } | Block delimiter controlling scope/structure in this language.
L0422 | } | Block delimiter controlling scope/structure in this language.
L0423 | | Blank line used for readability and logical separation.
L0424 | body { | Block delimiter controlling scope/structure in this language.
L0425 |   background-color: var(--secondary); | Operational statement participating in the file's runtime behavior.
L0426 |   background-image: linear-gradient(rgba(255, 255, 255, 0.52), rgba(255, 255, 255, 0.52)), url("/static/background-watermark.jpeg");
L0427 |   background-size: cover; | Operational statement participating in the file's runtime behavior.
L0428 |   background-position: center; | Operational statement participating in the file's runtime behavior.
L0429 |   background-attachment: fixed; | Operational statement participating in the file's runtime behavior.
L0430 |   color: var(--text-color); | Operational statement participating in the file's runtime behavior.
L0431 |   font-family: "Segoe UI", Roboto, Helvetica, Arial, sans-serif; | Operational statement participating in the file's runtime behavior.
L0432 |   margin: 0; | Operational statement participating in the file's runtime behavior.
L0433 |   padding: 0; | Operational statement participating in the file's runtime behavior.
L0434 | } | Block delimiter controlling scope/structure in this language.
L0435 | | Blank line used for readability and logical separation.
L0436 | body[data-theme="dark"] { | Assignment statement storing or updating program state.
L0437 |   background-image: linear-gradient(rgba(15, 23, 36, 0.60), rgba(15, 23, 36, 0.60)), url("/static/background-watermark.jpeg"); | Op
L0438 | } | Block delimiter controlling scope/structure in this language.

```

L0439 | | Blank line used for readability and logical separation.

L0440 | header { | Block delimiter controlling scope/structure in this language.

L0441 | background: var(--primary); | Operational statement participating in the file's runtime behavior.

L0442 | color: #ffffff; | Operational statement participating in the file's runtime behavior.

L0443 | padding: 1rem; | Operational statement participating in the file's runtime behavior.

L0444 | text-align: center; | Operational statement participating in the file's runtime behavior.

L0445 | font-size: 1.5rem; | Operational statement participating in the file's runtime behavior.

L0446 | font-weight: bold; | Operational statement participating in the file's runtime behavior.

L0447 | } | Block delimiter controlling scope/structure in this language.

L0448 | | Blank line used for readability and logical separation.

L0449 | button { | Block delimiter controlling scope/structure in this language.

L0450 | background: var(--primary); | Operational statement participating in the file's runtime behavior.

L0451 | color: #ffffff; | Operational statement participating in the file's runtime behavior.

L0452 | border: none; | Operational statement participating in the file's runtime behavior.

L0453 | border-radius: 4px; | Operational statement participating in the file's runtime behavior.

L0454 | padding: 0.5rem 1rem; | Operational statement participating in the file's runtime behavior.

L0455 | cursor: pointer; | Operational statement participating in the file's runtime behavior.

L0456 | transition: background 0.3s, box-shadow 0.25s ease, transform 0.25s ease; | Operational statement participating in the file's runtime behavior.

L0457 | } | Block delimiter controlling scope/structure in this language.

L0458 | | Blank line used for readability and logical separation.

L0459 | button:hover { | Block delimiter controlling scope/structure in this language.

L0460 | background: var(--accent); | Operational statement participating in the file's runtime behavior.

L0461 | animation: hover-float 0.6s ease-in-out infinite alternate; | Operational statement participating in the file's runtime behavior.

L0462 | box-shadow: 0 12px 24px rgba(5, 77, 166, 0.2); | Operational statement participating in the file's runtime behavior.

L0463 | } | Block delimiter controlling scope/structure in this language.

L0464 | | Blank line used for readability and logical separation.

L0465 | .card { | CSS selector line choosing the elements styled below.

L0466 | background: var(--card-bg); | Operational statement participating in the file's runtime behavior.

L0467 | box-shadow: var(--card-shadow); | Operational statement participating in the file's runtime behavior.

L0468 | border-radius: 8px; | Operational statement participating in the file's runtime behavior.

L0469 | padding: 1rem; | Operational statement participating in the file's runtime behavior.

L0470 | margin: 1rem 0; | Operational statement participating in the file's runtime behavior.

L0471 | } | Block delimiter controlling scope/structure in this language.

L0472 | | Blank line used for readability and logical separation.

L0473 | body[data-theme="dark"] .navbar, | Assignment statement storing or updating program state.

L0474 | body[data-theme="dark"] .offcanvas, | Assignment statement storing or updating program state.

L0475 | body[data-theme="dark"] .table, | Assignment statement storing or updating program state.

L0476 | body[data-theme="dark"] .table thead th, | Assignment statement storing or updating program state.

L0477 | body[data-theme="dark"] .list-group-item, | Assignment statement storing or updating program state.

L0478 | body[data-theme="dark"] .menu-work-card, | Assignment statement storing or updating program state.

L0479 | body[data-theme="dark"] .signature-card, | Assignment statement storing or updating program state.

L0480 | body[data-theme="dark"] .pm-form-table thead th { | Assignment statement storing or updating program state.

L0481 | background: #172234 !important; | Operational statement participating in the file's runtime behavior.

L0482 | color: #e8eef8; | Operational statement participating in the file's runtime behavior.

L0483 | } | Block delimiter controlling scope/structure in this language.

L0484 | | Blank line used for readability and logical separation.

L0485 | body[data-theme="dark"] .menu-link { | Assignment statement storing or updating program state.

L0486 | color: #b5c4d9; | Operational statement participating in the file's runtime behavior.

L0487 | } | Block delimiter controlling scope/structure in this language.

L0488 | | Blank line used for readability and logical separation.

L0489 | body[data-theme="dark"] .menu-toggle-button { | Assignment statement storing or updating program state.

L0490 | background: #223652 !important; | Operational statement participating in the file's runtime behavior.

L0491 | border-color: #4e719f !important; | Operational statement participating in the file's runtime behavior.

L0492 | box-shadow: 0 10px 24px rgba(0, 0, 0, 0.28); | Operational statement participating in the file's runtime behavior.

L0493 | } | Block delimiter controlling scope/structure in this language.

L0494 | | Blank line used for readability and logical separation.

L0495 | body[data-theme="dark"] .menu-toggle-button:hover { | Assignment statement storing or updating program state.

L0496 | background: #2a4366 !important; | Operational statement participating in the file's runtime behavior.

L0497 | } | Block delimiter controlling scope/structure in this language.

L0498 | | Blank line used for readability and logical separation.

L0499 | body[data-theme="dark"] .menu-toggle-lines span { | Assignment statement storing or updating program state.

L0500 | background: #ffffff; | Operational statement participating in the file's runtime behavior.

L0501 | height: 3px; | Operational statement participating in the file's runtime behavior.

L0502 | width: 24px; | Operational statement participating in the file's runtime behavior.

L0503 | box-shadow: 0 0 0 1px rgba(255, 255, 255, 0.14); | Operational statement participating in the file's runtime behavior.

L0504 | } | Block delimiter controlling scope/structure in this language.

L0505 | | Blank line used for readability and logical separation.

L0506 | body[data-theme="dark"] .btn-close { | Assignment statement storing or updating program state.

L0507 | filter: invert(1) grayscale(100%) brightness(200%); | Operational statement participating in the file's runtime behavior.

L0508 | } | Block delimiter controlling scope/structure in this language.

L0509 | | Blank line used for readability and logical separation.

L0510 | body[data-theme="dark"] .menu-link.active, | Assignment statement storing or updating program state.

L0511 | body[data-theme="dark"] .menu-link:hover { | Assignment statement storing or updating program state.

L0512 | background: #223652; | Operational statement participating in the file's runtime behavior.

L0513 | color: #ffffff; | Operational statement participating in the file's runtime behavior.

L0514 | } | Block delimiter controlling scope/structure in this language.

L0515 | | Blank line used for readability and logical separation.

L0516 | body[data-theme="dark"] .text-muted, | Assignment statement storing or updating program state.

L0517 | body[data-theme="dark"] .not-found-text, | Assignment statement storing or updating program state.

L0518 | body[data-theme="dark"] .dashboard-subtitle, | Assignment statement storing or updating program state.

L0519 | body[data-theme="dark"] .contact-role { | Assignment statement storing or updating program state.

L0520 | color: #a9b7cc !important; | Operational statement participating in the file's runtime behavior.

L0521 | } | Block delimiter controlling scope/structure in this language.

L0522 | | Blank line used for readability and logical separation.

L0523 | .main-container { | CSS selector line choosing the elements styled below.

L0524 | max-width: 1180px; | Operational statement participating in the file's runtime behavior.

L0525 | margin: 0 auto; | Operational statement participating in the file's runtime behavior.

L0526 | padding: 18px 16px; | Operational statement participating in the file's runtime behavior.

L0527 | } | Block delimiter controlling scope/structure in this language.

L0528 | | Blank line used for readability and logical separation.

L0529 | .dashboard-header h1 { | CSS selector line choosing the elements styled below.

L0530 | font-size: 30px; | Operational statement participating in the file's runtime behavior.

L0531 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L0532 | color: #0c3e73; | Operational statement participating in the file's runtime behavior.

L0533 | margin-bottom: 10px; | Operational statement participating in the file's runtime behavior.

L0534 | } | Block delimiter controlling scope/structure in this language.

L0535 | | Blank line used for readability and logical separation.

L0536 | .dashboard-hero { | CSS selector line choosing the elements styled below.

L0537 | display: grid; | Operational statement participating in the file's runtime behavior.

L0538 | gap: 1.25rem; | Operational statement participating in the file's runtime behavior.

L0539 | padding: 1.5rem; | Operational statement participating in the file's runtime behavior.

L0540 | border-radius: 24px; | Operational statement participating in the file's runtime behavior.

L0541 | background: linear-gradient(135deg, #fff8f0 0%, #eef6ff 55%, #e3f1ff 100%); | Operational statement participating in the file's runtime behavior.

L0542 | box-shadow: 0 18px 45px rgba(13, 58, 121, 0.12); | Operational statement participating in the file's runtime behavior.

L0543 | border: 1px solid rgba(13, 58, 121, 0.08); | Operational statement participating in the file's runtime behavior.

L0544 | } | Block delimiter controlling scope/structure in this language.

L0545 | | Blank line used for readability and logical separation.

L0546 | .dashboard-hero-brand { | CSS selector line choosing the elements styled below.

L0547 | display: flex; | Operational statement participating in the file's runtime behavior.

L0548 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L0549 | gap: 0.85rem; | Operational statement participating in the file's runtime behavior.

L0550 | } | Block delimiter controlling scope/structure in this language.

L0551 | | Blank line used for readability and logical separation.

L0552 | .dashboard-logo-stack { | CSS selector line choosing the elements styled below.

L0553 | display: flex; | Operational statement participating in the file's runtime behavior.

L0554 | flex-wrap: wrap; | Operational statement participating in the file's runtime behavior.

L0555 | gap: 0.75rem; | Operational statement participating in the file's runtime behavior.

L0556 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0557 | } | Block delimiter controlling scope/structure in this language.

L0558 | | Blank line used for readability and logical separation.

L0559 | .dashboard-eyebrow { | CSS selector line choosing the elements styled below.

L0560 | margin: 0; | Operational statement participating in the file's runtime behavior.

L0561 | color: #a11d2a; | Operational statement participating in the file's runtime behavior.

L0562 | font-size: 0.95rem; | Operational statement participating in the file's runtime behavior.

L0563 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L0564 | letter-spacing: 0.08em; | Operational statement participating in the file's runtime behavior.

L0565 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L0566 | } | Block delimiter controlling scope/structure in this language.

L0567 | | Blank line used for readability and logical separation.

L0568 | .dashboard-subtitle { | CSS selector line choosing the elements styled below.

L0569 | max-width: 760px; | Operational statement participating in the file's runtime behavior.

L0570 | margin: 0; | Operational statement participating in the file's runtime behavior.

L0571 | color: #385271; | Operational statement participating in the file's runtime behavior.

L0572 | font-size: 1rem; | Operational statement participating in the file's runtime behavior.

L0573 | } | Block delimiter controlling scope/structure in this language.

L0574 | | Blank line used for readability and logical separation.

L0575 | .feature-card { | CSS selector line choosing the elements styled below.

L0576 | border: 0; | Operational statement participating in the file's runtime behavior.

L0577 | border-radius: 22px; | Operational statement participating in the file's runtime behavior.

L0578 | min-height: 220px; | Operational statement participating in the file's runtime behavior.

L0579 | box-shadow: 0 16px 36px rgba(0, 44, 99, 0.12); | Operational statement participating in the file's runtime behavior.

L0580 | transition: transform 0.2s ease, box-shadow 0.2s ease; | Operational statement participating in the file's runtime behavior.

L0581 | } | Block delimiter controlling scope/structure in this language.

L0582 | | Blank line used for readability and logical separation.

L0583 | .feature-card .card-body { | CSS selector line choosing the elements styled below.

L0584 | display: flex; | Operational statement participating in the file's runtime behavior.

L0585 | align-items: flex-start; | Operational statement participating in the file's runtime behavior.

L0586 | gap: 1rem; | Operational statement participating in the file's runtime behavior.

L0587 | padding: 1.5rem; | Operational statement participating in the file's runtime behavior.

L0588 | } | Block delimiter controlling scope/structure in this language.

L0589 | | Blank line used for readability and logical separation.

L0590 | .feature-card:hover { | CSS selector line choosing the elements styled below.

L0591 | animation: hover-float 0.6s ease-in-out infinite alternate; | Operational statement participating in the file's runtime behavior.

L0592 | box-shadow: 0 20px 42px rgba(0, 44, 99, 0.18); | Operational statement participating in the file's runtime behavior.

L0593 | } | Block delimiter controlling scope/structure in this language.

L0594 | | Blank line used for readability and logical separation.

L0595 | .feature-card-pm { | CSS selector line choosing the elements styled below.

L0596 | background: linear-gradient(145deg, #fff0d7 0%, #fff8ee 100%); | Operational statement participating in the file's runtime behavior.

L0597 | } | Block delimiter controlling scope/structure in this language.

L0598 | | Blank line used for readability and logical separation.

L0599 | .feature-card-rca { | CSS selector line choosing the elements styled below.

L0600 | background: linear-gradient(145deg, #e8f4ff 0%, #f6fbff 100%); | Operational statement participating in the file's runtime behavior.

L0601 | } | Block delimiter controlling scope/structure in this language.

L0602 | | Blank line used for readability and logical separation.

L0603 | .feature-icon { | CSS selector line choosing the elements styled below.

L0604 | width: 72px; | Operational statement participating in the file's runtime behavior.

L0605 | height: 72px; | Operational statement participating in the file's runtime behavior.

L0606 | border-radius: 18px; | Operational statement participating in the file's runtime behavior.

L0607 | display: flex; | Operational statement participating in the file's runtime behavior.

L0608 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0609 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L0610 | font-size: 2rem; | Operational statement participating in the file's runtime behavior.

L0611 | flex-shrink: 0; | Operational statement participating in the file's runtime behavior.

L0612 | color: #fff; | Operational statement participating in the file's runtime behavior.

L0613 | background: linear-gradient(135deg, #d91525, #8d1020); | Operational statement participating in the file's runtime behavior.

L0614 | } | Block delimiter controlling scope/structure in this language.

L0615 | | Blank line used for readability and logical separation.

L0616 | .feature-card-rca .feature-icon { | CSS selector line choosing the elements styled below.

L0617 | background: linear-gradient(135deg, #0c5cc0, #08306f); | Operational statement participating in the file's runtime behavior.

L0618 | } | Block delimiter controlling scope/structure in this language.

L0619 | | Blank line used for readability and logical separation.

L0620 | .feature-label { | CSS selector line choosing the elements styled below.

L0621 | display: inline-block; | Operational statement participating in the file's runtime behavior.

L0622 | margin-bottom: 0.5rem; | Operational statement participating in the file's runtime behavior.

L0623 | color: #395373; | Operational statement participating in the file's runtime behavior.

L0624 | font-size: 0.9rem; | Operational statement participating in the file's runtime behavior.

L0625 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L0626 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L0627 | letter-spacing: 0.06em; | Operational statement participating in the file's runtime behavior.

L0628 | } | Block delimiter controlling scope/structure in this language.

L0629 | | Blank line used for readability and logical separation.

L0630 | .feature-card h2 { | CSS selector line choosing the elements styled below.

L0631 | font-size: 2.4rem; | Operational statement participating in the file's runtime behavior.

L0632 | margin-bottom: 0.5rem; | Operational statement participating in the file's runtime behavior.

L0633 | color: #102f59; | Operational statement participating in the file's runtime behavior.

L0634 | } | Block delimiter controlling scope/structure in this language.

L0635 | | Blank line used for readability and logical separation.

L0636 | .feature-card p { | CSS selector line choosing the elements styled below.

L0637 | margin: 0; | Operational statement participating in the file's runtime behavior.

L0638 | color: #385271; | Operational statement participating in the file's runtime behavior.

L0639 | } | Block delimiter controlling scope/structure in this language.

L0640 | | Blank line used for readability and logical separation.

L0641 | .stats-card { | CSS selector line choosing the elements styled below.

L0642 | border: 0; | Operational statement participating in the file's runtime behavior.

L0643 | border-radius: 20px; | Operational statement participating in the file's runtime behavior.

L0644 | min-height: 210px; | Operational statement participating in the file's runtime behavior.

L0645 | background: var(--card-bg-soft); | Operational statement participating in the file's runtime behavior.

L0646 | box-shadow: var(--card-shadow); | Operational statement participating in the file's runtime behavior.

L0647 | transition: transform 0.2s ease, box-shadow 0.2s ease; | Operational statement participating in the file's runtime behavior.

L0648 | } | Block delimiter controlling scope/structure in this language.

L0649 | | Blank line used for readability and logical separation.

L0650 | .card-link { | CSS selector line choosing the elements styled below.

L0651 | text-decoration: none; | Operational statement participating in the file's runtime behavior.

L0652 | color: inherit; | Operational statement participating in the file's runtime behavior.

L0653 | } | Block delimiter controlling scope/structure in this language.

L0654 | | Blank line used for readability and logical separation.

L0655 | .card-link:hover .stats-card { | CSS selector line choosing the elements styled below.

L0656 | animation: hover-float 0.6s ease-in-out infinite alternate; | Operational statement participating in the file's runtime behavior.

L0657 | box-shadow: 0 17px 40px rgba(45, 105, 255, 0.18); | Operational statement participating in the file's runtime behavior.

L0658 | } | Block delimiter controlling scope/structure in this language.

L0659 | | Blank line used for readability and logical separation.

L0660 | .stats-card:hover { | CSS selector line choosing the elements styled below.

L0661 | animation: hover-float 0.6s ease-in-out infinite alternate; | Operational statement participating in the file's runtime behavior.

L0662 | box-shadow: 0 17px 40px rgba(45, 105, 255, 0.18); | Operational statement participating in the file's runtime behavior.

L0663 | } | Block delimiter controlling scope/structure in this language.

L0664 | | Blank line used for readability and logical separation.

L0665 | .stats-icon { | CSS selector line choosing the elements styled below.

L0666 | width: 86px; | Operational statement participating in the file's runtime behavior.

L0667 | height: 86px; | Operational statement participating in the file's runtime behavior.

L0668 | border-radius: 50%; | Operational statement participating in the file's runtime behavior.

L0669 | background: radial-gradient(circle at top left, #b1deff, #d9edff); | Operational statement participating in the file's runtime behavior.

L0670 | display: flex; | Operational statement participating in the file's runtime behavior.

L0671 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0672 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L0673 | font-size: 2.2rem; | Operational statement participating in the file's runtime behavior.

L0674 | color: #0f53b0; | Operational statement participating in the file's runtime behavior.

L0675 | margin: 0 auto 12px; | Operational statement participating in the file's runtime behavior.

L0676 | box-shadow: 0 8px 25px rgba(0, 84, 164, 0.15); | Operational statement participating in the file's runtime behavior.

L0677 | } | Block delimiter controlling scope/structure in this language.

L0678 | | Blank line used for readability and logical separation.

L0679 | .stats-icon i { | CSS selector line choosing the elements styled below.

L0680 | font-size: 30px; | Operational statement participating in the file's runtime behavior.

L0681 | } | Block delimiter controlling scope/structure in this language.

L0682 | | Blank line used for readability and logical separation.

L0683 | .stats-card h1 { | CSS selector line choosing the elements styled below.

L0684 | color: #08306f; | Operational statement participating in the file's runtime behavior.

L0685 | font-size: 42px; | Operational statement participating in the file's runtime behavior.

L0686 | margin-bottom: 0; | Operational statement participating in the file's runtime behavior.

L0687 | } | Block delimiter controlling scope/structure in this language.

L0688 | | Blank line used for readability and logical separation.

L0689 | .stats-card p { | CSS selector line choosing the elements styled below.

L0690 | color: #0f53b0; | Operational statement participating in the file's runtime behavior.

L0691 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L0692 | font-size: 1.1rem; | Operational statement participating in the file's runtime behavior.

L0693 | margin: 0; | Operational statement participating in the file's runtime behavior.

L0694 | } | Block delimiter controlling scope/structure in this language.

L0695 | | Blank line used for readability and logical separation.

L0696 | .detail-header, .dashboard-header { | CSS selector line choosing the elements styled below.

L0697 | padding: 12px 0; | Operational statement participating in the file's runtime behavior.

L0698 | } | Block delimiter controlling scope/structure in this language.

L0699 | | Blank line used for readability and logical separation.

L0700 | .stats-card .card-body { | CSS selector line choosing the elements styled below.

L0701 | display: flex; | Operational statement participating in the file's runtime behavior.

L0702 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L0703 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L0704 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0705 | gap: 0.5rem; | Operational statement participating in the file's runtime behavior.

L0706 | } | Block delimiter controlling scope/structure in this language.

L0707 | | Blank line used for readability and logical separation.

L0708 | .stats-icon { | CSS selector line choosing the elements styled below.

L0709 | width: 90px; | Operational statement participating in the file's runtime behavior.

L0710 | height: 90px; | Operational statement participating in the file's runtime behavior.

L0711 | border-radius: 50%; | Operational statement participating in the file's runtime behavior.

L0712 | background: radial-gradient(circle at top left, #a8d9ff, #cfefff); | Operational statement participating in the file's runtime behavior.

L0713 | display: flex; | Operational statement participating in the file's runtime behavior.

L0714 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0715 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L0716 | font-size: 2rem; | Operational statement participating in the file's runtime behavior.

L0717 | color: #0f53b0; | Operational statement participating in the file's runtime behavior.

L0718 | margin-bottom: 0.5rem; | Operational statement participating in the file's runtime behavior.

L0719 | box-shadow: 0 8px 20px rgba(0, 81, 173, 0.2); | Operational statement participating in the file's runtime behavior.

L0720 | } | Block delimiter controlling scope/structure in this language.

L0721 | | Blank line used for readability and logical separation.

L0722 | .stats-card h1 { | CSS selector line choosing the elements styled below.

L0723 | color: #073999; | Operational statement participating in the file's runtime behavior.

L0724 | font-size: 2.5rem; | Operational statement participating in the file's runtime behavior.

L0725 | margin-bottom: 0; | Operational statement participating in the file's runtime behavior.

L0726 | } | Block delimiter controlling scope/structure in this language.

L0727 | | Blank line used for readability and logical separation.

L0728 | .stats-card p { | CSS selector line choosing the elements styled below.

L0729 | color: #0f53b0; | Operational statement participating in the file's runtime behavior.

L0730 | font-weight: 600; | Operational statement participating in the file's runtime behavior.

L0731 | margin-bottom: 0; | Operational statement participating in the file's runtime behavior.

L0732 | } | Block delimiter controlling scope/structure in this language.

L0733 | | Blank line used for readability and logical separation.

L0734 | .technician-action-card { | CSS selector line choosing the elements styled below.

L0735 | background: linear-gradient(145deg, #edf8ff 0%, #f8fcff 100%); | Operational statement participating in the file's runtime behavior.

L0736 | } | Block delimiter controlling scope/structure in this language.

L0737 | | Blank line used for readability and logical separation.

L0738 | h1 { | Block delimiter controlling scope/structure in this language.

L0739 | font-size: 2.2rem; | Operational statement participating in the file's runtime behavior.

L0740 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L0741 | margin-bottom: 1.25rem; | Operational statement participating in the file's runtime behavior.

L0742 | color: #0f264f; | Operational statement participating in the file's runtime behavior.

L0743 | } | Block delimiter controlling scope/structure in this language.

L0744 | | Blank line used for readability and logical separation.

L0745 | h2 { | Block delimiter controlling scope/structure in this language.

L0746 | font-size: 1.6rem; | Operational statement participating in the file's runtime behavior.

L0747 | color: #0d2949; | Operational statement participating in the file's runtime behavior.

L0748 | margin-bottom: 0.75rem; | Operational statement participating in the file's runtime behavior.

L0749 | } | Block delimiter controlling scope/structure in this language.

L0750 | | Blank line used for readability and logical separation.

L0751 | .detail-header h1 { | CSS selector line choosing the elements styled below.

L0752 | color: #132f6b; | Operational statement participating in the file's runtime behavior.

L0753 | font-size: 2rem; | Operational statement participating in the file's runtime behavior.

L0754 | font-weight: 900; | Operational statement participating in the file's runtime behavior.

L0755 | line-height: 1.1; | Operational statement participating in the file's runtime behavior.

L0756 | margin: 0; | Operational statement participating in the file's runtime behavior.

L0757 | } | Block delimiter controlling scope/structure in this language.

L0758 | | Blank line used for readability and logical separation.

L0759 | .detail-logo { | CSS selector line choosing the elements styled below.

L0760 | max-height: 60px; | Operational statement participating in the file's runtime behavior.

L0761 | height: 60px; | Operational statement participating in the file's runtime behavior.

L0762 | object-fit: contain; | Operational statement participating in the file's runtime behavior.

L0763 | } | Block delimiter controlling scope/structure in this language.

L0764 | | Blank line used for readability and logical separation.

L0765 | .detail-logo-box { | CSS selector line choosing the elements styled below.

L0766 | min-width: 100px; | Operational statement participating in the file's runtime behavior.

L0767 | padding: 8px 12px; | Operational statement participating in the file's runtime behavior.

L0768 | border-radius: 10px; | Operational statement participating in the file's runtime behavior.

L0769 | border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L0770 | background: #eef6ff; | Operational statement participating in the file's runtime behavior.

L0771 | } | Block delimiter controlling scope/structure in this language.

L0772 | | Blank line used for readability and logical separation.

L0773 | .logo-label { | CSS selector line choosing the elements styled below.

L0774 | font-size: 0.85rem; | Operational statement participating in the file's runtime behavior.

L0775 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L0776 | color: #174f88; | Operational statement participating in the file's runtime behavior.

L0777 | } | Block delimiter controlling scope/structure in this language.

L0778 | | Blank line used for readability and logical separation.

L0779 | .detail-card { | CSS selector line choosing the elements styled below.

L0780 | background: #ffffff; | Operational statement participating in the file's runtime behavior.

L0781 | border-radius: 18px; | Operational statement participating in the file's runtime behavior.

L0782 | box-shadow: 0 15px 35px rgba(0, 30, 80, 0.14); | Operational statement participating in the file's runtime behavior.

L0783 | padding: 24px; | Operational statement participating in the file's runtime behavior.

L0784 | } | Block delimiter controlling scope/structure in this language.

L0785 | | Blank line used for readability and logical separation.

L0786 | .detail-card .row + .row { | CSS selector line choosing the elements styled below.

L0787 | margin-top: 14px; | Operational statement participating in the file's runtime behavior.

L0788 | } | Block delimiter controlling scope/structure in this language.

L0789 | | Blank line used for readability and logical separation.

L0790 | .detail-card strong { | CSS selector line choosing the elements styled below.

L0791 | color: #143d78; | Operational statement participating in the file's runtime behavior.

L0792 | } | Block delimiter controlling scope/structure in this language.

L0793 | | Blank line used for readability and logical separation.

L0794 | .detail-card img { | CSS selector line choosing the elements styled below.

L0795 | border: 1px solid #dee2e6; | Operational statement participating in the file's runtime behavior.

L0796 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L0797 | max-height: 240px; | Operational statement participating in the file's runtime behavior.

L0798 | object-fit: cover; | Operational statement participating in the file's runtime behavior.

L0799 | } | Block delimiter controlling scope/structure in this language.

L0800 | | Blank line used for readability and logical separation.

L0801 | .card.course-card { | CSS selector line choosing the elements styled below.

L0802 | background: #fff; | Operational statement participating in the file's runtime behavior.

L0803 | border-radius: 16px; | Operational statement participating in the file's runtime behavior.

L0804 | box-shadow: 0 3px 15px rgba(20, 20, 60, 0.08); | Operational statement participating in the file's runtime behavior.

L0805 | padding: 1rem; | Operational statement participating in the file's runtime behavior.

L0806 | } | Block delimiter controlling scope/structure in this language.

L0807 | | Blank line used for readability and logical separation.

L0808 | .table { | CSS selector line choosing the elements styled below.

L0809 | background: white; | Operational statement participating in the file's runtime behavior.

L0810 | border-radius: 14px; | Operational statement participating in the file's runtime behavior.

L0811 | overflow: hidden; | Operational statement participating in the file's runtime behavior.

L0812 | } | Block delimiter controlling scope/structure in this language.

L0813 | | Blank line used for readability and logical separation.

L0814 | .table thead th { | CSS selector line choosing the elements styled below.

L0815 | background: #f6fbff; | Operational statement participating in the file's runtime behavior.

L0816 | color: #0c3d74; | Operational statement participating in the file's runtime behavior.

L0817 | border-bottom: 0; | Operational statement participating in the file's runtime behavior.

L0818 | } | Block delimiter controlling scope/structure in this language.

L0819 | | Blank line used for readability and logical separation.

L0820 | .table-hover tbody tr:hover { | CSS selector line choosing the elements styled below.

L0821 | background: #f4fafe; | Operational statement participating in the file's runtime behavior.

L0822 | animation: hover-float 0.6s ease-in-out infinite alternate; | Operational statement participating in the file's runtime behavior.

L0823 | box-shadow: 0 10px 24px rgba(12, 61, 116, 0.08); | Operational statement participating in the file's runtime behavior.

L0824 | } | Block delimiter controlling scope/structure in this language.

L0825 | | Blank line used for readability and logical separation.

L0826 | .list-group-item { | CSS selector line choosing the elements styled below.

L0827 | transition: transform 0.25s ease, box-shadow 0.25s ease, background-color 0.25s ease; | Operational statement participating in the file's runtime behavior.

L0828 | } | Block delimiter controlling scope/structure in this language.

L0829 | | Blank line used for readability and logical separation.

L0830 | .list-group-item:hover { | CSS selector line choosing the elements styled below.

L0831 | animation: hover-float 0.6s ease-in-out infinite alternate; | Operational statement participating in the file's runtime behavior.

L0832 | box-shadow: 0 10px 24px rgba(12, 61, 116, 0.08); | Operational statement participating in the file's runtime behavior.

L0833 | background: #f7fbff; | Operational statement participating in the file's runtime behavior.

L0834 | } | Block delimiter controlling scope/structure in this language.

L0835 | | Blank line used for readability and logical separation.

L0836 | .brand-chip { | CSS selector line choosing the elements styled below.

L0837 | display: inline-block; | Operational statement participating in the file's runtime behavior.

L0838 | font-size: 0.88rem; | Operational statement participating in the file's runtime behavior.

L0839 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L0840 | letter-spacing: 0.08em; | Operational statement participating in the file's runtime behavior.

L0841 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L0842 | padding: 0.3rem 0.65rem; | Operational statement participating in the file's runtime behavior.

L0843 | border-radius: 6px; | Operational statement participating in the file's runtime behavior.

L0844 | border: 1px solid transparent; | Operational statement participating in the file's runtime behavior.

L0845 | } | Block delimiter controlling scope/structure in this language.

L0846 | | Blank line used for readability and logical separation.

L0847 | .brand-soliton { | CSS selector line choosing the elements styled below.

L0848 | background-color: #d91525; | Operational statement participating in the file's runtime behavior.

L0849 | color: #fff; | Operational statement participating in the file's runtime behavior.

L0850 | border-color: #d91525; | Operational statement participating in the file's runtime behavior.

L0851 | } | Block delimiter controlling scope/structure in this language.

L0852 | | Blank line used for readability and logical separation.

L0853 | .brand-telmec { | CSS selector line choosing the elements styled below.

L0854 | background-color: #0055a4; | Operational statement participating in the file's runtime behavior.

L0855 | color: #ffde00; | Operational statement participating in the file's runtime behavior.

L0856 | border-color: #0055a4; | Operational statement participating in the file's runtime behavior.

L0857 | } | Block delimiter controlling scope/structure in this language.

L0858 | | Blank line used for readability and logical separation.

L0859 | .build-chip { | CSS selector line choosing the elements styled below.

L0860 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L0861 | align-items: center; | Operational statement participating in the file's runtime behavior.

L0862 | font-size: 0.68rem; | Operational statement participating in the file's runtime behavior.

L0863 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L0864 | letter-spacing: 0.04em; | Operational statement participating in the file's runtime behavior.

L0865 | color: #3f5f8d; | Operational statement participating in the file's runtime behavior.

L0866 | border: 1px solid #c8daf6; | Operational statement participating in the file's runtime behavior.

L0867 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L0868 | padding: 0.12rem 0.45rem; | Operational statement participating in the file's runtime behavior.

L0869 | background: #eef5ff; | Operational statement participating in the file's runtime behavior.

L0870 | } | Block delimiter controlling scope/structure in this language.

L0871 | | Blank line used for readability and logical separation.

L0872 | [data-theme="dark"] .build-chip { | Assignment statement storing or updating program state.

L0873 | color: #b9d1f2; | Operational statement participating in the file's runtime behavior.

L0874 | border-color: #45638b; | Operational statement participating in the file's runtime behavior.

L0875 | background: #1d304b; | Operational statement participating in the file's runtime behavior.

L0876 | } | Block delimiter controlling scope/structure in this language.

L0877 | | Blank line used for readability and logical separation.

L0878 | .navbar { | CSS selector line choosing the elements styled below.

L0879 | min-height: 76px; | Operational statement participating in the file's runtime behavior.
L0880 | } | Block delimiter controlling scope/structure in this language.
L0881 | | Blank line used for readability and logical separation.
L0882 | .menu-toggle-button { | CSS selector line choosing the elements styled below.
L0883 | width: 46px; | Operational statement participating in the file's runtime behavior.
L0884 | height: 46px; | Operational statement participating in the file's runtime behavior.
L0885 | border-radius: 14px; | Operational statement participating in the file's runtime behavior.
L0886 | display: inline-flex; | Operational statement participating in the file's runtime behavior.
L0887 | align-items: center; | Operational statement participating in the file's runtime behavior.
L0888 | justify-content: center; | Operational statement participating in the file's runtime behavior.
L0889 | text-decoration: none; | Operational statement participating in the file's runtime behavior.
L0890 | padding: 0 !important; | Operational statement participating in the file's runtime behavior.
L0891 | background: #eef6ff !important; | Operational statement participating in the file's runtime behavior.
L0892 | border: 1px solid #d7e7ff !important; | Operational statement participating in the file's runtime behavior.
L0893 | box-shadow: 0 8px 18px rgba(8, 59, 125, 0.08); | Operational statement participating in the file's runtime behavior.
L0894 | color: inherit !important; | Operational statement participating in the file's runtime behavior.
L0895 | } | Block delimiter controlling scope/structure in this language.
L0896 | | Blank line used for readability and logical separation.
L0897 | .menu-toggle-button:hover { | CSS selector line choosing the elements styled below.
L0898 | background: #dbeafe !important; | Operational statement participating in the file's runtime behavior.
L0899 | animation: none; | Operational statement participating in the file's runtime behavior.
L0900 | box-shadow: 0 10px 24px rgba(8, 59, 125, 0.14); | Operational statement participating in the file's runtime behavior.
L0901 | } | Block delimiter controlling scope/structure in this language.
L0902 | | Blank line used for readability and logical separation.
L0903 | .menu-toggle-lines { | CSS selector line choosing the elements styled below.
L0904 | display: inline-flex; | Operational statement participating in the file's runtime behavior.
L0905 | flex-direction: column; | Operational statement participating in the file's runtime behavior.
L0906 | justify-content: center; | Operational statement participating in the file's runtime behavior.
L0907 | gap: 5px; | Operational statement participating in the file's runtime behavior.
L0908 | } | Block delimiter controlling scope/structure in this language.
L0909 | | Blank line used for readability and logical separation.
L0910 | .menu-toggle-lines span { | CSS selector line choosing the elements styled below.
L0911 | display: block; | Operational statement participating in the file's runtime behavior.
L0912 | width: 22px; | Operational statement participating in the file's runtime behavior.
L0913 | height: 2.5px; | Operational statement participating in the file's runtime behavior.
L0914 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.
L0915 | background: #0d3c78; | Operational statement participating in the file's runtime behavior.
L0916 | } | Block delimiter controlling scope/structure in this language.
L0917 | | Blank line used for readability and logical separation.
L0918 | .login-page { | CSS selector line choosing the elements styled below.
L0919 | display: flex; | Operational statement participating in the file's runtime behavior.
L0920 | min-height: calc(100vh - 160px); | Operational statement participating in the file's runtime behavior.
L0921 | align-items: center; | Operational statement participating in the file's runtime behavior.
L0922 | justify-content: center; | Operational statement participating in the file's runtime behavior.
L0923 | padding: 24px 12px; | Operational statement participating in the file's runtime behavior.
L0924 | border-radius: 24px; | Operational statement participating in the file's runtime behavior.
L0925 | background-image: linear-gradient(rgba(8, 28, 53, 0.18), rgba(8, 28, 53, 0.18)), url("/static/background-watermark.jpeg"); | Oper
L0926 | background-size: cover; | Operational statement participating in the file's runtime behavior.
L0927 | background-position: center; | Operational statement participating in the file's runtime behavior.
L0928 | background-repeat: no-repeat; | Operational statement participating in the file's runtime behavior.
L0929 | } | Block delimiter controlling scope/structure in this language.
L0930 | | Blank line used for readability and logical separation.
L0931 | .login-card { | CSS selector line choosing the elements styled below.
L0932 | width: min(100%, 400px); | Operational statement participating in the file's runtime behavior.
L0933 | background: rgba(255, 255, 255, 0.95); | Operational statement participating in the file's runtime behavior.

L0934 | border-radius: 16px; | Operational statement participating in the file's runtime behavior.

L0935 | box-shadow: 0 12px 36px rgba(25, 63, 124, 0.15); | Operational statement participating in the file's runtime behavior.

L0936 | border: 1px solid #f0f5ff; | Operational statement participating in the file's runtime behavior.

L0937 | backdrop-filter: blur(2px); | Operational statement participating in the file's runtime behavior.

L0938 | } | Block delimiter controlling scope/structure in this language.

L0939 | | Blank line used for readability and logical separation.

L0940 | .login-share-card { | CSS selector line choosing the elements styled below.

L0941 | margin-top: 1rem; | Operational statement participating in the file's runtime behavior.

L0942 | padding: 0.9rem; | Operational statement participating in the file's runtime behavior.

L0943 | border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L0944 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L0945 | background: #f7fbff; | Operational statement participating in the file's runtime behavior.

L0946 | } | Block delimiter controlling scope/structure in this language.

L0947 | | Blank line used for readability and logical separation.

L0948 | .login-share-card h6 { | CSS selector line choosing the elements styled below.

L0949 | margin: 0 0 0.35rem; | Operational statement participating in the file's runtime behavior.

L0950 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L0951 | color: #0b3f80; | Operational statement participating in the file's runtime behavior.

L0952 | } | Block delimiter controlling scope/structure in this language.

L0953 | | Blank line used for readability and logical separation.

L0954 | .share-link-output { | CSS selector line choosing the elements styled below.

L0955 | word-break: break-all; | Operational statement participating in the file's runtime behavior.

L0956 | font-size: 0.93rem; | Operational statement participating in the file's runtime behavior.

L0957 | color: #174b8a; | Operational statement participating in the file's runtime behavior.

L0958 | } | Block delimiter controlling scope/structure in this language.

L0959 | | Blank line used for readability and logical separation.

L0960 | .share-link-actions { | CSS selector line choosing the elements styled below.

L0961 | display: flex; | Operational statement participating in the file's runtime behavior.

L0962 | gap: 0.5rem; | Operational statement participating in the file's runtime behavior.

L0963 | flex-wrap: wrap; | Operational statement participating in the file's runtime behavior.

L0964 | margin-top: 0.7rem; | Operational statement participating in the file's runtime behavior.

L0965 | } | Block delimiter controlling scope/structure in this language.

L0966 | | Blank line used for readability and logical separation.

L0967 | .share-link-actions .btn { | CSS selector line choosing the elements styled below.

L0968 | flex: 1 1 140px; | Operational statement participating in the file's runtime behavior.

L0969 | } | Block delimiter controlling scope/structure in this language.

L0970 | | Blank line used for readability and logical separation.

L0971 | .share-qr-wrap { | CSS selector line choosing the elements styled below.

L0972 | margin-top: 0.85rem; | Operational statement participating in the file's runtime behavior.

L0973 | padding: 0.8rem; | Operational statement participating in the file's runtime behavior.

L0974 | border: 1px dashed #bfd7fb; | Operational statement participating in the file's runtime behavior.

L0975 | border-radius: 10px; | Operational statement participating in the file's runtime behavior.

L0976 | background: #ffffff; | Operational statement participating in the file's runtime behavior.

L0977 | text-align: center; | Operational statement participating in the file's runtime behavior.

L0978 | } | Block delimiter controlling scope/structure in this language.

L0979 | | Blank line used for readability and logical separation.

L0980 | .share-qr-wrap img { | CSS selector line choosing the elements styled below.

L0981 | width: 170px; | Operational statement participating in the file's runtime behavior.

L0982 | height: 170px; | Operational statement participating in the file's runtime behavior.

L0983 | border-radius: 8px; | Operational statement participating in the file's runtime behavior.

L0984 | border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L0985 | background: #fff; | Operational statement participating in the file's runtime behavior.

L0986 | margin-bottom: 0.55rem; | Operational statement participating in the file's runtime behavior.

L0987 | } | Block delimiter controlling scope/structure in this language.

L0988 | | Blank line used for readability and logical separation.

L0989 | .share-qr-wrap p { | CSS selector line choosing the elements styled below.

L0990 | font-size: 0.86rem; | Operational statement participating in the file's runtime behavior.

L0991 | color: #4b6286; | Operational statement participating in the file's runtime behavior.

L0992 | } | Block delimiter controlling scope/structure in this language.

L0993 | | Blank line used for readability and logical separation.

L0994 | .notifications-board { | CSS selector line choosing the elements styled below.

L0995 | display: grid; | Operational statement participating in the file's runtime behavior.

L0996 | gap: 1rem; | Operational statement participating in the file's runtime behavior.

L0997 | } | Block delimiter controlling scope/structure in this language.

L0998 | | Blank line used for readability and logical separation.

L0999 | .notifications-headline { | CSS selector line choosing the elements styled below.

L1000 | padding: 1rem 1.1rem; | Operational statement participating in the file's runtime behavior.

L1001 | border-radius: 16px; | Operational statement participating in the file's runtime behavior.

L1002 | background: linear-gradient(135deg, #eef6ff 0%, #f9fcff 100%); | Operational statement participating in the file's runtime behavior.

L1003 | border: 1px solid #d8e8ff; | Operational statement participating in the file's runtime behavior.

L1004 | box-shadow: 0 12px 26px rgba(10, 58, 122, 0.1); | Operational statement participating in the file's runtime behavior.

L1005 | } | Block delimiter controlling scope/structure in this language.

L1006 | | Blank line used for readability and logical separation.

L1007 | .notifications-headline h1 { | CSS selector line choosing the elements styled below.

L1008 | margin-bottom: 0.35rem; | Operational statement participating in the file's runtime behavior.

L1009 | } | Block delimiter controlling scope/structure in this language.

L1010 | | Blank line used for readability and logical separation.

L1011 | .notify-shell { | CSS selector line choosing the elements styled below.

L1012 | border: 1px solid rgba(11, 63, 128, 0.12); | Operational statement participating in the file's runtime behavior.

L1013 | border-radius: 16px; | Operational statement participating in the file's runtime behavior.

L1014 | box-shadow: 0 14px 30px rgba(8, 50, 106, 0.1); | Operational statement participating in the file's runtime behavior.

L1015 | } | Block delimiter controlling scope/structure in this language.

L1016 | | Blank line used for readability and logical separation.

L1017 | .notify-composer-card { | CSS selector line choosing the elements styled below.

L1018 | background: linear-gradient(140deg, #ffffff 0%, #f9fcff 100%); | Operational statement participating in the file's runtime behavior.

L1019 | } | Block delimiter controlling scope/structure in this language.

L1020 | | Blank line used for readability and logical separation.

L1021 | .notify-inbox-card { | CSS selector line choosing the elements styled below.

L1022 | background: linear-gradient(160deg, #ffffff 0%, #f6fbff 100%); | Operational statement participating in the file's runtime behavior.

L1023 | } | Block delimiter controlling scope/structure in this language.

L1024 | | Blank line used for readability and logical separation.

L1025 | .notify-count-chip { | CSS selector line choosing the elements styled below.

L1026 | border: 1px solid #d1e3fd; | Operational statement participating in the file's runtime behavior.

L1027 | color: #0d4a96; | Operational statement participating in the file's runtime behavior.

L1028 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L1029 | padding: 0.45rem 0.7rem; | Operational statement participating in the file's runtime behavior.

L1030 | } | Block delimiter controlling scope/structure in this language.

L1031 | | Blank line used for readability and logical separation.

L1032 | .notify-message-list { | CSS selector line choosing the elements styled below.

L1033 | gap: 0.65rem; | Operational statement participating in the file's runtime behavior.

L1034 | background: transparent; | Operational statement participating in the file's runtime behavior.

L1035 | } | Block delimiter controlling scope/structure in this language.

L1036 | | Blank line used for readability and logical separation.

L1037 | .notify-message-card { | CSS selector line choosing the elements styled below.

L1038 | border: 1px solid #d9e8fb; | Operational statement participating in the file's runtime behavior.

L1039 | border-radius: 14px; | Operational statement participating in the file's runtime behavior.

L1040 | background: #ffffff; | Operational statement participating in the file's runtime behavior.

L1041 | box-shadow: 0 8px 22px rgba(15, 69, 139, 0.08); | Operational statement participating in the file's runtime behavior.

L1042 | } | Block delimiter controlling scope/structure in this language.

L1043 | | Blank line used for readability and logical separation.

L1044 | .notify-message-card .message-toggle-btn { | CSS selector line choosing the elements styled below.
L1045 | text-decoration: none; | Operational statement participating in the file's runtime behavior.
L1046 | color: inherit; | Operational statement participating in the file's runtime behavior.
L1047 | } | Block delimiter controlling scope/structure in this language.
L1048 | | Blank line used for readability and logical separation.
L1049 | .notify-message-card .message-toggle-btn:hover { | CSS selector line choosing the elements styled below.
L1050 | color: inherit; | Operational statement participating in the file's runtime behavior.
L1051 | } | Block delimiter controlling scope/structure in this language.
L1052 | | Blank line used for readability and logical separation.
L1053 | .notify-message-card .message-full-body { | CSS selector line choosing the elements styled below.
L1054 | background: linear-gradient(180deg, rgba(238, 246, 255, 0.6) 0%, rgba(255, 255, 255, 0.9) 100%); | Operational statement participating in the file's runtime behavior.
L1055 | border-radius: 10px; | Operational statement participating in the file's runtime behavior.
L1056 | } | Block delimiter controlling scope/structure in this language.
L1057 | | Blank line used for readability and logical separation.
L1058 | .review-board { | CSS selector line choosing the elements styled below.
L1059 | display: grid; | Operational statement participating in the file's runtime behavior.
L1060 | gap: 0.95rem; | Operational statement participating in the file's runtime behavior.
L1061 | } | Block delimiter controlling scope/structure in this language.
L1062 | | Blank line used for readability and logical separation.
L1063 | .review-headline-card { | CSS selector line choosing the elements styled below.
L1064 | padding: 1rem 1.1rem; | Operational statement participating in the file's runtime behavior.
L1065 | border-radius: 16px; | Operational statement participating in the file's runtime behavior.
L1066 | border: 1px solid #d7e8ff; | Operational statement participating in the file's runtime behavior.
L1067 | background: linear-gradient(135deg, #eef6ff 0%, #f9fcff 100%); | Operational statement participating in the file's runtime behavior.
L1068 | box-shadow: 0 12px 26px rgba(10, 58, 122, 0.1); | Operational statement participating in the file's runtime behavior.
L1069 | } | Block delimiter controlling scope/structure in this language.
L1070 | | Blank line used for readability and logical separation.
L1071 | .review-mode-card, | CSS selector line choosing the elements styled below.
L1072 | .review-status-card, | CSS selector line choosing the elements styled below.
L1073 | .review-filter-card, | CSS selector line choosing the elements styled below.
L1074 | .review-table-card { | CSS selector line choosing the elements styled below.
L1075 | border: 1px solid rgba(11, 63, 128, 0.12); | Operational statement participating in the file's runtime behavior.
L1076 | border-radius: 16px; | Operational statement participating in the file's runtime behavior.
L1077 | box-shadow: 0 14px 30px rgba(8, 50, 106, 0.1); | Operational statement participating in the file's runtime behavior.
L1078 | } | Block delimiter controlling scope/structure in this language.
L1079 | | Blank line used for readability and logical separation.
L1080 | .review-mode-card { | CSS selector line choosing the elements styled below.
L1081 | background: linear-gradient(145deg, #ffffff 0%, #f8fcff 100%); | Operational statement participating in the file's runtime behavior.
L1082 | } | Block delimiter controlling scope/structure in this language.
L1083 | | Blank line used for readability and logical separation.
L1084 | .review-status-card { | CSS selector line choosing the elements styled below.
L1085 | background: linear-gradient(160deg, #ffffff 0%, #f6fbff 100%); | Operational statement participating in the file's runtime behavior.
L1086 | } | Block delimiter controlling scope/structure in this language.
L1087 | | Blank line used for readability and logical separation.
L1088 | .review-filter-card { | CSS selector line choosing the elements styled below.
L1089 | background: linear-gradient(160deg, #ffffff 0%, #f9fcff 100%); | Operational statement participating in the file's runtime behavior.
L1090 | } | Block delimiter controlling scope/structure in this language.
L1091 | | Blank line used for readability and logical separation.
L1092 | .review-table-card { | CSS selector line choosing the elements styled below.
L1093 | background: linear-gradient(170deg, #ffffff 0%, #f7fbff 100%); | Operational statement participating in the file's runtime behavior.
L1094 | } | Block delimiter controlling scope/structure in this language.
L1095 | | Blank line used for readability and logical separation.
L1096 | .review-table-card .table { | CSS selector line choosing the elements styled below.
L1097 | margin-bottom: 0; | Operational statement participating in the file's runtime behavior.
L1098 | } | Block delimiter controlling scope/structure in this language.

L1099 | | Blank line used for readability and logical separation.

L1100 | .review-table-card thead th { | CSS selector line choosing the elements styled below.

L1101 | background: #eaf4ff; | Operational statement participating in the file's runtime behavior.

L1102 | color: #0d3f7d; | Operational statement participating in the file's runtime behavior.

L1103 | } | Block delimiter controlling scope/structure in this language.

L1104 | | Blank line used for readability and logical separation.

L1105 | .review-items-list { | CSS selector line choosing the elements styled below.

L1106 | display: flex; | Operational statement participating in the file's runtime behavior.

L1107 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L1108 | gap: 0.75rem; | Operational statement participating in the file's runtime behavior.

L1109 | } | Block delimiter controlling scope/structure in this language.

L1110 | | Blank line used for readability and logical separation.

L1111 | .review-item-card { | CSS selector line choosing the elements styled below.

L1112 | border: 1px solid rgba(11, 63, 128, 0.13); | Operational statement participating in the file's runtime behavior.

L1113 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L1114 | padding: 0.9rem 1rem; | Operational statement participating in the file's runtime behavior.

L1115 | background: linear-gradient(160deg, #ffffff 0%, #f4f9ff 100%); | Operational statement participating in the file's runtime behavior.

L1116 | box-shadow: 0 4px 12px rgba(8, 50, 106, 0.07); | Operational statement participating in the file's runtime behavior.

L1117 | transition: box-shadow 0.2s ease, transform 0.15s ease; | Operational statement participating in the file's runtime behavior.

L1118 | } | Block delimiter controlling scope/structure in this language.

L1119 | | Blank line used for readability and logical separation.

L1120 | .review-item-card:hover { | CSS selector line choosing the elements styled below.

L1121 | box-shadow: 0 8px 22px rgba(8, 50, 106, 0.14); | Operational statement participating in the file's runtime behavior.

L1122 | transform: translateY(-1px); | Operational statement participating in the file's runtime behavior.

L1123 | } | Block delimiter controlling scope/structure in this language.

L1124 | | Blank line used for readability and logical separation.

L1125 | .review-item-details { | CSS selector line choosing the elements styled below.

L1126 | font-size: 0.875rem; | Operational statement participating in the file's runtime behavior.

L1127 | color: #374151; | Operational statement participating in the file's runtime behavior.

L1128 | line-height: 1.55; | Operational statement participating in the file's runtime behavior.

L1129 | } | Block delimiter controlling scope/structure in this language.

L1130 | | Blank line used for readability and logical separation.

L1131 | .review-item-meta { | CSS selector line choosing the elements styled below.

L1132 | font-size: 0.78rem; | Operational statement participating in the file's runtime behavior.

L1133 | color: #6b7280; | Operational statement participating in the file's runtime behavior.

L1134 | } | Block delimiter controlling scope/structure in this language.

L1135 | | Blank line used for readability and logical separation.

L1136 | .review-item-rec { | CSS selector line choosing the elements styled below.

L1137 | font-size: 0.8rem; | Operational statement participating in the file's runtime behavior.

L1138 | color: #555; | Operational statement participating in the file's runtime behavior.

L1139 | } | Block delimiter controlling scope/structure in this language.

L1140 | | Blank line used for readability and logical separation.

L1141 | .review-item-actions { | CSS selector line choosing the elements styled below.

L1142 | align-items: flex-start; | Operational statement participating in the file's runtime behavior.

L1143 | padding-top: 0.15rem; | Operational statement participating in the file's runtime behavior.

L1144 | } | Block delimiter controlling scope/structure in this language.

L1145 | | Blank line used for readability and logical separation.

L1146 | [data-theme="dark"] .notifications-headline { | Assignment statement storing or updating program state.

L1147 | background: linear-gradient(135deg, #1a2a41 0%, #20354f 100%); | Operational statement participating in the file's runtime behavior.

L1148 | border-color: #38557c; | Operational statement participating in the file's runtime behavior.

L1149 | box-shadow: 0 16px 32px rgba(0, 0, 0, 0.28); | Operational statement participating in the file's runtime behavior.

L1150 | } | Block delimiter controlling scope/structure in this language.

L1151 | | Blank line used for readability and logical separation.

L1152 | [data-theme="dark"] .notify-shell { | Assignment statement storing or updating program state.

L1153 | border-color: #355274; | Operational statement participating in the file's runtime behavior.

L1154 | box-shadow: 0 18px 34px rgba(0, 0, 0, 0.3); | Operational statement participating in the file's runtime behavior.

L1155 | } | Block delimiter controlling scope/structure in this language.

L1156 | | Blank line used for readability and logical separation.

L1157 | [data-theme="dark"] .notify-composer-card, | Assignment statement storing or updating program state.

L1158 | [data-theme="dark"] .notify-inbox-card, | Assignment statement storing or updating program state.

L1159 | [data-theme="dark"] .notify-message-card { | Assignment statement storing or updating program state.

L1160 | background: #1b2b43; | Operational statement participating in the file's runtime behavior.

L1161 | border-color: #355274; | Operational statement participating in the file's runtime behavior.

L1162 | } | Block delimiter controlling scope/structure in this language.

L1163 | | Blank line used for readability and logical separation.

L1164 | [data-theme="dark"] .notify-count-chip { | Assignment statement storing or updating program state.

L1165 | color: #d8e8ff; | Operational statement participating in the file's runtime behavior.

L1166 | border-color: #4d709b; | Operational statement participating in the file's runtime behavior.

L1167 | background: #223652 !important; | Operational statement participating in the file's runtime behavior.

L1168 | } | Block delimiter controlling scope/structure in this language.

L1169 | | Blank line used for readability and logical separation.

L1170 | [data-theme="dark"] .notify-message-card .message-full-body { | Assignment statement storing or updating program state.

L1171 | background: linear-gradient(180deg, rgba(33, 54, 82, 0.65) 0%, rgba(27, 43, 67, 0.95) 100%); | Operational statement participating in the file's runtime behavior.

L1172 | } | Block delimiter controlling scope/structure in this language.

L1173 | | Blank line used for readability and logical separation.

L1174 | [data-theme="dark"] .review-headline-card { | Assignment statement storing or updating program state.

L1175 | background: linear-gradient(135deg, #1a2a41 0%, #20354f 100%); | Operational statement participating in the file's runtime behavior.

L1176 | border-color: #38557c; | Operational statement participating in the file's runtime behavior.

L1177 | box-shadow: 0 16px 32px rgba(0, 0, 0, 0.28); | Operational statement participating in the file's runtime behavior.

L1178 | } | Block delimiter controlling scope/structure in this language.

L1179 | | Blank line used for readability and logical separation.

L1180 | [data-theme="dark"] .review-mode-card, | Assignment statement storing or updating program state.

L1181 | [data-theme="dark"] .review-status-card, | Assignment statement storing or updating program state.

L1182 | [data-theme="dark"] .review-filter-card, | Assignment statement storing or updating program state.

L1183 | [data-theme="dark"] .review-table-card { | Assignment statement storing or updating program state.

L1184 | border-color: #355274; | Operational statement participating in the file's runtime behavior.

L1185 | background: #1b2b43; | Operational statement participating in the file's runtime behavior.

L1186 | box-shadow: 0 18px 34px rgba(0, 0, 0, 0.3); | Operational statement participating in the file's runtime behavior.

L1187 | } | Block delimiter controlling scope/structure in this language.

L1188 | | Blank line used for readability and logical separation.

L1189 | [data-theme="dark"] .review-table-card thead th { | Assignment statement storing or updating program state.

L1190 | background: #223652; | Operational statement participating in the file's runtime behavior.

L1191 | color: #d8e8ff; | Operational statement participating in the file's runtime behavior.

L1192 | } | Block delimiter controlling scope/structure in this language.

L1193 | | Blank line used for readability and logical separation.

L1194 | [data-theme="dark"] .review-item-card { | Assignment statement storing or updating program state.

L1195 | background: linear-gradient(160deg, #1b2b43 0%, #1d3049 100%); | Operational statement participating in the file's runtime behavior.

L1196 | border-color: #355274; | Operational statement participating in the file's runtime behavior.

L1197 | box-shadow: 0 4px 14px rgba(0, 0, 0, 0.24); | Operational statement participating in the file's runtime behavior.

L1198 | } | Block delimiter controlling scope/structure in this language.

L1199 | | Blank line used for readability and logical separation.

L1200 | [data-theme="dark"] .review-item-card:hover { | Assignment statement storing or updating program state.

L1201 | box-shadow: 0 8px 24px rgba(0, 0, 0, 0.36); | Operational statement participating in the file's runtime behavior.

L1202 | } | Block delimiter controlling scope/structure in this language.

L1203 | | Blank line used for readability and logical separation.

L1204 | [data-theme="dark"] .review-item-details { | Assignment statement storing or updating program state.

L1205 | color: #c8d8ed; | Operational statement participating in the file's runtime behavior.

L1206 | } | Block delimiter controlling scope/structure in this language.

L1207 | | Blank line used for readability and logical separation.

L1208 | [data-theme="dark"] .review-item-meta { | Assignment statement storing or updating program state.

L1209 | color: #7a9bbf; | Operational statement participating in the file's runtime behavior.

L1210 | } | Block delimiter controlling scope/structure in this language.

L1211 | | Blank line used for readability and logical separation.

L1212 | [data-theme="dark"] .review-item-rec { | Assignment statement storing or updating program state.

L1213 | color: #8ab4d8; | Operational statement participating in the file's runtime behavior.

L1214 | } | Block delimiter controlling scope/structure in this language.

L1215 | | Blank line used for readability and logical separation.

L1216 | @media (max-width: 768px) { | Decorator line that modifies the behavior of the definition below.

L1217 | .notifications-headline { | CSS selector line choosing the elements styled below.

L1218 | padding: 0.9rem; | Operational statement participating in the file's runtime behavior.

L1219 | } | Block delimiter controlling scope/structure in this language.

L1220 | | Blank line used for readability and logical separation.

L1221 | .review-headline-card { | CSS selector line choosing the elements styled below.

L1222 | padding: 0.9rem; | Operational statement participating in the file's runtime behavior.

L1223 | } | Block delimiter controlling scope/structure in this language.

L1224 | | Blank line used for readability and logical separation.

L1225 | .notify-message-card { | CSS selector line choosing the elements styled below.

L1226 | padding-left: 0.7rem !important; | Operational statement participating in the file's runtime behavior.

L1227 | padding-right: 0.7rem !important; | Operational statement participating in the file's runtime behavior.

L1228 | } | Block delimiter controlling scope/structure in this language.

L1229 | | Blank line used for readability and logical separation.

L1230 | .review-item-card { | CSS selector line choosing the elements styled below.

L1231 | padding: 0.75rem 0.8rem; | Operational statement participating in the file's runtime behavior.

L1232 | } | Block delimiter controlling scope/structure in this language.

L1233 | | Blank line used for readability and logical separation.

L1234 | .review-item-actions { | CSS selector line choosing the elements styled below.

L1235 | width: 100%; | Operational statement participating in the file's runtime behavior.

L1236 | margin-top: 0.5rem; | Operational statement participating in the file's runtime behavior.

L1237 | } | Block delimiter controlling scope/structure in this language.

L1238 | } | Block delimiter controlling scope/structure in this language.

L1239 | | Blank line used for readability and logical separation.

L1240 | [data-theme="dark"] .login-page { | Assignment statement storing or updating program state.

L1241 | background-image: linear-gradient(rgba(2, 8, 18, 0.52), rgba(2, 8, 18, 0.52)), url("/static/background-watermark.jpeg"); | Operat

L1242 | } | Block delimiter controlling scope/structure in this language.

L1243 | | Blank line used for readability and logical separation.

L1244 | [data-theme="dark"] .login-card { | Assignment statement storing or updating program state.

L1245 | background: rgba(23, 34, 52, 0.93); | Operational statement participating in the file's runtime behavior.

L1246 | border-color: #2d3f59; | Operational statement participating in the file's runtime behavior.

L1247 | } | Block delimiter controlling scope/structure in this language.

L1248 | | Blank line used for readability and logical separation.

L1249 | [data-theme="dark"] .login-share-card { | Assignment statement storing or updating program state.

L1250 | border-color: #31486b; | Operational statement participating in the file's runtime behavior.

L1251 | background: #1a2a41; | Operational statement participating in the file's runtime behavior.

L1252 | } | Block delimiter controlling scope/structure in this language.

L1253 | | Blank line used for readability and logical separation.

L1254 | [data-theme="dark"] .login-share-card h6, | Assignment statement storing or updating program state.

L1255 | [data-theme="dark"] .share-link-output { | Assignment statement storing or updating program state.

L1256 | color: #d8e8ff; | Operational statement participating in the file's runtime behavior.

L1257 | } | Block delimiter controlling scope/structure in this language.

L1258 | | Blank line used for readability and logical separation.

L1259 | [data-theme="dark"] .share-qr-wrap { | Assignment statement storing or updating program state.

L1260 | border-color: #31486b; | Operational statement participating in the file's runtime behavior.

L1261 | background: #172234; | Operational statement participating in the file's runtime behavior.

L1262 | } | Block delimiter controlling scope/structure in this language.

L1263 | | Blank line used for readability and logical separation.

```
L1264 | [data-theme="dark"] .share-qr-wrap img { | Assignment statement storing or updating program state.  
L1265 |   border-color: #31486b; | Operational statement participating in the file's runtime behavior.  
L1266 | } | Block delimiter controlling scope/structure in this language.  
L1267 | | Blank line used for readability and logical separation.  
L1268 | [data-theme="dark"] .share-qr-wrap p { | Assignment statement storing or updating program state.  
L1269 |   color: #c2d2e8; | Operational statement participating in the file's runtime behavior.  
L1270 | } | Block delimiter controlling scope/structure in this language.  
L1271 | | Blank line used for readability and logical separation.  
L1272 | .login-logo { | CSS selector line choosing the elements styled below.  
L1273 |   max-width: 170px; | Operational statement participating in the file's runtime behavior.  
L1274 |   height: auto; | Operational statement participating in the file's runtime behavior.  
L1275 | } | Block delimiter controlling scope/structure in this language.  
L1276 | | Blank line used for readability and logical separation.  
L1277 | .login-brand { | CSS selector line choosing the elements styled below.  
L1278 |   text-align: center; | Operational statement participating in the file's runtime behavior.  
L1279 | } | Block delimiter controlling scope/structure in this language.  
L1280 | | Blank line used for readability and logical separation.  
L1281 | .role-select-wrap .form-select { | CSS selector line choosing the elements styled below.  
L1282 |   border: 1px solid #c9dcfb; | Operational statement participating in the file's runtime behavior.  
L1283 |   border-radius: 10px; | Operational statement participating in the file's runtime behavior.  
L1284 |   background: linear-gradient(180deg, #ffffff 0%, #f3f8ff 100%); | Operational statement participating in the file's runtime behavi  
L1285 |   font-weight: 600; | Operational statement participating in the file's runtime behavior.  
L1286 | } | Block delimiter controlling scope/structure in this language.  
L1287 | | Blank line used for readability and logical separation.  
L1288 | .role-select-wrap .form-text { | CSS selector line choosing the elements styled below.  
L1289 |   color: #1f4c8c; | Operational statement participating in the file's runtime behavior.  
L1290 |   font-size: 0.82rem; | Operational statement participating in the file's runtime behavior.  
L1291 | } | Block delimiter controlling scope/structure in this language.  
L1292 | | Blank line used for readability and logical separation.  
L1293 | /* ■■■ Role pill row ████████████████████████████████████████████████████████████████████████████ */ | Operational statement participating in the fil  
L1294 | .role-pill-row { | CSS selector line choosing the elements styled below.  
L1295 |   display: flex; | Operational statement participating in the file's runtime behavior.  
L1296 |   flex-wrap: wrap; | Operational statement participating in the file's runtime behavior.  
L1297 |   gap: 0.4rem; | Operational statement participating in the file's runtime behavior.  
L1298 |   margin-top: 0.35rem; | Operational statement participating in the file's runtime behavior.  
L1299 | } | Block delimiter controlling scope/structure in this language.  
L1300 | | Blank line used for readability and logical separation.  
L1301 | .role-pill { | CSS selector line choosing the elements styled below.  
L1302 |   display: inline-flex; | Operational statement participating in the file's runtime behavior.  
L1303 |   align-items: center; | Operational statement participating in the file's runtime behavior.  
L1304 |   gap: 0.35rem; | Operational statement participating in the file's runtime behavior.  
L1305 |   padding: 0.32rem 0.75rem; | Operational statement participating in the file's runtime behavior.  
L1306 |   border-radius: 999px; | Operational statement participating in the file's runtime behavior.  
L1307 |   border: 1.5px solid #c6d9f5; | Operational statement participating in the file's runtime behavior.  
L1308 |   background: #f1f6fd; | Operational statement participating in the file's runtime behavior.  
L1309 |   color: #3566aa; | Operational statement participating in the file's runtime behavior.  
L1310 |   font-size: 0.8rem; | Operational statement participating in the file's runtime behavior.  
L1311 |   font-weight: 500; | Operational statement participating in the file's runtime behavior.  
L1312 |   cursor: pointer; | Operational statement participating in the file's runtime behavior.  
L1313 |   transition: background 0.15s, border-color 0.15s, color 0.15s, box-shadow 0.15s; | Operational statement participating in the fil  
L1314 |   white-space: nowrap; | Operational statement participating in the file's runtime behavior.  
L1315 |   line-height: 1.2; | Operational statement participating in the file's runtime behavior.  
L1316 | } | Block delimiter controlling scope/structure in this language.  
L1317 | | Blank line used for readability and logical separation.  
L1318 | .role-pill:hover:not(:disabled) { | CSS selector line choosing the elements styled below.
```

L1319 | background: #ddeeff; | Operational statement participating in the file's runtime behavior.

L1320 | border-color: #90b6e8; | Operational statement participating in the file's runtime behavior.

L1321 | color: #1a4d98; | Operational statement participating in the file's runtime behavior.

L1322 | } | Block delimiter controlling scope/structure in this language.

L1323 | | Blank line used for readability and logical separation.

L1324 | .role-pill.is-active { | CSS selector line choosing the elements styled below.

L1325 | background: #1a5fbf; | Operational statement participating in the file's runtime behavior.

L1326 | border-color: #1a5fbf; | Operational statement participating in the file's runtime behavior.

L1327 | color: #fff; | Operational statement participating in the file's runtime behavior.

L1328 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L1329 | box-shadow: 0 2px 8px rgba(26,95,186,0.22); | Operational statement participating in the file's runtime behavior.

L1330 | } | Block delimiter controlling scope/structure in this language.

L1331 | | Blank line used for readability and logical separation.

L1332 | .role-pill.disabled { | CSS selector line choosing the elements styled below.

L1333 | opacity: 0.45; | Operational statement participating in the file's runtime behavior.

L1334 | cursor: not-allowed; | Operational statement participating in the file's runtime behavior.

L1335 | } | Block delimiter controlling scope/structure in this language.

L1336 | | Blank line used for readability and logical separation.

L1337 | /* Per-role active colours */ | Operational statement participating in the file's runtime behavior.

L1338 | .role-pill[data-role="technician"].is-active { background: #0f7667; border-color: #0f7667; } | Assignment statement storing or updating program state.

L1339 | .role-pill[data-role="staff"].is-active { background: #1c61b4; border-color: #1c61b4; } | Assignment statement storing or updating program state.

L1340 | .role-pill[data-role="manager"].is-active { background: #a85a0d; border-color: #a85a0d; } | Assignment statement storing or updating program state.

L1341 | .role-pill[data-role="general_manager"].is-active { background: #0b7462; border-color: #0b7462; } | Assignment statement storing or updating program state.

L1342 | .role-pill[data-role="developer"].is-active { background: #ba3d33; border-color: #ba3d33; } | Assignment statement storing or updating program state.

L1343 | | Blank line used for readability and logical separation.

L1344 | [data-theme="dark"] .role-pill { | Assignment statement storing or updating program state.

L1345 | background: #1c2d44; | Operational statement participating in the file's runtime behavior.

L1346 | border-color: #2f4a6a; | Operational statement participating in the file's runtime behavior.

L1347 | color: #a8c4e0; | Operational statement participating in the file's runtime behavior.

L1348 | } | Block delimiter controlling scope/structure in this language.

L1349 | [data-theme="dark"] .role-pill:hover:not(:disabled) { | Assignment statement storing or updating program state.

L1350 | background: #223554; | Operational statement participating in the file's runtime behavior.

L1351 | border-color: #4a78b4; | Operational statement participating in the file's runtime behavior.

L1352 | color: #d0e5ff; | Operational statement participating in the file's runtime behavior.

L1353 | } | Block delimiter controlling scope/structure in this language.

L1354 | [data-theme="dark"] .role-pill.is-active { | Assignment statement storing or updating program state.

L1355 | background: #2a73d6; | Operational statement participating in the file's runtime behavior.

L1356 | border-color: #2a73d6; | Operational statement participating in the file's runtime behavior.

L1357 | color: #fff; | Operational statement participating in the file's runtime behavior.

L1358 | } | Block delimiter controlling scope/structure in this language.

L1359 | [data-theme="dark"] .role-pill[data-role="technician"].is-active { background: #0d8a7a; border-color: #0d8a7a; } | Assignment statement storing or updating program state.

L1360 | [data-theme="dark"] .role-pill[data-role="staff"].is-active { background: #2070cc; border-color: #2070cc; } | Assignment statement storing or updating program state.

L1361 | [data-theme="dark"] .role-pill[data-role="manager"].is-active { background: #c06a15; border-color: #c06a15; } | Assignment statement storing or updating program state.

L1362 | [data-theme="dark"] .role-pill[data-role="general_manager"].is-active { background: #0e8a76; border-color: #0e8a76; } | Assignment statement storing or updating program state.

L1363 | [data-theme="dark"] .role-pill[data-role="developer"].is-active { background: #cc4a40; border-color: #cc4a40; } | Assignment statement storing or updating program state.

L1364 | | Blank line used for readability and logical separation.

L1365 | .login-role-preview { | CSS selector line choosing the elements styled below.

L1366 | margin-top: 0.65rem; | Operational statement participating in the file's runtime behavior.

L1367 | border: 1px solid #cfe2ff; | Operational statement participating in the file's runtime behavior.

L1368 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L1369 | background: linear-gradient(135deg, #f4f9ff 0%, #edf6ff 100%); | Operational statement participating in the file's runtime behavior.

L1370 | padding: 0.6rem 0.7rem; | Operational statement participating in the file's runtime behavior.

L1371 | display: flex; | Operational statement participating in the file's runtime behavior.

L1372 | align-items: center; | Operational statement participating in the file's runtime behavior.

L1373 | gap: 0.6rem; | Operational statement participating in the file's runtime behavior.

L1374 | } | Block delimiter controlling scope/structure in this language.

L1375 | | Blank line used for readability and logical separation.

L1376 | .login-role-icon { | CSS selector line choosing the elements styled below.

L1377 | width: 32px; | Operational statement participating in the file's runtime behavior.

L1378 | height: 32px; | Operational statement participating in the file's runtime behavior.

L1379 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L1380 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L1381 | align-items: center; | Operational statement participating in the file's runtime behavior.

L1382 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L1383 | font-size: 0.95rem; | Operational statement participating in the file's runtime behavior.

L1384 | background: rgba(26, 95, 186, 0.12); | Operational statement participating in the file's runtime behavior.

L1385 | color: #2059a9; | Operational statement participating in the file's runtime behavior.

L1386 | } | Block delimiter controlling scope/structure in this language.

L1387 | | Blank line used for readability and logical separation.

L1388 | .login-role-copy { | CSS selector line choosing the elements styled below.

L1389 | display: flex; | Operational statement participating in the file's runtime behavior.

L1390 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L1391 | gap: 0.08rem; | Operational statement participating in the file's runtime behavior.

L1392 | } | Block delimiter controlling scope/structure in this language.

L1393 | | Blank line used for readability and logical separation.

L1394 | .login-role-copy strong { | CSS selector line choosing the elements styled below.

L1395 | font-size: 0.84rem; | Operational statement participating in the file's runtime behavior.

L1396 | color: #123f79; | Operational statement participating in the file's runtime behavior.

L1397 | line-height: 1.1; | Operational statement participating in the file's runtime behavior.

L1398 | } | Block delimiter controlling scope/structure in this language.

L1399 | | Blank line used for readability and logical separation.

L1400 | .login-role-copy small { | CSS selector line choosing the elements styled below.

L1401 | font-size: 0.73rem; | Operational statement participating in the file's runtime behavior.

L1402 | color: #466894; | Operational statement participating in the file's runtime behavior.

L1403 | line-height: 1.1; | Operational statement participating in the file's runtime behavior.

L1404 | } | Block delimiter controlling scope/structure in this language.

L1405 | | Blank line used for readability and logical separation.

L1406 | .login-role-preview.role-technician .login-role-icon { | CSS selector line choosing the elements styled below.

L1407 | background: rgba(20, 150, 130, 0.14); | Operational statement participating in the file's runtime behavior.

L1408 | color: #0f7667; | Operational statement participating in the file's runtime behavior.

L1409 | } | Block delimiter controlling scope/structure in this language.

L1410 | | Blank line used for readability and logical separation.

L1411 | .login-role-preview.role-staff .login-role-icon { | CSS selector line choosing the elements styled below.

L1412 | background: rgba(23, 109, 208, 0.14); | Operational statement participating in the file's runtime behavior.

L1413 | color: #1c61b4; | Operational statement participating in the file's runtime behavior.

L1414 | } | Block delimiter controlling scope/structure in this language.

L1415 | | Blank line used for readability and logical separation.

L1416 | .login-role-preview.role-manager .login-role-icon { | CSS selector line choosing the elements styled below.

L1417 | background: rgba(224, 122, 20, 0.18); | Operational statement participating in the file's runtime behavior.

L1418 | color: #a85a0d; | Operational statement participating in the file's runtime behavior.

L1419 | } | Block delimiter controlling scope/structure in this language.

L1420 | | Blank line used for readability and logical separation.

L1421 | .login-role-preview.role-general-manager .login-role-icon { | CSS selector line choosing the elements styled below.

L1422 | background: rgba(14, 126, 106, 0.16); | Operational statement participating in the file's runtime behavior.

L1423 | color: #0b7462; | Operational statement participating in the file's runtime behavior.

L1424 | } | Block delimiter controlling scope/structure in this language.

L1425 | | Blank line used for readability and logical separation.

L1426 | .login-role-preview.role-developer .login-role-icon { | CSS selector line choosing the elements styled below.

L1427 | background: rgba(220, 74, 64, 0.14); | Operational statement participating in the file's runtime behavior.

L1428 | color: #ba3d33; | Operational statement participating in the file's runtime behavior.

L1429 | } | Block delimiter controlling scope/structure in this language.

L1430 | | Blank line used for readability and logical separation.

L1431 | [data-theme="dark"] .login-role-preview { | Assignment statement storing or updating program state.

L1432 | border-color: #345072; | Operational statement participating in the file's runtime behavior.

L1433 | background: linear-gradient(135deg, #1b2b42 0%, #1a2a41 100%); | Operational statement participating in the file's runtime behavior.

L1434 | } | Block delimiter controlling scope/structure in this language.

L1435 | | Blank line used for readability and logical separation.

L1436 | [data-theme="dark"] .login-role-copy strong { | Assignment statement storing or updating program state.

L1437 | color: #dcecff; | Operational statement participating in the file's runtime behavior.

L1438 | } | Block delimiter controlling scope/structure in this language.

L1439 | | Blank line used for readability and logical separation.

L1440 | [data-theme="dark"] .login-role-copy small { | Assignment statement storing or updating program state.

L1441 | color: #a9bf9c; | Operational statement participating in the file's runtime behavior.

L1442 | } | Block delimiter controlling scope/structure in this language.

L1443 | | Blank line used for readability and logical separation.

L1444 | .active-role-pill { | CSS selector line choosing the elements styled below.

L1445 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L1446 | align-items: center; | Operational statement participating in the file's runtime behavior.

L1447 | gap: 0.4rem; | Operational statement participating in the file's runtime behavior.

L1448 | padding: 0.35rem 0.7rem; | Operational statement participating in the file's runtime behavior.

L1449 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L1450 | background: linear-gradient(135deg, #e7f2ff, #d4e8ff); | Operational statement participating in the file's runtime behavior.

L1451 | color: #0f4e9c; | Operational statement participating in the file's runtime behavior.

L1452 | border: 1px solid #b9d5fb; | Operational statement participating in the file's runtime behavior.

L1453 | font-size: 0.82rem; | Operational statement participating in the file's runtime behavior.

L1454 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L1455 | letter-spacing: 0.02em; | Operational statement participating in the file's runtime behavior.

L1456 | } | Block delimiter controlling scope/structure in this language.

L1457 | | Blank line used for readability and logical separation.

L1458 | .role-notification-wrap { | CSS selector line choosing the elements styled below.

L1459 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L1460 | align-items: center; | Operational statement participating in the file's runtime behavior.

L1461 | gap: 0.55rem; | Operational statement participating in the file's runtime behavior.

L1462 | } | Block delimiter controlling scope/structure in this language.

L1463 | | Blank line used for readability and logical separation.

L1464 | .role-icon-badge { | CSS selector line choosing the elements styled below.

L1465 | width: 20px; | Operational statement participating in the file's runtime behavior.

L1466 | height: 20px; | Operational statement participating in the file's runtime behavior.

L1467 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L1468 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L1469 | align-items: center; | Operational statement participating in the file's runtime behavior.

L1470 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L1471 | background: rgba(255, 255, 255, 0.6); | Operational statement participating in the file's runtime behavior.

L1472 | border: 1px solid rgba(64, 121, 201, 0.25); | Operational statement participating in the file's runtime behavior.

L1473 | } | Block delimiter controlling scope/structure in this language.

L1474 | | Blank line used for readability and logical separation.

L1475 | .role-icon-badge i { | CSS selector line choosing the elements styled below.

L1476 | font-size: 0.72rem; | Operational statement participating in the file's runtime behavior.

L1477 | } | Block delimiter controlling scope/structure in this language.

L1478 | | Blank line used for readability and logical separation.

L1479 | :root { | Block delimiter controlling scope/structure in this language.

L1480 | --ios-blue: #0a84ff; | Operational statement participating in the file's runtime behavior.

L1481 | --ios-indigo: #5e5ce6; | Operational statement participating in the file's runtime behavior.

L1482 | --ios-green: #34c759; | Operational statement participating in the file's runtime behavior.

L1483 | --ios-red: #ff3b30; | Operational statement participating in the file's runtime behavior.

L1484 | --ios-orange: #ff9f0a; | Operational statement participating in the file's runtime behavior.

L1485 | --ios-surface: rgba(255, 255, 255, 0.78); | Operational statement participating in the file's runtime behavior.

L1486 | --ios-surface-strong: rgba(255, 255, 255, 0.9); | Operational statement participating in the file's runtime behavior.

L1487 | --ios-border: rgba(15, 23, 42, 0.08); | Operational statement participating in the file's runtime behavior.

L1488 | --ios-shadow: 0 20px 48px rgba(15, 23, 42, 0.08); | Operational statement participating in the file's runtime behavior.

L1489 | --ios-shadow-soft: 0 10px 24px rgba(15, 23, 42, 0.06); | Operational statement participating in the file's runtime behavior.

L1490 | } | Block delimiter controlling scope/structure in this language.

L1491 | | Blank line used for readability and logical separation.

L1492 | body[data-theme="dark"] { | Assignment statement storing or updating program state.

L1493 | --ios-surface: rgba(24, 28, 40, 0.8); | Operational statement participating in the file's runtime behavior.

L1494 | --ios-surface-strong: rgba(28, 34, 48, 0.92); | Operational statement participating in the file's runtime behavior.

L1495 | --ios-border: rgba(255, 255, 255, 0.08); | Operational statement participating in the file's runtime behavior.

L1496 | --ios-shadow: 0 24px 54px rgba(0, 0, 0, 0.35); | Operational statement participating in the file's runtime behavior.

L1497 | --ios-shadow-soft: 0 12px 28px rgba(0, 0, 0, 0.24); | Operational statement participating in the file's runtime behavior.

L1498 | } | Block delimiter controlling scope/structure in this language.

L1499 | | Blank line used for readability and logical separation.

L1500 | body { | Block delimiter controlling scope/structure in this language.

L1501 | font-family: "SF Pro Display", "SF Pro Text", -apple-system, BlinkMacSystemFont, "Segoe UI", sans-serif; | Operational statement

L1502 | background-color: #eef3f9; | Operational statement participating in the file's runtime behavior.

L1503 | background-image: | Operational statement participating in the file's runtime behavior.

L1504 | radial-gradient(circle at top left, rgba(255, 255, 255, 0.72), rgba(255, 255, 255, 0) 34%), | Operational statement participating

L1505 | radial-gradient(circle at top right, rgba(189, 227, 255, 0.48), rgba(189, 227, 255, 0) 28%), | Operational statement participating

L1506 | linear-gradient(180deg, rgba(245, 248, 252, 0.76), rgba(233, 239, 247, 0.76)), | Operational statement participating in the file's runtime behavior.

L1507 | url("/static/background-watermark.jpeg"); | Operational statement participating in the file's runtime behavior.

L1508 | background-size: cover, cover, cover, 720px auto; | Operational statement participating in the file's runtime behavior.

L1509 | background-position: top left, top right, center, center top; | Operational statement participating in the file's runtime behavior.

L1510 | } | Block delimiter controlling scope/structure in this language.

L1511 | | Blank line used for readability and logical separation.

L1512 | body[data-theme="dark"] { | Assignment statement storing or updating program state.

L1513 | background-image: | Operational statement participating in the file's runtime behavior.

L1514 | radial-gradient(circle at top left, rgba(85, 112, 255, 0.18), rgba(85, 112, 255, 0) 28%), | Operational statement participating

L1515 | radial-gradient(circle at top right, rgba(10, 132, 255, 0.24), rgba(10, 132, 255, 0) 28%), | Operational statement participating

L1516 | linear-gradient(180deg, rgba(10, 14, 24, 0.82), rgba(17, 22, 34, 0.86)), | Operational statement participating in the file's runtime behavior.

L1517 | url("/static/background-watermark.jpeg"); | Operational statement participating in the file's runtime behavior.

L1518 | background-size: cover, cover, cover, 760px auto; | Operational statement participating in the file's runtime behavior.

L1519 | background-position: top left, top right, center, center top; | Operational statement participating in the file's runtime behavior.

L1520 | } | Block delimiter controlling scope/structure in this language.

L1521 | | Blank line used for readability and logical separation.

L1522 | .navbar, | CSS selector line choosing the elements styled below.

L1523 | .offcanvas, | CSS selector line choosing the elements styled below.

L1524 | .card, | CSS selector line choosing the elements styled below.

L1525 | .detail-card, | CSS selector line choosing the elements styled below.

L1526 | .stats-card, | CSS selector line choosing the elements styled below.

L1527 | .app-loader-card, | CSS selector line choosing the elements styled below.

L1528 | .app-confirm-modal, | CSS selector line choosing the elements styled below.

L1529 | .holiday-popup-card, | CSS selector line choosing the elements styled below.

L1530 | .menu-work-card, | CSS selector line choosing the elements styled below.

L1531 | .login-card, | CSS selector line choosing the elements styled below.

L1532 | .notify-shell, | CSS selector line choosing the elements styled below.

L1533 | .review-mode-card, | CSS selector line choosing the elements styled below.

L1534 | .review-status-card, | CSS selector line choosing the elements styled below.

L1535 | .review-filter-card, | CSS selector line choosing the elements styled below.

L1536 | .review-table-card, | CSS selector line choosing the elements styled below.

L1537 | .review-item-card, | CSS selector line choosing the elements styled below.

L1538 | .notifications-headline, | CSS selector line choosing the elements styled below.

L1539 | .review-headline-card { | CSS selector line choosing the elements styled below.

L1540 | background: var(--ios-surface) !important; | Operational statement participating in the file's runtime behavior.

L1541 | border: 1px solid var(--ios-border) !important; | Operational statement participating in the file's runtime behavior.

L1542 | box-shadow: var(--ios-shadow) !important; | Operational statement participating in the file's runtime behavior.

L1543 | backdrop-filter: blur(22px); | Operational statement participating in the file's runtime behavior.

L1544 | -webkit-backdrop-filter: blur(22px); | Operational statement participating in the file's runtime behavior.

L1545 | } | Block delimiter controlling scope/structure in this language.

L1546 | | Blank line used for readability and logical separation.

L1547 | .navbar { | CSS selector line choosing the elements styled below.

L1548 | background: rgba(255, 255, 255, 0.72) !important; | Operational statement participating in the file's runtime behavior.

L1549 | border-bottom: 1px solid rgba(15, 23, 42, 0.06) !important; | Operational statement participating in the file's runtime behavior.

L1550 | box-shadow: 0 8px 28px rgba(15, 23, 42, 0.05) !important; | Operational statement participating in the file's runtime behavior.

L1551 | } | Block delimiter controlling scope/structure in this language.

L1552 | | Blank line used for readability and logical separation.

L1553 | body[data-theme="dark"] .navbar { | Assignment statement storing or updating program state.

L1554 | background: rgba(20, 24, 34, 0.74) !important; | Operational statement participating in the file's runtime behavior.

L1555 | } | Block delimiter controlling scope/structure in this language.

L1556 | | Blank line used for readability and logical separation.

L1557 | .main-container { | CSS selector line choosing the elements styled below.

L1558 | max-width: 1240px; | Operational statement participating in the file's runtime behavior.

L1559 | padding-top: 1.35rem; | Operational statement participating in the file's runtime behavior.

L1560 | padding-bottom: 2rem; | Operational statement participating in the file's runtime behavior.

L1561 | } | Block delimiter controlling scope/structure in this language.

L1562 | | Blank line used for readability and logical separation.

L1563 | .page-utility-bar { | CSS selector line choosing the elements styled below.

L1564 | display: flex; | Operational statement participating in the file's runtime behavior.

L1565 | justify-content: flex-start; | Operational statement participating in the file's runtime behavior.

L1566 | margin-bottom: 0.9rem; | Operational statement participating in the file's runtime behavior.

L1567 | } | Block delimiter controlling scope/structure in this language.

L1568 | | Blank line used for readability and logical separation.

L1569 | .page-back-pill { | CSS selector line choosing the elements styled below.

L1570 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L1571 | align-items: center; | Operational statement participating in the file's runtime behavior.

L1572 | gap: 0.45rem; | Operational statement participating in the file's runtime behavior.

L1573 | padding: 0.72rem 1.05rem; | Operational statement participating in the file's runtime behavior.

L1574 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L1575 | text-decoration: none; | Operational statement participating in the file's runtime behavior.

L1576 | color: #0b4d92; | Operational statement participating in the file's runtime behavior.

L1577 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L1578 | letter-spacing: -0.01em; | Operational statement participating in the file's runtime behavior.

L1579 | background: rgba(255, 255, 255, 0.72); | Operational statement participating in the file's runtime behavior.

L1580 | border: 1px solid rgba(15, 23, 42, 0.06); | Operational statement participating in the file's runtime behavior.

L1581 | box-shadow: 0 10px 24px rgba(15, 23, 42, 0.08); | Operational statement participating in the file's runtime behavior.

L1582 | backdrop-filter: blur(18px); | Operational statement participating in the file's runtime behavior.

L1583 | -webkit-backdrop-filter: blur(18px); | Operational statement participating in the file's runtime behavior.

L1584 | transition: transform 0.18s ease, box-shadow 0.18s ease, background-color 0.18s ease, color 0.18s ease; | Operational statement participating in the file's runtime behavior.

L1585 | } | Block delimiter controlling scope/structure in this language.

L1586 | | Blank line used for readability and logical separation.

L1587 | .page-back-pill:hover, | CSS selector line choosing the elements styled below.

L1588 | .page-back-pill:focus-visible { | CSS selector line choosing the elements styled below.

L1589 | color: #ffffff; | Operational statement participating in the file's runtime behavior.

L1590 | background: linear-gradient(180deg, #3da0ff 0%, var(--ios-blue) 100%); | Operational statement participating in the file's runtime behavior.

L1591 | box-shadow: 0 16px 30px rgba(10, 132, 255, 0.2); | Operational statement participating in the file's runtime behavior.

L1592 | transform: translateY(-1px); | Operational statement participating in the file's runtime behavior.

L1593 | } | Block delimiter controlling scope/structure in this language.

L1594 | | Blank line used for readability and logical separation.

L1595 | .page-back-pill i { | CSS selector line choosing the elements styled below.

L1596 | font-size: 0.92rem; | Operational statement participating in the file's runtime behavior.

L1597 | } | Block delimiter controlling scope/structure in this language.

L1598 | | Blank line used for readability and logical separation.

L1599 | body[data-theme="dark"] .page-back-pill { | Assignment statement storing or updating program state.

L1600 | color: #dcecff; | Operational statement participating in the file's runtime behavior.

L1601 | background: rgba(28, 34, 48, 0.84); | Operational statement participating in the file's runtime behavior.

L1602 | border-color: rgba(255, 255, 255, 0.08); | Operational statement participating in the file's runtime behavior.

L1603 | } | Block delimiter controlling scope/structure in this language.

L1604 | | Blank line used for readability and logical separation.

L1605 | body[data-theme="dark"] .page-back-pill:hover, | Assignment statement storing or updating program state.

L1606 | body[data-theme="dark"] .page-back-pill:focus-visible { | Assignment statement storing or updating program state.

L1607 | color: #ffffff; | Operational statement participating in the file's runtime behavior.

L1608 | } | Block delimiter controlling scope/structure in this language.

L1609 | | Blank line used for readability and logical separation.

L1610 | h1, | Operational statement participating in the file's runtime behavior.

L1611 | h2, | Operational statement participating in the file's runtime behavior.

L1612 | h3, | Operational statement participating in the file's runtime behavior.

L1613 | h4, | Operational statement participating in the file's runtime behavior.

L1614 | h5, | Operational statement participating in the file's runtime behavior.

L1615 | h6 { | Block delimiter controlling scope/structure in this language.

L1616 | letter-spacing: -0.02em; | Operational statement participating in the file's runtime behavior.

L1617 | } | Block delimiter controlling scope/structure in this language.

L1618 | | Blank line used for readability and logical separation.

L1619 | h1 { | Block delimiter controlling scope/structure in this language.

L1620 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L1621 | } | Block delimiter controlling scope/structure in this language.

L1622 | | Blank line used for readability and logical separation.

L1623 | .card, | CSS selector line choosing the elements styled below.

L1624 | .detail-card, | CSS selector line choosing the elements styled below.

L1625 | .stats-card, | CSS selector line choosing the elements styled below.

L1626 | .login-card, | CSS selector line choosing the elements styled below.

L1627 | .notify-message-card, | CSS selector line choosing the elements styled below.

L1628 | .review-item-card, | CSS selector line choosing the elements styled below.

L1629 | .table, | CSS selector line choosing the elements styled below.

L1630 | .alert, | CSS selector line choosing the elements styled below.

L1631 | .list-group-item, | CSS selector line choosing the elements styled below.

L1632 | .modal-content, | CSS selector line choosing the elements styled below.

L1633 | .offcanvas, | CSS selector line choosing the elements styled below.

L1634 | .share-qr-wrap, | CSS selector line choosing the elements styled below.

L1635 | .login-share-card, | CSS selector line choosing the elements styled below.

L1636 | .login-role-preview { | CSS selector line choosing the elements styled below.

L1637 | border-radius: 24px !important; | Operational statement participating in the file's runtime behavior.

L1638 | } | Block delimiter controlling scope/structure in this language.

L1639 | | Blank line used for readability and logical separation.

L1640 | .table, | CSS selector line choosing the elements styled below.

L1641 | .list-group-item, | CSS selector line choosing the elements styled below.

L1642 | .alert, | CSS selector line choosing the elements styled below.

L1643 | .share-qr-wrap, | CSS selector line choosing the elements styled below.

L1644 | .login-share-card, | CSS selector line choosing the elements styled below.

L1645 | .login-role-preview, | CSS selector line choosing the elements styled below.

L1646 | .table thead th { | CSS selector line choosing the elements styled below.

L1647 | background: var(--ios-surface-strong) !important; | Operational statement participating in the file's runtime behavior.

L1648 | } | Block delimiter controlling scope/structure in this language.

L1649 | | Blank line used for readability and logical separation.

L1650 | .btn, | CSS selector line choosing the elements styled below.

L1651 | button, | Operational statement participating in the file's runtime behavior.

L1652 | .page-link, | CSS selector line choosing the elements styled below.

L1653 | .menu-link, | CSS selector line choosing the elements styled below.

L1654 | .active-role-pill, | CSS selector line choosing the elements styled below.

L1655 | .notification-bell, | CSS selector line choosing the elements styled below.

L1656 | .build-chip, | CSS selector line choosing the elements styled below.

L1657 | .brand-chip, | CSS selector line choosing the elements styled below.

L1658 | .badge, | CSS selector line choosing the elements styled below.

L1659 | .form-control, | CSS selector line choosing the elements styled below.

L1660 | .form-select, | CSS selector line choosing the elements styled below.

L1661 | .form-check-input { | CSS selector line choosing the elements styled below.

L1662 | border-radius: 16px !important; | Operational statement participating in the file's runtime behavior.

L1663 | } | Block delimiter controlling scope/structure in this language.

L1664 | | Blank line used for readability and logical separation.

L1665 | .btn, | CSS selector line choosing the elements styled below.

L1666 | button, | Operational statement participating in the file's runtime behavior.

L1667 | .page-link { | CSS selector line choosing the elements styled below.

L1668 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L1669 | border: 0; | Operational statement participating in the file's runtime behavior.

L1670 | box-shadow: var(--ios-shadow-soft); | Operational statement participating in the file's runtime behavior.

L1671 | transition: transform 0.18s ease, box-shadow 0.18s ease, background-color 0.18s ease, opacity 0.18s ease; | Operational statement participating in the file's runtime behavior.

L1672 | } | Block delimiter controlling scope/structure in this language.

L1673 | | Blank line used for readability and logical separation.

L1674 | .btn:hover, | CSS selector line choosing the elements styled below.

L1675 | button:hover, | Operational statement participating in the file's runtime behavior.

L1676 | .page-link:hover { | CSS selector line choosing the elements styled below.

L1677 | animation: none; | Operational statement participating in the file's runtime behavior.

L1678 | transform: translateY(-1px) scale(1.01); | Operational statement participating in the file's runtime behavior.

L1679 | box-shadow: 0 16px 30px rgba(15, 23, 42, 0.12); | Operational statement participating in the file's runtime behavior.

L1680 | } | Block delimiter controlling scope/structure in this language.

L1681 | | Blank line used for readability and logical separation.

L1682 | .btn:active, | CSS selector line choosing the elements styled below.

L1683 | button:active, | Operational statement participating in the file's runtime behavior.

L1684 | .page-link:active { | CSS selector line choosing the elements styled below.

L1685 | transform: scale(0.985); | Operational statement participating in the file's runtime behavior.

L1686 | } | Block delimiter controlling scope/structure in this language.

L1687 | | Blank line used for readability and logical separation.

L1688 | .btn-primary, | CSS selector line choosing the elements styled below.

L1689 | button.btn-primary, | Operational statement participating in the file's runtime behavior.

L1690 | .app-confirm-modal .btn-danger, | CSS selector line choosing the elements styled below.

L1691 | .app-confirm-modal .btn-primary { | CSS selector line choosing the elements styled below.

L1692 | background: linear-gradient(180deg, #3da0ff 0%, var(--ios-blue) 100%) !important; | Operational statement participating in the file's runtime behavior.

L1693 | color: #fff !important; | Operational statement participating in the file's runtime behavior.

L1694 | } | Block delimiter controlling scope/structure in this language.

L1695 | | Blank line used for readability and logical separation.

L1696 | .btn-outline-primary { | CSS selector line choosing the elements styled below.

L1697 | background: rgba(10, 132, 255, 0.08) !important; | Operational statement participating in the file's runtime behavior.

L1698 | color: var(--ios-blue) !important; | Operational statement participating in the file's runtime behavior.

L1699 | border: 1px solid rgba(10, 132, 255, 0.14) !important; | Operational statement participating in the file's runtime behavior.

L1700 | } | Block delimiter controlling scope/structure in this language.

L1701 | | Blank line used for readability and logical separation.

L1702 | .btn-outline-secondary, | CSS selector line choosing the elements styled below.

L1703 | .btn-outline-dark, | CSS selector line choosing the elements styled below.

L1704 | .btn-outline-warning, | CSS selector line choosing the elements styled below.

L1705 | .btn-outline-danger, | CSS selector line choosing the elements styled below.

L1706 | .btn-success, | CSS selector line choosing the elements styled below.

L1707 | .btn-warning, | CSS selector line choosing the elements styled below.

L1708 | .btn-danger { | CSS selector line choosing the elements styled below.

L1709 | background: rgba(255, 255, 255, 0.6) !important; | Operational statement participating in the file's runtime behavior.

L1710 | border: 1px solid var(--ios-border) !important; | Operational statement participating in the file's runtime behavior.

L1711 | } | Block delimiter controlling scope/structure in this language.

L1712 | | Blank line used for readability and logical separation.

L1713 | .btn-outline-danger, | CSS selector line choosing the elements styled below.

L1714 | .btn-danger { | CSS selector line choosing the elements styled below.

L1715 | color: var(--ios-red) !important; | Operational statement participating in the file's runtime behavior.

L1716 | } | Block delimiter controlling scope/structure in this language.

L1717 | | Blank line used for readability and logical separation.

L1718 | .btn-success { | CSS selector line choosing the elements styled below.

L1719 | color: #fff !important; | Operational statement participating in the file's runtime behavior.

L1720 | background: linear-gradient(180deg, #4dda75 0%, var(--ios-green) 100%) !important; | Operational statement participating in the file's runtime behavior.

L1721 | } | Block delimiter controlling scope/structure in this language.

L1722 | | Blank line used for readability and logical separation.

L1723 | .btn-warning { | CSS selector line choosing the elements styled below.

L1724 | color: #1f2937 !important; | Operational statement participating in the file's runtime behavior.

L1725 | background: linear-gradient(180deg, #ffc555 0%, var(--ios-orange) 100%) !important; | Operational statement participating in the file's runtime behavior.

L1726 | } | Block delimiter controlling scope/structure in this language.

L1727 | | Blank line used for readability and logical separation.

L1728 | .form-control, | CSS selector line choosing the elements styled below.

L1729 | .form-select, | CSS selector line choosing the elements styled below.

L1730 | textarea.form-control, | Operational statement participating in the file's runtime behavior.

L1731 | input.form-control { | Block delimiter controlling scope/structure in this language.

L1732 | min-height: 48px; | Operational statement participating in the file's runtime behavior.

L1733 | border: 1px solid rgba(15, 23, 42, 0.08) !important; | Operational statement participating in the file's runtime behavior.

L1734 | background: rgba(255, 255, 255, 0.72) !important; | Operational statement participating in the file's runtime behavior.

L1735 | box-shadow: inset 0 1px 0 rgba(255, 255, 255, 0.55), 0 6px 18px rgba(15, 23, 42, 0.03); | Operational statement participating in the file's runtime behavior.

L1736 | padding-left: 0.9rem; | Operational statement participating in the file's runtime behavior.

L1737 | padding-right: 0.9rem; | Operational statement participating in the file's runtime behavior.

L1738 | } | Block delimiter controlling scope/structure in this language.

L1739 | | Blank line used for readability and logical separation.

L1740 | .form-control:focus, | CSS selector line choosing the elements styled below.

L1741 | .form-select:focus { | CSS selector line choosing the elements styled below.

L1742 | border-color: rgba(10, 132, 255, 0.35) !important; | Operational statement participating in the file's runtime behavior.

L1743 | box-shadow: 0 0 4px rgba(10, 132, 255, 0.12), 0 10px 22px rgba(10, 132, 255, 0.08) !important; | Operational statement participating in the file's runtime behavior.

L1744 | } | Block delimiter controlling scope/structure in this language.

L1745 | | Blank line used for readability and logical separation.

L1746 | .form-check-input { | CSS selector line choosing the elements styled below.

L1747 | width: 1.1rem; | Operational statement participating in the file's runtime behavior.

L1748 | height: 1.1rem; | Operational statement participating in the file's runtime behavior.

L1749 | border-color: rgba(15, 23, 42, 0.16); | Operational statement participating in the file's runtime behavior.

L1750 | } | Block delimiter controlling scope/structure in this language.

L1751 | | Blank line used for readability and logical separation.

L1752 | .form-check-input:checked { | CSS selector line choosing the elements styled below.

L1753 | background-color: var(--ios-blue); | Operational statement participating in the file's runtime behavior.

L1754 | border-color: var(--ios-blue); | Operational statement participating in the file's runtime behavior.

L1755 | } | Block delimiter controlling scope/structure in this language.

L1756 | | Blank line used for readability and logical separation.

L1757 | .menu-toggle-button, | CSS selector line choosing the elements styled below.

L1758 | .notification-bell, | CSS selector line choosing the elements styled below.

L1759 | .role-icon-badge, | CSS selector line choosing the elements styled below.

L1760 | .stats-icon, | CSS selector line choosing the elements styled below.

L1761 | .feature-icon { | CSS selector line choosing the elements styled below.

L1762 | box-shadow: var(--ios-shadow-soft) !important; | Operational statement participating in the file's runtime behavior.

L1763 | } | Block delimiter controlling scope/structure in this language.

L1764 | | Blank line used for readability and logical separation.

L1765 | .menu-toggle-button, | CSS selector line choosing the elements styled below.

L1766 | .notification-bell { | CSS selector line choosing the elements styled below.

L1767 | background: rgba(255, 255, 255, 0.68) !important; | Operational statement participating in the file's runtime behavior.

L1768 | border: 1px solid rgba(15, 23, 42, 0.06) !important; | Operational statement participating in the file's runtime behavior.

L1769 | } | Block delimiter controlling scope/structure in this language.

L1770 | | Blank line used for readability and logical separation.

L1771 | .notification-bell { | CSS selector line choosing the elements styled below.

L1772 | width: 46px; | Operational statement participating in the file's runtime behavior.

L1773 | height: 46px; | Operational statement participating in the file's runtime behavior.

L1774 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L1775 | align-items: center; | Operational statement participating in the file's runtime behavior.

L1776 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L1777 | color: #0f4e9c; | Operational statement participating in the file's runtime behavior.

L1778 | text-decoration: none; | Operational statement participating in the file's runtime behavior.

L1779 | } | Block delimiter controlling scope/structure in this language.

L1780 | | Blank line used for readability and logical separation.

L1781 | .active-role-pill, | CSS selector line choosing the elements styled below.

L1782 | .build-chip { | CSS selector line choosing the elements styled below.

L1783 | background: rgba(255, 255, 255, 0.62) !important; | Operational statement participating in the file's runtime behavior.

L1784 | border: 1px solid rgba(15, 23, 42, 0.08) !important; | Operational statement participating in the file's runtime behavior.

L1785 | } | Block delimiter controlling scope/structure in this language.

L1786 | | Blank line used for readability and logical separation.

L1787 | .alert { | CSS selector line choosing the elements styled below.

L1788 | border: 1px solid rgba(255, 255, 255, 0.42) !important; | Operational statement participating in the file's runtime behavior.

L1789 | box-shadow: var(--ios-shadow-soft); | Operational statement participating in the file's runtime behavior.

L1790 | } | Block delimiter controlling scope/structure in this language.

L1791 | | Blank line used for readability and logical separation.

L1792 | .alert-success { | CSS selector line choosing the elements styled below.

L1793 | background: rgba(52, 199, 89, 0.14) !important; | Operational statement participating in the file's runtime behavior.

L1794 | color: #176033 !important; | Operational statement participating in the file's runtime behavior.

L1795 | } | Block delimiter controlling scope/structure in this language.

L1796 | | Blank line used for readability and logical separation.

L1797 | .alert-warning { | CSS selector line choosing the elements styled below.

L1798 | background: rgba(255, 159, 10, 0.16) !important; | Operational statement participating in the file's runtime behavior.

L1799 | color: #8a4a00 !important; | Operational statement participating in the file's runtime behavior.

L1800 | } | Block delimiter controlling scope/structure in this language.

L1801 | | Blank line used for readability and logical separation.

L1802 | .alert-danger { | CSS selector line choosing the elements styled below.

L1803 | background: rgba(255, 59, 48, 0.14) !important; | Operational statement participating in the file's runtime behavior.

L1804 | color: #8b1e19 !important; | Operational statement participating in the file's runtime behavior.

L1805 | } | Block delimiter controlling scope/structure in this language.

L1806 | | Blank line used for readability and logical separation.

L1807 | .alert-info, | CSS selector line choosing the elements styled below.

L1808 | .alert-primary { | CSS selector line choosing the elements styled below.

L1809 | background: rgba(10, 132, 255, 0.12) !important; | Operational statement participating in the file's runtime behavior.

L1810 | color: #0b4d92 !important; | Operational statement participating in the file's runtime behavior.

L1811 | } | Block delimiter controlling scope/structure in this language.

L1812 | | Blank line used for readability and logical separation.

L1813 | .table { | CSS selector line choosing the elements styled below.

L1814 | border-collapse: separate; | Operational statement participating in the file's runtime behavior.

L1815 | border-spacing: 0; | Operational statement participating in the file's runtime behavior.

L1816 | } | Block delimiter controlling scope/structure in this language.

L1817 | | Blank line used for readability and logical separation.

L1818 | .table thead th { | CSS selector line choosing the elements styled below.

L1819 | font-size: 0.78rem; | Operational statement participating in the file's runtime behavior.

L1820 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L1821 | letter-spacing: 0.06em; | Operational statement participating in the file's runtime behavior.

L1822 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L1823 | } | Block delimiter controlling scope/structure in this language.

L1824 | | Blank line used for readability and logical separation.

L1825 | .table tbody tr { | CSS selector line choosing the elements styled below.

L1826 | transition: background-color 0.18s ease, transform 0.18s ease; | Operational statement participating in the file's runtime behavior.

L1827 | } | Block delimiter controlling scope/structure in this language.

L1828 | | Blank line used for readability and logical separation.

L1829 | .table-hover tbody tr:hover, | CSS selector line choosing the elements styled below.

L1830 | .list-group-item:hover, | CSS selector line choosing the elements styled below.

L1831 | .stats-card:hover, | CSS selector line choosing the elements styled below.

L1832 | .feature-card:hover, | CSS selector line choosing the elements styled below.

L1833 | .review-item-card:hover { | CSS selector line choosing the elements styled below.

L1834 | animation: none; | Operational statement participating in the file's runtime behavior.

L1835 | transform: translateY(-1px); | Operational statement participating in the file's runtime behavior.

L1836 | } | Block delimiter controlling scope/structure in this language.

L1837 | | Blank line used for readability and logical separation.

L1838 | .page-link { | CSS selector line choosing the elements styled below.

L1839 | border: 1px solid rgba(15, 23, 42, 0.06) !important; | Operational statement participating in the file's runtime behavior.

L1840 | background: rgba(255, 255, 255, 0.74) !important; | Operational statement participating in the file's runtime behavior.

L1841 | color: #0b4d92; | Operational statement participating in the file's runtime behavior.

L1842 | } | Block delimiter controlling scope/structure in this language.

L1843 | | Blank line used for readability and logical separation.

L1844 | .page-item.active .page-link { | CSS selector line choosing the elements styled below.

L1845 | background: linear-gradient(180deg, #3da0ff 0%, var(--ios-blue) 100%) !important; | Operational statement participating in the file's runtime behavior.

L1846 | color: #fff; | Operational statement participating in the file's runtime behavior.

L1847 | } | Block delimiter controlling scope/structure in this language.

L1848 | | Blank line used for readability and logical separation.

L1849 | .offcanvas-body, | CSS selector line choosing the elements styled below.

L1850 | .card-body, | CSS selector line choosing the elements styled below.

L1851 | .modal-body { | CSS selector line choosing the elements styled below.

L1852 | -webkit-font-smoothing: antialiased; | Operational statement participating in the file's runtime behavior.

L1853 | } | Block delimiter controlling scope/structure in this language.

L1854 | | Blank line used for readability and logical separation.

L1855 | .app-loader-card { | CSS selector line choosing the elements styled below.

L1856 | border-radius: 28px !important; | Operational statement participating in the file's runtime behavior.

L1857 | } | Block delimiter controlling scope/structure in this language.

L1858 | | Blank line used for readability and logical separation.

L1859 | .loader-text { | CSS selector line choosing the elements styled below.

L1860 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L1861 | letter-spacing: 0.12em; | Operational statement participating in the file's runtime behavior.

L1862 | font-size: 0.94rem; | Operational statement participating in the file's runtime behavior.

L1863 | } | Block delimiter controlling scope/structure in this language.

L1864 | | Blank line used for readability and logical separation.

L1865 | body[data-theme="dark"] .form-control, | Assignment statement storing or updating program state.

L1866 | body[data-theme="dark"] .form-select, | Assignment statement storing or updating program state.

L1867 | body[data-theme="dark"] .page-link, | Assignment statement storing or updating program state.

L1868 | body[data-theme="dark"] .menu-toggle-button, | Assignment statement storing or updating program state.

L1869 | body[data-theme="dark"] .notification-bell, | Assignment statement storing or updating program state.

L1870 | body[data-theme="dark"] .active-role-pill, | Assignment statement storing or updating program state.

L1871 | body[data-theme="dark"] .build-chip, | Assignment statement storing or updating program state.

L1872 | body[data-theme="dark"] .btn-outline-primary, | Assignment statement storing or updating program state.

L1873 | body[data-theme="dark"] .btn-outline-secondary, | Assignment statement storing or updating program state.

L1874 | body[data-theme="dark"] .btn-outline-dark, | Assignment statement storing or updating program state.

L1875 | body[data-theme="dark"] .btn-outline-warning, | Assignment statement storing or updating program state.

L1876 | body[data-theme="dark"] .btn-outline-danger, | Assignment statement storing or updating program state.

L1877 | body[data-theme="dark"] .table, | Assignment statement storing or updating program state.

L1878 | body[data-theme="dark"] .table thead th, | Assignment statement storing or updating program state.

L1879 | body[data-theme="dark"] .list-group-item, | Assignment statement storing or updating program state.

L1880 | body[data-theme="dark"] .alert, | Assignment statement storing or updating program state.

L1881 | body[data-theme="dark"] .share-qr-wrap, | Assignment statement storing or updating program state.

L1882 | body[data-theme="dark"] .login-share-card, | Assignment statement storing or updating program state.

L1883 | body[data-theme="dark"] .login-role-preview { | Assignment statement storing or updating program state.

L1884 | background: rgba(28, 34, 48, 0.82) !important; | Operational statement participating in the file's runtime behavior.

L1885 | color: #e8eef8 !important; | Operational statement participating in the file's runtime behavior.

L1886 | border-color: rgba(255, 255, 255, 0.08) !important; | Operational statement participating in the file's runtime behavior.

L1887 | } | Block delimiter controlling scope/structure in this language.

L1888 | | Blank line used for readability and logical separation.

L1889 | body[data-theme="dark"] .btn-outline-primary { | Assignment statement storing or updating program state.

L1890 | color: #8fc8ff !important; | Operational statement participating in the file's runtime behavior.

L1891 | } | Block delimiter controlling scope/structure in this language.

L1892 | | Blank line used for readability and logical separation.

L1893 | body[data-theme="dark"] .alert-success { | Assignment statement storing or updating program state.

L1894 | color: #a4f0ba !important; | Operational statement participating in the file's runtime behavior.

L1895 | } | Block delimiter controlling scope/structure in this language.

L1896 | | Blank line used for readability and logical separation.

L1897 | body[data-theme="dark"] .alert-warning { | Assignment statement storing or updating program state.

L1898 | color: #ffd18a !important; | Operational statement participating in the file's runtime behavior.

L1899 | } | Block delimiter controlling scope/structure in this language.

L1900 | | Blank line used for readability and logical separation.

L1901 | body[data-theme="dark"] .alert-danger { | Assignment statement storing or updating program state.

L1902 | color: #ffb1ab !important; | Operational statement participating in the file's runtime behavior.

L1903 | } | Block delimiter controlling scope/structure in this language.

L1904 | | Blank line used for readability and logical separation.

L1905 | @media (max-width: 768px) { | Decorator line that modifies the behavior of the definition below.

L1906 | .main-container { | CSS selector line choosing the elements styled below.

L1907 | padding-left: 0.85rem; | Operational statement participating in the file's runtime behavior.

L1908 | padding-right: 0.85rem; | Operational statement participating in the file's runtime behavior.

L1909 | } | Block delimiter controlling scope/structure in this language.

L1910 | | Blank line used for readability and logical separation.

L1911 | .page-utility-bar { | CSS selector line choosing the elements styled below.

L1912 | margin-bottom: 0.8rem; | Operational statement participating in the file's runtime behavior.

L1913 | } | Block delimiter controlling scope/structure in this language.

L1914 | | Blank line used for readability and logical separation.

L1915 | .page-back-pill { | CSS selector line choosing the elements styled below.

L1916 | width: auto; | Operational statement participating in the file's runtime behavior.

L1917 | min-height: 44px; | Operational statement participating in the file's runtime behavior.

L1918 | padding: 0.7rem 0.95rem; | Operational statement participating in the file's runtime behavior.

L1919 | } | Block delimiter controlling scope/structure in this language.

L1920 | | Blank line used for readability and logical separation.

L1921 | .btn, | CSS selector line choosing the elements styled below.

L1922 | button, | Operational statement participating in the file's runtime behavior.

L1923 | .form-control, | CSS selector line choosing the elements styled below.

```

L1924 | .form-select { | CSS selector line choosing the elements styled below.
L1925 |     min-height: 46px; | Operational statement participating in the file's runtime behavior.
L1926 | } | Block delimiter controlling scope/structure in this language.
L1927 | | Blank line used for readability and logical separation.
L1928 | .card, | CSS selector line choosing the elements styled below.
L1929 | .detail-card, | CSS selector line choosing the elements styled below.
L1930 | .stats-card, | CSS selector line choosing the elements styled below.
L1931 | .login-card, | CSS selector line choosing the elements styled below.
L1932 | .notify-message-card, | CSS selector line choosing the elements styled below.
L1933 | .review-item-card, | CSS selector line choosing the elements styled below.
L1934 | .alert, | CSS selector line choosing the elements styled below.
L1935 | .modal-content, | CSS selector line choosing the elements styled below.
L1936 | .offcanvas { | CSS selector line choosing the elements styled below.
L1937 |     border-radius: 22px !important; | Operational statement participating in the file's runtime behavior.
L1938 | } | Block delimiter controlling scope/structure in this language.
L1939 | } | Block delimiter controlling scope/structure in this language.
L1940 | | Blank line used for readability and logical separation.
L1941 | .active-role-pill.role-technician .role-icon-badge { | CSS selector line choosing the elements styled below.
L1942 |     background: rgba(20, 150, 130, 0.14); | Operational statement participating in the file's runtime behavior.
L1943 |     color: #0a7b69; | Operational statement participating in the file's runtime behavior.
L1944 | } | Block delimiter controlling scope/structure in this language.
L1945 | | Blank line used for readability and logical separation.
L1946 | .active-role-pill.role-staff .role-icon-badge { | CSS selector line choosing the elements styled below.
L1947 |     background: rgba(24, 111, 212, 0.14); | Operational statement participating in the file's runtime behavior.
L1948 |     color: #1b63ba; | Operational statement participating in the file's runtime behavior.
L1949 | } | Block delimiter controlling scope/structure in this language.
L1950 | | Blank line used for readability and logical separation.
L1951 | .active-role-pill.role-manager .role-icon-badge, | CSS selector line choosing the elements styled below.
L1952 | .active-role-pill.role-general_manager .role-icon-badge { | CSS selector line choosing the elements styled below.
L1953 |     background: rgba(133, 90, 207, 0.14); | Operational statement participating in the file's runtime behavior.
L1954 |     color: #6c45b3; | Operational statement participating in the file's runtime behavior.
L1955 | } | Block delimiter controlling scope/structure in this language.
L1956 | | Blank line used for readability and logical separation.
L1957 | .active-role-pill.role-developer .role-icon-badge { | CSS selector line choosing the elements styled below.
L1958 |     background: rgba(220, 74, 64, 0.14); | Operational statement participating in the file's runtime behavior.
L1959 |     color: #b93b31; | Operational statement participating in the file's runtime behavior.
L1960 | } | Block delimiter controlling scope/structure in this language.
L1961 | | Blank line used for readability and logical separation.
L1962 | [data-theme="dark"] .active-role-pill { | Assignment statement storing or updating program state.
L1963 |     background: linear-gradient(135deg, #223652, #1a2a41); | Operational statement participating in the file's runtime behavior.
L1964 |     color: #dcecff; | Operational statement participating in the file's runtime behavior.
L1965 |     border-color: #35527a; | Operational statement participating in the file's runtime behavior.
L1966 | } | Block delimiter controlling scope/structure in this language.
L1967 | | Blank line used for readability and logical separation.
L1968 | [data-theme="dark"] .role-icon-badge { | Assignment statement storing or updating program state.
L1969 |     background: rgba(8, 20, 38, 0.65); | Operational statement participating in the file's runtime behavior.
L1970 |     border-color: rgba(96, 138, 194, 0.4); | Operational statement participating in the file's runtime behavior.
L1971 | } | Block delimiter controlling scope/structure in this language.
L1972 | | Blank line used for readability and logical separation.
L1973 | [data-theme="dark"] .active-role-pill.role-technician .role-icon-badge { | Assignment statement storing or updating program state.
L1974 |     color: #78e2d1; | Operational statement participating in the file's runtime behavior.
L1975 | } | Block delimiter controlling scope/structure in this language.
L1976 | | Blank line used for readability and logical separation.
L1977 | [data-theme="dark"] .active-role-pill.role-staff .role-icon-badge { | Assignment statement storing or updating program state.
L1978 |     color: #95c8ff; | Operational statement participating in the file's runtime behavior.

```

L1979 | } | Block delimiter controlling scope/structure in this language.

L1980 | | Blank line used for readability and logical separation.

L1981 | [data-theme="dark"] .active-role-pill.role-manager .role-icon-badge, | Assignment statement storing or updating program state.

L1982 | [data-theme="dark"] .active-role-pill.role-general_manager .role-icon-badge { | Assignment statement storing or updating program state.

L1983 | color: #c7afff; | Operational statement participating in the file's runtime behavior.

L1984 | } | Block delimiter controlling scope/structure in this language.

L1985 | | Blank line used for readability and logical separation.

L1986 | [data-theme="dark"] .active-role-pill.role-developer .role-icon-badge { | Assignment statement storing or updating program state.

L1987 | color: #ffb2a9; | Operational statement participating in the file's runtime behavior.

L1988 | } | Block delimiter controlling scope/structure in this language.

L1989 | | Blank line used for readability and logical separation.

L1990 | @media (max-width: 576px) { | Decorator line that modifies the behavior of the definition below.

L1991 | .role-notification-wrap { | CSS selector line choosing the elements styled below.

L1992 | gap: 0.35rem; | Operational statement participating in the file's runtime behavior.

L1993 | } | Block delimiter controlling scope/structure in this language.

L1994 | | Blank line used for readability and logical separation.

L1995 | .active-role-pill { | CSS selector line choosing the elements styled below.

L1996 | font-size: 0.74rem; | Operational statement participating in the file's runtime behavior.

L1997 | padding: 0.28rem 0.55rem; | Operational statement participating in the file's runtime behavior.

L1998 | } | Block delimiter controlling scope/structure in this language.

L1999 | | Blank line used for readability and logical separation.

L2000 | .role-icon-badge { | CSS selector line choosing the elements styled below.

L2001 | width: 18px; | Operational statement participating in the file's runtime behavior.

L2002 | height: 18px; | Operational statement participating in the file's runtime behavior.

L2003 | } | Block delimiter controlling scope/structure in this language.

L2004 | } | Block delimiter controlling scope/structure in this language.

L2005 | | Blank line used for readability and logical separation.

L2006 | .input-group .form-control { | CSS selector line choosing the elements styled below.

L2007 | border-top-right-radius: 0; | Operational statement participating in the file's runtime behavior.

L2008 | border-bottom-right-radius: 0; | Operational statement participating in the file's runtime behavior.

L2009 | } | Block delimiter controlling scope/structure in this language.

L2010 | | Blank line used for readability and logical separation.

L2011 | .input-group .btn { | CSS selector line choosing the elements styled below.

L2012 | border-top-left-radius: 0; | Operational statement participating in the file's runtime behavior.

L2013 | border-bottom-left-radius: 0; | Operational statement participating in the file's runtime behavior.

L2014 | } | Block delimiter controlling scope/structure in this language.

L2015 | | Blank line used for readability and logical separation.

L2016 | .footer { | CSS selector line choosing the elements styled below.

L2017 | padding: 1.5rem; | Operational statement participating in the file's runtime behavior.

L2018 | } | Block delimiter controlling scope/structure in this language.

L2019 | | Blank line used for readability and logical separation.

L2020 | .not-found-wrap { | CSS selector line choosing the elements styled below.

L2021 | min-height: calc(100vh - 280px); | Operational statement participating in the file's runtime behavior.

L2022 | display: flex; | Operational statement participating in the file's runtime behavior.

L2023 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L2024 | align-items: center; | Operational statement participating in the file's runtime behavior.

L2025 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L2026 | gap: 1rem; | Operational statement participating in the file's runtime behavior.

L2027 | padding: 1.5rem; | Operational statement participating in the file's runtime behavior.

L2028 | } | Block delimiter controlling scope/structure in this language.

L2029 | | Blank line used for readability and logical separation.

L2030 | .not-found-wrap h1 { | CSS selector line choosing the elements styled below.

L2031 | margin: 0; | Operational statement participating in the file's runtime behavior.

L2032 | } | Block delimiter controlling scope/structure in this language.

L2033 | | Blank line used for readability and logical separation.

```

L2034 | .not-found-text { | CSS selector line choosing the elements styled below.
L2035 |   max-width: 520px; | Operational statement participating in the file's runtime behavior.
L2036 |   color: #5b6a82; | Operational statement participating in the file's runtime behavior.
L2037 |   margin-bottom: 1rem; | Operational statement participating in the file's runtime behavior.
L2038 | } | Block delimiter controlling scope/structure in this language.
L2039 | | Blank line used for readability and logical separation.
L2040 | .pm-form-table { | CSS selector line choosing the elements styled below.
L2041 |   border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.
L2042 |   border-radius: 12px; | Operational statement participating in the file's runtime behavior.
L2043 |   overflow: hidden; | Operational statement participating in the file's runtime behavior.
L2044 | } | Block delimiter controlling scope/structure in this language.
L2045 | | Blank line used for readability and logical separation.
L2046 | .pm-form-table th, | CSS selector line choosing the elements styled below.
L2047 | .pm-form-table td { | CSS selector line choosing the elements styled below.
L2048 |   border-color: #dbe8ff; | Operational statement participating in the file's runtime behavior.
L2049 |   vertical-align: middle; | Operational statement participating in the file's runtime behavior.
L2050 | } | Block delimiter controlling scope/structure in this language.
L2051 | | Blank line used for readability and logical separation.
L2052 | .pm-form-table thead th { | CSS selector line choosing the elements styled below.
L2053 |   background: #e8f4f8; | Operational statement participating in the file's runtime behavior.
L2054 |   color: #0f3a73; | Operational statement participating in the file's runtime behavior.
L2055 |   font-weight: 800; | Operational statement participating in the file's runtime behavior.
L2056 | } | Block delimiter controlling scope/structure in this language.
L2057 | | Blank line used for readability and logical separation.
L2058 | .pm-form-table .pm-label-col { | CSS selector line choosing the elements styled below.
L2059 |   width: 46%; | Operational statement participating in the file's runtime behavior.
L2060 | } | Block delimiter controlling scope/structure in this language.
L2061 | | Blank line used for readability and logical separation.
L2062 | .pm-form-table .pm-value-col { | CSS selector line choosing the elements styled below.
L2063 |   width: 54%; | Operational statement participating in the file's runtime behavior.
L2064 | } | Block delimiter controlling scope/structure in this language.
L2065 | | Blank line used for readability and logical separation.
L2066 | .signature-card { | CSS selector line choosing the elements styled below.
L2067 |   border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.
L2068 |   border-radius: 12px; | Operational statement participating in the file's runtime behavior.
L2069 |   padding: 1.25rem; | Operational statement participating in the file's runtime behavior.
L2070 |   background: #fff; | Operational statement participating in the file's runtime behavior.
L2071 |   box-shadow: 0 1px 3px rgba(0,0,0,0.08); | Operational statement participating in the file's runtime behavior.
L2072 | } | Block delimiter controlling scope/structure in this language.
L2073 | | Blank line used for readability and logical separation.
L2074 | .signature-pad { | CSS selector line choosing the elements styled below.
L2075 |   width: 100%; | Operational statement participating in the file's runtime behavior.
L2076 |   height: 240px; | Operational statement participating in the file's runtime behavior.
L2077 |   border: 2px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.
L2078 |   border-radius: 10px; | Operational statement participating in the file's runtime behavior.
L2079 |   background: #fbfdff; | Operational statement participating in the file's runtime behavior.
L2080 |   touch-action: none; | Operational statement participating in the file's runtime behavior.
L2081 |   cursor: crosshair; | Operational statement participating in the file's runtime behavior.
L2082 |   box-shadow: inset 0 1px 3px rgba(0,0,0,0.05); | Operational statement participating in the file's runtime behavior.
L2083 | } | Block delimiter controlling scope/structure in this language.
L2084 | | Blank line used for readability and logical separation.
L2085 | [data-bs-theme="dark"] .signature-pad { | Assignment statement storing or updating program state.
L2086 |   border-color: #3a4a5c; | Operational statement participating in the file's runtime behavior.
L2087 |   background: #1e2a3a; | Operational statement participating in the file's runtime behavior.
L2088 |   box-shadow: inset 0 1px 3px rgba(0,0,0,0.5); | Operational statement participating in the file's runtime behavior.

```


L2089 | } | Block delimiter controlling scope/structure in this language.

L2090 | | Blank line used for readability and logical separation.

L2091 | .photo-upload-input { | CSS selector line choosing the elements styled below.

L2092 | position: absolute; | Operational statement participating in the file's runtime behavior.

L2093 | width: 1px; | Operational statement participating in the file's runtime behavior.

L2094 | height: 1px; | Operational statement participating in the file's runtime behavior.

L2095 | padding: 0; | Operational statement participating in the file's runtime behavior.

L2096 | margin: -1px; | Operational statement participating in the file's runtime behavior.

L2097 | overflow: hidden; | Operational statement participating in the file's runtime behavior.

L2098 | clip: rect(0, 0, 0, 0); | Operational statement participating in the file's runtime behavior.

L2099 | border: 0; | Operational statement participating in the file's runtime behavior.

L2100 | } | Block delimiter controlling scope/structure in this language.

L2101 | | Blank line used for readability and logical separation.

L2102 | .upload-icon-placeholder { | CSS selector line choosing the elements styled below.

L2103 | display: inline-block; | Operational statement participating in the file's runtime behavior.

L2104 | width: 50px; | Operational statement participating in the file's runtime behavior.

L2105 | height: 50px; | Operational statement participating in the file's runtime behavior.

L2106 | background-color: #f8f9fa; | Operational statement participating in the file's runtime behavior.

L2107 | border: 1px dashed #ced4da; | Operational statement participating in the file's runtime behavior.

L2108 | border-radius: 4px; | Operational statement participating in the file's runtime behavior.

L2109 | display: flex; | Operational statement participating in the file's runtime behavior.

L2110 | align-items: center; | Operational statement participating in the file's runtime behavior.

L2111 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L2112 | cursor: pointer; | Operational statement participating in the file's runtime behavior.

L2113 | background-size: cover; | Operational statement participating in the file's runtime behavior.

L2114 | background-position: center; | Operational statement participating in the file's runtime behavior.

L2115 | } | Block delimiter controlling scope/structure in this language.

L2116 | | Blank line used for readability and logical separation.

L2117 | .upload-icon-placeholder i { | CSS selector line choosing the elements styled below.

L2118 | font-size: 24px; | Operational statement participating in the file's runtime behavior.

L2119 | color: #6c757d; | Operational statement participating in the file's runtime behavior.

L2120 | } | Block delimiter controlling scope/structure in this language.

L2121 | | Blank line used for readability and logical separation.

L2122 | .upload-icon-placeholder.uploaded { | CSS selector line choosing the elements styled below.

L2123 | border: none; | Operational statement participating in the file's runtime behavior.

L2124 | background-color: transparent; | Operational statement participating in the file's runtime behavior.

L2125 | } | Block delimiter controlling scope/structure in this language.

L2126 | | Blank line used for readability and logical separation.

L2127 | .upload-icon-placeholder.uploaded i { | CSS selector line choosing the elements styled below.

L2128 | display: none; | Operational statement participating in the file's runtime behavior.

L2129 | } | Block delimiter controlling scope/structure in this language.

L2130 | | Blank line used for readability and logical separation.

L2131 | /* PM Form â€” photo card grid (matches Consumables Detail layout) */ | Operational statement participating in the file's runtime behavior.

L2132 | .pm-photo-section-title { | CSS selector line choosing the elements styled below.

L2133 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L2134 | font-size: 1rem; | Operational statement participating in the file's runtime behavior.

L2135 | letter-spacing: 0.04em; | Operational statement participating in the file's runtime behavior.

L2136 | color: #1a2540; | Operational statement participating in the file's runtime behavior.

L2137 | stroke: linear-gradient(90deg, #74c6ff 0%, #0a84ff 55%, #5e5ce6 100%); | Operational statement participating in the file's runtime behavior.

L2138 | border-bottom: 2px solid #e3eaf5; | Operational statement participating in the file's runtime behavior.

L2139 | padding-bottom: 0.4rem; | Operational statement participating in the file's runtime behavior.

L2140 | margin-bottom: 1rem; | Operational statement participating in the file's runtime behavior.

L2141 | } | Block delimiter controlling scope/structure in this language.

L2142 | | Blank line used for readability and logical separation.

L2143 | .pm-photo-card { | CSS selector line choosing the elements styled below.

L2144 | display: flex; | Operational statement participating in the file's runtime behavior.

L2145 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L2146 | gap: 0.45rem; | Operational statement participating in the file's runtime behavior.

L2147 | } | Block delimiter controlling scope/structure in this language.

L2148 | | Blank line used for readability and logical separation.

L2149 | .pm-photo-label { | CSS selector line choosing the elements styled below.

L2150 | font-size: 0.88rem; | Operational statement participating in the file's runtime behavior.

L2151 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L2152 | color: #1a2540; | Operational statement participating in the file's runtime behavior.

L2153 | } | Block delimiter controlling scope/structure in this language.

L2154 | | Blank line used for readability and logical separation.

L2155 | .pm-photo-upload-area { | CSS selector line choosing the elements styled below.

L2156 | display: block; | Operational statement participating in the file's runtime behavior.

L2157 | width: 100%; | Operational statement participating in the file's runtime behavior.

L2158 | min-height: 180px; | Operational statement participating in the file's runtime behavior.

L2159 | border: 1.5px solid #ced4da; | Operational statement participating in the file's runtime behavior.

L2160 | border-radius: 10px; | Operational statement participating in the file's runtime behavior.

L2161 | cursor: pointer; | Operational statement participating in the file's runtime behavior.

L2162 | background-color: #f4f7fb; | Operational statement participating in the file's runtime behavior.

L2163 | background-size: cover; | Operational statement participating in the file's runtime behavior.

L2164 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L2165 | letter-spacing: 0.38em; | Operational statement participating in the file's runtime behavior.

L2166 | font-size: 0.95rem; | Operational statement participating in the file's runtime behavior.

L2167 | position: relative; | Operational statement participating in the file's runtime behavior.

L2168 | transition: border-color 0.2s, background-color 0.2s; | Operational statement participating in the file's runtime behavior.

L2169 | } | Block delimiter controlling scope/structure in this language.

L2170 | | Blank line used for readability and logical separation.

L2171 | .pm-photo-upload-area:hover { | CSS selector line choosing the elements styled below.

L2172 | border-color: #1c4da8; | Operational statement participating in the file's runtime behavior.

L2173 | background-color: #eef3fc; | Operational statement participating in the file's runtime behavior.

L2174 | } | Block delimiter controlling scope/structure in this language.

L2175 | | Blank line used for readability and logical separation.

L2176 | .pm-photo-upload-area.uploaded { | CSS selector line choosing the elements styled below.

L2177 | border-color: #198754; | Operational statement participating in the file's runtime behavior.

L2178 | } | Block delimiter controlling scope/structure in this language.

L2179 | | Blank line used for readability and logical separation.

L2180 | .pm-photo-placeholder { | CSS selector line choosing the elements styled below.

L2181 | display: flex; | Operational statement participating in the file's runtime behavior.

L2182 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L2183 | align-items: center; | Operational statement participating in the file's runtime behavior.

L2184 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L2185 | height: 180px; | Operational statement participating in the file's runtime behavior.

L2186 | gap: 0.35rem; | Operational statement participating in the file's runtime behavior.

L2187 | transition: opacity 0.2s; | Operational statement participating in the file's runtime behavior.

L2188 | } | Block delimiter controlling scope/structure in this language.

L2189 | | Blank line used for readability and logical separation.

L2190 | .pm-photo-icon { | CSS selector line choosing the elements styled below.

L2191 | font-size: 2.2rem; | Operational statement participating in the file's runtime behavior.

L2192 | color: #adb5bd; | Operational statement participating in the file's runtime behavior.

L2193 | } | Block delimiter controlling scope/structure in this language.

L2194 | | Blank line used for readability and logical separation.

L2195 | .pm-photo-hint { | CSS selector line choosing the elements styled below.

L2196 | font-size: 0.75rem; | Operational statement participating in the file's runtime behavior.

L2197 | color: #6c757d; | Operational statement participating in the file's runtime behavior.

L2198 | } | Block delimiter controlling scope/structure in this language.

L2199 | | Blank line used for readability and logical separation.

L2200 | .pm-photo-controls { | CSS selector line choosing the elements styled below.

L2201 | display: flex; | Operational statement participating in the file's runtime behavior.

L2202 | gap: 0.5rem; | Operational statement participating in the file's runtime behavior.

L2203 | flex-wrap: wrap; | Operational statement participating in the file's runtime behavior.

L2204 | } | Block delimiter controlling scope/structure in this language.

L2205 | | Blank line used for readability and logical separation.

L2206 | .pm-photo-controls.d-none { | CSS selector line choosing the elements styled below.

L2207 | display: none !important; | Operational statement participating in the file's runtime behavior.

L2208 | } | Block delimiter controlling scope/structure in this language.

L2209 | | Blank line used for readability and logical separation.

L2210 | .pm-photo-delete-btn { | CSS selector line choosing the elements styled below.

L2211 | flex: 1; | Operational statement participating in the file's runtime behavior.

L2212 | min-width: 100px; | Operational statement participating in the file's runtime behavior.

L2213 | } | Block delimiter controlling scope/structure in this language.

L2214 | | Blank line used for readability and logical separation.

L2215 | .pm-photo-delete-btn:hover { | CSS selector line choosing the elements styled below.

L2216 | background-color: #dc3545; | Operational statement participating in the file's runtime behavior.

L2217 | color: #fff; | Operational statement participating in the file's runtime behavior.

L2218 | } | Block delimiter controlling scope/structure in this language.

L2219 | | Blank line used for readability and logical separation.

L2220 | [data-bs-theme="dark"] .pm-photo-section-title { | Assignment statement storing or updating program state.

L2221 | color: #c8d6f0; | Operational statement participating in the file's runtime behavior.

L2222 | border-bottom-color: #2e3a50; | Operational statement participating in the file's runtime behavior.

L2223 | } | Block delimiter controlling scope/structure in this language.

L2224 | | Blank line used for readability and logical separation.

L2225 | [data-bs-theme="dark"] .pm-photo-label { | Assignment statement storing or updating program state.

L2226 | color: #c8d6f0; | Operational statement participating in the file's runtime behavior.

L2227 | } | Block delimiter controlling scope/structure in this language.

L2228 | | Blank line used for readability and logical separation.

L2229 | [data-bs-theme="dark"] .pm-photo-upload-area { | Assignment statement storing or updating program state.

L2230 | background-color: #1e2a3a; | Operational statement participating in the file's runtime behavior.

L2231 | border-color: #3a4a5c; | Operational statement participating in the file's runtime behavior.

L2232 | } | Block delimiter controlling scope/structure in this language.

L2233 | | Blank line used for readability and logical separation.

L2234 | [data-bs-theme="dark"] .pm-photo-upload-area:hover { | Assignment statement storing or updating program state.

L2235 | border-color: #5b8dee; | Operational statement participating in the file's runtime behavior.

L2236 | background-color: #1a2d48; | Operational statement participating in the file's runtime behavior.

L2237 | } | Block delimiter controlling scope/structure in this language.

L2238 | | Blank line used for readability and logical separation.

L2239 | [data-bs-theme="dark"] .pm-photo-icon { | Assignment statement storing or updating program state.

L2240 | color: #4a6a90; | Operational statement participating in the file's runtime behavior.

L2241 | } | Block delimiter controlling scope/structure in this language.

L2242 | | Blank line used for readability and logical separation.

L2243 | [data-bs-theme="dark"] .pm-photo-hint { | Assignment statement storing or updating program state.

L2244 | color: #7a90a8; | Operational statement participating in the file's runtime behavior.

L2245 | } | Block delimiter controlling scope/structure in this language.

L2246 | | Blank line used for readability and logical separation.

L2247 | [data-bs-theme="dark"] .pm-photo-delete-btn { | Assignment statement storing or updating program state.

L2248 | border-color: #7a90a8; | Operational statement participating in the file's runtime behavior.

L2249 | color: #7a90a8; | Operational statement participating in the file's runtime behavior.

L2250 | } | Block delimiter controlling scope/structure in this language.

L2251 | | Blank line used for readability and logical separation.

L2252 | [data-bs-theme="dark"] .pm-photo-delete-btn:hover { | Assignment statement storing or updating program state.

L2253 | background-color: #dc3545; | Operational statement participating in the file's runtime behavior.

L2254 | border-color: #dc3545; | Operational statement participating in the file's runtime behavior.

L2255 | color: #fff; | Operational statement participating in the file's runtime behavior.

L2256 | } | Block delimiter controlling scope/structure in this language.

L2257 | | Blank line used for readability and logical separation.

L2258 | @media (max-width: 767.98px) { | Decorator line that modifies the behavior of the definition below.

L2259 | .main-container { | CSS selector line choosing the elements styled below.

L2260 | padding: 14px 10px; | Operational statement participating in the file's runtime behavior.

L2261 | } | Block delimiter controlling scope/structure in this language.

L2262 | | Blank line used for readability and logical separation.

L2263 | h1 { | Block delimiter controlling scope/structure in this language.

L2264 | font-size: 2rem; | Operational statement participating in the file's runtime behavior.

L2265 | } | Block delimiter controlling scope/structure in this language.

L2266 | | Blank line used for readability and logical separation.

L2267 | .dashboard-hero { | CSS selector line choosing the elements styled below.

L2268 | padding: 1.25rem; | Operational statement participating in the file's runtime behavior.

L2269 | } | Block delimiter controlling scope/structure in this language.

L2270 | | Blank line used for readability and logical separation.

L2271 | .feature-card .card-body { | CSS selector line choosing the elements styled below.

L2272 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L2273 | } | Block delimiter controlling scope/structure in this language.

L2274 | | Blank line used for readability and logical separation.

L2275 | .consumables-table thead { | CSS selector line choosing the elements styled below.

L2276 | display: none; | Operational statement participating in the file's runtime behavior.

L2277 | } | Block delimiter controlling scope/structure in this language.

L2278 | | Blank line used for readability and logical separation.

L2279 | .consumables-table, | CSS selector line choosing the elements styled below.

L2280 | .consumables-table tbody, | CSS selector line choosing the elements styled below.

L2281 | .consumables-table tr, | CSS selector line choosing the elements styled below.

L2282 | .consumables-table td { | CSS selector line choosing the elements styled below.

L2283 | display: block; | Operational statement participating in the file's runtime behavior.

L2284 | width: 100%; | Operational statement participating in the file's runtime behavior.

L2285 | } | Block delimiter controlling scope/structure in this language.

L2286 | | Blank line used for readability and logical separation.

L2287 | .consumables-table tr { | CSS selector line choosing the elements styled below.

L2288 | margin-bottom: 0.85rem; | Operational statement participating in the file's runtime behavior.

L2289 | border: 1px solid #e4eefb; | Operational statement participating in the file's runtime behavior.

L2290 | border-radius: 14px; | Operational statement participating in the file's runtime behavior.

L2291 | background: #fff; | Operational statement participating in the file's runtime behavior.

L2292 | padding: 0.35rem; | Operational statement participating in the file's runtime behavior.

L2293 | } | Block delimiter controlling scope/structure in this language.

L2294 | | Blank line used for readability and logical separation.

L2295 | .consumables-table td { | CSS selector line choosing the elements styled below.

L2296 | border: 0; | Operational statement participating in the file's runtime behavior.

L2297 | padding: 0.45rem 0.7rem; | Operational statement participating in the file's runtime behavior.

L2298 | } | Block delimiter controlling scope/structure in this language.

L2299 | | Blank line used for readability and logical separation.

L2300 | .consumables-table td::before { | CSS selector line choosing the elements styled below.

L2301 | content: attr(data-label); | Operational statement participating in the file's runtime behavior.

L2302 | display: block; | Operational statement participating in the file's runtime behavior.

L2303 | color: #5d6e8c; | Operational statement participating in the file's runtime behavior.

L2304 | font-size: 0.8rem; | Operational statement participating in the file's runtime behavior.

L2305 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L2306 | margin-bottom: 0.2rem; | Operational statement participating in the file's runtime behavior.

L2307 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L2308 | letter-spacing: 0.03em; | Operational statement participating in the file's runtime behavior.

L2309 | } | Block delimiter controlling scope/structure in this language.

L2310 | | Blank line used for readability and logical separation.

L2311 | .pm-form-table .pm-label-col, | CSS selector line choosing the elements styled below.

L2312 | .pm-form-table .pm-value-col { | CSS selector line choosing the elements styled below.

L2313 | width: auto; | Operational statement participating in the file's runtime behavior.

L2314 | } | Block delimiter controlling scope/structure in this language.

L2315 | | Blank line used for readability and logical separation.

L2316 | .pm-form-table th, | CSS selector line choosing the elements styled below.

L2317 | .pm-form-table td { | CSS selector line choosing the elements styled below.

L2318 | min-width: 160px; | Operational statement participating in the file's runtime behavior.

L2319 | font-size: 0.92rem; | Operational statement participating in the file's runtime behavior.

L2320 | } | Block delimiter controlling scope/structure in this language.

L2321 | | Blank line used for readability and logical separation.

L2322 | .signature-pad { | CSS selector line choosing the elements styled below.

L2323 | height: 140px; | Operational statement participating in the file's runtime behavior.

L2324 | } | Block delimiter controlling scope/structure in this language.

L2325 | } | Block delimiter controlling scope/structure in this language.

L2326 | | Blank line used for readability and logical separation.

L2327 | .menu-brand-wrap { | CSS selector line choosing the elements styled below.

L2328 | opacity: 0; | Operational statement participating in the file's runtime behavior.

L2329 | pointer-events: none; | Operational statement participating in the file's runtime behavior.

L2330 | } | Block delimiter controlling scope/structure in this language.

L2331 | | Blank line used for readability and logical separation.

L2332 | .notification-bell { | CSS selector line choosing the elements styled below.

L2333 | position: relative; | Operational statement participating in the file's runtime behavior.

L2334 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L2335 | align-items: center; | Operational statement participating in the file's runtime behavior.

L2336 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L2337 | width: 40px; | Operational statement participating in the file's runtime behavior.

L2338 | height: 40px; | Operational statement participating in the file's runtime behavior.

L2339 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L2340 | text-decoration: none; | Operational statement participating in the file's runtime behavior.

L2341 | color: #0f53b0; | Operational statement participating in the file's runtime behavior.

L2342 | background: #eef6ff; | Operational statement participating in the file's runtime behavior.

L2343 | border: 1px solid #d8e8ff; | Operational statement participating in the file's runtime behavior.

L2344 | } | Block delimiter controlling scope/structure in this language.

L2345 | | Blank line used for readability and logical separation.

L2346 | .notification-bell i { | CSS selector line choosing the elements styled below.

L2347 | font-size: 1.1rem; | Operational statement participating in the file's runtime behavior.

L2348 | } | Block delimiter controlling scope/structure in this language.

L2349 | | Blank line used for readability and logical separation.

L2350 | .notification-badge { | CSS selector line choosing the elements styled below.

L2351 | position: absolute; | Operational statement participating in the file's runtime behavior.

L2352 | top: -6px; | Operational statement participating in the file's runtime behavior.

L2353 | right: -6px; | Operational statement participating in the file's runtime behavior.

L2354 | min-width: 20px; | Operational statement participating in the file's runtime behavior.

L2355 | height: 20px; | Operational statement participating in the file's runtime behavior.

L2356 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L2357 | background: #d91525; | Operational statement participating in the file's runtime behavior.

L2358 | color: #fff; | Operational statement participating in the file's runtime behavior.

L2359 | font-size: 0.72rem; | Operational statement participating in the file's runtime behavior.

L2360 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L2361 | line-height: 20px; | Operational statement participating in the file's runtime behavior.

L2362 | text-align: center; | Operational statement participating in the file's runtime behavior.

L2363 | padding: 0 5px; | Operational statement participating in the file's runtime behavior.

L2364 | } | Block delimiter controlling scope/structure in this language.

L2365 | | Blank line used for readability and logical separation.

L2366 | .notification-list { | CSS selector line choosing the elements styled below.

L2367 | gap: 0.6rem; | Operational statement participating in the file's runtime behavior.

L2368 | } | Block delimiter controlling scope/structure in this language.

L2369 | | Blank line used for readability and logical separation.

L2370 | .notification-item { | CSS selector line choosing the elements styled below.

L2371 | border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L2372 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L2373 | } | Block delimiter controlling scope/structure in this language.

L2374 | | Blank line used for readability and logical separation.

L2375 | .message-pad-card textarea.form-control { | CSS selector line choosing the elements styled below.

L2376 | resize: vertical; | Operational statement participating in the file's runtime behavior.

L2377 | min-height: 110px; | Operational statement participating in the file's runtime behavior.

L2378 | } | Block delimiter controlling scope/structure in this language.

L2379 | | Blank line used for readability and logical separation.

L2380 | .message-item { | CSS selector line choosing the elements styled below.

L2381 | border-left: 4px solid #0f53b0; | Operational statement participating in the file's runtime behavior.

L2382 | } | Block delimiter controlling scope/structure in this language.

L2383 | | Blank line used for readability and logical separation.

L2384 | .message-item .badge { | CSS selector line choosing the elements styled below.

L2385 | font-size: 0.7rem; | Operational statement participating in the file's runtime behavior.

L2386 | } | Block delimiter controlling scope/structure in this language.

L2387 | | Blank line used for readability and logical separation.

L2388 | .profile-card { | CSS selector line choosing the elements styled below.

L2389 | border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L2390 | border-radius: 16px; | Operational statement participating in the file's runtime behavior.

L2391 | box-shadow: 0 12px 28px rgba(9, 61, 126, 0.1); | Operational statement participating in the file's runtime behavior.

L2392 | } | Block delimiter controlling scope/structure in this language.

L2393 | | Blank line used for readability and logical separation.

L2394 | .profile-grid-row > .col, | CSS selector line choosing the elements styled below.

L2395 | .profile-grid-row > [class*="col-"] { | Assignment statement storing or updating program state.

L2396 | display: flex; | Operational statement participating in the file's runtime behavior.

L2397 | align-items: stretch; | Operational statement participating in the file's runtime behavior.

L2398 | } | Block delimiter controlling scope/structure in this language.

L2399 | | Blank line used for readability and logical separation.

L2400 | .profile-grid-row .profile-card { | CSS selector line choosing the elements styled below.

L2401 | width: 100%; | Operational statement participating in the file's runtime behavior.

L2402 | display: flex; | Operational statement participating in the file's runtime behavior.

L2403 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L2404 | } | Block delimiter controlling scope/structure in this language.

L2405 | | Blank line used for readability and logical separation.

L2406 | .profile-grid-row .profile-card .card-body { | CSS selector line choosing the elements styled below.

L2407 | display: flex; | Operational statement participating in the file's runtime behavior.

L2408 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L2409 | } | Block delimiter controlling scope/structure in this language.

L2410 | | Blank line used for readability and logical separation.

L2411 | .developer-control-panel { | CSS selector line choosing the elements styled below.

L2412 | margin-top: auto; | Operational statement participating in the file's runtime behavior.

L2413 | padding: 0.85rem 0.9rem; | Operational statement participating in the file's runtime behavior.

L2414 | border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L2415 | border-radius: 14px; | Operational statement participating in the file's runtime behavior.

L2416 | background: linear-gradient(135deg, #fbfdff 0%, #f1f7ff 100%); | Operational statement participating in the file's runtime behavior.

L2417 | } | Block delimiter controlling scope/structure in this language.

L2418 | | Blank line used for readability and logical separation.

L2419 | .developer-control-panel-header { | CSS selector line choosing the elements styled below.
L2420 | display: flex; | Operational statement participating in the file's runtime behavior.
L2421 | align-items: flex-start; | Operational statement participating in the file's runtime behavior.
L2422 | justify-content: space-between; | Operational statement participating in the file's runtime behavior.
L2423 | gap: 0.75rem; | Operational statement participating in the file's runtime behavior.
L2424 | margin-bottom: 0.65rem; | Operational statement participating in the file's runtime behavior.
L2425 | } | Block delimiter controlling scope/structure in this language.
L2426 | | Blank line used for readability and logical separation.
L2427 | .developer-control-chips { | CSS selector line choosing the elements styled below.
L2428 | display: flex; | Operational statement participating in the file's runtime behavior.
L2429 | flex-wrap: wrap; | Operational statement participating in the file's runtime behavior.
L2430 | gap: 0.4rem; | Operational statement participating in the file's runtime behavior.
L2431 | } | Block delimiter controlling scope/structure in this language.
L2432 | | Blank line used for readability and logical separation.
L2433 | .developer-control-chip { | CSS selector line choosing the elements styled below.
L2434 | display: inline-flex; | Operational statement participating in the file's runtime behavior.
L2435 | align-items: center; | Operational statement participating in the file's runtime behavior.
L2436 | gap: 0.32rem; | Operational statement participating in the file's runtime behavior.
L2437 | padding: 0.24rem 0.58rem; | Operational statement participating in the file's runtime behavior.
L2438 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.
L2439 | background: #eaf3ff; | Operational statement participating in the file's runtime behavior.
L2440 | border: 1px solid #c9defc; | Operational statement participating in the file's runtime behavior.
L2441 | color: #255596; | Operational statement participating in the file's runtime behavior.
L2442 | font-size: 0.72rem; | Operational statement participating in the file's runtime behavior.
L2443 | font-weight: 700; | Operational statement participating in the file's runtime behavior.
L2444 | line-height: 1; | Operational statement participating in the file's runtime behavior.
L2445 | } | Block delimiter controlling scope/structure in this language.
L2446 | | Blank line used for readability and logical separation.
L2447 | .developer-control-chip i { | CSS selector line choosing the elements styled below.
L2448 | font-size: 0.78rem; | Operational statement participating in the file's runtime behavior.
L2449 | } | Block delimiter controlling scope/structure in this language.
L2450 | | Blank line used for readability and logical separation.
L2451 | body[data-theme="dark"] .developer-control-panel { | Assignment statement storing or updating program state.
L2452 | border-color: #31486b; | Operational statement participating in the file's runtime behavior.
L2453 | background: linear-gradient(145deg, rgba(23, 38, 61, 0.96) 0%, rgba(19, 32, 53, 0.96) 100%); | Operational statement participating in the file's runtime behavior.
L2454 | } | Block delimiter controlling scope/structure in this language.
L2455 | | Blank line used for readability and logical separation.
L2456 | body[data-theme="dark"] .developer-control-chip { | Assignment statement storing or updating program state.
L2457 | background: rgba(32, 59, 95, 0.92); | Operational statement participating in the file's runtime behavior.
L2458 | border-color: rgba(106, 160, 235, 0.28); | Operational statement participating in the file's runtime behavior.
L2459 | color: #c9e2ff; | Operational statement participating in the file's runtime behavior.
L2460 | } | Block delimiter controlling scope/structure in this language.
L2461 | | Blank line used for readability and logical separation.
L2462 | .profile-gender-icon { | CSS selector line choosing the elements styled below.
L2463 | width: 34px; | Operational statement participating in the file's runtime behavior.
L2464 | height: 34px; | Operational statement participating in the file's runtime behavior.
L2465 | border-radius: 50%; | Operational statement participating in the file's runtime behavior.
L2466 | display: inline-flex; | Operational statement participating in the file's runtime behavior.
L2467 | align-items: center; | Operational statement participating in the file's runtime behavior.
L2468 | justify-content: center; | Operational statement participating in the file's runtime behavior.
L2469 | background: #eaf3ff; | Operational statement participating in the file's runtime behavior.
L2470 | color: #0f53b0; | Operational statement participating in the file's runtime behavior.
L2471 | font-size: 1.1rem; | Operational statement participating in the file's runtime behavior.
L2472 | } | Block delimiter controlling scope/structure in this language.
L2473 | | Blank line used for readability and logical separation.

L2474 | .profile-avatar-icon { | CSS selector line choosing the elements styled below.

L2475 | width: 38px; | Operational statement participating in the file's runtime behavior.

L2476 | height: 38px; | Operational statement participating in the file's runtime behavior.

L2477 | border-radius: 50%; | Operational statement participating in the file's runtime behavior.

L2478 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L2479 | align-items: center; | Operational statement participating in the file's runtime behavior.

L2480 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L2481 | background: #d8ebff; | Operational statement participating in the file's runtime behavior.

L2482 | color: #0a4fa8; | Operational statement participating in the file's runtime behavior.

L2483 | font-size: 1.15rem; | Operational statement participating in the file's runtime behavior.

L2484 | border: 1px solid #b8d9ff; | Operational statement participating in the file's runtime behavior.

L2485 | } | Block delimiter controlling scope/structure in this language.

L2486 | | Blank line used for readability and logical separation.

L2487 | .profile-identity-stack { | CSS selector line choosing the elements styled below.

L2488 | display: flex; | Operational statement participating in the file's runtime behavior.

L2489 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L2490 | align-items: flex-end; | Operational statement participating in the file's runtime behavior.

L2491 | gap: 0.36rem; | Operational statement participating in the file's runtime behavior.

L2492 | min-width: 130px; | Operational statement participating in the file's runtime behavior.

L2493 | } | Block delimiter controlling scope/structure in this language.

L2494 | | Blank line used for readability and logical separation.

L2495 | .profile-avatar-pill { | CSS selector line choosing the elements styled below.

L2496 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L2497 | align-items: center; | Operational statement participating in the file's runtime behavior.

L2498 | gap: 0.44rem; | Operational statement participating in the file's runtime behavior.

L2499 | padding: 0.24rem 0.52rem; | Operational statement participating in the file's runtime behavior.

L2500 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L2501 | border: 1px solid #b8d9ff; | Operational statement participating in the file's runtime behavior.

L2502 | background: linear-gradient(135deg, #eaf3ff 0%, #dcecff 100%); | Operational statement participating in the file's runtime behavior.

L2503 | color: #0a4fa8; | Operational statement participating in the file's runtime behavior.

L2504 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L2505 | font-size: 0.72rem; | Operational statement participating in the file's runtime behavior.

L2506 | line-height: 1; | Operational statement participating in the file's runtime behavior.

L2507 | } | Block delimiter controlling scope/structure in this language.

L2508 | | Blank line used for readability and logical separation.

L2509 | .profile-avatar-pill .avatar-glyph { | CSS selector line choosing the elements styled below.

L2510 | font-size: 1.04rem; | Operational statement participating in the file's runtime behavior.

L2511 | line-height: 1; | Operational statement participating in the file's runtime behavior.

L2512 | } | Block delimiter controlling scope/structure in this language.

L2513 | | Blank line used for readability and logical separation.

L2514 | .profile-avatar-pill .avatar-meta { | CSS selector line choosing the elements styled below.

L2515 | max-width: 105px; | Operational statement participating in the file's runtime behavior.

L2516 | overflow: hidden; | Operational statement participating in the file's runtime behavior.

L2517 | text-overflow: ellipsis; | Operational statement participating in the file's runtime behavior.

L2518 | white-space: nowrap; | Operational statement participating in the file's runtime behavior.

L2519 | } | Block delimiter controlling scope/structure in this language.

L2520 | | Blank line used for readability and logical separation.

L2521 | .profile-gender-pill { | CSS selector line choosing the elements styled below.

L2522 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L2523 | align-items: center; | Operational statement participating in the file's runtime behavior.

L2524 | gap: 0.34rem; | Operational statement participating in the file's runtime behavior.

L2525 | padding: 0.18rem 0.5rem; | Operational statement participating in the file's runtime behavior.

L2526 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L2527 | border: 1px solid #d6e5ff; | Operational statement participating in the file's runtime behavior.

L2528 | background: #f6fa99; | Operational statement participating in the file's runtime behavior.

L2529 | color: #2f5f9f; | Operational statement participating in the file's runtime behavior.

L2530 | font-size: 0.71rem; | Operational statement participating in the file's runtime behavior.

L2531 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L2532 | line-height: 1; | Operational statement participating in the file's runtime behavior.

L2533 | } | Block delimiter controlling scope/structure in this language.

L2534 | | Blank line used for readability and logical separation.

L2535 | .profile-gender-pill i { | CSS selector line choosing the elements styled below.

L2536 | font-size: 0.88rem; | Operational statement participating in the file's runtime behavior.

L2537 | line-height: 1; | Operational statement participating in the file's runtime behavior.

L2538 | } | Block delimiter controlling scope/structure in this language.

L2539 | | Blank line used for readability and logical separation.

L2540 | @media (max-width: 576px) { | Decorator line that modifies the behavior of the definition below.

L2541 | .profile-identity-stack { | CSS selector line choosing the elements styled below.

L2542 | min-width: 106px; | Operational statement participating in the file's runtime behavior.

L2543 | gap: 0.28rem; | Operational statement participating in the file's runtime behavior.

L2544 | } | Block delimiter controlling scope/structure in this language.

L2545 | | Blank line used for readability and logical separation.

L2546 | .profile-avatar-pill { | CSS selector line choosing the elements styled below.

L2547 | padding: 0.18rem 0.42rem; | Operational statement participating in the file's runtime behavior.

L2548 | font-size: 0.67rem; | Operational statement participating in the file's runtime behavior.

L2549 | } | Block delimiter controlling scope/structure in this language.

L2550 | | Blank line used for readability and logical separation.

L2551 | .profile-avatar-pill .avatar-meta { | CSS selector line choosing the elements styled below.

L2552 | max-width: 82px; | Operational statement participating in the file's runtime behavior.

L2553 | } | Block delimiter controlling scope/structure in this language.

L2554 | | Blank line used for readability and logical separation.

L2555 | .profile-gender-pill { | CSS selector line choosing the elements styled below.

L2556 | font-size: 0.66rem; | Operational statement participating in the file's runtime behavior.

L2557 | padding: 0.14rem 0.42rem; | Operational statement participating in the file's runtime behavior.

L2558 | } | Block delimiter controlling scope/structure in this language.

L2559 | } | Block delimiter controlling scope/structure in this language.

L2560 | | Blank line used for readability and logical separation.

L2561 | body[data-theme="dark"] .profile-card, | Assignment statement storing or updating program state.

L2562 | body[data-theme="dark"] .profile-gender-icon, | Assignment statement storing or updating program state.

L2563 | body[data-theme="dark"] .profile-avatar-icon { | Assignment statement storing or updating program state.

L2564 | background: #1a2a41; | Operational statement participating in the file's runtime behavior.

L2565 | border-color: #31486b; | Operational statement participating in the file's runtime behavior.

L2566 | color: #e8eef8; | Operational statement participating in the file's runtime behavior.

L2567 | } | Block delimiter controlling scope/structure in this language.

L2568 | | Blank line used for readability and logical separation.

L2569 | body[data-theme="dark"] .profile-avatar-pill { | Assignment statement storing or updating program state.

L2570 | border-color: rgba(124, 173, 238, 0.4); | Operational statement participating in the file's runtime behavior.

L2571 | background: linear-gradient(140deg, rgba(31, 57, 91, 0.95) 0%, rgba(22, 44, 74, 0.95) 100%); | Operational statement participating in the file's runtime behavior.

L2572 | color: #cae3ff; | Operational statement participating in the file's runtime behavior.

L2573 | } | Block delimiter controlling scope/structure in this language.

L2574 | | Blank line used for readability and logical separation.

L2575 | /* --- per-avatar-key colour themes (light) --- */ | Operational statement participating in the file's runtime behavior.

L2576 | .profile-avatar-pill[data-avatar-key="technician"] { | Assignment statement storing or updating program state.

L2577 | background: linear-gradient(135deg, #fff4e5 0%, #ffe8cc 100%); | Operational statement participating in the file's runtime behavior.

L2578 | border-color: #f9a55c; | Operational statement participating in the file's runtime behavior.

L2579 | color: #a84e00; | Operational statement participating in the file's runtime behavior.

L2580 | } | Block delimiter controlling scope/structure in this language.

L2581 | .profile-avatar-pill[data-avatar-key="male_exec"] { | Assignment statement storing or updating program state.

L2582 | background: linear-gradient(135deg, #e8f2ff 0%, #d3e8ff 100%); | Operational statement participating in the file's runtime behavior.

L2583 | border-color: #5a9fd4; | Operational statement participating in the file's runtime behavior.

L2584 | color: #0a4fa8; | Operational statement participating in the file's runtime behavior.

L2585 | } | Block delimiter controlling scope/structure in this language.

L2586 | .profile-avatar-pill[data-avatar-key="female_exec"] { | Assignment statement storing or updating program state.

L2587 | background: linear-gradient(135deg, #f5eaff 0%, #ead5ff 100%); | Operational statement participating in the file's runtime behavior.

L2588 | border-color: #aa7dc2; | Operational statement participating in the file's runtime behavior.

L2589 | color: #6b22a8; | Operational statement participating in the file's runtime behavior.

L2590 | } | Block delimiter controlling scope/structure in this language.

L2591 | .profile-avatar-pill[data-avatar-key="developer"] { | Assignment statement storing or updating program state.

L2592 | background: linear-gradient(135deg, #e9fff3 0%, #d3f5e7 100%); | Operational statement participating in the file's runtime behavior.

L2593 | border-color: #4dbf84; | Operational statement participating in the file's runtime behavior.

L2594 | color: #0d6e3f; | Operational statement participating in the file's runtime behavior.

L2595 | } | Block delimiter controlling scope/structure in this language.

L2596 | | Blank line used for readability and logical separation.

L2597 | /* --- per-avatar-key colour themes (dark) --- */ | Operational statement participating in the file's runtime behavior.

L2598 | body[data-theme="dark"] .profile-avatar-pill[data-avatar-key="technician"] { | Assignment statement storing or updating program state.

L2599 | background: linear-gradient(140deg, rgba(95, 48, 0, 0.92) 0%, rgba(72, 34, 0, 0.92) 100%); | Operational statement participating in the file's runtime behavior.

L2600 | border-color: rgba(249, 165, 92, 0.55); | Operational statement participating in the file's runtime behavior.

L2601 | color: #ffbd78; | Operational statement participating in the file's runtime behavior.

L2602 | } | Block delimiter controlling scope/structure in this language.

L2603 | body[data-theme="dark"] .profile-avatar-pill[data-avatar-key="male_exec"] { | Assignment statement storing or updating program state.

L2604 | background: linear-gradient(140deg, rgba(18, 55, 105, 0.95) 0%, rgba(12, 40, 82, 0.95) 100%); | Operational statement participating in the file's runtime behavior.

L2605 | border-color: rgba(90, 159, 212, 0.45); | Operational statement participating in the file's runtime behavior.

L2606 | color: #80c8ff; | Operational statement participating in the file's runtime behavior.

L2607 | } | Block delimiter controlling scope/structure in this language.

L2608 | body[data-theme="dark"] .profile-avatar-pill[data-avatar-key="female_exec"] { | Assignment statement storing or updating program state.

L2609 | background: linear-gradient(140deg, rgba(68, 25, 108, 0.92) 0%, rgba(50, 16, 82, 0.92) 100%); | Operational statement participating in the file's runtime behavior.

L2610 | border-color: rgba(170, 125, 194, 0.48); | Operational statement participating in the file's runtime behavior.

L2611 | color: #dcaaff; | Operational statement participating in the file's runtime behavior.

L2612 | } | Block delimiter controlling scope/structure in this language.

L2613 | body[data-theme="dark"] .profile-avatar-pill[data-avatar-key="developer"] { | Assignment statement storing or updating program state.

L2614 | background: linear-gradient(140deg, rgba(12, 68, 42, 0.92) 0%, rgba(8, 50, 30, 0.92) 100%); | Operational statement participating in the file's runtime behavior.

L2615 | border-color: rgba(77, 191, 132, 0.48); | Operational statement participating in the file's runtime behavior.

L2616 | color: #7de0ae; | Operational statement participating in the file's runtime behavior.

L2617 | } | Block delimiter controlling scope/structure in this language.

L2618 | | Blank line used for readability and logical separation.

L2619 | body[data-theme="dark"] .profile-gender-pill { | Assignment statement storing or updating program state.

L2620 | border-color: rgba(130, 177, 239, 0.32); | Operational statement participating in the file's runtime behavior.

L2621 | background: rgba(24, 44, 72, 0.88); | Operational statement participating in the file's runtime behavior.

L2622 | color: #c7dcfb; | Operational statement participating in the file's runtime behavior.

L2623 | } | Block delimiter controlling scope/structure in this language.

L2624 | | Blank line used for readability and logical separation.

L2625 | .avatar-pick-group { | CSS selector line choosing the elements styled below.

L2626 | display: flex; | Operational statement participating in the file's runtime behavior.

L2627 | flex-wrap: wrap; | Operational statement participating in the file's runtime behavior.

L2628 | gap: 0.4rem; | Operational statement participating in the file's runtime behavior.

L2629 | } | Block delimiter controlling scope/structure in this language.

L2630 | | Blank line used for readability and logical separation.

L2631 | .avatar-pick-tile { | CSS selector line choosing the elements styled below.

L2632 | display: flex; | Operational statement participating in the file's runtime behavior.

L2633 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L2634 | align-items: center; | Operational statement participating in the file's runtime behavior.

L2635 | gap: 0.15rem; | Operational statement participating in the file's runtime behavior.

L2636 | padding: 0.45rem 0.55rem; | Operational statement participating in the file's runtime behavior.

L2637 | border: 2px solid rgba(47, 125, 255, 0.2); | Operational statement participating in the file's runtime behavior.

L2638 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L2639 | cursor: pointer; | Operational statement participating in the file's runtime behavior.

L2640 | font-size: 0.64rem; | Operational statement participating in the file's runtime behavior.

L2641 | font-weight: 600; | Operational statement participating in the file's runtime behavior.

L2642 | color: var(--muted); | Operational statement participating in the file's runtime behavior.

L2643 | background: var(--card-bg); | Operational statement participating in the file's runtime behavior.

L2644 | transition: border-color 0.15s ease, background 0.15s ease, color 0.15s ease; | Operational statement participating in the file's runtime behavior.

L2645 | min-width: 58px; | Operational statement participating in the file's runtime behavior.

L2646 | text-align: center; | Operational statement participating in the file's runtime behavior.

L2647 | user-select: none; | Operational statement participating in the file's runtime behavior.

L2648 | line-height: 1.2; | Operational statement participating in the file's runtime behavior.

L2649 | } | Block delimiter controlling scope/structure in this language.

L2650 | | Blank line used for readability and logical separation.

L2651 | .avatar-pick-tile i { | CSS selector line choosing the elements styled below.

L2652 | font-size: 1.55rem; | Operational statement participating in the file's runtime behavior.

L2653 | line-height: 1; | Operational statement participating in the file's runtime behavior.

L2654 | display: block; | Operational statement participating in the file's runtime behavior.

L2655 | } | Block delimiter controlling scope/structure in this language.

L2656 | | Blank line used for readability and logical separation.

L2657 | .avatar-pick-tile:hover { | CSS selector line choosing the elements styled below.

L2658 | border-color: rgba(10, 132, 255, 0.5); | Operational statement participating in the file's runtime behavior.

L2659 | } | Block delimiter controlling scope/structure in this language.

L2660 | | Blank line used for readability and logical separation.

L2661 | .avatar-pick-tile.is-selected { | CSS selector line choosing the elements styled below.

L2662 | border-color: #0a84ff; | Operational statement participating in the file's runtime behavior.

L2663 | background: rgba(10, 132, 255, 0.09); | Operational statement participating in the file's runtime behavior.

L2664 | color: #0a84ff; | Operational statement participating in the file's runtime behavior.

L2665 | box-shadow: 0 0 3px rgba(10, 132, 255, 0.15); | Operational statement participating in the file's runtime behavior.

L2666 | } | Block delimiter controlling scope/structure in this language.

L2667 | | Blank line used for readability and logical separation.

L2668 | body[data-theme="dark"] .avatar-pick-tile { | Assignment statement storing or updating program state.

L2669 | background: var(--card-bg-soft); | Operational statement participating in the file's runtime behavior.

L2670 | border-color: rgba(78, 148, 255, 0.22); | Operational statement participating in the file's runtime behavior.

L2671 | } | Block delimiter controlling scope/structure in this language.

L2672 | | Blank line used for readability and logical separation.

L2673 | body[data-theme="dark"] .avatar-pick-tile.is-selected { | Assignment statement storing or updating program state.

L2674 | background: rgba(10, 132, 255, 0.18); | Operational statement participating in the file's runtime behavior.

L2675 | border-color: #3d9bff; | Operational statement participating in the file's runtime behavior.

L2676 | color: #7ec8ff; | Operational statement participating in the file's runtime behavior.

L2677 | } | Block delimiter controlling scope/structure in this language.

L2678 | | Blank line used for readability and logical separation.

L2679 | /* ===== Role Access Matrix ===== */ | Operational statement participating in the file's runtime behavior.

L2680 | .role-matrix-card { | CSS selector line choosing the elements styled below.

L2681 | border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L2682 | border-radius: 18px; | Operational statement participating in the file's runtime behavior.

L2683 | box-shadow: 0 6px 24px rgba(8, 49, 110, 0.07); | Operational statement participating in the file's runtime behavior.

L2684 | overflow: hidden; | Operational statement participating in the file's runtime behavior.

L2685 | } | Block delimiter controlling scope/structure in this language.

L2686 | | Blank line used for readability and logical separation.

L2687 | .role-matrix-header { | CSS selector line choosing the elements styled below.

L2688 | background: linear-gradient(135deg, #f0f6ff 0%, #e6f0ff 100%); | Operational statement participating in the file's runtime behavior.

L2689 | border-bottom: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L2690 | } | Block delimiter controlling scope/structure in this language.

L2691 | | Blank line used for readability and logical separation.

L2692 | .role-matrix-icon { | CSS selector line choosing the elements styled below.

L2693 | width: 42px; | Operational statement participating in the file's runtime behavior.

L2694 | height: 42px; | Operational statement participating in the file's runtime behavior.

L2695 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L2696 | background: linear-gradient(135deg, #0a84ff 0%, #5e5ce6 100%); | Operational statement participating in the file's runtime behavior.

L2697 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L2698 | align-items: center; | Operational statement participating in the file's runtime behavior.

L2699 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L2700 | color: #fff; | Operational statement participating in the file's runtime behavior.

L2701 | font-size: 1.2rem; | Operational statement participating in the file's runtime behavior.

L2702 | flex-shrink: 0; | Operational statement participating in the file's runtime behavior.

L2703 | } | Block delimiter controlling scope/structure in this language.

L2704 | | Blank line used for readability and logical separation.

L2705 | .role-matrix-table { | CSS selector line choosing the elements styled below.

L2706 | font-size: 0.82rem; | Operational statement participating in the file's runtime behavior.

L2707 | border-collapse: separate; | Operational statement participating in the file's runtime behavior.

L2708 | border-spacing: 0; | Operational statement participating in the file's runtime behavior.

L2709 | } | Block delimiter controlling scope/structure in this language.

L2710 | | Blank line used for readability and logical separation.

L2711 | .role-matrix-table thead tr th { | CSS selector line choosing the elements styled below.

L2712 | background: #f8fa; | Operational statement participating in the file's runtime behavior.

L2713 | color: #3a5580; | Operational statement participating in the file's runtime behavior.

L2714 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L2715 | font-size: 0.73rem; | Operational statement participating in the file's runtime behavior.

L2716 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L2717 | letter-spacing: 0.06em; | Operational statement participating in the file's runtime behavior.

L2718 | border-bottom: 2px solid #d8e8ff; | Operational statement participating in the file's runtime behavior.

L2719 | padding: 0.65rem 1rem; | Operational statement participating in the file's runtime behavior.

L2720 | white-space: nowrap; | Operational statement participating in the file's runtime behavior.

L2721 | } | Block delimiter controlling scope/structure in this language.

L2722 | | Blank line used for readability and logical separation.

L2723 | .role-matrix-table thead tr th:first-child { padding-left: 1.4rem; } | CSS selector line choosing the elements styled below.

L2724 | .role-matrix-table tbody tr td:first-child { padding-left: 1.4rem; } | CSS selector line choosing the elements styled below.

L2725 | | Blank line used for readability and logical separation.

L2726 | .role-matrix-row td { | CSS selector line choosing the elements styled below.

L2727 | padding: 0.9rem 1rem; | Operational statement participating in the file's runtime behavior.

L2728 | vertical-align: top; | Operational statement participating in the file's runtime behavior.

L2729 | border-bottom: 1px solid #eef3fc; | Operational statement participating in the file's runtime behavior.

L2730 | } | Block delimiter controlling scope/structure in this language.

L2731 | | Blank line used for readability and logical separation.

L2732 | .role-matrix-row:last-child td { | CSS selector line choosing the elements styled below.

L2733 | border-bottom: none; | Operational statement participating in the file's runtime behavior.

L2734 | } | Block delimiter controlling scope/structure in this language.

L2735 | | Blank line used for readability and logical separation.

L2736 | .role-matrix-row:hover td { | CSS selector line choosing the elements styled below.

L2737 | background: #f5f9ff; | Operational statement participating in the file's runtime behavior.

L2738 | } | Block delimiter controlling scope/structure in this language.

L2739 | | Blank line used for readability and logical separation.

L2740 | /* Role badges */ | Operational statement participating in the file's runtime behavior.

L2741 | .role-matrix-badge { | CSS selector line choosing the elements styled below.

L2742 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L2743 | align-items: center; | Operational statement participating in the file's runtime behavior.

L2744 | gap: 0.38rem; | Operational statement participating in the file's runtime behavior.

L2745 | padding: 0.3rem 0.7rem; | Operational statement participating in the file's runtime behavior.

L2746 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L2747 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L2748 | font-size: 0.76rem; | Operational statement participating in the file's runtime behavior.

L2749 | white-space: nowrap; | Operational statement participating in the file's runtime behavior.

L2750 | } | Block delimiter controlling scope/structure in this language.

L2751 | | Blank line used for readability and logical separation.

L2752 | .role-badge-technician { background: #fff4e5; color: #a84e00; border: 1px solid #f9a55c; } | CSS selector line choosing the element

L2753 | .role-badge-staff { background: #eaf3ff; color: #0a4fa8; border: 1px solid #5a9fd4; } | CSS selector line choosing the element

L2754 | .role-badge-manager { background: #f0ebff; color: #5b22a8; border: 1px solid #9a6fd8; } | CSS selector line choosing the element

L2755 | .role-badge-developer { background: #e9fff3; color: #0d6e3f; border: 1px solid #4dbf84; } | CSS selector line choosing the element

L2756 | | Blank line used for readability and logical separation.

L2757 | /* Page filename chip */ | Operational statement participating in the file's runtime behavior.

L2758 | .role-matrix-page { | CSS selector line choosing the elements styled below.

L2759 | font-size: 0.73rem; | Operational statement participating in the file's runtime behavior.

L2760 | background: #eef4ff; | Operational statement participating in the file's runtime behavior.

L2761 | color: #1a4a9f; | Operational statement participating in the file's runtime behavior.

L2762 | border: 1px solid #c7d9f8; | Operational statement participating in the file's runtime behavior.

L2763 | border-radius: 6px; | Operational statement participating in the file's runtime behavior.

L2764 | padding: 0.18rem 0.42rem; | Operational statement participating in the file's runtime behavior.

L2765 | white-space: nowrap; | Operational statement participating in the file's runtime behavior.

L2766 | } | Block delimiter controlling scope/structure in this language.

L2767 | | Blank line used for readability and logical separation.

L2768 | /* Bullet list inside cells */ | Operational statement participating in the file's runtime behavior.

L2769 | .role-matrix-list { | CSS selector line choosing the elements styled below.

L2770 | margin: 0; | Operational statement participating in the file's runtime behavior.

L2771 | padding: 0; | Operational statement participating in the file's runtime behavior.

L2772 | list-style: none; | Operational statement participating in the file's runtime behavior.

L2773 | display: flex; | Operational statement participating in the file's runtime behavior.

L2774 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L2775 | gap: 0.28rem; | Operational statement participating in the file's runtime behavior.

L2776 | } | Block delimiter controlling scope/structure in this language.

L2777 | | Blank line used for readability and logical separation.

L2778 | .role-matrix-list li { | CSS selector line choosing the elements styled below.

L2779 | display: flex; | Operational statement participating in the file's runtime behavior.

L2780 | align-items: flex-start; | Operational statement participating in the file's runtime behavior.

L2781 | gap: 0.38rem; | Operational statement participating in the file's runtime behavior.

L2782 | color: #2c3e60; | Operational statement participating in the file's runtime behavior.

L2783 | } | Block delimiter controlling scope/structure in this language.

L2784 | | Blank line used for readability and logical separation.

L2785 | .role-matrix-list li i { | CSS selector line choosing the elements styled below.

L2786 | font-size: 0.78rem; | Operational statement participating in the file's runtime behavior.

L2787 | margin-top: 0.1rem; | Operational statement participating in the file's runtime behavior.

L2788 | flex-shrink: 0; | Operational statement participating in the file's runtime behavior.

L2789 | color: #4a80cc; | Operational statement participating in the file's runtime behavior.

L2790 | } | Block delimiter controlling scope/structure in this language.

L2791 | | Blank line used for readability and logical separation.

L2792 | /* Data scope pill */ | Operational statement participating in the file's runtime behavior.

L2793 | .role-matrix-scope { | CSS selector line choosing the elements styled below.

L2794 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L2795 | align-items: center; | Operational statement participating in the file's runtime behavior.

L2796 | gap: 0.36rem; | Operational statement participating in the file's runtime behavior.

L2797 | padding: 0.25rem 0.6rem; | Operational statement participating in the file's runtime behavior.

L2798 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L2799 | font-size: 0.73rem; | Operational statement participating in the file's runtime behavior.

L2800 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L2801 | white-space: nowrap; | Operational statement participating in the file's runtime behavior.

L2802 | } | Block delimiter controlling scope/structure in this language.

L2803 | | Blank line used for readability and logical separation.

L2804 | .scope-own { background: #fff8e6; color: #8a5800; border: 1px solid #f5c96a; } | CSS selector line choosing the elements styled

L2805 | .scope-all { background: #e8f6ff; color: #0a4fa8; border: 1px solid #82c1f0; } | CSS selector line choosing the elements styled

L2806 | .scope-system { background: #edfff5; color: #0d6e3f; border: 1px solid #5dd49a; } | CSS selector line choosing the elements styled

L2807 | | Blank line used for readability and logical separation.

L2808 | /* Process dependency text */ | Operational statement participating in the file's runtime behavior.

L2809 | .role-matrix-dep { | CSS selector line choosing the elements styled below.

L2810 | color: #4a5e80; | Operational statement participating in the file's runtime behavior.

L2811 | font-size: 0.79rem; | Operational statement participating in the file's runtime behavior.

L2812 | line-height: 1.45; | Operational statement participating in the file's runtime behavior.

L2813 | } | Block delimiter controlling scope/structure in this language.

L2814 | | Blank line used for readability and logical separation.

L2815 | /* Dark mode */ | Operational statement participating in the file's runtime behavior.

L2816 | body[data-theme="dark"] .role-matrix-card { | Assignment statement storing or updating program state.

L2817 | border-color: #2a3d5c; | Operational statement participating in the file's runtime behavior.

L2818 | box-shadow: 0 6px 24px rgba(0, 0, 0, 0.25); | Operational statement participating in the file's runtime behavior.

L2819 | } | Block delimiter controlling scope/structure in this language.

L2820 | | Blank line used for readability and logical separation.

L2821 | body[data-theme="dark"] .role-matrix-header { | Assignment statement storing or updating program state.

L2822 | background: linear-gradient(135deg, #182840 0%, #1d3050 100%); | Operational statement participating in the file's runtime behavior.

L2823 | border-color: #2a3d5c; | Operational statement participating in the file's runtime behavior.

L2824 | } | Block delimiter controlling scope/structure in this language.

L2825 | | Blank line used for readability and logical separation.

L2826 | body[data-theme="dark"] .role-matrix-table thead tr th { | Assignment statement storing or updating program state.

L2827 | background: #162235; | Operational statement participating in the file's runtime behavior.

L2828 | color: #8cb4e0; | Operational statement participating in the file's runtime behavior.

L2829 | border-color: #2a3d5c; | Operational statement participating in the file's runtime behavior.

L2830 | } | Block delimiter controlling scope/structure in this language.

L2831 | | Blank line used for readability and logical separation.

L2832 | body[data-theme="dark"] .role-matrix-row td { | Assignment statement storing or updating program state.

L2833 | border-color: #1e3050; | Operational statement participating in the file's runtime behavior.

L2834 | color: #c8d8f0; | Operational statement participating in the file's runtime behavior.

L2835 | } | Block delimiter controlling scope/structure in this language.

L2836 | | Blank line used for readability and logical separation.

L2837 | body[data-theme="dark"] .role-matrix-row:hover td { | Assignment statement storing or updating program state.

L2838 | background: #182c48; | Operational statement participating in the file's runtime behavior.

L2839 | } | Block delimiter controlling scope/structure in this language.

L2840 | | Blank line used for readability and logical separation.

L2841 | body[data-theme="dark"] .role-matrix-page { | Assignment statement storing or updating program state.

L2842 | background: #1a2f4a; | Operational statement participating in the file's runtime behavior.

L2843 | color: #7ab4f0; | Operational statement participating in the file's runtime behavior.

L2844 | border-color: #2a4260; | Operational statement participating in the file's runtime behavior.

L2845 | } | Block delimiter controlling scope/structure in this language.

L2846 | | Blank line used for readability and logical separation.

L2847 | body[data-theme="dark"] .role-matrix-list li { color: #b8cce8; } | Assignment statement storing or updating program state.

L2848 | body[data-theme="dark"] .role-matrix-list li i { color: #5a9fd4; } | Assignment statement storing or updating program state.

L2849 | body[data-theme="dark"] .role-matrix-dep { color: #8aa8cc; } | Assignment statement storing or updating program state.

L2850 | | Blank line used for readability and logical separation.

L2851 | body[data-theme="dark"] .role-badge-technician { background: rgba(95,48,0,0.6); color: #ffbd78; border-color: rgba(249,165,92,0.5);

L2852 | body[data-theme="dark"] .role-badge-staff { background: rgba(18,55,105,0.6); color: #80c8ff; border-color: rgba(90,159,212,0.5);

L2853 | body[data-theme="dark"] .role-badge-manager { background: rgba(55,20,95,0.6); color: #cda8ff; border-color: rgba(154,111,216,0.5);

L2854 | body[data-theme="dark"] .role-badge-developer { background: rgba(12,68,42,0.6); color: #7de0ae; border-color: rgba(77,191,132,0.5);

L2855 | | Blank line used for readability and logical separation.

L2856 | body[data-theme="dark"] .scope-own { background: rgba(80,48,0,0.5); color: #ffc966; border-color: rgba(200,160,50,0.45); } | A

L2857 | body[data-theme="dark"] .scope-all { background: rgba(15,50,95,0.55); color: #7ec8ff; border-color: rgba(90,160,220,0.4); } | A

L2858 | body[data-theme="dark"] .scope-system { background: rgba(10,60,35,0.55); color: #6ddfaa; border-color: rgba(77,180,132,0.4); } | A

```
L2859 | /* ===== */ | Operational statement participating in the file's runtime beh
L2860 | | Blank line used for readability and logical separation.
L2861 | .settings-grid { | CSS selector line choosing the elements styled below.
L2862 |   margin-top: 0.15rem; | Operational statement participating in the file's runtime behavior.
L2863 | } | Block delimiter controlling scope/structure in this language.
L2864 | | Blank line used for readability and logical separation.
L2865 | .settings-card { | CSS selector line choosing the elements styled below.
L2866 |   border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.
L2867 |   border-radius: 18px; | Operational statement participating in the file's runtime behavior.
L2868 |   box-shadow: 0 16px 32px rgba(8, 59, 125, 0.08); | Operational statement participating in the file's runtime behavior.
L2869 |   background: linear-gradient(145deg, #f9fcff 0%, #ffffff 100%); | Operational statement participating in the file's runtime behav
L2870 | } | Block delimiter controlling scope/structure in this language.
L2871 | | Blank line used for readability and logical separation.
L2872 | .settings-card-title { | CSS selector line choosing the elements styled below.
L2873 |   display: flex; | Operational statement participating in the file's runtime behavior.
L2874 |   align-items: center; | Operational statement participating in the file's runtime behavior.
L2875 |   gap: 0.55rem; | Operational statement participating in the file's runtime behavior.
L2876 |   font-weight: 800; | Operational statement participating in the file's runtime behavior.
L2877 |   color: #0d3d7a; | Operational statement participating in the file's runtime behavior.
L2878 | } | Block delimiter controlling scope/structure in this language.
L2879 | | Blank line used for readability and logical separation.
L2880 | .mode-switch-wrap { | CSS selector line choosing the elements styled below.
L2881 |   display: inline-flex; | Operational statement participating in the file's runtime behavior.
L2882 |   align-items: center; | Operational statement participating in the file's runtime behavior.
L2883 |   gap: 0.65rem; | Operational statement participating in the file's runtime behavior.
L2884 | } | Block delimiter controlling scope/structure in this language.
L2885 | | Blank line used for readability and logical separation.
L2886 | .mode-switch-wrap input { | CSS selector line choosing the elements styled below.
L2887 |   display: none; | Operational statement participating in the file's runtime behavior.
L2888 | } | Block delimiter controlling scope/structure in this language.
L2889 | | Blank line used for readability and logical separation.
L2890 | .mode-switch-slider { | CSS selector line choosing the elements styled below.
L2891 |   width: 52px; | Operational statement participating in the file's runtime behavior.
L2892 |   height: 28px; | Operational statement participating in the file's runtime behavior.
L2893 |   border-radius: 999px; | Operational statement participating in the file's runtime behavior.
L2894 |   background: #d3def0; | Operational statement participating in the file's runtime behavior.
L2895 |   position: relative; | Operational statement participating in the file's runtime behavior.
L2896 |   transition: background 0.25s ease; | Operational statement participating in the file's runtime behavior.
L2897 | } | Block delimiter controlling scope/structure in this language.
L2898 | | Blank line used for readability and logical separation.
L2899 | .mode-switch-slider::after { | CSS selector line choosing the elements styled below.
L2900 |   content: ""; | Operational statement participating in the file's runtime behavior.
L2901 |   width: 22px; | Operational statement participating in the file's runtime behavior.
L2902 |   height: 22px; | Operational statement participating in the file's runtime behavior.
L2903 |   border-radius: 50%; | Operational statement participating in the file's runtime behavior.
L2904 |   background: #fff; | Operational statement participating in the file's runtime behavior.
L2905 |   position: absolute; | Operational statement participating in the file's runtime behavior.
L2906 |   top: 3px; | Operational statement participating in the file's runtime behavior.
L2907 |   left: 3px; | Operational statement participating in the file's runtime behavior.
L2908 |   transition: transform 0.25s ease; | Operational statement participating in the file's runtime behavior.
L2909 | } | Block delimiter controlling scope/structure in this language.
L2910 | | Blank line used for readability and logical separation.
L2911 | .mode-switch-wrap input:checked + .mode-switch-slider { | CSS selector line choosing the elements styled below.
L2912 |   background: #0f53b0; | Operational statement participating in the file's runtime behavior.
L2913 | } | Block delimiter controlling scope/structure in this language.
```

L2914 | | Blank line used for readability and logical separation.

L2915 | .mode-switch-wrap input:checked + .mode-switch-slider::after { | CSS selector line choosing the elements styled below.

L2916 | transform: translateX(24px); | Operational statement participating in the file's runtime behavior.

L2917 | } | Block delimiter controlling scope/structure in this language.

L2918 | | Blank line used for readability and logical separation.

L2919 | .mode-switch-label { | CSS selector line choosing the elements styled below.

L2920 | font-weight: 600; | Operational statement participating in the file's runtime behavior.

L2921 | color: #30557f; | Operational statement participating in the file's runtime behavior.

L2922 | } | Block delimiter controlling scope/structure in this language.

L2923 | | Blank line used for readability and logical separation.

L2924 | .folded-calendar-card { | CSS selector line choosing the elements styled below.

L2925 | position: relative; | Operational statement participating in the file's runtime behavior.

L2926 | overflow: hidden; | Operational statement participating in the file's runtime behavior.

L2927 | } | Block delimiter controlling scope/structure in this language.

L2928 | | Blank line used for readability and logical separation.

L2929 | .folded-calendar-card::after { | CSS selector line choosing the elements styled below.

L2930 | content: ""; | Operational statement participating in the file's runtime behavior.

L2931 | position: absolute; | Operational statement participating in the file's runtime behavior.

L2932 | top: 0; | Operational statement participating in the file's runtime behavior.

L2933 | right: 0; | Operational statement participating in the file's runtime behavior.

L2934 | width: 0; | Operational statement participating in the file's runtime behavior.

L2935 | height: 0; | Operational statement participating in the file's runtime behavior.

L2936 | border-style: solid; | Operational statement participating in the file's runtime behavior.

L2937 | border-width: 0 44px 44px 0; | Operational statement participating in the file's runtime behavior.

L2938 | border-color: transparent #dbe8ff transparent transparent; | Operational statement participating in the file's runtime behavior.

L2939 | } | Block delimiter controlling scope/structure in this language.

L2940 | | Blank line used for readability and logical separation.

L2941 | .calendar-preview { | CSS selector line choosing the elements styled below.

L2942 | border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L2943 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L2944 | background: #fff; | Operational statement participating in the file's runtime behavior.

L2945 | padding: 0.75rem; | Operational statement participating in the file's runtime behavior.

L2946 | } | Block delimiter controlling scope/structure in this language.

L2947 | | Blank line used for readability and logical separation.

L2948 | .calendar-head { | CSS selector line choosing the elements styled below.

L2949 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L2950 | color: #0d3c78; | Operational statement participating in the file's runtime behavior.

L2951 | margin-bottom: 0.55rem; | Operational statement participating in the file's runtime behavior.

L2952 | } | Block delimiter controlling scope/structure in this language.

L2953 | | Blank line used for readability and logical separation.

L2954 | .holiday-calendar { | CSS selector line choosing the elements styled below.

L2955 | display: grid; | Operational statement participating in the file's runtime behavior.

L2956 | gap: 1rem; | Operational statement participating in the file's runtime behavior.

L2957 | } | Block delimiter controlling scope/structure in this language.

L2958 | | Blank line used for readability and logical separation.

L2959 | .holiday-calendar-full .calendar-book { | CSS selector line choosing the elements styled below.

L2960 | max-width: 560px; | Operational statement participating in the file's runtime behavior.

L2961 | margin: 0 auto; | Operational statement participating in the file's runtime behavior.

L2962 | } | Block delimiter controlling scope/structure in this language.

L2963 | | Blank line used for readability and logical separation.

L2964 | .holiday-calendar-dashboard .calendar-book { | CSS selector line choosing the elements styled below.

L2965 | max-width: 520px; | Operational statement participating in the file's runtime behavior.

L2966 | } | Block delimiter controlling scope/structure in this language.

L2967 | | Blank line used for readability and logical separation.

L2968 | .calendar-book { | CSS selector line choosing the elements styled below.

L2969 | position: relative; | Operational statement participating in the file's runtime behavior.

L2970 | overflow: hidden; | Operational statement participating in the file's runtime behavior.

L2971 | border-radius: 24px; | Operational statement participating in the file's runtime behavior.

L2972 | border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L2973 | background: linear-gradient(145deg, #ffffff 0%, #edf7ef 100%); | Operational statement participating in the file's runtime behavior.

L2974 | box-shadow: inset 0 1px 0 rgba(255, 255, 255, 0.85), 0 20px 40px rgba(8, 59, 125, 0.08); | Operational statement participating in the file's runtime behavior.

L2975 | perspective: 1600px; | Operational statement participating in the file's runtime behavior.

L2976 | } | Block delimiter controlling scope/structure in this language.

L2977 | | Blank line used for readability and logical separation.

L2978 | .calendar-watermark { | CSS selector line choosing the elements styled below.

L2979 | display: none; | Operational statement participating in the file's runtime behavior.

L2980 | } | Block delimiter controlling scope/structure in this language.

L2981 | | Blank line used for readability and logical separation.

L2982 | .calendar-watermark img { | CSS selector line choosing the elements styled below.

L2983 | width: min(72%, 300px); | Operational statement participating in the file's runtime behavior.

L2984 | height: auto; | Operational statement participating in the file's runtime behavior.

L2985 | opacity: 0.15; | Operational statement participating in the file's runtime behavior.

L2986 | filter: saturate(0.95) contrast(1.04); | Operational statement participating in the file's runtime behavior.

L2987 | } | Block delimiter controlling scope/structure in this language.

L2988 | | Blank line used for readability and logical separation.

L2989 | .calendar-book::before { | CSS selector line choosing the elements styled below.

L2990 | content: ""; | Operational statement participating in the file's runtime behavior.

L2991 | position: absolute; | Operational statement participating in the file's runtime behavior.

L2992 | top: 0; | Operational statement participating in the file's runtime behavior.

L2993 | bottom: 0; | Operational statement participating in the file's runtime behavior.

L2994 | left: 50%; | Operational statement participating in the file's runtime behavior.

L2995 | width: 1px; | Operational statement participating in the file's runtime behavior.

L2996 | background: linear-gradient(180deg, rgba(15, 83, 176, 0), rgba(15, 83, 176, 0.14), rgba(15, 83, 176, 0)); | Operational statement participating in the file's runtime behavior.

L2997 | pointer-events: none; | Operational statement participating in the file's runtime behavior.

L2998 | } | Block delimiter controlling scope/structure in this language.

L2999 | | Blank line used for readability and logical separation.

L3000 | .calendar-book::after { | CSS selector line choosing the elements styled below.

L3001 | content: ""; | Operational statement participating in the file's runtime behavior.

L3002 | position: absolute; | Operational statement participating in the file's runtime behavior.

L3003 | right: 0; | Operational statement participating in the file's runtime behavior.

L3004 | top: 0; | Operational statement participating in the file's runtime behavior.

L3005 | width: 42px; | Operational statement participating in the file's runtime behavior.

L3006 | height: 42px; | Operational statement participating in the file's runtime behavior.

L3007 | background: linear-gradient(135deg, rgba(15, 83, 176, 0.08), rgba(15, 83, 176, 0)); | Operational statement participating in the file's runtime behavior.

L3008 | clip-path: polygon(100% 0, 0 0, 100% 100%); | Operational statement participating in the file's runtime behavior.

L3009 | pointer-events: none; | Operational statement participating in the file's runtime behavior.

L3010 | } | Block delimiter controlling scope/structure in this language.

L3011 | | Blank line used for readability and logical separation.

L3012 | .calendar-toolbar { | CSS selector line choosing the elements styled below.

L3013 | display: flex; | Operational statement participating in the file's runtime behavior.

L3014 | align-items: center; | Operational statement participating in the file's runtime behavior.

L3015 | justify-content: space-between; | Operational statement participating in the file's runtime behavior.

L3016 | gap: 0.75rem; | Operational statement participating in the file's runtime behavior.

L3017 | padding: 0.75rem 0.75rem 0; | Operational statement participating in the file's runtime behavior.

L3018 | position: relative; | Operational statement participating in the file's runtime behavior.

L3019 | z-index: 1; | Operational statement participating in the file's runtime behavior.

L3020 | } | Block delimiter controlling scope/structure in this language.

L3021 | | Blank line used for readability and logical separation.

L3022 | .calendar-month-label { | CSS selector line choosing the elements styled below.

L3023 | flex: 1; | Operational statement participating in the file's runtime behavior.

L3024 | text-align: center; | Operational statement participating in the file's runtime behavior.

L3025 | font-size: 0.95rem; | Operational statement participating in the file's runtime behavior.

L3026 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L3027 | color: #0d3c78; | Operational statement participating in the file's runtime behavior.

L3028 | letter-spacing: 0.04em; | Operational statement participating in the file's runtime behavior.

L3029 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L3030 | } | Block delimiter controlling scope/structure in this language.

L3031 | | Blank line used for readability and logical separation.

L3032 | .calendar-nav { | CSS selector line choosing the elements styled below.

L3033 | width: 2rem; | Operational statement participating in the file's runtime behavior.

L3034 | height: 2rem; | Operational statement participating in the file's runtime behavior.

L3035 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L3036 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L3037 | align-items: center; | Operational statement participating in the file's runtime behavior.

L3038 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L3039 | padding: 0; | Operational statement participating in the file's runtime behavior.

L3040 | } | Block delimiter controlling scope/structure in this language.

L3041 | | Blank line used for readability and logical separation.

L3042 | .calendar-sheet { | CSS selector line choosing the elements styled below.

L3043 | padding: 0.7rem; | Operational statement participating in the file's runtime behavior.

L3044 | transform-origin: center center; | Operational statement participating in the file's runtime behavior.

L3045 | backface-visibility: hidden; | Operational statement participating in the file's runtime behavior.

L3046 | transform-style: preserve-3d; | Operational statement participating in the file's runtime behavior.

L3047 | position: relative; | Operational statement participating in the file's runtime behavior.

L3048 | z-index: 1; | Operational statement participating in the file's runtime behavior.

L3049 | } | Block delimiter controlling scope/structure in this language.

L3050 | | Blank line used for readability and logical separation.

L3051 | .calendar-sheet.turn-next { | CSS selector line choosing the elements styled below.

L3052 | animation: calendarTurnNext 0.45s ease; | Operational statement participating in the file's runtime behavior.

L3053 | transform-origin: right center; | Operational statement participating in the file's runtime behavior.

L3054 | } | Block delimiter controlling scope/structure in this language.

L3055 | | Blank line used for readability and logical separation.

L3056 | .calendar-sheet.turn-prev { | CSS selector line choosing the elements styled below.

L3057 | animation: calendarTurnPrev 0.45s ease; | Operational statement participating in the file's runtime behavior.

L3058 | transform-origin: left center; | Operational statement participating in the file's runtime behavior.

L3059 | } | Block delimiter controlling scope/structure in this language.

L3060 | | Blank line used for readability and logical separation.

L3061 | .calendar-sheet::before { | CSS selector line choosing the elements styled below.

L3062 | content: ""; | Operational statement participating in the file's runtime behavior.

L3063 | position: absolute; | Operational statement participating in the file's runtime behavior.

L3064 | top: 0.35rem; | Operational statement participating in the file's runtime behavior.

L3065 | bottom: 0.35rem; | Operational statement participating in the file's runtime behavior.

L3066 | width: 18px; | Operational statement participating in the file's runtime behavior.

L3067 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L3068 | pointer-events: none; | Operational statement participating in the file's runtime behavior.

L3069 | opacity: 0; | Operational statement participating in the file's runtime behavior.

L3070 | } | Block delimiter controlling scope/structure in this language.

L3071 | | Blank line used for readability and logical separation.

L3072 | .calendar-sheet::after { | CSS selector line choosing the elements styled below.

L3073 | content: ""; | Operational statement participating in the file's runtime behavior.

L3074 | position: absolute; | Operational statement participating in the file's runtime behavior.

L3075 | inset: 0.25rem; | Operational statement participating in the file's runtime behavior.

L3076 | border-radius: 16px; | Operational statement participating in the file's runtime behavior.

L3077 | pointer-events: none; | Operational statement participating in the file's runtime behavior.

L3078 | opacity: 0; | Operational statement participating in the file's runtime behavior.

L3079 | } | Block delimiter controlling scope/structure in this language.

L3080 | | Blank line used for readability and logical separation.

L3081 | .calendar-sheet.turn-next::before { | CSS selector line choosing the elements styled below.

L3082 | left: 0.15rem; | Operational statement participating in the file's runtime behavior.

L3083 | background: radial-gradient(circle at left center, rgba(8, 59, 125, 0.24), rgba(8, 59, 125, 0)); | Operational statement participating in the file's runtime behavior.

L3084 | animation: calendarBendNext 0.45s ease; | Operational statement participating in the file's runtime behavior.

L3085 | } | Block delimiter controlling scope/structure in this language.

L3086 | | Blank line used for readability and logical separation.

L3087 | .calendar-sheet.turn-prev::before { | CSS selector line choosing the elements styled below.

L3088 | right: 0.15rem; | Operational statement participating in the file's runtime behavior.

L3089 | background: radial-gradient(circle at right center, rgba(8, 59, 125, 0.24), rgba(8, 59, 125, 0)); | Operational statement participating in the file's runtime behavior.

L3090 | animation: calendarBendPrev 0.45s ease; | Operational statement participating in the file's runtime behavior.

L3091 | } | Block delimiter controlling scope/structure in this language.

L3092 | | Blank line used for readability and logical separation.

L3093 | .calendar-sheet.turn-next::after, | CSS selector line choosing the elements styled below.

L3094 | .calendar-sheet.turn-prev::after { | CSS selector line choosing the elements styled below.

L3095 | animation: calendarFaceSheen 0.45s ease; | Operational statement participating in the file's runtime behavior.

L3096 | } | Block delimiter controlling scope/structure in this language.

L3097 | | Blank line used for readability and logical separation.

L3098 | .calendar-grid { | CSS selector line choosing the elements styled below.

L3099 | display: grid; | Operational statement participating in the file's runtime behavior.

L3100 | grid-template-columns: repeat(7, minmax(0, 1fr)); | Operational statement participating in the file's runtime behavior.

L3101 | gap: 0.28rem; | Operational statement participating in the file's runtime behavior.

L3102 | } | Block delimiter controlling scope/structure in this language.

L3103 | | Blank line used for readability and logical separation.

L3104 | .calendar-cell { | CSS selector line choosing the elements styled below.

L3105 | min-height: 3.35rem; | Operational statement participating in the file's runtime behavior.

L3106 | padding: 0.35rem 0.3rem; | Operational statement participating in the file's runtime behavior.

L3107 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L3108 | background: #f3f8ff; | Operational statement participating in the file's runtime behavior.

L3109 | border: 1px solid rgba(15, 83, 176, 0.08); | Operational statement participating in the file's runtime behavior.

L3110 | display: flex; | Operational statement participating in the file's runtime behavior.

L3111 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L3112 | gap: 0.28rem; | Operational statement participating in the file's runtime behavior.

L3113 | transition: transform 0.2s ease, box-shadow 0.2s ease, border-color 0.2s ease; | Operational statement participating in the file's runtime behavior.

L3114 | } | Block delimiter controlling scope/structure in this language.

L3115 | | Blank line used for readability and logical separation.

L3116 | .calendar-cell:hover { | CSS selector line choosing the elements styled below.

L3117 | transform: translateY(-2px); | Operational statement participating in the file's runtime behavior.

L3118 | box-shadow: 0 10px 18px rgba(8, 59, 125, 0.08); | Operational statement participating in the file's runtime behavior.

L3119 | } | Block delimiter controlling scope/structure in this language.

L3120 | | Blank line used for readability and logical separation.

L3121 | .calendar-day { | CSS selector line choosing the elements styled below.

L3122 | min-height: 0; | Operational statement participating in the file's runtime behavior.

L3123 | text-align: center; | Operational statement participating in the file's runtime behavior.

L3124 | font-size: 0.64rem; | Operational statement participating in the file's runtime behavior.

L3125 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L3126 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L3127 | background: #e7f0ff; | Operational statement participating in the file's runtime behavior.

L3128 | color: #174b8a; | Operational statement participating in the file's runtime behavior.

L3129 | text-transform: uppercase; | Operational statement participating in the file's runtime behavior.

L3130 | letter-spacing: 0.04em; | Operational statement participating in the file's runtime behavior.

L3131 | } | Block delimiter controlling scope/structure in this language.

L3132 | | Blank line used for readability and logical separation.

L3133 | .calendar-empty { | CSS selector line choosing the elements styled below.

L3134 | background: transparent; | Operational statement participating in the file's runtime behavior.

L3135 | border-style: dashed; | Operational statement participating in the file's runtime behavior.

L3136 | box-shadow: none; | Operational statement participating in the file's runtime behavior.

L3137 | } | Block delimiter controlling scope/structure in this language.

L3138 | | Blank line used for readability and logical separation.

L3139 | .calendar-date { | CSS selector line choosing the elements styled below.

L3140 | color: #17324e; | Operational statement participating in the file's runtime behavior.

L3141 | } | Block delimiter controlling scope/structure in this language.

L3142 | | Blank line used for readability and logical separation.

L3143 | .calendar-date-number { | CSS selector line choosing the elements styled below.

L3144 | font-size: 0.93rem; | Operational statement participating in the file's runtime behavior.

L3145 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L3146 | line-height: 1; | Operational statement participating in the file's runtime behavior.

L3147 | } | Block delimiter controlling scope/structure in this language.

L3148 | | Blank line used for readability and logical separation.

L3149 | .calendar-cell.calendar-today { | CSS selector line choosing the elements styled below.

L3150 | border-color: rgba(15, 83, 176, 0.35); | Operational statement participating in the file's runtime behavior.

L3151 | box-shadow: 0 0 2px rgba(15, 83, 176, 0.12); | Operational statement participating in the file's runtime behavior.

L3152 | } | Block delimiter controlling scope/structure in this language.

L3153 | | Blank line used for readability and logical separation.

L3154 | .calendar-cell.calendar-today .calendar-date-number { | CSS selector line choosing the elements styled below.

L3155 | color: #0f53b0; | Operational statement participating in the file's runtime behavior.

L3156 | } | Block delimiter controlling scope/structure in this language.

L3157 | | Blank line used for readability and logical separation.

L3158 | .calendar-cell.calendar-holiday { | CSS selector line choosing the elements styled below.

L3159 | background: linear-gradient(160deg, #e7f8e8 0%, #d6f1d9 100%); | Operational statement participating in the file's runtime behavior.

L3160 | border-color: rgba(78, 154, 97, 0.35); | Operational statement participating in the file's runtime behavior.

L3161 | } | Block delimiter controlling scope/structure in this language.

L3162 | | Blank line used for readability and logical separation.

L3163 | .calendar-holiday-list { | CSS selector line choosing the elements styled below.

L3164 | display: grid; | Operational statement participating in the file's runtime behavior.

L3165 | gap: 0.6rem; | Operational statement participating in the file's runtime behavior.

L3166 | } | Block delimiter controlling scope/structure in this language.

L3167 | | Blank line used for readability and logical separation.

L3168 | .holiday-list-item { | CSS selector line choosing the elements styled below.

L3169 | display: flex; | Operational statement participating in the file's runtime behavior.

L3170 | align-items: center; | Operational statement participating in the file's runtime behavior.

L3171 | justify-content: flex-start; | Operational statement participating in the file's runtime behavior.

L3172 | gap: 0.25rem; | Operational statement participating in the file's runtime behavior.

L3173 | padding: 0.8rem 0.95rem; | Operational statement participating in the file's runtime behavior.

L3174 | border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L3175 | border-radius: 14px; | Operational statement participating in the file's runtime behavior.

L3176 | background: #fff; | Operational statement participating in the file's runtime behavior.

L3177 | text-align: left; | Operational statement participating in the file's runtime behavior.

L3178 | } | Block delimiter controlling scope/structure in this language.

L3179 | | Blank line used for readability and logical separation.

L3180 | .holiday-list-item span, | CSS selector line choosing the elements styled below.

L3181 | .holiday-day, | CSS selector line choosing the elements styled below.

L3182 | .holiday-dash { | CSS selector line choosing the elements styled below.

L3183 | color: #2f6f3d; | Operational statement participating in the file's runtime behavior.

L3184 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L3185 | } | Block delimiter controlling scope/structure in this language.

L3186 | | Blank line used for readability and logical separation.

L3187 | .holiday-list-item strong, | CSS selector line choosing the elements styled below.

L3188 | .holiday-name { | CSS selector line choosing the elements styled below.

L3189 | color: #17324e; | Operational statement participating in the file's runtime behavior.

L3190 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L3191 | } | Block delimiter controlling scope/structure in this language.

L3192 | | Blank line used for readability and logical separation.

L3193 | .holiday-dash { | CSS selector line choosing the elements styled below.

L3194 | margin: 0 0.1rem; | Operational statement participating in the file's runtime behavior.

L3195 | } | Block delimiter controlling scope/structure in this language.

L3196 | | Blank line used for readability and logical separation.

L3197 | .holiday-calendar-dashboard .calendar-cell { | CSS selector line choosing the elements styled below.

L3198 | min-height: 3rem; | Operational statement participating in the file's runtime behavior.

L3199 | } | Block delimiter controlling scope/structure in this language.

L3200 | | Blank line used for readability and logical separation.

L3201 | .holiday-calendar-dashboard .calendar-grid { | CSS selector line choosing the elements styled below.

L3202 | gap: 0.2rem; | Operational statement participating in the file's runtime behavior.

L3203 | } | Block delimiter controlling scope/structure in this language.

L3204 | | Blank line used for readability and logical separation.

L3205 | .holiday-calendar-dashboard .calendar-cell { | CSS selector line choosing the elements styled below.

L3206 | min-height: 2.55rem; | Operational statement participating in the file's runtime behavior.

L3207 | padding: 0.28rem 0.2rem; | Operational statement participating in the file's runtime behavior.

L3208 | border-radius: 10px; | Operational statement participating in the file's runtime behavior.

L3209 | } | Block delimiter controlling scope/structure in this language.

L3210 | | Blank line used for readability and logical separation.

L3211 | .holiday-calendar-dashboard .calendar-day { | CSS selector line choosing the elements styled below.

L3212 | font-size: 0.58rem; | Operational statement participating in the file's runtime behavior.

L3213 | } | Block delimiter controlling scope/structure in this language.

L3214 | | Blank line used for readability and logical separation.

L3215 | .holiday-calendar-dashboard .calendar-date-number { | CSS selector line choosing the elements styled below.

L3216 | font-size: 0.8rem; | Operational statement participating in the file's runtime behavior.

L3217 | } | Block delimiter controlling scope/structure in this language.

L3218 | | Blank line used for readability and logical separation.

L3219 | .holiday-calendar-dashboard .calendar-toolbar { | CSS selector line choosing the elements styled below.

L3220 | padding: 0.55rem 0.55rem 0; | Operational statement participating in the file's runtime behavior.

L3221 | } | Block delimiter controlling scope/structure in this language.

L3222 | | Blank line used for readability and logical separation.

L3223 | .holiday-calendar-dashboard .calendar-nav { | CSS selector line choosing the elements styled below.

L3224 | width: 1.7rem; | Operational statement participating in the file's runtime behavior.

L3225 | height: 1.7rem; | Operational statement participating in the file's runtime behavior.

L3226 | } | Block delimiter controlling scope/structure in this language.

L3227 | | Blank line used for readability and logical separation.

L3228 | .dashboard-calendar-card .calendar-month-label { | CSS selector line choosing the elements styled below.

L3229 | font-size: 0.82rem; | Operational statement participating in the file's runtime behavior.

L3230 | } | Block delimiter controlling scope/structure in this language.

L3231 | | Blank line used for readability and logical separation.

L3232 | .dashboard-calendar-card .calendar-sheet { | CSS selector line choosing the elements styled below.

L3233 | padding: 0.5rem; | Operational statement participating in the file's runtime behavior.

L3234 | } | Block delimiter controlling scope/structure in this language.

L3235 | | Blank line used for readability and logical separation.

L3236 | .dashboard-calendar-card .calendar-holiday-list { | CSS selector line choosing the elements styled below.

L3237 | gap: 0.45rem; | Operational statement participating in the file's runtime behavior.

L3238 | } | Block delimiter controlling scope/structure in this language.

L3239 | | Blank line used for readability and logical separation.

L3240 | .dashboard-calendar-card .holiday-list-item { | CSS selector line choosing the elements styled below.

L3241 | padding: 0.6rem 0.7rem; | Operational statement participating in the file's runtime behavior.

L3242 | border-radius: 11px; | Operational statement participating in the file's runtime behavior.

L3243 | } | Block delimiter controlling scope/structure in this language.

```

L3244 | | Blank line used for readability and logical separation.
L3245 | .dashboard-calendar-card .card-body { | CSS selector line choosing the elements styled below.
L3246 | padding: 1.4rem; | Operational statement participating in the file's runtime behavior.
L3247 | } | Block delimiter controlling scope/structure in this language.
L3248 | | Blank line used for readability and logical separation.
L3249 | .holiday-popup-backdrop { | CSS selector line choosing the elements styled below.
L3250 | position: fixed; | Operational statement participating in the file's runtime behavior.
L3251 | inset: 0; | Operational statement participating in the file's runtime behavior.
L3252 | display: none; | Operational statement participating in the file's runtime behavior.
L3253 | align-items: center; | Operational statement participating in the file's runtime behavior.
L3254 | justify-content: center; | Operational statement participating in the file's runtime behavior.
L3255 | padding: 1.25rem; | Operational statement participating in the file's runtime behavior.
L3256 | background: rgba(7, 18, 29, 0.45); | Operational statement participating in the file's runtime behavior.
L3257 | backdrop-filter: blur(6px); | Operational statement participating in the file's runtime behavior.
L3258 | z-index: 1080; | Operational statement participating in the file's runtime behavior.
L3259 | } | Block delimiter controlling scope/structure in this language.
L3260 | | Blank line used for readability and logical separation.
L3261 | .holiday-popup-backdrop.show { | CSS selector line choosing the elements styled below.
L3262 | display: flex; | Operational statement participating in the file's runtime behavior.
L3263 | } | Block delimiter controlling scope/structure in this language.
L3264 | | Blank line used for readability and logical separation.
L3265 | .holiday-popup-card { | CSS selector line choosing the elements styled below.
L3266 | width: min(100%, 420px); | Operational statement participating in the file's runtime behavior.
L3267 | border-radius: 24px; | Operational statement participating in the file's runtime behavior.
L3268 | background: linear-gradient(160deg, #ffffff 0%, #eef8f0 100%); | Operational statement participating in the file's runtime behavior.
L3269 | border: 1px solid rgba(78, 154, 97, 0.28); | Operational statement participating in the file's runtime behavior.
L3270 | box-shadow: 0 24px 60px rgba(7, 33, 59, 0.2); | Operational statement participating in the file's runtime behavior.
L3271 | padding: 1.4rem; | Operational statement participating in the file's runtime behavior.
L3272 | text-align: center; | Operational statement participating in the file's runtime behavior.
L3273 | } | Block delimiter controlling scope/structure in this language.
L3274 | | Blank line used for readability and logical separation.
L3275 | .holiday-popup-icon { | CSS selector line choosing the elements styled below.
L3276 | width: 60px; | Operational statement participating in the file's runtime behavior.
L3277 | height: 60px; | Operational statement participating in the file's runtime behavior.
L3278 | border-radius: 50%; | Operational statement participating in the file's runtime behavior.
L3279 | display: inline-flex; | Operational statement participating in the file's runtime behavior.
L3280 | align-items: center; | Operational statement participating in the file's runtime behavior.
L3281 | justify-content: center; | Operational statement participating in the file's runtime behavior.
L3282 | margin: 0 auto 0.8rem; | Operational statement participating in the file's runtime behavior.
L3283 | background: #e7f8e8; | Operational statement participating in the file's runtime behavior.
L3284 | color: #2f6f3d; | Operational statement participating in the file's runtime behavior.
L3285 | font-size: 1.55rem; | Operational statement participating in the file's runtime behavior.
L3286 | } | Block delimiter controlling scope/structure in this language.
L3287 | | Blank line used for readability and logical separation.
L3288 | @keyframes calendarTurnNext { | Decorator line that modifies the behavior of the definition below.
L3289 | 0% { | Block delimiter controlling scope/structure in this language.
L3290 | opacity: 0.22; | Operational statement participating in the file's runtime behavior.
L3291 | transform: perspective(1500px) rotateY(-42deg) translateX(28px) scale(0.97); | Operational statement participating in the file's runtime behavior.
L3292 | } | Block delimiter controlling scope/structure in this language.
L3293 | 45% { | Block delimiter controlling scope/structure in this language.
L3294 | opacity: 0.55; | Operational statement participating in the file's runtime behavior.
L3295 | transform: perspective(1500px) rotateY(-18deg) translateX(10px) scale(0.985); | Operational statement participating in the file's runtime behavior.
L3296 | } | Block delimiter controlling scope/structure in this language.
L3297 | 100% { | Block delimiter controlling scope/structure in this language.
L3298 | opacity: 1; | Operational statement participating in the file's runtime behavior.

```

L3299 | transform: perspective(1500px) rotateY(0deg) translateX(0) scale(1); | Operational statement participating in the file's runtime behavior.

L3300 | } | Block delimiter controlling scope/structure in this language.

L3301 | } | Block delimiter controlling scope/structure in this language.

L3302 | | Blank line used for readability and logical separation.

L3303 | @keyframes calendarTurnPrev { | Decorator line that modifies the behavior of the definition below.

L3304 | 0% { | Block delimiter controlling scope/structure in this language.

L3305 | opacity: 0.22; | Operational statement participating in the file's runtime behavior.

L3306 | transform: perspective(1500px) rotateY(42deg) translateX(-28px) scale(0.97); | Operational statement participating in the file's runtime behavior.

L3307 | } | Block delimiter controlling scope/structure in this language.

L3308 | 45% { | Block delimiter controlling scope/structure in this language.

L3309 | opacity: 0.55; | Operational statement participating in the file's runtime behavior.

L3310 | transform: perspective(1500px) rotateY(18deg) translateX(-10px) scale(0.985); | Operational statement participating in the file's runtime behavior.

L3311 | } | Block delimiter controlling scope/structure in this language.

L3312 | 100% { | Block delimiter controlling scope/structure in this language.

L3313 | opacity: 1; | Operational statement participating in the file's runtime behavior.

L3314 | transform: perspective(1500px) rotateY(0deg) translateX(0) scale(1); | Operational statement participating in the file's runtime behavior.

L3315 | } | Block delimiter controlling scope/structure in this language.

L3316 | } | Block delimiter controlling scope/structure in this language.

L3317 | | Blank line used for readability and logical separation.

L3318 | @keyframes calendarBendNext { | Decorator line that modifies the behavior of the definition below.

L3319 | 0% { | Block delimiter controlling scope/structure in this language.

L3320 | opacity: 0; | Operational statement participating in the file's runtime behavior.

L3321 | transform: scaleX(0.4); | Operational statement participating in the file's runtime behavior.

L3322 | } | Block delimiter controlling scope/structure in this language.

L3323 | 35% { | Block delimiter controlling scope/structure in this language.

L3324 | opacity: 1; | Operational statement participating in the file's runtime behavior.

L3325 | transform: scaleX(1.15); | Operational statement participating in the file's runtime behavior.

L3326 | } | Block delimiter controlling scope/structure in this language.

L3327 | 100% { | Block delimiter controlling scope/structure in this language.

L3328 | opacity: 0; | Operational statement participating in the file's runtime behavior.

L3329 | transform: scaleX(0.5); | Operational statement participating in the file's runtime behavior.

L3330 | } | Block delimiter controlling scope/structure in this language.

L3331 | } | Block delimiter controlling scope/structure in this language.

L3332 | | Blank line used for readability and logical separation.

L3333 | @keyframes calendarBendPrev { | Decorator line that modifies the behavior of the definition below.

L3334 | 0% { | Block delimiter controlling scope/structure in this language.

L3335 | opacity: 0; | Operational statement participating in the file's runtime behavior.

L3336 | transform: scaleX(0.4); | Operational statement participating in the file's runtime behavior.

L3337 | } | Block delimiter controlling scope/structure in this language.

L3338 | 35% { | Block delimiter controlling scope/structure in this language.

L3339 | opacity: 1; | Operational statement participating in the file's runtime behavior.

L3340 | transform: scaleX(1.15); | Operational statement participating in the file's runtime behavior.

L3341 | } | Block delimiter controlling scope/structure in this language.

L3342 | 100% { | Block delimiter controlling scope/structure in this language.

L3343 | opacity: 0; | Operational statement participating in the file's runtime behavior.

L3344 | transform: scaleX(0.5); | Operational statement participating in the file's runtime behavior.

L3345 | } | Block delimiter controlling scope/structure in this language.

L3346 | } | Block delimiter controlling scope/structure in this language.

L3347 | | Blank line used for readability and logical separation.

L3348 | @keyframes calendarFaceSheen { | Decorator line that modifies the behavior of the definition below.

L3349 | 0% { | Block delimiter controlling scope/structure in this language.

L3350 | opacity: 0; | Operational statement participating in the file's runtime behavior.

L3351 | background: linear-gradient(120deg, rgba(255, 255, 255, 0), rgba(255, 255, 255, 0)); | Operational statement participating in the file's runtime behavior.

L3352 | } | Block delimiter controlling scope/structure in this language.

L3353 | 40% { | Block delimiter controlling scope/structure in this language.

L3354 | opacity: 1; | Operational statement participating in the file's runtime behavior.

L3355 | background: linear-gradient(120deg, rgba(255, 255, 255, 0.16), rgba(255, 255, 255, 0)); | Operational statement participating in the file's runtime behavior.

L3356 | } | Block delimiter controlling scope/structure in this language.

L3357 | 100% { | Block delimiter controlling scope/structure in this language.

L3358 | opacity: 0; | Operational statement participating in the file's runtime behavior.

L3359 | background: linear-gradient(120deg, rgba(255, 255, 255, 0), rgba(255, 255, 255, 0)); | Operational statement participating in the file's runtime behavior.

L3360 | } | Block delimiter controlling scope/structure in this language.

L3361 | } | Block delimiter controlling scope/structure in this language.

L3362 | | Blank line used for readability and logical separation.

L3363 | .notification-settings-card .notification-card-stat { | CSS selector line choosing the elements styled below.

L3364 | border: 1px dashed #bfd7fb; | Operational statement participating in the file's runtime behavior.

L3365 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L3366 | padding: 0.75rem; | Operational statement participating in the file's runtime behavior.

L3367 | background: #eef6ff; | Operational statement participating in the file's runtime behavior.

L3368 | display: flex; | Operational statement participating in the file's runtime behavior.

L3369 | justify-content: space-between; | Operational statement participating in the file's runtime behavior.

L3370 | align-items: center; | Operational statement participating in the file's runtime behavior.

L3371 | } | Block delimiter controlling scope/structure in this language.

L3372 | | Blank line used for readability and logical separation.

L3373 | .notification-settings-card .stat-label { | CSS selector line choosing the elements styled below.

L3374 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L3375 | color: #1d4f8c; | Operational statement participating in the file's runtime behavior.

L3376 | } | Block delimiter controlling scope/structure in this language.

L3377 | | Blank line used for readability and logical separation.

L3378 | .notification-settings-card .stat-value { | CSS selector line choosing the elements styled below.

L3379 | font-size: 1.2rem; | Operational statement participating in the file's runtime behavior.

L3380 | font-weight: 900; | Operational statement participating in the file's runtime behavior.

L3381 | color: #0b3e7c; | Operational statement participating in the file's runtime behavior.

L3382 | } | Block delimiter controlling scope/structure in this language.

L3383 | | Blank line used for readability and logical separation.

L3384 | .sla-settings-card { | CSS selector line choosing the elements styled below.

L3385 | border-color: #cfe0ff; | Operational statement participating in the file's runtime behavior.

L3386 | } | Block delimiter controlling scope/structure in this language.

L3387 | | Blank line used for readability and logical separation.

L3388 | .sla-policy-status-wrap { | CSS selector line choosing the elements styled below.

L3389 | min-width: 210px; | Operational statement participating in the file's runtime behavior.

L3390 | } | Block delimiter controlling scope/structure in this language.

L3391 | | Blank line used for readability and logical separation.

L3392 | .sla-policy-panel { | CSS selector line choosing the elements styled below.

L3393 | border: 1px solid #d7e6ff; | Operational statement participating in the file's runtime behavior.

L3394 | border-radius: 16px; | Operational statement participating in the file's runtime behavior.

L3395 | background: linear-gradient(145deg, #f4f9ff 0%, #ffffff 100%); | Operational statement participating in the file's runtime behavior.

L3396 | padding: 1rem; | Operational statement participating in the file's runtime behavior.

L3397 | } | Block delimiter controlling scope/structure in this language.

L3398 | | Blank line used for readability and logical separation.

L3399 | .sla-policy-stats { | CSS selector line choosing the elements styled below.

L3400 | display: grid; | Operational statement participating in the file's runtime behavior.

L3401 | grid-template-columns: repeat(3, minmax(0, 1fr)); | Operational statement participating in the file's runtime behavior.

L3402 | gap: 0.75rem; | Operational statement participating in the file's runtime behavior.

L3403 | } | Block delimiter controlling scope/structure in this language.

L3404 | | Blank line used for readability and logical separation.

L3405 | .sla-policy-stat { | CSS selector line choosing the elements styled below.

L3406 | border: 1px dashed #bdd6ff; | Operational statement participating in the file's runtime behavior.

L3407 | border-radius: 14px; | Operational statement participating in the file's runtime behavior.

L3408 | background: #eef5ff; | Operational statement participating in the file's runtime behavior.

L3409 | padding: 0.8rem; | Operational statement participating in the file's runtime behavior.

L3410 | text-align: center; | Operational statement participating in the file's runtime behavior.

L3411 | } | Block delimiter controlling scope/structure in this language.

L3412 | | Blank line used for readability and logical separation.

L3413 | .sla-policy-stat-label { | CSS selector line choosing the elements styled below.

L3414 | display: block; | Operational statement participating in the file's runtime behavior.

L3415 | font-size: 0.76rem; | Operational statement participating in the file's runtime behavior.

L3416 | color: #4a678d; | Operational statement participating in the file's runtime behavior.

L3417 | margin-bottom: 0.25rem; | Operational statement participating in the file's runtime behavior.

L3418 | } | Block delimiter controlling scope/structure in this language.

L3419 | | Blank line used for readability and logical separation.

L3420 | .sla-policy-list { | CSS selector line choosing the elements styled below.

L3421 | padding-left: 1.1rem; | Operational statement participating in the file's runtime behavior.

L3422 | color: #25466f; | Operational statement participating in the file's runtime behavior.

L3423 | } | Block delimiter controlling scope/structure in this language.

L3424 | | Blank line used for readability and logical separation.

L3425 | .sla-policy-list li + li { | CSS selector line choosing the elements styled below.

L3426 | margin-top: 0.45rem; | Operational statement participating in the file's runtime behavior.

L3427 | } | Block delimiter controlling scope/structure in this language.

L3428 | | Blank line used for readability and logical separation.

L3429 | .sla-agreement-box { | CSS selector line choosing the elements styled below.

L3430 | display: flex; | Operational statement participating in the file's runtime behavior.

L3431 | gap: 0.65rem; | Operational statement participating in the file's runtime behavior.

L3432 | align-items: flex-start; | Operational statement participating in the file's runtime behavior.

L3433 | padding: 0.85rem 0.95rem; | Operational statement participating in the file's runtime behavior.

L3434 | border: 1px solid #d9e7ff; | Operational statement participating in the file's runtime behavior.

L3435 | border-radius: 14px; | Operational statement participating in the file's runtime behavior.

L3436 | background: #f7fbff; | Operational statement participating in the file's runtime behavior.

L3437 | color: #22456d; | Operational statement participating in the file's runtime behavior.

L3438 | font-weight: 500; | Operational statement participating in the file's runtime behavior.

L3439 | } | Block delimiter controlling scope/structure in this language.

L3440 | | Blank line used for readability and logical separation.

L3441 | .sla-agreement-box input { | CSS selector line choosing the elements styled below.

L3442 | margin-top: 0.2rem; | Operational statement participating in the file's runtime behavior.

L3443 | } | Block delimiter controlling scope/structure in this language.

L3444 | | Blank line used for readability and logical separation.

L3445 | .sla-policy-summary-card .card-body { | CSS selector line choosing the elements styled below.

L3446 | min-height: 132px; | Operational statement participating in the file's runtime behavior.

L3447 | } | Block delimiter controlling scope/structure in this language.

L3448 | | Blank line used for readability and logical separation.

L3449 | body[data-theme="dark"] .settings-card, | Assignment statement storing or updating program state.

L3450 | body[data-theme="dark"] .calendar-preview, | Assignment statement storing or updating program state.

L3451 | body[data-theme="dark"] .calendar-cell, | Assignment statement storing or updating program state.

L3452 | body[data-theme="dark"] .notification-settings-card .notification-card-stat, | Assignment statement storing or updating program state.

L3453 | body[data-theme="dark"] .sla-policy-panel, | Assignment statement storing or updating program state.

L3454 | body[data-theme="dark"] .sla-policy-stat, | Assignment statement storing or updating program state.

L3455 | body[data-theme="dark"] .sla-agreement-box, | Assignment statement storing or updating program state.

L3456 | body[data-theme="dark"] .contact-escalation, | Assignment statement storing or updating program state.

L3457 | body[data-theme="dark"] .emergency-contact-card, | Assignment statement storing or updating program state.

L3458 | body[data-theme="dark"] .notification-bell, | Assignment statement storing or updating program state.

L3459 | body[data-theme="dark"] .notification-item { | Assignment statement storing or updating program state.

L3460 | background: #1a2a41; | Operational statement participating in the file's runtime behavior.

L3461 | border-color: #31486b; | Operational statement participating in the file's runtime behavior.

L3462 | color: #e8eef8; | Operational statement participating in the file's runtime behavior.

L3463 | } | Block delimiter controlling scope/structure in this language.

L3464 | | Blank line used for readability and logical separation.

L3465 | body[data-theme="dark"] .calendar-day, | Assignment statement storing or updating program state.

L3466 | body[data-theme="dark"] .mode-switch-label, | Assignment statement storing or updating program state.

L3467 | body[data-theme="dark"] .settings-card-title, | Assignment statement storing or updating program state.

L3468 | body[data-theme="dark"] .notification-settings-card .stat-label, | Assignment statement storing or updating program state.

L3469 | body[data-theme="dark"] .notification-settings-card .stat-value, | Assignment statement storing or updating program state.

L3470 | body[data-theme="dark"] .sla-policy-stat-label, | Assignment statement storing or updating program state.

L3471 | body[data-theme="dark"] .sla-policy-list, | Assignment statement storing or updating program state.

L3472 | body[data-theme="dark"] .calendar-head, | Assignment statement storing or updating program state.

L3473 | body[data-theme="dark"] .contact-name, | Assignment statement storing or updating program state.

L3474 | body[data-theme="dark"] .contact-phone a { | Assignment statement storing or updating program state.

L3475 | color: #d8e8ff; | Operational statement participating in the file's runtime behavior.

L3476 | } | Block delimiter controlling scope/structure in this language.

L3477 | | Blank line used for readability and logical separation.

L3478 | @media (max-width: 767.98px) { | Decorator line that modifies the behavior of the definition below.

L3479 | .sla-policy-stats { | CSS selector line choosing the elements styled below.

L3480 | grid-template-columns: 1fr; | Operational statement participating in the file's runtime behavior.

L3481 | } | Block delimiter controlling scope/structure in this language.

L3482 | } | Block delimiter controlling scope/structure in this language.

L3483 | | Blank line used for readability and logical separation.

L3484 | .emergency-grid { | CSS selector line choosing the elements styled below.

L3485 | margin-top: 0.25rem; | Operational statement participating in the file's runtime behavior.

L3486 | } | Block delimiter controlling scope/structure in this language.

L3487 | | Blank line used for readability and logical separation.

L3488 | | Blank line used for readability and logical separation.

L3489 | body[data-theme="dark"] .calendar-book, | Assignment statement storing or updating program state.

L3490 | body[data-theme="dark"] .holiday-list-item, | Assignment statement storing or updating program state.

L3491 | body[data-theme="dark"] .holiday-popup-card { | Assignment statement storing or updating program state.

L3492 | background: linear-gradient(145deg, #1a2a41 0%, #1b3a2b 100%); | Operational statement participating in the file's runtime behavior.

L3493 | border-color: #31486b; | Operational statement participating in the file's runtime behavior.

L3494 | color: #e8eef8; | Operational statement participating in the file's runtime behavior.

L3495 | } | Block delimiter controlling scope/structure in this language.

L3496 | | Blank line used for readability and logical separation.

L3497 | body[data-theme="dark"] .calendar-watermark img { | Assignment statement storing or updating program state.

L3498 | opacity: 0.2; | Operational statement participating in the file's runtime behavior.

L3499 | filter: brightness(1.2) saturate(0.85) contrast(1.06); | Operational statement participating in the file's runtime behavior.

L3500 | } | Block delimiter controlling scope/structure in this language.

L3501 | | Blank line used for readability and logical separation.

L3502 | body[data-theme="dark"] .calendar-book::before { | Assignment statement storing or updating program state.

L3503 | background: linear-gradient(180deg, rgba(216, 232, 255, 0), rgba(216, 232, 255, 0.18), rgba(216, 232, 255, 0)); | Operational statement participating in the file's runtime behavior.

L3504 | } | Block delimiter controlling scope/structure in this language.

L3505 | | Blank line used for readability and logical separation.

L3506 | body[data-theme="dark"] .calendar-empty { | Assignment statement storing or updating program state.

L3507 | background: transparent; | Operational statement participating in the file's runtime behavior.

L3508 | } | Block delimiter controlling scope/structure in this language.

L3509 | | Blank line used for readability and logical separation.

L3510 | body[data-theme="dark"] .calendar-cell.calendar-holiday { | Assignment statement storing or updating program state.

L3511 | background: linear-gradient(160deg, #214b2b 0%, #2a5e37 100%); | Operational statement participating in the file's runtime behavior.

L3512 | border-color: rgba(138, 211, 156, 0.32); | Operational statement participating in the file's runtime behavior.

L3513 | } | Block delimiter controlling scope/structure in this language.

L3514 | | Blank line used for readability and logical separation.

L3515 | body[data-theme="dark"] .holiday-list-item span, | Assignment statement storing or updating program state.

L3516 | body[data-theme="dark"] .holiday-popup-icon { | Assignment statement storing or updating program state.

L3517 | color: #a9ecb7; | Operational statement participating in the file's runtime behavior.

L3518 | } | Block delimiter controlling scope/structure in this language.

L3519 | | Blank line used for readability and logical separation.

L3520 | body[data-theme="dark"] .holiday-popup-icon { | Assignment statement storing or updating program state.

L3521 | background: rgba(169, 236, 183, 0.14); | Operational statement participating in the file's runtime behavior.

L3522 | } | Block delimiter controlling scope/structure in this language.

L3523 | .emergency-contact-card { | CSS selector line choosing the elements styled below.

L3524 | border: 1px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L3525 | border-radius: 18px; | Operational statement participating in the file's runtime behavior.

L3526 | box-shadow: 0 14px 28px rgba(6, 62, 130, 0.08); | Operational statement participating in the file's runtime behavior.

L3527 | background: linear-gradient(145deg, #f8fbff 0%, #ffffff 100%); | Operational statement participating in the file's runtime behavior.

L3528 | } | Block delimiter controlling scope/structure in this language.

L3529 | | Blank line used for readability and logical separation.

L3530 | .contact-name { | CSS selector line choosing the elements styled below.

L3531 | margin-bottom: 0.25rem; | Operational statement participating in the file's runtime behavior.

L3532 | color: #0b3f80; | Operational statement participating in the file's runtime behavior.

L3533 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L3534 | } | Block delimiter controlling scope/structure in this language.

L3535 | | Blank line used for readability and logical separation.

L3536 | .contact-role { | CSS selector line choosing the elements styled below.

L3537 | margin-bottom: 0.8rem; | Operational statement participating in the file's runtime behavior.

L3538 | color: #406487; | Operational statement participating in the file's runtime behavior.

L3539 | font-weight: 600; | Operational statement participating in the file's runtime behavior.

L3540 | } | Block delimiter controlling scope/structure in this language.

L3541 | | Blank line used for readability and logical separation.

L3542 | .contact-phone { | CSS selector line choosing the elements styled below.

L3543 | display: flex; | Operational statement participating in the file's runtime behavior.

L3544 | align-items: center; | Operational statement participating in the file's runtime behavior.

L3545 | gap: 0.5rem; | Operational statement participating in the file's runtime behavior.

L3546 | margin-bottom: 1rem; | Operational statement participating in the file's runtime behavior.

L3547 | font-weight: 700; | Operational statement participating in the file's runtime behavior.

L3548 | } | Block delimiter controlling scope/structure in this language.

L3549 | | Blank line used for readability and logical separation.

L3550 | .contact-phone a { | CSS selector line choosing the elements styled below.

L3551 | color: #0f53b0; | Operational statement participating in the file's runtime behavior.

L3552 | text-decoration: none; | Operational statement participating in the file's runtime behavior.

L3553 | } | Block delimiter controlling scope/structure in this language.

L3554 | | Blank line used for readability and logical separation.

L3555 | .contact-escalation { | CSS selector line choosing the elements styled below.

L3556 | border: 1px dashed #bdd7ff; | Operational statement participating in the file's runtime behavior.

L3557 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L3558 | background: #eef6ff; | Operational statement participating in the file's runtime behavior.

L3559 | padding: 0.75rem; | Operational statement participating in the file's runtime behavior.

L3560 | } | Block delimiter controlling scope/structure in this language.

L3561 | | Blank line used for readability and logical separation.

L3562 | .contact-escalation h6 { | CSS selector line choosing the elements styled below.

L3563 | margin-bottom: 0.35rem; | Operational statement participating in the file's runtime behavior.

L3564 | color: #0f3f7a; | Operational statement participating in the file's runtime behavior.

L3565 | font-weight: 800; | Operational statement participating in the file's runtime behavior.

L3566 | } | Block delimiter controlling scope/structure in this language.

L3567 | | Blank line used for readability and logical separation.

L3568 | .offcanvas { | CSS selector line choosing the elements styled below.

L3569 | max-width: 360px; | Operational statement participating in the file's runtime behavior.

L3570 | } | Block delimiter controlling scope/structure in this language.

L3571 | | Blank line used for readability and logical separation.

L3572 | .menu-logo { | CSS selector line choosing the elements styled below.

L3573 | max-width: 160px; | Operational statement participating in the file's runtime behavior.

L3574 | height: auto; | Operational statement participating in the file's runtime behavior.

L3575 | } | Block delimiter controlling scope/structure in this language.

L3576 | | Blank line used for readability and logical separation.

L3577 | .menu-work-card { | CSS selector line choosing the elements styled below.

L3578 | border-radius: 16px; | Operational statement participating in the file's runtime behavior.

L3579 | background: #f0f3f8; | Operational statement participating in the file's runtime behavior.

L3580 | padding: 1rem; | Operational statement participating in the file's runtime behavior.

L3581 | } | Block delimiter controlling scope/structure in this language.

L3582 | | Blank line used for readability and logical separation.

L3583 | .menu-links { | CSS selector line choosing the elements styled below.

L3584 | display: flex; | Operational statement participating in the file's runtime behavior.

L3585 | flex-direction: column; | Operational statement participating in the file's runtime behavior.

L3586 | gap: 0.25rem; | Operational statement participating in the file's runtime behavior.

L3587 | } | Block delimiter controlling scope/structure in this language.

L3588 | | Blank line used for readability and logical separation.

L3589 | .menu-link { | CSS selector line choosing the elements styled below.

L3590 | display: flex; | Operational statement participating in the file's runtime behavior.

L3591 | align-items: center; | Operational statement participating in the file's runtime behavior.

L3592 | gap: 0.9rem; | Operational statement participating in the file's runtime behavior.

L3593 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L3594 | padding: 0.75rem 0.9rem; | Operational statement participating in the file's runtime behavior.

L3595 | color: #5d6f86; | Operational statement participating in the file's runtime behavior.

L3596 | text-decoration: none; | Operational statement participating in the file's runtime behavior.

L3597 | font-size: 1.05rem; | Operational statement participating in the file's runtime behavior.

L3598 | font-weight: 500; | Operational statement participating in the file's runtime behavior.

L3599 | transition: transform 0.25s ease, box-shadow 0.25s ease, background-color 0.25s ease, color 0.25s ease; | Operational statement participating in the file's runtime behavior.

L3600 | } | Block delimiter controlling scope/structure in this language.

L3601 | | Blank line used for readability and logical separation.

L3602 | .menu-link i { | CSS selector line choosing the elements styled below.

L3603 | font-size: 1.35rem; | Operational statement participating in the file's runtime behavior.

L3604 | } | Block delimiter controlling scope/structure in this language.

L3605 | | Blank line used for readability and logical separation.

L3606 | .menu-link.active, | CSS selector line choosing the elements styled below.

L3607 | .menu-link:hover { | CSS selector line choosing the elements styled below.

L3608 | background: #e6edf8; | Operational statement participating in the file's runtime behavior.

L3609 | color: #1a58a9; | Operational statement participating in the file's runtime behavior.

L3610 | } | Block delimiter controlling scope/structure in this language.

L3611 | | Blank line used for readability and logical separation.

L3612 | .recent-activity-item { | CSS selector line choosing the elements styled below.

L3613 | width: 100%; | Operational statement participating in the file's runtime behavior.

L3614 | } | Block delimiter controlling scope/structure in this language.

L3615 | | Blank line used for readability and logical separation.

L3616 | .recent-activity-time { | CSS selector line choosing the elements styled below.

L3617 | white-space: nowrap; | Operational statement participating in the file's runtime behavior.

L3618 | } | Block delimiter controlling scope/structure in this language.

L3619 | | Blank line used for readability and logical separation.

L3620 | .menu-link:hover, | CSS selector line choosing the elements styled below.

L3621 | .btn:hover, | CSS selector line choosing the elements styled below.

L3622 | button:hover, | Operational statement participating in the file's runtime behavior.

L3623 | .table-hover tbody tr:hover, | CSS selector line choosing the elements styled below.

L3624 | .card-link:hover .stats-card, | CSS selector line choosing the elements styled below.

L3625 | .stats-card:hover, | CSS selector line choosing the elements styled below.

L3626 | .feature-card:hover, | CSS selector line choosing the elements styled below.

L3627 | .list-group-item:hover { | CSS selector line choosing the elements styled below.

L3628 | animation: hover-float 0.6s ease-in-out infinite alternate; | Operational statement participating in the file's runtime behavior.

L3629 | } | Block delimiter controlling scope/structure in this language.

L3630 | | Blank line used for readability and logical separation.

L3631 | /* Final hover/focus contrast safety net to keep labels readable across the app. */ | Operational statement participating in the file's runtime behavior.

L3632 | .btn:hover, | CSS selector line choosing the elements styled below.

L3633 | .btn:focus-visible, | CSS selector line choosing the elements styled below.

L3634 | button:hover, | Operational statement participating in the file's runtime behavior.

L3635 | button:focus-visible, | Operational statement participating in the file's runtime behavior.

L3636 | .page-link:hover, | CSS selector line choosing the elements styled below.

L3637 | .page-link:focus-visible, | CSS selector line choosing the elements styled below.

L3638 | .menu-link:hover, | CSS selector line choosing the elements styled below.

L3639 | .menu-link:focus-visible, | CSS selector line choosing the elements styled below.

L3640 | .notification-bell:hover, | CSS selector line choosing the elements styled below.

L3641 | .notification-bell:focus-visible, | CSS selector line choosing the elements styled below.

L3642 | .active-role-pill:hover, | CSS selector line choosing the elements styled below.

L3643 | .active-role-pill:focus-visible, | CSS selector line choosing the elements styled below.

L3644 | .build-chip:hover, | CSS selector line choosing the elements styled below.

L3645 | .build-chip:focus-visible { | CSS selector line choosing the elements styled below.

L3646 | color: #123a67 !important; | Operational statement participating in the file's runtime behavior.

L3647 | } | Block delimiter controlling scope/structure in this language.

L3648 | | Blank line used for readability and logical separation.

L3649 | .btn-primary:hover, | CSS selector line choosing the elements styled below.

L3650 | .btn-primary:focus-visible, | CSS selector line choosing the elements styled below.

L3651 | button.btn-primary:hover, | Operational statement participating in the file's runtime behavior.

L3652 | button.btn-primary:focus-visible, | Operational statement participating in the file's runtime behavior.

L3653 | .btn-danger:hover, | CSS selector line choosing the elements styled below.

L3654 | .btn-danger:focus-visible, | CSS selector line choosing the elements styled below.

L3655 | .btn-success:hover, | CSS selector line choosing the elements styled below.

L3656 | .btn-success:focus-visible, | CSS selector line choosing the elements styled below.

L3657 | .app-confirm-modal .btn-danger:hover, | CSS selector line choosing the elements styled below.

L3658 | .app-confirm-modal .btn-danger:focus-visible, | CSS selector line choosing the elements styled below.

L3659 | .app-confirm-modal .btn-primary:hover, | CSS selector line choosing the elements styled below.

L3660 | .app-confirm-modal .btn-primary:focus-visible { | CSS selector line choosing the elements styled below.

L3661 | color: #ffffff !important; | Operational statement participating in the file's runtime behavior.

L3662 | } | Block delimiter controlling scope/structure in this language.

L3663 | | Blank line used for readability and logical separation.

L3664 | .btn-warning:hover, | CSS selector line choosing the elements styled below.

L3665 | .btn-warning:focus-visible { | CSS selector line choosing the elements styled below.

L3666 | color: #1f2937 !important; | Operational statement participating in the file's runtime behavior.

L3667 | } | Block delimiter controlling scope/structure in this language.

L3668 | | Blank line used for readability and logical separation.

L3669 | .btn-outline-primary:hover, | CSS selector line choosing the elements styled below.

L3670 | .btn-outline-primary:focus-visible { | CSS selector line choosing the elements styled below.

L3671 | background: linear-gradient(180deg, #3da0ff 0%, var(--ios-blue) 100%) !important; | Operational statement participating in the file's runtime behavior.

L3672 | color: #ffffff !important; | Operational statement participating in the file's runtime behavior.

L3673 | border-color: rgba(10, 132, 255, 0.45) !important; | Operational statement participating in the file's runtime behavior.

L3674 | } | Block delimiter controlling scope/structure in this language.

L3675 | | Blank line used for readability and logical separation.

L3676 | .btn-outline-secondary:hover, | CSS selector line choosing the elements styled below.

L3677 | .btn-outline-secondary:focus-visible { | CSS selector line choosing the elements styled below.

L3678 | background: #5b6573 !important; | Operational statement participating in the file's runtime behavior.

L3679 | color: #ffffff !important; | Operational statement participating in the file's runtime behavior.

L3680 | border-color: #5b6573 !important; | Operational statement participating in the file's runtime behavior.

L3681 | } | Block delimiter controlling scope/structure in this language.

L3682 | | Blank line used for readability and logical separation.

L3683 | .btn-outline-dark:hover, | CSS selector line choosing the elements styled below.

L3684 | .btn-outline-dark:focus-visible { | CSS selector line choosing the elements styled below.
L3685 | background: #1f2937 !important; | Operational statement participating in the file's runtime behavior.
L3686 | color: #ffffff !important; | Operational statement participating in the file's runtime behavior.
L3687 | border-color: #1f2937 !important; | Operational statement participating in the file's runtime behavior.
L3688 | } | Block delimiter controlling scope/structure in this language.
L3689 | | Blank line used for readability and logical separation.
L3690 | .btn-outline-danger:hover, | CSS selector line choosing the elements styled below.
L3691 | .btn-outline-danger:focus-visible { | CSS selector line choosing the elements styled below.
L3692 | background: #dc3545 !important; | Operational statement participating in the file's runtime behavior.
L3693 | color: #ffffff !important; | Operational statement participating in the file's runtime behavior.
L3694 | border-color: #dc3545 !important; | Operational statement participating in the file's runtime behavior.
L3695 | } | Block delimiter controlling scope/structure in this language.
L3696 | | Blank line used for readability and logical separation.
L3697 | .btn-outline-warning:hover, | CSS selector line choosing the elements styled below.
L3698 | .btn-outline-warning:focus-visible { | CSS selector line choosing the elements styled below.
L3699 | background: #f59e0b !important; | Operational statement participating in the file's runtime behavior.
L3700 | color: #1f2937 !important; | Operational statement participating in the file's runtime behavior.
L3701 | border-color: #f59e0b !important; | Operational statement participating in the file's runtime behavior.
L3702 | } | Block delimiter controlling scope/structure in this language.
L3703 | | Blank line used for readability and logical separation.
L3704 | body[data-theme="dark"] .btn:hover, | Assignment statement storing or updating program state.
L3705 | body[data-theme="dark"] .btn:focus-visible, | Assignment statement storing or updating program state.
L3706 | body[data-theme="dark"] button:hover, | Assignment statement storing or updating program state.
L3707 | body[data-theme="dark"] button:focus-visible, | Assignment statement storing or updating program state.
L3708 | body[data-theme="dark"] .page-link:hover, | Assignment statement storing or updating program state.
L3709 | body[data-theme="dark"] .page-link:focus-visible, | Assignment statement storing or updating program state.
L3710 | body[data-theme="dark"] .menu-link:hover, | Assignment statement storing or updating program state.
L3711 | body[data-theme="dark"] .menu-link:focus-visible, | Assignment statement storing or updating program state.
L3712 | body[data-theme="dark"] .notification-bell:hover, | Assignment statement storing or updating program state.
L3713 | body[data-theme="dark"] .notification-bell:focus-visible, | Assignment statement storing or updating program state.
L3714 | body[data-theme="dark"] .active-role-pill:hover, | Assignment statement storing or updating program state.
L3715 | body[data-theme="dark"] .active-role-pill:focus-visible, | Assignment statement storing or updating program state.
L3716 | body[data-theme="dark"] .build-chip:hover, | Assignment statement storing or updating program state.
L3717 | body[data-theme="dark"] .build-chip:focus-visible { | Assignment statement storing or updating program state.
L3718 | color: #e8eef8 !important; | Operational statement participating in the file's runtime behavior.
L3719 | } | Block delimiter controlling scope/structure in this language.
L3720 | | Blank line used for readability and logical separation.
L3721 | .dashboard-hero-lite { | CSS selector line choosing the elements styled below.
L3722 | margin-bottom: 1rem; | Operational statement participating in the file's runtime behavior.
L3723 | } | Block delimiter controlling scope/structure in this language.
L3724 | | Blank line used for readability and logical separation.
L3725 | #copyShareUrlBtn, | Comment line documenting intent or context for nearby code.
L3726 | #nativeShareBtn, | Comment line documenting intent or context for nearby code.
L3727 | #downloadQrBtn, | Comment line documenting intent or context for nearby code.
L3728 | #refreshQrBtn { | Comment line documenting intent or context for nearby code.
L3729 | color: inherit; | Operational statement participating in the file's runtime behavior.
L3730 | } | Block delimiter controlling scope/structure in this language.
L3731 | | Blank line used for readability and logical separation.
L3732 | #copyShareUrlBtn:hover, | Comment line documenting intent or context for nearby code.
L3733 | #copyShareUrlBtn:focus-visible { | Comment line documenting intent or context for nearby code.
L3734 | background: linear-gradient(180deg, #3da0ff 0%, var(--ios-blue) 100%) !important; | Operational statement participating in the fi
L3735 | color: #ffffff !important; | Operational statement participating in the file's runtime behavior.
L3736 | } | Block delimiter controlling scope/structure in this language.
L3737 | | Blank line used for readability and logical separation.
L3738 | #nativeShareBtn:hover, | Comment line documenting intent or context for nearby code.

```

L3739 | #nativeShareBtn:focus-visible, | Comment line documenting intent or context for nearby code.
L3740 | #refreshQrBtn:hover, | Comment line documenting intent or context for nearby code.
L3741 | #refreshQrBtn:focus-visible { | Comment line documenting intent or context for nearby code.
L3742 |   background: rgba(10, 132, 255, 0.14) !important; | Operational statement participating in the file's runtime behavior.
L3743 |   color: #0a84ff !important; | Operational statement participating in the file's runtime behavior.
L3744 |   border-color: rgba(10, 132, 255, 0.22) !important; | Operational statement participating in the file's runtime behavior.
L3745 | } | Block delimiter controlling scope/structure in this language.
L3746 | | Blank line used for readability and logical separation.
L3747 | #downloadQrBtn:hover, | Comment line documenting intent or context for nearby code.
L3748 | #downloadQrBtn:focus-visible { | Comment line documenting intent or context for nearby code.
L3749 |   background: rgba(15, 23, 42, 0.1) !important; | Operational statement participating in the file's runtime behavior.
L3750 |   color: #111827 !important; | Operational statement participating in the file's runtime behavior.
L3751 |   border-color: rgba(15, 23, 42, 0.16) !important; | Operational statement participating in the file's runtime behavior.
L3752 | } | Block delimiter controlling scope/structure in this language.
L3753 | | Blank line used for readability and logical separation.
L3754 | body[data-theme="dark"] #nativeShareBtn:hover, | Assignment statement storing or updating program state.
L3755 | body[data-theme="dark"] #nativeShareBtn:focus-visible, | Assignment statement storing or updating program state.
L3756 | body[data-theme="dark"] #refreshQrBtn:hover, | Assignment statement storing or updating program state.
L3757 | body[data-theme="dark"] #refreshQrBtn:focus-visible { | Assignment statement storing or updating program state.
L3758 |   background: rgba(10, 132, 255, 0.24) !important; | Operational statement participating in the file's runtime behavior.
L3759 |   color: #8fc8ff !important; | Operational statement participating in the file's runtime behavior.
L3760 |   border-color: rgba(143, 200, 255, 0.28) !important; | Operational statement participating in the file's runtime behavior.
L3761 | } | Block delimiter controlling scope/structure in this language.
L3762 | | Blank line used for readability and logical separation.
L3763 | body[data-theme="dark"] #downloadQrBtn:hover, | Assignment statement storing or updating program state.
L3764 | body[data-theme="dark"] #downloadQrBtn:focus-visible { | Assignment statement storing or updating program state.
L3765 |   background: rgba(255, 255, 255, 0.1) !important; | Operational statement participating in the file's runtime behavior.
L3766 |   color: #f3f4f6 !important; | Operational statement participating in the file's runtime behavior.
L3767 |   border-color: rgba(255, 255, 255, 0.14) !important; | Operational statement participating in the file's runtime behavior.
L3768 | } | Block delimiter controlling scope/structure in this language.
L3769 | | Blank line used for readability and logical separation.
L3770 | .dashboard-hero-lite h1 { | CSS selector line choosing the elements styled below.
L3771 |   margin: 0; | Operational statement participating in the file's runtime behavior.
L3772 | } | Block delimiter controlling scope/structure in this language.
L3773 | | Blank line used for readability and logical separation.
L3774 | .detail-modal-image { | CSS selector line choosing the elements styled below.
L3775 |   width: 100%; | Operational statement participating in the file's runtime behavior.
L3776 |   max-height: 360px; | Operational statement participating in the file's runtime behavior.
L3777 |   object-fit: contain; | Operational statement participating in the file's runtime behavior.
L3778 |   background: #f8fbff; | Operational statement participating in the file's runtime behavior.
L3779 | } | Block delimiter controlling scope/structure in this language.
L3780 | | Blank line used for readability and logical separation.
L3781 | @media (max-width: 767.98px) { | Decorator line that modifies the behavior of the definition below.
L3782 |   .offcanvas { | CSS selector line choosing the elements styled below.
L3783 |     max-width: 86vw; | Operational statement participating in the file's runtime behavior.
L3784 |   } | Block delimiter controlling scope/structure in this language.
L3785 | | Blank line used for readability and logical separation.
L3786 | .stats-card { | CSS selector line choosing the elements styled below.
L3787 |   min-height: 190px; | Operational statement participating in the file's runtime behavior.
L3788 |   border-radius: 18px; | Operational statement participating in the file's runtime behavior.
L3789 | } | Block delimiter controlling scope/structure in this language.
L3790 | | Blank line used for readability and logical separation.
L3791 | .stats-card h1 { | CSS selector line choosing the elements styled below.
L3792 |   font-size: 2.2rem; | Operational statement participating in the file's runtime behavior.
L3793 | } | Block delimiter controlling scope/structure in this language.

```

L3794 | | Blank line used for readability and logical separation.

L3795 | .notification-bell { | CSS selector line choosing the elements styled below.

L3796 | width: 36px; | Operational statement participating in the file's runtime behavior.

L3797 | height: 36px; | Operational statement participating in the file's runtime behavior.

L3798 | } | Block delimiter controlling scope/structure in this language.

L3799 | } | Block delimiter controlling scope/structure in this language.

L3800 | | Blank line used for readability and logical separation.

L3801 | .form-access-card { | CSS selector line choosing the elements styled below.

L3802 | border: 2px solid #dbe8ff; | Operational statement participating in the file's runtime behavior.

L3803 | border-radius: 12px; | Operational statement participating in the file's runtime behavior.

L3804 | background: linear-gradient(135deg, #fbfdff 0%, #f0f5ff 100%); | Operational statement participating in the file's runtime behavior.

L3805 | box-shadow: 0 2px 8px rgba(15, 58, 115, 0.08); | Operational statement participating in the file's runtime behavior.

L3806 | transition: all 0.3s ease; | Operational statement participating in the file's runtime behavior.

L3807 | } | Block delimiter controlling scope/structure in this language.

L3808 | | Blank line used for readability and logical separation.

L3809 | .form-access-card:hover { | CSS selector line choosing the elements styled below.

L3810 | border-color: #1c4da8; | Operational statement participating in the file's runtime behavior.

L3811 | box-shadow: 0 4px 12px rgba(15, 58, 115, 0.15); | Operational statement participating in the file's runtime behavior.

L3812 | transform: translateY(-2px); | Operational statement participating in the file's runtime behavior.

L3813 | } | Block delimiter controlling scope/structure in this language.

L3814 | | Blank line used for readability and logical separation.

L3815 | .form-access-card .btn-lg { | CSS selector line choosing the elements styled below.

L3816 | padding: 0.75rem 1.5rem; | Operational statement participating in the file's runtime behavior.

L3817 | font-weight: 600; | Operational statement participating in the file's runtime behavior.

L3818 | } | Block delimiter controlling scope/structure in this language.

L3819 | | Blank line used for readability and logical separation.

L3820 | [data-bs-theme="dark"] .form-access-card { | Assignment statement storing or updating program state.

L3821 | border-color: #3a4a5c; | Operational statement participating in the file's runtime behavior.

L3822 | background: linear-gradient(135deg, #1e2a3a 0%, #252f42 100%); | Operational statement participating in the file's runtime behavior.

L3823 | box-shadow: 0 2px 8px rgba(0, 0, 0, 0.4); | Operational statement participating in the file's runtime behavior.

L3824 | } | Block delimiter controlling scope/structure in this language.

L3825 | | Blank line used for readability and logical separation.

L3826 | [data-bs-theme="dark"] .form-access-card:hover { | Assignment statement storing or updating program state.

L3827 | border-color: #5b8dee; | Operational statement participating in the file's runtime behavior.

L3828 | box-shadow: 0 4px 12px rgba(91, 141, 238, 0.2); | Operational statement participating in the file's runtime behavior.

L3829 | } | Block delimiter controlling scope/structure in this language.

L3830 | | Blank line used for readability and logical separation.

L3831 | /* Final dark-mode readability foundation (placed last to win the cascade). */ | Operational statement participating in the file's

L3832 | body[data-theme="dark"] { | Assignment statement storing or updating program state.

L3833 | color-scheme: dark; | Operational statement participating in the file's runtime behavior.

L3834 | --dm-bg: #0b1320; | Operational statement participating in the file's runtime behavior.

L3835 | --dm-surface: #131f33; | Operational statement participating in the file's runtime behavior.

L3836 | --dm-surface-soft: #192741; | Operational statement participating in the file's runtime behavior.

L3837 | --dm-border: rgba(163, 189, 230, 0.22); | Operational statement participating in the file's runtime behavior.

L3838 | --dm-text: #e9f1ff; | Operational statement participating in the file's runtime behavior.

L3839 | --dm-text-muted: #b8c8e2; | Operational statement participating in the file's runtime behavior.

L3840 | --dm-accent: #79bdff; | Operational statement participating in the file's runtime behavior.

L3841 | --dm-accent-strong: #4ea5ff; | Operational statement participating in the file's runtime behavior.

L3842 | --dm-success: #57d68d; | Operational statement participating in the file's runtime behavior.

L3843 | --dm-warning: #ffd166; | Operational statement participating in the file's runtime behavior.

L3844 | --dm-danger: #ff8e8e; | Operational statement participating in the file's runtime behavior.

L3845 | background-color: var(--dm-bg) !important; | Operational statement participating in the file's runtime behavior.

L3846 | background-image: linear-gradient(rgba(7, 14, 24, 0.76), rgba(7, 14, 24, 0.76)), url("/static/background-watermark.jpeg") !important;

L3847 | color: var(--dm-text) !important; | Operational statement participating in the file's runtime behavior.

L3848 | } | Block delimiter controlling scope/structure in this language.

L3849 | | Blank line used for readability and logical separation.

L3850 | body[data-theme="dark"] h1, | Assignment statement storing or updating program state.

L3851 | body[data-theme="dark"] h2, | Assignment statement storing or updating program state.

L3852 | body[data-theme="dark"] h3, | Assignment statement storing or updating program state.

L3853 | body[data-theme="dark"] h4, | Assignment statement storing or updating program state.

L3854 | body[data-theme="dark"] h5, | Assignment statement storing or updating program state.

L3855 | body[data-theme="dark"] h6, | Assignment statement storing or updating program state.

L3856 | body[data-theme="dark"] p, | Assignment statement storing or updating program state.

L3857 | body[data-theme="dark"] span, | Assignment statement storing or updating program state.

L3858 | body[data-theme="dark"] strong, | Assignment statement storing or updating program state.

L3859 | body[data-theme="dark"] label, | Assignment statement storing or updating program state.

L3860 | body[data-theme="dark"] legend, | Assignment statement storing or updating program state.

L3861 | body[data-theme="dark"] li, | Assignment statement storing or updating program state.

L3862 | body[data-theme="dark"] dt, | Assignment statement storing or updating program state.

L3863 | body[data-theme="dark"] dd, | Assignment statement storing or updating program state.

L3864 | body[data-theme="dark"] td, | Assignment statement storing or updating program state.

L3865 | body[data-theme="dark"] th, | Assignment statement storing or updating program state.

L3866 | body[data-theme="dark"] .text-body, | Assignment statement storing or updating program state.

L3867 | body[data-theme="dark"] .text-dark, | Assignment statement storing or updating program state.

L3868 | body[data-theme="dark"] .text-reset { | Assignment statement storing or updating program state.

L3869 | color: var(--dm-text) !important; | Operational statement participating in the file's runtime behavior.

L3870 | } | Block delimiter controlling scope/structure in this language.

L3871 | | Blank line used for readability and logical separation.

L3872 | body[data-theme="dark"] .text-muted, | Assignment statement storing or updating program state.

L3873 | body[data-theme="dark"] .small, | Assignment statement storing or updating program state.

L3874 | body[data-theme="dark"] small, | Assignment statement storing or updating program state.

L3875 | body[data-theme="dark"] .form-text, | Assignment statement storing or updating program state.

L3876 | body[data-theme="dark"] .text-secondary, | Assignment statement storing or updating program state.

L3877 | body[data-theme="dark"] .text-body-secondary, | Assignment statement storing or updating program state.

L3878 | body[data-theme="dark"] .dashboard-subtitle, | Assignment statement storing or updating program state.

L3879 | body[data-theme="dark"] .contact-role { | Assignment statement storing or updating program state.

L3880 | color: var(--dm-text-muted) !important; | Operational statement participating in the file's runtime behavior.

L3881 | } | Block delimiter controlling scope/structure in this language.

L3882 | | Blank line used for readability and logical separation.

L3883 | body[data-theme="dark"] .card, | Assignment statement storing or updating program state.

L3884 | body[data-theme="dark"] .detail-card, | Assignment statement storing or updating program state.

L3885 | body[data-theme="dark"] .stats-card, | Assignment statement storing or updating program state.

L3886 | body[data-theme="dark"] .feature-card, | Assignment statement storing or updating program state.

L3887 | body[data-theme="dark"] .review-item-card, | Assignment statement storing or updating program state.

L3888 | body[data-theme="dark"] .notify-message-card, | Assignment statement storing or updating program state.

L3889 | body[data-theme="dark"] .settings-card, | Assignment statement storing or updating program state.

L3890 | body[data-theme="dark"] .notification-item, | Assignment statement storing or updating program state.

L3891 | body[data-theme="dark"] .calendar-preview, | Assignment statement storing or updating program state.

L3892 | body[data-theme="dark"] .calendar-cell, | Assignment statement storing or updating program state.

L3893 | body[data-theme="dark"] .sla-policy-panel, | Assignment statement storing or updating program state.

L3894 | body[data-theme="dark"] .sla-policy-stat, | Assignment statement storing or updating program state.

L3895 | body[data-theme="dark"] .sla-agreement-box, | Assignment statement storing or updating program state.

L3896 | body[data-theme="dark"] .contact-escalation, | Assignment statement storing or updating program state.

L3897 | body[data-theme="dark"] .emergency-contact-card, | Assignment statement storing or updating program state.

L3898 | body[data-theme="dark"] .profile-card, | Assignment statement storing or updating program state.

L3899 | body[data-theme="dark"] .modal-content, | Assignment statement storing or updating program state.

L3900 | body[data-theme="dark"] .offcanvas, | Assignment statement storing or updating program state.

L3901 | body[data-theme="dark"] .dropdown-menu, | Assignment statement storing or updating program state.

L3902 | body[data-theme="dark"] .list-group-item, | Assignment statement storing or updating program state.

L3903 | body[data-theme="dark"] .table, | Assignment statement storing or updating program state.

L3904 | body[data-theme="dark"] .table thead th, | Assignment statement storing or updating program state.

L3905 | body[data-theme="dark"] .table tbody td, | Assignment statement storing or updating program state.

L3906 | body[data-theme="dark"] .table tbody th { | Assignment statement storing or updating program state.

L3907 | background: var(--dm-surface) !important; | Operational statement participating in the file's runtime behavior.

L3908 | color: var(--dm-text) !important; | Operational statement participating in the file's runtime behavior.

L3909 | border-color: var(--dm-border) !important; | Operational statement participating in the file's runtime behavior.

L3910 | } | Block delimiter controlling scope/structure in this language.

L3911 | | Blank line used for readability and logical separation.

L3912 | body[data-theme="dark"] .table-hover tbody tr:hover, | Assignment statement storing or updating program state.

L3913 | body[data-theme="dark"] .list-group-item:hover, | Assignment statement storing or updating program state.

L3914 | body[data-theme="dark"] .calendar-cell:hover { | Assignment statement storing or updating program state.

L3915 | background: var(--dm-surface-soft) !important; | Operational statement participating in the file's runtime behavior.

L3916 | } | Block delimiter controlling scope/structure in this language.

L3917 | | Blank line used for readability and logical separation.

L3918 | body[data-theme="dark"] a, | Assignment statement storing or updating program state.

L3919 | body[data-theme="dark"] .link-primary, | Assignment statement storing or updating program state.

L3920 | body[data-theme="dark"] .link-body-emphasis, | Assignment statement storing or updating program state.

L3921 | body[data-theme="dark"] .page-link, | Assignment statement storing or updating program state.

L3922 | body[data-theme="dark"] .menu-link { | Assignment statement storing or updating program state.

L3923 | color: var(--dm-accent) !important; | Operational statement participating in the file's runtime behavior.

L3924 | } | Block delimiter controlling scope/structure in this language.

L3925 | | Blank line used for readability and logical separation.

L3926 | body[data-theme="dark"] a:hover, | Assignment statement storing or updating program state.

L3927 | body[data-theme="dark"] .menu-link:hover, | Assignment statement storing or updating program state.

L3928 | body[data-theme="dark"] .page-link:hover { | Assignment statement storing or updating program state.

L3929 | color: #cde6ff !important; | Operational statement participating in the file's runtime behavior.

L3930 | } | Block delimiter controlling scope/structure in this language.

L3931 | | Blank line used for readability and logical separation.

L3932 | body[data-theme="dark"] .form-control, | Assignment statement storing or updating program state.

L3933 | body[data-theme="dark"] .form-select, | Assignment statement storing or updating program state.

L3934 | body[data-theme="dark"] textarea.form-control, | Assignment statement storing or updating program state.

L3935 | body[data-theme="dark"] input.form-control, | Assignment statement storing or updating program state.

L3936 | body[data-theme="dark"] .form-check-input { | Assignment statement storing or updating program state.

L3937 | background: #0f1b2f !important; | Operational statement participating in the file's runtime behavior.

L3938 | color: var(--dm-text) !important; | Operational statement participating in the file's runtime behavior.

L3939 | border: 1px solid var(--dm-border) !important; | Operational statement participating in the file's runtime behavior.

L3940 | } | Block delimiter controlling scope/structure in this language.

L3941 | | Blank line used for readability and logical separation.

L3942 | body[data-theme="dark"] .form-control::placeholder, | Assignment statement storing or updating program state.

L3943 | body[data-theme="dark"] textarea.form-control::placeholder, | Assignment statement storing or updating program state.

L3944 | body[data-theme="dark"] input.form-control::placeholder { | Assignment statement storing or updating program state.

L3945 | color: #8ea6c8 !important; | Operational statement participating in the file's runtime behavior.

L3946 | } | Block delimiter controlling scope/structure in this language.

L3947 | | Blank line used for readability and logical separation.

L3948 | body[data-theme="dark"] .form-control:focus, | Assignment statement storing or updating program state.

L3949 | body[data-theme="dark"] .form-select:focus, | Assignment statement storing or updating program state.

L3950 | body[data-theme="dark"] .form-check-input:focus { | Assignment statement storing or updating program state.

L3951 | border-color: rgba(121, 189, 255, 0.72) !important; | Operational statement participating in the file's runtime behavior.

L3952 | box-shadow: 0 0 0 0.24rem rgba(78, 165, 255, 0.22) !important; | Operational statement participating in the file's runtime behavior.

L3953 | } | Block delimiter controlling scope/structure in this language.

L3954 | | Blank line used for readability and logical separation.

L3955 | body[data-theme="dark"] .btn-primary, | Assignment statement storing or updating program state.

L3956 | body[data-theme="dark"] .app-confirm-modal .btn-primary { | Assignment statement storing or updating program state.

L3957 | background: linear-gradient(180deg, #5ab0ff 0%, #238cff 100%) !important; | Operational statement participating in the file's runtime behavior.

L3958 | border-color: #238cff !important; | Operational statement participating in the file's runtime behavior.

L3959 | color: #ffffff !important; | Operational statement participating in the file's runtime behavior.

L3960 | } | Block delimiter controlling scope/structure in this language.

L3961 | | Blank line used for readability and logical separation.

L3962 | body[data-theme="dark"] .btn-success { | Assignment statement storing or updating program state.

L3963 | background: linear-gradient(180deg, #49cc84 0%, #26a76a 100%) !important; | Operational statement participating in the file's runtime behavior.

L3964 | border-color: #26a76a !important; | Operational statement participating in the file's runtime behavior.

L3965 | color: #ffffff !important; | Operational statement participating in the file's runtime behavior.

L3966 | } | Block delimiter controlling scope/structure in this language.

L3967 | | Blank line used for readability and logical separation.

L3968 | body[data-theme="dark"] .btn-danger, | Assignment statement storing or updating program state.

L3969 | body[data-theme="dark"] .app-confirm-modal .btn-danger { | Assignment statement storing or updating program state.

L3970 | background: linear-gradient(180deg, #ff7f7f 0%, #e04b4b 100%) !important; | Operational statement participating in the file's runtime behavior.

L3971 | border-color: #e04b4b !important; | Operational statement participating in the file's runtime behavior.

L3972 | color: #ffffff !important; | Operational statement participating in the file's runtime behavior.

L3973 | } | Block delimiter controlling scope/structure in this language.

L3974 | | Blank line used for readability and logical separation.

L3975 | body[data-theme="dark"] .btn-warning { | Assignment statement storing or updating program state.

L3976 | background: linear-gradient(180deg, #ffd166 0%, #f4b740 100%) !important; | Operational statement participating in the file's runtime behavior.

L3977 | border-color: #f4b740 !important; | Operational statement participating in the file's runtime behavior.

L3978 | color: #2b230b !important; | Operational statement participating in the file's runtime behavior.

L3979 | } | Block delimiter controlling scope/structure in this language.

L3980 | | Blank line used for readability and logical separation.

L3981 | body[data-theme="dark"] .btn-outline-primary, | Assignment statement storing or updating program state.

L3982 | body[data-theme="dark"] .btn-outline-secondary, | Assignment statement storing or updating program state.

L3983 | body[data-theme="dark"] .btn-outline-dark, | Assignment statement storing or updating program state.

L3984 | body[data-theme="dark"] .btn-outline-warning, | Assignment statement storing or updating program state.

L3985 | body[data-theme="dark"] .btn-outline-danger { | Assignment statement storing or updating program state.

L3986 | background: rgba(19, 31, 51, 0.75) !important; | Operational statement participating in the file's runtime behavior.

L3987 | border-color: var(--dm-border) !important; | Operational statement participating in the file's runtime behavior.

L3988 | color: var(--dm-text) !important; | Operational statement participating in the file's runtime behavior.

L3989 | } | Block delimiter controlling scope/structure in this language.

L3990 | | Blank line used for readability and logical separation.

L3991 | body[data-theme="dark"] .btn-outline-primary:hover, | Assignment statement storing or updating program state.

L3992 | body[data-theme="dark"] .btn-outline-secondary:hover, | Assignment statement storing or updating program state.

L3993 | body[data-theme="dark"] .btn-outline-dark:hover, | Assignment statement storing or updating program state.

L3994 | body[data-theme="dark"] .btn-outline-warning:hover, | Assignment statement storing or updating program state.

L3995 | body[data-theme="dark"] .btn-outline-danger:hover, | Assignment statement storing or updating program state.

L3996 | body[data-theme="dark"] .btn-outline-primary:focus-visible, | Assignment statement storing or updating program state.

L3997 | body[data-theme="dark"] .btn-outline-secondary:focus-visible, | Assignment statement storing or updating program state.

L3998 | body[data-theme="dark"] .btn-outline-dark:focus-visible, | Assignment statement storing or updating program state.

L3999 | body[data-theme="dark"] .btn-outline-warning:focus-visible, | Assignment statement storing or updating program state.

L4000 | body[data-theme="dark"] .btn-outline-danger:focus-visible { | Assignment statement storing or updating program state.

L4001 | background: var(--dm-surface-soft) !important; | Operational statement participating in the file's runtime behavior.

L4002 | color: #ffffff !important; | Operational statement participating in the file's runtime behavior.

L4003 | border-color: rgba(121, 189, 255, 0.6) !important; | Operational statement participating in the file's runtime behavior.

L4004 | } | Block delimiter controlling scope/structure in this language.

L4005 | | Blank line used for readability and logical separation.

L4006 | body[data-theme="dark"] .alert { | Assignment statement storing or updating program state.

L4007 | border-color: var(--dm-border) !important; | Operational statement participating in the file's runtime behavior.

L4008 | } | Block delimiter controlling scope/structure in this language.

L4009 | | Blank line used for readability and logical separation.

L4010 | body[data-theme="dark"] .alert-success { | Assignment statement storing or updating program state.

L4011 | background: rgba(28, 95, 63, 0.5) !important; | Operational statement participating in the file's runtime behavior.

L4012 | color: #bdf6d7 !important; | Operational statement participating in the file's runtime behavior.

L4013 | } | Block delimiter controlling scope/structure in this language.

L4014 | | Blank line used for readability and logical separation.

L4015 | body[data-theme="dark"] .alert-warning { | Assignment statement storing or updating program state.

L4016 | background: rgba(121, 91, 21, 0.48) !important; | Operational statement participating in the file's runtime behavior.

L4017 | color: #ffe3a8 !important; | Operational statement participating in the file's runtime behavior.

L4018 | } | Block delimiter controlling scope/structure in this language.

L4019 | | Blank line used for readability and logical separation.

L4020 | body[data-theme="dark"] .alert-danger { | Assignment statement storing or updating program state.

L4021 | background: rgba(120, 34, 34, 0.5) !important; | Operational statement participating in the file's runtime behavior.

L4022 | color: #ffc2c2 !important; | Operational statement participating in the file's runtime behavior.

L4023 | } | Block delimiter controlling scope/structure in this language.

L4024 | | Blank line used for readability and logical separation.

L4025 | body[data-theme="dark"] .alert-info, | Assignment statement storing or updating program state.

L4026 | body[data-theme="dark"] .alert-primary { | Assignment statement storing or updating program state.

L4027 | background: rgba(24, 70, 122, 0.5) !important; | Operational statement participating in the file's runtime behavior.

L4028 | color: #cde6ff !important; | Operational statement participating in the file's runtime behavior.

L4029 | } | Block delimiter controlling scope/structure in this language.

L4030 | | Blank line used for readability and logical separation.

L4031 | body[data-theme="dark"] .badge { | Assignment statement storing or updating program state.

L4032 | color: #ffffff !important; | Operational statement participating in the file's runtime behavior.

L4033 | } | Block delimiter controlling scope/structure in this language.

L4034 | | Blank line used for readability and logical separation.

L4035 | body[data-theme="dark"] .modal-header, | Assignment statement storing or updating program state.

L4036 | body[data-theme="dark"] .modal-footer, | Assignment statement storing or updating program state.

L4037 | body[data-theme="dark"] .offcanvas-header, | Assignment statement storing or updating program state.

L4038 | body[data-theme="dark"] .offcanvas-footer { | Assignment statement storing or updating program state.

L4039 | border-color: var(--dm-border) !important; | Operational statement participating in the file's runtime behavior.

L4040 | } | Block delimiter controlling scope/structure in this language.

L4041 | | Blank line used for readability and logical separation.

L4042 | /* Global icon polish layer */ | Operational statement participating in the file's runtime behavior.

L4043 | @keyframes icon-soft-float { | Decorator line that modifies the behavior of the definition below.

L4044 | 0%, | Operational statement participating in the file's runtime behavior.

L4045 | 100% { | Block delimiter controlling scope/structure in this language.

L4046 | transform: translateY(0) scale(1); | Operational statement participating in the file's runtime behavior.

L4047 | } | Block delimiter controlling scope/structure in this language.

L4048 | 50% { | Block delimiter controlling scope/structure in this language.

L4049 | transform: translateY(-1px) scale(1.02); | Operational statement participating in the file's runtime behavior.

L4050 | } | Block delimiter controlling scope/structure in this language.

L4051 | } | Block delimiter controlling scope/structure in this language.

L4052 | | Blank line used for readability and logical separation.

L4053 | .bi { | CSS selector line choosing the elements styled below.

L4054 | vertical-align: -0.08em; | Operational statement participating in the file's runtime behavior.

L4055 | transition: color 0.2s ease, filter 0.2s ease, transform 0.2s ease; | Operational statement participating in the file's runtime behavior.

L4056 | } | Block delimiter controlling scope/structure in this language.

L4057 | | Blank line used for readability and logical separation.

L4058 | .btn .bi, | CSS selector line choosing the elements styled below.

L4059 | .page-back-pill .bi, | CSS selector line choosing the elements styled below.

L4060 | .settings-card-title .bi, | CSS selector line choosing the elements styled below.

L4061 | .notify-message-card .bi, | CSS selector line choosing the elements styled below.

L4062 | .holiday-popup-icon .bi, | CSS selector line choosing the elements styled below.

L4063 | .notification-bell .bi { | CSS selector line choosing the elements styled below.

L4064 | filter: drop-shadow(0 1px 1px rgba(10, 32, 76, 0.16)); | Operational statement participating in the file's runtime behavior.

L4065 | } | Block delimiter controlling scope/structure in this language.

L4066 | | Blank line used for readability and logical separation.

L4067 | .menu-link i { | CSS selector line choosing the elements styled below.

L4068 | width: 2rem; | Operational statement participating in the file's runtime behavior.

L4069 | height: 2rem; | Operational statement participating in the file's runtime behavior.

L4070 | border-radius: 999px; | Operational statement participating in the file's runtime behavior.

L4071 | display: inline-flex; | Operational statement participating in the file's runtime behavior.

L4072 | align-items: center; | Operational statement participating in the file's runtime behavior.

L4073 | justify-content: center; | Operational statement participating in the file's runtime behavior.

L4074 | font-size: 1.05rem; | Operational statement participating in the file's runtime behavior.

L4075 | background: linear-gradient(155deg, rgba(255, 255, 255, 0.95) 0%, rgba(229, 241, 255, 0.95) 100%); | Operational statement participating in the file's runtime behavior.

L4076 | border: 1px solid rgba(58, 118, 196, 0.2); | Operational statement participating in the file's runtime behavior.

L4077 | box-shadow: 0 6px 14px rgba(14, 71, 146, 0.12); | Operational statement participating in the file's runtime behavior.

L4078 | color: #1d60b5; | Operational statement participating in the file's runtime behavior.

L4079 | } | Block delimiter controlling scope/structure in this language.

L4080 | | Blank line used for readability and logical separation.

L4081 | .menu-link.active i, | CSS selector line choosing the elements styled below.

L4082 | .menu-link:hover i { | CSS selector line choosing the elements styled below.

L4083 | background: linear-gradient(180deg, #4aa5ff 0%, #0a84ff 100%); | Operational statement participating in the file's runtime behavior.

L4084 | border-color: rgba(10, 132, 255, 0.4); | Operational statement participating in the file's runtime behavior.

L4085 | color: #ffffff; | Operational statement participating in the file's runtime behavior.

L4086 | box-shadow: 0 9px 18px rgba(10, 132, 255, 0.25); | Operational statement participating in the file's runtime behavior.

L4087 | transform: translateY(-1px); | Operational statement participating in the file's runtime behavior.

L4088 | } | Block delimiter controlling scope/structure in this language.

L4089 | | Blank line used for readability and logical separation.

L4090 | .stats-icon, | CSS selector line choosing the elements styled below.

L4091 | .feature-icon, | CSS selector line choosing the elements styled below.

L4092 | .role-icon-badge, | CSS selector line choosing the elements styled below.

L4093 | .login-role-icon, | CSS selector line choosing the elements styled below.

L4094 | .profile-gender-icon, | CSS selector line choosing the elements styled below.

L4095 | .upload-icon-placeholder, | CSS selector line choosing the elements styled below.

L4096 | .holiday-popup-icon { | CSS selector line choosing the elements styled below.

L4097 | position: relative; | Operational statement participating in the file's runtime behavior.

L4098 | overflow: hidden; | Operational statement participating in the file's runtime behavior.

L4099 | } | Block delimiter controlling scope/structure in this language.

L4100 | | Blank line used for readability and logical separation.

L4101 | .stats-icon::after, | CSS selector line choosing the elements styled below.

L4102 | .feature-icon::after, | CSS selector line choosing the elements styled below.

L4103 | .role-icon-badge::after, | CSS selector line choosing the elements styled below.

L4104 | .login-role-icon::after, | CSS selector line choosing the elements styled below.

L4105 | .profile-gender-icon::after, | CSS selector line choosing the elements styled below.

L4106 | .upload-icon-placeholder::after, | CSS selector line choosing the elements styled below.

L4107 | .holiday-popup-icon::after { | CSS selector line choosing the elements styled below.

L4108 | content: ""; | Operational statement participating in the file's runtime behavior.

L4109 | position: absolute; | Operational statement participating in the file's runtime behavior.

L4110 | inset: 0; | Operational statement participating in the file's runtime behavior.

L4111 | background: radial-gradient(circle at 28% 22%, rgba(255, 255, 255, 0.5) 0%, rgba(255, 255, 255, 0) 55%); | Operational statement participating in the file's runtime behavior.

L4112 | pointer-events: none; | Operational statement participating in the file's runtime behavior.

L4113 | } | Block delimiter controlling scope/structure in this language.

L4114 | | Blank line used for readability and logical separation.

L4115 | .stats-icon { | CSS selector line choosing the elements styled below.

L4116 | border: 1px solid rgba(57, 132, 222, 0.2); | Operational statement participating in the file's runtime behavior.

L4117 | box-shadow: 0 10px 24px rgba(17, 86, 170, 0.18); | Operational statement participating in the file's runtime behavior.

L4118 | } | Block delimiter controlling scope/structure in this language.

L4119 | | Blank line used for readability and logical separation.

L4120 | .stats-icon i { | CSS selector line choosing the elements styled below.

L4121 | color: #0c5bbb; | Operational statement participating in the file's runtime behavior.

L4122 | text-shadow: 0 2px 10px rgba(16, 90, 179, 0.2); | Operational statement participating in the file's runtime behavior.

L4123 | } | Block delimiter controlling scope/structure in this language.

L4124 | | Blank line used for readability and logical separation.

L4125 | .feature-icon { | CSS selector line choosing the elements styled below.

L4126 | box-shadow: 0 12px 26px rgba(8, 55, 122, 0.2); | Operational statement participating in the file's runtime behavior.

L4127 | } | Block delimiter controlling scope/structure in this language.

L4128 | | Blank line used for readability and logical separation.

L4129 | .card-link:hover .stats-icon i, | CSS selector line choosing the elements styled below.

L4130 | .stats-card:hover .stats-icon i, | CSS selector line choosing the elements styled below.

L4131 | .feature-card:hover .feature-icon i { | CSS selector line choosing the elements styled below.

L4132 | animation: icon-soft-float 0.75s ease-in-out infinite; | Operational statement participating in the file's runtime behavior.

L4133 | } | Block delimiter controlling scope/structure in this language.

L4134 | | Blank line used for readability and logical separation.

L4135 | .btn .bi { | CSS selector line choosing the elements styled below.

L4136 | margin-right: 0.32rem; | Operational statement participating in the file's runtime behavior.

L4137 | } | Block delimiter controlling scope/structure in this language.

L4138 | | Blank line used for readability and logical separation.

L4139 | .btn .bi:last-child, | CSS selector line choosing the elements styled below.

L4140 | .btn .bi:only-child { | CSS selector line choosing the elements styled below.

L4141 | margin-right: 0; | Operational statement participating in the file's runtime behavior.

L4142 | } | Block delimiter controlling scope/structure in this language.

L4143 | | Blank line used for readability and logical separation.

L4144 | body[data-theme="dark"] .menu-link i { | Assignment statement storing or updating program state.

L4145 | background: linear-gradient(160deg, rgba(30, 47, 75, 0.92) 0%, rgba(22, 36, 58, 0.92) 100%); | Operational statement participating in the file's runtime behavior.

L4146 | border-color: rgba(131, 174, 233, 0.26); | Operational statement participating in the file's runtime behavior.

L4147 | box-shadow: 0 8px 18px rgba(2, 8, 18, 0.42); | Operational statement participating in the file's runtime behavior.

L4148 | color: #9fcfff; | Operational statement participating in the file's runtime behavior.

L4149 | } | Block delimiter controlling scope/structure in this language.

L4150 | | Blank line used for readability and logical separation.

L4151 | body[data-theme="dark"] .menu-link.active i, | Assignment statement storing or updating program state.

L4152 | body[data-theme="dark"] .menu-link:hover i { | Assignment statement storing or updating program state.

L4153 | background: linear-gradient(180deg, #5eb4ff 0%, #238cff 100%); | Operational statement participating in the file's runtime behavior.

L4154 | border-color: rgba(155, 208, 255, 0.6); | Operational statement participating in the file's runtime behavior.

L4155 | box-shadow: 0 10px 22px rgba(36, 140, 255, 0.35); | Operational statement participating in the file's runtime behavior.

L4156 | color: #ffffff; | Operational statement participating in the file's runtime behavior.

L4157 | } | Block delimiter controlling scope/structure in this language.

L4158 | | Blank line used for readability and logical separation.

L4159 | body[data-theme="dark"] .stats-icon, | Assignment statement storing or updating program state.

L4160 | body[data-theme="dark"] .feature-icon, | Assignment statement storing or updating program state.

L4161 | body[data-theme="dark"] .role-icon-badge, | Assignment statement storing or updating program state.

L4162 | body[data-theme="dark"] .login-role-icon, | Assignment statement storing or updating program state.

L4163 | body[data-theme="dark"] .profile-gender-icon, | Assignment statement storing or updating program state.

L4164 | body[data-theme="dark"] .upload-icon-placeholder, | Assignment statement storing or updating program state.

L4165 | body[data-theme="dark"] .holiday-popup-icon { | Assignment statement storing or updating program state.

L4166 | box-shadow: 0 10px 22px rgba(0, 0, 0, 0.35); | Operational statement participating in the file's runtime behavior.

L4167 | } | Block delimiter controlling scope/structure in this language.

L4168 | | Blank line used for readability and logical separation.

L4169 | body[data-theme="dark"] .stats-icon i, | Assignment statement storing or updating program state.

L4170 | body[data-theme="dark"] .feature-icon i, | Assignment statement storing or updating program state.

L4171 | body[data-theme="dark"] .role-icon-badge i, | Assignment statement storing or updating program state.

L4172 | body[data-theme="dark"] .login-role-icon i, | Assignment statement storing or updating program state.

L4173 | body[data-theme="dark"] .holiday-popup-icon i, | Assignment statement storing or updating program state.

L4174 | body[data-theme="dark"] .profile-gender-icon i { | Assignment statement storing or updating program state.

L4175 | color: #d8eaff; | Operational statement participating in the file's runtime behavior.

L4176 | text-shadow: 0 2px 10px rgba(64, 145, 255, 0.35); | Operational statement participating in the file's runtime behavior.

L4177 | } | Block delimiter controlling scope/structure in this language.

L4178 | | Blank line used for readability and logical separation.

L4179 | @media (max-width: 576px) { | Decorator line that modifies the behavior of the definition below.

L4180 | .menu-link i { | CSS selector line choosing the elements styled below.

L4181 | width: 1.85rem; | Operational statement participating in the file's runtime behavior.

L4182 | height: 1.85rem; | Operational statement participating in the file's runtime behavior.

L4183 | font-size: 0.98rem; | Operational statement participating in the file's runtime behavior.

L4184 | } | Block delimiter controlling scope/structure in this language.

L4185 | } | Block delimiter controlling scope/structure in this language.

L4186 | | Blank line used for readability and logical separation.

L4187 | /* Final role identity icon palette */ | Operational statement participating in the file's runtime behavior.

L4188 | .login-role-preview, | CSS selector line choosing the elements styled below.

L4189 | .active-role-pill { | CSS selector line choosing the elements styled below.

L4190 | --role-accent: #1f6ed4; | Operational statement participating in the file's runtime behavior.

L4191 | --role-accent-soft: rgba(31, 110, 212, 0.14); | Operational statement participating in the file's runtime behavior.

L4192 | --role-accent-border: rgba(31, 110, 212, 0.24); | Operational statement participating in the file's runtime behavior.

L4193 | --role-accent-strong: #0f4e9c; | Operational statement participating in the file's runtime behavior.

L4194 | } | Block delimiter controlling scope/structure in this language.

L4195 | | Blank line used for readability and logical separation.

L4196 | .login-role-preview.role-technician, | CSS selector line choosing the elements styled below.

L4197 | .active-role-pill.role-technician { | CSS selector line choosing the elements styled below.

L4198 | --role-accent: #14a38b; | Operational statement participating in the file's runtime behavior.

L4199 | --role-accent-soft: rgba(20, 163, 139, 0.16); | Operational statement participating in the file's runtime behavior.

L4200 | --role-accent-border: rgba(20, 163, 139, 0.24); | Operational statement participating in the file's runtime behavior.

L4201 | --role-accent-strong: #0c7f6c; | Operational statement participating in the file's runtime behavior.

L4202 | } | Block delimiter controlling scope/structure in this language.

L4203 | | Blank line used for readability and logical separation.

L4204 | .login-role-preview.role-staff, | CSS selector line choosing the elements styled below.

L4205 | .active-role-pill.role-staff { | CSS selector line choosing the elements styled below.

L4206 | --role-accent: #2684ff; | Operational statement participating in the file's runtime behavior.

L4207 | --role-accent-soft: rgba(38, 132, 255, 0.15); | Operational statement participating in the file's runtime behavior.

L4208 | --role-accent-border: rgba(38, 132, 255, 0.24); | Operational statement participating in the file's runtime behavior.

L4209 | --role-accent-strong: #175fb9; | Operational statement participating in the file's runtime behavior.

L4210 | } | Block delimiter controlling scope/structure in this language.

L4211 | | Blank line used for readability and logical separation.

L4212 | .login-role-preview.role-manager, | CSS selector line choosing the elements styled below.

L4213 | .active-role-pill.role-manager { | CSS selector line choosing the elements styled below.

L4214 | --role-accent: #1f73e6; | Operational statement participating in the file's runtime behavior.

L4215 | --role-accent-soft: rgba(31, 115, 230, 0.17); | Operational statement participating in the file's runtime behavior.

L4216 | --role-accent-border: rgba(31, 115, 230, 0.25); | Operational statement participating in the file's runtime behavior.

L4217 | --role-accent-strong: #1454ad; | Operational statement participating in the file's runtime behavior.

L4218 | } | Block delimiter controlling scope/structure in this language.

L4219 | | Blank line used for readability and logical separation.

L4220 | .login-role-preview.role-general-manager, | CSS selector line choosing the elements styled below.

L4221 | .active-role-pill.role-general_manager { | CSS selector line choosing the elements styled below.

L4222 | --role-accent: #2d7fff; | Operational statement participating in the file's runtime behavior.

L4223 | --role-accent-soft: rgba(45, 127, 255, 0.16); | Operational statement participating in the file's runtime behavior.

L4224 | --role-accent-border: rgba(45, 127, 255, 0.24); | Operational statement participating in the file's runtime behavior.

L4225 | --role-accent-strong: #1a63cf; | Operational statement participating in the file's runtime behavior.

L4226 | } | Block delimiter controlling scope/structure in this language.

L4227 | | Blank line used for readability and logical separation.

L4228 | .login-role-preview.role-developer, | CSS selector line choosing the elements styled below.

L4229 | .active-role-pill.role-developer { | CSS selector line choosing the elements styled below.

L4230 | --role-accent: #0a84ff; | Operational statement participating in the file's runtime behavior.

L4231 | --role-accent-soft: rgba(10, 132, 255, 0.16); | Operational statement participating in the file's runtime behavior.

L4232 | --role-accent-border: rgba(10, 132, 255, 0.25); | Operational statement participating in the file's runtime behavior.

L4233 | --role-accent-strong: #0a5fb8; | Operational statement participating in the file's runtime behavior.

L4234 | } | Block delimiter controlling scope/structure in this language.

L4235 | | Blank line used for readability and logical separation.

L4236 | .login-role-preview { | CSS selector line choosing the elements styled below.

L4237 | border-color: var(--role-accent-border) !important; | Operational statement participating in the file's runtime behavior.

L4238 | } | Block delimiter controlling scope/structure in this language.

L4239 | | Blank line used for readability and logical separation.

L4240 | .login-role-preview .login-role-icon, | CSS selector line choosing the elements styled below.

L4241 | .active-role-pill .role-icon-badge { | CSS selector line choosing the elements styled below.

L4242 | background: linear-gradient(160deg, rgba(255, 255, 255, 0.96) 0%, var(--role-accent-soft) 100%) !important; | Operational statement participating in the file's runtime behavior.

L4243 | border-color: var(--role-accent-border) !important; | Operational statement participating in the file's runtime behavior.

L4244 | color: var(--role-accent-strong) !important; | Operational statement participating in the file's runtime behavior.

L4245 | box-shadow: 0 8px 18px color-mix(in srgb, var(--role-accent) 22%, transparent); | Operational statement participating in the file's runtime behavior.

L4246 | } | Block delimiter controlling scope/structure in this language.

L4247 | | Blank line used for readability and logical separation.

L4248 | .login-role-preview .login-role-icon i, | CSS selector line choosing the elements styled below.

L4249 | .active-role-pill .role-icon-badge i { | CSS selector line choosing the elements styled below.

L4250 | color: inherit !important; | Operational statement participating in the file's runtime behavior.

L4251 | text-shadow: 0 2px 10px color-mix(in srgb, var(--role-accent) 26%, transparent); | Operational statement participating in the file's runtime behavior.

L4252 | } | Block delimiter controlling scope/structure in this language.

L4253 | | Blank line used for readability and logical separation.

L4254 | .login-role-preview .login-role-copy strong, | CSS selector line choosing the elements styled below.

L4255 | .active-role-pill { | CSS selector line choosing the elements styled below.

L4256 | color: var(--role-accent-strong) !important; | Operational statement participating in the file's runtime behavior.

L4257 | } | Block delimiter controlling scope/structure in this language.

L4258 | | Blank line used for readability and logical separation.

L4259 | body[data-theme="dark"] .login-role-preview, | Assignment statement storing or updating program state.

L4260 | body[data-theme="dark"] .active-role-pill { | Assignment statement storing or updating program state.

L4261 | --role-accent-soft: color-mix(in srgb, var(--role-accent) 18%, rgba(18, 28, 46, 0.95)); | Operational statement participating in the file's runtime behavior.

L4262 | --role-accent-border: color-mix(in srgb, var(--role-accent) 38%, rgba(164, 189, 229, 0.2)); | Operational statement participating in the file's runtime behavior.

L4263 | --role-accent-strong: color-mix(in srgb, var(--role-accent) 54%, white); | Operational statement participating in the file's runtime behavior.

L4264 | } | Block delimiter controlling scope/structure in this language.

L4265 | | Blank line used for readability and logical separation.

L4266 | body[data-theme="dark"] .login-role-preview .login-role-icon, | Assignment statement storing or updating program state.

L4267 | body[data-theme="dark"] .active-role-pill .role-icon-badge { | Assignment statement storing or updating program state.

L4268 | background: linear-gradient(160deg, rgba(18, 28, 46, 0.96) 0%, var(--role-accent-soft) 100%) !important; | Operational statement participating in the file's runtime behavior.

L4269 | border-color: var(--role-accent-border) !important; | Operational statement participating in the file's runtime behavior.

L4270 | color: var(--role-accent-strong) !important; | Operational statement participating in the file's runtime behavior.

L4271 | box-shadow: 0 10px 22px color-mix(in srgb, var(--role-accent) 22%, rgba(0, 0, 0, 0.28)); | Operational statement participating in the file's runtime behavior.

L4272 | } | Block delimiter controlling scope/structure in this language.

L4273 | | Blank line used for readability and logical separation.

L4274 | body[data-theme="dark"] .login-role-preview .login-role-copy strong, | Assignment statement storing or updating program state.

L4275 | body[data-theme="dark"] .active-role-pill { | Assignment statement storing or updating program state.

L4276 | color: #e8f1ff !important; | Operational statement participating in the file's runtime behavior.

L4277 | } | Block delimiter controlling scope/structure in this language.

L4278 | | Blank line used for readability and logical separation.

L4279 | /* Role-tinted profile cards and dashboard stat cards */ | Operational statement participating in the file's runtime behavior.

L4280 | .profile-card, | CSS selector line choosing the elements styled below.

L4281 | .role-dashboard-shell { | CSS selector line choosing the elements styled below.

L4282 | --role-accent: #1f6ed4; | Operational statement participating in the file's runtime behavior.

L4283 | --role-accent-soft: rgba(31, 110, 212, 0.12); | Operational statement participating in the file's runtime behavior.

L4284 | --role-accent-border: rgba(31, 110, 212, 0.2); | Operational statement participating in the file's runtime behavior.

L4285 | --role-accent-strong: #0f4e9c; | Operational statement participating in the file's runtime behavior.

L4286 | } | Block delimiter controlling scope/structure in this language.

L4287 | | Blank line used for readability and logical separation.

L4288 | .profile-card.role-technician, | CSS selector line choosing the elements styled below.

L4289 | .role-dashboard-shell.role-technician { | CSS selector line choosing the elements styled below.
L4290 | --role-accent: #14a38b; | Operational statement participating in the file's runtime behavior.
L4291 | --role-accent-soft: rgba(20, 163, 139, 0.13); | Operational statement participating in the file's runtime behavior.
L4292 | --role-accent-border: rgba(20, 163, 139, 0.24); | Operational statement participating in the file's runtime behavior.
L4293 | --role-accent-strong: #0c7f6c; | Operational statement participating in the file's runtime behavior.
L4294 | } | Block delimiter controlling scope/structure in this language.
L4295 | | Blank line used for readability and logical separation.
L4296 | .profile-card.role-staff, | CSS selector line choosing the elements styled below.
L4297 | .role-dashboard-shell.role-staff { | CSS selector line choosing the elements styled below.
L4298 | --role-accent: #2684ff; | Operational statement participating in the file's runtime behavior.
L4299 | --role-accent-soft: rgba(38, 132, 255, 0.13); | Operational statement participating in the file's runtime behavior.
L4300 | --role-accent-border: rgba(38, 132, 255, 0.22); | Operational statement participating in the file's runtime behavior.
L4301 | --role-accent-strong: #175fb9; | Operational statement participating in the file's runtime behavior.
L4302 | } | Block delimiter controlling scope/structure in this language.
L4303 | | Blank line used for readability and logical separation.
L4304 | .profile-card.role-manager, | CSS selector line choosing the elements styled below.
L4305 | .role-dashboard-shell.role-manager { | CSS selector line choosing the elements styled below.
L4306 | --role-accent: #1f73e6; | Operational statement participating in the file's runtime behavior.
L4307 | --role-accent-soft: rgba(31, 115, 230, 0.14); | Operational statement participating in the file's runtime behavior.
L4308 | --role-accent-border: rgba(31, 115, 230, 0.24); | Operational statement participating in the file's runtime behavior.
L4309 | --role-accent-strong: #1454ad; | Operational statement participating in the file's runtime behavior.
L4310 | } | Block delimiter controlling scope/structure in this language.
L4311 | | Blank line used for readability and logical separation.
L4312 | .profile-card.role-general-manager, | CSS selector line choosing the elements styled below.
L4313 | .role-dashboard-shell.role-general-manager, | CSS selector line choosing the elements styled below.
L4314 | .role-dashboard-shell.role-general_manager { | CSS selector line choosing the elements styled below.
L4315 | --role-accent: #2d7fff; | Operational statement participating in the file's runtime behavior.
L4316 | --role-accent-soft: rgba(45, 127, 255, 0.14); | Operational statement participating in the file's runtime behavior.
L4317 | --role-accent-border: rgba(45, 127, 255, 0.24); | Operational statement participating in the file's runtime behavior.
L4318 | --role-accent-strong: #1a63cf; | Operational statement participating in the file's runtime behavior.
L4319 | } | Block delimiter controlling scope/structure in this language.
L4320 | | Blank line used for readability and logical separation.
L4321 | .profile-card.role-developer, | CSS selector line choosing the elements styled below.
L4322 | .role-dashboard-shell.role-developer { | CSS selector line choosing the elements styled below.
L4323 | --role-accent: #0a84ff; | Operational statement participating in the file's runtime behavior.
L4324 | --role-accent-soft: rgba(10, 132, 255, 0.14); | Operational statement participating in the file's runtime behavior.
L4325 | --role-accent-border: rgba(10, 132, 255, 0.24); | Operational statement participating in the file's runtime behavior.
L4326 | --role-accent-strong: #0a5fb8; | Operational statement participating in the file's runtime behavior.
L4327 | } | Block delimiter controlling scope/structure in this language.
L4328 | | Blank line used for readability and logical separation.
L4329 | .profile-card { | CSS selector line choosing the elements styled below.
L4330 | background: linear-gradient(145deg, #ffffff 0%, color-mix(in srgb, var(--role-accent) 4%, #f7fbff) 100%); | Operational statement
L4331 | border-color: var(--role-accent-border) !important; | Operational statement participating in the file's runtime behavior.
L4332 | box-shadow: 0 14px 30px color-mix(in srgb, var(--role-accent) 10%, rgba(9, 61, 126, 0.08)); | Operational statement participating
L4333 | } | Block delimiter controlling scope/structure in this language.
L4334 | | Blank line used for readability and logical separation.
L4335 | .profile-card::before { | CSS selector line choosing the elements styled below.
L4336 | content: ""; | Operational statement participating in the file's runtime behavior.
L4337 | position: absolute; | Operational statement participating in the file's runtime behavior.
L4338 | inset: 0 auto 0 0; | Operational statement participating in the file's runtime behavior.
L4339 | width: 4px; | Operational statement participating in the file's runtime behavior.
L4340 | border-radius: 16px 0 0 16px; | Operational statement participating in the file's runtime behavior.
L4341 | background: linear-gradient(180deg, color-mix(in srgb, var(--role-accent) 82%, white) 0%, var(--role-accent-strong) 100%); | Oper
L4342 | opacity: 0.9; | Operational statement participating in the file's runtime behavior.
L4343 | } | Block delimiter controlling scope/structure in this language.

L4344 | | Blank line used for readability and logical separation.

L4345 | .profile-card .profile-gender-icon, | CSS selector line choosing the elements styled below.

L4346 | .profile-card .badge.text-bg-dark { | CSS selector line choosing the elements styled below.

L4347 | border-color: var(--role-accent-border) !important; | Operational statement participating in the file's runtime behavior.

L4348 | } | Block delimiter controlling scope/structure in this language.

L4349 | | Blank line used for readability and logical separation.

L4350 | .profile-card .profile-gender-icon { | CSS selector line choosing the elements styled below.

L4351 | background: linear-gradient(160deg, #ffffff 0%, var(--role-accent-soft) 100%) !important; | Operational statement participating in the file's runtime behavior.

L4352 | color: var(--role-accent-strong) !important; | Operational statement participating in the file's runtime behavior.

L4353 | } | Block delimiter controlling scope/structure in this language.

L4354 | | Blank line used for readability and logical separation.

L4355 | .role-dashboard-shell .stats-card { | CSS selector line choosing the elements styled below.

L4356 | border: 1px solid var(--role-accent-border); | Operational statement participating in the file's runtime behavior.

L4357 | background: linear-gradient(155deg, #ffffff 0%, color-mix(in srgb, var(--role-accent) 6%, #f8fbff) 100%); | Operational statement participating in the file's runtime behavior.

L4358 | } | Block delimiter controlling scope/structure in this language.

L4359 | | Blank line used for readability and logical separation.

L4360 | .role-dashboard-shell .stats-icon { | CSS selector line choosing the elements styled below.

L4361 | background: radial-gradient(circle at top left, color-mix(in srgb, var(--role-accent) 28%, white) 0%, color-mix(in srgb, var(--role-accent) 28%, white) 100%); | Operational statement participating in the file's runtime behavior.

L4362 | border: 1px solid var(--role-accent-border); | Operational statement participating in the file's runtime behavior.

L4363 | box-shadow: 0 10px 22px color-mix(in srgb, var(--role-accent) 18%, rgba(0, 84, 164, 0.12)); | Operational statement participating in the file's runtime behavior.

L4364 | } | Block delimiter controlling scope/structure in this language.

L4365 | | Blank line used for readability and logical separation.

L4366 | .role-dashboard-shell .stats-icon i, | CSS selector line choosing the elements styled below.

L4367 | .role-dashboard-shell .stats-card p, | CSS selector line choosing the elements styled below.

L4368 | .role-dashboard-shell .stats-card h1 { | CSS selector line choosing the elements styled below.

L4369 | color: var(--role-accent-strong) !important; | Operational statement participating in the file's runtime behavior.

L4370 | } | Block delimiter controlling scope/structure in this language.

L4371 | | Blank line used for readability and logical separation.

L4372 | .role-dashboard-shell .card-link:hover .stats-card, | CSS selector line choosing the elements styled below.

L4373 | .role-dashboard-shell .stats-card:hover { | CSS selector line choosing the elements styled below.

L4374 | box-shadow: 0 20px 40px color-mix(in srgb, var(--role-accent) 18%, rgba(45, 105, 255, 0.14)); | Operational statement participating in the file's runtime behavior.

L4375 | } | Block delimiter controlling scope/structure in this language.

L4376 | | Blank line used for readability and logical separation.

L4377 | body[data-theme="dark"] .profile-card, | Assignment statement storing or updating program state.

L4378 | body[data-theme="dark"] .role-dashboard-shell { | Assignment statement storing or updating program state.

L4379 | --role-accent-soft: color-mix(in srgb, var(--role-accent) 16%, rgba(17, 27, 45, 0.92)); | Operational statement participating in the file's runtime behavior.

L4380 | --role-accent-border: color-mix(in srgb, var(--role-accent) 34%, rgba(163, 189, 230, 0.16)); | Operational statement participating in the file's runtime behavior.

L4381 | --role-accent-strong: color-mix(in srgb, var(--role-accent) 55%, white); | Operational statement participating in the file's runtime behavior.

L4382 | } | Block delimiter controlling scope/structure in this language.

L4383 | | Blank line used for readability and logical separation.

L4384 | body[data-theme="dark"] .profile-card { | Assignment statement storing or updating program state.

L4385 | background: linear-gradient(155deg, rgba(16, 25, 41, 0.98) 0%, var(--role-accent-soft) 100%) !important; | Operational statement participating in the file's runtime behavior.

L4386 | border-color: var(--role-accent-border) !important; | Operational statement participating in the file's runtime behavior.

L4387 | box-shadow: 0 18px 34px color-mix(in srgb, var(--role-accent) 14%, rgba(0, 0, 0, 0.28)); | Operational statement participating in the file's runtime behavior.

L4388 | } | Block delimiter controlling scope/structure in this language.

L4389 | | Blank line used for readability and logical separation.

L4390 | body[data-theme="dark"] .profile-card .profile-gender-icon { | Assignment statement storing or updating program state.

L4391 | background: linear-gradient(160deg, rgba(17, 28, 45, 0.95) 0%, var(--role-accent-soft) 100%) !important; | Operational statement participating in the file's runtime behavior.

L4392 | color: var(--role-accent-strong) !important; | Operational statement participating in the file's runtime behavior.

L4393 | } | Block delimiter controlling scope/structure in this language.

L4394 | | Blank line used for readability and logical separation.

L4395 | body[data-theme="dark"] .role-dashboard-shell .stats-card { | Assignment statement storing or updating program state.

L4396 | background: linear-gradient(160deg, rgba(16, 25, 41, 0.98) 0%, var(--role-accent-soft) 100%) !important; | Operational statement participating in the file's runtime behavior.

L4397 | border-color: var(--role-accent-border) !important; | Operational statement participating in the file's runtime behavior.

L4398 | } | Block delimiter controlling scope/structure in this language.

L4399 | | Blank line used for readability and logical separation.

L4400 | body[data-theme="dark"] .role-dashboard-shell .stats-icon { | Assignment statement storing or updating program state.

L4401 | background: radial-gradient(circle at top left, color-mix(in srgb, var(--role-accent) 28%, rgba(28, 44, 72, 0.96)) 0%, rgba(17, 2

L4402 | border-color: var(--role-accent-border) !important; | Operational statement participating in the file's runtime behavior.

L4403 | box-shadow: 0 12px 24px color-mix(in srgb, var(--role-accent) 16%, rgba(0, 0, 0, 0.34)); | Operational statement participating in

L4404 | } | Block delimiter controlling scope/structure in this language.

L4405 | | Blank line used for readability and logical separation.

L4406 | body[data-theme="dark"] .role-dashboard-shell .stats-icon i, | Assignment statement storing or updating program state.

L4407 | body[data-theme="dark"] .role-dashboard-shell .stats-card p, | Assignment statement storing or updating program state.

L4408 | body[data-theme="dark"] .role-dashboard-shell .stats-card h1 { | Assignment statement storing or updating program state.

L4409 | color: #edf5ff !important; | Operational statement participating in the file's runtime behavior.

L4410 | } | Block delimiter controlling scope/structure in this language.

L4411 | | Blank line used for readability and logical separation.

File 89: templates/500.html

L0001 | <h1>Something went wrong</h1> | Markup line defining structure in an HTML-like template file.

L0002 | <p>We're fixing it. Try again.</p> | Markup line defining structure in an HTML-like template file.

File 90: templates/activities.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <h1>Recent Activities {% if activity_type %}{{ activity_type\upper }}{% endif %}</h1> | Markup line defining structure in an HTML-like template file.
L0004 | <div class="card mt-3 p-3"> | Assignment statement storing or updating program state.
L0005 |     <p class="text-muted mb-3">Newest activity appears first.</p> | Assignment statement storing or updating program state.
L0006 |     {% if activities %} | Block delimiter controlling scope/structure in this language.
L0007 |         <ul class="list-group"> | Assignment statement storing or updating program state.
L0008 |             {% for act in activities %} | Block delimiter controlling scope/structure in this language.
L0009 |                 <li class="list-group-item"> | Assignment statement storing or updating program state.
L0010 |                     <div class="d-flex justify-content-between align-items-start gap-3 recent-activity-item"> | Assignment statement storing or updating program state.
L0011 |                         <div><strong>{{ act.activity_type\upper }}</strong> - {{ act.details }}</div> | Markup line defining structure in an HTML-like template file.
L0012 |                         <span class="text-muted small recent-activity-time">{{ act.created_at.strftime('%Y-%m-%d %H:%M:%S') }}</span> | Assignment statement storing or updating program state.
L0013 |                     </div> | Markup line defining structure in an HTML-like template file.
L0014 |                 </li> | Markup line defining structure in an HTML-like template file.
L0015 |             {% endfor %} | Block delimiter controlling scope/structure in this language.
L0016 |         </ul> | Markup line defining structure in an HTML-like template file.
L0017 |     {% else %} | Block delimiter controlling scope/structure in this language.
L0018 |         <p>No activities yet for you.</p> | Markup line defining structure in an HTML-like template file.
L0019 |     {% endif %} | Block delimiter controlling scope/structure in this language.
L0020 | </div> | Markup line defining structure in an HTML-like template file.
L0021 | {% endblock %} | Block delimiter controlling scope/structure in this language.
```

File 91: templates/activity_view.html

L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.

L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.

L0003 | <h1>{{ activity.activity_type|upper }} Form #{{ activity.id }}</h1> | Markup line defining structure in an HTML-like template file.

L0004 | <p class="text-muted mb-3">Submitted by {{ activity.created_by or 'Unknown' }} on {{ activity.created_at.strftime('%Y-%m-%d %H:%M:%S') }}</p> | Markup line defining structure in an HTML-like template file.

L0005 | | Blank line used for readability and logical separation.

L0006 | <div class="card mt-3"> | Assignment statement storing or updating program state.

L0007 | <div class="card-body"> | Assignment statement storing or updating program state.

L0008 | <div class="d-flex flex-wrap gap-2 mb-3"> | Assignment statement storing or updating program state.

L0009 | <i class="bi bi-arrow-left"></i> Back | Markup line defining structure in an HTML-like template file.

L0010 | {% if activity.is_approved %} | Block delimiter controlling scope/structure in this language.

L0011 | <i class="bi bi-download"></i> Download | Markup line defining structure in an HTML-like template file.

L0012 | {% else %} | Block delimiter controlling scope/structure in this language.

L0013 | <form method="post" action="{{ url_for('approve_activity', activity_id=activity.id) }}" class="d-inline"> | Assignment statement storing or updating program state.

L0014 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0015 | <button type="submit" class="btn btn-outline-success"> | Assignment statement storing or updating program state.

L0016 | <i class="bi bi-check-circle me-1"></i>Approve | Assignment statement storing or updating program state.

L0017 | </button> | Markup line defining structure in an HTML-like template file.

L0018 | </form> | Markup line defining structure in an HTML-like template file.

L0019 | <form method="post" action="{{ url_for('reject_activity', activity_id=activity.id) }}" class="d-inline" data-confirm-message="Are you sure you want to reject this activity?"> | Assignment statement storing or updating program state.

L0020 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0021 | <button type="submit" class="btn btn-outline-danger"> | Assignment statement storing or updating program state.

L0022 | <i class="bi bi-x-circle me-1"></i>Reject | Assignment statement storing or updating program state.

L0023 | </button> | Markup line defining structure in an HTML-like template file.

L0024 | </form> | Markup line defining structure in an HTML-like template file.

L0025 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0026 | </div> | Markup line defining structure in an HTML-like template file.

L0027 | | Blank line used for readability and logical separation.

L0028 | <h5 class="mb-2">Form Details</h5> | Assignment statement storing or updating program state.

L0029 | <pre class="mb-0" style="white-space: pre-wrap; word-break: break-word;">{{ activity.details }}</pre> | Assignment statement storing or updating program state.

L0030 | </div> | Markup line defining structure in an HTML-like template file.

L0031 | </div> | Markup line defining structure in an HTML-like template file.

L0032 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 92: templates/add_general_manager.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <h1>Add General Manager</h1> | Markup line defining structure in an HTML-like template file.
L0004 | <div class="card mt-3 mb-4 p-3"> | Assignment statement storing or updating program state.
L0005 |   <h5><i class="bi bi-person-badge-fill me-2"></i>General Manager Form</h5> | Assignment statement storing or updating program state.
L0006 |   <form method="post" class="row g-3 mt-1"> | Assignment statement storing or updating program state.
L0007 |     <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.
L0008 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0009 |       <label class="form-label">First Name</label> | Assignment statement storing or updating program state.
L0010 |       <input name="first_name" class="form-control" required /> | Assignment statement storing or updating program state.
L0011 |     </div> | Markup line defining structure in an HTML-like template file.
L0012 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0013 |       <label class="form-label">Last Name</label> | Assignment statement storing or updating program state.
L0014 |       <input name="last_name" class="form-control" required /> | Assignment statement storing or updating program state.
L0015 |     </div> | Markup line defining structure in an HTML-like template file.
L0016 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0017 |       <label class="form-label">Region</label> | Assignment statement storing or updating program state.
L0018 |       <input name="region" class="form-control" /> | Assignment statement storing or updating program state.
L0019 |     </div> | Markup line defining structure in an HTML-like template file.
L0020 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0021 |       <label class="form-label">Gender</label> | Assignment statement storing or updating program state.
L0022 |       <select name="gender" class="form-select"> | Assignment statement storing or updating program state.
L0023 |         <option value="">Select gender</option> | Assignment statement storing or updating program state.
L0024 |         <option value="male">Male</option> | Assignment statement storing or updating program state.
L0025 |         <option value="female">Female</option> | Assignment statement storing or updating program state.
L0026 |       </select> | Markup line defining structure in an HTML-like template file.
L0027 |     </div> | Markup line defining structure in an HTML-like template file.
L0028 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0029 |       <label class="form-label">Role</label> | Assignment statement storing or updating program state.
L0030 |       <input class="form-control" value="General Manager" readonly /> | Assignment statement storing or updating program state.
L0031 |     </div> | Markup line defining structure in an HTML-like template file.
L0032 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0033 |       <label class="form-label">Email</label> | Assignment statement storing or updating program state.
L0034 |       <input name="email" type="email" class="form-control" required /> | Assignment statement storing or updating program state.
L0035 |     </div> | Markup line defining structure in an HTML-like template file.
L0036 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0037 |       <label class="form-label">Password (optional)</label> | Assignment statement storing or updating program state.
L0038 |       <input name="password" type="password" class="form-control" placeholder="Leave blank to auto-generate" /> | Assignment statement storing or updating program state.
L0039 |     </div> | Markup line defining structure in an HTML-like template file.
L0040 |     <div class="col-12 text-end"> | Assignment statement storing or updating program state.
L0041 |       <button type="submit" class="btn btn-primary">Create General Manager</button> | Assignment statement storing or updating program state.
L0042 |     </div> | Markup line defining structure in an HTML-like template file.
L0043 |   </form> | Markup line defining structure in an HTML-like template file.
L0044 | </div> | Markup line defining structure in an HTML-like template file.
L0045 | {% endblock %} | Block delimiter controlling scope/structure in this language.
```

File 93: templates/add_manager.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <h1>Add Manager</h1> | Markup line defining structure in an HTML-like template file.
L0004 | <div class="card mt-3 mb-4 p-3"> | Assignment statement storing or updating program state.
L0005 |   <h5><i class="bi bi-person-workspace me-2"></i>Manager Form</h5> | Assignment statement storing or updating program state.
L0006 |   <form method="post" class="row g-3 mt-1"> | Assignment statement storing or updating program state.
L0007 |     <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.
L0008 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0009 |       <label class="form-label">First Name</label> | Assignment statement storing or updating program state.
L0010 |       <input name="first_name" class="form-control" required /> | Assignment statement storing or updating program state.
L0011 |     </div> | Markup line defining structure in an HTML-like template file.
L0012 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0013 |       <label class="form-label">Last Name</label> | Assignment statement storing or updating program state.
L0014 |       <input name="last_name" class="form-control" required /> | Assignment statement storing or updating program state.
L0015 |     </div> | Markup line defining structure in an HTML-like template file.
L0016 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0017 |       <label class="form-label">Region</label> | Assignment statement storing or updating program state.
L0018 |       <input name="region" class="form-control" /> | Assignment statement storing or updating program state.
L0019 |     </div> | Markup line defining structure in an HTML-like template file.
L0020 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0021 |       <label class="form-label">Gender</label> | Assignment statement storing or updating program state.
L0022 |       <select name="gender" class="form-select"> | Assignment statement storing or updating program state.
L0023 |         <option value="">Select gender</option> | Assignment statement storing or updating program state.
L0024 |         <option value="male">Male</option> | Assignment statement storing or updating program state.
L0025 |         <option value="female">Female</option> | Assignment statement storing or updating program state.
L0026 |       </select> | Markup line defining structure in an HTML-like template file.
L0027 |     </div> | Markup line defining structure in an HTML-like template file.
L0028 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0029 |       <label class="form-label">Role</label> | Assignment statement storing or updating program state.
L0030 |       <input class="form-control" value="Manager" readonly /> | Assignment statement storing or updating program state.
L0031 |     </div> | Markup line defining structure in an HTML-like template file.
L0032 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0033 |       <label class="form-label">Email</label> | Assignment statement storing or updating program state.
L0034 |       <input name="email" type="email" class="form-control" required /> | Assignment statement storing or updating program state.
L0035 |     </div> | Markup line defining structure in an HTML-like template file.
L0036 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0037 |       <label class="form-label">Password (optional)</label> | Assignment statement storing or updating program state.
L0038 |       <input name="password" type="password" class="form-control" placeholder="Leave blank to auto-generate" /> | Assignment statemen
L0039 |     </div> | Markup line defining structure in an HTML-like template file.
L0040 |     <div class="col-12 text-end"> | Assignment statement storing or updating program state.
L0041 |       <button type="submit" class="btn btn-primary">Create Manager</button> | Assignment statement storing or updating program stat
L0042 |     </div> | Markup line defining structure in an HTML-like template file.
L0043 |   </form> | Markup line defining structure in an HTML-like template file.
L0044 | </div> | Markup line defining structure in an HTML-like template file.
L0045 | {% endblock %} | Block delimiter controlling scope/structure in this language.
```


File 94: templates/add_staff.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <h1>Add Staff</h1> | Markup line defining structure in an HTML-like template file.
L0004 | <div class="card mt-3 mb-4 p-3"> | Assignment statement storing or updating program state.
L0005 |   <h5><i class="bi bi-plus-square me-2"></i>Staff Form</h5> | Assignment statement storing or updating program state.
L0006 |   <form method="post" class="row g-3 mt-1"> | Assignment statement storing or updating program state.
L0007 |     <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.
L0008 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0009 |       <label class="form-label">First Name</label> | Assignment statement storing or updating program state.
L0010 |       <input name="first_name" class="form-control" required /> | Assignment statement storing or updating program state.
L0011 |     </div> | Markup line defining structure in an HTML-like template file.
L0012 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0013 |       <label class="form-label">Last Name</label> | Assignment statement storing or updating program state.
L0014 |       <input name="last_name" class="form-control" required /> | Assignment statement storing or updating program state.
L0015 |     </div> | Markup line defining structure in an HTML-like template file.
L0016 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0017 |       <label class="form-label">Region</label> | Assignment statement storing or updating program state.
L0018 |       <input name="region" class="form-control" /> | Assignment statement storing or updating program state.
L0019 |     </div> | Markup line defining structure in an HTML-like template file.
L0020 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0021 |       <label class="form-label">Gender</label> | Assignment statement storing or updating program state.
L0022 |       <select name="gender" class="form-select"> | Assignment statement storing or updating program state.
L0023 |         <option value="">Select gender</option> | Assignment statement storing or updating program state.
L0024 |         <option value="male">Male</option> | Assignment statement storing or updating program state.
L0025 |         <option value="female">Female</option> | Assignment statement storing or updating program state.
L0026 |       </select> | Markup line defining structure in an HTML-like template file.
L0027 |     </div> | Markup line defining structure in an HTML-like template file.
L0028 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0029 |       <label class="form-label">Role</label> | Assignment statement storing or updating program state.
L0030 |       <input class="form-control" value="Staff" readonly /> | Assignment statement storing or updating program state.
L0031 |       <input type="hidden" name="role" value="staff" /> | Assignment statement storing or updating program state.
L0032 |     </div> | Markup line defining structure in an HTML-like template file.
L0033 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0034 |       <label class="form-label">Email</label> | Assignment statement storing or updating program state.
L0035 |       <input name="email" type="email" class="form-control" required /> | Assignment statement storing or updating program state.
L0036 |     </div> | Markup line defining structure in an HTML-like template file.
L0037 |     <div class="col-md-6"> | Assignment statement storing or updating program state.
L0038 |       <label class="form-label">Password (optional)</label> | Assignment statement storing or updating program state.
L0039 |       <input name="password" type="password" class="form-control" placeholder="Leave blank to auto-generate" /> | Assignment statemen
L0040 |     </div> | Markup line defining structure in an HTML-like template file.
L0041 |     <div class="col-12 text-end"> | Assignment statement storing or updating program state.
L0042 |       <button type="submit" class="btn btn-primary">Create Staff Account</button> | Assignment statement storing or updating progra
L0043 |     </div> | Markup line defining structure in an HTML-like template file.
L0044 |   </form> | Markup line defining structure in an HTML-like template file.
L0045 | </div> | Markup line defining structure in an HTML-like template file.
L0046 | {% endblock %} | Block delimiter controlling scope/structure in this language.
```

File 95: templates/add_technician.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <h1>Add Technician</h1> | Markup line defining structure in an HTML-like template file.
L0004 | <div class="card mt-3 mb-4 p-3"> | Assignment statement storing or updating program state.
L0005 |     <h5><i class="bi bi-plus-circle me-2"></i>Technician Form</h5> | Assignment statement storing or updating program state.
L0006 |     <form method="post" class="row g-3 mt-1"> | Assignment statement storing or updating program state.
L0007 |         <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.
L0008 |         <div class="col-md-6"> | Assignment statement storing or updating program state.
L0009 |             <label class="form-label">First Name</label> | Assignment statement storing or updating program state.
L0010 |             <input name="first_name" class="form-control" required /> | Assignment statement storing or updating program state.
L0011 |         </div> | Markup line defining structure in an HTML-like template file.
L0012 |         <div class="col-md-6"> | Assignment statement storing or updating program state.
L0013 |             <label class="form-label">Last Name</label> | Assignment statement storing or updating program state.
L0014 |             <input name="last_name" class="form-control" required /> | Assignment statement storing or updating program state.
L0015 |         </div> | Markup line defining structure in an HTML-like template file.
L0016 |         <div class="col-md-6"> | Assignment statement storing or updating program state.
L0017 |             <label class="form-label">Region</label> | Assignment statement storing or updating program state.
L0018 |             <input name="region" class="form-control" /> | Assignment statement storing or updating program state.
L0019 |         </div> | Markup line defining structure in an HTML-like template file.
L0020 |         <div class="col-md-6"> | Assignment statement storing or updating program state.
L0021 |             <label class="form-label">Gender</label> | Assignment statement storing or updating program state.
L0022 |             <select name="gender" class="form-select"> | Assignment statement storing or updating program state.
L0023 |                 <option value="">Select gender</option> | Assignment statement storing or updating program state.
L0024 |                 <option value="male">Male</option> | Assignment statement storing or updating program state.
L0025 |                 <option value="female">Female</option> | Assignment statement storing or updating program state.
L0026 |             </select> | Markup line defining structure in an HTML-like template file.
L0027 |         </div> | Markup line defining structure in an HTML-like template file.
L0028 |         <div class="col-md-6"> | Assignment statement storing or updating program state.
L0029 |             <label class="form-label">Role</label> | Assignment statement storing or updating program state.
L0030 |             <input class="form-control" value="Technician" readonly /> | Assignment statement storing or updating program state.
L0031 |         </div> | Markup line defining structure in an HTML-like template file.
L0032 |         <div class="col-md-6"> | Assignment statement storing or updating program state.
L0033 |             <label class="form-label">Email</label> | Assignment statement storing or updating program state.
L0034 |             <input name="email" type="email" class="form-control" required /> | Assignment statement storing or updating program state.
L0035 |         </div> | Markup line defining structure in an HTML-like template file.
L0036 |         <div class="col-md-6"> | Assignment statement storing or updating program state.
L0037 |             <label class="form-label">Password (optional)</label> | Assignment statement storing or updating program state.
L0038 |             <input name="password" type="password" class="form-control" placeholder="Leave blank to auto-generate" /> | Assignment statemen
L0039 |         </div> | Markup line defining structure in an HTML-like template file.
L0040 |         <div class="col-12 text-end"> | Assignment statement storing or updating program state.
L0041 |             <button type="submit" class="btn btn-primary">Create Technician</button> | Assignment statement storing or updating program s
L0042 |         </div> | Markup line defining structure in an HTML-like template file.
L0043 |     </form> | Markup line defining structure in an HTML-like template file.
L0044 | </div> | Markup line defining structure in an HTML-like template file.
L0045 | {% endblock %} | Block delimiter controlling scope/structure in this language.
```

File 96: templates/admin_staff.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | | Blank line used for readability and logical separation.
L0004 | {% set role_groups = [ | Assignment statement storing or updating program state.
L0005 |     ('technician',      'Technicians',      'bi-person-gear',      'text-bg-info'), | Operational statement participating in the f
L0006 |     ('staff',          'Staff',              'bi-person-badge',     'text-bg-primary'), | Operational statement participating in th
L0007 |     ('manager',        'Managers',          'bi-person-workspace', 'text-bg-warning'), | Operational statement participating in th
L0008 |     ('general_manager', 'General Managers', 'bi-person-badge-fill', 'text-bg-success'), | Operational statement participating in th
L0009 |     ('developer',      'Developers',      'bi-code-slash',       'text-bg-dark'), | Operational statement participating in the f
L0010 | ] %} | Block delimiter controlling scope/structure in this language.
L0011 | | Blank line used for readability and logical separation.
L0012 | <div class="d-flex justify-content-between align-items-center mt-1 mb-3 flex-wrap gap-2"> | Assignment statement storing or updating
L0013 |     <h1 class="mb-0">Account Management</h1> | Assignment statement storing or updating program state.
L0014 |     <div class="d-flex flex-wrap gap-2"> | Assignment statement storing or updating program state.
L0015 |         <span class="badge text-bg-dark fs-6 px-3 py-2"> | Assignment statement storing or updating program state.
L0016 |             <i class="bi bi-people-fill me-1"></i> {{ total_users }} Total Users | Assignment statement storing or updating program state
L0017 |         </span> | Markup line defining structure in an HTML-like template file.
L0018 |         {% if search_query %} | Block delimiter controlling scope/structure in this language.
L0019 |             <span class="badge text-bg-primary fs-6 px-3 py-2"> | Assignment statement storing or updating program state.
L0020 |                 <i class="bi bi-search me-1"></i> {{ matched_users }} Match{% if matched_users != 1 %}es{% endif %} | Block delimiter control
L0021 |             </span> | Markup line defining structure in an HTML-like template file.
L0022 |         {% endif %} | Block delimiter controlling scope/structure in this language.
L0023 |     </div> | Markup line defining structure in an HTML-like template file.
L0024 | </div> | Markup line defining structure in an HTML-like template file.
L0025 | | Blank line used for readability and logical separation.
L0026 | <div class="card mb-4 p-3"> | Assignment statement storing or updating program state.
L0027 |     <h5 class="mb-3">User Pages Created</h5> | Assignment statement storing or updating program state.
L0028 |     <div class="row g-3"> | Assignment statement storing or updating program state.
L0029 |         <div class="col-12 col-md-4 col-xl-2"> | Assignment statement storing or updating program state.
L0030 |             <div class="border rounded-3 p-3 h-100"> | Assignment statement storing or updating program state.
L0031 |                 <div class="small text-muted">Total User Pages</div> | Assignment statement storing or updating program state.
L0032 |                 <div class="fs-3 fw-bold">{{ total_user_pages }}</div> | Assignment statement storing or updating program state.
L0033 |             </div> | Markup line defining structure in an HTML-like template file.
L0034 |         </div> | Markup line defining structure in an HTML-like template file.
L0035 |         <div class="col-6 col-md-4 col-xl-2"> | Assignment statement storing or updating program state.
L0036 |             <div class="border rounded-3 p-3 h-100"> | Assignment statement storing or updating program state.
L0037 |                 <div class="small text-muted">Technician Pages</div> | Assignment statement storing or updating program state.
L0038 |                 <div class="fs-4 fw-semibold">{{ role_page_counts.technician }}</div> | Assignment statement storing or updating program st
L0039 |             </div> | Markup line defining structure in an HTML-like template file.
L0040 |         </div> | Markup line defining structure in an HTML-like template file.
L0041 |         <div class="col-6 col-md-4 col-xl-2"> | Assignment statement storing or updating program state.
L0042 |             <div class="border rounded-3 p-3 h-100"> | Assignment statement storing or updating program state.
L0043 |                 <div class="small text-muted">Staff Pages</div> | Assignment statement storing or updating program state.
L0044 |                 <div class="fs-4 fw-semibold">{{ role_page_counts.staff }}</div> | Assignment statement storing or updating program state.
L0045 |             </div> | Markup line defining structure in an HTML-like template file.
L0046 |         </div> | Markup line defining structure in an HTML-like template file.
L0047 |         <div class="col-6 col-md-4 col-xl-2"> | Assignment statement storing or updating program state.
L0048 |             <div class="border rounded-3 p-3 h-100"> | Assignment statement storing or updating program state.
L0049 |                 <div class="small text-muted">Manager Pages</div> | Assignment statement storing or updating program state.
L0050 |                 <div class="fs-4 fw-semibold">{{ role_page_counts.manager }}</div> | Assignment statement storing or updating program state
L0051 |             </div> | Markup line defining structure in an HTML-like template file.
L0052 |         </div> | Markup line defining structure in an HTML-like template file.
L0053 |         <div class="col-6 col-md-4 col-xl-2"> | Assignment statement storing or updating program state.
```

L0054 | <div class="border rounded-3 p-3 h-100"> | Assignment statement storing or updating program state.

L0055 | <div class="small text-muted">General Manager Pages</div> | Assignment statement storing or updating program state.

L0056 | <div class="fs-4 fw-semibold">{{ role_page_counts.general_manager }}</div> | Assignment statement storing or updating program state.

L0057 | </div> | Markup line defining structure in an HTML-like template file.

L0058 | </div> | Markup line defining structure in an HTML-like template file.

L0059 | <div class="col-6 col-md-4 col-xl-2"> | Assignment statement storing or updating program state.

L0060 | <div class="border rounded-3 p-3 h-100"> | Assignment statement storing or updating program state.

L0061 | <div class="small text-muted">Developer Pages</div> | Assignment statement storing or updating program state.

L0062 | <div class="fs-4 fw-semibold">{{ role_page_counts.developer }}</div> | Assignment statement storing or updating program state.

L0063 | </div> | Markup line defining structure in an HTML-like template file.

L0064 | </div> | Markup line defining structure in an HTML-like template file.

L0065 | </div> | Markup line defining structure in an HTML-like template file.

L0066 | <p class="text-muted small mt-3 mb-0">Each account maps to one independent user page experience based on role.</p> | Assignment statement storing or updating program state.

L0067 | </div> | Markup line defining structure in an HTML-like template file.

L0068 | | Blank line used for readability and logical separation.

L0069 | <div class="card mb-4 p-3"> | Assignment statement storing or updating program state.

L0070 | <h5 class="mb-2">Add New Account</h5> | Assignment statement storing or updating program state.

L0071 | <div class="d-flex flex-wrap gap-2"> | Assignment statement storing or updating program state.

L0072 | <i class="bi bi-plus-circle me-1"></i>Add Technician | Assignment statement storing or updating program state.

L0073 | <i class="bi bi-plus-square me-1"></i>Add Staff | Assignment statement storing or updating program state.

L0074 | <i class="bi bi-person-workspace me-1"></i>Add Manager | Assignment statement storing or updating program state.

L0075 | <i class="bi bi-person-badge-fill me-1"></i>Add General Manager | Assignment statement storing or updating program state.

L0076 | </div> | Markup line defining structure in an HTML-like template file.

L0077 | </div> | Markup line defining structure in an HTML-like template file.

L0078 | | Blank line used for readability and logical separation.

L0079 | <div class="card mb-4 p-3"> | Assignment statement storing or updating program state.

L0080 | <h5 class="mb-2">Role Access Matrix</h5> | Assignment statement storing or updating program state.

L0081 | <p class="text-muted mb-3">This matrix shows page independence by role and process dependencies across levels.</p> | Assignment statement storing or updating program state.

L0082 | <div class="table-responsive"> | Assignment statement storing or updating program state.

L0083 | <table class="table table-bordered align-middle mb-0"> | Assignment statement storing or updating program state.

L0084 | <thead> | Markup line defining structure in an HTML-like template file.

L0085 | <tr> | Markup line defining structure in an HTML-like template file.

L0086 | <th>Role</th> | Markup line defining structure in an HTML-like template file.

L0087 | <th>Dashboard Page</th> | Markup line defining structure in an HTML-like template file.

L0088 | <th>Primary Access</th> | Markup line defining structure in an HTML-like template file.

L0089 | <th>Data Scope</th> | Markup line defining structure in an HTML-like template file.

L0090 | <th>Process Dependency</th> | Markup line defining structure in an HTML-like template file.

L0091 | </tr> | Markup line defining structure in an HTML-like template file.

L0092 | </thead> | Markup line defining structure in an HTML-like template file.

L0093 | <tbody> | Markup line defining structure in an HTML-like template file.

L0094 | <tr> | Markup line defining structure in an HTML-like template file.

L0095 | <td>Technician</td> | Assignment statement storing or updating program state.

L0096 | <td><code>technician_dashboard.html</code></td> | Markup line defining structure in an HTML-like template file.

L0097 | <td>Fill PM/RCA form, view own rejected reports, send messages to staff/manager/developer</td> | Markup line defining structure in an HTML-like template file.

L0098 | <td>Own submissions only</td> | Markup line defining structure in an HTML-like template file.

L0099 | <td>Submits work for staff review and decision</td> | Markup line defining structure in an HTML-like template file.

L0100 | </tr> | Markup line defining structure in an HTML-like template file.

L0101 | <tr> | Markup line defining structure in an HTML-like template file.

L0102 | <td>Staff</td> | Assignment statement storing or updating program state.

L0103 | <td><code>staff_dashboard.html</code></td> | Markup line defining structure in an HTML-like template file.

L0104 | <td>Desk review, approve/reject PM/RCA, notifications, exports</td> | Markup line defining structure in an HTML-like template file.

L0105 | <td>All technician submissions</td> | Markup line defining structure in an HTML-like template file.

L0106 | <td>Acts on technician forms and feeds review outcomes</td> | Markup line defining structure in an HTML-like template file.

L0107 | </tr> | Markup line defining structure in an HTML-like template file.

L0108 | <tr> | Markup line defining structure in an HTML-like template file.

L0109 | <td>Manager / General Manager</td> | Assignment statement storing or updating
L0110 | <td><code>manager_dashboard.html</code></td> | Markup line defining structure in an HTML-like template file.
L0111 | <td>Oversight review queue, SLA/risk monitoring, approvals/rejections</td> | Markup line defining structure in an HTML-like template file.
L0112 | <td>All technician submissions</td> | Markup line defining structure in an HTML-like template file.
L0113 | <td>Supervises staff review pipeline and escalations</td> | Markup line defining structure in an HTML-like template file.
L0114 | </tr> | Markup line defining structure in an HTML-like template file.
L0115 | <tr> | Markup line defining structure in an HTML-like template file.
L0116 | <td>Developer</td> | Assignment statement storing or updating program state.
L0117 | <td><code>developer_role_dashboard.html</code></td> | Markup line defining structure in an HTML-like template file.
L0118 | <td>Account management, user controls, system notifications/settings</td> | Markup line defining structure in an HTML-like template file.
L0119 | <td>System-wide</td> | Markup line defining structure in an HTML-like template file.
L0120 | <td>Creates users and governs role/page boundaries</td> | Markup line defining structure in an HTML-like template file.
L0121 | </tr> | Markup line defining structure in an HTML-like template file.
L0122 | </tbody> | Markup line defining structure in an HTML-like template file.
L0123 | </table> | Markup line defining structure in an HTML-like template file.
L0124 | </div> | Markup line defining structure in an HTML-like template file.
L0125 | </div> | Markup line defining structure in an HTML-like template file.
L0126 | | Blank line used for readability and logical separation.
L0127 | <div class="card mb-4 p-3"> | Assignment statement storing or updating program state.
L0128 | <h5 class="mb-2">Research Tool</h5> | Assignment statement storing or updating program state.
L0129 | <form method="get" action="{ { url_for('admin_staff') } }" class="row g-2 align-items-end"> | Assignment statement storing or updating program state.
L0130 | <div class="col-12 col-lg-8"> | Assignment statement storing or updating program state.
L0131 | <label class="form-label">Search by UID, name, email, region, or role</label> | Assignment statement storing or updating program state.
L0132 | <input type="search" name="q" class="form-control" value="{ { search_query } }" placeholder="Example: TEC-001, staff, Kampala,"> | Markup line defining structure in an HTML-like template file.
L0133 | </div> | Markup line defining structure in an HTML-like template file.
L0134 | <div class="col-6 col-lg-2"> | Assignment statement storing or updating program state.
L0135 | <button class="btn btn-primary w-100" type="submit"><i class="bi bi-search me-1"></i>Search</button> | Assignment statement storing or updating program state.
L0136 | </div> | Markup line defining structure in an HTML-like template file.
L0137 | <div class="col-6 col-lg-2"> | Assignment statement storing or updating program state.
L0138 | Clear | Assignment statement storing or updating program state.
L0139 | </div> | Markup line defining structure in an HTML-like template file.
L0140 | </form> | Markup line defining structure in an HTML-like template file.
L0141 | </div> | Markup line defining structure in an HTML-like template file.
L0142 | | Blank line used for readability and logical separation.
L0143 | {% if issued_credentials %} | Block delimiter controlling scope/structure in this language.
L0144 | <div class="card mb-4 border-success shadow-sm"> | Assignment statement storing or updating program state.
L0145 | <div class="card-body"> | Assignment statement storing or updating program state.
L0146 | <div class="d-flex justify-content-between align-items-start gap-3 flex-wrap"> | Assignment statement storing or updating program state.
L0147 | <div> | Markup line defining structure in an HTML-like template file.
L0148 | <h5 class="mb-1 text-success"><i class="bi bi-key-fill me-2"></i>Latest Issued Credentials</h5> | Assignment statement storing or updating program state.
L0149 | <p class="mb-1">User: { { issued_credentials.display_name } } ({ { issued_credentials.role } })</p> | Assignment statement storing or updating program state.
L0150 | <p class="mb-1">Email: { { issued_credentials.email } }</p> | Assignment statement storing or updating program state.
L0151 | <p class="mb-1">UID: { { issued_credentials.uid or 'Pending UID' } }</p> | Assignment statement storing or updating program state.
L0152 | <p class="mb-1">Action: { { issued_credentials.action.title() } }</p> | Assignment statement storing or updating program state.
L0153 | {% if issued_credentials.action == 'reset' %} | Block delimiter controlling scope/structure in this language.
L0154 | <p class="mb-1">Previous Password (Provided): { { issued_credentials.previous_password or 'Not provided by system' } }</p> | Assignment statement storing or updating program state.
L0155 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0156 | <p class="mb-0">Issued: { { issued_credentials.issued_at } }</p> | Assignment statement storing or updating program state.
L0157 | </div> | Markup line defining structure in an HTML-like template file.
L0158 | <div class="text-start text-md-end"> | Assignment statement storing or updating program state.
L0159 | <div class="small text-muted mb-1">{% if issued_credentials.action == 'reset' %}New password{% else %}Issued password{% endif %}</div> | Assignment statement storing or updating program state.
L0160 | <div class="badge text-bg-dark fs-6 px-3 py-2" style="font-family:monospace; letter-spacing:0.06em;">{ { issued_credentials.action } }</div> | Assignment statement storing or updating program state.
L0161 | {% if issued_credentials.is_generated %} | Block delimiter controlling scope/structure in this language.
L0162 | <div class="small text-muted mt-1">Auto-generated by system</div> | Assignment statement storing or updating program state.
L0163 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0164 | </div> | Markup line defining structure in an HTML-like template file.

L0165 | </div> | Markup line defining structure in an HTML-like template file.

L0166 | <p class="text-muted small mt-3 mb-0">Existing passwords are stored as hashes and cannot be read back. A password is only shown

L0167 | </div> | Markup line defining structure in an HTML-like template file.

L0168 | </div> | Markup line defining structure in an HTML-like template file.

L0169 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0170 | | Blank line used for readability and logical separation.

L0171 | {% for role_key, role_label, role_icon, badge_class in role_groups %} | Block delimiter controlling scope/structure in this language

L0172 | {% set group = grouped.get(role_key, []) %} | Assignment statement storing or updating program state.

L0173 | {% if group %} | Block delimiter controlling scope/structure in this language.

L0174 | <section class="mb-5"> | Assignment statement storing or updating program state.

L0175 | <h5 class="mb-3"> | Assignment statement storing or updating program state.

L0176 | <i class="bi {{ role_icon }} me-2"></i>{{ role_label }} | Assignment statement storing or updating program state.

L0177 | {{ group|length }} | Assignment statement storing or updating program state

L0178 | </h5> | Markup line defining structure in an HTML-like template file.

L0179 | <div class="row g-3 profile-grid-row"> | Assignment statement storing or updating program state.

L0180 | {% for user in group %} | Block delimiter controlling scope/structure in this language.

L0181 | {% set gender_value = (user.gender or '')|lower %} | Assignment statement storing or updating program state.

L0182 | {% set avatar_key = avatar_choice_map.get(user.id, 'neutral') %} | Assignment statement storing or updating program state.

L0183 | {% set avatar_icon = avatar_icon_map.get(avatar_key, 'person-circle') %} | Assignment statement storing or updating program state

L0184 | {% set avatar_meta = namespace(label='Default') %} | Assignment statement storing or updating program state.

L0185 | {% for avatar in avatar_options %} | Block delimiter controlling scope/structure in this language.

L0186 | {% if avatar.key == avatar_key %} | Block delimiter controlling scope/structure in this language.

L0187 | {% set avatar_meta.label = avatar.label %} | Assignment statement storing or updating program state.

L0188 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0189 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0190 | <div class="col-12 col-md-6 col-xl-4"> | Assignment statement storing or updating program state.

L0191 | <div class="card profile-card role-{{ (user.role or 'user')|replace('_', '-')|lower }} h-100"> | Assignment statement storing or updating program state

L0192 | <div class="card-body"> | Assignment statement storing or updating program state.

L0193 | <div class="d-flex justify-content-between align-items-start gap-2 mb-2"> | Assignment statement storing or updating program state

L0194 | <div> | Markup line defining structure in an HTML-like template file.

L0195 | <h5 class="mb-0">{{ user.display_name }}</h5> | Assignment statement storing or updating program state.

L0196 | {% if user.uid %} | Block delimiter controlling scope/structure in this language.

L0197 | {{ user.uid }} |

L0198 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0199 | </div> | Markup line defining structure in an HTML-like template file.

L0200 | <div class="profile-identity-stack"> | Assignment statement storing or updating program state.

L0201 | <div class="profile-avatar-pill" data-avatar-key="{{ avatar_key }}" title="Avatar preset: {{ avatar_meta.label }}">

L0202 | <i class="bi bi-{{ avatar_icon }} avatar-glyph"></i> | Assignment statement storing or updating program state.

L0203 | {{ avatar_meta.label }} | Assignment statement storing or updating program state

L0204 | </div> | Markup line defining structure in an HTML-like template file.

L0205 | <div class="profile-gender-pill"> | Assignment statement storing or updating program state.

L0206 | {% if gender_value in ['female', 'f'] %} | Block delimiter controlling scope/structure in this language.

L0207 | <i class="bi bi-gender-female"></i>Female | Assignment statement storing or updating program state.

L0208 | {% elif gender_value in ['male', 'm'] %} | Block delimiter controlling scope/structure in this language.

L0209 | <i class="bi bi-gender-male"></i>Male | Assignment statement storing or updating program state.

L0210 | {% elif gender_value in ['other', 'o'] %} | Block delimiter controlling scope/structure in this language.

L0211 | <i class="bi bi-gender-ambiguous"></i>Other | Assignment statement storing or updating program state

L0212 | {% else %} | Block delimiter controlling scope/structure in this language.

L0213 | <i class="bi bi-person-fill"></i>Not set | Assignment statement storing or updating program state.

L0214 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0215 | </div> | Markup line defining structure in an HTML-like template file.

L0216 | </div> | Markup line defining structure in an HTML-like template file.

L0217 | </div> | Markup line defining structure in an HTML-like template file.

L0218 | <p class="mb-1">Region: {{ user.region or 'Not set' }}</p> | Assignment statement storing or updating

L0219 | <p class="mb-1">Email: {{ user.email }}</p> | Assignment statement storing or updating program state.

L0220 | <p class="mb-1">Status: | Assignment statement storing or updating program state.

L0221 | {% if user.is_blocked %} | Block delimiter controlling scope/structure in this language.

L0222 | Blocked | Assignment statement storing or updating program state.

L0223 | {% else %} | Block delimiter controlling scope/structure in this language.

L0224 | Active | Assignment statement storing or updating program state.

L0225 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0226 | </p> | Markup line defining structure in an HTML-like template file.

L0227 | <p class="mb-3">Since: {{ user.created_at.strftime('%Y-%m-%d') }}</p> | Assignment statement storing or updating program state.

L0228 | | Blank line used for readability and logical separation.

L0229 | <details class="mb-3"> | Assignment statement storing or updating program state.

L0230 | <summary class="fw-semibold" style="cursor:pointer;">Edit Profile</summary> | Assignment statement storing or updating program state.

L0231 | <form method="post" action="{% url_for('edit_user_profile', user_id=user.id) %}" class="mt-2"> | Assignment statement storing or updating program state.

L0232 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0233 | <input type="hidden" name="q" value="{{ search_query }}" /> | Assignment statement storing or updating program state.

L0234 | <div class="row g-2"> | Assignment statement storing or updating program state.

L0235 | <div class="col-12 col-md-6"> | Assignment statement storing or updating program state.

L0236 | <input type="text" name="first_name" class="form-control form-control-sm" value="{{ user.first_name or '' }}" /> | Assignment statement storing or updating program state.

L0237 | </div> | Markup line defining structure in an HTML-like template file.

L0238 | <div class="col-12 col-md-6"> | Assignment statement storing or updating program state.

L0239 | <input type="text" name="last_name" class="form-control form-control-sm" value="{{ user.last_name or '' }}" /> | Assignment statement storing or updating program state.

L0240 | </div> | Markup line defining structure in an HTML-like template file.

L0241 | <div class="col-12"> | Assignment statement storing or updating program state.

L0242 | <input type="email" name="email" class="form-control form-control-sm" value="{{ user.email }}" placeholder="Email" /> | Assignment statement storing or updating program state.

L0243 | </div> | Markup line defining structure in an HTML-like template file.

L0244 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.

L0245 | <input type="text" name="uid" class="form-control form-control-sm" value="{{ user.uid or '' }}" placeholder="UID" /> | Assignment statement storing or updating program state.

L0246 | </div> | Markup line defining structure in an HTML-like template file.

L0247 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.

L0248 | <input type="text" name="region" class="form-control form-control-sm" value="{{ user.region or '' }}" placeholder="Region" /> | Assignment statement storing or updating program state.

L0249 | </div> | Markup line defining structure in an HTML-like template file.

L0250 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.

L0251 | <select name="gender" class="form-select form-select-sm" aria-label="Gender for {{ user.email }}"> | Assignment statement storing or updating program state.

L0252 | <option value="" {% if not user.gender %}selected{% endif %}>Gender</option> | Assignment statement storing or updating program state.

L0253 | <option value="male" {% if (user.gender or '')|lower == 'male' %}selected{% endif %}>Male</option> | Markup line defining structure in an HTML-like template file.

L0254 | <option value="female" {% if (user.gender or '')|lower == 'female' %}selected{% endif %}>Female</option> | Markup line defining structure in an HTML-like template file.

L0255 | <option value="other" {% if (user.gender or '')|lower == 'other' %}selected{% endif %}>Other</option> | Markup line defining structure in an HTML-like template file.

L0256 | </select> | Markup line defining structure in an HTML-like template file.

L0257 | </div> | Markup line defining structure in an HTML-like template file.

L0258 | <div class="col-12"> | Assignment statement storing or updating program state.

L0259 | <div class="avatar-pick-group" role="group" aria-label="Avatar preset for {{ user.email }}"> | Assignment statement storing or updating program state.

L0260 | {% for avatar in avatar_options %} | Block delimiter controlling scope/structure in this language.

L0261 | <label class="avatar-pick-tile{% if avatar_key == avatar.key %} is-selected{% endif %}" title="{{ avatar.label }}"> | Assignment statement storing or updating program state.

L0262 | <input type="radio" name="avatar_key" value="{{ avatar.key }}" {% if avatar_key == avatar.key %}checked{% endif %} /> | Assignment statement storing or updating program state.

L0263 | <i class="bi bi-{{ avatar.icon }}"></i> | Assignment statement storing or updating program state.

L0264 | {{ avatar.label }} | Markup line defining structure in an HTML-like template file.

L0265 | </label> | Markup line defining structure in an HTML-like template file.

L0266 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0267 | </div> | Markup line defining structure in an HTML-like template file.

L0268 | </div> | Markup line defining structure in an HTML-like template file.

L0269 | <div class="col-12"> | Assignment statement storing or updating program state.

L0270 | <input type="text" name="support_desk" class="form-control form-control-sm" value="{{ user.support_desk or '' }}" /> | Assignment statement storing or updating program state.

L0271 | </div> | Markup line defining structure in an HTML-like template file.

L0272 | <div class="col-12 col-md-6"> | Assignment statement storing or updating program state.

L0273 | <input type="text" name="site_operations_phone" class="form-control form-control-sm" value="{{ user.site_operations_phone or '' }}" /> | Assignment statement storing or updating program state.

L0274 | </div> | Markup line defining structure in an HTML-like template file.

L0275 | <div class="col-12 col-md-6"> | Assignment statement storing or updating program state.

L0276 | <input type="text" name="emergency_phone" class="form-control form-control-sm" value="{{ user.emergency_phone }}" /> | Assignment statement storing or updating program state.

L0277 | </div> | Markup line defining structure in an HTML-like template file.

L0278 | </div> | Markup line defining structure in an HTML-like template file.

L0279 | <div class="mt-2 d-flex justify-content-end"> | Assignment statement storing or updating program state.

L0280 | <button type="submit" class="btn btn-sm btn-primary">Save Profile</button> | Assignment statement storing or updating program state.

L0281 | </div> | Markup line defining structure in an HTML-like template file.

L0282 | </form> | Markup line defining structure in an HTML-like template file.

L0283 | </details> | Markup line defining structure in an HTML-like template file.

L0284 | | Blank line used for readability and logical separation.

L0285 | {% if user.id != current_user.id %} | Block delimiter controlling scope/structure in this language.

L0286 | <div class="d-flex gap-2 flex-wrap"> | Assignment statement storing or updating program state.

L0287 | <form method="post" action="{{ url_for('toggle_user_block', user_id=user.id) }}"> | Assignment statement storing or updating program state.

L0288 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0289 | <input type="hidden" name="q" value="{{ search_query }}" /> | Assignment statement storing or updating program state.

L0290 | <button type="submit" class="btn btn-sm {% if user.is_blocked %}btn-success{% else %}btn-outline-warning{% endif %}"> | Assignment statement storing or updating program state.

L0291 | {% if user.is_blocked %}<i class="bi bi-unlock-fill me-1"></i>Unblock{% else %}<i class="bi bi-lock-fill me-1"></i>Lock{% endif %}</button> | Assignment statement storing or updating program state.

L0292 | </button> | Markup line defining structure in an HTML-like template file.

L0293 | </form> | Markup line defining structure in an HTML-like template file.

L0294 | <form method="post" action="{{ url_for('reset_user_password', user_id=user.id) }}" data-reset-password-form="true" data-confirm-message="Delete {{ user.display_name }} ({{ user.uid or user.id }})? This cannot be undone." data-confirm-title="Delete User" data-confirm-label="Yes, delete"> | Assignment statement storing or updating program state.

L0295 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0296 | <input type="hidden" name="q" value="{{ search_query }}" /> | Assignment statement storing or updating program state.

L0297 | <input type="password" name="current_password" autocomplete="current-password" class="form-control form-control-sm" /> | Assignment statement storing or updating program state.

L0298 | <input type="password" name="new_password" autocomplete="new-password" class="form-control form-control-sm mt-1" /> | Assignment statement storing or updating program state.

L0299 | <button type="submit" class="btn btn-sm btn-outline-primary"> | Assignment statement storing or updating program state.

L0300 | <i class="bi bi-key-fill me-1"></i>Reset Password | Assignment statement storing or updating program state.

L0301 | </button> | Markup line defining structure in an HTML-like template file.

L0302 | </form> | Markup line defining structure in an HTML-like template file.

L0303 | <form method="post" action="{{ url_for('delete_user', user_id=user.id) }}" data-confirm-message="Delete {{ user.display_name }} ({{ user.uid or user.id }})? This cannot be undone." data-confirm-title="Delete User" data-confirm-label="Yes, delete"> | Assignment statement storing or updating program state.

L0304 | data-confirm-message="Delete {{ user.display_name }} ({{ user.uid or user.id }})? This cannot be undone." | Assignment statement storing or updating program state.

L0305 | data-confirm-title="Delete User" | Assignment statement storing or updating program state.

L0306 | data-confirm-label="Yes, delete" | Assignment statement storing or updating program state.

L0307 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0308 | <input type="hidden" name="q" value="{{ search_query }}" /> | Assignment statement storing or updating program state.

L0309 | <button type="submit" class="btn btn-sm btn-outline-danger"> | Assignment statement storing or updating program state.

L0310 | <i class="bi bi-trash-fill me-1"></i>Delete | Assignment statement storing or updating program state.

L0311 | </button> | Markup line defining structure in an HTML-like template file.

L0312 | </form> | Markup line defining structure in an HTML-like template file.

L0313 | </div> | Markup line defining structure in an HTML-like template file.

L0314 | {% else %} | Block delimiter controlling scope/structure in this language.

L0315 | Current user. Profile edits are allowed here, but block, delete, and password reset actions are disabled. | Assignment statement storing or updating program state.

L0316 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0317 | </div> | Markup line defining structure in an HTML-like template file.

L0318 | </div> | Markup line defining structure in an HTML-like template file.

L0319 | </div> | Markup line defining structure in an HTML-like template file.

L0320 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0321 | </div> | Markup line defining structure in an HTML-like template file.

L0322 | </section> | Markup line defining structure in an HTML-like template file.

L0323 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0324 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0325 | | Blank line used for readability and logical separation.

L0326 | {% if pagination and pagination.pages > 1 %} | Block delimiter controlling scope/structure in this language.

L0327 | <nav aria-label="User pagination" class="mt-3"> | Assignment statement storing or updating program state.

L0328 | <ul class="pagination flex-wrap"> | Assignment statement storing or updating program state.


```

L0329 | <li class="page-item {% if not pagination.has_prev %}disabled{% endif %}"> | Assignment statement storing or updating program s
L0330 | <a class="page-link" href="{% url_for('admin_staff', q=search_query or None, page=pagination.prev_num, per_page=pagination.pe
L0331 | </li> | Markup line defining structure in an HTML-like template file.
L0332 | {% for page_num in pagination.iter_pages(left_edge=1, left_current=2, right_current=2, right_edge=1) %} | Assignment statement
L0333 | {% if page_num %} | Block delimiter controlling scope/structure in this language.
L0334 | <li class="page-item {% if page_num == pagination.page %}active{% endif %}"> | Markup line defining structure in an HTML-like
L0335 | <a class="page-link" href="{% url_for('admin_staff', q=search_query or None, page=page_num, per_page=pagination.per_page) %}
L0336 | </li> | Markup line defining structure in an HTML-like template file.
L0337 | {% else %} | Block delimiter controlling scope/structure in this language.
L0338 | <li class="page-item disabled"><span class="page-link">...</span></li> | Assignment statement storing or updating program sta
L0339 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0340 | {% endfor %} | Block delimiter controlling scope/structure in this language.
L0341 | <li class="page-item {% if not pagination.has_next %}disabled{% endif %}"> | Assignment statement storing or updating program s
L0342 | <a class="page-link" href="{% url_for('admin_staff', q=search_query or None, page=pagination.next_num, per_page=pagination.pe
L0343 | </li> | Markup line defining structure in an HTML-like template file.
L0344 | </ul> | Markup line defining structure in an HTML-like template file.
L0345 | </nav> | Markup line defining structure in an HTML-like template file.
L0346 | <p class="text-muted small">Showing {{ users|length }} of {{ matched_users }} matched users on page {{ pagination.page }} of {{ pa
L0347 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0348 | | Blank line used for readability and logical separation.
L0349 | {% if total_users == 0 %} | Block delimiter controlling scope/structure in this language.
L0350 | <p class="text-muted mt-4">No users yet. Use the buttons above to add accounts.</p> | Assignment statement storing or updating prog
L0351 | {% elif matched_users == 0 %} | Block delimiter controlling scope/structure in this language.
L0352 | <p class="text-muted mt-4">No users matched your search. Try UID, role, email, name, or region.</p> | Assignment statement storing
L0353 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0354 | | Blank line used for readability and logical separation.
L0355 | <script> | Markup line defining structure in an HTML-like template file.
L0356 | document.querySelectorAll('form[data-reset-password-form="true"]').forEach(function (form) { | Assignment statement storing or up
L0357 | form.addEventListener("submit", function (event) { | Block delimiter controlling scope/structure in this language.
L0358 | event.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0359 | var displayName = form.getAttribute("data-user-display-name") || "this user"; | Assignment statement storing or updating pr
L0360 | var newPasswordInput = form.querySelector('input[name="new_password"]'); | Assignment statement storing or updating program s
L0361 | var enteredNewPassword = (newPasswordInput && newPasswordInput.value ? newPasswordInput.value : "").trim(); | Assignment stat
L0362 | var confirmMessage = enteredNewPassword | Assignment statement storing or updating program state.
L0363 | ? "Reset password for " + displayName + " using the entered new password?" | Operational statement participating in the fil
L0364 | : "Reset password for " + displayName + "? A new temporary password will be generated."; | Operational statement participat
L0365 | | Blank line used for readability and logical separation.
L0366 | if (typeof window.appConfirm === "function") { | Conditional branch that runs only when its condition is true.
L0367 | window.appConfirm({ | Block delimiter controlling scope/structure in this language.
L0368 | title: "Reset Password", | Operational statement participating in the file's runtime behavior.
L0369 | message: confirmMessage, | Operational statement participating in the file's runtime behavior.
L0370 | confirmLabel: "Yes, reset", | Operational statement participating in the file's runtime behavior.
L0371 | cancelLabel: "No" | Operational statement participating in the file's runtime behavior.
L0372 | }).then(function (confirmed) { | Block delimiter controlling scope/structure in this language.
L0373 | if (confirmed) { | Conditional branch that runs only when its condition is true.
L0374 | form.submit(); | Operational statement participating in the file's runtime behavior.
L0375 | } | Block delimiter controlling scope/structure in this language.
L0376 | }); | Operational statement participating in the file's runtime behavior.
L0377 | } else { | Block delimiter controlling scope/structure in this language.
L0378 | form.submit(); | Operational statement participating in the file's runtime behavior.
L0379 | } | Block delimiter controlling scope/structure in this language.
L0380 | }); | Operational statement participating in the file's runtime behavior.
L0381 | }); | Operational statement participating in the file's runtime behavior.
L0382 | </script> | Markup line defining structure in an HTML-like template file.
L0383 | | Blank line used for readability and logical separation.

```

L0384 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 97: templates/consumable_detail.html

L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.

L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.

L0003 | <div class="detail-header d-flex align-items-center justify-content-between mb-3"> | Assignment statement storing or updating program state.

L0004 | <div><h1>CONSUMABLES
<DETAILS</h1></div> | Markup line defining structure in an HTML-like template file.

L0005 | <div class="d-flex gap-3 align-items-center"> | Assignment statement storing or updating program state.

L0006 | <div class="detail-logo-box text-center"> | Assignment statement storing or updating program state.

L0007 | <i class="bi bi-building" style="font-size: 1.8rem;color:#1c4da8;"></i> | Assignment statement storing or updating program state.

L0008 | <div class="logo-label">ATC Uganda</div> | Assignment statement storing or updating program state.

L0009 | </div> | Markup line defining structure in an HTML-like template file.

L0010 | <div class="detail-logo-box text-center"> | Assignment statement storing or updating program state.

L0011 | <i class="bi bi-rainbow" style="font-size: 1.8rem;color:#d42116;"></i> | Assignment statement storing or updating program state.

L0012 | <div class="logo-label">Soliton Telmec</div> | Assignment statement storing or updating program state.

L0013 | </div> | Markup line defining structure in an HTML-like template file.

L0014 | </div> | Markup line defining structure in an HTML-like template file.

L0015 | </div> | Markup line defining structure in an HTML-like template file.

L0016 | <div class="card detail-card p-4"> | Assignment statement storing or updating program state.

L0017 | <div class="row"> | Assignment statement storing or updating program state.

L0018 | <div class="col-md-6"> | Assignment statement storing or updating program state.

L0019 | <p>Site ID: {{ item.site_id }}</p> | Markup line defining structure in an HTML-like template file.

L0020 | <p>Site Name: {{ item.site_name }}</p> | Markup line defining structure in an HTML-like template file.

L0021 | <p>Description: {{ item.description }}</p> | Markup line defining structure in an HTML-like template file.

L0022 | <p>Created By: {{ item.created_by }}</p> | Markup line defining structure in an HTML-like template file.

L0023 | <p>Created Date: {{ item.created_at.strftime('%a %b %d %Y') }}</p> | Markup line defining structure in an HTML-like template file.

L0024 | <p>Location: {{ item.location }}</p> | Markup line defining structure in an HTML-like template file.

L0025 | </div> | Markup line defining structure in an HTML-like template file.

L0026 | <div class="col-md-6"> | Assignment statement storing or updating program state.

L0027 | Signage Image
 | Markup line defining structure in an HTML-like template file.

L0028 | {% if item.signage_image_url %} | Block delimiter controlling scope/structure in this language.

L0029 | | Assignment statement storing or updating program state.

L0030 | {% else %} | Block delimiter controlling scope/structure in this language.

L0031 | None | Markup line defining structure in an HTML-like template file.

L0032 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0033 | </div> | Markup line defining structure in an HTML-like template file.

L0034 | </div> | Markup line defining structure in an HTML-like template file.

L0035 | | Blank line used for readability and logical separation.

L0036 | <div class="row mt-3"> | Assignment statement storing or updating program state.

L0037 | <div class="col-md-6"> | Assignment statement storing or updating program state.

L0038 | Screenshot Image
 | Markup line defining structure in an HTML-like template file.

L0039 | {% if item.screenshot_url %} | Block delimiter controlling scope/structure in this language.

L0040 | | Assignment statement storing or updating program state.

L0041 | {% else %} | Block delimiter controlling scope/structure in this language.

L0042 | None | Markup line defining structure in an HTML-like template file.

L0043 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0044 | </div> | Markup line defining structure in an HTML-like template file.

L0045 | <div class="col-md-6"> | Assignment statement storing or updating program state.

L0046 | Before Usage Image
 | Markup line defining structure in an HTML-like template file.

L0047 | {% if item.before_usage_image_url %} | Block delimiter controlling scope/structure in this language.

L0048 | | Assignment statement storing or updating program state.

L0049 | {% else %} | Block delimiter controlling scope/structure in this language.

L0050 | None | Markup line defining structure in an HTML-like template file.

L0051 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0052 | </div> | Markup line defining structure in an HTML-like template file.

L0053 | </div> | Markup line defining structure in an HTML-like template file.

L0054 | | Blank line used for readability and logical separation.

L0055 | Back to list | Assignment statement storing or updating

L0056 | </div> | Markup line defining structure in an HTML-like template file.

L0057 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 98: templates/consumables.html

```
L0001 | {% extends "layout.html" %} | Block delimiter controlling scope/structure in this language.
L0002 | | Blank line used for readability and logical separation.
L0003 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0004 | <h1>Consumables List</h1> | Markup line defining structure in an HTML-like template file.
L0005 | <div class="card mt-3 mb-3 p-3"> | Assignment statement storing or updating program state.
L0006 | <h5>Add new consumable (desk team)</h5> | Markup line defining structure in an HTML-like template file.
L0007 | <form method="post" enctype="multipart/form-data" class="row g-3"> | Assignment statement storing or updating program state.
L0008 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.
L0009 | <div class="col-md-2"> | Assignment statement storing or updating program state.
L0010 | <label class="form-label">Site ID</label> | Assignment statement storing or updating program state.
L0011 | <input name="site_id" class="form-control" required /> | Assignment statement storing or updating program state.
L0012 | </div> | Markup line defining structure in an HTML-like template file.
L0013 | <div class="col-md-3"> | Assignment statement storing or updating program state.
L0014 | <label class="form-label">Site Name</label> | Assignment statement storing or updating program state.
L0015 | <input name="site_name" class="form-control" required /> | Assignment statement storing or updating program state.
L0016 | </div> | Markup line defining structure in an HTML-like template file.
L0017 | <div class="col-md-3"> | Assignment statement storing or updating program state.
L0018 | <label class="form-label">Created By</label> | Assignment statement storing or updating program state.
L0019 | <input name="created_by" class="form-control" value="{{ current_user.email }}" readonly /> | Assignment statement storing or updating program state.
L0020 | </div> | Markup line defining structure in an HTML-like template file.
L0021 | <div class="col-md-4"> | Assignment statement storing or updating program state.
L0022 | <label class="form-label">Location</label> | Assignment statement storing or updating program state.
L0023 | <input name="location" class="form-control" placeholder="e.g. 0.4591N 31.6836E" /> | Assignment statement storing or updating program state.
L0024 | </div> | Markup line defining structure in an HTML-like template file.
L0025 | <div class="col-12"> | Assignment statement storing or updating program state.
L0026 | <label class="form-label">Description</label> | Assignment statement storing or updating program state.
L0027 | <textarea name="description" class="form-control" rows="2" required></textarea> | Assignment statement storing or updating program state.
L0028 | </div> | Markup line defining structure in an HTML-like template file.
L0029 | <div class="col-md-4"> | Assignment statement storing or updating program state.
L0030 | <label class="form-label">Signage Image URL</label> | Assignment statement storing or updating program state.
L0031 | <input name="signage_image_url" class="form-control" placeholder="http://..." /> | Assignment statement storing or updating program state.
L0032 | </div> | Markup line defining structure in an HTML-like template file.
L0033 | <div class="col-md-4"> | Assignment statement storing or updating program state.
L0034 | <label class="form-label">WhatsApp Screenshot URL</label> | Assignment statement storing or updating program state.
L0035 | <input name="screenshot_url" class="form-control" placeholder="http://..." /> | Assignment statement storing or updating program state.
L0036 | </div> | Markup line defining structure in an HTML-like template file.
L0037 | <div class="col-md-4"> | Assignment statement storing or updating program state.
L0038 | <label class="form-label">Before Usage Image URL</label> | Assignment statement storing or updating program state.
L0039 | <input name="before_usage_image_url" class="form-control" placeholder="http://..." /> | Assignment statement storing or updating program state.
L0040 | </div> | Markup line defining structure in an HTML-like template file.
L0041 | <div class="col-md-4"> | Assignment statement storing or updating program state.
L0042 | <label class="form-label">Signage Image File</label> | Assignment statement storing or updating program state.
L0043 | <input name="signage_image_file" type="file" accept="image/*" class="form-control" /> | Assignment statement storing or updating program state.
L0044 | </div> | Markup line defining structure in an HTML-like template file.
L0045 | <div class="col-md-4"> | Assignment statement storing or updating program state.
L0046 | <label class="form-label">WhatsApp Screenshot File</label> | Assignment statement storing or updating program state.
L0047 | <input name="screenshot_file" type="file" accept="image/*" class="form-control" /> | Assignment statement storing or updating program state.
L0048 | </div> | Markup line defining structure in an HTML-like template file.
L0049 | <div class="col-md-4"> | Assignment statement storing or updating program state.
L0050 | <label class="form-label">Before Usage Image File</label> | Assignment statement storing or updating program state.
L0051 | <input name="before_usage_file" type="file" accept="image/*" class="form-control" /> | Assignment statement storing or updating program state.
L0052 | </div> | Markup line defining structure in an HTML-like template file.
L0053 | <div class="col-12 text-end"> | Assignment statement storing or updating program state.
```

L0054 | <button type="submit" class="btn btn-primary">Save Consumable</button> | Assignment statement storing or updating program state.

L0055 | </div> | Markup line defining structure in an HTML-like template file.

L0056 | </form> | Markup line defining structure in an HTML-like template file.

L0057 | </div> | Markup line defining structure in an HTML-like template file.

L0058 | <div class="card mb-3 p-3"> | Assignment statement storing or updating program state.

L0059 | <form method="get" class="row g-2 align-items-end"> | Assignment statement storing or updating program state.

L0060 | <div class="col-12 col-lg-10"> | Assignment statement storing or updating program state.

L0061 | <label class="form-label">Search consumables</label> | Assignment statement storing or updating program state.

L0062 | <input name="q" type="search" class="form-control" value="{{ search_query or '' }}" placeholder="Search by site ID, site name"> | Assignment statement storing or updating program state.

L0063 | </div> | Markup line defining structure in an HTML-like template file.

L0064 | <div class="col-6 col-lg-1 d-grid"> | Assignment statement storing or updating program state.

L0065 | <button type="submit" class="btn btn-primary">Search</button> | Assignment statement storing or updating program state.

L0066 | </div> | Markup line defining structure in an HTML-like template file.

L0067 | <div class="col-6 col-lg-1 d-grid"> | Assignment statement storing or updating program state.

L0068 | Clear | Assignment statement storing or updating program state.

L0069 | </div> | Markup line defining structure in an HTML-like template file.

L0070 | </form> | Markup line defining structure in an HTML-like template file.

L0071 | </div> | Markup line defining structure in an HTML-like template file.

L0072 | <div class="table-responsive"> | Assignment statement storing or updating program state.

L0073 | <table class="table table-hover align-middle mt-3 consumables-table"> | Assignment statement storing or updating program state.

L0074 | <thead class="table-light"> | Assignment statement storing or updating program state.

L0075 | <tr> | Markup line defining structure in an HTML-like template file.

L0076 | <th>#</th> | Markup line defining structure in an HTML-like template file.

L0077 | <th>Site ID</th> | Markup line defining structure in an HTML-like template file.

L0078 | <th>Site Name</th> | Markup line defining structure in an HTML-like template file.

L0079 | <th>Description</th> | Markup line defining structure in an HTML-like template file.

L0080 | <th>Created By</th> | Markup line defining structure in an HTML-like template file.

L0081 | <th>Created Date</th> | Markup line defining structure in an HTML-like template file.

L0082 | <th>Actions</th> | Markup line defining structure in an HTML-like template file.

L0083 | </tr> | Markup line defining structure in an HTML-like template file.

L0084 | </thead> | Markup line defining structure in an HTML-like template file.

L0085 | <tbody> | Markup line defining structure in an HTML-like template file.

L0086 | {% for item in consumables %} | Block delimiter controlling scope/structure in this language.

L0087 | <tr> | Markup line defining structure in an HTML-like template file.

L0088 | <td data-label="#">{{ loop.index }}</td> | Assignment statement storing or updating program state.

L0089 | <td data-label="Site ID">{{ item.site_id }}</td> | Assignment statement storing or updating program state.

L0090 | <td data-label="Site Name">{{ item.site_name }}</td> | Assignment statement storing or updating program state.

L0091 | <td data-label="Description">{{ item.description }}</td> | Assignment statement storing or updating program state.

L0092 | <td data-label="Created By">{{ item.created_by }}</td> | Assignment statement storing or updating program state.

L0093 | <td data-label="Created Date">{{ item.created_at.strftime('%m/%d/%Y, %I:%M:%S %p') }}</td> | Assignment statement storing or updating program state.

L0094 | <td data-label="Actions" class="d-flex gap-2"> | Assignment statement storing or updating program state.

L0095 | <button | Operational statement participating in the file's runtime behavior.

L0096 | type="button" | Assignment statement storing or updating program state.

L0097 | class="btn btn-sm btn-primary" | Assignment statement storing or updating program state.

L0098 | data-bs-toggle="modal" | Assignment statement storing or updating program state.

L0099 | data-bs-target="#consumableDetailModal" | Assignment statement storing or updating program state.

L0100 | data-item-id="{{ item.id }}" | Assignment statement storing or updating program state.

L0101 | data-site-id="{{ item.site_id }}" | Assignment statement storing or updating program state.

L0102 | data-site-name="{{ item.site_name }}" | Assignment statement storing or updating program state.

L0103 | data-description="{{ item.description|e }}" | Assignment statement storing or updating program state.

L0104 | data-created-by="{{ item.created_by }}" | Assignment statement storing or updating program state.

L0105 | data-created-date="{{ item.created_at.strftime('%a %b %d %Y') }}" | Assignment statement storing or updating program state.

L0106 | data-location="{{ item.location or '' }}" | Assignment statement storing or updating program state.

L0107 | data-signage="{{ item.signage_image_url or '' }}" | Assignment statement storing or updating program state.

L0108 | data-screenshot="{{ item.screenshot_url or '' }}" | Assignment statement storing or updating program state.

L0109 | data-before="{ { item.before_usage_image_url or ' ' } }" | Assignment statement storing or updating program state.

L0110 | > | Operational statement participating in the file's runtime behavior.

L0111 | <i class="bi bi-eye"></i> | Assignment statement storing or updating program state.

L0112 | </button> | Markup line defining structure in an HTML-like template file.

L0113 | Open | Assignment statement storing or updating program state.

L0114 | </td> | Markup line defining structure in an HTML-like template file.

L0115 | </tr> | Markup line defining structure in an HTML-like template file.

L0116 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0117 | {% if not consumables %} | Block delimiter controlling scope/structure in this language.

L0118 | <tr> | Markup line defining structure in an HTML-like template file.

L0119 | <td colspan="7" class="text-center text-muted py-4">No consumables matched this view.</td> | Assignment statement storing or updating program state.

L0120 | </tr> | Markup line defining structure in an HTML-like template file.

L0121 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0122 | </tbody> | Markup line defining structure in an HTML-like template file.

L0123 | </table> | Markup line defining structure in an HTML-like template file.

L0124 | </div> | Markup line defining structure in an HTML-like template file.

L0125 | | Blank line used for readability and logical separation.

L0126 | {% if pagination and pagination.pages > 1 %} | Block delimiter controlling scope/structure in this language.

L0127 | <nav aria-label="Consumables pagination" class="mt-3"> | Assignment statement storing or updating program state.

L0128 | <ul class="pagination flex-wrap"> | Assignment statement storing or updating program state.

L0129 | <li class="page-item {% if not pagination.has_prev %}disabled{% endif %}"> | Assignment statement storing or updating program state.

L0130 | | Assignment statement storing or updating program state.

L0131 | | Markup line defining structure in an HTML-like template file.

L0132 | {% for page_num in pagination.iter_pages(left_edge=1, left_current=2, right_current=2, right_edge=1) %} | Assignment statement storing or updating program state.

L0133 | {% if page_num %} | Block delimiter controlling scope/structure in this language.

L0134 | <li class="page-item {% if page_num == pagination.page %}active{% endif %}"> | Markup line defining structure in an HTML-like template file.

L0135 | | Assignment statement storing or updating program state.

L0136 | | Markup line defining structure in an HTML-like template file.

L0137 | {% else %} | Block delimiter controlling scope/structure in this language.

L0138 | <li class="page-item disabled">... | Assignment statement storing or updating program state.

L0139 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0140 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0141 | <li class="page-item {% if not pagination.has_next %}disabled{% endif %}"> | Assignment statement storing or updating program state.

L0142 | | Assignment statement storing or updating program state.

L0143 | | Markup line defining structure in an HTML-like template file.

L0144 | | Markup line defining structure in an HTML-like template file.

L0145 | </nav> | Markup line defining structure in an HTML-like template file.

L0146 | <p class="text-muted small">Showing { { consumables\|length } } of { { pagination.total } } consumables on page { { pagination.page } } </p> | Assignment statement storing or updating program state.

L0147 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0148 | | Blank line used for readability and logical separation.

L0149 | <div class="modal fade" id="consumableDetailModal" tabindex="-1" aria-labelledby="consumableDetailModalLabel" aria-hidden="true"> | Assignment statement storing or updating program state.

L0150 | <div class="modal-dialog modal-dialog-scrollable modal-lg"> | Assignment statement storing or updating program state.

L0151 | <div class="modal-content"> | Assignment statement storing or updating program state.

L0152 | <div class="modal-header"> | Assignment statement storing or updating program state.

L0153 | <h5 class="modal-title" id="consumableDetailModalLabel">CONSUMABLES DETAILS</h5> | Assignment statement storing or updating program state.

L0154 | <button type="button" class="btn-close" data-bs-dismiss="modal" aria-label="Close"></button> | Assignment statement storing or updating program state.

L0155 | </div> | Markup line defining structure in an HTML-like template file.

L0156 | <div class="modal-body"> | Assignment statement storing or updating program state.

L0157 | <div class="row g-3"> | Assignment statement storing or updating program state.

L0158 | <div class="col-md-6">Site ID: </div> | Assignment statement storing or updating program state.

L0159 | <div class="col-md-6">Created Date: </div> | Assignment statement storing or updating program state.

L0160 | <div class="col-md-6">Site Name: </div> | Assignment statement storing or updating program state.

L0161 | <div class="col-md-6">Created By: </div> | Assignment statement storing or updating program state.

L0162 | <div class="col-12">Description: </div> | Assignment statement storing or updating program state.

L0163 | <div class="col-12">Location: </div> | Assignment statement storing or updating program state.

L0164 | </div> | Markup line defining structure in an HTML-like template file.

L0165 | | Blank line used for readability and logical separation.

L0166 | <hr /> | Markup line defining structure in an HTML-like template file.

L0167 | | Blank line used for readability and logical separation.

L0168 | <div class="mb-3"> | Assignment statement storing or updating program state.

L0169 | <h5>Signage Image</h5> | Markup line defining structure in an HTML-like template file.

L0170 | | Assignment statement storing or updating program state.

L0171 | </div> | Markup line defining structure in an HTML-like template file.

L0172 | <div class="mb-3"> | Assignment statement storing or updating program state.

L0173 | <h5>Screenshot Image</h5> | Markup line defining structure in an HTML-like template file.

L0174 | | Assignment statement storing or updating program state.

L0175 | </div> | Markup line defining structure in an HTML-like template file.

L0176 | <div class="mb-3"> | Assignment statement storing or updating program state.

L0177 | <h5>Before Usage Images</h5> | Markup line defining structure in an HTML-like template file.

L0178 | | Assignment statement storing or updating program state.

L0179 | </div> | Markup line defining structure in an HTML-like template file.

L0180 | </div> | Markup line defining structure in an HTML-like template file.

L0181 | <div class="modal-footer"> | Assignment statement storing or updating program state.

L0182 | Open Full Page | Assignment statement storing or updating program state.

L0183 | <button type="button" class="btn btn-primary" data-bs-dismiss="modal">Close</button> | Assignment statement storing or updating program state.

L0184 | </div> | Markup line defining structure in an HTML-like template file.

L0185 | </div> | Markup line defining structure in an HTML-like template file.

L0186 | </div> | Markup line defining structure in an HTML-like template file.

L0187 | </div> | Markup line defining structure in an HTML-like template file.

L0188 | | Blank line used for readability and logical separation.

L0189 | <script> | Markup line defining structure in an HTML-like template file.

L0190 | document.addEventListener('DOMContentLoaded', function () { | Block delimiter controlling scope/structure in this language.

L0191 | const modal = document.getElementById('consumableDetailModal'); | Assignment statement storing or updating program state.

L0192 | if (!modal) { | Conditional branch that runs only when its condition is true.

L0193 | return; | Returns a value (or control) back to the caller.

L0194 | } | Block delimiter controlling scope/structure in this language.

L0195 | | Blank line used for readability and logical separation.

L0196 | function setImageOrFallback(el, url) { | Block delimiter controlling scope/structure in this language.

L0197 | if (url) { | Conditional branch that runs only when its condition is true.

L0198 | el.src = url; | Assignment statement storing or updating program state.

L0199 | el.style.display = 'block'; | Assignment statement storing or updating program state.

L0200 | } else { | Block delimiter controlling scope/structure in this language.

L0201 | el.removeAttribute('src'); | Operational statement participating in the file's runtime behavior.

L0202 | el.style.display = 'none'; | Assignment statement storing or updating program state.

L0203 | } | Block delimiter controlling scope/structure in this language.

L0204 | } | Block delimiter controlling scope/structure in this language.

L0205 | | Blank line used for readability and logical separation.

L0206 | modal.addEventListener('show.bs.modal', function (event) { | Block delimiter controlling scope/structure in this language.

L0207 | const trigger = event.relatedTarget; | Assignment statement storing or updating program state.

L0208 | if (!trigger) { | Conditional branch that runs only when its condition is true.

L0209 | return; | Returns a value (or control) back to the caller.

L0210 | } | Block delimiter controlling scope/structure in this language.

L0211 | | Blank line used for readability and logical separation.

L0212 | const itemId = trigger.getAttribute('data-item-id') || ''; | Assignment statement storing or updating program state.

L0213 | document.getElementById('modalSiteId').textContent = trigger.getAttribute('data-site-id') || '-'; | Assignment statement storing or updating program state.

L0214 | document.getElementById('modalCreatedDate').textContent = trigger.getAttribute('data-created-date') || '-'; | Assignment statement storing or updating program state.

L0215 | document.getElementById('modalSiteName').textContent = trigger.getAttribute('data-site-name') || '-'; | Assignment statement storing or updating program state.

L0216 | document.getElementById('modalCreatedBy').textContent = trigger.getAttribute('data-created-by') || '-'; | Assignment statement storing or updating program state.

L0217 | document.getElementById('modalDescription').textContent = trigger.getAttribute('data-description') || '-'; | Assignment statement storing or updating program state.

L0218 | document.getElementById('modalLocation').textContent = trigger.getAttribute('data-location') || '-'; | Assignment statement storing or updating program state.

L0219 | | Blank line used for readability and logical separation.

L0220 | setImageOrFallback(document.getElementById('modalSignage'), trigger.getAttribute('data-signage') \\|\\| ''); | Operational stat

L0221 | setImageOrFallback(document.getElementById('modalScreenshot'), trigger.getAttribute('data-screenshot') \\|\\| ''); | Operationa

L0222 | setImageOrFallback(document.getElementById('modalBeforeUsage'), trigger.getAttribute('data-before') \\|\\| ''); | Operational s

L0223 | | Blank line used for readability and logical separation.

L0224 | document.getElementById('modalOpenPageLink').href = '/consumables/' + itemId + '/'; | Assignment statement storing or updatin

L0225 | }); | Operational statement participating in the file's runtime behavior.

L0226 | }); | Operational statement participating in the file's runtime behavior.

L0227 | </script> | Markup line defining structure in an HTML-like template file.

L0228 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 99: templates/dashboard.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <div class="role-dashboard-shell role-{{ (current_role or 'user')\|replace('_', '-')\|lower }}"> | Assignment statement storing or
L0004 | <section class="dashboard-hero-lite"> | Assignment statement storing or updating program state.
L0005 |   <h1>Hello, {{ user_name }}. Welcome back!</h1> | Markup line defining structure in an HTML-like template file.
L0006 | </section> | Markup line defining structure in an HTML-like template file.
L0007 | | Blank line used for readability and logical separation.
L0008 | {% if current_role in ['manager', 'general_manager'] %} | Block delimiter controlling scope/structure in this language.
L0009 | <div class="row row-cols-1 row-cols-md-3 g-3 mt-1"> | Assignment statement storing or updating program state.
L0010 |   <div class="col"> | Assignment statement storing or updating program state.
L0011 |     <a href="{{ url_for('desk_activities', mode='rcas') }}" class="card-link"> | Assignment statement storing or updating program s
L0012 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0013 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0014 |           <div class="stats-icon"><i class="bi bi-journal-check"></i></div> | Assignment statement storing or updating program sta
L0015 |           <h1 data-count-key="pending_pm_rcas">{{ pending_pm_rcas }}</h1> | Assignment statement storing or updating program state.
L0016 |           <p>PM RCAs To Review</p> | Markup line defining structure in an HTML-like template file.
L0017 |         </div> | Markup line defining structure in an HTML-like template file.
L0018 |       </div> | Markup line defining structure in an HTML-like template file.
L0019 |     </a> | Markup line defining structure in an HTML-like template file.
L0020 |   </div> | Markup line defining structure in an HTML-like template file.
L0021 | <div class="col"> | Assignment statement storing or updating program state.
L0022 |   <a href="{{ url_for('desk_activities', mode='forms') }}" class="card-link"> | Assignment statement storing or updating program
L0023 |     <div class="card stats-card"> | Assignment statement storing or updating program state.
L0024 |       <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0025 |         <div class="stats-icon"><i class="bi bi-file-earmark-pdf"></i></div> | Assignment statement storing or updating program s
L0026 |         <h1 data-count-key="field_total_forms">{{ pending_pm_rcas + approved_pm_forms + rejected_pm_rcas }}</h1> | Assignment sta
L0027 |         <p>Total PM Forms</p> | Markup line defining structure in an HTML-like template file.
L0028 |       </div> | Markup line defining structure in an HTML-like template file.
L0029 |     </div> | Markup line defining structure in an HTML-like template file.
L0030 |   </a> | Markup line defining structure in an HTML-like template file.
L0031 | </div> | Markup line defining structure in an HTML-like template file.
L0032 | <div class="col"> | Assignment statement storing or updating program state.
L0033 |   <a href="{{ url_for('desk_activities', mode='rejected') }}" class="card-link"> | Assignment statement storing or updating progr
L0034 |     <div class="card stats-card"> | Assignment statement storing or updating program state.
L0035 |       <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0036 |         <div class="stats-icon"><i class="bi bi-x-octagon"></i></div> | Assignment statement storing or updating program state.
L0037 |         <h1 data-count-key="rejected_pm_rcas">{{ rejected_pm_rcas }}</h1> | Assignment statement storing or updating program sta
L0038 |         <p>Rejected PM RCAs</p> | Markup line defining structure in an HTML-like template file.
L0039 |       </div> | Markup line defining structure in an HTML-like template file.
L0040 |     </div> | Markup line defining structure in an HTML-like template file.
L0041 |   </a> | Markup line defining structure in an HTML-like template file.
L0042 | </div> | Markup line defining structure in an HTML-like template file.
L0043 | <div class="col"> | Assignment statement storing or updating program state.
L0044 |   <a href="{{ url_for('desk_activities', mode='rcas', risk='high') }}" class="card-link"> | Assignment statement storing or updat
L0045 |     <div class="card stats-card"> | Assignment statement storing or updating program state.
L0046 |       <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0047 |         <div class="stats-icon"><i class="bi bi-exclamation-diamond"></i></div> | Assignment statement storing or updating progra
L0048 |         <h1 data-count-key="high_risk_pending_pm_rcas">{{ high_risk_pending_pm_rcas }}</h1> | Assignment statement storing or upo
L0049 |         <p>High-Risk PM RCAs</p> | Markup line defining structure in an HTML-like template file.
L0050 |       </div> | Markup line defining structure in an HTML-like template file.
L0051 |     </div> | Markup line defining structure in an HTML-like template file.
L0052 |   </a> | Markup line defining structure in an HTML-like template file.
L0053 | </div> | Markup line defining structure in an HTML-like template file.
```

L0054 | <div class="col"> | Assignment statement storing or updating program state.

L0055 | | Assignment statement storing or updating program state.

L0056 | <div class="card stats-card"> | Assignment statement storing or updating program state.

L0057 | <div class="card-body text-center"> | Assignment statement storing or updating program state.

L0058 | <div class="stats-icon"><i class="bi bi-alarm"></i></div> | Assignment statement storing or updating program state.

L0059 | <h1 data-count-key="sla_overdue_pm_rcas">{{ sla_overdue_pm_rcas }}</h1> | Assignment statement storing or updating program state.

L0060 | <p>SLA Overdue</p> | Markup line defining structure in an HTML-like template file.

L0061 | </div> | Markup line defining structure in an HTML-like template file.

L0062 | </div> | Markup line defining structure in an HTML-like template file.

L0063 | | Markup line defining structure in an HTML-like template file.

L0064 | </div> | Markup line defining structure in an HTML-like template file.

L0065 | </div> | Markup line defining structure in an HTML-like template file.

L0066 | <section class="mt-4 mb-4"> | Assignment statement storing or updating program state.

L0067 | <div class="card form-access-card"> | Assignment statement storing or updating program state.

L0068 | <div class="card-body d-flex justify-content-between align-items-center gap-3 flex-wrap"> | Assignment statement storing or updating program state.

L0069 | <div> | Markup line defining structure in an HTML-like template file.

L0070 | <h3 class="mb-1">Smart Review Center</h3> | Assignment statement storing or updating program state.

L0071 | <p class="text-muted mb-0">Prioritize high-risk PM/RCA submissions, SLA overdue items, and recommendation-driven reviews.</p>

L0072 | </div> | Markup line defining structure in an HTML-like template file.

L0073 | | Assignment statement storing or updating program state.

L0074 | <i class="bi bi-lightning-charge"></i> Open Smart Queue | Assignment statement storing or updating program state.

L0075 | | Markup line defining structure in an HTML-like template file.

L0076 | </div> | Markup line defining structure in an HTML-like template file.

L0077 | </div> | Markup line defining structure in an HTML-like template file.

L0078 | </section> | Markup line defining structure in an HTML-like template file.

L0079 | | Blank line used for readability and logical separation.

L0080 | <section class="mt-4 mb-4"> | Assignment statement storing or updating program state.

L0081 | <div class="card form-access-card"> | Assignment statement storing or updating program state.

L0082 | <div class="card-body d-flex justify-content-between align-items-center gap-3 flex-wrap"> | Assignment statement storing or updating program state.

L0083 | <div> | Markup line defining structure in an HTML-like template file.

L0084 | <h3 class="mb-1">Approved Forms Excel Tracker</h3> | Assignment statement storing or updating program state.

L0085 | <p class="text-muted mb-0">Download approved PM/RCA forms with site info, risk score, SLA, and recommendations in Excel.</p>

L0086 | </div> | Markup line defining structure in an HTML-like template file.

L0087 | | Assignment statement storing or updating program state.

L0088 | <i class="bi bi-file-earmark-excel"></i> Download Excel | Assignment statement storing or updating program state.

L0089 | | Markup line defining structure in an HTML-like template file.

L0090 | </div> | Markup line defining structure in an HTML-like template file.

L0091 | </div> | Markup line defining structure in an HTML-like template file.

L0092 | </section> | Markup line defining structure in an HTML-like template file.

L0093 | {% if not staff_has_form_data %} | Block delimiter controlling scope/structure in this language.

L0094 | <div class="alert alert-info mt-3 mb-0" role="alert"> | Assignment statement storing or updating program state.

L0095 | No recent forms have been submitted by field technicians yet. PM RCA, approved, and rejected lists will populate automatically after the next sync.

L0096 | </div> | Markup line defining structure in an HTML-like template file.

L0097 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0098 | | Blank line used for readability and logical separation.

L0099 | {% elif current_role == 'developer' %} | Block delimiter controlling scope/structure in this language.

L0100 | <div class="row row-cols-1 row-cols-md-2 row-cols-xl-3 g-3 mt-1"> | Assignment statement storing or updating program state.

L0101 | <div class="col"> | Assignment statement storing or updating program state.

L0102 | | Assignment statement storing or updating program state.

L0103 | <div class="card stats-card"> | Assignment statement storing or updating program state.

L0104 | <div class="card-body text-center"> | Assignment statement storing or updating program state.

L0105 | <div class="stats-icon"><i class="bi bi-people-fill"></i></div> | Assignment statement storing or updating program state.

L0106 | <h1 data-count-key="users_total">{{ dashboard_counts.users_total }}</h1> | Assignment statement storing or updating program state.

L0107 | <p>Account Profiles</p> | Markup line defining structure in an HTML-like template file.

L0108 | </div> | Markup line defining structure in an HTML-like template file.

L0109 | </div> | Markup line defining structure in an HTML-like template file.

L0110 | | Markup line defining structure in an HTML-like template file.

L0111 | </div> | Markup line defining structure in an HTML-like template file.

L0112 | <div class="col"> | Assignment statement storing or updating program state.

L0113 | | Assignment statement storing or updating program state.

L0114 | <div class="card stats-card"> | Assignment statement storing or updating program state.

L0115 | <div class="card-body text-center"> | Assignment statement storing or updating program state.

L0116 | <div class="stats-icon"><i class="bi bi-person-lock"></i></div> | Assignment statement storing or updating program state.

L0117 | <h1 data-count-key="blocked_users">{{ dashboard_counts.blocked_users }}</h1> | Assignment statement storing or updating program state.

L0118 | <p>Block / Unblock User</p> | Markup line defining structure in an HTML-like template file.

L0119 | </div> | Markup line defining structure in an HTML-like template file.

L0120 | </div> | Markup line defining structure in an HTML-like template file.

L0121 | | Markup line defining structure in an HTML-like template file.

L0122 | </div> | Markup line defining structure in an HTML-like template file.

L0123 | <div class="col"> | Assignment statement storing or updating program state.

L0124 | | Assignment statement storing or updating program state.

L0125 | <div class="card stats-card"> | Assignment statement storing or updating program state.

L0126 | <div class="card-body text-center"> | Assignment statement storing or updating program state.

L0127 | <div class="stats-icon"><i class="bi bi-plus-circle"></i></div> | Assignment statement storing or updating program state.

L0128 | <h1 data-count-key="technician_users">{{ dashboard_counts.technician_users }}</h1> | Assignment statement storing or updating program state.

L0129 | <p>Add Technician</p> | Markup line defining structure in an HTML-like template file.

L0130 | </div> | Markup line defining structure in an HTML-like template file.

L0131 | </div> | Markup line defining structure in an HTML-like template file.

L0132 | | Markup line defining structure in an HTML-like template file.

L0133 | </div> | Markup line defining structure in an HTML-like template file.

L0134 | <div class="col"> | Assignment statement storing or updating program state.

L0135 | | Assignment statement storing or updating program state.

L0136 | <div class="card stats-card"> | Assignment statement storing or updating program state.

L0137 | <div class="card-body text-center"> | Assignment statement storing or updating program state.

L0138 | <div class="stats-icon"><i class="bi bi-plus-square"></i></div> | Assignment statement storing or updating program state.

L0139 | <h1 data-count-key="staff_users">{{ dashboard_counts.staff_users }}</h1> | Assignment statement storing or updating program state.

L0140 | <p>Add Staff</p> | Markup line defining structure in an HTML-like template file.

L0141 | </div> | Markup line defining structure in an HTML-like template file.

L0142 | </div> | Markup line defining structure in an HTML-like template file.

L0143 | | Markup line defining structure in an HTML-like template file.

L0144 | </div> | Markup line defining structure in an HTML-like template file.

L0145 | <div class="col"> | Assignment statement storing or updating program state.

L0146 | | Assignment statement storing or updating program state.

L0147 | <div class="card stats-card"> | Assignment statement storing or updating program state.

L0148 | <div class="card-body text-center"> | Assignment statement storing or updating program state.

L0149 | <div class="stats-icon"><i class="bi bi-person-workspace"></i></div> | Assignment statement storing or updating program state.

L0150 | <h1 data-count-key="manager_users">{{ dashboard_counts.manager_users }}</h1> | Assignment statement storing or updating program state.

L0151 | <p>Add Manager</p> | Markup line defining structure in an HTML-like template file.

L0152 | </div> | Markup line defining structure in an HTML-like template file.

L0153 | </div> | Markup line defining structure in an HTML-like template file.

L0154 | | Markup line defining structure in an HTML-like template file.

L0155 | </div> | Markup line defining structure in an HTML-like template file.

L0156 | <div class="col"> | Assignment statement storing or updating program state.

L0157 | | Assignment statement storing or updating program state.

L0158 | <div class="card stats-card"> | Assignment statement storing or updating program state.

L0159 | <div class="card-body text-center"> | Assignment statement storing or updating program state.

L0160 | <div class="stats-icon"><i class="bi bi-person-badge-fill"></i></div> | Assignment statement storing or updating program state.

L0161 | <h1 data-count-key="general_manager_users">{{ dashboard_counts.general_manager_users }}</h1> | Assignment statement storing or updating program state.

L0162 | <p>Add General Manager</p> | Markup line defining structure in an HTML-like template file.

L0163 | </div> | Markup line defining structure in an HTML-like template file.

L0164 | </div> | Markup line defining structure in an HTML-like template file.

L0165 | | Markup line defining structure in an HTML-like template file.

L0166 | </div> | Markup line defining structure in an HTML-like template file.

L0167 | <div class="col"> | Assignment statement storing or updating program state.

L0168 | | Assignment statement storing or updating program state.

L0169 | <div class="card stats-card"> | Assignment statement storing or updating program state.

L0170 | <div class="card-body text-center"> | Assignment statement storing or updating program state.

L0171 | <div class="stats-icon"><i class="bi bi-gear-fill"></i></div> | Assignment statement storing or updating program state.

L0172 | <h1 data-count-key="holiday_entries">{{ public_holidays\|length }}</h1> | Assignment statement storing or updating program state.

L0173 | <p>Settings & Holiday Entries</p> | Markup line defining structure in an HTML-like template file.

L0174 | </div> | Markup line defining structure in an HTML-like template file.

L0175 | </div> | Markup line defining structure in an HTML-like template file.

L0176 | | Markup line defining structure in an HTML-like template file.

L0177 | </div> | Markup line defining structure in an HTML-like template file.

L0178 | <div class="col"> | Assignment statement storing or updating program state.

L0179 | | Assignment statement storing or updating program state.

L0180 | <div class="card stats-card"> | Assignment statement storing or updating program state.

L0181 | <div class="card-body text-center"> | Assignment statement storing or updating program state.

L0182 | <div class="stats-icon"><i class="bi bi-bell-fill"></i></div> | Assignment statement storing or updating program state.

L0183 | <h1 data-count-key="notification_count">{{ notification_count }}</h1> | Assignment statement storing or updating program state.

L0184 | <p>Unread System Notifications</p> | Markup line defining structure in an HTML-like template file.

L0185 | </div> | Markup line defining structure in an HTML-like template file.

L0186 | </div> | Markup line defining structure in an HTML-like template file.

L0187 | | Markup line defining structure in an HTML-like template file.

L0188 | </div> | Markup line defining structure in an HTML-like template file.

L0189 | <div class="col"> | Assignment statement storing or updating program state.

L0190 | <div class="card stats-card h-100"> | Assignment statement storing or updating program state.

L0191 | <div class="card-body"> | Assignment statement storing or updating program state.

L0192 | <div class="stats-icon text-center"><i class="bi bi-share-fill"></i></div> | Assignment statement storing or updating program state.

L0193 | <p class="mb-1 fw-semibold text-center">Shareable Login Link</p> | Assignment statement storing or updating program state.

L0194 | <p class="text-muted small mb-2 text-center">Paste your public URL below before sharing</p> | Assignment statement storing or updating program state.

L0195 | <input | Operational statement participating in the file's runtime behavior.

L0196 | type="url" | Assignment statement storing or updating program state.

L0197 | class="form-control form-control-sm mb-2" | Assignment statement storing or updating program state.

L0198 | id="loginShareUrl" | Assignment statement storing or updating program state.

L0199 | value="{{ technician_login_url }}" | Assignment statement storing or updating program state.

L0200 | placeholder="https://your-domain.com/technician/login" | Assignment statement storing or updating program state.

L0201 | spellcheck="false" | Assignment statement storing or updating program state.

L0202 | /> | Operational statement participating in the file's runtime behavior.

L0203 | <p class="text-muted" style="font-size:0.7rem;">Local IP (192.168.x.x) will not work on WhatsApp — use a public URL, —

L0204 | <div class="d-flex gap-2 justify-content-center flex-wrap mt-1"> | Assignment statement storing or updating program state.

L0205 | <button type="button" class="btn btn-outline-primary btn-sm" id="copyLoginLinkBtn"> | Assignment statement storing or updating program state.

L0206 | <i class="bi bi-link-45deg"></i> Copy | Assignment statement storing or updating program state.

L0207 | </button> | Markup line defining structure in an HTML-like template file.

L0208 | <button type="button" class="btn btn-primary btn-sm" id="shareLoginLinkBtn"> | Assignment statement storing or updating program state.

L0209 | <i class="bi bi-share"></i> Share | Assignment statement storing or updating program state.

L0210 | </button> | Markup line defining structure in an HTML-like template file.

L0211 | <button type="button" class="btn btn-outline-secondary btn-sm" id="showQrBtn"> | Assignment statement storing or updating program state.

L0212 | <i class="bi bi-qr-code"></i> QR | Assignment statement storing or updating program state.

L0213 | </button> | Markup line defining structure in an HTML-like template file.

L0214 | </div> | Markup line defining structure in an HTML-like template file.

L0215 | <div class="share-qr-wrap d-none mt-3" id="shareQrWrap"> | Assignment statement storing or updating program state.

L0216 | | Assignment statement storing or updating program state.

L0217 | <p class="mb-0 text-center">Scan to open login page.</p> | Assignment statement storing or updating program state.

L0218 | </div> | Markup line defining structure in an HTML-like template file.

L0219 | </div> | Markup line defining structure in an HTML-like template file.

L0220 | </div> | Markup line defining structure in an HTML-like template file.

L0221 | </div> | Markup line defining structure in an HTML-like template file.

L0222 | </div> | Markup line defining structure in an HTML-like template file.

L0223 | {% else %} | Block delimiter controlling scope/structure in this language.

L0224 | <div class="alert alert-info mt-3 mb-0" role="alert"> | Assignment statement storing or updating program state.

L0225 | Your role does not have a custom dashboard yet. Contact developer support. | Operational statement participating in the file's runtime behavior.

L0226 | </div> | Markup line defining structure in an HTML-like template file.

L0227 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0228 | | Blank line used for readability and logical separation.

L0229 | <p class="text-center text-muted small mt-4 mb-0"> | Assignment statement storing or updating program state.

L0230 | Dashboard Footnote: {{ (current_role or 'user')\|replace('_', ' ')\|title }} | Block delimiter controlling scope/structure in this language.

L0231 | </p> | Markup line defining structure in an HTML-like template file.

L0232 | | Blank line used for readability and logical separation.

L0233 | <script> | Markup line defining structure in an HTML-like template file.

L0234 | (function () { | Block delimiter controlling scope/structure in this language.

L0235 | const countNodes = document.querySelectorAll('[data-count-key]); | Assignment statement storing or updating program state.

L0236 | if (!countNodes.length) { | Conditional branch that runs only when its condition is true.

L0237 | return; | Returns a value (or control) back to the caller.

L0238 | } | Block delimiter controlling scope/structure in this language.

L0239 | | Blank line used for readability and logical separation.

L0240 | function applyCounts(counts) { | Block delimiter controlling scope/structure in this language.

L0241 | countNodes.forEach(function (node) { | Block delimiter controlling scope/structure in this language.

L0242 | const key = node.getAttribute('data-count-key'); | Assignment statement storing or updating program state.

L0243 | if (!key || typeof counts[key] === 'undefined' || counts[key] === null) { | Conditional branch that runs only when its condition is true.

L0244 | return; | Returns a value (or control) back to the caller.

L0245 | } | Block delimiter controlling scope/structure in this language.

L0246 | node.textContent = String(counts[key]); | Assignment statement storing or updating program state.

L0247 | }); | Operational statement participating in the file's runtime behavior.

L0248 | } | Block delimiter controlling scope/structure in this language.

L0249 | | Blank line used for readability and logical separation.

L0250 | function refreshCounts() { | Block delimiter controlling scope/structure in this language.

L0251 | fetch('{{ url_for("dashboard_counts_api") }}', { | Block delimiter controlling scope/structure in this language.

L0252 | method: 'GET', | Operational statement participating in the file's runtime behavior.

L0253 | headers: { Accept: 'application/json' }, | Operational statement participating in the file's runtime behavior.

L0254 | cache: 'no-store', | Operational statement participating in the file's runtime behavior.

L0255 | }) | Operational statement participating in the file's runtime behavior.

L0256 | .then(function (response) { | CSS selector line choosing the elements styled below.

L0257 | if (!response.ok) { | Conditional branch that runs only when its condition is true.

L0258 | throw new Error('dashboard count refresh failed'); | Operational statement participating in the file's runtime behavior.

L0259 | } | Block delimiter controlling scope/structure in this language.

L0260 | return response.json(); | Returns a value (or control) back to the caller.

L0261 | }) | Operational statement participating in the file's runtime behavior.

L0262 | .then(function (payload) { | CSS selector line choosing the elements styled below.

L0263 | if (payload && payload.counts) { | Conditional branch that runs only when its condition is true.

L0264 | applyCounts(payload.counts); | Operational statement participating in the file's runtime behavior.

L0265 | } | Block delimiter controlling scope/structure in this language.

L0266 | }) | Operational statement participating in the file's runtime behavior.

L0267 | .catch(function () { | CSS selector line choosing the elements styled below.

L0268 | // keep existing numbers on transient errors | Operational statement participating in the file's runtime behavior.

L0269 | }); | Operational statement participating in the file's runtime behavior.

L0270 | } | Block delimiter controlling scope/structure in this language.

L0271 | | Blank line used for readability and logical separation.

L0272 | refreshCounts(); | Operational statement participating in the file's runtime behavior.

L0273 | window.setInterval(refreshCounts, 45000); | Operational statement participating in the file's runtime behavior.

```

L0274 | })(); | Operational statement participating in the file's runtime behavior.
L0275 | | Blank line used for readability and logical separation.
L0276 | (function () { | Block delimiter controlling scope/structure in this language.
L0277 |     const copyLoginLinkBtn = document.querySelector('#copyLoginLinkBtn'); | Assignment statement storing or updating program state.
L0278 |     const shareLoginLinkBtn = document.querySelector('#shareLoginLinkBtn'); | Assignment statement storing or updating program state.
L0279 |     const showQrBtn = document.querySelector('#showQrBtn'); | Assignment statement storing or updating program state.
L0280 |     const shareQrWrap = document.querySelector('#shareQrWrap'); | Assignment statement storing or updating program state.
L0281 |     const shareQrImage = document.querySelector('#shareQrImage'); | Assignment statement storing or updating program state.
L0282 |     const loginShareUrl = document.querySelector('#loginShareUrl'); | Assignment statement storing or updating program state.
L0283 | | Blank line used for readability and logical separation.
L0284 |     if (!loginShareUrl) { | Conditional branch that runs only when its condition is true.
L0285 |         return; | Returns a value (or control) back to the caller.
L0286 |     } | Block delimiter controlling scope/structure in this language.
L0287 | | Blank line used for readability and logical separation.
L0288 |     const STORAGE_KEY = 'pm_share_url'; | Assignment statement storing or updating program state.
L0289 | | Blank line used for readability and logical separation.
L0290 |     // restore previously saved custom URL from localStorage | Operational statement participating in the file's runtime behavior.
L0291 |     const savedUrl = localStorage.getItem(STORAGE_KEY); | Assignment statement storing or updating program state.
L0292 |     if (savedUrl) { | Conditional branch that runs only when its condition is true.
L0293 |         const savedLooksLocal = /^https?:\/\/(localhost\|127\.\0\.\0\.\1\|\\[::1\]|::1)(:\d+)?\/\./i.test(savedUrl); | Assignment statement storing or updating program state.
L0294 |         if (!savedLooksLocal) { | Conditional branch that runs only when its condition is true.
L0295 |             loginShareUrl.value = savedUrl; | Assignment statement storing or updating program state.
L0296 |         } | Block delimiter controlling scope/structure in this language.
L0297 |     } | Block delimiter controlling scope/structure in this language.
L0298 | | Blank line used for readability and logical separation.
L0299 |     // persist any manual edits to localStorage | Operational statement participating in the file's runtime behavior.
L0300 |     loginShareUrl.addEventListener('input', function () { | Block delimiter controlling scope/structure in this language.
L0301 |         localStorage.setItem(STORAGE_KEY, loginShareUrl.value.trim()); | Operational statement participating in the file's runtime behavior.
L0302 |     }); | Operational statement participating in the file's runtime behavior.
L0303 | | Blank line used for readability and logical separation.
L0304 |     function getLinkText() { | Block delimiter controlling scope/structure in this language.
L0305 |         return loginShareUrl.value.trim() || loginShareUrl.placeholder; | Returns a value (or control) back to the caller.
L0306 |     } | Block delimiter controlling scope/structure in this language.
L0307 | | Blank line used for readability and logical separation.
L0308 |     if (copyLoginLinkBtn) { | Conditional branch that runs only when its condition is true.
L0309 |         copyLoginLinkBtn.addEventListener('click', async function () { | Block delimiter controlling scope/structure in this language.
L0310 |             const url = getLinkText(); | Assignment statement storing or updating program state.
L0311 |             try { | Block delimiter controlling scope/structure in this language.
L0312 |                 await navigator.clipboard.writeText(url); | Operational statement participating in the file's runtime behavior.
L0313 |                 copyLoginLinkBtn.innerHTML = '<i class="bi bi-check2"></i> Copied'; | Assignment statement storing or updating program state.
L0314 |                 window.setTimeout(function () { | Block delimiter controlling scope/structure in this language.
L0315 |                     copyLoginLinkBtn.innerHTML = '<i class="bi bi-link-45deg"></i> Copy'; | Assignment statement storing or updating program state.
L0316 |                 }, 1400); | Operational statement participating in the file's runtime behavior.
L0317 |             } catch (err) { | Block delimiter controlling scope/structure in this language.
L0318 |                 window.prompt('Copy this login link', url); | Operational statement participating in the file's runtime behavior.
L0319 |             } | Block delimiter controlling scope/structure in this language.
L0320 |         }); | Operational statement participating in the file's runtime behavior.
L0321 |     } | Block delimiter controlling scope/structure in this language.
L0322 | | Blank line used for readability and logical separation.
L0323 |     if (shareLoginLinkBtn) { | Conditional branch that runs only when its condition is true.
L0324 |         shareLoginLinkBtn.addEventListener('click', async function () { | Block delimiter controlling scope/structure in this language.
L0325 |             const url = getLinkText(); | Assignment statement storing or updating program state.
L0326 |             const shareMessage = 'Use this link to access the PM/RCA login page:\n' + url; | Assignment statement storing or updating program state.
L0327 |             if (navigator.share) { | Conditional branch that runs only when its condition is true.
L0328 |                 try { | Block delimiter controlling scope/structure in this language.

```

```

L0329 |         await navigator.share({ | Block delimiter controlling scope/structure in this language.
L0330 |             title: 'Preventative Maintenance RCA', | Operational statement participating in the file's runtime behavior.
L0331 |             text: shareMessage, | Operational statement participating in the file's runtime behavior.
L0332 |             url: url, | Operational statement participating in the file's runtime behavior.
L0333 |         }); | Operational statement participating in the file's runtime behavior.
L0334 |         return; | Returns a value (or control) back to the caller.
L0335 |     } catch (err) { | Block delimiter controlling scope/structure in this language.
L0336 |         // fallback to WhatsApp | Operational statement participating in the file's runtime behavior.
L0337 |     } | Block delimiter controlling scope/structure in this language.
L0338 | } | Block delimiter controlling scope/structure in this language.
L0339 | const waUrl = 'https://wa.me/?text=' + encodeURIComponent(shareMessage); | Assignment statement storing or updating program
L0340 | window.open(waUrl, '_blank', 'noopener,noreferrer'); | Operational statement participating in the file's runtime behavior.
L0341 | }); | Operational statement participating in the file's runtime behavior.
L0342 | } | Block delimiter controlling scope/structure in this language.
L0343 | | Blank line used for readability and logical separation.
L0344 | if (showQrBtn && shareQrWrap && shareQrImage) { | Conditional branch that runs only when its condition is true.
L0345 |     showQrBtn.addEventListener('click', function () { | Block delimiter controlling scope/structure in this language.
L0346 |         const url = getLinkText(); | Assignment statement storing or updating program state.
L0347 |         const qrSrc = 'https://api.qrserver.com/v1/create-qr-code/?size=220x220&data=' + encodeURIComponent(url); | Assignment stat
L0348 |         shareQrImage.src = qrSrc; | Assignment statement storing or updating program state.
L0349 |         shareQrWrap.classList.toggle('d-none'); | Operational statement participating in the file's runtime behavior.
L0350 |         showQrBtn.innerHTML = shareQrWrap.classList.contains('d-none') | Assignment statement storing or updating program state.
L0351 |         ? '<i class="bi bi-qr-code"></i> QR' | Assignment statement storing or updating program state.
L0352 |         : '<i class="bi bi-x-lg"></i> Hide'; | Assignment statement storing or updating program state.
L0353 |     }); | Operational statement participating in the file's runtime behavior.
L0354 | } | Block delimiter controlling scope/structure in this language.
L0355 | })(); | Operational statement participating in the file's runtime behavior.
L0356 | </script> | Markup line defining structure in an HTML-like template file.
L0357 | </div> | Markup line defining structure in an HTML-like template file.
L0358 | {% endblock %} | Block delimiter controlling scope/structure in this language.

```


File 100: templates/desk_activities.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | {% set is_forms_mode = (view_mode == 'forms') %} | Block delimiter controlling scope/structure in this language.
L0004 | {% set is_rejected_mode = (view_mode == 'rejected') %} | Block delimiter controlling scope/structure in this language.
L0005 | <section class="review-board"> | Assignment statement storing or updating program state.
L0006 | <div class="review-headline-card"> | Assignment statement storing or updating program state.
L0007 | <h1> | Markup line defining structure in an HTML-like template file.
L0008 | {% if is_forms_mode %} | Block delimiter controlling scope/structure in this language.
L0009 | Total PM Forms | Operational statement participating in the file's runtime behavior.
L0010 | {% elif is_rejected_mode %} | Block delimiter controlling scope/structure in this language.
L0011 | Rejected PM RCAs | Operational statement participating in the file's runtime behavior.
L0012 | {% else %} | Block delimiter controlling scope/structure in this language.
L0013 | PM RCAs | Operational statement participating in the file's runtime behavior.
L0014 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0015 | </h1> | Markup line defining structure in an HTML-like template file.
L0016 | <p class="text-muted mb-0"> | Assignment statement storing or updating program state.
L0017 | {% if is_forms_mode %} | Block delimiter controlling scope/structure in this language.
L0018 | All PM/RCA forms submitted by the field team. Newest records appear first for easy date/time monitoring. | Operational statement
L0019 | {% elif is_rejected_mode %} | Block delimiter controlling scope/structure in this language.
L0020 | Rejected PM/RCA forms from the field team. Newest records appear first. | Operational statement participating in the file's runtime behavior.
L0021 | {% else %} | Block delimiter controlling scope/structure in this language.
L0022 | Field-submitted PM/RCA forms waiting for desk or staff review. Newest submissions appear first. | Operational statement participating in the file's runtime behavior.
L0023 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0024 | </p> | Markup line defining structure in an HTML-like template file.
L0025 | </div> | Markup line defining structure in an HTML-like template file.
L0026 | | Blank line used for readability and logical separation.
L0027 | <div class="card p-3 review-mode-card mt-3"> | Assignment statement storing or updating program state.
L0028 | <div class="d-flex gap-2 flex-wrap"> | Assignment statement storing or updating program state.
L0029 | <a class="btn {% if (not is_forms_mode) and (not is_rejected_mode) %}btn-primary{% else %}btn-outline-primary{% endif %}" href="{% url_for('desk_activities', mode='forms') %}"> | Assignment statement storing or updating program state.
L0030 | <i class="bi bi-journal-check"></i> PM RCAs | Assignment statement storing or updating program state.
L0031 | </a> | Markup line defining structure in an HTML-like template file.
L0032 | <a class="btn {% if is_forms_mode %}btn-primary{% else %}btn-outline-primary{% endif %}" href="{% url_for('desk_activities', mode='forms') %}"> | Assignment statement storing or updating program state.
L0033 | <i class="bi bi-file-earmark-pdf"></i> Total PM Forms | Assignment statement storing or updating program state.
L0034 | </a> | Markup line defining structure in an HTML-like template file.
L0035 | <a class="btn {% if is_rejected_mode %}btn-primary{% else %}btn-outline-primary{% endif %}" href="{% url_for('desk_activities', mode='rejected') %}"> | Assignment statement storing or updating program state.
L0036 | <i class="bi bi-x-octagon"></i> Rejected PM RCAs | Assignment statement storing or updating program state.
L0037 | </a> | Markup line defining structure in an HTML-like template file.
L0038 | </div> | Markup line defining structure in an HTML-like template file.
L0039 | </div> | Markup line defining structure in an HTML-like template file.
L0040 | | Blank line used for readability and logical separation.
L0041 | <div class="card p-3 review-status-card mt-3"> | Assignment statement storing or updating program state.
L0042 | <div class="d-flex align-items-center gap-2 flex-wrap" aria-label="Status legend"> | Assignment statement storing or updating program state.
L0043 | <span class="text-muted small">Status:</span> | Assignment statement storing or updating program state.
L0044 | <span class="badge text-bg-warning">Pending</span> | Assignment statement storing or updating program state.
L0045 | <span class="badge text-bg-success">Approved</span> | Assignment statement storing or updating program state.
L0046 | <span class="badge text-bg-danger">Rejected</span> | Assignment statement storing or updating program state.
L0047 | </div> | Markup line defining structure in an HTML-like template file.
L0048 | </div> | Markup line defining structure in an HTML-like template file.
L0049 | | Blank line used for readability and logical separation.
L0050 | <div class="card p-3 review-filter-card mt-3"> | Assignment statement storing or updating program state.
L0051 | <form method="get" class="row g-2 align-items-end mb-0"> | Assignment statement storing or updating program state.
L0052 | <input type="hidden" name="mode" value="{% view_mode %}" /> | Assignment statement storing or updating program state.
L0053 | <div class="col-12 col-md-6 col-lg-5"> | Assignment statement storing or updating program state.
```

L0054 | <label class="form-label">Search (site ID/number, technician name/email, form text, type, ID)</label> | Assignment statement storing or updating program state.

L0055 | <input type="text" class="form-control" name="q" value="{{ search_query or '' }}" placeholder="Search PM/RCA records" /> | Assignment statement storing or updating program state.

L0056 | </div> | Markup line defining structure in an HTML-like template file.

L0057 | <div class="col-12 col-md-4 col-lg-3"> | Assignment statement storing or updating program state.

L0058 | <label class="form-label">Created date</label> | Assignment statement storing or updating program state.

L0059 | <input type="date" class="form-control" name="date" value="{{ created_on or '' }}" /> | Assignment statement storing or updating program state.

L0060 | </div> | Markup line defining structure in an HTML-like template file.

L0061 | <div class="col-12 col-md-3 col-lg-2"> | Assignment statement storing or updating program state.

L0062 | <label class="form-label">Risk</label> | Assignment statement storing or updating program state.

L0063 | <select class="form-select" name="risk"> | Assignment statement storing or updating program state.

L0064 | <option value="" {% if not risk_filter %}selected{% endif %}>All</option> | Assignment statement storing or updating program state.

L0065 | <option value="high" {% if risk_filter == 'high' %}selected{% endif %}>High</option> | Markup line defining structure in an HTML-like template file.

L0066 | <option value="medium" {% if risk_filter == 'medium' %}selected{% endif %}>Medium</option> | Markup line defining structure in an HTML-like template file.

L0067 | <option value="low" {% if risk_filter == 'low' %}selected{% endif %}>Low</option> | Markup line defining structure in an HTML-like template file.

L0068 | </select> | Markup line defining structure in an HTML-like template file.

L0069 | </div> | Markup line defining structure in an HTML-like template file.

L0070 | <div class="col-12 col-md-3 col-lg-2"> | Assignment statement storing or updating program state.

L0071 | <label class="form-label">SLA</label> | Assignment statement storing or updating program state.

L0072 | <select class="form-select" name="sla"> | Assignment statement storing or updating program state.

L0073 | <option value="" {% if not sla_filter %}selected{% endif %}>All</option> | Assignment statement storing or updating program state.

L0074 | <option value="overdue" {% if sla_filter == 'overdue' %}selected{% endif %}>Overdue</option> | Markup line defining structure in an HTML-like template file.

L0075 | <option value="due_soon" {% if sla_filter == 'due_soon' %}selected{% endif %}>Due Soon</option> | Markup line defining structure in an HTML-like template file.

L0076 | <option value="on_track" {% if sla_filter == 'on_track' %}selected{% endif %}>On Track</option> | Markup line defining structure in an HTML-like template file.

L0077 | </select> | Markup line defining structure in an HTML-like template file.

L0078 | </div> | Markup line defining structure in an HTML-like template file.

L0079 | <div class="col-12 col-md-2 col-lg-2 d-grid"> | Assignment statement storing or updating program state.

L0080 | <button type="submit" class="btn btn-primary">Filter</button> | Assignment statement storing or updating program state.

L0081 | </div> | Markup line defining structure in an HTML-like template file.

L0082 | <div class="col-12 col-lg-2 d-grid"> | Assignment statement storing or updating program state.

L0083 | Clear | Assignment statement storing or updating program state.

L0084 | </div> | Markup line defining structure in an HTML-like template file.

L0085 | </form> | Markup line defining structure in an HTML-like template file.

L0086 | </div> | Markup line defining structure in an HTML-like template file.

L0087 | | Blank line used for readability and logical separation.

L0088 | <div class="card p-3 review-filter-card mt-3 sla-policy-summary-card"> | Assignment statement storing or updating program state.

L0089 | <div class="d-flex justify-content-between align-items-center gap-3 flex-wrap"> | Assignment statement storing or updating program state.

L0090 | <div> | Markup line defining structure in an HTML-like template file.

L0091 | <div class="small text-muted mb-1">Active Desk SLA Policy</div> | Assignment statement storing or updating program state.

L0092 | <div class="fw-semibold mb-1"> | Assignment statement storing or updating program state.

L0093 | {% if active_sla_policy.enabled %} | Block delimiter controlling scope/structure in this language.

L0094 | {{ active_sla_policy.standard_hours }}h standard PM, {{ active_sla_policy.critical_hours }}h critical/RCA, due soon at {{ active_sla_policy.due_soon }}h | Assignment statement storing or updating program state.

L0095 | {% else %} | Block delimiter controlling scope/structure in this language.

L0096 | SLA is inactive for new PM/RCA submissions. | Operational statement participating in the file's runtime behavior.

L0097 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0098 | </div> | Markup line defining structure in an HTML-like template file.

L0099 | <div class="small text-muted">Updated by {{ active_sla_policy.updated_by }}</div> | Assignment statement storing or updating program state.

L0100 | </div> | Markup line defining structure in an HTML-like template file.

L0101 | | Assignment statement storing or updating program state.

L0102 | <i class="bi bi-sliders"></i> Manage SLA Policy | Assignment statement storing or updating program state.

L0103 | | Markup line defining structure in an HTML-like template file.

L0104 | </div> | Markup line defining structure in an HTML-like template file.

L0105 | </div> | Markup line defining structure in an HTML-like template file.

L0106 | | Blank line used for readability and logical separation.

L0107 | <div class="card p-3 review-table-card mt-3"> | Assignment statement storing or updating program state.

L0108 | {% if review_rows %} | Block delimiter controlling scope/structure in this language.

```

L0109 | <div class="review-items-list"> | Assignment statement storing or updating program state.
L0110 |     {% for row in review_rows %} | Block delimiter controlling scope/structure in this language.
L0111 |     {% set activity = row.activity %} | Assignment statement storing or updating program state.
L0112 |     <div class="review-item-card"> | Assignment statement storing or updating program state.
L0113 |         <div class="d-flex align-items-start gap-2 flex-wrap"> | Assignment statement storing or updating program state.
L0114 |             <div class="flex-grow-1"> | Assignment statement storing or updating program state.
L0115 | | Blank line used for readability and logical separation.
L0116 |                 <div class="d-flex align-items-center gap-2 mb-2 flex-wrap"> | Assignment statement storing or updating program state.
L0117 |                     <span class="badge text-bg-secondary">{{ activity.activity_type|upper }}</span> | Assignment statement storing or upda
L0118 |                     {% if row.risk_score >= 70 %} | Block delimiter controlling scope/structure in this language.
L0119 |                         <span class="badge text-bg-danger"><i class="bi bi-thermometer-high"></i> {{ row.risk_score }} &middot; High</span> |
L0120 |                     {% elif row.risk_score >= 40 %} | Block delimiter controlling scope/structure in this language.
L0121 |                         <span class="badge text-bg-warning"><i class="bi bi-thermometer-half"></i> {{ row.risk_score }} &middot; Medium</span>
L0122 |                     {% else %} | Block delimiter controlling scope/structure in this language.
L0123 |                         <span class="badge text-bg-success"><i class="bi bi-thermometer-low"></i> {{ row.risk_score }} &middot; Low</span> |
L0124 |                     {% endif %} | Block delimiter controlling scope/structure in this language.
L0125 |                     {% if row.sla_state == 'Overdue' %} | Block delimiter controlling scope/structure in this language.
L0126 |                         <span class="badge text-bg-danger">SLA: Overdue</span> | Assignment statement storing or updating program state.
L0127 |                     {% elif row.sla_state == 'Due Soon' %} | Block delimiter controlling scope/structure in this language.
L0128 |                         <span class="badge text-bg-warning">SLA: Due Soon</span> | Assignment statement storing or updating program state.
L0129 |                     {% elif row.sla_state == 'On Track' %} | Block delimiter controlling scope/structure in this language.
L0130 |                         <span class="badge text-bg-success">SLA: On Track</span> | Assignment statement storing or updating program state.
L0131 |                     {% elif row.sla_state == 'Resolved' %} | Block delimiter controlling scope/structure in this language.
L0132 |                         <span class="badge text-bg-secondary">SLA: Resolved</span> | Assignment statement storing or updating program state.
L0133 |                     {% else %} | Block delimiter controlling scope/structure in this language.
L0134 |                         <span class="badge text-bg-light text-dark">SLA: Not Set</span> | Assignment statement storing or updating program st
L0135 |                     {% endif %} | Block delimiter controlling scope/structure in this language.
L0136 |                     {% if activity.is_approved %} | Block delimiter controlling scope/structure in this language.
L0137 |                         <span class="badge text-bg-success"><i class="bi bi-check-circle"></i> Approved</span> | Assignment statement storing
L0138 |                     {% elif activity.approved_at %} | Block delimiter controlling scope/structure in this language.
L0139 |                         <span class="badge text-bg-danger"><i class="bi bi-x-circle"></i> Rejected</span> | Assignment statement storing or u
L0140 |                     {% else %} | Block delimiter controlling scope/structure in this language.
L0141 |                         <span class="badge text-bg-warning"><i class="bi bi-clock"></i> Pending</span> | Assignment statement storing or upda
L0142 |                     {% endif %} | Block delimiter controlling scope/structure in this language.
L0143 |                 </div> | Markup line defining structure in an HTML-like template file.
L0144 | | Blank line used for readability and logical separation.
L0145 |                 <p class="review-item-details mb-1">{{ activity.details[:160] }}{% if activity.details\|length > 160 %}&hellip;{% endif %}
L0146 | | Blank line used for readability and logical separation.
L0147 |                 <div class="review-item-meta d-flex gap-3 flex-wrap"> | Assignment statement storing or updating program state.
L0148 |                     <span><i class="bi bi-person"></i> {{ activity.created_by or 'Unknown' }}</span> | Assignment statement storing or upda
L0149 |                     <span><i class="bi bi-calendar-event"></i> {{ activity.created_at.strftime('%Y-%m-%d %H:%M') }}</span> | Assignment sta
L0150 |                     {% if activity.approved_at %} | Block delimiter controlling scope/structure in this language.
L0151 |                         <span><i class="bi bi-check2-square"></i> Reviewed {{ activity.approved_at.strftime('%Y-%m-%d %H:%M') }}</span> | Assig
L0152 |                     {% endif %} | Block delimiter controlling scope/structure in this language.
L0153 |                     {% if row.sla_deadline %} | Block delimiter controlling scope/structure in this language.
L0154 |                         <span><i class="bi bi-alarm"></i> SLA by {{ row.sla_deadline.strftime('%Y-%m-%d %H:%M') }}</span> | Assignment statemen
L0155 |                     {% endif %} | Block delimiter controlling scope/structure in this language.
L0156 |                 </div> | Markup line defining structure in an HTML-like template file.
L0157 | | Blank line used for readability and logical separation.
L0158 |                 {% if row.top_recommendation %} | Block delimiter controlling scope/structure in this language.
L0159 |                 <div class="review-item-rec mt-2"> | Assignment statement storing or updating program state.
L0160 |                     <i class="bi bi-lightbulb text-warning"></i> {{ row.top_recommendation }} | Assignment statement storing or updating pr
L0161 |                 </div> | Markup line defining structure in an HTML-like template file.
L0162 |                 {% endif %} | Block delimiter controlling scope/structure in this language.
L0163 | | Blank line used for readability and logical separation.

```

L0164 | </div> | Markup line defining structure in an HTML-like template file.

L0165 | <div class="review-item-actions d-flex gap-1 flex-shrink-0 flex-wrap"> | Assignment statement storing or updating program state.

L0166 |

L0167 | <i class="bi bi-eye-fill"></i> | Assignment statement storing or updating program state.

L0168 | | Markup line defining structure in an HTML-like template file.

L0169 | {% if is_forms_mode %} | Block delimiter controlling scope/structure in this language.

L0170 | {% if activity.is_approved %} | Block delimiter controlling scope/structure in this language.

L0171 |

L0172 | <i class="bi bi-download"></i> | Assignment statement storing or updating program state.

L0173 | | Markup line defining structure in an HTML-like template file.

L0174 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0175 | {% elif not is_rejected_mode %} | Block delimiter controlling scope/structure in this language.

L0176 | <form method="post" action="{{ url_for('approve_activity', activity_id=activity.id) }}" class="d-inline"> | Assignment statement storing or updating program state.

L0177 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0178 | <button type="submit" class="btn btn-sm btn-outline-success">Approve</button> | Assignment statement storing or updating program state.

L0179 | </form> | Markup line defining structure in an HTML-like template file.

L0180 | <form method="post" action="{{ url_for('reject_activity', activity_id=activity.id) }}" class="d-inline"> | Assignment statement storing or updating program state.

L0181 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0182 | <button type="submit" class="btn btn-sm btn-outline-danger">Reject</button> | Assignment statement storing or updating program state.

L0183 | </form> | Markup line defining structure in an HTML-like template file.

L0184 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0185 | </div> | Markup line defining structure in an HTML-like template file.

L0186 | </div> | Markup line defining structure in an HTML-like template file.

L0187 | </div> | Markup line defining structure in an HTML-like template file.

L0188 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0189 | </div> | Markup line defining structure in an HTML-like template file.

L0190 | {% else %} | Block delimiter controlling scope/structure in this language.

L0191 | <div class="text-center text-muted py-4"> | Assignment statement storing or updating program state.

L0192 | {% if is_forms_mode %} | Block delimiter controlling scope/structure in this language.

L0193 | No field forms submitted yet. | Operational statement participating in the file's runtime behavior.

L0194 | {% elif is_rejected_mode %} | Block delimiter controlling scope/structure in this language.

L0195 | No rejected PM RCA forms yet. | Operational statement participating in the file's runtime behavior.

L0196 | {% else %} | Block delimiter controlling scope/structure in this language.

L0197 | No PM RCA forms are pending review. | Operational statement participating in the file's runtime behavior.

L0198 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0199 | </div> | Markup line defining structure in an HTML-like template file.

L0200 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0201 | </div> | Markup line defining structure in an HTML-like template file.

L0202 | {% if pagination and pagination.pages > 1 %} | Block delimiter controlling scope/structure in this language.

L0203 | <nav aria-label="Desk activities pagination" class="mt-3"> | Assignment statement storing or updating program state.

L0204 | <ul class="pagination flex-wrap"> | Assignment statement storing or updating program state.

L0205 | <li class="page-item {% if not pagination.has_prev %}disabled{% endif %}"> | Assignment statement storing or updating program state.

L0206 |

L0207 | | Markup line defining structure in an HTML-like template file.

L0208 | {% for page_num in pagination.iter_pages(left_edge=1, left_current=2, right_current=2, right_edge=1) %} | Assignment statement storing or updating program state.

L0209 | {% if page_num %} | Block delimiter controlling scope/structure in this language.

L0210 | <li class="page-item {% if page_num == pagination.page %}active{% endif %}"> | Markup line defining structure in an HTML-like template file.

L0211 |

L0212 | | Markup line defining structure in an HTML-like template file.

L0213 | {% else %} | Block delimiter controlling scope/structure in this language.

L0214 | <li class="page-item disabled">... | Assignment statement storing or updating program state.

L0215 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0216 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0217 | <li class="page-item {% if not pagination.has_next %}disabled{% endif %}"> | Assignment statement storing or updating program state.

L0218 |

L0219 | | Markup line defining structure in an HTML-like template file.

L0220 | | Markup line defining structure in an HTML-like template file.

L0221 | </nav> | Markup line defining structure in an HTML-like template file.

L0222 | <p class="text-muted small">Showing {{ review_rows\|length }} of {{ pagination.total }} records on page {{ pagination.page }} of {{ }}

L0223 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0224 | </section> | Markup line defining structure in an HTML-like template file.

L0225 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 101: templates/developer_photo_library.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <div class="photo-library-shell role-dashboard-shell role-developer"> | Assignment statement storing or updating program state.
L0004 |     <section class="dashboard-hero-lite photo-library-hero"> | Assignment statement storing or updating program state.
L0005 |         <div> | Markup line defining structure in an HTML-like template file.
L0006 |             <h1>Monitored Photo Library</h1> | Markup line defining structure in an HTML-like template file.
L0007 |             <p class="text-muted mb-0">Scans the <strong>photo</strong> folder, generates system descriptions, and lets you import select
L0008 |         </div> | Markup line defining structure in an HTML-like template file.
L0009 |     </section> | Markup line defining structure in an HTML-like template file.
L0010 | | Blank line used for readability and logical separation.
L0011 | <div class="row g-3 mb-4"> | Assignment statement storing or updating program state.
L0012 |     <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.
L0013 |         <div class="card photo-library-stat-card h-100"> | Assignment statement storing or updating program state.
L0014 |             <div class="card-body"> | Assignment statement storing or updating program state.
L0015 |                 <div class="photo-library-stat-label">Visible Images</div> | Assignment statement storing or updating program state.
L0016 |                 <div class="photo-library-stat-value">{{ photo_library_total }}</div> | Assignment statement storing or updating program
L0017 |                 <div class="small text-muted">From the monitored photo source.</div> | Assignment statement storing or updating program s
L0018 |             </div> | Markup line defining structure in an HTML-like template file.
L0019 |         </div> | Markup line defining structure in an HTML-like template file.
L0020 |     </div> | Markup line defining structure in an HTML-like template file.
L0021 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.
L0022 |     <div class="card photo-library-stat-card h-100"> | Assignment statement storing or updating program state.
L0023 |         <div class="card-body"> | Assignment statement storing or updating program state.
L0024 |             <div class="photo-library-stat-label">Screenshots In View</div> | Assignment statement storing or updating program state.
L0025 |             <div class="photo-library-stat-value">{{ screenshot_count }}</div> | Assignment statement storing or updating program sta
L0026 |             <div class="small text-muted">Detected by filename heuristics.</div> | Assignment statement storing or updating program s
L0027 |         </div> | Markup line defining structure in an HTML-like template file.
L0028 |     </div> | Markup line defining structure in an HTML-like template file.
L0029 | </div> | Markup line defining structure in an HTML-like template file.
L0030 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.
L0031 |     <div class="card photo-library-stat-card h-100"> | Assignment statement storing or updating program state.
L0032 |         <div class="card-body"> | Assignment statement storing or updating program state.
L0033 |             <div class="photo-library-stat-label">Monitored Path</div> | Assignment statement storing or updating program state.
L0034 |             <div class="photo-library-path">{{ photo_library_path }}</div> | Assignment statement storing or updating program state.
L0035 |             <div class="small text-muted">Additional monitored source: {{ monitored_sources|join(' ') }}</div> | Assignment stateme
L0036 |         </div> | Markup line defining structure in an HTML-like template file.
L0037 |     </div> | Markup line defining structure in an HTML-like template file.
L0038 | </div> | Markup line defining structure in an HTML-like template file.
L0039 | </div> | Markup line defining structure in an HTML-like template file.
L0040 | | Blank line used for readability and logical separation.
L0041 | <div class="card photo-library-toolbar-card mb-4"> | Assignment statement storing or updating program state.
L0042 |     <div class="card-body"> | Assignment statement storing or updating program state.
L0043 |         <form method="get" action="{{ url_for('developer_photo_library') }}" class="row g-2 align-items-end"> | Assignment statement
L0044 |             <div class="col-12 col-md-7"> | Assignment statement storing or updating program state.
L0045 |                 <label class="form-label mb-1" for="photoLibrarySearch">Search images</label> | Assignment statement storing or updating
L0046 |                 <input id="photoLibrarySearch" type="search" name="q" class="form-control" value="{{ photo_query }}" placeholder="Search
L0047 |             </div> | Markup line defining structure in an HTML-like template file.
L0048 |             <div class="col-12 col-md-3"> | Assignment statement storing or updating program state.
L0049 |                 <label class="form-label mb-1" for="photoLibraryLimit">Show</label> | Assignment statement storing or updating program st
L0050 |                 <select id="photoLibraryLimit" name="limit" class="form-select"> | Assignment statement storing or updating program state
L0051 |                     {% for size in [12, 24, 48, 96] %} | Block delimiter controlling scope/structure in this language.
L0052 |                     {% if size <= photo_library_controls.max_scan_limit %} | Block delimiter controlling scope/structure in this language.
L0053 |                     <option value="{{ size }}" {% if photo_limit == size %}selected{% endif %}>{{ size }} images</option> | Markup line def
```

L0054 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0055 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0056 | {% if photo_library_controls.max_scan_limit not in [12, 24, 48, 96] %} | Block delimiter controlling scope/structure in

L0057 | <option value="{{ photo_library_controls.max_scan_limit }}" selected="{{ photo_library_controls.max_scan_limit }}" images

L0058 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0059 | </select> | Markup line defining structure in an HTML-like template file.

L0060 | </div> | Markup line defining structure in an HTML-like template file.

L0061 | <div class="col-12 col-md-2 d-grid"> | Assignment statement storing or updating program state.

L0062 | <button type="submit" class="btn btn-primary">Scan</button> | Assignment statement storing or updating program state.

L0063 | </div> | Markup line defining structure in an HTML-like template file.

L0064 | </form> | Markup line defining structure in an HTML-like template file.

L0065 | </div> | Markup line defining structure in an HTML-like template file.

L0066 | </div> | Markup line defining structure in an HTML-like template file.

L0067 | | Blank line used for readability and logical separation.

L0068 | {% if photo_entries %} | Block delimiter controlling scope/structure in this language.

L0069 | <div class="row row-cols-1 row-cols-md-2 row-cols-xl-3 g-3"> | Assignment statement storing or updating program state.

L0070 | {% for entry in photo_entries %} | Block delimiter controlling scope/structure in this language.

L0071 | <div class="col d-flex"> | Assignment statement storing or updating program state.

L0072 | <div class="card photo-library-card w-100"> | Assignment statement storing or updating program state.

L0073 | | Assignment statement s

L0074 | | Assignment stat

L0075 | | Markup line defining structure in an HTML-like template file.

L0076 | <div class="card-body d-flex flex-column"> | Assignment statement storing or updating program state.

L0077 | <div class="d-flex justify-content-between align-items-start gap-2 mb-2"> | Assignment statement storing or updating prog

L0078 | <div> | Markup line defining structure in an HTML-like template file.

L0079 | <h5 class="photo-library-title mb-1">{{ entry.name }}</h5> | Assignment statement storing or updating program state.

L0080 | <div class="small text-muted">{{ entry.modified_at.strftime('%Y-%m-%d %H:%M:%S') }}</div> | Assignment statement stor

L0081 | </div> | Markup line defining structure in an HTML-like template file.

L0082 | {{ entry.kind|title }} | Assignment statement storin

L0083 | </div> | Markup line defining structure in an HTML-like template file.

L0084 | | Blank line used for readability and logical separation.

L0085 | <p class="photo-library-description">{{ entry.description }}</p> | Assignment statement storing or updating program state

L0086 | | Blank line used for readability and logical separation.

L0087 | <div class="photo-library-meta mb-3"> | Assignment statement storing or updating program state.

L0088 | <i class="bi bi-file-earmark-image"></i> {{ entry.extension|upper }} | Assignment statement storing or up

L0089 | <i class="bi bi-hdd"></i> {{ entry.size_kb }} KB | Assignment statement storing or updating program state.

L0090 | </div> | Markup line defining structure in an HTML-like template file.

L0091 | | Blank line used for readability and logical separation.

L0092 | <div class="mt-auto d-flex flex-wrap gap-2"> | Assignment statement storing or updating program state.

L0093 | Open | Assi

L0094 | <form method="post" action="{{ url_for('import_photo_library_file') }}"> | Assignment statement storing or updating pro

L0095 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program

L0096 | <input type="hidden" name="filename" value="{{ entry.name }}" /> | Assignment statement storing or updating program s

L0097 | <button type="submit" class="btn btn-sm btn-primary" {% if not photo_library_controls.allow_import %}disabled title="

L0098 | </form> | Markup line defining structure in an HTML-like template file.

L0099 | </div> | Markup line defining structure in an HTML-like template file.

L0100 | </div> | Markup line defining structure in an HTML-like template file.

L0101 | </div> | Markup line defining structure in an HTML-like template file.

L0102 | </div> | Markup line defining structure in an HTML-like template file.

L0103 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0104 | </div> | Markup line defining structure in an HTML-like template file.

L0105 | {% else %} | Block delimiter controlling scope/structure in this language.

L0106 | <div class="card photo-library-empty-card"> | Assignment statement storing or updating program state.

L0107 | <div class="card-body text-center py-5"> | Assignment statement storing or updating program state.

L0108 | <div class="photo-library-empty-icon"><i class="bi bi-images"></i></div> | Assignment statement storing or updating program s

L0109 | <h4 class="mb-2">No monitored images found</h4> | Assignment statement storing or updating program state.

L0110 | <p class="text-muted mb-0">Add images to the photo folder or clear the current search filter.</p> | Assignment statement storing or updating program state.

L0111 | </div> | Markup line defining structure in an HTML-like template file.

L0112 | </div> | Markup line defining structure in an HTML-like template file.

L0113 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0114 | </div> | Markup line defining structure in an HTML-like template file.

L0115 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 102: templates/developer_role_dashboard.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <div class="role-dashboard-shell role-developer"> | Assignment statement storing or updating program state.
L0004 | <section class="dashboard-hero-lite"> | Assignment statement storing or updating program state.
L0005 |   <h1>Hello, {{ user_name }}. Welcome back!</h1> | Markup line defining structure in an HTML-like template file.
L0006 | </section> | Markup line defining structure in an HTML-like template file.
L0007 | | Blank line used for readability and logical separation.
L0008 | <div class="row row-cols-1 row-cols-md-2 row-cols-xl-3 g-3 mt-1"> | Assignment statement storing or updating program state.
L0009 |   <div class="col"> | Assignment statement storing or updating program state.
L0010 |     <a href="{{ url_for('admin_staff') }}" class="card-link"> | Assignment statement storing or updating program state.
L0011 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0012 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0013 |           <div class="stats-icon"><i class="bi bi-people-fill"></i></div> | Assignment statement storing or updating program state.
L0014 |           <h1>{{ dashboard_counts.users_total }}</h1> | Markup line defining structure in an HTML-like template file.
L0015 |           <p>Account Profiles</p> | Markup line defining structure in an HTML-like template file.
L0016 |         </div> | Markup line defining structure in an HTML-like template file.
L0017 |       </div> | Markup line defining structure in an HTML-like template file.
L0018 |     </a> | Markup line defining structure in an HTML-like template file.
L0019 |   </div> | Markup line defining structure in an HTML-like template file.
L0020 |   <div class="col"> | Assignment statement storing or updating program state.
L0021 |     <a href="{{ url_for('developer_user_control') }}" class="card-link"> | Assignment statement storing or updating program state.
L0022 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0023 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0024 |           <div class="stats-icon"><i class="bi bi-person-lock"></i></div> | Assignment statement storing or updating program state.
L0025 |           <h1>{{ dashboard_counts.blocked_users }}</h1> | Markup line defining structure in an HTML-like template file.
L0026 |           <p>Block / Unblock User</p> | Markup line defining structure in an HTML-like template file.
L0027 |         </div> | Markup line defining structure in an HTML-like template file.
L0028 |       </div> | Markup line defining structure in an HTML-like template file.
L0029 |     </a> | Markup line defining structure in an HTML-like template file.
L0030 |   </div> | Markup line defining structure in an HTML-like template file.
L0031 |   <div class="col"> | Assignment statement storing or updating program state.
L0032 |     <a href="{{ url_for('add_technician') }}" class="card-link"> | Assignment statement storing or updating program state.
L0033 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0034 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0035 |           <div class="stats-icon"><i class="bi bi-plus-circle"></i></div> | Assignment statement storing or updating program state.
L0036 |           <h1>{{ dashboard_counts.technician_users }}</h1> | Markup line defining structure in an HTML-like template file.
L0037 |           <p>Add Technician</p> | Markup line defining structure in an HTML-like template file.
L0038 |         </div> | Markup line defining structure in an HTML-like template file.
L0039 |       </div> | Markup line defining structure in an HTML-like template file.
L0040 |     </a> | Markup line defining structure in an HTML-like template file.
L0041 |   </div> | Markup line defining structure in an HTML-like template file.
L0042 |   <div class="col"> | Assignment statement storing or updating program state.
L0043 |     <a href="{{ url_for('add_staff') }}" class="card-link"> | Assignment statement storing or updating program state.
L0044 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0045 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0046 |           <div class="stats-icon"><i class="bi bi-plus-square"></i></div> | Assignment statement storing or updating program state.
L0047 |           <h1>{{ dashboard_counts.staff_users }}</h1> | Markup line defining structure in an HTML-like template file.
L0048 |           <p>Add Staff</p> | Markup line defining structure in an HTML-like template file.
L0049 |         </div> | Markup line defining structure in an HTML-like template file.
L0050 |       </div> | Markup line defining structure in an HTML-like template file.
L0051 |     </a> | Markup line defining structure in an HTML-like template file.
L0052 |   </div> | Markup line defining structure in an HTML-like template file.
L0053 | </div class="col"> | Assignment statement storing or updating program state.
```

L0054 | | Assignment statement storing or updating program state.
L0055 | <div class="card stats-card"> | Assignment statement storing or updating program state.
L0056 | <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0057 | <div class="stats-icon"><i class="bi bi-person-workspace"></i></div> | Assignment statement storing or updating program state.
L0058 | <h1>{{ dashboard_counts.manager_users }}</h1> | Markup line defining structure in an HTML-like template file.
L0059 | <p>Add Manager</p> | Markup line defining structure in an HTML-like template file.
L0060 | </div> | Markup line defining structure in an HTML-like template file.
L0061 | </div> | Markup line defining structure in an HTML-like template file.
L0062 | | Markup line defining structure in an HTML-like template file.
L0063 | </div> | Markup line defining structure in an HTML-like template file.
L0064 | <div class="col"> | Assignment statement storing or updating program state.
L0065 | | Assignment statement storing or updating program state.
L0066 | <div class="card stats-card"> | Assignment statement storing or updating program state.
L0067 | <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0068 | <div class="stats-icon"><i class="bi bi-person-badge-fill"></i></div> | Assignment statement storing or updating program state.
L0069 | <h1>{{ dashboard_counts.general_manager_users }}</h1> | Markup line defining structure in an HTML-like template file.
L0070 | <p>Add General Manager</p> | Markup line defining structure in an HTML-like template file.
L0071 | </div> | Markup line defining structure in an HTML-like template file.
L0072 | </div> | Markup line defining structure in an HTML-like template file.
L0073 | | Markup line defining structure in an HTML-like template file.
L0074 | </div> | Markup line defining structure in an HTML-like template file.
L0075 | <div class="col"> | Assignment statement storing or updating program state.
L0076 | | Assignment statement storing or updating program state.
L0077 | <div class="card stats-card"> | Assignment statement storing or updating program state.
L0078 | <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0079 | <div class="stats-icon"><i class="bi bi-gear-fill"></i></div> | Assignment statement storing or updating program state.
L0080 | <h1>{{ public_holidays|length }}</h1> | Markup line defining structure in an HTML-like template file.
L0081 | <p>Settings & Holiday Entries</p> | Markup line defining structure in an HTML-like template file.
L0082 | </div> | Markup line defining structure in an HTML-like template file.
L0083 | </div> | Markup line defining structure in an HTML-like template file.
L0084 | | Markup line defining structure in an HTML-like template file.
L0085 | </div> | Markup line defining structure in an HTML-like template file.
L0086 | <div class="col"> | Assignment statement storing or updating program state.
L0087 | | Assignment statement storing or updating program state.
L0088 | <div class="card stats-card"> | Assignment statement storing or updating program state.
L0089 | <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0090 | <div class="stats-icon"><i class="bi bi-bell-fill"></i></div> | Assignment statement storing or updating program state.
L0091 | <h1>{{ notification_count }}</h1> | Markup line defining structure in an HTML-like template file.
L0092 | <p>Unread System Notifications</p> | Markup line defining structure in an HTML-like template file.
L0093 | </div> | Markup line defining structure in an HTML-like template file.
L0094 | </div> | Markup line defining structure in an HTML-like template file.
L0095 | | Markup line defining structure in an HTML-like template file.
L0096 | </div> | Markup line defining structure in an HTML-like template file.
L0097 | <div class="col"> | Assignment statement storing or updating program state.
L0098 | | Assignment statement storing or updating program state.
L0099 | <div class="card stats-card"> | Assignment statement storing or updating program state.
L0100 | <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0101 | <div class="stats-icon"><i class="bi bi-images"></i></div> | Assignment statement storing or updating program state.
L0102 | <h1>{{ photo_library_count }}</h1> | Markup line defining structure in an HTML-like template file.
L0103 | <p>Photo Library Scanner</p> | Markup line defining structure in an HTML-like template file.
L0104 | </div> | Markup line defining structure in an HTML-like template file.
L0105 | </div> | Markup line defining structure in an HTML-like template file.
L0106 | | Markup line defining structure in an HTML-like template file.
L0107 | </div> | Markup line defining structure in an HTML-like template file.
L0108 | <div class="col"> | Assignment statement storing or updating program state.

```

L0109 | <div class="card stats-card h-100"> | Assignment statement storing or updating program state.
L0110 | <div class="card-body"> | Assignment statement storing or updating program state.
L0111 | <div class="stats-icon text-center"><i class="bi bi-share-fill"></i></div> | Assignment statement storing or updating program state.
L0112 | <p class="mb-1 fw-semibold text-center">Shareable PM/RCA Login Link + QR</p> | Assignment statement storing or updating program state.
L0113 | <p class="text-muted small mb-2 text-center">Use this card to copy, share, and generate a scannable login QR code.</p> | Assignment statement storing or updating program state.
L0114 | <input | Operational statement participating in the file's runtime behavior.
L0115 | type="url" | Assignment statement storing or updating program state.
L0116 | class="form-control form-control-sm mb-2" | Assignment statement storing or updating program state.
L0117 | id="loginShareUrl" | Assignment statement storing or updating program state.
L0118 | value="{{ technician_login_url }}" | Assignment statement storing or updating program state.
L0119 | data-share-link-public="{{ 1 if share_link_is_public else 0 }}" | Assignment statement storing or updating program state.
L0120 | placeholder="https://your-domain.com/technician/login" | Assignment statement storing or updating program state.
L0121 | spellcheck="false" | Assignment statement storing or updating program state.
L0122 | /> | Operational statement participating in the file's runtime behavior.
L0123 | <div class="d-flex gap-2 justify-content-center flex-wrap mt-1 mb-2"> | Assignment statement storing or updating program state.
L0124 | <button type="button" class="btn btn-primary btn-sm id="copyShareUrlBtn"> | Assignment statement storing or updating program state.
L0125 | <i class="bi bi-clipboard-check"></i> Copy Link | Assignment statement storing or updating program state.
L0126 | </button> | Markup line defining structure in an HTML-like template file.
L0127 | <button type="button" class="btn btn-outline-secondary btn-sm id="nativeShareBtn"> | Assignment statement storing or updating program state.
L0128 | <i class="bi bi-send"></i> Share | Assignment statement storing or updating program state.
L0129 | </button> | Markup line defining structure in an HTML-like template file.
L0130 | <a href="{{ technician_login_url }}" target="_blank" rel="noopener" class="btn btn-outline-primary btn-sm"> | Assignment statement storing or updating program state.
L0131 | <i class="bi bi-box-arrow-up-right"></i> Open Link | Assignment statement storing or updating program state.
L0132 | </a> | Markup line defining structure in an HTML-like template file.
L0133 | </div> | Markup line defining structure in an HTML-like template file.
L0134 | | Blank line used for readability and logical separation.
L0135 | <div class="border rounded-3 p-2 mt-1 text-center bg-light-subtle" id="shareQrCard"> | Assignment statement storing or updating program state.
L0136 | <img | Operational statement participating in the file's runtime behavior.
L0137 | id="shareQrImage" | Assignment statement storing or updating program state.
L0138 | alt="Login QR code" | Assignment statement storing or updating program state.
L0139 | width="180" | Assignment statement storing or updating program state.
L0140 | height="180" | Assignment statement storing or updating program state.
L0141 | style="border-radius:10px; border:1px solid rgba(15,60,115,0.15); background:#fff; object-fit:contain;" | Assignment statement storing or updating program state.
L0142 | /> | Operational statement participating in the file's runtime behavior.
L0143 | <div class="small text-muted mt-2" id="qrStatusText">QR code ready</div> | Assignment statement storing or updating program state.
L0144 | <div class="d-flex gap-2 justify-content-center flex-wrap mt-2"> | Assignment statement storing or updating program state.
L0145 | <button type="button" class="btn btn-outline-dark btn-sm id="downloadQrBtn"> | Assignment statement storing or updating program state.
L0146 | <i class="bi bi-download"></i> Download QR | Assignment statement storing or updating program state.
L0147 | </button> | Markup line defining structure in an HTML-like template file.
L0148 | <button type="button" class="btn btn-outline-secondary btn-sm id="refreshQrBtn"> | Assignment statement storing or updating program state.
L0149 | <i class="bi bi-arrow-repeat"></i> Refresh QR | Assignment statement storing or updating program state.
L0150 | </button> | Markup line defining structure in an HTML-like template file.
L0151 | </div> | Markup line defining structure in an HTML-like template file.
L0152 | </div> | Markup line defining structure in an HTML-like template file.
L0153 | | Blank line used for readability and logical separation.
L0154 | {% if not share_link_is_public %} | Block delimiter controlling scope/structure in this language.
L0155 | <div class="alert alert-warning mt-2 mb-0 py-2 small" role="alert"> | Assignment statement storing or updating program state.
L0156 | This is a local/private link and may not work when shared externally. Set PUBLIC_BASE_URL to your real hosted domain. | Operational statement participating in the file's runtime behavior.
L0157 | </div> | Markup line defining structure in an HTML-like template file.
L0158 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0159 | </div> | Markup line defining structure in an HTML-like template file.
L0160 | </div> | Markup line defining structure in an HTML-like template file.
L0161 | </div> | Markup line defining structure in an HTML-like template file.
L0162 | </div> | Markup line defining structure in an HTML-like template file.
L0163 | | Blank line used for readability and logical separation.

```

L0164 | <p class="text-center text-muted small mt-4 mb-0"> | Assignment statement storing or updating program state.

L0165 | Dashboard Footnote: {{ (current_role or 'developer')\|replace('_', ' ')\|title }} | Block delimiter controlling scope/structure in an HTML-like template file.

L0166 | </p> | Markup line defining structure in an HTML-like template file.

L0167 | | Blank line used for readability and logical separation.

L0168 | <!-- Role Access Matrix --> | Markup line defining structure in an HTML-like template file.

L0169 | <div class="card mt-4 mb-2 role-matrix-card"> | Assignment statement storing or updating program state.

L0170 | <div class="card-body p-0"> | Assignment statement storing or updating program state.

L0171 | <div class="role-matrix-header px-4 pt-4 pb-3"> | Assignment statement storing or updating program state.

L0172 | <div class="d-flex align-items-center gap-2"> | Assignment statement storing or updating program state.

L0173 | <i class="bi bi-diagram-3-fill"></i> | Assignment statement storing or updating program state.

L0174 | <div> | Markup line defining structure in an HTML-like template file.

L0175 | <h5 class="mb-0 fw-800">Role Access Matrix</h5> | Assignment statement storing or updating program state.

L0176 | <p class="mb-0 text-muted small">Page ownership, data scope and process dependencies across all system roles.</p> | Assignment statement storing or updating program state.

L0177 | </div> | Markup line defining structure in an HTML-like template file.

L0178 | </div> | Markup line defining structure in an HTML-like template file.

L0179 | </div> | Markup line defining structure in an HTML-like template file.

L0180 | <div class="table-responsive"> | Assignment statement storing or updating program state.

L0181 | <table class="table role-matrix-table mb-0"> | Assignment statement storing or updating program state.

L0182 | <thead> | Markup line defining structure in an HTML-like template file.

L0183 | <tr> | Markup line defining structure in an HTML-like template file.

L0184 | <th>Role</th> | Markup line defining structure in an HTML-like template file.

L0185 | <th>Dashboard</th> | Markup line defining structure in an HTML-like template file.

L0186 | <th>Primary Access</th> | Markup line defining structure in an HTML-like template file.

L0187 | <th>Data Scope</th> | Markup line defining structure in an HTML-like template file.

L0188 | <th>Process Dependency</th> | Markup line defining structure in an HTML-like template file.

L0189 | </tr> | Markup line defining structure in an HTML-like template file.

L0190 | </thead> | Markup line defining structure in an HTML-like template file.

L0191 | <tbody> | Markup line defining structure in an HTML-like template file.

L0192 | <tr class="role-matrix-row role-matrix-technician"> | Assignment statement storing or updating program state.

L0193 | <td> | Markup line defining structure in an HTML-like template file.

L0194 | | Assignment statement storing or updating program state.

L0195 | <i class="bi bi-person-fill-gear"></i> Technician | Assignment statement storing or updating program state.

L0196 | | Markup line defining structure in an HTML-like template file.

L0197 | </td> | Markup line defining structure in an HTML-like template file.

L0198 | <td><code class="role-matrix-page">technician_dashboard</code></td> | Assignment statement storing or updating program state.

L0199 | <td> | Markup line defining structure in an HTML-like template file.

L0200 | <ul class="role-matrix-list"> | Assignment statement storing or updating program state.

L0201 | <i class="bi bi-journal-plus"></i> Fill PM / RCA form | Assignment statement storing or updating program state.

L0202 | <i class="bi bi-x-circle"></i> View own rejected reports | Assignment statement storing or updating program state.

L0203 | <i class="bi bi-chat-dots"></i> Message staff, manager, developer | Assignment statement storing or updating program state.

L0204 | | Markup line defining structure in an HTML-like template file.

L0205 | </td> | Markup line defining structure in an HTML-like template file.

L0206 | <td><i class="bi bi-person-lock"></i> Own submissions only</td> | Assignment statement storing or updating program state.

L0207 | <td>Submits work → staff review and decision</td> | Assignment statement storing or updating program state.

L0208 | </tr> | Markup line defining structure in an HTML-like template file.

L0209 | <tr class="role-matrix-row role-matrix-staff"> | Assignment statement storing or updating program state.

L0210 | <td> | Markup line defining structure in an HTML-like template file.

L0211 | | Assignment statement storing or updating program state.

L0212 | <i class="bi bi-person-badge-fill"></i> Staff | Assignment statement storing or updating program state.

L0213 | | Markup line defining structure in an HTML-like template file.

L0214 | </td> | Markup line defining structure in an HTML-like template file.

L0215 | <td><code class="role-matrix-page">staff_dashboard</code></td> | Assignment statement storing or updating program state.

L0216 | <td> | Markup line defining structure in an HTML-like template file.

L0217 | <ul class="role-matrix-list"> | Assignment statement storing or updating program state.

L0218 | <i class="bi bi-clipboard-check"></i> Desk review queue | Assignment statement storing or updating program state.

L0219 | <i class="bi bi-check2-circle"></i> Approve / reject PM & RCA | Assignment statement storing or updating program state.

L0220 | <i class="bi bi-bell"></i> Notifications & exports | Assignment statement storing or updating program state.

L0221 | | Markup line defining structure in an HTML-like template file.

L0222 | </td> | Markup line defining structure in an HTML-like template file.

L0223 | <td><i class="bi bi-collection"></i> All technician submissions</td> | Assignment statement storing or updating program state.

L0224 | <td>Acts on technician forms → feeds review outcomes to manager</td> | Assignment statement storing or updating program state.

L0225 | </tr> | Markup line defining structure in an HTML-like template file.

L0226 | <tr class="role-matrix-row role-matrix-manager"> | Assignment statement storing or updating program state.

L0227 | <td> | Markup line defining structure in an HTML-like template file.

L0228 | | Assignment statement storing or updating program state.

L0229 | <i class="bi bi-briefcase-fill"></i> Manager / GM | Assignment statement storing or updating program state.

L0230 | | Markup line defining structure in an HTML-like template file.

L0231 | </td> | Markup line defining structure in an HTML-like template file.

L0232 | <td><code class="role-matrix-page">manager_dashboard</code></td> | Assignment statement storing or updating program state.

L0233 | <td> | Markup line defining structure in an HTML-like template file.

L0234 | <ul class="role-matrix-list"> | Assignment statement storing or updating program state.

L0235 | <i class="bi bi-eye"></i> Oversight review queue | Assignment statement storing or updating program state.

L0236 | <i class="bi bi-graph-up-arrow"></i> SLA & risk monitoring | Assignment statement storing or updating program state.

L0237 | <i class="bi bi-shield-check"></i> Final approvals / rejections | Assignment statement storing or updating program state.

L0238 | | Markup line defining structure in an HTML-like template file.

L0239 | </td> | Markup line defining structure in an HTML-like template file.

L0240 | <td><i class="bi bi-collection"></i> All technician submissions</td> | Assignment statement storing or updating program state.

L0241 | <td>Supervises staff pipeline → handles escalations</td> | Assignment statement storing or updating program state.

L0242 | </tr> | Markup line defining structure in an HTML-like template file.

L0243 | <tr class="role-matrix-row role-matrix-developer"> | Assignment statement storing or updating program state.

L0244 | <td> | Markup line defining structure in an HTML-like template file.

L0245 | | Assignment statement storing or updating program state.

L0246 | <i class="bi bi-person-workspace"></i> Developer | Assignment statement storing or updating program state.

L0247 | | Markup line defining structure in an HTML-like template file.

L0248 | </td> | Markup line defining structure in an HTML-like template file.

L0249 | <td><code class="role-matrix-page">developer_role_dashboard</code></td> | Assignment statement storing or updating program state.

L0250 | <td> | Markup line defining structure in an HTML-like template file.

L0251 | <ul class="role-matrix-list"> | Assignment statement storing or updating program state.

L0252 | <i class="bi bi-people"></i> Account management | Assignment statement storing or updating program state.

L0253 | <i class="bi bi-person-lock"></i> User block / unblock controls | Assignment statement storing or updating program state.

L0254 | <i class="bi bi-gear-wide-connected"></i> System notifications & settings | Assignment statement storing or updating program state.

L0255 | | Markup line defining structure in an HTML-like template file.

L0256 | </td> | Markup line defining structure in an HTML-like template file.

L0257 | <td><i class="bi bi-hdd-network"></i> System-wide</td> | Assignment statement storing or updating program state.

L0258 | <td>Creates users → governs role and page boundaries</td> | Assignment statement storing or updating program state.

L0259 | </tr> | Markup line defining structure in an HTML-like template file.

L0260 | </tbody> | Markup line defining structure in an HTML-like template file.

L0261 | </table> | Markup line defining structure in an HTML-like template file.

L0262 | </div> | Markup line defining structure in an HTML-like template file.

L0263 | </div> | Markup line defining structure in an HTML-like template file.

L0264 | </div> | Markup line defining structure in an HTML-like template file.

L0265 | | Blank line used for readability and logical separation.

L0266 | <script> | Markup line defining structure in an HTML-like template file.

L0267 | (function () { | Block delimiter controlling scope/structure in this language.

L0268 | var input = document.getElementById('loginShareUrl'); | Assignment statement storing or updating program state.

L0269 | var qrImage = document.getElementById('shareQrImage'); | Assignment statement storing or updating program state.

L0270 | var statusText = document.getElementById('qrStatusText'); | Assignment statement storing or updating program state.

L0271 | var copyBtn = document.getElementById('copyShareUrlBtn'); | Assignment statement storing or updating program state.

L0272 | var shareBtn = document.getElementById('nativeShareBtn'); | Assignment statement storing or updating program state.

L0273 | var downloadBtn = document.getElementById('downloadQrBtn'); | Assignment statement storing or updating program state.

```

L0274 |     var refreshBtn = document.getElementById('refreshQrBtn'); | Assignment statement storing or updating program state.
L0275 |     var qrEndpoint = "{{ url_for('developer_share_qr') }}"; | Assignment statement storing or updating program state.
L0276 |     var qrFormat = 'svg'; | Assignment statement storing or updating program state.
L0277 |     var initialShareLinkPublic = (input.getAttribute('data-share-link-public') \\| '0') === '1'; | Operational statement participat
L0278 | | Blank line used for readability and logical separation.
L0279 |     if (!input \\| !qrImage) { | Conditional branch that runs only when its condition is true.
L0280 |         return; | Returns a value (or control) back to the caller.
L0281 |     } | Block delimiter controlling scope/structure in this language.
L0282 | | Blank line used for readability and logical separation.
L0283 |     function notify(title, message) { | Block delimiter controlling scope/structure in this language.
L0284 |         if (typeof window.appNotify === 'function') { | Conditional branch that runs only when its condition is true.
L0285 |             window.appNotify({ title: title, message: message }); | Operational statement participating in the file's runtime behavior.
L0286 |         } | Block delimiter controlling scope/structure in this language.
L0287 |     } | Block delimiter controlling scope/structure in this language.
L0288 | | Blank line used for readability and logical separation.
L0289 |     function sanitizeUrl(raw) { | Block delimiter controlling scope/structure in this language.
L0290 |         var value = (raw \\| ' ').trim(); | Assignment statement storing or updating program state.
L0291 |         if (!value) { | Conditional branch that runs only when its condition is true.
L0292 |             return ''; | Returns a value (or control) back to the caller.
L0293 |         } | Block delimiter controlling scope/structure in this language.
L0294 |         if (!/^https?:\\|\\/i.test(value)) { | Conditional branch that runs only when its condition is true.
L0295 |             value = 'https://' + value; | Assignment statement storing or updating program state.
L0296 |         } | Block delimiter controlling scope/structure in this language.
L0297 |         return value; | Returns a value (or control) back to the caller.
L0298 |     } | Block delimiter controlling scope/structure in this language.
L0299 | | Blank line used for readability and logical separation.
L0300 |     function renderQr() { | Block delimiter controlling scope/structure in this language.
L0301 |         var url = sanitizeUrl(input.value); | Assignment statement storing or updating program state.
L0302 |         input.value = url; | Assignment statement storing or updating program state.
L0303 |         if (!url) { | Conditional branch that runs only when its condition is true.
L0304 |             textStatus.textContent = 'Enter a valid URL to generate QR'; | Assignment statement storing or updating program state.
L0305 |             qrImage.removeAttribute('src'); | Operational statement participating in the file's runtime behavior.
L0306 |             return Promise.resolve(false); | Returns a value (or control) back to the caller.
L0307 |         } | Block delimiter controlling scope/structure in this language.
L0308 | | Blank line used for readability and logical separation.
L0309 |         return new Promise(function (resolve) { | Returns a value (or control) back to the caller.
L0310 |             textStatus.textContent = 'Generating QR...'; | Assignment statement storing or updating program state.
L0311 |             var src = qrEndpoint + '?format=' + encodeURIComponent(qrFormat) + '&url=' + encodeURIComponent(url) + '&ts=' + Date.now();
L0312 |             qrImage.onload = function () { | Assignment statement storing or updating program state.
L0313 |                 textStatus.textContent = 'QR code ready'; | Assignment statement storing or updating program state.
L0314 |                 resolve(true); | Operational statement participating in the file's runtime behavior.
L0315 |             }; | Operational statement participating in the file's runtime behavior.
L0316 |             qrImage.onerror = function () { | Assignment statement storing or updating program state.
L0317 |                 textStatus.textContent = 'QR generation failed'; | Assignment statement storing or updating program state.
L0318 |                 resolve(false); | Operational statement participating in the file's runtime behavior.
L0319 |             }; | Operational statement participating in the file's runtime behavior.
L0320 |             qrImage.src = src; | Assignment statement storing or updating program state.
L0321 |         }); | Operational statement participating in the file's runtime behavior.
L0322 |     } | Block delimiter controlling scope/structure in this language.
L0323 | | Blank line used for readability and logical separation.
L0324 |     function copyWithFallback(text) { | Block delimiter controlling scope/structure in this language.
L0325 |         if (navigator.clipboard && window.isSecureContext) { | Conditional branch that runs only when its condition is true.
L0326 |             return navigator.clipboard.writeText(text); | Returns a value (or control) back to the caller.
L0327 |         } | Block delimiter controlling scope/structure in this language.
L0328 |         return new Promise(function (resolve, reject) { | Returns a value (or control) back to the caller.

```

```

L0329 |         try { | Block delimiter controlling scope/structure in this language.
L0330 |             input.focus(); | Operational statement participating in the file's runtime behavior.
L0331 |             input.select(); | Operational statement participating in the file's runtime behavior.
L0332 |             input.setSelectionRange(0, input.value.length); | Operational statement participating in the file's runtime behavior.
L0333 |             var ok = document.execCommand('copy'); | Assignment statement storing or updating program state.
L0334 |             if (ok) { | Conditional branch that runs only when its condition is true.
L0335 |                 resolve(); | Operational statement participating in the file's runtime behavior.
L0336 |             } else { | Block delimiter controlling scope/structure in this language.
L0337 |                 reject(new Error('copy command failed')); | Operational statement participating in the file's runtime behavior.
L0338 |             } | Block delimiter controlling scope/structure in this language.
L0339 |         } catch (err) { | Block delimiter controlling scope/structure in this language.
L0340 |             reject(err); | Operational statement participating in the file's runtime behavior.
L0341 |         } | Block delimiter controlling scope/structure in this language.
L0342 |     }); | Operational statement participating in the file's runtime behavior.
L0343 | } | Block delimiter controlling scope/structure in this language.
L0344 | | Blank line used for readability and logical separation.
L0345 | copyBtn.addEventListener('click', function () { | Block delimiter controlling scope/structure in this language.
L0346 |     var url = sanitizeUrl(input.value); | Assignment statement storing or updating program state.
L0347 |     if (!url) { | Conditional branch that runs only when its condition is true.
L0348 |         notify('Share Link', 'Enter a valid URL before copying.');
```

```

L0384 |         return; | Returns a value (or control) back to the caller.
L0385 |     } | Block delimiter controlling scope/structure in this language.
L0386 |     renderQr().then(function (ready) { | Block delimiter controlling scope/structure in this language.
L0387 |         if (!ready || !qrImage.src) { | Conditional branch that runs only when its condition is true.
L0388 |             notify('Download QR', 'QR code is not ready yet. Click Refresh QR and try again.');
```

| Operational statement participating in the file's runtime behavior.

```

L0389 |             return; | Returns a value (or control) back to the caller.
L0390 |         } | Block delimiter controlling scope/structure in this language.
L0391 | | Blank line used for readability and logical separation.
L0392 |         var anchor = document.createElement('a'); | Assignment statement storing or updating program state.
L0393 |         anchor.href = qrImage.src; | Assignment statement storing or updating program state.
L0394 |         anchor.download = qrFormat === 'svg' ? 'pm_rca_login_qr.svg' : 'pm_rca_login_qr.png'; | Operational statement participating in the file's runtime behavior.
L0395 |         anchor.click(); | Operational statement participating in the file's runtime behavior.
L0396 |     }); | Operational statement participating in the file's runtime behavior.
L0397 | }); | Operational statement participating in the file's runtime behavior.
L0398 | | Blank line used for readability and logical separation.
L0399 |     refreshBtn.addEventListener('click', function () { | Block delimiter controlling scope/structure in this language.
L0400 |         renderQr(); | Operational statement participating in the file's runtime behavior.
L0401 |     }); | Operational statement participating in the file's runtime behavior.
L0402 | | Blank line used for readability and logical separation.
L0403 |     input.addEventListener('change', renderQr); | Operational statement participating in the file's runtime behavior.
L0404 |     input.addEventListener('blur', renderQr); | Operational statement participating in the file's runtime behavior.
L0405 | | Blank line used for readability and logical separation.
L0406 |     if (!initialShareLinkPublic) { | Conditional branch that runs only when its condition is true.
L0407 |         statusText.textContent = 'Set PUBLIC_BASE_URL or enter a reachable public URL before generating QR.'; | Assignment statement
L0408 |     } else { | Block delimiter controlling scope/structure in this language.
L0409 |         renderQr(); | Operational statement participating in the file's runtime behavior.
L0410 |     } | Block delimiter controlling scope/structure in this language.
L0411 | })(); | Operational statement participating in the file's runtime behavior.
L0412 | </script> | Markup line defining structure in an HTML-like template file.
L0413 | </div> | Markup line defining structure in an HTML-like template file.
L0414 | {% endblock %} | Block delimiter controlling scope/structure in this language.

```


File 103: templates/developer_user_activity.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <h1>User Activity Timeline</h1> | Markup line defining structure in an HTML-like template file.
L0004 | <div class="card mt-3 mb-3 p-3"> | Assignment statement storing or updating program state.
L0005 |     <div class="d-flex flex-wrap justify-content-between align-items-center gap-2"> | Assignment statement storing or updating program state.
L0006 |         <div> | Markup line defining structure in an HTML-like template file.
L0007 |             <h5 class="mb-1">{{ target_user.display_name }} ({{ target_user.email }})</h5> | Assignment statement storing or updating program state.
L0008 |             <p class="text-muted mb-0">Role: {{ target_user.role|replace('_', ' ')|title }} \ | Status: {% if target_user.is_blocked %}Blocked{% else %}Active{% endif %}</p>
L0009 |         </div> | Markup line defining structure in an HTML-like template file.
L0010 |         <a href="{{ url_for('developer_user_control') }}" class="btn btn-outline-secondary btn-sm">Back to User Control</a> | Assignment statement storing or updating program state.
L0011 |     </div> | Markup line defining structure in an HTML-like template file.
L0012 | </div> | Markup line defining structure in an HTML-like template file.
L0013 | | Blank line used for readability and logical separation.
L0014 | <div class="card mb-3 p-3"> | Assignment statement storing or updating program state.
L0015 |     <form method="get" class="row g-2 align-items-end"> | Assignment statement storing or updating program state.
L0016 |         <div class="col-12 col-md-6"> | Assignment statement storing or updating program state.
L0017 |             <label class="form-label" for="q">Search Timeline</label> | Assignment statement storing or updating program state.
L0018 |             <input id="q" name="q" type="text" class="form-control" value="{{ search_query }}" placeholder="activity type, details, or actor">
L0019 |         </div> | Markup line defining structure in an HTML-like template file.
L0020 |         <div class="col-6 col-md-3"> | Assignment statement storing or updating program state.
L0021 |             <label class="form-label" for="per_page">Rows</label> | Assignment statement storing or updating program state.
L0022 |             <select id="per_page" name="per_page" class="form-select"> | Assignment statement storing or updating program state.
L0023 |                 {% for option in [10, 20, 30, 50, 100] %} | Block delimiter controlling scope/structure in this language.
L0024 |                 <option value="{{ option }}" {% if per_page == option %}selected{% endif %}>{{ option }}</option> | Markup line defining structure in an HTML-like template file.
L0025 |                 {% endfor %} | Block delimiter controlling scope/structure in this language.
L0026 |             </select> | Markup line defining structure in an HTML-like template file.
L0027 |         </div> | Markup line defining structure in an HTML-like template file.
L0028 |         <div class="col-6 col-md-3"> | Assignment statement storing or updating program state.
L0029 |             <button class="btn btn-primary w-100" type="submit">Apply</button> | Assignment statement storing or updating program state.
L0030 |         </div> | Markup line defining structure in an HTML-like template file.
L0031 |     </form> | Markup line defining structure in an HTML-like template file.
L0032 | </div> | Markup line defining structure in an HTML-like template file.
L0033 | | Blank line used for readability and logical separation.
L0034 | <div class="card p-3"> | Assignment statement storing or updating program state.
L0035 |     {% if activities %} | Block delimiter controlling scope/structure in this language.
L0036 |     <div class="table-responsive"> | Assignment statement storing or updating program state.
L0037 |         <table class="table table-sm align-middle"> | Assignment statement storing or updating program state.
L0038 |             <thead class="table-light"> | Assignment statement storing or updating program state.
L0039 |                 <tr> | Markup line defining structure in an HTML-like template file.
L0040 |                     <th>Time</th> | Markup line defining structure in an HTML-like template file.
L0041 |                     <th>Type</th> | Markup line defining structure in an HTML-like template file.
L0042 |                     <th>Actor</th> | Markup line defining structure in an HTML-like template file.
L0043 |                     <th>Details</th> | Markup line defining structure in an HTML-like template file.
L0044 |                 </tr> | Markup line defining structure in an HTML-like template file.
L0045 |             </thead> | Markup line defining structure in an HTML-like template file.
L0046 |             <tbody> | Markup line defining structure in an HTML-like template file.
L0047 |                 {% for item in activities %} | Block delimiter controlling scope/structure in this language.
L0048 |                 <tr> | Markup line defining structure in an HTML-like template file.
L0049 |                     <td class="text-nowrap">{{ item.created_at.strftime('%Y-%m-%d %H:%M:%S') }}</td> | Assignment statement storing or updating program state.
L0050 |                     <td>{{ item.activity_type|upper }}</td> | Markup line defining structure in an HTML-like template file.
L0051 |                     <td>{{ item.created_by or 'system' }}</td> | Markup line defining structure in an HTML-like template file.
L0052 |                     <td>{{ item.details }}</td> | Markup line defining structure in an HTML-like template file.
L0053 |                 </tr> | Markup line defining structure in an HTML-like template file.
```

L0054 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0055 | </tbody> | Markup line defining structure in an HTML-like template file.

L0056 | </table> | Markup line defining structure in an HTML-like template file.

L0057 | </div> | Markup line defining structure in an HTML-like template file.

L0058 | | Blank line used for readability and logical separation.

L0059 | <div class="d-flex justify-content-between align-items-center mt-2"> | Assignment statement storing or updating program state.

L0060 | <small class="text-muted">Showing {{ activities\|length }} of {{ pagination.total }} records.</small> | Assignment statement storing or updating program state.

L0061 | <div class="btn-group" role="group" aria-label="Pagination"> | Assignment statement storing or updating program state.

L0062 | {% if pagination.has_prev %} | Block delimiter controlling scope/structure in this language.

L0063 | | Assignment statement storing or updating program state.

L0064 | {% else %} | Block delimiter controlling scope/structure in this language.

L0065 | <button class="btn btn-sm btn-outline-secondary" disabled>Previous</button> | Assignment statement storing or updating program state.

L0066 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0067 | | Blank line used for readability and logical separation.

L0068 | {% if pagination.has_next %} | Block delimiter controlling scope/structure in this language.

L0069 | | Assignment statement storing or updating program state.

L0070 | {% else %} | Block delimiter controlling scope/structure in this language.

L0071 | <button class="btn btn-sm btn-outline-secondary" disabled>Next</button> | Assignment statement storing or updating program state.

L0072 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0073 | </div> | Markup line defining structure in an HTML-like template file.

L0074 | </div> | Markup line defining structure in an HTML-like template file.

L0075 | {% else %} | Block delimiter controlling scope/structure in this language.

L0076 | <p class="text-muted mb-0">No activities found for this user with the current filters.</p> | Assignment statement storing or updating program state.

L0077 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0078 | </div> | Markup line defining structure in an HTML-like template file.

L0079 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 104: templates/developer_user_control.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | | Blank line used for readability and logical separation.
L0004 | <div class="d-flex align-items-center gap-2 mb-1"> | Assignment statement storing or updating program state.
L0005 |     <i class="bi bi-terminal-fill fs-4 text-primary"></i> | Assignment statement storing or updating program state.
L0006 |     <h1 class="mb-0">Developer User Control</h1> | Assignment statement storing or updating program state.
L0007 | </div> | Markup line defining structure in an HTML-like template file.
L0008 | <p class="text-muted mb-4">Full system governance – user access, upload limits, scanner policy, role matrix, security posture, and
L0009 | | Blank line used for readability and logical separation.
L0010 | <!-- System Status Bar --> | Markup line defining structure in an HTML-like template file.
L0011 | <div class="row g-3 mb-4"> | Assignment statement storing or updating program state.
L0012 |     <div class="col-6 col-md-3"> | Assignment statement storing or updating program state.
L0013 |         <div class="card text-center p-3 border-0 bg-success-subtle"> | Assignment statement storing or updating program state.
L0014 |             <div class="fs-2 fw-bold text-success">{{ users|length }}</div> | Assignment statement storing or updating program state.
L0015 |             <div class="small text-muted">Total Users</div> | Assignment statement storing or updating program state.
L0016 |         </div> | Markup line defining structure in an HTML-like template file.
L0017 |     </div> | Markup line defining structure in an HTML-like template file.
L0018 | <div class="col-6 col-md-3"> | Assignment statement storing or updating program state.
L0019 |     <div class="card text-center p-3 border-0 bg-danger-subtle"> | Assignment statement storing or updating program state.
L0020 |         <div class="fs-2 fw-bold text-danger">{{ users|selectattr('is_blocked')|list|length }}</div> | Assignment statement storing or updating program state.
L0021 |         <div class="small text-muted">Blocked Accounts</div> | Assignment statement storing or updating program state.
L0022 |     </div> | Markup line defining structure in an HTML-like template file.
L0023 | </div> | Markup line defining structure in an HTML-like template file.
L0024 | <div class="col-6 col-md-3"> | Assignment statement storing or updating program state.
L0025 |     <div class="card text-center p-3 border-0 bg-info-subtle"> | Assignment statement storing or updating program state.
L0026 |         <div class="fs-2 fw-bold text-info">{{ max_upload_mb }}MB</div> | Assignment statement storing or updating program state.
L0027 |         <div class="small text-muted">Upload Cap</div> | Assignment statement storing or updating program state.
L0028 |     </div> | Markup line defining structure in an HTML-like template file.
L0029 | </div> | Markup line defining structure in an HTML-like template file.
L0030 | <div class="col-6 col-md-3"> | Assignment statement storing or updating program state.
L0031 |     <div class="card text-center p-3 border-0 bg-warning-subtle"> | Assignment statement storing or updating program state.
L0032 |         <div class="fs-2 fw-bold text-warning">{{ photo_library_controls.max_scan_limit }}</div> | Assignment statement storing or updating program state.
L0033 |         <div class="small text-muted">Scan Limit</div> | Assignment statement storing or updating program state.
L0034 |     </div> | Markup line defining structure in an HTML-like template file.
L0035 | </div> | Markup line defining structure in an HTML-like template file.
L0036 | </div> | Markup line defining structure in an HTML-like template file.
L0037 | | Blank line used for readability and logical separation.
L0038 | <!-- Security Posture Card --> | Markup line defining structure in an HTML-like template file.
L0039 | <div class="card mb-4 p-3 border-warning"> | Assignment statement storing or updating program state.
L0040 |     <div class="d-flex align-items-center gap-2 mb-3"> | Assignment statement storing or updating program state.
L0041 |         <i class="bi bi-shield-lock-fill text-warning fs-5"></i> | Assignment statement storing or updating program state.
L0042 |         <h5 class="mb-0">Security Posture</h5> | Assignment statement storing or updating program state.
L0043 |         <span class="badge text-bg-secondary ms-auto">Runtime Config</span> | Assignment statement storing or updating program state.
L0044 |     </div> | Markup line defining structure in an HTML-like template file.
L0045 | <div class="row g-2"> | Assignment statement storing or updating program state.
L0046 |     <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.
L0047 |         <div class="d-flex align-items-center gap-2 p-2 rounded bg-body-secondary"> | Assignment statement storing or updating program state.
L0048 |             <i class="bi bi-cookie text-secondary"></i> | Assignment statement storing or updating program state.
L0049 |             <div> | Markup line defining structure in an HTML-like template file.
L0050 |                 <div class="small fw-semibold">Session Cookie Secure</div> | Assignment statement storing or updating program state.
L0051 |                 <div class="small text-muted">Set <code>SESSION_COOKIE_SECURE=1</code> in env</div> | Assignment statement storing or updating program state.
L0052 |             </div> | Markup line defining structure in an HTML-like template file.
L0053 |             <span class="badge ms-auto {% if config.SESSI
```

L0054 | {{ 'ON' if config.SESSION_COOKIE_SECURE else 'OFF' }} | Block delimiter controlling scope/structure in this language.

L0055 | | Markup line defining structure in an HTML-like template file.

L0056 | </div> | Markup line defining structure in an HTML-like template file.

L0057 | </div> | Markup line defining structure in an HTML-like template file.

L0058 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.

L0059 | <div class="d-flex align-items-center gap-2 p-2 rounded bg-body-secondary"> | Assignment statement storing or updating program state.

L0060 | <i class="bi bi-cookie text-secondary"></i> | Assignment statement storing or updating program state.

L0061 | </div> | Markup line defining structure in an HTML-like template file.

L0062 | <div class="small fw-semibold">Remember Cookie Secure</div> | Assignment statement storing or updating program state.

L0063 | <div class="small text-muted">Mirrors SESSION_COOKIE_SECURE</div> | Assignment statement storing or updating program state.

L0064 | </div> | Markup line defining structure in an HTML-like template file.

L0065 | | Assignment statement storing or updating program state.

L0066 | {{ 'ON' if config.REMEMBER_COOKIE_SECURE else 'OFF' }} | Block delimiter controlling scope/structure in this language.

L0067 | | Markup line defining structure in an HTML-like template file.

L0068 | </div> | Markup line defining structure in an HTML-like template file.

L0069 | </div> | Markup line defining structure in an HTML-like template file.

L0070 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.

L0071 | <div class="d-flex align-items-center gap-2 p-2 rounded bg-body-secondary"> | Assignment statement storing or updating program state.

L0072 | <i class="bi bi-globe text-secondary"></i> | Assignment statement storing or updating program state.

L0073 | </div> | Markup line defining structure in an HTML-like template file.

L0074 | <div class="small fw-semibold">URL Scheme</div> | Assignment statement storing or updating program state.

L0075 | <div class="small text-muted">Set <code>PREFERRED_URL_SCHEME=https</code></div> | Assignment statement storing or updating program state.

L0076 | </div> | Markup line defining structure in an HTML-like template file.

L0077 | | Assignment statement storing or updating program state.

L0078 | {{ config.PREFERRED_URL_SCHEME|upper }} | Block delimiter controlling scope/structure in this language.

L0079 | | Markup line defining structure in an HTML-like template file.

L0080 | </div> | Markup line defining structure in an HTML-like template file.

L0081 | </div> | Markup line defining structure in an HTML-like template file.

L0082 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.

L0083 | <div class="d-flex align-items-center gap-2 p-2 rounded bg-body-secondary"> | Assignment statement storing or updating program state.

L0084 | <i class="bi bi-shield-check text-secondary"></i> | Assignment statement storing or updating program state.

L0085 | </div> | Markup line defining structure in an HTML-like template file.

L0086 | <div class="small fw-semibold">CSRF Protection</div> | Assignment statement storing or updating program state.

L0087 | <div class="small text-muted">Always active on POST routes</div> | Assignment statement storing or updating program state.

L0088 | </div> | Markup line defining structure in an HTML-like template file.

L0089 | ON | Assignment statement storing or updating program state.

L0090 | </div> | Markup line defining structure in an HTML-like template file.

L0091 | </div> | Markup line defining structure in an HTML-like template file.

L0092 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.

L0093 | <div class="d-flex align-items-center gap-2 p-2 rounded bg-body-secondary"> | Assignment statement storing or updating program state.

L0094 | <i class="bi bi-lock-fill text-secondary"></i> | Assignment statement storing or updating program state.

L0095 | </div> | Markup line defining structure in an HTML-like template file.

L0096 | <div class="small fw-semibold">Session HttpOnly</div> | Assignment statement storing or updating program state.

L0097 | <div class="small text-muted">Always enforced</div> | Assignment statement storing or updating program state.

L0098 | </div> | Markup line defining structure in an HTML-like template file.

L0099 | ON | Assignment statement storing or updating program state.

L0100 | </div> | Markup line defining structure in an HTML-like template file.

L0101 | </div> | Markup line defining structure in an HTML-like template file.

L0102 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.

L0103 | <div class="d-flex align-items-center gap-2 p-2 rounded bg-body-secondary"> | Assignment statement storing or updating program state.

L0104 | <i class="bi bi-shield text-secondary"></i> | Assignment statement storing or updating program state.

L0105 | </div> | Markup line defining structure in an HTML-like template file.

L0106 | <div class="small fw-semibold">SameSite Policy</div> | Assignment statement storing or updating program state.

L0107 | <div class="small text-muted">Session + Remember cookies</div> | Assignment statement storing or updating program state.

L0108 | </div> | Markup line defining structure in an HTML-like template file.

L0109 | Lax | Assignment statement storing or updating program state.

L0110 | </div> | Markup line defining structure in an HTML-like template file.

L0111 | </div> | Markup line defining structure in an HTML-like template file.

L0112 | </div> | Markup line defining structure in an HTML-like template file.

L0113 | </div> | Markup line defining structure in an HTML-like template file.

L0114 | | Blank line used for readability and logical separation.

L0115 | {% if issued_credentials %} | Block delimiter controlling scope/structure in this language.

L0116 | <div class="alert alert-warning"> | Assignment statement storing or updating program state.

L0117 | Temporary Credentials: | Markup line defining structure in an HTML-like template file.

L0118 | <div>Email: {{ issued_credentials.email }}</div> | Markup line defining structure in an HTML-like template file.

L0119 | <div>Password: {{ issued_credentials.password }}</div> | Markup line defining structure in an HTML-like template file.

L0120 | <div class="small text-muted">Copy now. This is shown once.</div> | Assignment statement storing or updating program state.

L0121 | </div> | Markup line defining structure in an HTML-like template file.

L0122 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0123 | | Blank line used for readability and logical separation.

L0124 | <div class="row g-3 mb-4"> | Assignment statement storing or updating program state.

L0125 | <div class="col-12 col-lg-6"> | Assignment statement storing or updating program state.

L0126 | <div class="card h-100 p-3"> | Assignment statement storing or updating program state.

L0127 | <h5 class="mb-1"><i class="bi bi-sliders me-2"></i>System Upload Limits</h5> | Assignment statement storing or updating program state.

L0128 | <p class="text-muted small mb-3">Cap per-image and per-request file sizes. Changes apply immediately to all users.</p> | Assignment statement storing or updating program state.

L0129 | <form method="post" action="{{ url_for('developer_user_control') }}"> | Assignment statement storing or updating program state.

L0130 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0131 | <input type="hidden" name="action" value="update_upload_limits" /> | Assignment statement storing or updating program state.

L0132 | | Blank line used for readability and logical separation.

L0133 | <div class="mb-3"> | Assignment statement storing or updating program state.

L0134 | <label class="form-label" for="max_photo_mb">MAX_PHOTO_MB (per image)</label> | Assignment statement storing or updating program state.

L0135 | <input | Operational statement participating in the file's runtime behavior.

L0136 | type="number" | Assignment statement storing or updating program state.

L0137 | min="1" | Assignment statement storing or updating program state.

L0138 | max="20" | Assignment statement storing or updating program state.

L0139 | step="1" | Assignment statement storing or updating program state.

L0140 | id="max_photo_mb" | Assignment statement storing or updating program state.

L0141 | name="max_photo_mb" | Assignment statement storing or updating program state.

L0142 | class="form-control" | Assignment statement storing or updating program state.

L0143 | value="{{ max_photo_mb }}" | Assignment statement storing or updating program state.

L0144 | required | Operational statement participating in the file's runtime behavior.

L0145 | /> | Operational statement participating in the file's runtime behavior.

L0146 | <small class="text-muted">Reduce or increase the per-image cap in MB.</small> | Assignment statement storing or updating program state.

L0147 | </div> | Markup line defining structure in an HTML-like template file.

L0148 | | Blank line used for readability and logical separation.

L0149 | <div class="mb-3"> | Assignment statement storing or updating program state.

L0150 | <label class="form-label" for="max_upload_mb">MAX_UPLOAD_MB (full request)</label> | Assignment statement storing or updating program state.

L0151 | <input | Operational statement participating in the file's runtime behavior.

L0152 | type="number" | Assignment statement storing or updating program state.

L0153 | min="{{ min_upload_mb }}" | Assignment statement storing or updating program state.

L0154 | max="512" | Assignment statement storing or updating program state.

L0155 | step="1" | Assignment statement storing or updating program state.

L0156 | id="max_upload_mb" | Assignment statement storing or updating program state.

L0157 | name="max_upload_mb" | Assignment statement storing or updating program state.

L0158 | class="form-control" | Assignment statement storing or updating program state.

L0159 | value="{{ max_upload_mb }}" | Assignment statement storing or updating program state.

L0160 | required | Operational statement participating in the file's runtime behavior.

L0161 | /> | Operational statement participating in the file's runtime behavior.

L0162 | <small class="text-muted">Set a fixed total cap. Minimum currently required: {{ min_upload_mb }}MB.</small> | Assignment statement storing or updating program state.

L0163 | </div> | Markup line defining structure in an HTML-like template file.

L0164 | | Blank line used for readability and logical separation.

L0165 | <button type="submit" class="btn btn-primary">Save Upload Limits</button> | Assignment statement storing or updating program state.

L0166 | </form> | Markup line defining structure in an HTML-like template file.

L0167 | </div> | Markup line defining structure in an HTML-like template file.

L0168 | </div> | Markup line defining structure in an HTML-like template file.

L0169 | | Blank line used for readability and logical separation.

L0170 | <div class="col-12 col-lg-6"> | Assignment statement storing or updating program state.

L0171 | <div class="card h-100 p-3"> | Assignment statement storing or updating program state.

L0172 | <h5 class="mb-1"><i class="bi bi-images me-2"></i>Photo Scanner Controls</h5> | Assignment statement storing or updating program state.

L0173 | <p class="text-muted small mb-3">Set import and scan policy for the developer photo library. Limits apply per-request during upload.</p>

L0174 | <form method="post" action="{% url_for('developer_user_control') %}"> | Assignment statement storing or updating program state.

L0175 | <input type="hidden" name="csrf_token" value="{% csrf_token %}" /> | Assignment statement storing or updating program state.

L0176 | <input type="hidden" name="action" value="update_photo_library_controls" /> | Assignment statement storing or updating program state.

L0177 | | Blank line used for readability and logical separation.

L0178 | <div class="form-check form-switch mb-2"> | Assignment statement storing or updating program state.

L0179 | <input class="form-check-input" type="checkbox" id="include_screenshots" name="include_screenshots" value="1" {% if photo_library_controls.include_screenshots %}>

L0180 | <label class="form-check-label" for="include_screenshots">Include screenshots in scan results</label> | Assignment statement storing or updating program state.

L0181 | </div> | Markup line defining structure in an HTML-like template file.

L0182 | | Blank line used for readability and logical separation.

L0183 | <div class="form-check form-switch mb-3"> | Assignment statement storing or updating program state.

L0184 | <input class="form-check-input" type="checkbox" id="allow_import" name="allow_import" value="1" {% if photo_library_controls.allow_import %}>

L0185 | <label class="form-check-label" for="allow_import">Allow importing monitored images into uploads</label> | Assignment statement storing or updating program state.

L0186 | </div> | Markup line defining structure in an HTML-like template file.

L0187 | | Blank line used for readability and logical separation.

L0188 | <div class="mb-3"> | Assignment statement storing or updating program state.

L0189 | <label class="form-label" for="max_scan_limit">Maximum scan limit per request</label> | Assignment statement storing or updating program state.

L0190 | <input | Operational statement participating in the file's runtime behavior.

L0191 | type="number" | Assignment statement storing or updating program state.

L0192 | min="12" | Assignment statement storing or updating program state.

L0193 | max="200" | Assignment statement storing or updating program state.

L0194 | step="1" | Assignment statement storing or updating program state.

L0195 | id="max_scan_limit" | Assignment statement storing or updating program state.

L0196 | name="max_scan_limit" | Assignment statement storing or updating program state.

L0197 | class="form-control" | Assignment statement storing or updating program state.

L0198 | value="{% if photo_library_controls.max_scan_limit %}{{ photo_library_controls.max_scan_limit }}" | Assignment statement storing or updating program state.

L0199 | required | Operational statement participating in the file's runtime behavior.

L0200 | /> | Operational statement participating in the file's runtime behavior.

L0201 | <small class="text-muted">Controls how many images the Photo Library page can load at once.</small> | Assignment statement storing or updating program state.

L0202 | </div> | Markup line defining structure in an HTML-like template file.

L0203 | | Blank line used for readability and logical separation.

L0204 | <button type="submit" class="btn btn-primary">Save Photo Scanner Controls</button> | Assignment statement storing or updating program state.

L0205 | </form> | Markup line defining structure in an HTML-like template file.

L0206 | </div> | Markup line defining structure in an HTML-like template file.

L0207 | </div> | Markup line defining structure in an HTML-like template file.

L0208 | | Blank line used for readability and logical separation.

L0209 | <div class="col-12 col-lg-6"> | Assignment statement storing or updating program state.

L0210 | <div class="card h-100 p-3"> | Assignment statement storing or updating program state.

L0211 | <h5 class="mb-1"><i class="bi bi-clock-history me-2"></i>Audit Trail</h5> | Assignment statement storing or updating program state.

L0212 | <p class="text-muted small mb-3">Last 20 developer user-control actions recorded in the activity log.</p> | Assignment statement storing or updating program state.

L0213 | <div style="max-height: 300px; overflow-y: auto;"> | Assignment statement storing or updating program state.

L0214 | {% if recent_user_actions %} | Block delimiter controlling scope/structure in this language.

L0215 | <ul class="list-group list-group-flush"> | Assignment statement storing or updating program state.

L0216 | {% for event in recent_user_actions %} | Block delimiter controlling scope/structure in this language.

L0217 | <li class="list-group-item px-0"> | Assignment statement storing or updating program state.

L0218 | <div class="fw-semibold">{{ event.details }}</div> | Assignment statement storing or updating program state.

L0219 | <small class="text-muted">{{ event.created_at.strftime('%Y-%m-%d %H:%M:%S') }}</small> | Assignment statement storing or updating program state.

L0220 | | Markup line defining structure in an HTML-like template file.

L0221 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0222 | | Markup line defining structure in an HTML-like template file.

L0223 | {% else %} | Block delimiter controlling scope/structure in this language.

L0224 | <p class="text-muted mb-0">No admin actions recorded yet.</p> | Assignment statement storing or updating program state.

L0225 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0226 | </div> | Markup line defining structure in an HTML-like template file.

L0227 | </div> | Markup line defining structure in an HTML-like template file.

L0228 | </div> | Markup line defining structure in an HTML-like template file.

L0229 | </div> | Markup line defining structure in an HTML-like template file.

L0230 | | Blank line used for readability and logical separation.

L0231 | <div class="card mb-4 p-3"> | Assignment statement storing or updating program state.

L0232 | <div class="d-flex align-items-center gap-2 mb-1"> | Assignment statement storing or updating program state.

L0233 | <i class="bi bi-grid-3x3-gap fs-5 text-primary"></i> | Assignment statement storing or updating program state.

L0234 | <h5 class="mb-0">Role Access Matrix</h5> | Assignment statement storing or updating program state.

L0235 | Login Gate | Assignment statement storing or updating program state.

L0236 | </div> | Markup line defining structure in an HTML-like template file.

L0237 | <p class="text-muted small mb-3">Control which account roles can authenticate under each login entry point. Unchecked roles are blocked.

L0238 | <form method="post" action="{{ url_for('developer_user_control') }}"> | Assignment statement storing or updating program state.

L0239 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0240 | <input type="hidden" name="action" value="update_role_access_matrix" /> | Assignment statement storing or updating program state.

L0241 | | Blank line used for readability and logical separation.

L0242 | <div class="table-responsive"> | Assignment statement storing or updating program state.

L0243 | <table class="table table-sm align-middle"> | Assignment statement storing or updating program state.

L0244 | <thead class="table-light"> | Assignment statement storing or updating program state.

L0245 | <tr> | Markup line defining structure in an HTML-like template file.

L0246 | <th>Login Entry</th> | Markup line defining structure in an HTML-like template file.

L0247 | {% for role in role_matrix_columns %} | Block delimiter controlling scope/structure in this language.

L0248 | <th>{{ role|replace('_', ' ')|title }}</th> | Markup line defining structure in an HTML-like template file.

L0249 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0250 | </tr> | Markup line defining structure in an HTML-like template file.

L0251 | </thead> | Markup line defining structure in an HTML-like template file.

L0252 | <tbody> | Markup line defining structure in an HTML-like template file.

L0253 | {% for entry in role_matrix_keys %} | Block delimiter controlling scope/structure in this language.

L0254 | <tr> | Markup line defining structure in an HTML-like template file.

L0255 | <td>{{ entry|replace('_', ' ')|title }}</td> | Markup line defining structure in an HTML-like template file.

L0256 | {% for role in role_matrix_columns %} | Block delimiter controlling scope/structure in this language.

L0257 | <td> | Markup line defining structure in an HTML-like template file.

L0258 | <div class="form-check mb-0"> | Assignment statement storing or updating program state.

L0259 | <input | Operational statement participating in the file's runtime behavior.

L0260 | class="form-check-input" | Assignment statement storing or updating program state.

L0261 | type="checkbox" | Assignment statement storing or updating program state.

L0262 | id="matrix_{{ entry }}_{{ role }}" | Assignment statement storing or updating program state.

L0263 | name="matrix_{{ entry }}" | Assignment statement storing or updating program state.

L0264 | value="{{ role }}" | Assignment statement storing or updating program state.

L0265 | {% if role in role_matrix.get(entry, []) %}checked{% endif %} | Block delimiter controlling scope/structure in this language.

L0266 | /> | Operational statement participating in the file's runtime behavior.

L0267 | <label class="form-check-label" for="matrix_{{ entry }}_{{ role }}"></label> | Assignment statement storing or updating program state.

L0268 | </div> | Markup line defining structure in an HTML-like template file.

L0269 | </td> | Markup line defining structure in an HTML-like template file.

L0270 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0271 | </tr> | Markup line defining structure in an HTML-like template file.

L0272 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0273 | </tbody> | Markup line defining structure in an HTML-like template file.

L0274 | </table> | Markup line defining structure in an HTML-like template file.

L0275 | </div> | Markup line defining structure in an HTML-like template file.

L0276 | | Blank line used for readability and logical separation.

L0277 | <button type="submit" class="btn btn-primary">Save Role Matrix</button> | Assignment statement storing or updating program state.

L0278 | </form> | Markup line defining structure in an HTML-like template file.

L0279 | </div> | Markup line defining structure in an HTML-like template file.

L0280 | | Blank line used for readability and logical separation.

L0281 | <div class="d-flex align-items-center gap-2 mb-3"> | Assignment statement storing or updating program state.

L0282 | <i class="bi bi-people-fill fs-5 text-primary"></i> | Assignment statement storing or updating program state.

L0283 | <h5 class="mb-0">User Accounts</h5> | Assignment statement storing or updating program state.

L0284 | {{ users\|length }} total | Assignment statement storing or updating program state.

L0285 | {{ users\|selectattr('is_blocked')\|list\|length }} blocked | Assignment statement storing or updating program state.

L0286 | </div> | Markup line defining structure in an HTML-like template file.

L0287 | <div class="row row-cols-1 row-cols-lg-2 g-3 profile-grid-row"> | Assignment statement storing or updating program state.

L0288 | {% for user in users %} | Block delimiter controlling scope/structure in this language.

L0289 | {% set gender_value = (user.gender or '')\|lower %} | Assignment statement storing or updating program state.

L0290 | {% set avatar_key = avatar_choice_map.get(user.id, 'neutral') %} | Assignment statement storing or updating program state.

L0291 | {% set avatar_icon = avatar_icon_map.get(avatar_key, 'person-circle') %} | Assignment statement storing or updating program state.

L0292 | {% set user_settings = user_settings_map.get(user.id, {}) %} | Assignment statement storing or updating program state.

L0293 | {% set avatar_meta = namespace(label='Default') %} | Assignment statement storing or updating program state.

L0294 | {% for avatar in avatar_options %} | Block delimiter controlling scope/structure in this language.

L0295 | {% if avatar.key == avatar_key %} | Block delimiter controlling scope/structure in this language.

L0296 | {% set avatar_meta.label = avatar.label %} | Assignment statement storing or updating program state.

L0297 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0298 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0299 | <div class="col"> | Assignment statement storing or updating program state.

L0300 | <div class="card profile-card role-{{ (user.role or 'user')\|replace('_', '-')\|lower }} h-100 p-3"> | Assignment statement storing or updating program state.

L0301 | <div class="d-flex justify-content-between align-items-start gap-2 mb-2"> | Assignment statement storing or updating program state.

L0302 | <div> | Markup line defining structure in an HTML-like template file.

L0303 | <h5 class="mb-1">{{ user.display_name }}</h5> | Assignment statement storing or updating program state.

L0304 | {% if user.uid %} | Block delimiter controlling scope/structure in this language.

L0305 | {{ user.uid }} | Assignment statement storing or updating program state.

L0306 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0307 | <div class="small text-muted">{{ user.email }}</div> | Assignment statement storing or updating program state.

L0308 | </div> | Markup line defining structure in an HTML-like template file.

L0309 | <div class="profile-identity-stack"> | Assignment statement storing or updating program state.

L0310 | <div class="profile-avatar-pill" data-avatar-key="{{ avatar_key }}" title="Avatar preset: {{ avatar_meta.label }}"> | Assignment statement storing or updating program state.

L0311 | <i class="bi bi-{{ avatar_icon }} avatar-glyph"></i> | Assignment statement storing or updating program state.

L0312 | {{ avatar_meta.label }} | Assignment statement storing or updating program state.

L0313 | </div> | Markup line defining structure in an HTML-like template file.

L0314 | <div class="profile-gender-pill"> | Assignment statement storing or updating program state.

L0315 | {% if gender_value in ['female', 'f'] %} | Block delimiter controlling scope/structure in this language.

L0316 | <i class="bi bi-gender-female"></i>Female | Assignment statement storing or updating program state.

L0317 | {% elif gender_value in ['male', 'm'] %} | Block delimiter controlling scope/structure in this language.

L0318 | <i class="bi bi-gender-male"></i>Male | Assignment statement storing or updating program state.

L0319 | {% elif gender_value in ['other', 'o'] %} | Block delimiter controlling scope/structure in this language.

L0320 | <i class="bi bi-gender-ambiguous"></i>Other | Assignment statement storing or updating program state.

L0321 | {% else %} | Block delimiter controlling scope/structure in this language.

L0322 | <i class="bi bi-person-fill"></i>Not set | Assignment statement storing or updating program state.

L0323 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0324 | </div> | Markup line defining structure in an HTML-like template file.

L0325 | <div class="text-end"> | Assignment statement storing or updating program state.

L0326 | {% if user.is_blocked %} | Block delimiter controlling scope/structure in this language.

L0327 | Blocked | Assignment statement storing or updating program state.

L0328 | {% else %} | Block delimiter controlling scope/structure in this language.

L0329 | Active | Assignment statement storing or updating program state.

L0330 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0331 | </div> | Markup line defining structure in an HTML-like template file.

L0332 | </div> | Markup line defining structure in an HTML-like template file.

L0333 | </div> | Markup line defining structure in an HTML-like template file.

L0334 | | Blank line used for readability and logical separation.

L0335 | <div class="small text-muted mb-3"> | Assignment statement storing or updating program state.

L0336 | Region: {{ user.region or 'Not set' }} \ | Role: {{ user.role\|replace('_', ' ')\|title }} \ | Theme: {{ (user_settings.theme

L0337 | </div> | Markup line defining structure in an HTML-like template file.

L0338 | | Blank line used for readability and logical separation.

L0339 | <form method="post" action="{{ url_for('edit_user_profile', user_id=user.id) }}" class="mb-3"> | Assignment statement storing

L0340 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state

L0341 | <label class="form-label fw-semibold mb-2">Edit Profile</label> | Assignment statement storing or updating program state.

L0342 | <div class="row g-2"> | Assignment statement storing or updating program state.

L0343 | <div class="col-12 col-md-6"> | Assignment statement storing or updating program state.

L0344 | <input type="text" name="first_name" class="form-control form-control-sm" value="{{ user.first_name or ' ' }}" placeholder="First Name" /> | Assignment statement storing or updating program state.

L0345 | </div> | Markup line defining structure in an HTML-like template file.

L0346 | <div class="col-12 col-md-6"> | Assignment statement storing or updating program state.

L0347 | <input type="text" name="last_name" class="form-control form-control-sm" value="{{ user.last_name or ' ' }}" placeholder="Last Name" /> | Assignment statement storing or updating program state.

L0348 | </div> | Markup line defining structure in an HTML-like template file.

L0349 | <div class="col-12 col-md-8"> | Assignment statement storing or updating program state.

L0350 | <input type="email" name="email" class="form-control form-control-sm" value="{{ user.email }}" placeholder="Email" required="" /> | Assignment statement storing or updating program state.

L0351 | </div> | Markup line defining structure in an HTML-like template file.

L0352 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.

L0353 | <input type="text" name="uid" class="form-control form-control-sm" value="{{ user.uid or ' ' }}" placeholder="UID" maxlength="10" /> | Assignment statement storing or updating program state.

L0354 | </div> | Markup line defining structure in an HTML-like template file.

L0355 | <div class="col-12 col-md-6"> | Assignment statement storing or updating program state.

L0356 | <input type="text" name="region" class="form-control form-control-sm" value="{{ user.region or ' ' }}" placeholder="Region" /> | Assignment statement storing or updating program state.

L0357 | </div> | Markup line defining structure in an HTML-like template file.

L0358 | <div class="col-12 col-md-6"> | Assignment statement storing or updating program state.

L0359 | <select name="gender" class="form-select form-select-sm" aria-label="Gender for {{ user.email }}"> | Assignment statement storing or updating program state.

L0360 | <option value="" {% if not user.gender %}selected{% endif %}>Gender</option> | Assignment statement storing or updating program state.

L0361 | <option value="male" {% if (user.gender or '')\|lower == 'male' %}selected{% endif %}>Male</option> | Markup line defining structure in an HTML-like template file.

L0362 | <option value="female" {% if (user.gender or '')\|lower == 'female' %}selected{% endif %}>Female</option> | Markup line defining structure in an HTML-like template file.

L0363 | <option value="other" {% if (user.gender or '')\|lower == 'other' %}selected{% endif %}>Other</option> | Markup line defining structure in an HTML-like template file.

L0364 | </select> | Markup line defining structure in an HTML-like template file.

L0365 | </div> | Markup line defining structure in an HTML-like template file.

L0366 | <div class="col-12"> | Assignment statement storing or updating program state.

L0367 | <div class="avatar-pick-group" role="group" aria-label="Avatar preset for {{ user.email }}"> | Assignment statement storing or updating program state.

L0368 | {% for avatar in avatar_options %} | Block delimiter controlling scope/structure in this language.

L0369 | <label class="avatar-pick-tile{% if avatar_key == avatar.key %} is-selected{% endif %}" title="{{ avatar.label }}"> | Assignment statement storing or updating program state.

L0370 | <input type="radio" name="avatar_key" value="{{ avatar.key }}" {% if avatar_key == avatar.key %}checked{% endif %} /> | Assignment statement storing or updating program state.

L0371 | <i class="bi bi-{{ avatar.icon }}"></i> | Assignment statement storing or updating program state.

L0372 | {{ avatar.label }} | Markup line defining structure in an HTML-like template file.

L0373 | </label> | Markup line defining structure in an HTML-like template file.

L0374 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0375 | </div> | Markup line defining structure in an HTML-like template file.

L0376 | </div> | Markup line defining structure in an HTML-like template file.

L0377 | <div class="col-12"> | Assignment statement storing or updating program state.

L0378 | <input type="text" name="support_desk" class="form-control form-control-sm" value="{{ user.support_desk or ' ' }}" placeholder="Support Desk" /> | Assignment statement storing or updating program state.

L0379 | </div> | Markup line defining structure in an HTML-like template file.

L0380 | <div class="col-12 col-md-6"> | Assignment statement storing or updating program state.

L0381 | <input type="text" name="site_operations_phone" class="form-control form-control-sm" value="{{ user.site_operations_phone or ' ' }}" placeholder="Site Operations Phone" /> | Assignment statement storing or updating program state.

L0382 | </div> | Markup line defining structure in an HTML-like template file.

L0383 | <div class="col-12 col-md-6"> | Assignment statement storing or updating program state.

L0384 |

L0385 | </div> | Markup line defining structure in an HTML-like template file.

L0386 | </div> | Markup line defining structure in an HTML-like template file.

L0387 | <div class="mt-2 d-flex justify-content-end"> | Assignment statement storing or updating program state.

L0388 | <button type="submit" class="btn btn-sm btn-primary">Save Profile</button> | Assignment statement storing or updating program state.

L0389 | </div> | Markup line defining structure in an HTML-like template file.

L0390 | </form> | Markup line defining structure in an HTML-like template file.

L0391 | | Blank line used for readability and logical separation.

L0392 | {% if user.id != current_user.id %} | Block delimiter controlling scope/structure in this language.

L0393 | <div class="developer-control-panel mb-3"> | Assignment statement storing or updating program state.

L0394 | <div class="developer-control-panel-header"> | Assignment statement storing or updating program state.

L0395 | <div> | Markup line defining structure in an HTML-like template file.

L0396 | <div class="fw-semibold">Developer Controls</div> | Assignment statement storing or updating program state.

L0397 | <div class="small text-muted">Override app behavior and restore user state.</div> | Assignment statement storing or updating program state.

L0398 | </div> | Markup line defining structure in an HTML-like template file.

L0399 | | Assignment statement storing or updating program state.

L0400 | {{ user_settings.preference_keys|length }} pref{% if (user_settings.preference_keys|length) != 1 %}s{% endif %} | Block delimiter controlling scope/structure in this language.

L0401 | | Markup line defining structure in an HTML-like template file.

L0402 | </div> | Markup line defining structure in an HTML-like template file.

L0403 | | Blank line used for readability and logical separation.

L0404 | <form method="post" action="{{ url_for('update_user_controls', user_id=user.id) }}" class="mb-2"> | Assignment statement storing or updating program state.

L0405 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0406 | <input type="hidden" name="developer_control_action" value="update_settings" /> | Assignment statement storing or updating program state.

L0407 | <div class="row g-2 align-items-end"> | Assignment statement storing or updating program state.

L0408 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.

L0409 | <label class="form-label mb-1">Theme</label> | Assignment statement storing or updating program state.

L0410 | <select name="theme" class="form-select form-select-sm" aria-label="Theme for {{ user.email }}"> | Assignment statement storing or updating program state.

L0411 | {% for theme in theme_options %} | Block delimiter controlling scope/structure in this language.

L0412 | <option value="{{ theme }}" {% if (user_settings.theme or 'light') == theme %}selected{% endif %}>{{ theme|title }}</option>

L0413 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0414 | </select> | Markup line defining structure in an HTML-like template file.

L0415 | </div> | Markup line defining structure in an HTML-like template file.

L0416 | <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.

L0417 | <label class="form-label mb-1">Language</label> | Assignment statement storing or updating program state.

L0418 | <select name="language" class="form-select form-select-sm" aria-label="Language for {{ user.email }}"> | Assignment statement storing or updating program state.

L0419 | {% for language in language_options %} | Block delimiter controlling scope/structure in this language.

L0420 | <option value="{{ language }}" {% if (user_settings.language or 'en') == language %}selected{% endif %}>{{ language|title }}</option>

L0421 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0422 | </select> | Markup line defining structure in an HTML-like template file.

L0423 | </div> | Markup line defining structure in an HTML-like template file.

L0424 | <div class="col-12 col-md-4 d-grid"> | Assignment statement storing or updating program state.

L0425 | <button type="submit" class="btn btn-sm btn-outline-primary">Save User Settings</button> | Assignment statement storing or updating program state.

L0426 | </div> | Markup line defining structure in an HTML-like template file.

L0427 | </div> | Markup line defining structure in an HTML-like template file.

L0428 | </form> | Markup line defining structure in an HTML-like template file.

L0429 | | Blank line used for readability and logical separation.

L0430 | <div class="developer-control-chips mb-2"> | Assignment statement storing or updating program state.

L0431 | <i class="bi bi-palette"></i> {{ (user_settings.theme or 'light')|title }} | Assignment statement storing or updating program state.

L0432 | <i class="bi bi-translate"></i> {{ (user_settings.language or 'en')|upper }} | Assignment statement storing or updating program state.

L0433 | <i class="bi bi-bell-slash"></i> {{ user_settings.hidden_message_count or 0 }} hidden | Assignment statement storing or updating program state.

L0434 | </div> | Markup line defining structure in an HTML-like template file.

L0435 | | Blank line used for readability and logical separation.

L0436 | <div class="d-flex flex-wrap gap-2"> | Assignment statement storing or updating program state.

L0437 | <form method="post" action="{{ url_for('update_user_controls', user_id=user.id) }}" data-confirm-message="Reset app settings">

L0438 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0439 | <input type="hidden" name="developer_control_action" value="reset_app_settings" /> | Assignment statement storing or updating program state.

L0440 | <button type="submit" class="btn btn-sm btn-outline-secondary">Reset App Settings</button> | Assignment statement storing or updating program state.

L0441 | </form> | Markup line defining structure in an HTML-like template file.

L0442 | | Blank line used for readability and logical separation.

L0443 | <form method="post" action="{{ url_for('update_user_controls', user_id=user.id) }}" data-confirm-message="Restore hidden messages" /> | Assignment statement storing or updating program state.

L0444 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0445 | <input type="hidden" name="developer_control_action" value="clear_hidden_messages" /> | Assignment statement storing or updating program state.

L0446 | <button type="submit" class="btn btn-sm btn-outline-info">Restore Hidden Messages</button> | Assignment statement storing or updating program state.

L0447 | </form> | Markup line defining structure in an HTML-like template file.

L0448 | </div> | Markup line defining structure in an HTML-like template file.

L0449 | </div> | Markup line defining structure in an HTML-like template file.

L0450 | | Blank line used for readability and logical separation.

L0451 | <form method="post" action="{{ url_for('set_user_role', user_id=user.id) }}" class="mb-3"> | Assignment statement storing or updating program state.

L0452 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0453 | <label class="form-label mb-1">Role</label> | Assignment statement storing or updating program state.

L0454 | <div class="d-flex gap-2"> | Assignment statement storing or updating program state.

L0455 | <select name="role" class="form-select form-select-sm" aria-label="Role selector for {{ user.email }}"> | Assignment statement storing or updating program state.

L0456 | {% for role in role_options %} | Block delimiter controlling scope/structure in this language.

L0457 | <option value="{{ role }}" {% if user.role == role %}selected{% endif %}>{{ role|replace('_', ' ')|title }}</option> | Assignment statement storing or updating program state.

L0458 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0459 | </select> | Markup line defining structure in an HTML-like template file.

L0460 | <button type="submit" class="btn btn-sm btn-outline-primary">Save Role</button> | Assignment statement storing or updating program state.

L0461 | </div> | Markup line defining structure in an HTML-like template file.

L0462 | </form> | Markup line defining structure in an HTML-like template file.

L0463 | | Blank line used for readability and logical separation.

L0464 | <form method="post" action="{{ url_for('reset_user_password', user_id=user.id) }}" class="mb-3"> | Assignment statement storing or updating program state.

L0465 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0466 | <label class="form-label mb-1" for="pwd_{{ user.id }}">Change Password</label> | Assignment statement storing or updating program state.

L0467 | <div class="d-flex gap-2"> | Assignment statement storing or updating program state.

L0468 | <input id="pwd_{{ user.id }}" type="text" name="new_password" class="form-control form-control-sm" placeholder="Enter new password" /> | Assignment statement storing or updating program state.

L0469 | <button type="submit" class="btn btn-sm btn-warning">Save Password</button> | Assignment statement storing or updating program state.

L0470 | <button type="submit" class="btn btn-sm btn-outline-warning" formaction="{{ url_for('reset_user_password', user_id=user.id) }}" /> | Assignment statement storing or updating program state.

L0471 | </div> | Markup line defining structure in an HTML-like template file.

L0472 | <div class="form-text">Leave blank and click Generate Temp to issue a one-time password automatically.</div> | Assignment statement storing or updating program state.

L0473 | </form> | Markup line defining structure in an HTML-like template file.

L0474 | | Blank line used for readability and logical separation.

L0475 | <div class="d-flex flex-wrap gap-2"> | Assignment statement storing or updating program state.

L0476 | <form method="post" action="{{ url_for('toggle_user_block', user_id=user.id) }}"> | Assignment statement storing or updating program state.

L0477 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0478 | <button type="submit" class="btn btn-sm {% if user.is_blocked %}btn-success{% else %}btn-outline-danger{% endif %}"> | Assignment statement storing or updating program state.

L0479 | {% if user.is_blocked %}Unblock{% else %}Block{% endif %} | Block delimiter controlling scope/structure in this language.

L0480 | </button> | Markup line defining structure in an HTML-like template file.

L0481 | </form> | Markup line defining structure in an HTML-like template file.

L0482 | | Blank line used for readability and logical separation.

L0483 | <form method="post" action="{{ url_for('delete_user', user_id=user.id) }}" data-confirm-message="Delete {{ user.display_name }}" /> | Assignment statement storing or updating program state.

L0484 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.

L0485 | <button type="submit" class="btn btn-sm btn-outline-dark">Delete</button> | Assignment statement storing or updating program state.

L0486 | </form> | Markup line defining structure in an HTML-like template file.

L0487 | | Blank line used for readability and logical separation.

L0488 | View Activity | Assignment statement storing or updating program state.

L0489 | </div> | Markup line defining structure in an HTML-like template file.

L0490 | {% else %} | Block delimiter controlling scope/structure in this language.

L0491 | <div class="alert alert-light border mb-0">Current user profile can be edited here, but role changes, blocking, deleting, and deleting roles are not allowed.</div> | Assignment statement storing or updating program state.

L0492 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0493 | </div> | Markup line defining structure in an HTML-like template file.

L0494 | </div> | Markup line defining structure in an HTML-like template file.
L0495 | {% endfor %} | Block delimiter controlling scope/structure in this language.
L0496 | </div> | Markup line defining structure in an HTML-like template file.
L0497 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 105: templates/emergency.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <h1>Emergency Contacts</h1> | Markup line defining structure in an HTML-like template file.
L0004 | <div class="row g-3 emergency-grid mt-1"> | Assignment statement storing or updating program state.
L0005 |     <div class="col-12 col-md-6 col-xl-4"> | Assignment statement storing or updating program state.
L0006 |         <div class="card emergency-contact-card h-100"> | Assignment statement storing or updating program state.
L0007 |             <div class="card-body"> | Assignment statement storing or updating program state.
L0008 |                 <h5 class="contact-name">{{ current_user.support_desk or 'Support Desk Team' }}</h5> | Assignment statement storing or updating program state.
L0009 |                 <p class="contact-role">Support Desk</p> | Assignment statement storing or updating program state.
L0010 |                 <p class="contact-phone"> | Assignment statement storing or updating program state.
L0011 |                     <i class="bi bi-telephone-fill"></i> | Assignment statement storing or updating program state.
L0012 |                     <a href="tel:{{ current_user.site_operations_phone or '0312132700' }}">{{ current_user.site_operations_phone or '0312 132700' }}</a> | Assignment statement storing or updating program state.
L0013 |                 </p> | Markup line defining structure in an HTML-like template file.
L0014 |                 <div class="contact-escalation"> | Assignment statement storing or updating program state.
L0015 |                     <h6>Emergency Escalation</h6> | Markup line defining structure in an HTML-like template file.
L0016 |                     <p class="mb-0">Escalate unresolved incidents after 15 minutes to Site Operations.</p> | Assignment statement storing or updating program state.
L0017 |                 </div> | Markup line defining structure in an HTML-like template file.
L0018 |             </div> | Markup line defining structure in an HTML-like template file.
L0019 |         </div> | Markup line defining structure in an HTML-like template file.
L0020 |     </div> | Markup line defining structure in an HTML-like template file.
L0021 | | Blank line used for readability and logical separation.
L0022 | <div class="col-12 col-md-6 col-xl-4"> | Assignment statement storing or updating program state.
L0023 |     <div class="card emergency-contact-card h-100"> | Assignment statement storing or updating program state.
L0024 |         <div class="card-body"> | Assignment statement storing or updating program state.
L0025 |             <h5 class="contact-name">Site Operations Lead</h5> | Assignment statement storing or updating program state.
L0026 |             <p class="contact-role">Site Operations</p> | Assignment statement storing or updating program state.
L0027 |             <p class="contact-phone"> | Assignment statement storing or updating program state.
L0028 |                 <i class="bi bi-telephone-fill"></i> | Assignment statement storing or updating program state.
L0029 |                 <a href="tel:{{ current_user.site_operations_phone or '0312132700' }}">{{ current_user.site_operations_phone or '0312 132700' }}</a> | Assignment statement storing or updating program state.
L0030 |             </p> | Markup line defining structure in an HTML-like template file.
L0031 |             <div class="contact-escalation"> | Assignment statement storing or updating program state.
L0032 |                 <h6>Emergency Escalation</h6> | Markup line defining structure in an HTML-like template file.
L0033 |                 <p class="mb-0">Escalate service outages and field safety incidents immediately.</p> | Assignment statement storing or updating program state.
L0034 |             </div> | Markup line defining structure in an HTML-like template file.
L0035 |         </div> | Markup line defining structure in an HTML-like template file.
L0036 |     </div> | Markup line defining structure in an HTML-like template file.
L0037 | </div> | Markup line defining structure in an HTML-like template file.
L0038 | | Blank line used for readability and logical separation.
L0039 | <div class="col-12 col-md-6 col-xl-4"> | Assignment statement storing or updating program state.
L0040 |     <div class="card emergency-contact-card h-100"> | Assignment statement storing or updating program state.
L0041 |         <div class="card-body"> | Assignment statement storing or updating program state.
L0042 |             <h5 class="contact-name">Emergency Response</h5> | Assignment statement storing or updating program state.
L0043 |             <p class="contact-role">Critical Escalation</p> | Assignment statement storing or updating program state.
L0044 |             <p class="contact-phone"> | Assignment statement storing or updating program state.
L0045 |                 <i class="bi bi-telephone-fill"></i> | Assignment statement storing or updating program state.
L0046 |                 <a href="tel:{{ current_user.emergency_phone or '+256700672045' }}">{{ current_user.emergency_phone or '+256 700 672 045' }}</a> | Assignment statement storing or updating program state.
L0047 |             </p> | Markup line defining structure in an HTML-like template file.
L0048 |             <div class="contact-escalation"> | Assignment statement storing or updating program state.
L0049 |                 <h6>Emergency Escalation</h6> | Markup line defining structure in an HTML-like template file.
L0050 |                 <p class="mb-0">Use for life-safety events, major outages, and security escalation.</p> | Assignment statement storing or updating program state.
L0051 |             </div> | Markup line defining structure in an HTML-like template file.
L0052 |         </div> | Markup line defining structure in an HTML-like template file.
L0053 |     </div> | Markup line defining structure in an HTML-like template file.
```

L0054 | </div> | Markup line defining structure in an HTML-like template file.
L0055 | </div> | Markup line defining structure in an HTML-like template file.
L0056 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 106: templates/field_rca.html

```
L0001 | {% extends "layout.html" %} | Block delimiter controlling scope/structure in this language.
L0002 | | Blank line used for readability and logical separation.
L0003 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0004 | <div class="card detail-card mb-4"> | Assignment statement storing or updating program state.
L0005 |     <form method="post" enctype="multipart/form-data" class="row g-3" id="technicianPmForm"> | Assignment statement storing or updating program state.
L0006 |         <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.
L0007 |         <div class="col-12"> | Assignment statement storing or updating program state.
L0008 |             <div class="table-responsive"> | Assignment statement storing or updating program state.
L0009 |                 <table class="table pm-form-table align-middle mb-0"> | Assignment statement storing or updating program state.
L0010 |                     <tbody> | Markup line defining structure in an HTML-like template file.
L0011 |                         <tr> | Markup line defining structure in an HTML-like template file.
L0012 |                             <th class="pm-label-col">CLIENT</th> | Assignment statement storing or updating program state.
L0013 |                             <td class="pm-value-col">AIRTEL UGANDA</td> | Assignment statement storing or updating program state.
L0014 |                         </tr> | Markup line defining structure in an HTML-like template file.
L0015 |                         <tr> | Markup line defining structure in an HTML-like template file.
L0016 |                             <th>VENDOR</th> | Markup line defining structure in an HTML-like template file.
L0017 |                             <td>SOLITON TELMEC (U) LTD</td> | Markup line defining structure in an HTML-like template file.
L0018 |                         </tr> | Markup line defining structure in an HTML-like template file.
L0019 |                         <tr> | Markup line defining structure in an HTML-like template file.
L0020 |                             <th>Activity Name</th> | Markup line defining structure in an HTML-like template file.
L0021 |                             <td>AIRTEL UG Planned Preventive Maintenance Form</td> | Markup line defining structure in an HTML-like template file.
L0022 |                         </tr> | Markup line defining structure in an HTML-like template file.
L0023 |                         <tr> | Markup line defining structure in an HTML-like template file.
L0024 |                             <th>Submitted By</th> | Markup line defining structure in an HTML-like template file.
L0025 |                             <td><input name="submitted_by" class="form-control" value="{{ current_user.full_name }}" required /></td> | Assignment statement storing or updating program state.
L0026 |                         </tr> | Markup line defining structure in an HTML-like template file.
L0027 |                         <tr> | Markup line defining structure in an HTML-like template file.
L0028 |                             <th>Activity Start</th> | Markup line defining structure in an HTML-like template file.
L0029 |                             <td><input type="date" name="activity_start" class="form-control" required /></td> | Assignment statement storing or updating program state.
L0030 |                         </tr> | Markup line defining structure in an HTML-like template file.
L0031 |                         <tr> | Markup line defining structure in an HTML-like template file.
L0032 |                             <th>Activity End</th> | Markup line defining structure in an HTML-like template file.
L0033 |                             <td><input type="date" name="activity_end" class="form-control" required /></td> | Assignment statement storing or updating program state.
L0034 |                         </tr> | Markup line defining structure in an HTML-like template file.
L0035 |                         <tr> | Markup line defining structure in an HTML-like template file.
L0036 |                             <th>Validation Comments (By Technician)</th> | Markup line defining structure in an HTML-like template file.
L0037 |                             <td><textarea name="validation_comments" class="form-control" rows="2"></textarea></td> | Assignment statement storing or updating program state.
L0038 |                         </tr> | Markup line defining structure in an HTML-like template file.
L0039 |                     </tbody> | Markup line defining structure in an HTML-like template file.
L0040 |                 </table> | Markup line defining structure in an HTML-like template file.
L0041 |             </div> | Markup line defining structure in an HTML-like template file.
L0042 |         </div> | Markup line defining structure in an HTML-like template file.
L0043 | | Blank line used for readability and logical separation.
L0044 | {% for section in pm_sections %} | Block delimiter controlling scope/structure in this language.
L0045 |     <div class="col-12"> | Assignment statement storing or updating program state.
L0046 |         <div class="table-responsive"> | Assignment statement storing or updating program state.
L0047 |             <table class="table pm-form-table align-middle mb-0"> | Assignment statement storing or updating program state.
L0048 |                 <thead> | Markup line defining structure in an HTML-like template file.
L0049 |                     <tr> | Markup line defining structure in an HTML-like template file.
L0050 |                         <th class="pm-label-col">{{ section.title }}</th> | Assignment statement storing or updating program state.
L0051 |                         <th class="pm-value-col">CURRENT VALUE</th> | Assignment statement storing or updating program state.
L0052 |                     </tr> | Markup line defining structure in an HTML-like template file.
L0053 |                 </thead> | Markup line defining structure in an HTML-like template file.
```

L0054 | <tbody> | Markup line defining structure in an HTML-like template file.

L0055 | {% for label in section.fields %} | Block delimiter controlling scope/structure in this language.

L0056 | {% set field_name = 'field_' ~ slugify_label(label) %} | Assignment statement storing or updating program state.

L0057 | <tr> | Markup line defining structure in an HTML-like template file.

L0058 | <td>{{ label }}</td> | Markup line defining structure in an HTML-like template file.

L0059 | <td> | Markup line defining structure in an HTML-like template file.

L0060 | {% if label == 'Activity' %} | Block delimiter controlling scope/structure in this language.

L0061 | <select name="activity_type" class="form-select" required> | Assignment statement storing or updating program state.

L0062 | <option value="pm">Preventative Maintenance</option> | Assignment statement storing or updating program state.

L0063 | <option value="rca">RCA</option> | Assignment statement storing or updating program state.

L0064 | </select> | Markup line defining structure in an HTML-like template file.

L0065 | {% elif is_yes_no_label(label) %} | Block delimiter controlling scope/structure in this language.

L0066 | <select name="{{ field_name }}" class="form-select"> | Assignment statement storing or updating program state.

L0067 | <option value="">Select</option> | Assignment statement storing or updating program state.

L0068 | <option value="Yes">Yes</option> | Assignment statement storing or updating program state.

L0069 | <option value="No">No</option> | Assignment statement storing or updating program state.

L0070 | <option value="N/A">N/A</option> | Assignment statement storing or updating program state.

L0071 | </select> | Markup line defining structure in an HTML-like template file.

L0072 | {% elif 'date' in label|lower %} | Block delimiter controlling scope/structure in this language.

L0073 | <input type="date" name="{{ field_name }}" class="form-control" /> | Assignment statement storing or updating program state.

L0074 | {% elif 'time' in label|lower %} | Block delimiter controlling scope/structure in this language.

L0075 | <input type="time" name="{{ field_name }}" class="form-control" /> | Assignment statement storing or updating program state.

L0076 | {% elif 'comment' in label|lower or 'share' in label|lower %} | Block delimiter controlling scope/structure in this language.

L0077 | <textarea name="{{ field_name }}" class="form-control" rows="2"></textarea> | Assignment statement storing or updating program state.

L0078 | {% else %} | Block delimiter controlling scope/structure in this language.

L0079 | <input name="{{ field_name }}" class="form-control" {% if label in ['Site Number', 'Site Name'] %}required{%

L0080 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0081 | </td> | Markup line defining structure in an HTML-like template file.

L0082 | </tr> | Markup line defining structure in an HTML-like template file.

L0083 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0084 | </tbody> | Markup line defining structure in an HTML-like template file.

L0085 | </table> | Markup line defining structure in an HTML-like template file.

L0086 | </div> | Markup line defining structure in an HTML-like template file.

L0087 | </div> | Markup line defining structure in an HTML-like template file.

L0088 | {% endfor %} | Block delimiter controlling scope/structure in this language.

L0089 | | Blank line used for readability and logical separation.

L0090 | <div class="col-12"> | Assignment statement storing or updating program state.

L0091 | <h5 class="pm-photo-section-title mb-3">PHOTO SPECIFICATIONS</h5> | Assignment statement storing or updating program state.

L0092 | <div class="row g-3"> | Assignment statement storing or updating program state.

L0093 | {% for photo in photo_fields %} | Block delimiter controlling scope/structure in this language.

L0094 | {% set file_name = 'photo_' ~ photo.key %} | Assignment statement storing or updating program state.

L0095 | <div class="col-md-6"> | Assignment statement storing or updating program state.

L0096 | <div class="pm-photo-card"> | Assignment statement storing or updating program state.

L0097 | <strong class="pm-photo-label">{{ photo.label }} | Assignment statement storing or updating program state.

L0098 | <input type="file" id="{{ file_name }}" name="{{ file_name }}" class="photo-upload-input" accept="image/*" data-photo=

L0099 | <label for="{{ file_name }}" class="pm-photo-upload-area" title="Tap to upload image"> | Assignment statement storing or updating program state.

L0100 | | Assignment statement storing or updating program state.

L0101 | <i class="bi bi-cloud-upload pm-photo-icon"></i> | Assignment statement storing or updating program state.

L0102 | Tap to upload | Assignment statement storing or updating program state.

L0103 | | Markup line defining structure in an HTML-like template file.

L0104 | </label> | Markup line defining structure in an HTML-like template file.

L0105 | <div class="pm-photo-controls mt-2 d-none"> | Assignment statement storing or updating program state.

L0106 | <button type="button" class="btn btn-sm btn-outline-danger pm-photo-delete-btn" title="Delete photo"> | Assignment

L0107 | <i class="bi bi-trash"></i> Delete | Assignment statement storing or updating program state.

L0108 | </button> | Markup line defining structure in an HTML-like template file.


```

L0109 |         </div> | Markup line defining structure in an HTML-like template file.
L0110 |         <div class="pm-photo-system-note text-muted small mt-2"> | Assignment statement storing or updating program state.
L0111 |             System description will appear here after image selection. | Operational statement participating in the file's runtime behavior.
L0112 |         </div> | Markup line defining structure in an HTML-like template file.
L0113 |     </div> | Markup line defining structure in an HTML-like template file.
L0114 | </div> | Markup line defining structure in an HTML-like template file.
L0115 |     {% endfor %} | Block delimiter controlling scope/structure in this language.
L0116 | </div> | Markup line defining structure in an HTML-like template file.
L0117 | </div> | Markup line defining structure in an HTML-like template file.
L0118 | | Blank line used for readability and logical separation.
L0119 | <div class="col-12"> | Assignment statement storing or updating program state.
L0120 |     <h2 class="mb-3">Signatures</h2> | Assignment statement storing or updating program state.
L0121 |     <div class="signature-card"> | Assignment statement storing or updating program state.
L0122 |         <p class="mb-2"><strong>Field Technician Signature</strong></p> | Assignment statement storing or updating program state.
L0123 |         <p class="text-muted small mb-2">Draw your signature below</p> | Assignment statement storing or updating program state.
L0124 |         <canvas id="signaturePad" class="signature-pad"></canvas> | Assignment statement storing or updating program state.
L0125 |         <input type="hidden" name="signature_data" id="signatureData" /> | Assignment statement storing or updating program state.
L0126 |         <div class="d-flex gap-2 mt-3 flex-wrap"> | Assignment statement storing or updating program state.
L0127 |             <button type="button" class="btn btn-outline-secondary btn-sm" id="clearSignature"> | Assignment statement storing or updating program state.
L0128 |                 <i class="bi bi-arrow-counterclockwise"></i> Clear Signature | Assignment statement storing or updating program state.
L0129 |             </button> | Markup line defining structure in an HTML-like template file.
L0130 |             <button type="button" class="btn btn-warning btn-sm" id="clearFormBtn"> | Assignment statement storing or updating program state.
L0131 |                 <i class="bi bi-arrow-clockwise"></i> Clear Entire Form | Assignment statement storing or updating program state.
L0132 |             </button> | Markup line defining structure in an HTML-like template file.
L0133 |         </div> | Markup line defining structure in an HTML-like template file.
L0134 |     </div> | Markup line defining structure in an HTML-like template file.
L0135 | </div> | Markup line defining structure in an HTML-like template file.
L0136 | | Blank line used for readability and logical separation.
L0137 | <div class="col-12 text-center mt-4 pb-3"> | Assignment statement storing or updating program state.
L0138 |     <button type="submit" class="btn btn-lg btn-primary" id="uploadBtn" title="Upload form to review team"> | Assignment statement storing or updating program state.
L0139 |         <i class="bi bi-cloud-upload"></i> Upload to Review Team | Assignment statement storing or updating program state.
L0140 |     </button> | Markup line defining structure in an HTML-like template file.
L0141 | </div> | Markup line defining structure in an HTML-like template file.
L0142 | </form> | Markup line defining structure in an HTML-like template file.
L0143 | </div> | Markup line defining structure in an HTML-like template file.
L0144 | | Blank line used for readability and logical separation.
L0145 | <script> | Markup line defining structure in an HTML-like template file.
L0146 |     document.addEventListener('DOMContentLoaded', function () { | Block delimiter controlling scope/structure in this language.
L0147 |         const canvas = document.getElementById('signaturePad'); | Assignment statement storing or updating program state.
L0148 |         const clearSignatureBtn = document.getElementById('clearSignature'); | Assignment statement storing or updating program state.
L0149 |         const clearFormBtn = document.getElementById('clearFormBtn'); | Assignment statement storing or updating program state.
L0150 |         const uploadBtn = document.getElementById('uploadBtn'); | Assignment statement storing or updating program state.
L0151 |         const hiddenField = document.getElementById('signatureData'); | Assignment statement storing or updating program state.
L0152 |         const form = document.getElementById('technicianPmForm'); | Assignment statement storing or updating program state.
L0153 |         const ctx = canvas.getContext('2d', { willReadFrequently: true }); | Assignment statement storing or updating program state.
L0154 |         let drawing = false; | Assignment statement storing or updating program state.
L0155 |         let signatureDrawn = false; | Assignment statement storing or updating program state.
L0156 | | Blank line used for readability and logical separation.
L0157 |         // ===== SIGNATURE PAD ===== | Operational statement participating in the file's runtime behavior.
L0158 |         function resizeCanvas() { | Block delimiter controlling scope/structure in this language.
L0159 |             const ratio = window.devicePixelRatio > 1 ? 1 : window.devicePixelRatio; | Assignment statement storing or updating program state.
L0160 |             const width = canvas.clientWidth; | Assignment statement storing or updating program state.
L0161 |             const height = canvas.clientHeight; | Assignment statement storing or updating program state.
L0162 |             canvas.width = width * ratio; | Assignment statement storing or updating program state.
L0163 |             canvas.height = height * ratio; | Assignment statement storing or updating program state.

```

```

L0164 |         ctx.scale(ratio, ratio); | Operational statement participating in the file's runtime behavior.
L0165 |         ctx.lineWidth = 2.5; | Assignment statement storing or updating program state.
L0166 |         ctx.lineCap = 'round'; | Assignment statement storing or updating program state.
L0167 |         ctx.lineJoin = 'round'; | Assignment statement storing or updating program state.
L0168 |         ctx.strokeStyle = '#1a2540'; | Assignment statement storing or updating program state.
L0169 |     } | Block delimiter controlling scope/structure in this language.
L0170 | | Blank line used for readability and logical separation.
L0171 |     function getPos(event) { | Block delimiter controlling scope/structure in this language.
L0172 |         const rect = canvas.getBoundingClientRect(); | Assignment statement storing or updating program state.
L0173 |         const point = event.touches ? event.touches[0] : event; | Assignment statement storing or updating program state.
L0174 |         return { | Returns a value (or control) back to the caller.
L0175 |             x: point.clientX - rect.left, | Operational statement participating in the file's runtime behavior.
L0176 |             y: point.clientY - rect.top, | Operational statement participating in the file's runtime behavior.
L0177 |         }; | Operational statement participating in the file's runtime behavior.
L0178 |     } | Block delimiter controlling scope/structure in this language.
L0179 | | Blank line used for readability and logical separation.
L0180 |     function startDraw(event) { | Block delimiter controlling scope/structure in this language.
L0181 |         drawing = true; | Assignment statement storing or updating program state.
L0182 |         signatureDrawn = true; | Assignment statement storing or updating program state.
L0183 |         const pos = getPos(event); | Assignment statement storing or updating program state.
L0184 |         ctx.beginPath(); | Operational statement participating in the file's runtime behavior.
L0185 |         ctx.moveTo(pos.x, pos.y); | Operational statement participating in the file's runtime behavior.
L0186 |         event.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0187 |     } | Block delimiter controlling scope/structure in this language.
L0188 | | Blank line used for readability and logical separation.
L0189 |     function draw(event) { | Block delimiter controlling scope/structure in this language.
L0190 |         if (!drawing) return; | Conditional branch that runs only when its condition is true.
L0191 |         const pos = getPos(event); | Assignment statement storing or updating program state.
L0192 |         ctx.lineTo(pos.x, pos.y); | Operational statement participating in the file's runtime behavior.
L0193 |         ctx.stroke(); | Operational statement participating in the file's runtime behavior.
L0194 |         event.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0195 |     } | Block delimiter controlling scope/structure in this language.
L0196 | | Blank line used for readability and logical separation.
L0197 |     function endDraw(event) { | Block delimiter controlling scope/structure in this language.
L0198 |         if (!drawing) return; | Conditional branch that runs only when its condition is true.
L0199 |         drawing = false; | Assignment statement storing or updating program state.
L0200 |         hiddenField.value = canvas.toDataURL('image/png'); | Assignment statement storing or updating program state.
L0201 |         event.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0202 |     } | Block delimiter controlling scope/structure in this language.
L0203 | | Blank line used for readability and logical separation.
L0204 |     resizeCanvas(); | Operational statement participating in the file's runtime behavior.
L0205 |     window.addEventListener('resize', resizeCanvas); | Operational statement participating in the file's runtime behavior.
L0206 | | Blank line used for readability and logical separation.
L0207 |     canvas.addEventListener('mousedown', startDraw); | Operational statement participating in the file's runtime behavior.
L0208 |     canvas.addEventListener('mousemove', draw); | Operational statement participating in the file's runtime behavior.
L0209 |     canvas.addEventListener('mouseup', endDraw); | Operational statement participating in the file's runtime behavior.
L0210 |     canvas.addEventListener('mouseleave', endDraw); | Operational statement participating in the file's runtime behavior.
L0211 | | Blank line used for readability and logical separation.
L0212 |     canvas.addEventListener('touchstart', startDraw, { passive: false }); | Operational statement participating in the file's runtime behavior.
L0213 |     canvas.addEventListener('touchmove', draw, { passive: false }); | Operational statement participating in the file's runtime behavior.
L0214 |     canvas.addEventListener('touchend', endDraw, { passive: false }); | Operational statement participating in the file's runtime behavior.
L0215 | | Blank line used for readability and logical separation.
L0216 |     clearSignatureBtn.addEventListener('click', function (e) { | Block delimiter controlling scope/structure in this language.
L0217 |         e.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0218 |         ctx.clearRect(0, 0, canvas.width, canvas.height); | Operational statement participating in the file's runtime behavior.

```

```

L0219 |         hiddenField.value = ''; | Assignment statement storing or updating program state.
L0220 |         signatureDrawn = false; | Assignment statement storing or updating program state.
L0221 |     }); | Operational statement participating in the file's runtime behavior.
L0222 | | Blank line used for readability and logical separation.
L0223 |     // ===== PHOTO UPLOAD & DELETE ===== | Operational statement participating in the file's runtime behavior.
L0224 |     function buildSystemPhotoDescription(photoLabel, file) { | Block delimiter controlling scope/structure in this language.
L0225 |         const rawName = ((file && file.name) \\| ' ').trim(); | Assignment statement storing or updating program state.
L0226 |         const lowered = rawName.toLowerCase(); | Assignment statement storing or updating program state.
L0227 |         let sourceHint = 'Uploaded camera image'; | Assignment statement storing or updating program state.
L0228 | | Blank line used for readability and logical separation.
L0229 |         if (lowered.indexOf('screenshot') !== -1) { | Conditional branch that runs only when its condition is true.
L0230 |             sourceHint = 'Mobile screenshot'; | Assignment statement storing or updating program state.
L0231 |         } else if (lowered.indexOf('whatsapp') !== -1) { | Block delimiter controlling scope/structure in this language.
L0232 |             sourceHint = 'WhatsApp image'; | Assignment statement storing or updating program state.
L0233 |         } | Block delimiter controlling scope/structure in this language.
L0234 | | Blank line used for readability and logical separation.
L0235 |         let contextHint = 'Evidence for ' + photoLabel + '.'; | Assignment statement storing or updating program state.
L0236 |         if ([ 'chrome', 'pdf', 'download', 'zoom', 'viewer' ].some(function (token) { return lowered.indexOf(token) !== -1; })) { | Con
L0237 |             contextHint = 'Evidence for ' + photoLabel + ' '; filename suggests a screen capture of a document or app view.'; | Assignmen
L0238 |         } | Block delimiter controlling scope/structure in this language.
L0239 | | Blank line used for readability and logical separation.
L0240 |         const sizeKb = file && file.size ? Math.max(1, Math.round(file.size / 1024)) : 0; | Assignment statement storing or updating
L0241 |         return sourceHint + ' ' + contextHint + (sizeKb ? ' File size: ' + sizeKb + ' KB.' : ''); | Returns a value (or control) bac
L0242 |     } | Block delimiter controlling scope/structure in this language.
L0243 | | Blank line used for readability and logical separation.
L0244 |     document.querySelectorAll('.photo-upload-input').forEach(function (input) { | Block delimiter controlling scope/structure in th
L0245 |         const photoCard = input.closest('.pm-photo-card'); | Assignment statement storing or updating program state.
L0246 |         const label = photoCard.querySelector('.pm-photo-upload-area'); | Assignment statement storing or updating program state.
L0247 |         const controls = photoCard.querySelector('.pm-photo-controls'); | Assignment statement storing or updating program state.
L0248 |         const deleteBtn = controls.querySelector('.pm-photo-delete-btn'); | Assignment statement storing or updating program state.
L0249 |         const note = photoCard.querySelector('.pm-photo-system-note'); | Assignment statement storing or updating program state.
L0250 |         const photoLabel = input.getAttribute('data-photo-label') \\| 'Uploaded photo'; | Assignment statement storing or updating p
L0251 | | Blank line used for readability and logical separation.
L0252 |         input.addEventListener('change', function () { | Block delimiter controlling scope/structure in this language.
L0253 |             if (input.files && input.files.length > 0) { | Conditional branch that runs only when its condition is true.
L0254 |                 const file = input.files[0]; | Assignment statement storing or updating program state.
L0255 |                 // Read as high-res without compression | Operational statement participating in the file's runtime behavior.
L0256 |                 const reader = new FileReader(); | Assignment statement storing or updating program state.
L0257 |                 reader.onload = function (e) { | Assignment statement storing or updating program state.
L0258 |                     label.style.backgroundImage = 'url(' + e.target.result + ')'; | Assignment statement storing or updating program state.
L0259 |                     label.style.backgroundSize = 'cover'; | Assignment statement storing or updating program state.
L0260 |                     label.style.backgroundPosition = 'center'; | Assignment statement storing or updating program state.
L0261 |                     label.classList.add('uploaded'); | Operational statement participating in the file's runtime behavior.
L0262 |                     const hint = label.querySelector('.pm-photo-placeholder'); | Assignment statement storing or updating program state.
L0263 |                     if (hint) hint.style.opacity = '0'; | Conditional branch that runs only when its condition is true.
L0264 |                     controls.classList.remove('d-none'); | Operational statement participating in the file's runtime behavior.
L0265 |                     if (note) { | Conditional branch that runs only when its condition is true.
L0266 |                         note.textContent = buildSystemPhotoDescription(photoLabel, file); | Assignment statement storing or updating program
L0267 |                     } | Block delimiter controlling scope/structure in this language.
L0268 |                 }; | Operational statement participating in the file's runtime behavior.
L0269 |                 reader.readAsDataURL(file); // Reads full-quality image | Operational statement participating in the file's runtime behav
L0270 |             } | Block delimiter controlling scope/structure in this language.
L0271 |         }); | Operational statement participating in the file's runtime behavior.
L0272 | | Blank line used for readability and logical separation.
L0273 |         deleteBtn.addEventListener('click', function (e) { | Block delimiter controlling scope/structure in this language.

```

```

L0274 |         e.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0275 |         // Clear file input | Operational statement participating in the file's runtime behavior.
L0276 |         input.value = ''; | Assignment statement storing or updating program state.
L0277 |         // Clear background image | Operational statement participating in the file's runtime behavior.
L0278 |         label.style.backgroundImage = ''; | Assignment statement storing or updating program state.
L0279 |         label.classList.remove('uploaded'); | Operational statement participating in the file's runtime behavior.
L0280 |         const hint = label.querySelector('.pm-photo-placeholder'); | Assignment statement storing or updating program state.
L0281 |         if (hint) hint.style.opacity = '1'; | Conditional branch that runs only when its condition is true.
L0282 |         // Hide delete button | Operational statement participating in the file's runtime behavior.
L0283 |         controls.classList.add('d-none'); | Operational statement participating in the file's runtime behavior.
L0284 |         if (note) { | Conditional branch that runs only when its condition is true.
L0285 |             note.textContent = 'System description will appear here after image selection.'; | Assignment statement storing or updating program state.
L0286 |         } | Block delimiter controlling scope/structure in this language.
L0287 |     }); | Operational statement participating in the file's runtime behavior.
L0288 | }); | Operational statement participating in the file's runtime behavior.
L0289 | | Blank line used for readability and logical separation.
L0290 | // ===== CLEAR ENTIRE FORM ===== | Operational statement participating in the file's runtime behavior.
L0291 | clearFormBtn.addEventListener('click', function (e) { | Block delimiter controlling scope/structure in this language.
L0292 |     e.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0293 |     var clearAction = function () { | Assignment statement storing or updating program state.
L0294 |         // Clear all text inputs, textareas, selects | Operational statement participating in the file's runtime behavior.
L0295 |         form.querySelectorAll('input:not([type="hidden"]), textarea, select').forEach(function (field) { | Assignment statement storing or updating program state.
L0296 |             if (field.name && !field.name.includes('photo_')) { | Conditional branch that runs only when its condition is true.
L0297 |                 if (field.type === 'checkbox' || field.type === 'radio') { | Conditional branch that runs only when its condition is true.
L0298 |                     field.checked = false; | Assignment statement storing or updating program state.
L0299 |                 } else { | Block delimiter controlling scope/structure in this language.
L0300 |                     field.value = ''; | Assignment statement storing or updating program state.
L0301 |                 } | Block delimiter controlling scope/structure in this language.
L0302 |             } | Block delimiter controlling scope/structure in this language.
L0303 |         }); | Operational statement participating in the file's runtime behavior.
L0304 | | Blank line used for readability and logical separation.
L0305 | // Clear all photos | Operational statement participating in the file's runtime behavior.
L0306 | document.querySelectorAll('.photo-upload-input').forEach(function (input) { | Block delimiter controlling scope/structure in this language.
L0307 |     input.value = ''; | Assignment statement storing or updating program state.
L0308 |     const photoCard = input.closest('.pm-photo-card'); | Assignment statement storing or updating program state.
L0309 |     const label = photoCard.querySelector('.pm-photo-upload-area'); | Assignment statement storing or updating program state.
L0310 |     const controls = photoCard.querySelector('.pm-photo-controls'); | Assignment statement storing or updating program state.
L0311 |     label.style.backgroundImage = ''; | Assignment statement storing or updating program state.
L0312 |     label.classList.remove('uploaded'); | Operational statement participating in the file's runtime behavior.
L0313 |     const hint = label.querySelector('.pm-photo-placeholder'); | Assignment statement storing or updating program state.
L0314 |     const note = photoCard.querySelector('.pm-photo-system-note'); | Assignment statement storing or updating program state.
L0315 |     if (hint) hint.style.opacity = '1'; | Conditional branch that runs only when its condition is true.
L0316 |     if (note) note.textContent = 'System description will appear here after image selection.'; | Conditional branch that runs only when its condition is true.
L0317 |     controls.classList.add('d-none'); | Operational statement participating in the file's runtime behavior.
L0318 | }); | Operational statement participating in the file's runtime behavior.
L0319 | | Blank line used for readability and logical separation.
L0320 | // Clear signature | Operational statement participating in the file's runtime behavior.
L0321 | ctx.clearRect(0, 0, canvas.width, canvas.height); | Operational statement participating in the file's runtime behavior.
L0322 | hiddenField.value = ''; | Assignment statement storing or updating program state.
L0323 | signatureDrawn = false; | Assignment statement storing or updating program state.
L0324 | | Blank line used for readability and logical separation.
L0325 | // Set default dates | Operational statement participating in the file's runtime behavior.
L0326 | const now = new Date(); | Assignment statement storing or updating program state.
L0327 | const formattedDate = now.toISOString().split('T')[0]; | Assignment statement storing or updating program state.
L0328 | const activityStartInput = document.querySelector('input[name="activity_start"]'); | Assignment statement storing or updating program state.

```

```

L0329 |         const activityEndInput = document.querySelector('input[name="activity_end"]'); | Assignment statement storing or updating p
L0330 |         if (activityStartInput) activityStartInput.value = formattedDate; | Conditional branch that runs only when its condition is
L0331 |         if (activityEndInput) activityEndInput.value = formattedDate; | Conditional branch that runs only when its condition is tru
L0332 |     }); | Operational statement participating in the file's runtime behavior.
L0333 | | Blank line used for readability and logical separation.
L0334 |     if (typeof window.appConfirm === 'function') { | Conditional branch that runs only when its condition is true.
L0335 |         window.appConfirm({ | Block delimiter controlling scope/structure in this language.
L0336 |             title: 'Clear Form', | Operational statement participating in the file's runtime behavior.
L0337 |             message: 'Are you sure you want to clear the entire form? This cannot be undone.', | Operational statement participating
L0338 |             confirmLabel: 'Yes, clear', | Operational statement participating in the file's runtime behavior.
L0339 |             cancelLabel: 'No' | Operational statement participating in the file's runtime behavior.
L0340 |         }).then(function (confirmed) { | Block delimiter controlling scope/structure in this language.
L0341 |             if (confirmed) { | Conditional branch that runs only when its condition is true.
L0342 |                 clearAction(); | Operational statement participating in the file's runtime behavior.
L0343 |             } | Block delimiter controlling scope/structure in this language.
L0344 |         }); | Operational statement participating in the file's runtime behavior.
L0345 |     } else { | Block delimiter controlling scope/structure in this language.
L0346 |         clearAction(); | Operational statement participating in the file's runtime behavior.
L0347 |     } | Block delimiter controlling scope/structure in this language.
L0348 | }); | Operational statement participating in the file's runtime behavior.
L0349 | | Blank line used for readability and logical separation.
L0350 | // ===== FORM SUBMISSION ===== | Operational statement participating in the file's runtime behavior.
L0351 | form.addEventListener('submit', function (event) { | Block delimiter controlling scope/structure in this language.
L0352 |     if (!hiddenField.value || !signatureDrawn) { | Conditional branch that runs only when its condition is true.
L0353 |         event.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0354 |         if (typeof window.appNotify === 'function') { | Conditional branch that runs only when its condition is true.
L0355 |             window.appNotify({ | Block delimiter controlling scope/structure in this language.
L0356 |                 title: 'Signature Required', | Operational statement participating in the file's runtime behavior.
L0357 |                 message: 'Please draw your signature in the signature pad before uploading.' | Operational statement participating in t
L0358 |             }); | Operational statement participating in the file's runtime behavior.
L0359 |         } | Block delimiter controlling scope/structure in this language.
L0360 |         return; | Returns a value (or control) back to the caller.
L0361 |     } | Block delimiter controlling scope/structure in this language.
L0362 | | Blank line used for readability and logical separation.
L0363 |     const siteNumberInput = form.querySelector('input[name="field_site_number"]'); | Assignment statement storing or updating pro
L0364 |     const siteNameInput = form.querySelector('input[name="field_site_name"]'); | Assignment statement storing or updating program
L0365 |     const runHoursInput = form.querySelector('input[name="field_current_dg_run_hours"]'); | Assignment statement storing or updat
L0366 |     const startDateInput = form.querySelector('input[name="activity_start"]'); | Assignment statement storing or updating program
L0367 |     const endDateInput = form.querySelector('input[name="activity_end"]'); | Assignment statement storing or updating program sta
L0368 |     const hasAnyPhoto = Array.from(document.querySelectorAll('.photo-upload-input')).some(function (input) { | Assignment stateme
L0369 |         return input.files && input.files.length > 0; | Returns a value (or control) back to the caller.
L0370 |     }); | Operational statement participating in the file's runtime behavior.
L0371 | | Blank line used for readability and logical separation.
L0372 |     if (hasAnyPhoto && (!siteNumberInput || !siteNumberInput.value.trim())) { | Conditional branch that runs only when its cond
L0373 |         event.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0374 |         if (typeof window.appNotify === 'function') { | Conditional branch that runs only when its condition is true.
L0375 |             window.appNotify({ | Block delimiter controlling scope/structure in this language.
L0376 |                 title: 'Site Number Required', | Operational statement participating in the file's runtime behavior.
L0377 |                 message: 'Site Number is required when photos are uploaded.' | Operational statement participating in the file's runtim
L0378 |             }); | Operational statement participating in the file's runtime behavior.
L0379 |         } | Block delimiter controlling scope/structure in this language.
L0380 |         if (siteNumberInput) siteNumberInput.focus(); | Conditional branch that runs only when its condition is true.
L0381 |         return; | Returns a value (or control) back to the caller.
L0382 |     } | Block delimiter controlling scope/structure in this language.
L0383 | | Blank line used for readability and logical separation.

```

```

L0384 |         if (!siteNameInput || !siteNameInput.value.trim()) { | Conditional branch that runs only when its condition is true.
L0385 |             event.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0386 |             if (typeof window.appNotify === 'function') { | Conditional branch that runs only when its condition is true.
L0387 |                 window.appNotify({ | Block delimiter controlling scope/structure in this language.
L0388 |                     title: 'Site Name Required', | Operational statement participating in the file's runtime behavior.
L0389 |                     message: 'Site Name is required before submission.' | Operational statement participating in the file's runtime behavior.
L0390 |                 }); | Operational statement participating in the file's runtime behavior.
L0391 |             } | Block delimiter controlling scope/structure in this language.
L0392 |             if (siteNameInput) siteNameInput.focus(); | Conditional branch that runs only when its condition is true.
L0393 |             return; | Returns a value (or control) back to the caller.
L0394 |         } | Block delimiter controlling scope/structure in this language.
L0395 | | Blank line used for readability and logical separation.
L0396 |         if (runHoursInput && runHoursInput.value.trim()) { | Conditional branch that runs only when its condition is true.
L0397 |             const runHours = Number(runHoursInput.value); | Assignment statement storing or updating program state.
L0398 |             if (Number.isNaN(runHours) || runHours < 0) { | Conditional branch that runs only when its condition is true.
L0399 |                 event.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0400 |                 if (typeof window.appNotify === 'function') { | Conditional branch that runs only when its condition is true.
L0401 |                     window.appNotify({ | Block delimiter controlling scope/structure in this language.
L0402 |                         title: 'Invalid Run Hours', | Operational statement participating in the file's runtime behavior.
L0403 |                         message: 'Current DG Run Hours must be a valid non-negative number.' | Operational statement participating in the file's runtime behavior.
L0404 |                     }); | Operational statement participating in the file's runtime behavior.
L0405 |                 } | Block delimiter controlling scope/structure in this language.
L0406 |                 runHoursInput.focus(); | Operational statement participating in the file's runtime behavior.
L0407 |                 return; | Returns a value (or control) back to the caller.
L0408 |             } | Block delimiter controlling scope/structure in this language.
L0409 |         } | Block delimiter controlling scope/structure in this language.
L0410 | | Blank line used for readability and logical separation.
L0411 |         if (startDateInput && endDateInput && startDateInput.value && endDateInput.value && endDateInput.value < startDateInput.value) {
L0412 |             event.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0413 |             if (typeof window.appNotify === 'function') { | Conditional branch that runs only when its condition is true.
L0414 |                 window.appNotify({ | Block delimiter controlling scope/structure in this language.
L0415 |                     title: 'Invalid Date Range', | Operational statement participating in the file's runtime behavior.
L0416 |                     message: 'Activity End date cannot be earlier than Activity Start date.' | Operational statement participating in the file's runtime behavior.
L0417 |                 }); | Operational statement participating in the file's runtime behavior.
L0418 |             } | Block delimiter controlling scope/structure in this language.
L0419 |             endDateInput.focus(); | Operational statement participating in the file's runtime behavior.
L0420 |         } | Block delimiter controlling scope/structure in this language.
L0421 |     }); | Operational statement participating in the file's runtime behavior.
L0422 | | Blank line used for readability and logical separation.
L0423 |     // ===== SET DEFAULT DATES ===== | Operational statement participating in the file's runtime behavior.
L0424 |     const activityStartInput = document.querySelector('input[name="activity_start"]'); | Assignment statement storing or updating program state.
L0425 |     const activityEndInput = document.querySelector('input[name="activity_end"]'); | Assignment statement storing or updating program state.
L0426 |     const now = new Date(); | Assignment statement storing or updating program state.
L0427 |     const formattedDate = now.toISOString().split('T')[0]; | Assignment statement storing or updating program state.
L0428 | | Blank line used for readability and logical separation.
L0429 |     if (activityStartInput) { | Conditional branch that runs only when its condition is true.
L0430 |         activityStartInput.value = formattedDate; | Assignment statement storing or updating program state.
L0431 |     } | Block delimiter controlling scope/structure in this language.
L0432 | | Blank line used for readability and logical separation.
L0433 |     if (activityEndInput) { | Conditional branch that runs only when its condition is true.
L0434 |         activityEndInput.value = formattedDate; | Assignment statement storing or updating program state.
L0435 |     } | Block delimiter controlling scope/structure in this language.
L0436 | }); | Operational statement participating in the file's runtime behavior.
L0437 | </script> | Markup line defining structure in an HTML-like template file.
L0438 | {% endblock %} | Block delimiter controlling scope/structure in this language.

```

File 107: templates/layout.html

```
L0001 | <!DOCTYPE html> | Markup line defining structure in an HTML-like template file.
L0002 | <html lang="en"> | Assignment statement storing or updating program state.
L0003 | <head> | Markup line defining structure in an HTML-like template file.
L0004 | <meta charset="UTF-8" /> | Assignment statement storing or updating program state.
L0005 | <meta name="viewport" content="width=device-width, initial-scale=1, shrink-to-fit=no" /> | Assignment statement storing or updating program state.
L0006 | <title>Preventative Maintenance RCA System</title> | Markup line defining structure in an HTML-like template file.
L0007 | <meta property="og:title" content="Preventative Maintenance RCA System" /> | Assignment statement storing or updating program state.
L0008 | <meta property="og:description" content="Secure PM and RCA portal with role-based access." /> | Assignment statement storing or updating program state.
L0009 | <meta property="og:type" content="website" /> | Assignment statement storing or updating program state.
L0010 | <meta property="og:url" content="{{ request.url }}" /> | Assignment statement storing or updating program state.
L0011 | <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css" /> | Assignment statement storing or updating program state.
L0012 | <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.11.3/font/bootstrap-icons.css" /> | Assignment statement storing or updating program state.
L0013 | <link rel="stylesheet" href="{{ url_for('static', filename='style.css', v=app_build_id) }}" /> | Assignment statement storing or updating program state.
L0014 | </head> | Markup line defining structure in an HTML-like template file.
L0015 | <body data-theme="{{ app_theme }}"> | Assignment statement storing or updating program state.
L0016 | <div id="apploader" class="app-loader is-visible" aria-live="polite" aria-label="Loading" role="status"> | Assignment statement storing or updating program state.
L0017 | <div class="app-loader-card"> | Assignment statement storing or updating program state.
L0018 | <div class="loader-infinity-wrap" aria-hidden="true"> | Assignment statement storing or updating program state.
L0019 | <svg class="loader-infinity" viewBox="0 0 160 80" fill="none" xmlns:xlink="http://www.w3.org/1999/xlink"> | Assignment statement storing or updating program state.
L0020 | <defs> | Markup line defining structure in an HTML-like template file.
L0021 | <linearGradient id="loaderInfinityGradient" x1="20" y1="40" x2="140" y2="40" gradientUnits="userSpaceOnUse"> | Assignment statement storing or updating program state.
L0022 | <stop offset="0%" stop-color="#74c6ff" /> | Assignment statement storing or updating program state.
L0023 | <stop offset="55%" stop-color="#0a84ff" /> | Assignment statement storing or updating program state.
L0024 | <stop offset="100%" stop-color="#5e5ce6" /> | Assignment statement storing or updating program state.
L0025 | </linearGradient> | Markup line defining structure in an HTML-like template file.
L0026 | </defs> | Markup line defining structure in an HTML-like template file.
L0027 | <path | Operational statement participating in the file's runtime behavior.
L0028 | id="loaderInfinityPath" | Assignment statement storing or updating program state.
L0029 | class="loader-infinity-track" | Assignment statement storing or updating program state.
L0030 | d="M20 40C20 25.64 31.64 14 46 14C62.5 14 72.5 31 80 40C87.5 49 97.5 66 114 66C128.36 66 140 54.36 140 40C140 25.64 140 14 128.36 14" /> | Operational statement participating in the file's runtime behavior.
L0031 | /> | Operational statement participating in the file's runtime behavior.
L0032 | <path | Operational statement participating in the file's runtime behavior.
L0033 | class="loader-infinity-snake" | Assignment statement storing or updating program state.
L0034 | d="M20 40C20 25.64 31.64 14 46 14C62.5 14 72.5 31 80 40C87.5 49 97.5 66 114 66C128.36 66 140 54.36 140 40C140 25.64 140 14 128.36 14" /> | Operational statement participating in the file's runtime behavior.
L0035 | pathLength="100" | Assignment statement storing or updating program state.
L0036 | /> | Operational statement participating in the file's runtime behavior.
L0037 | <circle class="loader-snake-head" r="4.2" cx="20" cy="40"> | Assignment statement storing or updating program state.
L0038 | <animate attributeName="r" values="3.7;5.2;3.7" dur="0.42s" repeatCount="indefinite" /> | Assignment statement storing or updating program state.
L0039 | <animate attributeName="opacity" values="0.82;1;0.82" dur="0.42s" repeatCount="indefinite" /> | Assignment statement storing or updating program state.
L0040 | </circle> | Markup line defining structure in an HTML-like template file.
L0041 | <circle class="loader-snake-trail" r="2.6" cx="20" cy="40"></circle> | Assignment statement storing or updating program state.
L0042 | <circle class="loader-snake-trail-2" r="1.95" cx="20" cy="40"></circle> | Assignment statement storing or updating program state.
L0043 | </svg> | Markup line defining structure in an HTML-like template file.
L0044 | </div> | Markup line defining structure in an HTML-like template file.
L0045 | <p class="loader-text" id="appLoaderText">LOADING<span class="loader-dots" aria-hidden="true"><span></span><span></span><span></span><span></span></span></p> | Markup line defining structure in an HTML-like template file.
L0046 | </div> | Markup line defining structure in an HTML-like template file.
L0047 | </div> | Markup line defining structure in an HTML-like template file.
L0048 | | Blank line used for readability and logical separation.
L0049 | <nav class="navbar navbar-light bg-white border-bottom shadow-sm py-3"> | Assignment statement storing or updating program state.
L0050 | <div class="container-fluid justify-content-between align-items-center"> | Assignment statement storing or updating program state.
L0051 | <button class="btn btn-link p-0 menu-toggle-button" type="button" data-bs-toggle="offcanvas" data-bs-target="#offcanvasMenu"> | Assignment statement storing or updating program state.
L0052 | <span class="menu-toggle-lines" aria-hidden="true"> | Assignment statement storing or updating program state.
L0053 | <span></span> | Markup line defining structure in an HTML-like template file.
```

```

L0054 |         <span></span> | Markup line defining structure in an HTML-like template file.
L0055 |         <span></span> | Markup line defining structure in an HTML-like template file.
L0056 |     </span> | Markup line defining structure in an HTML-like template file.
L0057 | </button> | Markup line defining structure in an HTML-like template file.
L0058 | <div class="navbar-brand d-flex align-items-center menu-brand-wrap"> | Assignment statement storing or updating program state.
L0059 |     <span class="brand-chip brand-soliton">SOLITON</span> | Assignment statement storing or updating program state.
L0060 |     <span class="brand-chip brand-telmec ms-2">TELMEC</span> | Assignment statement storing or updating program state.
L0061 |     <span class="build-chip ms-2">Build {{ app_build_id }}</span> | Assignment statement storing or updating program state.
L0062 | </div> | Markup line defining structure in an HTML-like template file.
L0063 | {% set is_login_endpoint = request.endpoint in ['login', 'technician_login', 'staff_login', 'developer_login'] %} | Assignment statement storing or updating program state.
L0064 | {% if current_user.is_authenticated and not is_login_endpoint %} | Block delimiter controlling scope/structure in this language.
L0065 | {% set role_key = ((current_role or current_user.role or 'user')\|replace('-', '_')\|replace(' ', '_')\|lower) %} | Assignment statement storing or updating program state.
L0066 | {% set role_icon_map = { | Assignment statement storing or updating program state.
L0067 |     'technician': 'wrench-adjustable-circle-fill', | Operational statement participating in the file's runtime behavior.
L0068 |     'staff': 'person-workspace', | Operational statement participating in the file's runtime behavior.
L0069 |     'manager': 'briefcase-fill', | Operational statement participating in the file's runtime behavior.
L0070 |     'general_manager': 'shield-lock-fill', | Operational statement participating in the file's runtime behavior.
L0071 |     'developer': 'code-slash', | Operational statement participating in the file's runtime behavior.
L0072 |     'user': 'person-circle' | Operational statement participating in the file's runtime behavior.
L0073 | } %} | Block delimiter controlling scope/structure in this language.
L0074 | <div class="role-notification-wrap"> | Assignment statement storing or updating program state.
L0075 |     <div class="active-role-pill role-{{ role_key }}" title="Active role"> | Assignment statement storing or updating program state.
L0076 |         <span class="role-icon-badge" aria-hidden="true"> | Assignment statement storing or updating program state.
L0077 |             <i class="bi bi-{{ role_icon_map.get(role_key, 'person-circle') }}"></i> | Assignment statement storing or updating program state.
L0078 |         </span> | Markup line defining structure in an HTML-like template file.
L0079 |         <span>{{ (current_role or current_user.role or 'user')\|replace('-', '_')\|title }}</span> | Markup line defining structure in an HTML-like template file.
L0080 |     </div> | Markup line defining structure in an HTML-like template file.
L0081 |     <a class="notification-bell" href="{{ url_for('notifications') }}" aria-label="Notifications"> | Assignment statement storing or updating program state.
L0082 |         <i class="bi bi-bell-fill"></i> | Assignment statement storing or updating program state.
L0083 |         {% if notification_count %} | Block delimiter controlling scope/structure in this language.
L0084 |         <span class="notification-badge">{{ notification_count }}</span> | Assignment statement storing or updating program state.
L0085 |         {% endif %} | Block delimiter controlling scope/structure in this language.
L0086 |     </a> | Markup line defining structure in an HTML-like template file.
L0087 | </div> | Markup line defining structure in an HTML-like template file.
L0088 | {% else %} | Block delimiter controlling scope/structure in this language.
L0089 | <div class="d-none d-sm-block"></div> | Assignment statement storing or updating program state.
L0090 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0091 | </div> | Markup line defining structure in an HTML-like template file.
L0092 | </nav> | Markup line defining structure in an HTML-like template file.
L0093 | | Blank line used for readability and logical separation.
L0094 | <div class="offcanvas offcanvas-start" tabindex="-1" id="offcanvasMenu" aria-labelledby="offcanvasMenuLabel"> | Assignment statement storing or updating program state.
L0095 |     <div class="offcanvas-header"> | Assignment statement storing or updating program state.
L0096 |         <h5 class="offcanvas-title" id="offcanvasMenuLabel">Menu</h5> | Assignment statement storing or updating program state.
L0097 |         <button type="button" class="btn-close text-reset" data-bs-dismiss="offcanvas" aria-label="Close"></button> | Assignment statement storing or updating program state.
L0098 |     </div> | Markup line defining structure in an HTML-like template file.
L0099 |     <div class="offcanvas-body"> | Assignment statement storing or updating program state.
L0100 |         {% if current_user.is_authenticated %} | Block delimiter controlling scope/structure in this language.
L0101 |         <div class="menu-logo-block mb-4"> | Assignment statement storing or updating program state.
L0102 |              | Assignment statement storing or updating program state.
L0103 |         </div> | Markup line defining structure in an HTML-like template file.
L0104 | | Blank line used for readability and logical separation.
L0105 |         <div class="menu-work-card mb-4"> | Assignment statement storing or updating program state.
L0106 |             <h6 class="mb-1">Preventative Maintenance</h6> | Assignment statement storing or updating program state.
L0107 |             <p class="mb-0 text-muted">RCA</p> | Assignment statement storing or updating program state.
L0108 |         </div> | Markup line defining structure in an HTML-like template file.

```



```

L0109 | | Blank line used for readability and logical separation.
L0110 |         <ul class="list-unstyled menu-links"> | Assignment statement storing or updating program state.
L0111 |             <li><a class="menu-link active" href="{{ url_for('dashboard') }}"><i class="bi bi-pie-chart-fill"></i><span data-i18n="
L0112 | | Blank line used for readability and logical separation.
L0113 |             {% if current_role == 'technician' %} | Block delimiter controlling scope/structure in this language.
L0114 |                 <li><a class="menu-link" href="{{ url_for('field_rca') }}"><i class="bi bi-journal-plus"></i><span data-i18n="site_fo
L0115 |             {% elif current_role in ['staff', 'manager', 'general_manager'] %} | Block delimiter controlling scope/structure in thi
L0116 |                 <li><a class="menu-link" href="{{ url_for('desk_activities') }}"><i class="bi bi-clipboard-check"></i><span data-i18n=
L0117 |                 <li><a class="menu-link" href="{{ url_for('notifications') }}"><i class="bi bi-bell-fill"></i><span data-i18n="notifi
L0118 |                 <li><a class="menu-link" href="{{ url_for('settings_page') }}"><i class="bi bi-gear-fill"></i><span data-i18n="settir
L0119 |             {% elif current_role == 'developer' %} | Block delimiter controlling scope/structure in this language.
L0120 |                 <li><a class="menu-link" href="{{ url_for('admin_staff') }}"><i class="bi bi-people-fill"></i><span data-i18n="manag
L0121 |                 <li><a class="menu-link" href="{{ url_for('developer_photo_library') }}"><i class="bi bi-images"></i><span>Photo Libr
L0122 |                 <li><a class="menu-link" href="{{ url_for('notifications') }}"><i class="bi bi-bell-fill"></i><span data-i18n="notifi
L0123 |                 <li><a class="menu-link" href="{{ url_for('settings_page') }}"><i class="bi bi-gear-fill"></i><span data-i18n="settir
L0124 |             {% endif %} | Block delimiter controlling scope/structure in this language.
L0125 |                 <li><a class="menu-link" href="{{ url_for('logout') }}"><i class="bi bi-lock-fill"></i><span data-i18n="logout">Logout<
L0126 |         </ul> | Markup line defining structure in an HTML-like template file.
L0127 |     {% else %} | Block delimiter controlling scope/structure in this language.
L0128 |         <a class="btn btn-sm btn-primary me-2" href="{{ url_for('login') }}">Login</a> | Assignment statement storing or updating
L0129 |         <a class="btn btn-sm btn-secondary" href="{{ url_for('register') }}">Create Developer</a> | Assignment statement storing
L0130 |     {% endif %} | Block delimiter controlling scope/structure in this language.
L0131 | </div> | Markup line defining structure in an HTML-like template file.
L0132 | </div> | Markup line defining structure in an HTML-like template file.
L0133 | | Blank line used for readability and logical separation.
L0134 |     {% set back_fallback = request.referrer or (url_for('dashboard') if current_user.is_authenticated else url_for('login')) %} | A
L0135 |     {% set back_hidden_endpoints = ['dashboard', 'login', 'technician_login', 'staff_login', 'developer_login'] %} | Assignment sta
L0136 |     {% set show_back_pill = request.endpoint not in back_hidden_endpoints %} | Assignment statement storing or updating program sta
L0137 | | Blank line used for readability and logical separation.
L0138 |     <main class="container main-container py-4"> | Assignment statement storing or updating program state.
L0139 |         {% if show_back_pill %} | Block delimiter controlling scope/structure in this language.
L0140 |             <div class="page-utility-bar"> | Assignment statement storing or updating program state.
L0141 |                 <a | Operational statement participating in the file's runtime behavior.
L0142 |                     href="{{ back_fallback }}" | Assignment statement storing or updating program state.
L0143 |                     class="page-back-pill" | Assignment statement storing or updating program state.
L0144 |                     id="pageBackPill" | Assignment statement storing or updating program state.
L0145 |                     aria-label="Go back" | Assignment statement storing or updating program state.
L0146 |                     data-fallback-url="{{ back_fallback }}" | Assignment statement storing or updating program state.
L0147 |                 > | Operational statement participating in the file's runtime behavior.
L0148 |                 <i class="bi bi-chevron-left" aria-hidden="true"></i> | Assignment statement storing or updating program state.
L0149 |                 <span>Back</span> | Markup line defining structure in an HTML-like template file.
L0150 |             </a> | Markup line defining structure in an HTML-like template file.
L0151 |         </div> | Markup line defining structure in an HTML-like template file.
L0152 |     {% endif %} | Block delimiter controlling scope/structure in this language.
L0153 | | Blank line used for readability and logical separation.
L0154 |     {% with messages = get_flashed_messages(with_categories=true) %} | Assignment statement storing or updating program state.
L0155 |         {% if messages %} | Block delimiter controlling scope/structure in this language.
L0156 |             {% for category, message in messages %} | Block delimiter controlling scope/structure in this language.
L0157 |                 <div class="alert alert-{{ category }}">{{ message }}</div> | Assignment statement storing or updating program state.
L0158 |             {% endfor %} | Block delimiter controlling scope/structure in this language.
L0159 |         {% endif %} | Block delimiter controlling scope/structure in this language.
L0160 |     {% endwith %} | Block delimiter controlling scope/structure in this language.
L0161 |     {% block content %}{% endblock %} | Block delimiter controlling scope/structure in this language.
L0162 | </main> | Markup line defining structure in an HTML-like template file.
L0163 | | Blank line used for readability and logical separation.

```

L0164 | <script id="publicHolidayData" type="application/json">{{ public_holidays\|tojson }}</script> | Assignment statement storing or
L0165 | | Blank line used for readability and logical separation.
L0166 | <div class="holiday-popup-backdrop" id="holidayPopupBackdrop" hidden> | Assignment statement storing or updating program state.
L0167 | <div class="holiday-popup-card"> | Assignment statement storing or updating program state.
L0168 | <div class="holiday-popup-icon"><i class="bi bi-calendar-event-fill"></i></div> | Assignment statement storing or updating
L0169 | <h5 id="holidayPopupTitle">Public Holiday Today</h5> | Assignment statement storing or updating program state.
L0170 | <p id="holidayPopupText" class="mb-3"></p> | Assignment statement storing or updating program state.
L0171 | <button type="button" class="btn btn-primary" id="holidayPopupClose">Close</button> | Assignment statement storing or updating
L0172 | </div> | Markup line defining structure in an HTML-like template file.
L0173 | </div> | Markup line defining structure in an HTML-like template file.
L0174 | | Blank line used for readability and logical separation.
L0175 | <div class="modal fade" id="appConfirmModal" tabindex="-1" aria-hidden="true"> | Assignment statement storing or updating program
L0176 | <div class="modal-dialog modal-dialog-centered"> | Assignment statement storing or updating program state.
L0177 | <div class="modal-content app-confirm-modal"> | Assignment statement storing or updating program state.
L0178 | <div class="modal-header border-0 pb-1"> | Assignment statement storing or updating program state.
L0179 | <h5 class="modal-title" id="appConfirmTitle">Confirm Action</h5> | Assignment statement storing or updating program state.
L0180 | <button type="button" class="btn-close" data-bs-dismiss="modal" aria-label="Close"></button> | Assignment statement storing or updating
L0181 | </div> | Markup line defining structure in an HTML-like template file.
L0182 | <div class="modal-body pt-0"> | Assignment statement storing or updating program state.
L0183 | <p class="mb-0" id="appConfirmMessage">Are you sure you want to continue?</p> | Assignment statement storing or updating
L0184 | </div> | Markup line defining structure in an HTML-like template file.
L0185 | <div class="modal-footer border-0 pt-2"> | Assignment statement storing or updating program state.
L0186 | <button type="button" class="btn btn-outline-secondary" data-bs-dismiss="modal" id="appConfirmCancel">No</button> | Assignment statement storing or updating
L0187 | <button type="button" class="btn btn-danger" id="appConfirmOk">Yes</button> | Assignment statement storing or updating
L0188 | </div> | Markup line defining structure in an HTML-like template file.
L0189 | </div> | Markup line defining structure in an HTML-like template file.
L0190 | </div> | Markup line defining structure in an HTML-like template file.
L0191 | </div> | Markup line defining structure in an HTML-like template file.
L0192 | | Blank line used for readability and logical separation.
L0193 | <div class="modal fade" id="appNoticeModal" tabindex="-1" aria-hidden="true"> | Assignment statement storing or updating program
L0194 | <div class="modal-dialog modal-dialog-centered"> | Assignment statement storing or updating program state.
L0195 | <div class="modal-content app-confirm-modal"> | Assignment statement storing or updating program state.
L0196 | <div class="modal-header border-0 pb-1"> | Assignment statement storing or updating program state.
L0197 | <h5 class="modal-title" id="appNoticeTitle">Notice</h5> | Assignment statement storing or updating program state.
L0198 | <button type="button" class="btn-close" data-bs-dismiss="modal" aria-label="Close"></button> | Assignment statement storing or updating
L0199 | </div> | Markup line defining structure in an HTML-like template file.
L0200 | <div class="modal-body pt-0"> | Assignment statement storing or updating program state.
L0201 | <p class="mb-0" id="appNoticeMessage">Please review and continue.</p> | Assignment statement storing or updating program
L0202 | </div> | Markup line defining structure in an HTML-like template file.
L0203 | <div class="modal-footer border-0 pt-2"> | Assignment statement storing or updating program state.
L0204 | <button type="button" class="btn btn-primary" id="appNoticeOk">OK</button> | Assignment statement storing or updating program
L0205 | </div> | Markup line defining structure in an HTML-like template file.
L0206 | </div> | Markup line defining structure in an HTML-like template file.
L0207 | </div> | Markup line defining structure in an HTML-like template file.
L0208 | </div> | Markup line defining structure in an HTML-like template file.
L0209 | | Blank line used for readability and logical separation.
L0210 | <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"></script> | Assignment statement storing or
L0211 | <script> | Markup line defining structure in an HTML-like template file.
L0212 | (function () { | Block delimiter controlling scope/structure in this language.
L0213 | const loader = document.getElementById('appLoader'); | Assignment statement storing or updating program state.
L0214 | const loaderText = document.getElementById('appLoaderText'); | Assignment statement storing or updating program state.
L0215 | const loaderSnakePath = document.getElementById('loaderInfinityPath'); | Assignment statement storing or updating program state.
L0216 | const loaderSnakeHead = document.querySelector('.loader-snake-head'); | Assignment statement storing or updating program state.
L0217 | const loaderSnakeTrail = document.querySelector('.loader-snake-trail'); | Assignment statement storing or updating program state.
L0218 | const loaderSnakeTrail2 = document.querySelector('.loader-snake-trail-2'); | Assignment statement storing or updating program state.

```

L0219 |         if (!loader) { | Conditional branch that runs only when its condition is true.
L0220 |             return; | Returns a value (or control) back to the caller.
L0221 |         } | Block delimiter controlling scope/structure in this language.
L0222 |         let activeRequests = 0; | Assignment statement storing or updating program state.
L0223 |         const MIN_LOADER_VISIBLE_MS = 220; | Assignment statement storing or updating program state.
L0224 |         let loaderShownAt = Date.now(); | Assignment statement storing or updating program state.
L0225 |         let hideLoaderTimer = null; | Assignment statement storing or updating program state.
L0226 |         let loaderSnakeRaf = null; | Assignment statement storing or updating program state.
L0227 |         let loaderSnakeStartedAt = 0; | Assignment statement storing or updating program state.
L0228 |         const silentPathMarkers = ['/api/dashboard-counts']; | Assignment statement storing or updating program state.
L0229 | | Blank line used for readability and logical separation.
L0230 |         function setSnakePosition(node, distance) { | Block delimiter controlling scope/structure in this language.
L0231 |             if (!loaderSnakePath \\| !node) { | Conditional branch that runs only when its condition is true.
L0232 |                 return; | Returns a value (or control) back to the caller.
L0233 |             } | Block delimiter controlling scope/structure in this language.
L0234 |             const length = loaderSnakePath.getTotalLength(); | Assignment statement storing or updating program state.
L0235 |             if (!length) { | Conditional branch that runs only when its condition is true.
L0236 |                 return; | Returns a value (or control) back to the caller.
L0237 |             } | Block delimiter controlling scope/structure in this language.
L0238 |             const offset = ((distance % length) + length) % length; | Assignment statement storing or updating program state.
L0239 |             const point = loaderSnakePath.getPointAtLength(offset); | Assignment statement storing or updating program state.
L0240 |             node.setAttribute('cx', point.x.toFixed(2)); | Operational statement participating in the file's runtime behavior.
L0241 |             node.setAttribute('cy', point.y.toFixed(2)); | Operational statement participating in the file's runtime behavior.
L0242 |         } | Block delimiter controlling scope/structure in this language.
L0243 | | Blank line used for readability and logical separation.
L0244 |         function animateSnakeFallback(now) { | Block delimiter controlling scope/structure in this language.
L0245 |             if (!loader.classList.contains('is-visible') \\| !loaderSnakePath) { | Conditional branch that runs only when its condition is true.
L0246 |                 loaderSnakeRaf = null; | Assignment statement storing or updating program state.
L0247 |                 return; | Returns a value (or control) back to the caller.
L0248 |             } | Block delimiter controlling scope/structure in this language.
L0249 | | Blank line used for readability and logical separation.
L0250 |             if (!loaderSnakeStartedAt) { | Conditional branch that runs only when its condition is true.
L0251 |                 loaderSnakeStartedAt = now; | Assignment statement storing or updating program state.
L0252 |             } | Block delimiter controlling scope/structure in this language.
L0253 | | Blank line used for readability and logical separation.
L0254 |             const elapsed = now - loaderSnakeStartedAt; | Assignment statement storing or updating program state.
L0255 |             const durationMs = 1050; | Assignment statement storing or updating program state.
L0256 |             const progress = (elapsed % durationMs) / durationMs; | Assignment statement storing or updating program state.
L0257 |             const pathLength = loaderSnakePath.getTotalLength(); | Assignment statement storing or updating program state.
L0258 |             const headDistance = progress * pathLength; | Assignment statement storing or updating program state.
L0259 | | Blank line used for readability and logical separation.
L0260 |             setSnakePosition(loaderSnakeHead, headDistance); | Operational statement participating in the file's runtime behavior.
L0261 |             setSnakePosition(loaderSnakeTrail, headDistance - (pathLength * 0.16)); | Operational statement participating in the file's runtime behavior.
L0262 |             setSnakePosition(loaderSnakeTrail2, headDistance - (pathLength * 0.29)); | Operational statement participating in the file's runtime behavior.
L0263 | | Blank line used for readability and logical separation.
L0264 |             loaderSnakeRaf = window.requestAnimationFrame(animateSnakeFallback); | Assignment statement storing or updating program state.
L0265 |         } | Block delimiter controlling scope/structure in this language.
L0266 | | Blank line used for readability and logical separation.
L0267 |         function startSnakeFallback() { | Block delimiter controlling scope/structure in this language.
L0268 |             if (!loaderSnakePath \\| loaderSnakeRaf) { | Conditional branch that runs only when its condition is true.
L0269 |                 return; | Returns a value (or control) back to the caller.
L0270 |             } | Block delimiter controlling scope/structure in this language.
L0271 |             loaderSnakeStartedAt = 0; | Assignment statement storing or updating program state.
L0272 |             loaderSnakeRaf = window.requestAnimationFrame(animateSnakeFallback); | Assignment statement storing or updating program state.
L0273 |         } | Block delimiter controlling scope/structure in this language.

```

```

L0274 | | Blank line used for readability and logical separation.
L0275 |     function stopSnakeFallback() { | Block delimiter controlling scope/structure in this language.
L0276 |         if (loaderSnakeRaf) { | Conditional branch that runs only when its condition is true.
L0277 |             window.cancelAnimationFrame(loaderSnakeRaf); | Operational statement participating in the file's runtime behavior.
L0278 |             loaderSnakeRaf = null; | Assignment statement storing or updating program state.
L0279 |         } | Block delimiter controlling scope/structure in this language.
L0280 |     } | Block delimiter controlling scope/structure in this language.
L0281 | | Blank line used for readability and logical separation.
L0282 |     function isSilentRequest(inputUrl) { | Block delimiter controlling scope/structure in this language.
L0283 |         if (!inputUrl) { | Conditional branch that runs only when its condition is true.
L0284 |             return false; | Returns a value (or control) back to the caller.
L0285 |         } | Block delimiter controlling scope/structure in this language.
L0286 |         try { | Block delimiter controlling scope/structure in this language.
L0287 |             const absolute = new URL(inputUrl, window.location.href); | Assignment statement storing or updating program state.
L0288 |             return silentPathMarkers.some(function (marker) { | Returns a value (or control) back to the caller.
L0289 |                 return absolute.pathname.indexOf(marker) !== -1; | Returns a value (or control) back to the caller.
L0290 |             }); | Operational statement participating in the file's runtime behavior.
L0291 |         } catch (e) { | Block delimiter controlling scope/structure in this language.
L0292 |             return false; | Returns a value (or control) back to the caller.
L0293 |         } | Block delimiter controlling scope/structure in this language.
L0294 |     } | Block delimiter controlling scope/structure in this language.
L0295 | | Blank line used for readability and logical separation.
L0296 |     function showLoader() { | Block delimiter controlling scope/structure in this language.
L0297 |         if (hideLoaderTimer) { | Conditional branch that runs only when its condition is true.
L0298 |             window.clearTimeout(hideLoaderTimer); | Operational statement participating in the file's runtime behavior.
L0299 |             hideLoaderTimer = null; | Assignment statement storing or updating program state.
L0300 |         } | Block delimiter controlling scope/structure in this language.
L0301 |         if (!loader.classList.contains('is-visible')) { | Conditional branch that runs only when its condition is true.
L0302 |             loaderShownAt = Date.now(); | Assignment statement storing or updating program state.
L0303 |         } | Block delimiter controlling scope/structure in this language.
L0304 |         loader.classList.add('is-visible'); | Operational statement participating in the file's runtime behavior.
L0305 |         document.body.classList.add('app-is-loading'); | Operational statement participating in the file's runtime behavior.
L0306 |         startSnakeFallback(); | Operational statement participating in the file's runtime behavior.
L0307 |     } | Block delimiter controlling scope/structure in this language.
L0308 | | Blank line used for readability and logical separation.
L0309 |     function hideLoader() { | Block delimiter controlling scope/structure in this language.
L0310 |         const elapsed = Date.now() - loaderShownAt; | Assignment statement storing or updating program state.
L0311 |         const waitMs = Math.max(0, MIN_LOADER_VISIBLE_MS - elapsed); | Assignment statement storing or updating program state.
L0312 |         if (hideLoaderTimer) { | Conditional branch that runs only when its condition is true.
L0313 |             window.clearTimeout(hideLoaderTimer); | Operational statement participating in the file's runtime behavior.
L0314 |         } | Block delimiter controlling scope/structure in this language.
L0315 |         hideLoaderTimer = window.setTimeout(function () { | Assignment statement storing or updating program state.
L0316 |             if (activeRequests === 0) { | Conditional branch that runs only when its condition is true.
L0317 |                 loader.classList.remove('is-visible'); | Operational statement participating in the file's runtime behavior.
L0318 |                 document.body.classList.remove('app-is-loading'); | Operational statement participating in the file's runtime behavior.
L0319 |                 stopSnakeFallback(); | Operational statement participating in the file's runtime behavior.
L0320 |             } | Block delimiter controlling scope/structure in this language.
L0321 |             hideLoaderTimer = null; | Assignment statement storing or updating program state.
L0322 |         }, waitMs); | Operational statement participating in the file's runtime behavior.
L0323 |     } | Block delimiter controlling scope/structure in this language.
L0324 | | Blank line used for readability and logical separation.
L0325 |     function setLoaderMessage(message, submessage) { | Block delimiter controlling scope/structure in this language.
L0326 |         if (!loaderText) { | Conditional branch that runs only when its condition is true.
L0327 |             return; | Returns a value (or control) back to the caller.
L0328 |         } | Block delimiter controlling scope/structure in this language.

```

```

L0329 |         loaderText.childNodes[0].nodeValue = 'LOADING'; | Assignment statement storing or updating program state.
L0330 |     } | Block delimiter controlling scope/structure in this language.
L0331 | | Blank line used for readability and logical separation.
L0332 |     function beginRequest() { | Block delimiter controlling scope/structure in this language.
L0333 |         activeRequests += 1; | Assignment statement storing or updating program state.
L0334 |         showLoader(); | Operational statement participating in the file's runtime behavior.
L0335 |     } | Block delimiter controlling scope/structure in this language.
L0336 | | Blank line used for readability and logical separation.
L0337 |     function endRequest() { | Block delimiter controlling scope/structure in this language.
L0338 |         activeRequests = Math.max(0, activeRequests - 1); | Assignment statement storing or updating program state.
L0339 |         if (activeRequests === 0) { | Conditional branch that runs only when its condition is true.
L0340 |             hideLoader(); | Operational statement participating in the file's runtime behavior.
L0341 |         } | Block delimiter controlling scope/structure in this language.
L0342 |     } | Block delimiter controlling scope/structure in this language.
L0343 | | Blank line used for readability and logical separation.
L0344 |     window.appLoader = { show: showLoader, hide: hideLoader, setMessage: setLoaderMessage }; | Assignment statement storing or
L0345 | | Blank line used for readability and logical separation.
L0346 |     let confirmModalInstance = null; | Assignment statement storing or updating program state.
L0347 |     const confirmModalEl = document.getElementById('appConfirmModal'); | Assignment statement storing or updating program state
L0348 |     const confirmTitleEl = document.getElementById('appConfirmTitle'); | Assignment statement storing or updating program state
L0349 |     const confirmMessageEl = document.getElementById('appConfirmMessage'); | Assignment statement storing or updating program s
L0350 |     const confirmOkButton = document.getElementById('appConfirmOk'); | Assignment statement storing or updating program state.
L0351 |     const confirmCancelButton = document.getElementById('appConfirmCancel'); | Assignment statement storing or updating program
L0352 |     let noticeModalInstance = null; | Assignment statement storing or updating program state.
L0353 |     const noticeModalEl = document.getElementById('appNoticeModal'); | Assignment statement storing or updating program state.
L0354 |     const noticeTitleEl = document.getElementById('appNoticeTitle'); | Assignment statement storing or updating program state.
L0355 |     const noticeMessageEl = document.getElementById('appNoticeMessage'); | Assignment statement storing or updating program sta
L0356 |     const noticeOkButton = document.getElementById('appNoticeOk'); | Assignment statement storing or updating program state.
L0357 | | Blank line used for readability and logical separation.
L0358 |     function ensureConfirmModal() { | Block delimiter controlling scope/structure in this language.
L0359 |         if (!confirmModalEl || !window.bootstrap || !window.bootstrap.Modal) { | Conditional branch that runs only when its c
L0360 |             return null; | Returns a value (or control) back to the caller.
L0361 |         } | Block delimiter controlling scope/structure in this language.
L0362 |         if (!confirmModalInstance) { | Conditional branch that runs only when its condition is true.
L0363 |             confirmModalInstance = new window.bootstrap.Modal(confirmModalEl, { | Assignment statement storing or updating program
L0364 |                 backdrop: 'static', | Operational statement participating in the file's runtime behavior.
L0365 |                 keyboard: true, | Operational statement participating in the file's runtime behavior.
L0366 |             }); | Operational statement participating in the file's runtime behavior.
L0367 |         } | Block delimiter controlling scope/structure in this language.
L0368 |         return confirmModalInstance; | Returns a value (or control) back to the caller.
L0369 |     } | Block delimiter controlling scope/structure in this language.
L0370 | | Blank line used for readability and logical separation.
L0371 |     function ensureNoticeModal() { | Block delimiter controlling scope/structure in this language.
L0372 |         if (!noticeModalEl || !window.bootstrap || !window.bootstrap.Modal) { | Conditional branch that runs only when its co
L0373 |             return null; | Returns a value (or control) back to the caller.
L0374 |         } | Block delimiter controlling scope/structure in this language.
L0375 |         if (!noticeModalInstance) { | Conditional branch that runs only when its condition is true.
L0376 |             noticeModalInstance = new window.bootstrap.Modal(noticeModalEl, { | Assignment statement storing or updating program st
L0377 |                 backdrop: true, | Operational statement participating in the file's runtime behavior.
L0378 |                 keyboard: true, | Operational statement participating in the file's runtime behavior.
L0379 |             }); | Operational statement participating in the file's runtime behavior.
L0380 |         } | Block delimiter controlling scope/structure in this language.
L0381 |         return noticeModalInstance; | Returns a value (or control) back to the caller.
L0382 |     } | Block delimiter controlling scope/structure in this language.
L0383 | | Blank line used for readability and logical separation.

```

```

L0384 |         window.appConfirm = function (opts) { | Assignment statement storing or updating program state.
L0385 |             const options = opts \\| {}| | Assignment statement storing or updating program state.
L0386 |             const title = options.title \\| 'Confirm Action'| | Assignment statement storing or updating program state.
L0387 |             const message = options.message \\| 'Are you sure you want to continue?'; | Assignment statement storing or updating program state.
L0388 |             const confirmLabel = options.confirmLabel \\| 'Yes'; | Assignment statement storing or updating program state.
L0389 |             const cancelLabel = options.cancelLabel \\| 'No'; | Assignment statement storing or updating program state.
L0390 | | Blank line used for readability and logical separation.
L0391 |             const modal = ensureConfirmModal(); | Assignment statement storing or updating program state.
L0392 |             if (!modal \\| !confirmOkButton \\| !confirmCancelButton \\| !confirmTitleEl \\| !confirmMessageEl) { | Conditional branch that runs only when its condition is true.
L0393 |                 return Promise.resolve(false); | Returns a value (or control) back to the caller.
L0394 |             } | Block delimiter controlling scope/structure in this language.
L0395 | | Blank line used for readability and logical separation.
L0396 |             return new Promise(function (resolve) { | Returns a value (or control) back to the caller.
L0397 |                 let settled = false; | Assignment statement storing or updating program state.
L0398 |                 function settle(value) { | Block delimiter controlling scope/structure in this language.
L0399 |                     if (settled) { | Conditional branch that runs only when its condition is true.
L0400 |                         return; | Returns a value (or control) back to the caller.
L0401 |                     } | Block delimiter controlling scope/structure in this language.
L0402 |                     settled = true; | Assignment statement storing or updating program state.
L0403 |                     confirmOkButton.removeEventListener('click', onConfirm); | Operational statement participating in the file's runtime behavior.
L0404 |                     confirmCancelButton.removeEventListener('click', onCancel); | Operational statement participating in the file's runtime behavior.
L0405 |                     confirmModalEl.removeEventListener('hidden.bs.modal', onHide); | Operational statement participating in the file's runtime behavior.
L0406 |                     resolve(value); | Operational statement participating in the file's runtime behavior.
L0407 |                 } | Block delimiter controlling scope/structure in this language.
L0408 | | Blank line used for readability and logical separation.
L0409 |                 function onConfirm() { | Block delimiter controlling scope/structure in this language.
L0410 |                     modal.hide(); | Operational statement participating in the file's runtime behavior.
L0411 |                     settle(true); | Operational statement participating in the file's runtime behavior.
L0412 |                 } | Block delimiter controlling scope/structure in this language.
L0413 | | Blank line used for readability and logical separation.
L0414 |                 function onCancel() { | Block delimiter controlling scope/structure in this language.
L0415 |                     modal.hide(); | Operational statement participating in the file's runtime behavior.
L0416 |                     settle(false); | Operational statement participating in the file's runtime behavior.
L0417 |                 } | Block delimiter controlling scope/structure in this language.
L0418 | | Blank line used for readability and logical separation.
L0419 |                 function onHide() { | Block delimiter controlling scope/structure in this language.
L0420 |                     settle(false); | Operational statement participating in the file's runtime behavior.
L0421 |                 } | Block delimiter controlling scope/structure in this language.
L0422 | | Blank line used for readability and logical separation.
L0423 |                 confirmTitleEl.textContent = title; | Assignment statement storing or updating program state.
L0424 |                 confirmMessageEl.textContent = message; | Assignment statement storing or updating program state.
L0425 |                 confirmOkButton.textContent = confirmLabel; | Assignment statement storing or updating program state.
L0426 |                 confirmCancelButton.textContent = cancelLabel; | Assignment statement storing or updating program state.
L0427 | | Blank line used for readability and logical separation.
L0428 |                 confirmOkButton.addEventListener('click', onConfirm); | Operational statement participating in the file's runtime behavior.
L0429 |                 confirmCancelButton.addEventListener('click', onCancel); | Operational statement participating in the file's runtime behavior.
L0430 |                 confirmModalEl.addEventListener('hidden.bs.modal', onHide, { once: true }); | Operational statement participating in the file's runtime behavior.
L0431 | | Blank line used for readability and logical separation.
L0432 |                 modal.show(); | Operational statement participating in the file's runtime behavior.
L0433 |             }); | Operational statement participating in the file's runtime behavior.
L0434 |         }; | Operational statement participating in the file's runtime behavior.
L0435 | | Blank line used for readability and logical separation.
L0436 |         window.appNotify = function (opts) { | Assignment statement storing or updating program state.
L0437 |             const options = opts \\| {}| | Assignment statement storing or updating program state.
L0438 |             const title = options.title \\| 'Notice'; | Assignment statement storing or updating program state.

```

```

L0439 |         const message = options.message \\| 'Please review and continue.'; | Assignment statement storing or updating program state.
L0440 |         const okLabel = options.okLabel \\| 'OK'; | Assignment statement storing or updating program state.
L0441 | | Blank line used for readability and logical separation.
L0442 |         const modal = ensureNoticeModal(); | Assignment statement storing or updating program state.
L0443 |         if (!modal \\| !noticeTitleEl \\| !noticeMessageEl \\| !noticeOkButton) { | Conditional branch that runs only when its
L0444 |             return Promise.resolve(); | Returns a value (or control) back to the caller.
L0445 |         } | Block delimiter controlling scope/structure in this language.
L0446 | | Blank line used for readability and logical separation.
L0447 |         return new Promise(function (resolve) { | Returns a value (or control) back to the caller.
L0448 |             let settled = false; | Assignment statement storing or updating program state.
L0449 | | Blank line used for readability and logical separation.
L0450 |             function settle() { | Block delimiter controlling scope/structure in this language.
L0451 |                 if (settled) { | Conditional branch that runs only when its condition is true.
L0452 |                     return; | Returns a value (or control) back to the caller.
L0453 |                 } | Block delimiter controlling scope/structure in this language.
L0454 |                 settled = true; | Assignment statement storing or updating program state.
L0455 |                 noticeOkButton.removeEventListener('click', onOk); | Operational statement participating in the file's runtime behavior.
L0456 |                 noticeModalEl.removeEventListener('hidden.bs.modal', onHide); | Operational statement participating in the file's runtime behavior.
L0457 |                 resolve(); | Operational statement participating in the file's runtime behavior.
L0458 |             } | Block delimiter controlling scope/structure in this language.
L0459 | | Blank line used for readability and logical separation.
L0460 |             function onOk() { | Block delimiter controlling scope/structure in this language.
L0461 |                 modal.hide(); | Operational statement participating in the file's runtime behavior.
L0462 |                 settle(); | Operational statement participating in the file's runtime behavior.
L0463 |             } | Block delimiter controlling scope/structure in this language.
L0464 | | Blank line used for readability and logical separation.
L0465 |             function onHide() { | Block delimiter controlling scope/structure in this language.
L0466 |                 settle(); | Operational statement participating in the file's runtime behavior.
L0467 |             } | Block delimiter controlling scope/structure in this language.
L0468 | | Blank line used for readability and logical separation.
L0469 |             noticeTitleEl.textContent = title; | Assignment statement storing or updating program state.
L0470 |             noticeMessageEl.textContent = message; | Assignment statement storing or updating program state.
L0471 |             noticeOkButton.textContent = okLabel; | Assignment statement storing or updating program state.
L0472 |             noticeOkButton.addEventListener('click', onOk); | Operational statement participating in the file's runtime behavior.
L0473 |             noticeModalEl.addEventListener('hidden.bs.modal', onHide, { once: true }); | Operational statement participating in the file's runtime behavior.
L0474 |             modal.show(); | Operational statement participating in the file's runtime behavior.
L0475 |         }); | Operational statement participating in the file's runtime behavior.
L0476 |     }; | Operational statement participating in the file's runtime behavior.
L0477 | | Blank line used for readability and logical separation.
L0478 |     if (window.fetch) { | Conditional branch that runs only when its condition is true.
L0479 |         const nativeFetch = window.fetch.bind(window); | Assignment statement storing or updating program state.
L0480 |         window.fetch = function (input, init) { | Assignment statement storing or updating program state.
L0481 |             const requestUrl = typeof input === 'string' ? input : (input && input.url) \\| ''; | Operational statement participating in the file's runtime behavior.
L0482 |             const skipLoader = isSilentRequest(requestUrl) \\| (init && init.loader === false); | Operational statement participating in the file's runtime behavior.
L0483 | | Blank line used for readability and logical separation.
L0484 |             if (!skipLoader) { | Conditional branch that runs only when its condition is true.
L0485 |                 setLoaderMessage('Loading...', 'Syncing live data securely.');
```

```

L0494 |         }); | Operational statement participating in the file's runtime behavior.
L0495 |     }; | Operational statement participating in the file's runtime behavior.
L0496 | } | Block delimiter controlling scope/structure in this language.
L0497 | | Blank line used for readability and logical separation.
L0498 |     if (window.XMLHttpRequest) { | Conditional branch that runs only when its condition is true.
L0499 |         const nativeOpen = window.XMLHttpRequest.prototype.open; | Assignment statement storing or updating program state.
L0500 |         const nativeSend = window.XMLHttpRequest.prototype.send; | Assignment statement storing or updating program state.
L0501 | | Blank line used for readability and logical separation.
L0502 |         window.XMLHttpRequest.prototype.open = function (method, url) { | Assignment statement storing or updating program state.
L0503 |             this._loaderUrl = url; | Assignment statement storing or updating program state.
L0504 |             this._skipLoader = isSilentRequest(url); | Assignment statement storing or updating program state.
L0505 |             return nativeOpen.apply(this, arguments); | Returns a value (or control) back to the caller.
L0506 |         }; | Operational statement participating in the file's runtime behavior.
L0507 | | Blank line used for readability and logical separation.
L0508 |         window.XMLHttpRequest.prototype.send = function () { | Assignment statement storing or updating program state.
L0509 |             if (!this._skipLoader) { | Conditional branch that runs only when its condition is true.
L0510 |                 setLoaderMessage('Loading...', 'Syncing live data securely. '); | Operational statement participating in the file's runtime behavior.
L0511 |                 beginRequest(); | Operational statement participating in the file's runtime behavior.
L0512 |                 this.addEventListener('loadend', endRequest, { once: true }); | Operational statement participating in the file's runtime behavior.
L0513 |             } | Block delimiter controlling scope/structure in this language.
L0514 |             return nativeSend.apply(this, arguments); | Returns a value (or control) back to the caller.
L0515 |         }; | Operational statement participating in the file's runtime behavior.
L0516 |     } | Block delimiter controlling scope/structure in this language.
L0517 | | Blank line used for readability and logical separation.
L0518 |     window.addEventListener('pageshow', function () { | Block delimiter controlling scope/structure in this language.
L0519 |         window.setTimeout(hideLoader, 120); | Operational statement participating in the file's runtime behavior.
L0520 |     }); | Operational statement participating in the file's runtime behavior.
L0521 | | Blank line used for readability and logical separation.
L0522 |     document.addEventListener('DOMContentLoaded', function () { | Block delimiter controlling scope/structure in this language.
L0523 |         window.setTimeout(hideLoader, 120); | Operational statement participating in the file's runtime behavior.
L0524 | | Blank line used for readability and logical separation.
L0525 |     /* ■■ avatar tile picker ■■ */ | Operational statement participating in the file's runtime behavior.
L0526 |     document.querySelectorAll('.avatar-pick-group').forEach(function (group) { | Block delimiter controlling scope/structure in this language.
L0527 |         var tiles = group.querySelectorAll('.avatar-pick-tile'); | Assignment statement storing or updating program state.
L0528 |         tiles.forEach(function (tile) { | Block delimiter controlling scope/structure in this language.
L0529 |             tile.addEventListener('click', function () { | Block delimiter controlling scope/structure in this language.
L0530 |                 tiles.forEach(function (t) { t.classList.remove('is-selected'); }); | Operational statement participating in the file's runtime behavior.
L0531 |                 tile.classList.add('is-selected'); | Operational statement participating in the file's runtime behavior.
L0532 |             }); | Operational statement participating in the file's runtime behavior.
L0533 |         }); | Operational statement participating in the file's runtime behavior.
L0534 |     }); | Operational statement participating in the file's runtime behavior.
L0535 | }); | Operational statement participating in the file's runtime behavior.
L0536 | | Blank line used for readability and logical separation.
L0537 |     window.addEventListener('beforeunload', function () { | Block delimiter controlling scope/structure in this language.
L0538 |         setLoaderMessage('Loading...', 'Opening your next page. '); | Operational statement participating in the file's runtime behavior.
L0539 |         showLoader(); | Operational statement participating in the file's runtime behavior.
L0540 |     }); | Operational statement participating in the file's runtime behavior.
L0541 | | Blank line used for readability and logical separation.
L0542 |     document.addEventListener('submit', function (event) { | Block delimiter controlling scope/structure in this language.
L0543 |         const form = event.target; | Assignment statement storing or updating program state.
L0544 |         if (!(form instanceof HTMLFormElement)) { | Conditional branch that runs only when its condition is true.
L0545 |             return; | Returns a value (or control) back to the caller.
L0546 |         } | Block delimiter controlling scope/structure in this language.
L0547 | | Blank line used for readability and logical separation.
L0548 |         const confirmMessage = form.getAttribute('data-confirm-message'); | Assignment statement storing or updating program state.

```



```

L0549 |         if (confirmMessage && !form.dataset.confirmedSubmit) { | Conditional branch that runs only when its condition is true.
L0550 |             event.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0551 |             window.appConfirm({ | Block delimiter controlling scope/structure in this language.
L0552 |                 title: form.getAttribute('data-confirm-title') \\| 'Confirm Action', | Operational statement participating in the fi
L0553 |                 message: confirmMessage, | Operational statement participating in the file's runtime behavior.
L0554 |                 confirmLabel: form.getAttribute('data-confirm-label') \\| 'Yes', | Operational statement participating in the file's
L0555 |                 cancelLabel: form.getAttribute('data-cancel-label') \\| 'No', | Operational statement participating in the file's ru
L0556 |             }).then(function (confirmed) { | Block delimiter controlling scope/structure in this language.
L0557 |                 if (confirmed) { | Conditional branch that runs only when its condition is true.
L0558 |                     form.dataset.confirmedSubmit = '1'; | Assignment statement storing or updating program state.
L0559 |                     form.submit(); | Operational statement participating in the file's runtime behavior.
L0560 |                 } | Block delimiter controlling scope/structure in this language.
L0561 |             }); | Operational statement participating in the file's runtime behavior.
L0562 |             return; | Returns a value (or control) back to the caller.
L0563 |         } | Block delimiter controlling scope/structure in this language.
L0564 | | Blank line used for readability and logical separation.
L0565 |         if (form.hasAttribute('data-no-loader')) { | Conditional branch that runs only when its condition is true.
L0566 |             return; | Returns a value (or control) back to the caller.
L0567 |         } | Block delimiter controlling scope/structure in this language.
L0568 | | Blank line used for readability and logical separation.
L0569 |         setLoaderMessage('Loading...', 'Saving your changes. '); | Operational statement participating in the file's runtime behav
L0570 |         showLoader(); | Operational statement participating in the file's runtime behavior.
L0571 |     }); | Operational statement participating in the file's runtime behavior.
L0572 | | Blank line used for readability and logical separation.
L0573 |     document.addEventListener('click', function (event) { | Block delimiter controlling scope/structure in this language.
L0574 |         const backPill = event.target.closest('#pageBackPill'); | Assignment statement storing or updating program state.
L0575 |         if (backPill) { | Conditional branch that runs only when its condition is true.
L0576 |             event.preventDefault(); | Operational statement participating in the file's runtime behavior.
L0577 |             const fallbackUrl = backPill.getAttribute('data-fallback-url') \\| '/'; | Assignment statement storing or updating pro
L0578 |             const hasHistory = window.history.length > 1; | Assignment statement storing or updating program state.
L0579 |             const referrer = document.referrer \\| ' '; | Assignment statement storing or updating program state.
L0580 |             const sameOriginReferrer = referrer && referrer.indexOf(window.location.origin) === 0; | Operational statement particip
L0581 | | Blank line used for readability and logical separation.
L0582 |             if (hasHistory && sameOriginReferrer) { | Conditional branch that runs only when its condition is true.
L0583 |                 window.history.back(); | Operational statement participating in the file's runtime behavior.
L0584 |                 return; | Returns a value (or control) back to the caller.
L0585 |             } | Block delimiter controlling scope/structure in this language.
L0586 | | Blank line used for readability and logical separation.
L0587 |             window.location.href = fallbackUrl; | Assignment statement storing or updating program state.
L0588 |             return; | Returns a value (or control) back to the caller.
L0589 |         } | Block delimiter controlling scope/structure in this language.
L0590 | | Blank line used for readability and logical separation.
L0591 |         const link = event.target.closest('a[href]'); | Assignment statement storing or updating program state.
L0592 |         if (!link) { | Conditional branch that runs only when its condition is true.
L0593 |             return; | Returns a value (or control) back to the caller.
L0594 |         } | Block delimiter controlling scope/structure in this language.
L0595 |         if (link.hasAttribute('download') \\| link.target === '_blank') { | Conditional branch that runs only when its condition
L0596 |             return; | Returns a value (or control) back to the caller.
L0597 |         } | Block delimiter controlling scope/structure in this language.
L0598 |         if (event.metaKey \\| event.ctrlKey \\| event.shiftKey \\| event.altKey) { | Conditional branch that runs only when it
L0599 |             return; | Returns a value (or control) back to the caller.
L0600 |         } | Block delimiter controlling scope/structure in this language.
L0601 | | Blank line used for readability and logical separation.
L0602 |         const href = link.getAttribute('href') \\| ' '; | Assignment statement storing or updating program state.
L0603 |         if (!href \\| href.startsWith('#') \\| href.startsWith('javascript:')) { | Conditional branch that runs only when its c

```

```

L0604 |         return; | Returns a value (or control) back to the caller.
L0605 |     } | Block delimiter controlling scope/structure in this language.
L0606 | | Blank line used for readability and logical separation.
L0607 |         const destination = new URL(link.href, window.location.href); | Assignment statement storing or updating program state.
L0608 |         if (destination.origin !== window.location.origin) { | Conditional branch that runs only when its condition is true.
L0609 |             return; | Returns a value (or control) back to the caller.
L0610 |         } | Block delimiter controlling scope/structure in this language.
L0611 | | Blank line used for readability and logical separation.
L0612 |         setLoaderMessage('Loading...', 'Preparing your next screen.');
```

| Operational statement participating in the file's runtime behavior.

```

L0613 |         showLoader(); | Operational statement participating in the file's runtime behavior.
L0614 |     }); | Operational statement participating in the file's runtime behavior.
L0615 |     })(); | Operational statement participating in the file's runtime behavior.
L0616 | </script> | Markup line defining structure in an HTML-like template file.
L0617 | <script> | Markup line defining structure in an HTML-like template file.
L0618 |     (function () { | Block delimiter controlling scope/structure in this language.
L0619 |         /* ■■ i18n translation engine ■■ */ | Operational statement participating in the file's runtime behavior.
L0620 |         var LANG = '{ app_language }'; | Assignment statement storing or updating program state.
L0621 |         var T = { | Assignment statement storing or updating program state.
L0622 |             en: { | Block delimiter controlling scope/structure in this language.
L0623 |                 dashboard: 'Dashboard', site_form: 'Site Form', desk_review: 'Desk Review', | Operational statement participating in the file's runtime behavior.
L0624 |                 manage_accounts: 'Manage Accounts', notifications: 'Notifications', | Operational statement participating in the file's runtime behavior.
L0625 |                 settings: 'Settings', logout: 'Logout', settings_language: 'Language', | Operational statement participating in the file's runtime behavior.
L0626 |                 appearance: 'Appearance', dark_mode: 'Dark mode', apply_theme: 'Apply Theme', | Operational statement participating in the file's runtime behavior.
L0627 |                 choose_lang: 'Choose language' | Operational statement participating in the file's runtime behavior.
L0628 |             }, | Operational statement participating in the file's runtime behavior.
L0629 |             sw: { | Block delimiter controlling scope/structure in this language.
L0630 |                 dashboard: 'Dashibodi', site_form: 'Fomu ya Tovuti', desk_review: 'Ukaguzi wa Dawati', | Operational statement participating in the file's runtime behavior.
L0631 |                 manage_accounts: 'Simamia Akaunti', notifications: 'Arifa', | Operational statement participating in the file's runtime behavior.
L0632 |                 settings: 'Mipangilio', logout: 'Toka', settings_language: 'Lugha', | Operational statement participating in the file's runtime behavior.
L0633 |                 appearance: 'Mwonekano', dark_mode: 'Hali ya giza', apply_theme: 'Tumia Mandhari', | Operational statement participating in the file's runtime behavior.
L0634 |                 choose_lang: 'Chagua lugha' | Operational statement participating in the file's runtime behavior.
L0635 |             }, | Operational statement participating in the file's runtime behavior.
L0636 |             fr: { | Block delimiter controlling scope/structure in this language.
L0637 |                 dashboard: 'Tableau de bord', site_form: 'Formulaire de site', desk_review: 'Révision du bureau', | Operational statement participating in the file's runtime behavior.
L0638 |                 manage_accounts: 'Gérer les comptes', notifications: 'Notifications', | Operational statement participating in the file's runtime behavior.
L0639 |                 settings: 'Paramètres', logout: 'Déconnexion', settings_language: 'Langue', | Operational statement participating in the file's runtime behavior.
L0640 |                 appearance: 'Apparence', dark_mode: 'Mode sombre', apply_theme: 'Appliquer le thème', | Operational statement participating in the file's runtime behavior.
L0641 |                 choose_lang: 'Choisir la langue' | Operational statement participating in the file's runtime behavior.
L0642 |             }, | Operational statement participating in the file's runtime behavior.
L0643 |             ar: { | Block delimiter controlling scope/structure in this language.
L0644 |                 dashboard: '■■■■ ■■■■■', site_form: '■■■■ ■■■■■', desk_review: '■■■■ ■■■■■', | Operational statement participating in the file's runtime behavior.
L0645 |                 manage_accounts: '■■■■ ■■■■■', notifications: '■■■■■■■■', | Operational statement participating in the file's runtime behavior.
L0646 |                 settings: '■■■■■■■■', logout: '■■■■ ■■■■■', settings_language: '■■■■', | Operational statement participating in the file's runtime behavior.
L0647 |                 appearance: '■■■■■■', dark_mode: '■■■■ ■■■■■', apply_theme: '■■■■ ■■■■■', | Operational statement participating in the file's runtime behavior.
L0648 |                 choose_lang: '■■■■ ■■■■■' | Operational statement participating in the file's runtime behavior.
L0649 |             } | Block delimiter controlling scope/structure in this language.
L0650 |         }; | Operational statement participating in the file's runtime behavior.
L0651 |         function applyLang(lang) { | Block delimiter controlling scope/structure in this language.
L0652 |             var dict = T[lang] || T['en']; | Assignment statement storing or updating program state.
L0653 |             document.querySelectorAll('[data-i18n]').forEach(function (el) { | Block delimiter controlling scope/structure in this language.
L0654 |                 var key = el.getAttribute('data-i18n'); | Assignment statement storing or updating program state.
L0655 |                 if (dict[key]) { el.textContent = dict[key]; } | Conditional branch that runs only when its condition is true.
L0656 |             }); | Operational statement participating in the file's runtime behavior.
L0657 |             document.documentElement.setAttribute('dir', lang === 'ar' ? 'rtl' : 'ltr'); | Operational statement participating in the file's runtime behavior.
L0658 |             document.documentElement.setAttribute('lang', lang); | Operational statement participating in the file's runtime behavior.

```

```

L0659 |         } | Block delimiter controlling scope/structure in this language.
L0660 |         applyLang(LANG); | Operational statement participating in the file's runtime behavior.
L0661 |     }()); | Operational statement participating in the file's runtime behavior.
L0662 | </script> | Markup line defining structure in an HTML-like template file.
L0663 | <script> | Markup line defining structure in an HTML-like template file.
L0664 |     (function () { | Block delimiter controlling scope/structure in this language.
L0665 |         const holidayDataNode = document.getElementById('publicHolidayData'); | Assignment statement storing or updating program state.
L0666 |         const holidays = holidayDataNode ? JSON.parse(holidayDataNode.textContent) : []; | Assignment statement storing or updating program state.
L0667 |         const holidayMap = new Map(holidays.map((item) => [item.date, item.name])); | Assignment statement storing or updating program state.
L0668 | | Blank line used for readability and logical separation.
L0669 |         function pad(value) { | Block delimiter controlling scope/structure in this language.
L0670 |             return String(value).padStart(2, '0'); | Returns a value (or control) back to the caller.
L0671 |         } | Block delimiter controlling scope/structure in this language.
L0672 | | Blank line used for readability and logical separation.
L0673 |         function isoDate(date) { | Block delimiter controlling scope/structure in this language.
L0674 |             return [date.getFullYear(), pad(date.getMonth() + 1), pad(date.getDate())].join('-'); | Returns a value (or control) back to the caller.
L0675 |         } | Block delimiter controlling scope/structure in this language.
L0676 | | Blank line used for readability and logical separation.
L0677 |         function toOrdinal(dayNumber) { | Block delimiter controlling scope/structure in this language.
L0678 |             const n = Number(dayNumber); | Assignment statement storing or updating program state.
L0679 |             const mod10 = n % 10; | Assignment statement storing or updating program state.
L0680 |             const mod100 = n % 100; | Assignment statement storing or updating program state.
L0681 |             if (mod10 === 1 && mod100 !== 11) { | Conditional branch that runs only when its condition is true.
L0682 |                 return `${n}st`; | Returns a value (or control) back to the caller.
L0683 |             } | Block delimiter controlling scope/structure in this language.
L0684 |             if (mod10 === 2 && mod100 !== 12) { | Conditional branch that runs only when its condition is true.
L0685 |                 return `${n}nd`; | Returns a value (or control) back to the caller.
L0686 |             } | Block delimiter controlling scope/structure in this language.
L0687 |             if (mod10 === 3 && mod100 !== 13) { | Conditional branch that runs only when its condition is true.
L0688 |                 return `${n}rd`; | Returns a value (or control) back to the caller.
L0689 |             } | Block delimiter controlling scope/structure in this language.
L0690 |             return `${n}th`; | Returns a value (or control) back to the caller.
L0691 |         } | Block delimiter controlling scope/structure in this language.
L0692 | | Blank line used for readability and logical separation.
L0693 |         function renderHolidayCalendar(container, baseDate, direction) { | Block delimiter controlling scope/structure in this language.
L0694 |             const title = container.querySelector('.calendar-month-label'); | Assignment statement storing or updating program state.
L0695 |             const grid = container.querySelector('.calendar-grid'); | Assignment statement storing or updating program state.
L0696 |             const holidayList = container.querySelector('.calendar-holiday-list'); | Assignment statement storing or updating program state.
L0697 |             const sheet = container.querySelector('.calendar-sheet'); | Assignment statement storing or updating program state.
L0698 |             if (!title || !grid || !holidayList || !sheet) { | Conditional branch that runs only when its condition is true.
L0699 |                 return; | Returns a value (or control) back to the caller.
L0700 |             } | Block delimiter controlling scope/structure in this language.
L0701 | | Blank line used for readability and logical separation.
L0702 |             const monthDate = new Date(baseDate.getFullYear(), baseDate.getMonth(), 1); | Assignment statement storing or updating program state.
L0703 |             const monthName = monthDate.toLocaleString('default', { month: 'long' }); | Assignment statement storing or updating program state.
L0704 |             const year = monthDate.getFullYear(); | Assignment statement storing or updating program state.
L0705 |             const firstDay = new Date(year, monthDate.getMonth(), 1); | Assignment statement storing or updating program state.
L0706 |             const lastDay = new Date(year, monthDate.getMonth() + 1, 0); | Assignment statement storing or updating program state.
L0707 |             const startOffset = firstDay.getDay(); | Assignment statement storing or updating program state.
L0708 |             const totalDays = lastDay.getDate(); | Assignment statement storing or updating program state.
L0709 |             const monthKey = `${year}-${pad(monthDate.getMonth() + 1)}`; | Assignment statement storing or updating program state.
L0710 |             const monthHolidays = holidays | Assignment statement storing or updating program state.
L0711 |                 .filter((item) => item.date.startsWith(monthKey)) | Assignment statement storing or updating program state.
L0712 |                 .sort((a, b) => a.date.localeCompare(b.date)); | Assignment statement storing or updating program state.
L0713 |             const todayKey = isoDate(new Date()); | Assignment statement storing or updating program state.

```

```

L0714 | | Blank line used for readability and logical separation.
L0715 |         title.textContent = `${monthName} ${year}`; | Assignment statement storing or updating program state.
L0716 |         grid.innerHTML = ''; | Assignment statement storing or updating program state.
L0717 |         ['Sun', 'Mon', 'Tue', 'Wed', 'Thu', 'Fri', 'Sat'].forEach((day) => { | Assignment statement storing or updating program state.
L0718 |             const cell = document.createElement('div'); | Assignment statement storing or updating program state.
L0719 |             cell.className = 'calendar-cell calendar-day'; | Assignment statement storing or updating program state.
L0720 |             cell.textContent = day; | Assignment statement storing or updating program state.
L0721 |             grid.appendChild(cell); | Operational statement participating in the file's runtime behavior.
L0722 |         }); | Operational statement participating in the file's runtime behavior.
L0723 | | Blank line used for readability and logical separation.
L0724 |         for (let i = 0; i < startOffset; i += 1) { | Loop iterating over a sequence to process elements one by one.
L0725 |             const cell = document.createElement('div'); | Assignment statement storing or updating program state.
L0726 |             cell.className = 'calendar-cell calendar-empty'; | Assignment statement storing or updating program state.
L0727 |             grid.appendChild(cell); | Operational statement participating in the file's runtime behavior.
L0728 |         } | Block delimiter controlling scope/structure in this language.
L0729 | | Blank line used for readability and logical separation.
L0730 |         for (let day = 1; day <= totalDays; day += 1) { | Loop iterating over a sequence to process elements one by one.
L0731 |             const current = new Date(year, monthDate.getMonth(), day); | Assignment statement storing or updating program state.
L0732 |             const key = isoDate(current); | Assignment statement storing or updating program state.
L0733 |             const cell = document.createElement('div'); | Assignment statement storing or updating program state.
L0734 |             cell.className = 'calendar-cell calendar-date'; | Assignment statement storing or updating program state.
L0735 |             if (holidayMap.has(key)) { | Conditional branch that runs only when its condition is true.
L0736 |                 cell.classList.add('calendar-holiday'); | Operational statement participating in the file's runtime behavior.
L0737 |                 cell.title = holidayMap.get(key); | Assignment statement storing or updating program state.
L0738 |             } | Block delimiter controlling scope/structure in this language.
L0739 |             if (key === todayKey) { | Conditional branch that runs only when its condition is true.
L0740 |                 cell.classList.add('calendar-today'); | Operational statement participating in the file's runtime behavior.
L0741 |             } | Block delimiter controlling scope/structure in this language.
L0742 | | Blank line used for readability and logical separation.
L0743 |             const number = document.createElement('div'); | Assignment statement storing or updating program state.
L0744 |             number.className = 'calendar-date-number'; | Assignment statement storing or updating program state.
L0745 |             number.textContent = day; | Assignment statement storing or updating program state.
L0746 |             cell.appendChild(number); | Operational statement participating in the file's runtime behavior.
L0747 | | Blank line used for readability and logical separation.
L0748 |             grid.appendChild(cell); | Operational statement participating in the file's runtime behavior.
L0749 |         } | Block delimiter controlling scope/structure in this language.
L0750 | | Blank line used for readability and logical separation.
L0751 |         holidayList.innerHTML = monthHolidays.length | Assignment statement storing or updating program state.
L0752 |         ? monthHolidays | Operational statement participating in the file's runtime behavior.
L0753 |         .map((item) => { | Assignment statement storing or updating program state.
L0754 |             const parts = item.date.split('-'); | Assignment statement storing or updating program state.
L0755 |             const dayOrdinal = toOrdinal(parts[2]); | Assignment statement storing or updating program state.
L0756 |             return `<div class="holiday-list-item"><span class="holiday-day">${dayOrdinal}</span><span class="holiday-dash">-</span></div>`; | Operational statement participating in the file's runtime behavior.
L0757 |         }) | Operational statement participating in the file's runtime behavior.
L0758 |         .join('') | CSS selector line choosing the elements styled below.
L0759 |         : '<div class="holiday-list-item"><span>No public holiday</span><strong>This month has no listed public holiday.</strong></div>'; | Operational statement participating in the file's runtime behavior.
L0760 | | Blank line used for readability and logical separation.
L0761 |         sheet.classList.remove('turn-next', 'turn-prev'); | Operational statement participating in the file's runtime behavior.
L0762 |         void sheet.offsetWidth; | Operational statement participating in the file's runtime behavior.
L0763 |         if (direction === 'next') { | Conditional branch that runs only when its condition is true.
L0764 |             sheet.classList.add('turn-next'); | Operational statement participating in the file's runtime behavior.
L0765 |         } else if (direction === 'prev') { | Block delimiter controlling scope/structure in this language.
L0766 |             sheet.classList.add('turn-prev'); | Operational statement participating in the file's runtime behavior.
L0767 |         } | Block delimiter controlling scope/structure in this language.
L0768 |     } | Block delimiter controlling scope/structure in this language.

```

```

L0769 | | Blank line used for readability and logical separation.
L0770 |         function setupCalendar(container) { | Block delimiter controlling scope/structure in this language.
L0771 |             const initial = new Date(); | Assignment statement storing or updating program state.
L0772 |             container._calendarDate = new Date(initial.getFullYear(), initial.getMonth(), 1); | Assignment statement storing or updating program state.
L0773 | | Blank line used for readability and logical separation.
L0774 |             const prev = container.querySelector('.calendar-nav-prev'); | Assignment statement storing or updating program state.
L0775 |             const next = container.querySelector('.calendar-nav-next'); | Assignment statement storing or updating program state.
L0776 |             const book = container.querySelector('.calendar-book'); | Assignment statement storing or updating program state.
L0777 | | Blank line used for readability and logical separation.
L0778 |             renderHolidayCalendar(container, container._calendarDate); | Operational statement participating in the file's runtime behavior.
L0779 | | Blank line used for readability and logical separation.
L0780 |             if (prev) { | Conditional branch that runs only when its condition is true.
L0781 |                 prev.addEventListener('click', function () { | Block delimiter controlling scope/structure in this language.
L0782 |                     container._calendarDate.setMonth(container._calendarDate.getMonth() - 1); | Operational statement participating in the file's runtime behavior.
L0783 |                     renderHolidayCalendar(container, container._calendarDate, 'prev'); | Operational statement participating in the file's runtime behavior.
L0784 |                 }); | Operational statement participating in the file's runtime behavior.
L0785 |             } | Block delimiter controlling scope/structure in this language.
L0786 | | Blank line used for readability and logical separation.
L0787 |             if (next) { | Conditional branch that runs only when its condition is true.
L0788 |                 next.addEventListener('click', function () { | Block delimiter controlling scope/structure in this language.
L0789 |                     container._calendarDate.setMonth(container._calendarDate.getMonth() + 1); | Operational statement participating in the file's runtime behavior.
L0790 |                     renderHolidayCalendar(container, container._calendarDate, 'next'); | Operational statement participating in the file's runtime behavior.
L0791 |                 }); | Operational statement participating in the file's runtime behavior.
L0792 |             } | Block delimiter controlling scope/structure in this language.
L0793 | | Blank line used for readability and logical separation.
L0794 |             if (book) { | Conditional branch that runs only when its condition is true.
L0795 |                 let touchStartX = 0; | Assignment statement storing or updating program state.
L0796 |                 book.addEventListener('touchstart', function (event) { | Block delimiter controlling scope/structure in this language.
L0797 |                     touchStartX = event.changedTouches[0].clientX; | Assignment statement storing or updating program state.
L0798 |                 }, { passive: true }); | Operational statement participating in the file's runtime behavior.
L0799 |                 book.addEventListener('touchend', function (event) { | Block delimiter controlling scope/structure in this language.
L0800 |                     const delta = event.changedTouches[0].clientX - touchStartX; | Assignment statement storing or updating program state.
L0801 |                     if (Math.abs(delta) < 40) { | Conditional branch that runs only when its condition is true.
L0802 |                         return; | Returns a value (or control) back to the caller.
L0803 |                     } | Block delimiter controlling scope/structure in this language.
L0804 |                     container._calendarDate.setMonth(container._calendarDate.getMonth() + (delta < 0 ? 1 : -1)); | Operational statement participating in the file's runtime behavior.
L0805 |                     renderHolidayCalendar(container, container._calendarDate, delta < 0 ? 'next' : 'prev'); | Operational statement participating in the file's runtime behavior.
L0806 |                 }, { passive: true }); | Operational statement participating in the file's runtime behavior.
L0807 |             } | Block delimiter controlling scope/structure in this language.
L0808 |         } | Block delimiter controlling scope/structure in this language.
L0809 | | Blank line used for readability and logical separation.
L0810 |         document.querySelectorAll('.holiday-calendar').forEach(setupCalendar); | Operational statement participating in the file's runtime behavior.
L0811 | | Blank line used for readability and logical separation.
L0812 |         const today = isoDate(new Date()); | Assignment statement storing or updating program state.
L0813 |         const holidayName = holidayMap.get(today); | Assignment statement storing or updating program state.
L0814 |         const popupKey = `holiday-popup-${today}`; | Assignment statement storing or updating program state.
L0815 |         const backdrop = document.getElementById('holidayPopupBackdrop'); | Assignment statement storing or updating program state.
L0816 |         const closeBtn = document.getElementById('holidayPopupClose'); | Assignment statement storing or updating program state.
L0817 |         const text = document.getElementById('holidayPopupText'); | Assignment statement storing or updating program state.
L0818 | | Blank line used for readability and logical separation.
L0819 |         function closePopup() { | Block delimiter controlling scope/structure in this language.
L0820 |             if (backdrop) { | Conditional branch that runs only when its condition is true.
L0821 |                 backdrop.hidden = true; | Assignment statement storing or updating program state.
L0822 |                 backdrop.classList.remove('show'); | Operational statement participating in the file's runtime behavior.
L0823 |             } | Block delimiter controlling scope/structure in this language.

```

L0824 | } | Block delimiter controlling scope/structure in this language.

L0825 | | Blank line used for readability and logical separation.

L0826 | if (holidayName && backdrop && text && !localStorage.getItem(popupKey)) { | Conditional branch that runs only when its condition is true.

L0827 | text.textContent = `\${holidayName} is today (\${today}).`; | Assignment statement storing or updating program state.

L0828 | backdrop.hidden = false; | Assignment statement storing or updating program state.

L0829 | backdrop.classList.add('show'); | Operational statement participating in the file's runtime behavior.

L0830 | localStorage.setItem(popupKey, 'shown'); | Operational statement participating in the file's runtime behavior.

L0831 | } | Block delimiter controlling scope/structure in this language.

L0832 | | Blank line used for readability and logical separation.

L0833 | if (closeBtn) { | Conditional branch that runs only when its condition is true.

L0834 | closeBtn.addEventListener('click', closePopup); | Operational statement participating in the file's runtime behavior.

L0835 | } | Block delimiter controlling scope/structure in this language.

L0836 | if (backdrop) { | Conditional branch that runs only when its condition is true.

L0837 | backdrop.addEventListener('click', function (event) { | Block delimiter controlling scope/structure in this language.

L0838 | if (event.target === backdrop) { | Conditional branch that runs only when its condition is true.

L0839 | closePopup(); | Operational statement participating in the file's runtime behavior.

L0840 | } | Block delimiter controlling scope/structure in this language.

L0841 | }); | Operational statement participating in the file's runtime behavior.

L0842 | } | Block delimiter controlling scope/structure in this language.

L0843 | })(); | Operational statement participating in the file's runtime behavior.

L0844 | </script> | Markup line defining structure in an HTML-like template file.

L0845 | </body> | Markup line defining structure in an HTML-like template file.

L0846 | </html> | Markup line defining structure in an HTML-like template file.

File 108: templates/login.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <section class="login-page"> | Assignment statement storing or updating program state.
L0004 |     <div class="login-card shadow-sm px-4 py-4"> | Assignment statement storing or updating program state.
L0005 |         <div class="login-brand"> | Assignment statement storing or updating program state.
L0006 |              | Assignment statement storing or updating program state.
L0007 |             <h1>Welcome Back</h1> | Markup line defining structure in an HTML-like template file.
L0008 |         </div> | Markup line defining structure in an HTML-like template file.
L0009 | | Blank line used for readability and logical separation.
L0010 |         {% with messages = get_flashed_messages(with_categories=true) %} | Assignment statement storing or updating program state.
L0011 |             {% if messages %} | Block delimiter controlling scope/structure in this language.
L0012 |                 {% for category, msg in messages %} | Block delimiter controlling scope/structure in this language.
L0013 |                     <div class="alert alert-{{ category }}">{{ msg }}</div> | Assignment statement storing or updating program state.
L0014 |                 {% endfor %} | Block delimiter controlling scope/structure in this language.
L0015 |             {% endif %} | Block delimiter controlling scope/structure in this language.
L0016 |         {% endwith %} | Block delimiter controlling scope/structure in this language.
L0017 | | Blank line used for readability and logical separation.
L0018 |         <form method="POST" action="{{ url_for('login', role=preselected_role) if preselected_role else url_for('login') }}"> | Assignment statement storing or updating program state.
L0019 |             <input type="hidden" name="login_csrf_token" value="{{ login_csrf_token }}" /> | Assignment statement storing or updating program state.
L0020 |             <div class="mb-3"> | Assignment statement storing or updating program state.
L0021 |                 <label for="email" class="form-label">Email</label> | Assignment statement storing or updating program state.
L0022 |                 <input type="email" class="form-control" id="email" name="email" autocomplete="email" required /> | Assignment statement storing or updating program state.
L0023 |             </div> | Markup line defining structure in an HTML-like template file.
L0024 |             <div class="mb-3 position-relative"> | Assignment statement storing or updating program state.
L0025 |                 <label for="password" class="form-label">Password</label> | Assignment statement storing or updating program state.
L0026 |                 <input type="password" class="form-control" id="password" name="password" autocomplete="current-password" required /> | Assignment statement storing or updating program state.
L0027 |                 <i class="bi bi-eye-slash position-absolute" id="togglePassword" style="top: 50%; right: 10px; cursor: pointer;"></i> | Assignment statement storing or updating program state.
L0028 |             </div> | Markup line defining structure in an HTML-like template file.
L0029 |             <div class="mb-3 role-select-wrap"> | Assignment statement storing or updating program state.
L0030 |                 <label class="form-label">Account Type</label> | Assignment statement storing or updating program state.
L0031 | | Blank line used for readability and logical separation.
L0032 |                 <!-- Pill row (JS-enhanced) --> | Markup line defining structure in an HTML-like template file.
L0033 |                 <div class="role-pill-row" id="rolePillRow" role="group" aria-label="Account type"> | Assignment statement storing or updating program state.
L0034 |                     <button type="button" class="role-pill" data-role="technician"> | Assignment statement storing or updating program state.
L0035 |                         <i class="bi bi-wrench-adjustable-circle-fill"></i> | Assignment statement storing or updating program state.
L0036 |                         <span>Technician</span> | Markup line defining structure in an HTML-like template file.
L0037 |                     </button> | Markup line defining structure in an HTML-like template file.
L0038 |                     <button type="button" class="role-pill" data-role="staff"> | Assignment statement storing or updating program state.
L0039 |                         <i class="bi bi-person-workspace"></i> | Assignment statement storing or updating program state.
L0040 |                         <span>Staff</span> | Markup line defining structure in an HTML-like template file.
L0041 |                     </button> | Markup line defining structure in an HTML-like template file.
L0042 |                     <button type="button" class="role-pill" data-role="manager"> | Assignment statement storing or updating program state.
L0043 |                         <i class="bi bi-briefcase-fill"></i> | Assignment statement storing or updating program state.
L0044 |                         <span>Manager</span> | Markup line defining structure in an HTML-like template file.
L0045 |                     </button> | Markup line defining structure in an HTML-like template file.
L0046 |                     <button type="button" class="role-pill" data-role="general_manager"> | Assignment statement storing or updating program state.
L0047 |                         <i class="bi bi-clipboard2-check-fill"></i> | Assignment statement storing or updating program state.
L0048 |                         <span>Gen. Manager</span> | Markup line defining structure in an HTML-like template file.
L0049 |                     </button> | Markup line defining structure in an HTML-like template file.
L0050 |                     <button type="button" class="role-pill" data-role="developer"> | Assignment statement storing or updating program state.
L0051 |                         <i class="bi bi-code-slash"></i> | Assignment statement storing or updating program state.
L0052 |                         <span>Developer</span> | Markup line defining structure in an HTML-like template file.
L0053 |                     </button> | Markup line defining structure in an HTML-like template file.
```

```
L0054 |         </div> | Markup line defining structure in an HTML-like template file.
L0055 | | Blank line used for readability and logical separation.
L0056 |         <!-- Hidden input carries the selected value --> | Markup line defining structure in an HTML-like template file.
L0057 |         <input type="hidden" name="account_type" id="accountTypeHidden" | Assignment statement storing or updating program state.
L0058 |             value="{ { preselected_role if preselected_role else 'technician' } }" /> | Assignment statement storing or updating program state.
L0059 | | Blank line used for readability and logical separation.
L0060 |         <!-- Native <select> fallback (hidden when JS runs) --> | Markup line defining structure in an HTML-like template file.
L0061 |         <select class="form-select mt-2 d-none" id="accountType" name="account_type_fallback" | Assignment statement storing or updating program state.
L0062 |             aria-label="Account type fallback" {% if preselected_role == 'technician' %}disabled{% endif %}> | Operational statement participating in the file's runtime behavior.
L0063 |             <option value="developer" {% if preselected_role == 'developer' %}selected{% endif %}>Developer</option> | Markup line defining structure in an HTML-like template file.
L0064 |             <option value="staff" {% if preselected_role == 'staff' %}selected{% endif %}>Staff</option> | Markup line defining structure in an HTML-like template file.
L0065 |             <option value="manager" {% if preselected_role == 'manager' %}selected{% endif %}>Manager</option> | Markup line defining structure in an HTML-like template file.
L0066 |             <option value="general_manager" {% if preselected_role == 'general_manager' %}selected{% endif %}>General Manager</option> | Markup line defining structure in an HTML-like template file.
L0067 |             <option value="technician" {% if preselected_role == 'technician' %}selected{% endif %}>Technician</option> | Markup line defining structure in an HTML-like template file.
L0068 |         </select> | Markup line defining structure in an HTML-like template file.
L0069 | | Blank line used for readability and logical separation.
L0070 |         <div class="login-role-preview" id="loginRolePreview" aria-live="polite"> | Assignment statement storing or updating program state.
L0071 |             <span class="login-role-icon" id="loginRoleIcon"><i class="bi bi-wrench-adjustable-circle-fill"></i></span> | Assignment statement storing or updating program state.
L0072 |             <div class="login-role-copy"> | Assignment statement storing or updating program state.
L0073 |                 <strong id="loginRoleTitle">Technician Access</strong> | Assignment statement storing or updating program state.
L0074 |                 <small id="loginRoleHint">Field PM/RCA submission workspace</small> | Assignment statement storing or updating program state.
L0075 |             </div> | Markup line defining structure in an HTML-like template file.
L0076 |         </div> | Markup line defining structure in an HTML-like template file.
L0077 | | Blank line used for readability and logical separation.
L0078 |         {% if preselected_role %} | Block delimiter controlling scope/structure in this language.
L0079 |             <div class="form-text mt-2"><i class="bi bi-shield-lock-fill"></i> Role is locked for this login link.</div> | Assignment statement storing or updating program state.
L0080 |         {% endif %} | Block delimiter controlling scope/structure in this language.
L0081 |     </div> | Markup line defining structure in an HTML-like template file.
L0082 |     <button type="submit" class="btn btn-primary w-100">Login</button> | Assignment statement storing or updating program state.
L0083 | </form> | Markup line defining structure in an HTML-like template file.
L0084 | | Blank line used for readability and logical separation.
L0085 |     <p class="text-muted mt-3">Need help? Developer creates staff, manager, general manager, and technician accounts from the admin page.</p>
L0086 | </div> | Markup line defining structure in an HTML-like template file.
L0087 | </section> | Markup line defining structure in an HTML-like template file.
L0088 | | Blank line used for readability and logical separation.
L0089 | <script> | Markup line defining structure in an HTML-like template file.
L0090 |     const togglePassword = document.querySelector("#togglePassword"); | Assignment statement storing or updating program state.
L0091 |     const passwordField = document.querySelector("#password"); | Assignment statement storing or updating program state.
L0092 |     const roleIcon = document.querySelector("#loginRoleIcon"); | Assignment statement storing or updating program state.
L0093 |     const roleTitle = document.querySelector("#loginRoleTitle"); | Assignment statement storing or updating program state.
L0094 |     const roleHint = document.querySelector("#loginRoleHint"); | Assignment statement storing or updating program state.
L0095 |     const rolePreview = document.querySelector("#loginRolePreview"); | Assignment statement storing or updating program state.
L0096 |     const roleHiddenInput = document.querySelector("#accountTypeHidden"); | Assignment statement storing or updating program state.
L0097 |     const pillRow = document.querySelector("#rolePillRow"); | Assignment statement storing or updating program state.
L0098 | | Blank line used for readability and logical separation.
L0099 |     const roleConfig = { | Assignment statement storing or updating program state.
L0100 |         technician: { | Block delimiter controlling scope/structure in this language.
L0101 |             icon: "bi-wrench-adjustable-circle-fill", | Operational statement participating in the file's runtime behavior.
L0102 |             title: "Technician Access", | Operational statement participating in the file's runtime behavior.
L0103 |             hint: "Field PM/RCA submission workspace", | Operational statement participating in the file's runtime behavior.
L0104 |             cssClass: "role-technician" | Operational statement participating in the file's runtime behavior.
L0105 |         }, | Operational statement participating in the file's runtime behavior.
L0106 |         staff: { | Block delimiter controlling scope/structure in this language.
L0107 |             icon: "bi-person-workspace", | Operational statement participating in the file's runtime behavior.
L0108 |             title: "Staff Access", | Operational statement participating in the file's runtime behavior.
```



```

L0109 |         hint: "Desk review and coordination workspace", | Operational statement participating in the file's runtime behavior.
L0110 |         cssClass: "role-staff" | Operational statement participating in the file's runtime behavior.
L0111 |     }, | Operational statement participating in the file's runtime behavior.
L0112 |     manager: { | Block delimiter controlling scope/structure in this language.
L0113 |         icon: "bi-briefcase-fill", | Operational statement participating in the file's runtime behavior.
L0114 |         title: "Manager Access", | Operational statement participating in the file's runtime behavior.
L0115 |         hint: "Regional operations and approvals workspace", | Operational statement participating in the file's runtime behavior.
L0116 |         cssClass: "role-manager" | Operational statement participating in the file's runtime behavior.
L0117 |     }, | Operational statement participating in the file's runtime behavior.
L0118 |     general_manager: { | Block delimiter controlling scope/structure in this language.
L0119 |         icon: "bi-clipboard2-check-fill", | Operational statement participating in the file's runtime behavior.
L0120 |         title: "General Manager Access", | Operational statement participating in the file's runtime behavior.
L0121 |         hint: "Executive oversight and system-wide reporting", | Operational statement participating in the file's runtime behavior.
L0122 |         cssClass: "role-general-manager" | Operational statement participating in the file's runtime behavior.
L0123 |     }, | Operational statement participating in the file's runtime behavior.
L0124 |     developer: { | Block delimiter controlling scope/structure in this language.
L0125 |         icon: "bi-code-slash", | Operational statement participating in the file's runtime behavior.
L0126 |         title: "Developer Access", | Operational statement participating in the file's runtime behavior.
L0127 |         hint: "System administration and account management", | Operational statement participating in the file's runtime behavior.
L0128 |         cssClass: "role-developer" | Operational statement participating in the file's runtime behavior.
L0129 |     } | Block delimiter controlling scope/structure in this language.
L0130 | }; | Operational statement participating in the file's runtime behavior.
L0131 | | Blank line used for readability and logical separation.
L0132 | function applyRolePreview(role) { | Block delimiter controlling scope/structure in this language.
L0133 |     if (!roleIcon || !roleTitle || !roleHint || !rolePreview) return; | Conditional branch that runs only when its condition is true.
L0134 |     const config = roleConfig[role] || roleConfig.technician; | Assignment statement storing or updating program state.
L0135 |     rolePreview.classList.remove("role-technician", "role-staff", "role-manager", "role-general-manager", "role-developer"); | Operational statement participating in the file's runtime behavior.
L0136 |     rolePreview.classList.add(config.cssClass); | Operational statement participating in the file's runtime behavior.
L0137 |     roleIcon.innerHTML = '<i class="bi ' + config.icon + '"></i>'; | Assignment statement storing or updating program state.
L0138 |     roleTitle.textContent = config.title; | Assignment statement storing or updating program state.
L0139 |     roleHint.textContent = config.hint; | Assignment statement storing or updating program state.
L0140 | } | Block delimiter controlling scope/structure in this language.
L0141 | | Blank line used for readability and logical separation.
L0142 | function activatePill(role) { | Block delimiter controlling scope/structure in this language.
L0143 |     if (!pillRow) return; | Conditional branch that runs only when its condition is true.
L0144 |     pillRow.querySelectorAll(".role-pill").forEach(function (btn) { | Block delimiter controlling scope/structure in this language.
L0145 |         const active = btn.dataset.role === role; | Operational statement participating in the file's runtime behavior.
L0146 |         btn.classList.toggle("is-active", active); | Operational statement participating in the file's runtime behavior.
L0147 |         btn.setAttribute("aria-pressed", active ? "true" : "false"); | Operational statement participating in the file's runtime behavior.
L0148 |     }); | Operational statement participating in the file's runtime behavior.
L0149 | } | Block delimiter controlling scope/structure in this language.
L0150 | | Blank line used for readability and logical separation.
L0151 | const lockedRole = {('' + preselected_role + '') || safe if preselected_role else 'null' }; | Assignment statement storing or updating program state.
L0152 | | Blank line used for readability and logical separation.
L0153 | if (pillRow) { | Conditional branch that runs only when its condition is true.
L0154 |     // If role is locked, disable all pills except the locked one | Operational statement participating in the file's runtime behavior.
L0155 |     if (lockedRole) { | Conditional branch that runs only when its condition is true.
L0156 |         pillRow.querySelectorAll(".role-pill").forEach(function (btn) { | Block delimiter controlling scope/structure in this language.
L0157 |             if (btn.dataset.role !== lockedRole) { | Conditional branch that runs only when its condition is true.
L0158 |                 btn.disabled = true; | Assignment statement storing or updating program state.
L0159 |                 btn.setAttribute("aria-disabled", "true"); | Operational statement participating in the file's runtime behavior.
L0160 |             } | Block delimiter controlling scope/structure in this language.
L0161 |         }); | Operational statement participating in the file's runtime behavior.
L0162 |     } | Block delimiter controlling scope/structure in this language.
L0163 | | Blank line used for readability and logical separation.

```

```

L0164 | pillRow.querySelectorAll(".role-pill").forEach(function (btn) { | Block delimiter controlling scope/structure in this language.
L0165 |     btn.addEventListener("click", function () { | Block delimiter controlling scope/structure in this language.
L0166 |         if (lockedRole) return; | Conditional branch that runs only when its condition is true.
L0167 |         const role = btn.dataset.role; | Assignment statement storing or updating program state.
L0168 |         if (roleHiddenInput) roleHiddenInput.value = role; | Conditional branch that runs only when its condition is true.
L0169 |         activatePill(role); | Operational statement participating in the file's runtime behavior.
L0170 |         applyRolePreview(role); | Operational statement participating in the file's runtime behavior.
L0171 |     }); | Operational statement participating in the file's runtime behavior.
L0172 | }); | Operational statement participating in the file's runtime behavior.
L0173 | } | Block delimiter controlling scope/structure in this language.
L0174 | | Blank line used for readability and logical separation.
L0175 | // Initialise with current value | Operational statement participating in the file's runtime behavior.
L0176 | const initialRole = (roleHiddenInput && roleHiddenInput.value) ? roleHiddenInput.value : "technician"; | Assignment statement s
L0177 | activatePill(initialRole); | Operational statement participating in the file's runtime behavior.
L0178 | applyRolePreview(initialRole); | Operational statement participating in the file's runtime behavior.
L0179 | | Blank line used for readability and logical separation.
L0180 | if (togglePassword && passwordField) { | Conditional branch that runs only when its condition is true.
L0181 |     togglePassword.addEventListener("click", function () { | Block delimiter controlling scope/structure in this language.
L0182 |         const type = passwordField.getAttribute("type") === "password" ? "text" : "password"; | Operational statement participating
L0183 |         passwordField.setAttribute("type", type); | Operational statement participating in the file's runtime behavior.
L0184 |         this.classList.toggle("bi-eye"); | Operational statement participating in the file's runtime behavior.
L0185 |         this.classList.toggle("bi-eye-slash"); | Operational statement participating in the file's runtime behavior.
L0186 |     }); | Operational statement participating in the file's runtime behavior.
L0187 | } | Block delimiter controlling scope/structure in this language.
L0188 | </script> | Markup line defining structure in an HTML-like template file.
L0189 | {% endblock %} | Block delimiter controlling scope/structure in this language.

```

File 109: templates/manager_dashboard.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <div class="role-dashboard-shell role-manager"> | Assignment statement storing or updating program state.
L0004 | <section class="dashboard-hero-lite"> | Assignment statement storing or updating program state.
L0005 |   <h1>Hello, {{ user_name }}. Welcome back!</h1> | Markup line defining structure in an HTML-like template file.
L0006 | </section> | Markup line defining structure in an HTML-like template file.
L0007 | | Blank line used for readability and logical separation.
L0008 | <div class="row row-cols-1 row-cols-md-3 g-3 mt-1"> | Assignment statement storing or updating program state.
L0009 |   <div class="col"> | Assignment statement storing or updating program state.
L0010 |     <a href="{{ url_for('desk_activities', mode='rcas') }}" class="card-link"> | Assignment statement storing or updating program state.
L0011 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0012 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0013 |           <div class="stats-icon"><i class="bi bi-journal-check"></i></div> | Assignment statement storing or updating program state.
L0014 |           <h1>{{ pending_pm_rcas }}</h1> | Markup line defining structure in an HTML-like template file.
L0015 |           <p>PM RCAs To Review</p> | Markup line defining structure in an HTML-like template file.
L0016 |         </div> | Markup line defining structure in an HTML-like template file.
L0017 |       </div> | Markup line defining structure in an HTML-like template file.
L0018 |     </a> | Markup line defining structure in an HTML-like template file.
L0019 |   </div> | Markup line defining structure in an HTML-like template file.
L0020 |   <div class="col"> | Assignment statement storing or updating program state.
L0021 |     <a href="{{ url_for('desk_activities', mode='forms') }}" class="card-link"> | Assignment statement storing or updating program state.
L0022 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0023 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0024 |           <div class="stats-icon"><i class="bi bi-file-earmark-pdf"></i></div> | Assignment statement storing or updating program state.
L0025 |           <h1>{{ pending_pm_rcas + approved_pm_forms + rejected_pm_rcas }}</h1> | Markup line defining structure in an HTML-like template file.
L0026 |           <p>Total PM Forms</p> | Markup line defining structure in an HTML-like template file.
L0027 |         </div> | Markup line defining structure in an HTML-like template file.
L0028 |       </div> | Markup line defining structure in an HTML-like template file.
L0029 |     </a> | Markup line defining structure in an HTML-like template file.
L0030 |   </div> | Markup line defining structure in an HTML-like template file.
L0031 |   <div class="col"> | Assignment statement storing or updating program state.
L0032 |     <a href="{{ url_for('desk_activities', mode='rejected') }}" class="card-link"> | Assignment statement storing or updating program state.
L0033 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0034 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0035 |           <div class="stats-icon"><i class="bi bi-x-octagon"></i></div> | Assignment statement storing or updating program state.
L0036 |           <h1>{{ rejected_pm_rcas }}</h1> | Markup line defining structure in an HTML-like template file.
L0037 |           <p>Rejected PM RCAs</p> | Markup line defining structure in an HTML-like template file.
L0038 |         </div> | Markup line defining structure in an HTML-like template file.
L0039 |       </div> | Markup line defining structure in an HTML-like template file.
L0040 |     </a> | Markup line defining structure in an HTML-like template file.
L0041 |   </div> | Markup line defining structure in an HTML-like template file.
L0042 |   <div class="col"> | Assignment statement storing or updating program state.
L0043 |     <a href="{{ url_for('desk_activities', mode='rcas', risk='high') }}" class="card-link"> | Assignment statement storing or updating program state.
L0044 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0045 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0046 |           <div class="stats-icon"><i class="bi bi-exclamation-diamond"></i></div> | Assignment statement storing or updating program state.
L0047 |           <h1>{{ high_risk_pending_pm_rcas }}</h1> | Markup line defining structure in an HTML-like template file.
L0048 |           <p>High-Risk PM RCAs</p> | Markup line defining structure in an HTML-like template file.
L0049 |         </div> | Markup line defining structure in an HTML-like template file.
L0050 |       </div> | Markup line defining structure in an HTML-like template file.
L0051 |     </a> | Markup line defining structure in an HTML-like template file.
L0052 |   </div> | Markup line defining structure in an HTML-like template file.
L0053 |   <div class="col"> | Assignment statement storing or updating program state.
```

L0054 | | Assignment statement storing or updating program state.

L0055 | <div class="card stats-card"> | Assignment statement storing or updating program state.

L0056 | <div class="card-body text-center"> | Assignment statement storing or updating program state.

L0057 | <div class="stats-icon"><i class="bi bi-alarm"></i></div> | Assignment statement storing or updating program state.

L0058 | <h1>{{ sla_overdue_pm_rcas }}</h1> | Markup line defining structure in an HTML-like template file.

L0059 | <p>SLA Overdue</p> | Markup line defining structure in an HTML-like template file.

L0060 | </div> | Markup line defining structure in an HTML-like template file.

L0061 | </div> | Markup line defining structure in an HTML-like template file.

L0062 | | Markup line defining structure in an HTML-like template file.

L0063 | </div> | Markup line defining structure in an HTML-like template file.

L0064 | </div> | Markup line defining structure in an HTML-like template file.

L0065 | | Blank line used for readability and logical separation.

L0066 | <section class="mt-4 mb-4"> | Assignment statement storing or updating program state.

L0067 | <div class="card form-access-card sla-policy-summary-card"> | Assignment statement storing or updating program state.

L0068 | <div class="card-body d-flex justify-content-between align-items-center gap-3 flex-wrap"> | Assignment statement storing or updating program state.

L0069 | <div> | Markup line defining structure in an HTML-like template file.

L0070 | <h3 class="mb-1">Desk SLA Policy</h3> | Assignment statement storing or updating program state.

L0071 | <p class="text-muted mb-2"> | Assignment statement storing or updating program state.

L0072 | {% if active_sla_policy.enabled %} | Block delimiter controlling scope/structure in this language.

L0073 | Active policy: {{ active_sla_policy.standard_hours }}h standard PM, {{ active_sla_policy.critical_hours }}h critical/RCA,

L0074 | {% else %} | Block delimiter controlling scope/structure in this language.

L0075 | SLA is currently inactive for new desk submissions. | Operational statement participating in the file's runtime behavior.

L0076 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0077 | </p> | Markup line defining structure in an HTML-like template file.

L0078 | <div class="small text-muted">Last updated by {{ active_sla_policy.updated_by }}</div> | Assignment statement storing or updating program state.

L0079 | </div> | Markup line defining structure in an HTML-like template file.

L0080 | | Assignment statement storing or updating program state.

L0081 | <i class="bi bi-sliders"></i> Manage SLA Policy | Assignment statement storing or updating program state.

L0082 | | Markup line defining structure in an HTML-like template file.

L0083 | </div> | Markup line defining structure in an HTML-like template file.

L0084 | </div> | Markup line defining structure in an HTML-like template file.

L0085 | </section> | Markup line defining structure in an HTML-like template file.

L0086 | | Blank line used for readability and logical separation.

L0087 | <section class="mt-4 mb-4"> | Assignment statement storing or updating program state.

L0088 | <div class="card form-access-card"> | Assignment statement storing or updating program state.

L0089 | <div class="card-body d-flex justify-content-between align-items-center gap-3 flex-wrap"> | Assignment statement storing or updating program state.

L0090 | <div> | Markup line defining structure in an HTML-like template file.

L0091 | <h3 class="mb-1">Smart Review Center</h3> | Assignment statement storing or updating program state.

L0092 | <p class="text-muted mb-0">Prioritize high-risk PM/RCA submissions and overdue SLA items.</p> | Assignment statement storing or updating program state.

L0093 | </div> | Markup line defining structure in an HTML-like template file.

L0094 | | Assignment statement storing or updating program state.

L0095 | <i class="bi bi-lightning-charge"></i> Open Smart Queue | Assignment statement storing or updating program state.

L0096 | | Markup line defining structure in an HTML-like template file.

L0097 | </div> | Markup line defining structure in an HTML-like template file.

L0098 | </div> | Markup line defining structure in an HTML-like template file.

L0099 | </section> | Markup line defining structure in an HTML-like template file.

L0100 | | Blank line used for readability and logical separation.

L0101 | <section class="mt-4 mb-4"> | Assignment statement storing or updating program state.

L0102 | <div class="card form-access-card"> | Assignment statement storing or updating program state.

L0103 | <div class="card-body d-flex justify-content-between align-items-center gap-3 flex-wrap"> | Assignment statement storing or updating program state.

L0104 | <div> | Markup line defining structure in an HTML-like template file.

L0105 | <h3 class="mb-1">Approved Forms Excel Tracker</h3> | Assignment statement storing or updating program state.

L0106 | <p class="text-muted mb-0">Download approved PM/RCA forms in Excel.</p> | Assignment statement storing or updating program state.

L0107 | </div> | Markup line defining structure in an HTML-like template file.

L0108 | | Assignment statement storing or updating program state.

L0109 | <i class="bi bi-file-earmark-excel"></i> Download Excel | Assignment statement storing or updating program state.

L0110 | | Markup line defining structure in an HTML-like template file.

L0111 | </div> | Markup line defining structure in an HTML-like template file.

L0112 | </div> | Markup line defining structure in an HTML-like template file.

L0113 | </section> | Markup line defining structure in an HTML-like template file.

L0114 | | Blank line used for readability and logical separation.

L0115 | {% if not staff_has_form_data %} | Block delimiter controlling scope/structure in this language.

L0116 | <div class="alert alert-info mt-3 mb-0" role="alert"> | Assignment statement storing or updating program state.

L0117 | No recent forms have been submitted by field technicians yet. PM RCA, approved, and rejected lists will populate automatically af

L0118 | </div> | Markup line defining structure in an HTML-like template file.

L0119 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0120 | | Blank line used for readability and logical separation.

L0121 | <p class="text-center text-muted small mt-4 mb-0"> | Assignment statement storing or updating program state.

L0122 | Dashboard Footnote: {{ (current_role or 'manager')\|replace('_', ' ')\|title }} | Block delimiter controlling scope/structure in

L0123 | </p> | Markup line defining structure in an HTML-like template file.

L0124 | </div> | Markup line defining structure in an HTML-like template file.

L0125 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 110: templates/not_found.html

L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.

L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.

L0003 | <section class="not-found-wrap text-center"> | Assignment statement storing or updating program state.

L0004 | ■<h1>Sorry, page not found!</h1> | Markup line defining structure in an HTML-like template file.

L0005 | ■<p class="not-found-text">Sorry, we couldn't find the page you're looking for. Please check your URL and try again.</p> | Assignment statement storing or updating program state.

L0006 | ■Go To Home | Assignment statement storing or updating program state.

L0007 | </section> | Markup line defining structure in an HTML-like template file.

L0008 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 111: templates/notifications.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <section class="notifications-board"> | Assignment statement storing or updating program state.
L0004 | <div class="notifications-headline"> | Assignment statement storing or updating program state.
L0005 | <h1>Notifications & Messages</h1> | Markup line defining structure in an HTML-like template file.
L0006 | <p class="text-muted mb-0">Review team updates, send targeted messages, and manage your inbox quickly.</p> | Assignment statement storing or updating program state.
L0007 | </div> | Markup line defining structure in an HTML-like template file.
L0008 | | Blank line used for readability and logical separation.
L0009 | <div class="card mt-3 p-3 message-pad-card notify-shell notify-composer-card"> | Assignment statement storing or updating program state.
L0010 | <h5 class="mb-3 d-flex align-items-center gap-2"><i class="bi bi-pencil-square"></i>Message Pad</h5> | Assignment statement storing or updating program state.
L0011 | <form method="post" action="{% url_for('send_system_message') %}" class="row g-3"> | Assignment statement storing or updating program state.
L0012 | <input type="hidden" name="csrf_token" value="{% csrf_token %}" /> | Assignment statement storing or updating program state.
L0013 | <div class="col-md-4"> | Assignment statement storing or updating program state.
L0014 | <label class="form-label">Send To</label> | Assignment statement storing or updating program state.
L0015 | <select class="form-select" name="recipient_role" required> | Assignment statement storing or updating program state.
L0016 | {% for option in recipient_options %} | Block delimiter controlling scope/structure in this language.
L0017 | {% if option == 'all' %} | Block delimiter controlling scope/structure in this language.
L0018 | <option value="all">All Teams</option> | Assignment statement storing or updating program state.
L0019 | {% elif option == 'developer' %} | Block delimiter controlling scope/structure in this language.
L0020 | <option value="developer">Developer</option> | Assignment statement storing or updating program state.
L0021 | {% elif option == 'staff' %} | Block delimiter controlling scope/structure in this language.
L0022 | <option value="staff">Staff</option> | Assignment statement storing or updating program state.
L0023 | {% elif option == 'technician' %} | Block delimiter controlling scope/structure in this language.
L0024 | <option value="technician">Technician</option> | Assignment statement storing or updating program state.
L0025 | {% elif option == 'manager' %} | Block delimiter controlling scope/structure in this language.
L0026 | <option value="manager">Manager</option> | Assignment statement storing or updating program state.
L0027 | {% elif option == 'general_manager' %} | Block delimiter controlling scope/structure in this language.
L0028 | <option value="general_manager">General Manager</option> | Assignment statement storing or updating program state.
L0029 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0030 | {% endfor %} | Block delimiter controlling scope/structure in this language.
L0031 | </select> | Markup line defining structure in an HTML-like template file.
L0032 | </div> | Markup line defining structure in an HTML-like template file.
L0033 | <div class="col-md-8"> | Assignment statement storing or updating program state.
L0034 | <label class="form-label">Message</label> | Assignment statement storing or updating program state.
L0035 | <textarea class="form-control" name="message_body" rows="3" placeholder="Type your message to team members..." required></textarea> | Assignment statement storing or updating program state.
L0036 | </div> | Markup line defining structure in an HTML-like template file.
L0037 | <div class="col-12 text-end"> | Assignment statement storing or updating program state.
L0038 | <button class="btn btn-primary" type="submit"><i class="bi bi-send-fill"></i> Send Message</button> | Assignment statement storing or updating program state.
L0039 | </div> | Markup line defining structure in an HTML-like template file.
L0040 | </form> | Markup line defining structure in an HTML-like template file.
L0041 | </div> | Markup line defining structure in an HTML-like template file.
L0042 | | Blank line used for readability and logical separation.
L0043 | <div class="card mt-3 p-3 notify-shell notify-inbox-card"> | Assignment statement storing or updating program state.
L0044 | <div class="d-flex justify-content-between align-items-center flex-wrap gap-2 mb-3"> | Assignment statement storing or updating program state.
L0045 | <h5 class="mb-0 d-flex align-items-center gap-2"><i class="bi bi-inbox-fill"></i>Inbox Messages</h5> | Assignment statement storing or updating program state.
L0046 | <span class="badge text-bg-light notify-count-chip">{{ messages|length }} message{% if messages|length != 1 %}s{% endif %}</span> | Assignment statement storing or updating program state.
L0047 | </div> | Markup line defining structure in an HTML-like template file.
L0048 | {% if messages %} | Block delimiter controlling scope/structure in this language.
L0049 | <ul class="list-group notification-list notify-message-list" id="inboxMessageList"> | Assignment statement storing or updating program state.
L0050 | {% for msg in messages %} | Block delimiter controlling scope/structure in this language.
L0051 | {% set can_delete_message = msg.sender_email == current_user.email or (current_user.role or '')|lower == 'developer' %} | Assignment statement storing or updating program state.
L0052 | <li class="list-group-item notification-item message-item notify-message-card px-3 py-2"> | Assignment statement storing or updating program state.
L0053 | <div class="d-flex justify-content-between align-items-start gap-2 flex-wrap"> | Assignment statement storing or updating program state.
```

```

L0054 |         <button | Operational statement participating in the file's runtime behavior.
L0055 |             type="button" | Assignment statement storing or updating program state.
L0056 |             class="btn btn-link p-0 text-start flex-grow-1 message-toggle-btn" | Assignment statement storing or updating program state.
L0057 |             data-target="msg-body-{{ loop.index }}" | Assignment statement storing or updating program state.
L0058 |             aria-expanded="false" | Assignment statement storing or updating program state.
L0059 |         > | Operational statement participating in the file's runtime behavior.
L0060 |         <div class="d-flex justify-content-between align-items-center gap-3 flex-wrap"> | Assignment statement storing or updating program state.
L0061 |             <div> | Markup line defining structure in an HTML-like template file.
L0062 |                 <strong>{{ msg.sender_email }}</strong> | Markup line defining structure in an HTML-like template file.
L0063 |                 <span class="badge text-bg-primary ms-2">{{ msg.sender_role|upper }}</span> | Assignment statement storing or updating program state.
L0064 |                 {% if msg.recipient_email %} | Block delimiter controlling scope/structure in this language.
L0065 |                 <span class="badge text-bg-secondary ms-1">TO {{ msg.recipient_email }}</span> | Assignment statement storing or updating program state.
L0066 |                 {% else %} | Block delimiter controlling scope/structure in this language.
L0067 |                 <span class="badge text-bg-secondary ms-1">TO {{ msg.recipient_role|upper }}</span> | Assignment statement storing or updating program state.
L0068 |                 {% endif %} | Block delimiter controlling scope/structure in this language.
L0069 |                 <span class="text-muted ms-2" style="font-size:0.78rem;">{{ msg.body[:60] }}{% if msg.body|length > 60 %}...{% endif %}</span> | Assignment statement storing or updating program state.
L0070 |             </div> | Markup line defining structure in an HTML-like template file.
L0071 |             <div class="d-flex align-items-center gap-2"> | Assignment statement storing or updating program state.
L0072 |                 <span class="text-muted small">{{ msg.created_at.strftime('%Y-%m-%d %H:%M') }}</span> | Assignment statement storing or updating program state.
L0073 |                 <i class="bi bi-chevron-down message-chevron" style="transition:transform .2s;"></i> | Assignment statement storing or updating program state.
L0074 |             </div> | Markup line defining structure in an HTML-like template file.
L0075 |         </div> | Markup line defining structure in an HTML-like template file.
L0076 |     </button> | Markup line defining structure in an HTML-like template file.
L0077 |     {% if can_delete_message %} | Block delimiter controlling scope/structure in this language.
L0078 |     <form method="post" action="{{ url_for('delete_system_message', message_id=msg.id) }}" class="ms-auto" data-no-loader="true"> | Assignment statement storing or updating program state.
L0079 |         <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.
L0080 |         <button | Operational statement participating in the file's runtime behavior.
L0081 |             type="submit" | Assignment statement storing or updating program state.
L0082 |             class="btn btn-sm btn-outline-danger" | Assignment statement storing or updating program state.
L0083 |         > | Operational statement participating in the file's runtime behavior.
L0084 |         <i class="bi bi-trash-fill me-1"></i>Delete Message | Assignment statement storing or updating program state.
L0085 |         </button> | Markup line defining structure in an HTML-like template file.
L0086 |     </form> | Markup line defining structure in an HTML-like template file.
L0087 |     {% endif %} | Block delimiter controlling scope/structure in this language.
L0088 | </div> | Markup line defining structure in an HTML-like template file.
L0089 | <div class="message-full-body mt-2 px-1 pb-1" id="msg-body-{{ loop.index }}" hidden> | Assignment statement storing or updating program state.
L0090 |     <div class="border-start border-3 border-primary ps-3 py-1" style="white-space:pre-wrap;">{{ msg.body }}</div> | Assignment statement storing or updating program state.
L0091 | </div> | Markup line defining structure in an HTML-like template file.
L0092 | </li> | Markup line defining structure in an HTML-like template file.
L0093 | {% endfor %} | Block delimiter controlling scope/structure in this language.
L0094 | </ul> | Markup line defining structure in an HTML-like template file.
L0095 | {% else %} | Block delimiter controlling scope/structure in this language.
L0096 | <p class="mb-0">No messages yet.</p> | Assignment statement storing or updating program state.
L0097 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0098 | </div> | Markup line defining structure in an HTML-like template file.
L0099 | </section> | Markup line defining structure in an HTML-like template file.
L0100 | | Blank line used for readability and logical separation.
L0101 | <script> | Markup line defining structure in an HTML-like template file.
L0102 | (function () { | Block delimiter controlling scope/structure in this language.
L0103 |     document.querySelectorAll('.message-toggle-btn').forEach(function (btn) { | Block delimiter controlling scope/structure in this language.
L0104 |         btn.addEventListener('click', function () { | Block delimiter controlling scope/structure in this language.
L0105 |             const targetId = btn.getAttribute('data-target'); | Assignment statement storing or updating program state.
L0106 |             const body = document.getElementById(targetId); | Assignment statement storing or updating program state.
L0107 |             const chevron = btn.querySelector('.message-chevron'); | Assignment statement storing or updating program state.
L0108 |             if (!body) return; | Conditional branch that runs only when its condition is true.

```


L0109 | const isHidden = body.hidden; | Assignment statement storing or updating program state.
L0110 | body.hidden = !isHidden; | Assignment statement storing or updating program state.
L0111 | if (chevron) chevron.style.transform = isHidden ? 'rotate(180deg)' : ''; | Conditional branch that runs only when its condi
L0112 | btn.setAttribute('aria-expanded', String(isHidden)); | Operational statement participating in the file's runtime behavior.
L0113 | }); | Operational statement participating in the file's runtime behavior.
L0114 | }); | Operational statement participating in the file's runtime behavior.
L0115 | })(); | Operational statement participating in the file's runtime behavior.
L0116 | </script> | Markup line defining structure in an HTML-like template file.
L0117 | | Blank line used for readability and logical separation.
L0118 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 112: templates/register.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <h1>{% if first_user %}Create Developer Account{% else %}Create Team Account{% endif %}</h1> | Markup line defining structure in
L0004 | {% with messages = get_flashed_messages(with_categories=true) %} | Assignment statement storing or updating program state.
L0005 |     {% if messages %} | Block delimiter controlling scope/structure in this language.
L0006 |         {% for category, msg in messages %} | Block delimiter controlling scope/structure in this language.
L0007 |             <div class="alert alert-{{ category }}">{{ msg }}</div> | Assignment statement storing or updating program state.
L0008 |         {% endfor %} | Block delimiter controlling scope/structure in this language.
L0009 |     {% endif %} | Block delimiter controlling scope/structure in this language.
L0010 | {% endwith %} | Block delimiter controlling scope/structure in this language.
L0011 | <form method="post" class="row g-3" style="max-width: 420px;"> | Assignment statement storing or updating program state.
L0012 |     <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program state.
L0013 |     <div class="col-12"><label class="form-label">Full Name</label><input name="full_name" class="form-control" required></div> | A
L0014 |     <div class="col-12"><label class="form-label">Email</label><input name="email" class="form-control" required></div> | Assignmen
L0015 |     <div class="col-12"><label class="form-label">Password</label><input name="password" type="password" class="form-control" requi
L0016 |     <div class="col-12"> | Assignment statement storing or updating program state.
L0017 |         <label class="form-label">Role</label> | Assignment statement storing or updating program state.
L0018 |         <select name="role" class="form-select" {% if first_user %}disabled{% endif %}> | Assignment statement storing or updating pr
L0019 |             {% if first_user %} | Block delimiter controlling scope/structure in this language.
L0020 |                 <option value="developer" selected>Developer</option> | Assignment statement storing or updating program state.
L0021 |             {% else %} | Block delimiter controlling scope/structure in this language.
L0022 |                 <option value="staff" selected>Staff</option> | Assignment statement storing or updating program state.
L0023 |                 <option value="technician">Technician</option> | Assignment statement storing or updating program state.
L0024 |                 <option value="developer">Developer</option> | Assignment statement storing or updating program state.
L0025 |             {% endif %} | Block delimiter controlling scope/structure in this language.
L0026 |         </select> | Markup line defining structure in an HTML-like template file.
L0027 |         {% if first_user %} | Block delimiter controlling scope/structure in this language.
L0028 |             <input type="hidden" name="role" value="developer"> | Assignment statement storing or updating program state.
L0029 |         {% endif %} | Block delimiter controlling scope/structure in this language.
L0030 |     </div> | Markup line defining structure in an HTML-like template file.
L0031 |     <div class="col-12"><label class="form-label">Support Desk</label><input name="support_desk" class="form-control" placeholder="
L0032 |     <div class="col-12"><label class="form-label">Site Operations Phone</label><input name="site_operations_phone" class="form-cont
L0033 |     <div class="col-12"><label class="form-label">Emergency Escalation Phone</label><input name="emergency_phone" class="form-contr
L0034 |     <div class="col-12"><button type="submit" class="btn btn-primary">Save Account</button></div> | Assignment statement storing or
L0035 | </form> | Markup line defining structure in an HTML-like template file.
L0036 | <p class="mt-3">Already have account? <a href="{{ url_for('login') }}">Login</a></p> | Assignment statement storing or updating p
L0037 | {% endblock %} | Block delimiter controlling scope/structure in this language.
```

File 113: templates/settings.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <h1>System Settings</h1> | Markup line defining structure in an HTML-like template file.
L0004 | | Blank line used for readability and logical separation.
L0005 | <div class="row g-3 settings-grid"> | Assignment statement storing or updating program state.
L0006 |     {% if can_manage_sla %} | Block delimiter controlling scope/structure in this language.
L0007 |     <div class="col-12"> | Assignment statement storing or updating program state.
L0008 |         <div class="card settings-card sla-settings-card"> | Assignment statement storing or updating program state.
L0009 |             <div class="card-body"> | Assignment statement storing or updating program state.
L0010 |                 <div class="d-flex justify-content-between align-items-start gap-3 flex-wrap"> | Assignment statement storing or updating p
L0011 |                     <div> | Markup line defining structure in an HTML-like template file.
L0012 |                         <h5 class="settings-card-title"><i class="bi bi-alarm-fill"></i> SLA Policy Control</h5> | Assignment statement storing
L0013 |                         <p class="text-muted mb-2">Desk teams and managers can control the live SLA window used for new PM/RCA submissions.</p>
L0014 |                     </div> | Markup line defining structure in an HTML-like template file.
L0015 |                     <div class="sla-policy-status-wrap text-start text-md-end"> | Assignment statement storing or updating program state.
L0016 |                         <span class="badge {% if active_sla_policy.enabled %}text-bg-success{% else %}text-bg-secondary{% endif %}"> | Assignme
L0017 |                             {% if active_sla_policy.enabled %}SLA Active{% else %}SLA Inactive{% endif %} | Block delimiter controlling scope/str
L0018 |                         </span> | Markup line defining structure in an HTML-like template file.
L0019 |                         <div class="small text-muted mt-2">Updated by {{ active_sla_policy.updated_by }}{% if active_sla_policy.updated_role an
L0020 |                     </div> | Markup line defining structure in an HTML-like template file.
L0021 |                 </div> | Markup line defining structure in an HTML-like template file.
L0022 | | Blank line used for readability and logical separation.
L0023 |                 <div class="row g-3 mt-1"> | Assignment statement storing or updating program state.
L0024 |                     <div class="col-12 col-xl-7"> | Assignment statement storing or updating program state.
L0025 |                         <form method="post" class="row g-3"> | Assignment statement storing or updating program state.
L0026 |                             <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program
L0027 |                             <input type="hidden" name="save_section" value="sla_policy" /> | Assignment statement storing or updating program sta
L0028 |                             <input type="hidden" name="theme" value="{{ app_theme }}" /> | Assignment statement storing or updating program state
L0029 |                             <input type="hidden" name="language" value="{{ app_language }}" /> | Assignment statement storing or updating program
L0030 | | Blank line used for readability and logical separation.
L0031 |                             <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.
L0032 |                                 <label class="form-label">SLA Mode</label> | Assignment statement storing or updating program state.
L0033 |                                 <select class="form-select" name="sla_enabled"> | Assignment statement storing or updating program state.
L0034 |                                     <option value="active" {% if current_sla_policy.enabled %}selected{% endif %}>Activate SLA</option> | Assignment
L0035 |                                     <option value="inactive" {% if not current_sla_policy.enabled %}selected{% endif %}>Deactivate SLA</option> | Ass
L0036 |                                 </select> | Markup line defining structure in an HTML-like template file.
L0037 |                             </div> | Markup line defining structure in an HTML-like template file.
L0038 |                             <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.
L0039 |                                 <label class="form-label">Standard PM Hours</label> | Assignment statement storing or updating program state.
L0040 |                                 <input type="number" min="1" max="168" class="form-control" name="sla_standard_hours" value="{{ current_sla_policy.
L0041 |                             </div> | Markup line defining structure in an HTML-like template file.
L0042 |                             <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.
L0043 |                                 <label class="form-label">Critical / RCA Hours</label> | Assignment statement storing or updating program state.
L0044 |                                 <input type="number" min="1" max="168" class="form-control" name="sla_critical_hours" value="{{ current_sla_policy.
L0045 |                             </div> | Markup line defining structure in an HTML-like template file.
L0046 |                             <div class="col-12 col-md-4"> | Assignment statement storing or updating program state.
L0047 |                                 <label class="form-label">Due Soon Window</label> | Assignment statement storing or updating program state.
L0048 |                                 <input type="number" min="1" max="72" class="form-control" name="sla_due_soon_hours" value="{{ current_sla_policy.d
L0049 |                             </div> | Markup line defining structure in an HTML-like template file.
L0050 |                             <div class="col-12"> | Assignment statement storing or updating program state.
L0051 |                                 <label class="sla-agreement-box"> | Assignment statement storing or updating program state.
L0052 |                                     <input type="checkbox" name="sla_policy_agreed" required /> | Assignment statement storing or updating program st
L0053 |                                     <span>I agree that this SLA policy will apply to new PM/RCA submissions and desk review prioritization.</span> |
```

L0054 | </label> | Markup line defining structure in an HTML-like template file.

L0055 | </div> | Markup line defining structure in an HTML-like template file.

L0056 | <div class="col-12 d-flex justify-content-end"> | Assignment statement storing or updating program state.

L0057 | <button type="submit" class="btn btn-primary">Save SLA Policy</button> | Assignment statement storing or updating p

L0058 | </div> | Markup line defining structure in an HTML-like template file.

L0059 | </form> | Markup line defining structure in an HTML-like template file.

L0060 | </div> | Markup line defining structure in an HTML-like template file.

L0061 | | Blank line used for readability and logical separation.

L0062 | <div class="col-12 col-xl-5"> | Assignment statement storing or updating program state.

L0063 | <div class="sla-policy-panel"> | Assignment statement storing or updating program state.

L0064 | <div class="sla-policy-stats"> | Assignment statement storing or updating program state.

L0065 | <div class="sla-policy-stat"> | Assignment statement storing or updating program state.

L0066 | Standard PM | Assignment statement storing or updating program state.

L0067 | {{ active_sla_policy.standard_hours }}h | Markup line defining structure in an HTML-like template

L0068 | </div> | Markup line defining structure in an HTML-like template file.

L0069 | <div class="sla-policy-stat"> | Assignment statement storing or updating program state.

L0070 | Critical / RCA | Assignment statement storing or updating program stat

L0071 | {{ active_sla_policy.critical_hours }}h | Markup line defining structure in an HTML-like template

L0072 | </div> | Markup line defining structure in an HTML-like template file.

L0073 | <div class="sla-policy-stat"> | Assignment statement storing or updating program state.

L0074 | Due Soon | Assignment statement storing or updating program state.

L0075 | {{ active_sla_policy.due_soon_hours }}h | Markup line defining structure in an HTML-like template

L0076 | </div> | Markup line defining structure in an HTML-like template file.

L0077 | </div> | Markup line defining structure in an HTML-like template file.

L0078 | <div class="sla-policy-list-wrap mt-3"> | Assignment statement storing or updating program state.

L0079 | <div class="fw-semibold mb-2">Policy</div> | Assignment statement storing or updating program state.

L0080 | <ul class="sla-policy-list mb-0"> | Assignment statement storing or updating program state.

L0081 | When active, new PM and RCA submissions receive SLA deadlines automatically. | Markup line defining stru

L0082 | Critical or RCA items use the critical review window. | Markup line defining structure in an HTML-like t

L0083 | Standard PM items use the standard review window. | Markup line defining structure in an HTML-like temp

L0084 | Items inside the due-soon window are highlighted before breach. | Markup line defining structure in an H

L0085 | Overdue high-risk items escalate automatically to desk leadership. | Markup line defining structure in a

L0086 | | Markup line defining structure in an HTML-like template file.

L0087 | </div> | Markup line defining structure in an HTML-like template file.

L0088 | </div> | Markup line defining structure in an HTML-like template file.

L0089 | </div> | Markup line defining structure in an HTML-like template file.

L0090 | </div> | Markup line defining structure in an HTML-like template file.

L0091 | </div> | Markup line defining structure in an HTML-like template file.

L0092 | </div> | Markup line defining structure in an HTML-like template file.

L0093 | </div> | Markup line defining structure in an HTML-like template file.

L0094 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0095 | | Blank line used for readability and logical separation.

L0096 | <div class="col-12 col-lg-6"> | Assignment statement storing or updating program state.

L0097 | <div class="card settings-card h-100"> | Assignment statement storing or updating program state.

L0098 | <div class="card-body"> | Assignment statement storing or updating program state.

L0099 | <h5 class="settings-card-title"><i class="bi bi-translate"></i> Language</h5> |

L0100 | <p class="text-muted">Developer, desk staff, and technician can switch display language.</p> | Assignment statement storing

L0101 | <form method="post" class="row g-3"> | Assignment statement storing or updating program state.

L0102 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program sta

L0103 | <div class="col-12"> | Assignment statement storing or updating program state.

L0104 | <label class="form-label" data-i18n="choose_lang">Choose language</label> | Assignment statement storing or updating pr

L0105 | <select class="form-select" name="language" id="langSelect" onchange="this.form.submit()"> | Assignment statement stori

L0106 | <option value="en" {% if app_language == 'en' %}>selected{% endif %}>English</option> | Markup line defining structure

L0107 | <option value="sw" {% if app_language == 'sw' %}>selected{% endif %}>Swahili</option> | Markup line defining structure

L0108 | <option value="fr" {% if app_language == 'fr' %}>selected{% endif %}>French</option> | Markup line defining structure

L0109 | <option value="ar" {% if app_language == 'ar' %}selected{% endif %}>Arabic</option> | Markup line defining structure
L0110 | </select> | Markup line defining structure in an HTML-like template file.
L0111 | </div> | Markup line defining structure in an HTML-like template file.
L0112 | <div class="col-12"> | Assignment statement storing or updating program state.
L0113 | <input type="hidden" name="theme" value="{{ app_theme }}" /> | Assignment statement storing or updating program state.
L0114 | </div> | Markup line defining structure in an HTML-like template file.
L0115 | </form> | Markup line defining structure in an HTML-like template file.
L0116 | </div> | Markup line defining structure in an HTML-like template file.
L0117 | </div> | Markup line defining structure in an HTML-like template file.
L0118 | </div> | Markup line defining structure in an HTML-like template file.
L0119 | | Blank line used for readability and logical separation.
L0120 | <div class="col-12 col-lg-6"> | Assignment statement storing or updating program state.
L0121 | <div class="card settings-card h-100"> | Assignment statement storing or updating program state.
L0122 | <div class="card-body"> | Assignment statement storing or updating program state.
L0123 | <h5 class="settings-card-title"><i class="bi bi-circle-half"></i> Appearance</h5> | Ass
L0124 | <p class="text-muted">Switch between light mode and dark mode.</p> | Assignment statement storing or updating program state
L0125 | <form method="post" class="row g-3"> | Assignment statement storing or updating program state.
L0126 | <input type="hidden" name="csrf_token" value="{{ csrf_token }}" /> | Assignment statement storing or updating program sta
L0127 | <div class="col-12"> | Assignment statement storing or updating program state.
L0128 | <label class="mode-switch-wrap" for="theme-toggle"> | Assignment statement storing or updating program state.
L0129 | <input id="theme-toggle" type="checkbox" {% if app_theme == 'dark' %}checked{% endif %} /> | Markup line defining str
L0130 | | Assignment statement storing or updating program state.
L0131 | Dark mode | Assignment statement storing or updating pro
L0132 | </label> | Markup line defining structure in an HTML-like template file.
L0133 | <input id="theme-hidden" type="hidden" name="theme" value="{{ app_theme }}" /> | Assignment statement storing or updati
L0134 | <input type="hidden" name="language" value="{{ app_language }}" /> | Assignment statement storing or updating program s
L0135 | </div> | Markup line defining structure in an HTML-like template file.
L0136 | <div class="col-12"> | Assignment statement storing or updating program state.
L0137 | <button type="submit" class="btn btn-primary w-100" data-i18n="apply_theme">Apply Theme</button> | Assignment statement
L0138 | </div> | Markup line defining structure in an HTML-like template file.
L0139 | </form> | Markup line defining structure in an HTML-like template file.
L0140 | </div> | Markup line defining structure in an HTML-like template file.
L0141 | </div> | Markup line defining structure in an HTML-like template file.
L0142 | </div> | Markup line defining structure in an HTML-like template file.
L0143 | | Blank line used for readability and logical separation.
L0144 | <div class="col-12 col-lg-6"> | Assignment statement storing or updating program state.
L0145 | <div class="card settings-card folded-calendar-card h-100"> | Assignment statement storing or updating program state.
L0146 | <div class="card-body"> | Assignment statement storing or updating program state.
L0147 | <h5 class="settings-card-title"><i class="bi bi-calendar3"></i> Calendar</h5> | Assignment statement storing or updating pr
L0148 | <p class="text-muted">Swipe or use the arrows to turn months like a book and view public holidays.</p> | Assignment stateme
L0149 | <div class="holiday-calendar holiday-calendar-full"> | Assignment statement storing or updating program state.
L0150 | <div class="calendar-book"> | Assignment statement storing or updating program state.
L0151 | <div class="calendar-toolbar"> | Assignment statement storing or updating program state.
L0152 | <button type="button" class="btn btn-sm btn-outline-primary calendar-nav calendar-nav-prev"><i class="bi bi-chevron-l
L0153 | <div class="calendar-month-label"></div> | Assignment statement storing or updating program state.
L0154 | <button type="button" class="btn btn-sm btn-outline-primary calendar-nav calendar-nav-next"><i class="bi bi-chevron-r
L0155 | </div> | Markup line defining structure in an HTML-like template file.
L0156 | <div class="calendar-sheet"> | Assignment statement storing or updating program state.
L0157 | <div class="calendar-grid"></div> | Assignment statement storing or updating program state.
L0158 | </div> | Markup line defining structure in an HTML-like template file.
L0159 | </div> | Markup line defining structure in an HTML-like template file.
L0160 | <div class="calendar-holiday-list mt-3"></div> | Assignment statement storing or updating program state.
L0161 | </div> | Markup line defining structure in an HTML-like template file.
L0162 | </div> | Markup line defining structure in an HTML-like template file.
L0163 | </div> | Markup line defining structure in an HTML-like template file.

L0164 | </div> | Markup line defining structure in an HTML-like template file.

L0165 | | Blank line used for readability and logical separation.

L0166 | <div class="col-12 col-lg-6"> | Assignment statement storing or updating program state.

L0167 | <div class="card settings-card h-100 notification-settings-card"> | Assignment statement storing or updating program state.

L0168 | <div class="card-body"> | Assignment statement storing or updating program state.

L0169 | <h5 class="settings-card-title"><i class="bi bi-bell-fill"></i> Notifications</h5> | Assignment statement storing or updating program state.

L0170 | <p class="text-muted">Open recent notifications and system-wide messages.</p> | Assignment statement storing or updating program state.

L0171 | <div class="notification-card-stat"> | Assignment statement storing or updating program state.

L0172 | Recent items | Assignment statement storing or updating program state.

L0173 | {{ notification_count }} | Assignment statement storing or updating program state.

L0174 | </div> | Markup line defining structure in an HTML-like template file.

L0175 | Open Notification Feed | Assignment statement storing or updating program state.

L0176 | </div> | Markup line defining structure in an HTML-like template file.

L0177 | </div> | Markup line defining structure in an HTML-like template file.

L0178 | </div> | Markup line defining structure in an HTML-like template file.

L0179 | </div> | Markup line defining structure in an HTML-like template file.

L0180 | <script> | Markup line defining structure in an HTML-like template file.

L0181 | (function () { | Block delimiter controlling scope/structure in this language.

L0182 | const toggle = document.getElementById('theme-toggle'); | Assignment statement storing or updating program state.

L0183 | const hidden = document.getElementById('theme-hidden'); | Assignment statement storing or updating program state.

L0184 | if (toggle && hidden) { | Conditional branch that runs only when its condition is true.

L0185 | toggle.addEventListener('change', function () { | Block delimiter controlling scope/structure in this language.

L0186 | hidden.value = toggle.checked ? 'dark' : 'light'; | Assignment statement storing or updating program state.

L0187 | }); | Operational statement participating in the file's runtime behavior.

L0188 | hidden.value = toggle.checked ? 'dark' : 'light'; | Assignment statement storing or updating program state.

L0189 | } | Block delimiter controlling scope/structure in this language.

L0190 | })(); | Operational statement participating in the file's runtime behavior.

L0191 | </script> | Markup line defining structure in an HTML-like template file.

L0192 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 114: templates/staff_dashboard.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <div class="role-dashboard-shell role-staff"> | Assignment statement storing or updating program state.
L0004 | <section class="dashboard-hero-lite"> | Assignment statement storing or updating program state.
L0005 |   <h1>Hello, {{ user_name }}. Welcome back!</h1> | Markup line defining structure in an HTML-like template file.
L0006 |   <div class="mt-2"> | Assignment statement storing or updating program state.
L0007 |     <span class="badge text-bg-primary fs-6">Staff Dashboard</span> | Assignment statement storing or updating program state.
L0008 |   </div> | Markup line defining structure in an HTML-like template file.
L0009 | </section> | Markup line defining structure in an HTML-like template file.
L0010 | | Blank line used for readability and logical separation.
L0011 | <div class="row row-cols-1 row-cols-md-3 g-3 mt-1"> | Assignment statement storing or updating program state.
L0012 |   <div class="col"> | Assignment statement storing or updating program state.
L0013 |     <a href="{{ url_for('desk_activities', mode='rcas') }}" class="card-link"> | Assignment statement storing or updating program state.
L0014 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0015 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0016 |           <div class="stats-icon"><i class="bi bi-journal-check"></i></div> | Assignment statement storing or updating program state.
L0017 |           <h1 data-count-key="pending_pm_rcas">{{ pending_pm_rcas }}</h1> | Assignment statement storing or updating program state.
L0018 |           <p>PM RCAs To Review</p> | Markup line defining structure in an HTML-like template file.
L0019 |         </div> | Markup line defining structure in an HTML-like template file.
L0020 |       </div> | Markup line defining structure in an HTML-like template file.
L0021 |     </a> | Markup line defining structure in an HTML-like template file.
L0022 |   </div> | Markup line defining structure in an HTML-like template file.
L0023 |   <div class="col"> | Assignment statement storing or updating program state.
L0024 |     <a href="{{ url_for('desk_activities', mode='forms') }}" class="card-link"> | Assignment statement storing or updating program state.
L0025 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0026 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0027 |           <div class="stats-icon"><i class="bi bi-file-earmark-pdf"></i></div> | Assignment statement storing or updating program state.
L0028 |           <h1 data-count-key="field_total_forms">{{ pending_pm_rcas + approved_pm_forms + rejected_pm_rcas }}</h1> | Assignment statement storing or updating program state.
L0029 |           <p>Total PM Forms</p> | Markup line defining structure in an HTML-like template file.
L0030 |         </div> | Markup line defining structure in an HTML-like template file.
L0031 |       </div> | Markup line defining structure in an HTML-like template file.
L0032 |     </a> | Markup line defining structure in an HTML-like template file.
L0033 |   </div> | Markup line defining structure in an HTML-like template file.
L0034 |   <div class="col"> | Assignment statement storing or updating program state.
L0035 |     <a href="{{ url_for('desk_activities', mode='rejected') }}" class="card-link"> | Assignment statement storing or updating program state.
L0036 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0037 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0038 |           <div class="stats-icon"><i class="bi bi-x-octagon"></i></div> | Assignment statement storing or updating program state.
L0039 |           <h1 data-count-key="rejected_pm_rcas">{{ rejected_pm_rcas }}</h1> | Assignment statement storing or updating program state.
L0040 |           <p>Rejected PM RCAs</p> | Markup line defining structure in an HTML-like template file.
L0041 |         </div> | Markup line defining structure in an HTML-like template file.
L0042 |       </div> | Markup line defining structure in an HTML-like template file.
L0043 |     </a> | Markup line defining structure in an HTML-like template file.
L0044 |   </div> | Markup line defining structure in an HTML-like template file.
L0045 |   <div class="col"> | Assignment statement storing or updating program state.
L0046 |     <a href="{{ url_for('desk_activities', mode='rcas', risk='high') }}" class="card-link"> | Assignment statement storing or updating program state.
L0047 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0048 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0049 |           <div class="stats-icon"><i class="bi bi-exclamation-diamond"></i></div> | Assignment statement storing or updating program state.
L0050 |           <h1 data-count-key="high_risk_pending_pm_rcas">{{ high_risk_pending_pm_rcas }}</h1> | Assignment statement storing or updating program state.
L0051 |           <p>High-Risk PM RCAs</p> | Markup line defining structure in an HTML-like template file.
L0052 |         </div> | Markup line defining structure in an HTML-like template file.
L0053 |       </div> | Markup line defining structure in an HTML-like template file.
```

L0054 | | Markup line defining structure in an HTML-like template file.

L0055 | </div> | Markup line defining structure in an HTML-like template file.

L0056 | <div class="col"> | Assignment statement storing or updating program state.

L0057 | | Assignment statement storing or updating program state.

L0058 | <div class="card stats-card"> | Assignment statement storing or updating program state.

L0059 | <div class="card-body text-center"> | Assignment statement storing or updating program state.

L0060 | <div class="stats-icon"><i class="bi bi-alarm"></i></div> | Assignment statement storing or updating program state.

L0061 | <h1 data-count-key="sla_overdue_pm_rcas">{{ sla_overdue_pm_rcas }}</h1> | Assignment statement storing or updating program state.

L0062 | <p>SLA Overdue</p> | Markup line defining structure in an HTML-like template file.

L0063 | </div> | Markup line defining structure in an HTML-like template file.

L0064 | </div> | Markup line defining structure in an HTML-like template file.

L0065 | | Markup line defining structure in an HTML-like template file.

L0066 | </div> | Markup line defining structure in an HTML-like template file.

L0067 | </div> | Markup line defining structure in an HTML-like template file.

L0068 | | Blank line used for readability and logical separation.

L0069 | <section class="mt-4 mb-4"> | Assignment statement storing or updating program state.

L0070 | <div class="card form-access-card sla-policy-summary-card"> | Assignment statement storing or updating program state.

L0071 | <div class="card-body d-flex justify-content-between align-items-center gap-3 flex-wrap"> | Assignment statement storing or updating program state.

L0072 | <div> | Markup line defining structure in an HTML-like template file.

L0073 | <h3 class="mb-1">Desk SLA Policy</h3> | Assignment statement storing or updating program state.

L0074 | <p class="text-muted mb-2"> | Assignment statement storing or updating program state.

L0075 | {% if active_sla_policy.enabled %} | Block delimiter controlling scope/structure in this language.

L0076 | Active policy: {{ active_sla_policy.standard_hours }}h standard PM, {{ active_sla_policy.critical_hours }}h critical/RCA,

L0077 | {% else %} | Block delimiter controlling scope/structure in this language.

L0078 | SLA is currently inactive for new desk submissions. | Operational statement participating in the file's runtime behavior.

L0079 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0080 | </p> | Markup line defining structure in an HTML-like template file.

L0081 | <div class="small text-muted">Last updated by {{ active_sla_policy.updated_by }}</div> | Assignment statement storing or updating program state.

L0082 | </div> | Markup line defining structure in an HTML-like template file.

L0083 | | Assignment statement storing or updating program state.

L0084 | <i class="bi bi-sliders"></i> Manage SLA Policy | Assignment statement storing or updating program state.

L0085 | | Markup line defining structure in an HTML-like template file.

L0086 | </div> | Markup line defining structure in an HTML-like template file.

L0087 | </div> | Markup line defining structure in an HTML-like template file.

L0088 | </section> | Markup line defining structure in an HTML-like template file.

L0089 | | Blank line used for readability and logical separation.

L0090 | <section class="mt-4 mb-4"> | Assignment statement storing or updating program state.

L0091 | <div class="card form-access-card"> | Assignment statement storing or updating program state.

L0092 | <div class="card-body d-flex justify-content-between align-items-center gap-3 flex-wrap"> | Assignment statement storing or updating program state.

L0093 | <div> | Markup line defining structure in an HTML-like template file.

L0094 | <h3 class="mb-1">Smart Review Center</h3> | Assignment statement storing or updating program state.

L0095 | <p class="text-muted mb-0">Prioritize high-risk PM/RCA submissions and overdue SLA items.</p> | Assignment statement storing or updating program state.

L0096 | </div> | Markup line defining structure in an HTML-like template file.

L0097 | | Assignment statement storing or updating program state.

L0098 | <i class="bi bi-lightning-charge"></i> Open Smart Queue | Assignment statement storing or updating program state.

L0099 | | Markup line defining structure in an HTML-like template file.

L0100 | </div> | Markup line defining structure in an HTML-like template file.

L0101 | </div> | Markup line defining structure in an HTML-like template file.

L0102 | </section> | Markup line defining structure in an HTML-like template file.

L0103 | | Blank line used for readability and logical separation.

L0104 | <section class="mt-4 mb-4"> | Assignment statement storing or updating program state.

L0105 | <div class="card form-access-card"> | Assignment statement storing or updating program state.

L0106 | <div class="card-body d-flex justify-content-between align-items-center gap-3 flex-wrap"> | Assignment statement storing or updating program state.

L0107 | <div> | Markup line defining structure in an HTML-like template file.

L0108 | <h3 class="mb-1">Approved Forms Excel Tracker</h3> | Assignment statement storing or updating program state.

L0109 | <p class="text-muted mb-0">Download approved PM/RCA forms in Excel.</p> | Assignment statement storing or updating program
L0110 | </div> | Markup line defining structure in an HTML-like template file.
L0111 | | Assignment statement storing or upda
L0112 | <i class="bi bi-file-earmark-excel"></i> Download Excel | Assignment statement storing or updating program state.
L0113 | | Markup line defining structure in an HTML-like template file.
L0114 | </div> | Markup line defining structure in an HTML-like template file.
L0115 | </div> | Markup line defining structure in an HTML-like template file.
L0116 | </section> | Markup line defining structure in an HTML-like template file.
L0117 | | Blank line used for readability and logical separation.
L0118 | {% if not staff_has_form_data %} | Block delimiter controlling scope/structure in this language.
L0119 | <div class="alert alert-info mt-3 mb-0" role="alert"> | Assignment statement storing or updating program state.
L0120 | No recent forms have been submitted by field technicians yet. PM RCA, approved, and rejected lists will populate automatically af
L0121 | </div> | Markup line defining structure in an HTML-like template file.
L0122 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0123 | | Blank line used for readability and logical separation.
L0124 | <p class="text-center text-muted small mt-4 mb-0"> | Assignment statement storing or updating program state.
L0125 | Dashboard Footnote: {{ (current_role or 'staff')\|replace('_', ' ')\|title }} | Block delimiter controlling scope/structure in th
L0126 | </p> | Markup line defining structure in an HTML-like template file.
L0127 | </div> | Markup line defining structure in an HTML-like template file.
L0128 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 115: templates/technician_activity_view.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <section class="dashboard-hero-lite"> | Assignment statement storing or updating program state.
L0004 |   <h1>{{ activity.activity_type|upper }} Form #{{ activity.id }}</h1> | Markup line defining structure in an HTML-like template fi
L0005 |   <p class="text-muted mb-0">Submitted by you on {{ activity.created_at.strftime('%Y-%m-%d %H:%M:%S') if activity.created_at else '
L0006 | </section> | Markup line defining structure in an HTML-like template file.
L0007 | | Blank line used for readability and logical separation.
L0008 | <div class="card mt-3"> | Assignment statement storing or updating program state.
L0009 |   <div class="card-body"> | Assignment statement storing or updating program state.
L0010 |     <div class="d-flex flex-wrap gap-2 mb-3"> | Assignment statement storing or updating program state.
L0011 |       <a class="btn btn-outline-secondary" href="{{ url_for('dashboard') }}"><i class="bi bi-house"></i> Dashboard</a> | Assignment
L0012 |       <a class="btn btn-outline-secondary" href="{{ url_for('technician_rejected_reports') }}"><i class="bi bi-arrow-left"></i> Rej
L0013 |       {% if activity.approved_at and activity.is_approved %} | Block delimiter controlling scope/structure in this language.
L0014 |         <span class="badge text-bg-success align-self-center">Approved</span> | Assignment statement storing or updating program st
L0015 |       {% elif activity.approved_at and (not activity.is_approved) %} | Block delimiter controlling scope/structure in this language
L0016 |         <span class="badge text-bg-danger align-self-center">Rejected</span> | Assignment statement storing or updating program sta
L0017 |       {% else %} | Block delimiter controlling scope/structure in this language.
L0018 |         <span class="badge text-bg-warning text-dark align-self-center">Pending Review</span> | Assignment statement storing or up
L0019 |       {% endif %} | Block delimiter controlling scope/structure in this language.
L0020 |     </div> | Markup line defining structure in an HTML-like template file.
L0021 | | Blank line used for readability and logical separation.
L0022 |     <h5 class="mb-2">Form Details</h5> | Assignment statement storing or updating program state.
L0023 |     <pre class="mb-0" style="white-space: pre-wrap; word-break: break-word;">{{ activity.details }}</pre> | Assignment statement st
L0024 |   </div> | Markup line defining structure in an HTML-like template file.
L0025 | </div> | Markup line defining structure in an HTML-like template file.
L0026 | {% endblock %} | Block delimiter controlling scope/structure in this language.
```

File 116: templates/technician_calendar.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <section class="dashboard-hero-lite"> | Assignment statement storing or updating program state.
L0004 |   <h1>Technician Calendar</h1> | Markup line defining structure in an HTML-like template file.
L0005 |   <p class="text-muted mb-0">Public holiday schedule for planning PM/RCA field work.</p> | Assignment statement storing or updating
L0006 | </section> | Markup line defining structure in an HTML-like template file.
L0007 | | Blank line used for readability and logical separation.
L0008 | <div class="card detail-card mt-3"> | Assignment statement storing or updating program state.
L0009 |   <div class="card-body"> | Assignment statement storing or updating program state.
L0010 |     {% if holidays %} | Block delimiter controlling scope/structure in this language.
L0011 |       <div class="table-responsive"> | Assignment statement storing or updating program state.
L0012 |         <table class="table table-hover align-middle mb-0"> | Assignment statement storing or updating program state.
L0013 |           <thead> | Markup line defining structure in an HTML-like template file.
L0014 |             <tr> | Markup line defining structure in an HTML-like template file.
L0015 |               <th>Date</th> | Markup line defining structure in an HTML-like template file.
L0016 |               <th>Holiday</th> | Markup line defining structure in an HTML-like template file.
L0017 |             </tr> | Markup line defining structure in an HTML-like template file.
L0018 |           </thead> | Markup line defining structure in an HTML-like template file.
L0019 |           <tbody> | Markup line defining structure in an HTML-like template file.
L0020 |             {% for item in holidays %} | Block delimiter controlling scope/structure in this language.
L0021 |               <tr> | Markup line defining structure in an HTML-like template file.
L0022 |                 <td>{{ item.date }}</td> | Markup line defining structure in an HTML-like template file.
L0023 |                 <td>{{ item.name }}</td> | Markup line defining structure in an HTML-like template file.
L0024 |               </tr> | Markup line defining structure in an HTML-like template file.
L0025 |             {% endfor %} | Block delimiter controlling scope/structure in this language.
L0026 |           </tbody> | Markup line defining structure in an HTML-like template file.
L0027 |         </table> | Markup line defining structure in an HTML-like template file.
L0028 |       </div> | Markup line defining structure in an HTML-like template file.
L0029 |     {% else %} | Block delimiter controlling scope/structure in this language.
L0030 |       <p class="mb-0 text-muted">No calendar holidays available yet.</p> | Assignment statement storing or updating program state.
L0031 |     {% endif %} | Block delimiter controlling scope/structure in this language.
L0032 |   </div> | Markup line defining structure in an HTML-like template file.
L0033 | </div> | Markup line defining structure in an HTML-like template file.
L0034 | {% endblock %} | Block delimiter controlling scope/structure in this language.
```

File 117: templates/technician_dashboard.html

```
L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <div class="role-dashboard-shell role-technician"> | Assignment statement storing or updating program state.
L0004 | <section class="dashboard-hero-lite"> | Assignment statement storing or updating program state.
L0005 |   <h1>Hello, {{ user_name }}. Welcome back!</h1> | Markup line defining structure in an HTML-like template file.
L0006 | </section> | Markup line defining structure in an HTML-like template file.
L0007 | | Blank line used for readability and logical separation.
L0008 | <div class="row row-cols-1 row-cols-md-2 row-cols-xl-4 g-3 mt-1"> | Assignment statement storing or updating program state.
L0009 |   <div class="col"> | Assignment statement storing or updating program state.
L0010 |     <a href="{{ url_for('technician_calendar') }}" class="card-link"> | Assignment statement storing or updating program state.
L0011 |       <div class="card stats-card"> | Assignment statement storing or updating program state.
L0012 |         <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0013 |           <div class="stats-icon"><i class="bi bi-calendar-event"></i></div> | Assignment statement storing or updating program state.
L0014 |           <h1>{{ public_holidays|length }}</h1> | Markup line defining structure in an HTML-like template file.
L0015 |           <p>Calendar Holidays</p> | Markup line defining structure in an HTML-like template file.
L0016 |         </div> | Markup line defining structure in an HTML-like template file.
L0017 |       </div> | Markup line defining structure in an HTML-like template file.
L0018 |     </a> | Markup line defining structure in an HTML-like template file.
L0019 |   </div> | Markup line defining structure in an HTML-like template file.
L0020 | <div class="col"> | Assignment statement storing or updating program state.
L0021 |   <a href="{{ url_for('technician_submissions', type='pm') }}" class="card-link"> | Assignment statement storing or updating program state.
L0022 |     <div class="card stats-card"> | Assignment statement storing or updating program state.
L0023 |       <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0024 |         <div class="stats-icon"><i class="bi bi-tools"></i></div> | Assignment statement storing or updating program state.
L0025 |         <h1>{{ technician_stats.pm }}</h1> | Markup line defining structure in an HTML-like template file.
L0026 |         <p>PM Forms</p> | Markup line defining structure in an HTML-like template file.
L0027 |       </div> | Markup line defining structure in an HTML-like template file.
L0028 |     </div> | Markup line defining structure in an HTML-like template file.
L0029 |   </a> | Markup line defining structure in an HTML-like template file.
L0030 | </div> | Markup line defining structure in an HTML-like template file.
L0031 | <div class="col"> | Assignment statement storing or updating program state.
L0032 |   <a href="{{ url_for('technician_submissions', type='rca') }}" class="card-link"> | Assignment statement storing or updating program state.
L0033 |     <div class="card stats-card"> | Assignment statement storing or updating program state.
L0034 |       <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0035 |         <div class="stats-icon"><i class="bi bi-exclamation-triangle"></i></div> | Assignment statement storing or updating program state.
L0036 |         <h1>{{ technician_stats.rca }}</h1> | Markup line defining structure in an HTML-like template file.
L0037 |         <p>RCA Forms</p> | Markup line defining structure in an HTML-like template file.
L0038 |       </div> | Markup line defining structure in an HTML-like template file.
L0039 |     </div> | Markup line defining structure in an HTML-like template file.
L0040 |   </a> | Markup line defining structure in an HTML-like template file.
L0041 | </div> | Markup line defining structure in an HTML-like template file.
L0042 | <div class="col"> | Assignment statement storing or updating program state.
L0043 |   <a href="{{ url_for('technician_submissions', type='all') }}" class="card-link"> | Assignment statement storing or updating program state.
L0044 |     <div class="card stats-card"> | Assignment statement storing or updating program state.
L0045 |       <div class="card-body text-center"> | Assignment statement storing or updating program state.
L0046 |         <div class="stats-icon"><i class="bi bi-journal-plus"></i></div> | Assignment statement storing or updating program state.
L0047 |         <h1>{{ technician_stats.total }}</h1> | Markup line defining structure in an HTML-like template file.
L0048 |         <p>Total PM/RCA</p> | Markup line defining structure in an HTML-like template file.
L0049 |       </div> | Markup line defining structure in an HTML-like template file.
L0050 |     </div> | Markup line defining structure in an HTML-like template file.
L0051 |   </a> | Markup line defining structure in an HTML-like template file.
L0052 | </div> | Markup line defining structure in an HTML-like template file.
L0053 | <div class="col"> | Assignment statement storing or updating program state.
```

L0054 | | Assignment statement storing or updating program state.

L0055 | <div class="card stats-card"> | Assignment statement storing or updating program state.

L0056 | <div class="card-body text-center"> | Assignment statement storing or updating program state.

L0057 | <div class="stats-icon"><i class="bi bi-x-octagon"></i></div> | Assignment statement storing or updating program state.

L0058 | <h1>{{ technician_stats.rejected }}</h1> | Markup line defining structure in an HTML-like template file.

L0059 | <p>Rejected PM/RCA</p> | Markup line defining structure in an HTML-like template file.

L0060 | </div> | Markup line defining structure in an HTML-like template file.

L0061 | </div> | Markup line defining structure in an HTML-like template file.

L0062 | | Markup line defining structure in an HTML-like template file.

L0063 | </div> | Markup line defining structure in an HTML-like template file.

L0064 | </div> | Markup line defining structure in an HTML-like template file.

L0065 | | Blank line used for readability and logical separation.

L0066 | <section class="mt-3 mb-4"> | Assignment statement storing or updating program state.

L0067 | <div class="card settings-card folded-calendar-card"> | Assignment statement storing or updating program state.

L0068 | <div class="card-body"> | Assignment statement storing or updating program state.

L0069 | <div class="d-flex justify-content-between align-items-center gap-3 flex-wrap mb-2"> | Assignment statement storing or updating program state.

L0070 | <div> | Markup line defining structure in an HTML-like template file.

L0071 | <h3 class="mb-1"><i class="bi bi-calendar3"></i> Technician Calendar</h3> | Assignment statement storing or updating program state.

L0072 | <p class="text-muted mb-0">View public holidays while planning PM/RCA work.</p> | Assignment statement storing or updating program state.

L0073 | </div> | Markup line defining structure in an HTML-like template file.

L0074 | | Assignment statement storing or updating program state.

L0075 | Full Calendar Page | Operational statement participating in the file's runtime behavior.

L0076 | | Markup line defining structure in an HTML-like template file.

L0077 | </div> | Markup line defining structure in an HTML-like template file.

L0078 | <div class="holiday-calendar holiday-calendar-full"> | Assignment statement storing or updating program state.

L0079 | <div class="calendar-book"> | Assignment statement storing or updating program state.

L0080 | <div class="calendar-toolbar"> | Assignment statement storing or updating program state.

L0081 | <button type="button" class="btn btn-sm btn-outline-primary calendar-nav calendar-nav-prev"><i class="bi bi-chevron-left"></i> | Assignment statement storing or updating program state.

L0082 | <div class="calendar-month-label"></div> | Assignment statement storing or updating program state.

L0083 | <button type="button" class="btn btn-sm btn-outline-primary calendar-nav calendar-nav-next"><i class="bi bi-chevron-right"></i> | Assignment statement storing or updating program state.

L0084 | </div> | Markup line defining structure in an HTML-like template file.

L0085 | <div class="calendar-sheet"> | Assignment statement storing or updating program state.

L0086 | <div class="calendar-grid"></div> | Assignment statement storing or updating program state.

L0087 | </div> | Markup line defining structure in an HTML-like template file.

L0088 | </div> | Markup line defining structure in an HTML-like template file.

L0089 | <div class="calendar-holiday-list mt-3"></div> | Assignment statement storing or updating program state.

L0090 | </div> | Markup line defining structure in an HTML-like template file.

L0091 | </div> | Markup line defining structure in an HTML-like template file.

L0092 | </div> | Markup line defining structure in an HTML-like template file.

L0093 | </section> | Markup line defining structure in an HTML-like template file.

L0094 | | Blank line used for readability and logical separation.

L0095 | <section class="mt-4 mb-4"> | Assignment statement storing or updating program state.

L0096 | <div class="card form-access-card"> | Assignment statement storing or updating program state.

L0097 | <div class="card-body"> | Assignment statement storing or updating program state.

L0098 | <div class="d-flex justify-content-between align-items-center gap-3 flex-wrap"> | Assignment statement storing or updating program state.

L0099 | <div> | Markup line defining structure in an HTML-like template file.

L0100 | <h3 class="mb-1">Technician Site Form</h3> | Assignment statement storing or updating program state.

L0101 | <p class="text-muted mb-0">Fill and submit your PM/RCA form from here</p> | Assignment statement storing or updating program state.

L0102 | </div> | Markup line defining structure in an HTML-like template file.

L0103 | | Assignment statement storing or updating program state.

L0104 | <i class="bi bi-plus-circle"></i> Fill Form | Assignment statement storing or updating program state.

L0105 | | Markup line defining structure in an HTML-like template file.

L0106 | </div> | Markup line defining structure in an HTML-like template file.

L0107 | </div> | Markup line defining structure in an HTML-like template file.

L0108 | </div> | Markup line defining structure in an HTML-like template file.

```

L0109 | </section> | Markup line defining structure in an HTML-like template file.
L0110 | | Blank line used for readability and logical separation.
L0111 | <section class="mt-3 mb-4"> | Assignment statement storing or updating program state.
L0112 | <div class="card form-access-card"> | Assignment statement storing or updating program state.
L0113 | <div class="card-body"> | Assignment statement storing or updating program state.
L0114 | <div class="d-flex justify-content-between align-items-center gap-3 flex-wrap mb-3"> | Assignment statement storing or updating program state.
L0115 | <div> | Markup line defining structure in an HTML-like template file.
L0116 | <h3 class="mb-1">Submitted Forms</h3> | Assignment statement storing or updating program state.
L0117 | <p class="text-muted mb-0">Your latest PM/RCA submissions and their review status</p> | Assignment statement storing or updating program state.
L0118 | </div> | Markup line defining structure in an HTML-like template file.
L0119 | <a href="{ url_for('technician_submissions', type='all') }" class="btn btn-outline-primary btn-sm"> | Assignment statement storing or updating program state.
L0120 | View All Submissions | Operational statement participating in the file's runtime behavior.
L0121 | </a> | Markup line defining structure in an HTML-like template file.
L0122 | </div> | Markup line defining structure in an HTML-like template file.
L0123 | | Blank line used for readability and logical separation.
L0124 | {% if recent_submissions %} | Block delimiter controlling scope/structure in this language.
L0125 | <div class="table-responsive"> | Assignment statement storing or updating program state.
L0126 | <table class="table table-hover align-middle mb-0"> | Assignment statement storing or updating program state.
L0127 | <thead> | Markup line defining structure in an HTML-like template file.
L0128 | <tr> | Markup line defining structure in an HTML-like template file.
L0129 | <th>#</th> | Markup line defining structure in an HTML-like template file.
L0130 | <th>Type</th> | Markup line defining structure in an HTML-like template file.
L0131 | <th>Submitted</th> | Markup line defining structure in an HTML-like template file.
L0132 | <th>Status</th> | Markup line defining structure in an HTML-like template file.
L0133 | <th class="text-end">Action</th> | Assignment statement storing or updating program state.
L0134 | </tr> | Markup line defining structure in an HTML-like template file.
L0135 | </thead> | Markup line defining structure in an HTML-like template file.
L0136 | <tbody> | Markup line defining structure in an HTML-like template file.
L0137 | {% for item in recent_submissions %} | Block delimiter controlling scope/structure in this language.
L0138 | <tr> | Markup line defining structure in an HTML-like template file.
L0139 | <td>{{ item.id }}</td> | Markup line defining structure in an HTML-like template file.
L0140 | <td>{{ item.activity_type\upper }}</td> | Markup line defining structure in an HTML-like template file.
L0141 | <td>{{ item.created_at.strftime('%Y-%m-%d %H:%M') if item.created_at else '' }}</td> | Markup line defining structure in an HTML-like template file.
L0142 | <td> | Markup line defining structure in an HTML-like template file.
L0143 | {% if item.approved_at and item.is_approved %} | Block delimiter controlling scope/structure in this language.
L0144 | <span class="badge text-bg-success">Approved</span> | Assignment statement storing or updating program state.
L0145 | {% elif item.approved_at and (not item.is_approved) %} | Block delimiter controlling scope/structure in this language.
L0146 | <span class="badge text-bg-danger">Rejected</span> | Assignment statement storing or updating program state.
L0147 | {% else %} | Block delimiter controlling scope/structure in this language.
L0148 | <span class="badge text-bg-warning text-dark">Pending</span> | Assignment statement storing or updating program state.
L0149 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0150 | </td> | Markup line defining structure in an HTML-like template file.
L0151 | <td class="text-end"> | Assignment statement storing or updating program state.
L0152 | <a href="{ url_for('technician_activity_view', activity_id=item.id) }" class="btn btn-sm btn-outline-primary"> | Assignment statement storing or updating program state.
L0153 | <i class="bi bi-eye"></i> Open | Assignment statement storing or updating program state.
L0154 | </a> | Markup line defining structure in an HTML-like template file.
L0155 | </td> | Markup line defining structure in an HTML-like template file.
L0156 | </tr> | Markup line defining structure in an HTML-like template file.
L0157 | {% endfor %} | Block delimiter controlling scope/structure in this language.
L0158 | </tbody> | Markup line defining structure in an HTML-like template file.
L0159 | </table> | Markup line defining structure in an HTML-like template file.
L0160 | </div> | Markup line defining structure in an HTML-like template file.
L0161 | {% else %} | Block delimiter controlling scope/structure in this language.
L0162 | <p class="mb-0 text-muted">No PM/RCA forms submitted yet. Start with Fill Form above.</p> | Assignment statement storing or updating program state.
L0163 | {% endif %} | Block delimiter controlling scope/structure in this language.

```

L0164 | </div> | Markup line defining structure in an HTML-like template file.

L0165 | </div> | Markup line defining structure in an HTML-like template file.

L0166 | </section> | Markup line defining structure in an HTML-like template file.

L0167 | | Blank line used for readability and logical separation.

L0168 | <section class="mt-3 mb-4"> | Assignment statement storing or updating program state.

L0169 | <div class="card form-access-card"> | Assignment statement storing or updating program state.

L0170 | <div class="card-body"> | Assignment statement storing or updating program state.

L0171 | <div class="d-flex justify-content-between align-items-center gap-3 flex-wrap"> | Assignment statement storing or updating program state.

L0172 | <div> | Markup line defining structure in an HTML-like template file.

L0173 | <h3 class="mb-1">Settings</h3> | Assignment statement storing or updating program state.

L0174 | <p class="text-muted mb-0">Manage language and appearance preferences</p> | Assignment statement storing or updating program state.

L0175 | </div> | Markup line defining structure in an HTML-like template file.

L0176 | <div class="d-flex gap-2 flex-wrap"> | Assignment statement storing or updating program state.

L0177 | | Assignment statement storing or updating program state.

L0178 | <i class="bi bi-gear-fill"></i> Open Settings | Assignment statement storing or updating program state.

L0179 | | Markup line defining structure in an HTML-like template file.

L0180 | | Assignment statement storing or updating program state.

L0181 | <i class="bi bi-calendar3"></i> Open Calendar | Assignment statement storing or updating program state.

L0182 | | Markup line defining structure in an HTML-like template file.

L0183 | </div> | Markup line defining structure in an HTML-like template file.

L0184 | </div> | Markup line defining structure in an HTML-like template file.

L0185 | </div> | Markup line defining structure in an HTML-like template file.

L0186 | </div> | Markup line defining structure in an HTML-like template file.

L0187 | </section> | Markup line defining structure in an HTML-like template file.

L0188 | | Blank line used for readability and logical separation.

L0189 | <p class="text-center text-muted small mt-4 mb-0"> | Assignment statement storing or updating program state.

L0190 | Dashboard Footnote: {{ (current_role or 'technician')\|replace('_', ' ')\|title }} | Block delimiter controlling scope/structure

L0191 | </p> | Markup line defining structure in an HTML-like template file.

L0192 | </div> | Markup line defining structure in an HTML-like template file.

L0193 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 118: templates/technician_rejected_reports.html

L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.
L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.
L0003 | <section class="dashboard-hero-lite"> | Assignment statement storing or updating program state.
L0004 | <h1>Your Rejected PM/RCA Reports</h1> | Markup line defining structure in an HTML-like template file.
L0005 | </section> | Markup line defining structure in an HTML-like template file.
L0006 | | Blank line used for readability and logical separation.
L0007 | <div class="card detail-card mt-3"> | Assignment statement storing or updating program state.
L0008 | <div class="card-body"> | Assignment statement storing or updating program state.
L0009 | {% if reports %} | Block delimiter controlling scope/structure in this language.
L0010 | <div class="table-responsive"> | Assignment statement storing or updating program state.
L0011 | <table class="table table-hover align-middle"> | Assignment statement storing or updating program state.
L0012 | <thead> | Markup line defining structure in an HTML-like template file.
L0013 | <tr> | Markup line defining structure in an HTML-like template file.
L0014 | <th>#</th> | Markup line defining structure in an HTML-like template file.
L0015 | <th>Type</th> | Markup line defining structure in an HTML-like template file.
L0016 | <th>Submitted</th> | Markup line defining structure in an HTML-like template file.
L0017 | <th>Reviewed</th> | Markup line defining structure in an HTML-like template file.
L0018 | <th>Details</th> | Markup line defining structure in an HTML-like template file.
L0019 | <th class="text-end">Action</th> | Assignment statement storing or updating program state.
L0020 | </tr> | Markup line defining structure in an HTML-like template file.
L0021 | </thead> | Markup line defining structure in an HTML-like template file.
L0022 | <tbody> | Markup line defining structure in an HTML-like template file.
L0023 | {% for item in reports %} | Block delimiter controlling scope/structure in this language.
L0024 | <tr> | Markup line defining structure in an HTML-like template file.
L0025 | <td>{{ item.id }}</td> | Markup line defining structure in an HTML-like template file.
L0026 | <td>{{ item.activity_type|upper }}</td> | Markup line defining structure in an HTML-like template file.
L0027 | <td>{{ item.created_at.strftime('%Y-%m-%d %H:%M') if item.created_at else '' }}</td> | Markup line defining structure in an HTML-like template file.
L0028 | <td>{{ item.approved_at.strftime('%Y-%m-%d %H:%M') if item.approved_at else '' }}</td> | Markup line defining structure in an HTML-like template file.
L0029 | <td>{{ (item.details or '')[:120] }}{% if (item.details or '')|length > 120 %}...{% endif %}</td> | Markup line defining structure in an HTML-like template file.
L0030 | <td class="text-end"> | Assignment statement storing or updating program state.
L0031 | | Assignment statement storing or updating program state.
L0032 | <i class="bi bi-eye"></i> Open | Assignment statement storing or updating program state.
L0033 | | Markup line defining structure in an HTML-like template file.
L0034 | </td> | Markup line defining structure in an HTML-like template file.
L0035 | </tr> | Markup line defining structure in an HTML-like template file.
L0036 | {% endfor %} | Block delimiter controlling scope/structure in this language.
L0037 | </tbody> | Markup line defining structure in an HTML-like template file.
L0038 | </table> | Markup line defining structure in an HTML-like template file.
L0039 | </div> | Markup line defining structure in an HTML-like template file.
L0040 | {% else %} | Block delimiter controlling scope/structure in this language.
L0041 | <p class="mb-0 text-muted">No rejected PM/RCA reports for your account.</p> | Assignment statement storing or updating program state.
L0042 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0043 | </div> | Markup line defining structure in an HTML-like template file.
L0044 | </div> | Markup line defining structure in an HTML-like template file.
L0045 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 119: templates/technician_submissions.html

L0001 | {% extends 'layout.html' %} | Block delimiter controlling scope/structure in this language.

L0002 | {% block content %} | Block delimiter controlling scope/structure in this language.

L0003 | <section class="dashboard-hero-lite"> | Assignment statement storing or updating program state.

L0004 | <h1>My Submitted PM/RCA Forms</h1> | Markup line defining structure in an HTML-like template file.

L0005 | </section> | Markup line defining structure in an HTML-like template file.

L0006 | | Blank line used for readability and logical separation.

L0007 | <div class="d-flex gap-2 flex-wrap mt-3"> | Assignment statement storing or updating program state.

L0008 | | Assignment statement storing or updating program state.

L0009 | All | Operational statement participating in the file's runtime behavior.

L0010 | | Markup line defining structure in an HTML-like template file.

L0011 | | Assignment statement storing or updating program state.

L0012 | PM | Operational statement participating in the file's runtime behavior.

L0013 | | Markup line defining structure in an HTML-like template file.

L0014 | | Assignment statement storing or updating program state.

L0015 | RCA | Operational statement participating in the file's runtime behavior.

L0016 | | Markup line defining structure in an HTML-like template file.

L0017 | | Assignment statement storing or updating program state.

L0018 | <i class="bi bi-plus-circle"></i> New Form | Assignment statement storing or updating program state.

L0019 | | Markup line defining structure in an HTML-like template file.

L0020 | </div> | Markup line defining structure in an HTML-like template file.

L0021 | | Blank line used for readability and logical separation.

L0022 | <div class="card detail-card mt-3"> | Assignment statement storing or updating program state.

L0023 | <div class="card-body"> | Assignment statement storing or updating program state.

L0024 | {% if reports %} | Block delimiter controlling scope/structure in this language.

L0025 | <div class="table-responsive"> | Assignment statement storing or updating program state.

L0026 | <table class="table table-hover align-middle mb-0"> | Assignment statement storing or updating program state.

L0027 | <thead> | Markup line defining structure in an HTML-like template file.

L0028 | <tr> | Markup line defining structure in an HTML-like template file.

L0029 | <th>#</th> | Markup line defining structure in an HTML-like template file.

L0030 | <th>Type</th> | Markup line defining structure in an HTML-like template file.

L0031 | <th>Submitted</th> | Markup line defining structure in an HTML-like template file.

L0032 | <th>Status</th> | Markup line defining structure in an HTML-like template file.

L0033 | <th class="text-end">Action</th> | Assignment statement storing or updating program state.

L0034 | </tr> | Markup line defining structure in an HTML-like template file.

L0035 | </thead> | Markup line defining structure in an HTML-like template file.

L0036 | <tbody> | Markup line defining structure in an HTML-like template file.

L0037 | {% for item in reports %} | Block delimiter controlling scope/structure in this language.

L0038 | <tr> | Markup line defining structure in an HTML-like template file.

L0039 | <td>{{ item.id }}</td> | Markup line defining structure in an HTML-like template file.

L0040 | <td>{{ item.activity_type|upper }}</td> | Markup line defining structure in an HTML-like template file.

L0041 | <td>{{ item.created_at.strftime('%Y-%m-%d %H:%M') if item.created_at else '' }}</td> | Markup line defining structure in an HTML-like template file.

L0042 | <td> | Markup line defining structure in an HTML-like template file.

L0043 | {% if item.approved_at and item.is_approved %} | Block delimiter controlling scope/structure in this language.

L0044 | Approved | Assignment statement storing or updating program state.

L0045 | {% elif item.approved_at and (not item.is_approved) %} | Block delimiter controlling scope/structure in this language.

L0046 | Rejected | Assignment statement storing or updating program state.

L0047 | {% else %} | Block delimiter controlling scope/structure in this language.

L0048 | Pending | Assignment statement storing or updating program state.

L0049 | {% endif %} | Block delimiter controlling scope/structure in this language.

L0050 | </td> | Markup line defining structure in an HTML-like template file.

L0051 | <td class="text-end"> | Assignment statement storing or updating program state.

L0052 | | Assignment statement storing or updating program state.

L0053 | <i class="bi bi-eye"></i> Open | Assignment statement storing or updating program state.

L0054 | | Markup line defining structure in an HTML-like template file.
L0055 | </td> | Markup line defining structure in an HTML-like template file.
L0056 | </tr> | Markup line defining structure in an HTML-like template file.
L0057 | {% endfor %} | Block delimiter controlling scope/structure in this language.
L0058 | </tbody> | Markup line defining structure in an HTML-like template file.
L0059 | </table> | Markup line defining structure in an HTML-like template file.
L0060 | </div> | Markup line defining structure in an HTML-like template file.
L0061 | {% else %} | Block delimiter controlling scope/structure in this language.
L0062 | <p class="mb-0 text-muted">No submissions found for this filter.</p> | Assignment statement storing or updating program state
L0063 | {% endif %} | Block delimiter controlling scope/structure in this language.
L0064 | </div> | Markup line defining structure in an HTML-like template file.
L0065 | </div> | Markup line defining structure in an HTML-like template file.
L0066 | {% endblock %} | Block delimiter controlling scope/structure in this language.

File 120: test_all_output.txt

L0001 | ■.venv\Scripts\python : ImportError while loading conftest | Operational statement participating in the file's runtime behavior.

L0002 | 'C:\Users\jonas\OneDrive\Desktop\pm\tests\conftest.py'. | Operational statement participating in the file's runtime behavior.

L0003 | At line:1 char:1 | Operational statement participating in the file's runtime behavior.

L0004 | + .venv\Scripts\python -m pytest tests/test_auth.py -v --tb=short 2>&1 ... | Assignment statement storing or updating program state

L0005 | + ~~~~~ | Operational statement participating in the file's runtime behavior.

L0006 | + CategoryInfo : NotSpecified: (ImportError whi...s\conftest.py'. | Operational statement participating in the file's runtime behavior.

L0007 | :String) [], RemoteException | Operational statement participating in the file's runtime behavior.

L0008 | + FullyQualifiedErrorId : NativeCommandError | Operational statement participating in the file's runtime behavior.

L0009 | | Blank line used for readability and logical separation.

L0010 | tests\conftest.py:6: in <module> | Operational statement participating in the file's runtime behavior.

L0011 | from app import create_app | Imports specific names from another module for direct usage.

L0012 | E File "C:\Users\jonas\OneDrive\Desktop\pm\app.py", line 1250 | Operational statement participating in the file's runtime behavior.

L0013 | E).count() | Operational statement participating in the file's runtime behavior.

L0014 | E ^ | Operational statement participating in the file's runtime behavior.

L0015 | E SyntaxError: closing parenthesis ')' does not match opening parenthesis | Operational statement participating in the file's runtime behavior.

L0016 | '{' on line 1226 | Operational statement participating in the file's runtime behavior.

File 121: test_full_out.txt

```
L0001 | yb.....Fp | Operational statement participating in the file's runtime behavior.
```

```
L0002 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0003 | ██████████ F A I L U R E S ██████████
```

```
L0004 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0005 | ████████ t h e s t _ s e n d e r _ c a n _ d e l e t e _ o w n _ m e s s a g e █
```

```
L0006 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0007 | t h e s t _ s \ t h e s t _ n o t i f i c a t i o n s . p l a y : 2 2 6 : █ i n t h e s t _ s e n d e r _ c a n _ d e l e t e
```

```
L0008 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0009 | █ █ █ W a s s e r t " M e s s a g e _ d e l e t e d . " i n r e s p o n s e . g e t _ d a t a ( W a s _ t e x
```

```
L0010 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0011 | E █ █ W a s s e r t ' M e s s a g e _ d e l e t e d . ' i n ' < ! D O C T Y P E h t m l > \ n < h t m l
```

```
L0012 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0013 | E █ █ █ + █ w h e r e ' < ! D O C T Y P E h t m l > \ n < h t m l l a n g = " e n " > \ n █ < h e a d
```

```
L0014 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0015 | E █ █ █ + █ w h e r e g e t _ d a t a = < w r a p p e r T e s t R e s p o n s e 3 7 0 0 4 b y t
```

```
L0016 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0017 | - - - - - C a p t u r e d l o g s e t u p - - - - -
```

```
L0018 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0019 | W A R N I N G █ a p p : a p p . p l a y : 1 0 7 1 C o u l d n o t l o a d p e r s i s t e n t d e v e l o p
```

```
L0020 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0021 | [ S Q L : S E L E C T u s e r _ s e t t i n g s . i d A S u s e r _ s e t t i n g s . i d , u s e r _ s
```

```
L0022 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0023 | F R O M u s e r _ s e t t i n g s J O I N u s e r s O N u s e r _ s e t t i n g s . u s e r _ i d =
```

```
L0024 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0025 | W H E R E u s e r s . r o l e = ? O R D E R B Y u s e r _ s e t t i n g s . u p d a t e d _ a t D E
```

```
L0026 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0027 | █ L I M I T ? O F F S E T ? ] | Operational statement participating in the file's runtime behavior.
```

```
L0028 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0029 | [ p a r a m e t e r s : ('d e v e l o p e r ' , 1 , 0 ) ] | Operational statement participating in the file's r
```

```
L0030 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0031 | ( B a c k g r o u n d o n t h i s e r r o r a t : h t t p s : / / s q l a l c h e . m e / e / 2 0 / e 3
```

```
L0032 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0033 | ██████████ s h o r t t h e s t _ s u m m a r y i n f o ██████████
```

```
L0034 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0035 | F A I L E D t h e s t _ n o t i f i c a t i o n s . p l a y : t h e s t _ s e n d e r _ c a n _ d e l e t e
```

```
L0036 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0037 | !!!!!! s t o p p i n g a f t e r 1 f a i l u r e s !!!!!!
```

```
L0038 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0039 | 1 f a i l e d , 1 9 p a s s e d i n 1 5 1 . 6 9 s ( 0 : 0 2 : 3 1 ) | Operational statement participating
```

```
L0040 | █ | Operational statement participating in the file's runtime behavior.
```

```
L0041 | █ | Operational statement participating in the file's runtime behavior.
```

File 122: test_full_out2.txt

[illegible]

File 123: test_output.txt

```
L0001 | ■===== test session starts ===== | Operational statement participating in the file's runtime behavior.
L0002 | platform win32 -- Python 3.14.0, pytest-9.0.2, pluggy-1.6.0 -- C:\Users\jonas\OneDrive\Desktop\pm\.venv\Scripts\python.exe | Operat
L0003 | cachedir: .pytest_cache | Operational statement participating in the file's runtime behavior.
L0004 | rootdir: C:\Users\jonas\OneDrive\Desktop\pm | Operational statement participating in the file's runtime behavior.
L0005 | collecting ... collected 1 item | Operational statement participating in the file's runtime behavior.
L0006 | | Blank line used for readability and logical separation.
L0007 | tests/test_auth.py::test_user_settings_persist_in_database ERROR [100%] | Operational statement participating in the file's runtime behavior.
L0008 | | Blank line used for readability and logical separation.
L0009 | ===== ERRORS ===== | Operational statement participating in the file's runtime behavior.
L0010 | _____ ERROR at setup of test_user_settings_persist_in_database _____ | Operational statement participating in the file's runtime behavior.
L0011 | tests\conftest.py:21: in app | Operational statement participating in the file's runtime behavior.
L0012 |     app = create_app( | Assignment statement storing or updating program state.
L0013 | app.py:1129: in create_app | Operational statement participating in the file's runtime behavior.
L0014 |     get_live_dashboard_counts=get_live_dashboard_counts, | Assignment statement storing or updating program state.
L0015 |         ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^ | Operational statement participating in the file's runtime behavior.
L0016 | E UnboundLocalError: cannot access local variable 'get_live_dashboard_counts' where it is not associated with a value | Operational statement participating in the file's runtime behavior.
L0017 | ===== short test summary info ===== | Operational statement participating in the file's runtime behavior.
L0018 | ERROR tests/test_auth.py::test_user_settings_persist_in_database - UnboundLoc... | Operational statement participating in the file's runtime behavior.
L0019 | ===== 1 error in 1.80s ===== | Operational statement participating in the file's runtime behavior.
```

File 124: test_reset_out.txt

[illegible]

File 125: test_settings_output.txt

```
L0001 | ■===== test session starts ===== | Operational statement participating in the file's runtime behavior.
L0002 | platform win32 -- Python 3.14.0, pytest-9.0.2, pluggy-1.6.0 -- C:\Users\jonas\OneDrive\Desktop\pm\.venv\Scripts\python.exe | Operat
L0003 | cachedir: .pytest_cache | Operational statement participating in the file's runtime behavior.
L0004 | rootdir: C:\Users\jonas\OneDrive\Desktop\pm | Operational statement participating in the file's runtime behavior.
L0005 | collecting ... collected 1 item | Operational statement participating in the file's runtime behavior.
L0006 | | Blank line used for readability and logical separation.
L0007 | tests/test_auth.py::test_user_settings_persist_in_database ERROR [100%] | Operational statement participating in the file's runtime behavior.
L0008 | | Blank line used for readability and logical separation.
L0009 | ===== ERRORS ===== | Operational statement participating in the file's runtime behavior.
L0010 | _____ ERROR at setup of test_user_settings_persist_in_database _____ | Operational statement participating in the file's runtime behavior.
L0011 | tests\conftest.py:21: in app | Operational statement participating in the file's runtime behavior.
L0012 |     app = create_app( | Assignment statement storing or updating program state.
L0013 | app.py:1129: in create_app | Operational statement participating in the file's runtime behavior.
L0014 |     get_live_dashboard_counts=get_live_dashboard_counts, | Assignment statement storing or updating program state.
L0015 |         ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^ | Operational statement participating in the file's runtime behavior.
L0016 | E UnboundLocalError: cannot access local variable 'get_live_dashboard_counts' where it is not associated with a value | Operational statement participating in the file's runtime behavior.
L0017 | ===== short test summary info ===== | Operational statement participating in the file's runtime behavior.
L0018 | ERROR tests/test_auth.py::test_user_settings_persist_in_database - UnboundLoc... | Operational statement participating in the file's runtime behavior.
L0019 | ===== 1 error in 1.51s ===== | Operational statement participating in the file's runtime behavior.
```


File 126: tests/conftest.py

```
L0001 | import re | Imports dependency modules: re.
L0002 | | Blank line used for readability and logical separation.
L0003 | import pytest | Imports dependency modules: pytest.
L0004 | from werkzeug.security import generate_password_hash | Imports specific names from another module for direct usage.
L0005 | | Blank line used for readability and logical separation.
L0006 | from app import create_app | Imports specific names from another module for direct usage.
L0007 | from model import Consumable, User, db | Imports specific names from another module for direct usage.
L0008 | | Blank line used for readability and logical separation.
L0009 | | Blank line used for readability and logical separation.
L0010 | def extract_hidden_input(html: str, field_name: str) -> str: | Declares a function/method as a reusable unit of behavior.
L0011 |     pattern = rf'name="{re.escape(field_name)}" value="([^\"]+)"' | Assignment statement storing or updating program state.
L0012 |     match = re.search(pattern, html) | Assignment statement storing or updating program state.
L0013 |     if not match: | Conditional branch that runs only when its condition is true.
L0014 |         raise AssertionError(f"Hidden field {field_name!r} was not found in response HTML") | Raises an explicit exception to signal an error.
L0015 |     return match.group(1) | Returns a value (or control) back to the caller.
L0016 | | Blank line used for readability and logical separation.
L0017 | | Blank line used for readability and logical separation.
L0018 | @pytest.fixture() | Decorator line that modifies the behavior of the definition below.
L0019 | def app(tmp_path): | Declares a function/method as a reusable unit of behavior.
L0020 |     database_path = tmp_path / "test_pm.sqlite" | Assignment statement storing or updating program state.
L0021 |     app = create_app( | Assignment statement storing or updating program state.
L0022 |         { | Block delimiter controlling scope/structure in this language.
L0023 |             "TESTING": True, | Operational statement participating in the file's runtime behavior.
L0024 |             "SECRET_KEY": "test-secret-key", | Operational statement participating in the file's runtime behavior.
L0025 |             "SQLALCHEMY_DATABASE_URI": f"sqlite:/// {database_path.as_posix()}", | Operational statement participating in the file's runtime behavior.
L0026 |             "SEED_SAMPLE_DATA": False, | Operational statement participating in the file's runtime behavior.
L0027 |             "WTF_CSRF_ENABLED": False, | Operational statement participating in the file's runtime behavior.
L0028 |             "PASSWORD_HASH_METHOD": "pbkdf2:sha256:1", | Operational statement participating in the file's runtime behavior.
L0029 |         } | Block delimiter controlling scope/structure in this language.
L0030 |     ) | Operational statement participating in the file's runtime behavior.
L0031 | | Blank line used for readability and logical separation.
L0032 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0033 |         db.session.remove() | Operational statement participating in the file's runtime behavior.
L0034 |         db.drop_all() | Operational statement participating in the file's runtime behavior.
L0035 |         db.create_all() | Operational statement participating in the file's runtime behavior.
L0036 | | Blank line used for readability and logical separation.
L0037 |     yield app | Operational statement participating in the file's runtime behavior.
L0038 | | Blank line used for readability and logical separation.
L0039 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0040 |         db.session.remove() | Operational statement participating in the file's runtime behavior.
L0041 | | Blank line used for readability and logical separation.
L0042 | | Blank line used for readability and logical separation.
L0043 | @pytest.fixture() | Decorator line that modifies the behavior of the definition below.
L0044 | def client(app): | Declares a function/method as a reusable unit of behavior.
L0045 |     return app.test_client() | Returns a value (or control) back to the caller.
L0046 | | Blank line used for readability and logical separation.
L0047 | | Blank line used for readability and logical separation.
L0048 | @pytest.fixture() | Decorator line that modifies the behavior of the definition below.
L0049 | def developer_user(app): | Declares a function/method as a reusable unit of behavior.
L0050 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0051 |         user = User( | Assignment statement storing or updating program state.
L0052 |             email="developer@example.com", | Assignment statement storing or updating program state.
L0053 |             full_name="Developer User", | Assignment statement storing or updating program state.
```

```
L0054 |         role="developer", | Assignment statement storing or updating program state.
L0055 |         password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0056 |     ) | Operational statement participating in the file's runtime behavior.
L0057 |     db.session.add(user) | Operational statement participating in the file's runtime behavior.
L0058 |     db.session.commit() | Operational statement participating in the file's runtime behavior.
L0059 |     return {"email": user.email, "password": "Password123!"} | Returns a value (or control) back to the caller.
L0060 | | Blank line used for readability and logical separation.
L0061 | | Blank line used for readability and logical separation.
L0062 | @pytest.fixture() | Decorator line that modifies the behavior of the definition below.
L0063 | def login_as_developer(client, developer_user): | Declares a function/method as a reusable unit of behavior.
L0064 |     def _login(): | Declares a function/method as a reusable unit of behavior.
L0065 |         response = client.get("/login?role=developer") | Assignment statement storing or updating program state.
L0066 |         assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0067 |         token = extract_hidden_input(response.get_data(as_text=True), "login_csrf_token") | Assignment statement storing or updating program state.
L0068 | | Blank line used for readability and logical separation.
L0069 |         response = client.post( | Assignment statement storing or updating program state.
L0070 |             "/login?role=developer", | Assignment statement storing or updating program state.
L0071 |             data={ | Assignment statement storing or updating program state.
L0072 |                 "email": developer_user["email"], | Operational statement participating in the file's runtime behavior.
L0073 |                 "password": developer_user["password"], | Operational statement participating in the file's runtime behavior.
L0074 |                 "account_type": "developer", | Operational statement participating in the file's runtime behavior.
L0075 |                 "login_csrf_token": token, | Operational statement participating in the file's runtime behavior.
L0076 |             }, | Operational statement participating in the file's runtime behavior.
L0077 |             follow_redirects=False, | Assignment statement storing or updating program state.
L0078 |         ) | Operational statement participating in the file's runtime behavior.
L0079 |         assert response.status_code == 302 | Operational statement participating in the file's runtime behavior.
L0080 |         assert "/dashboard/" in response.headers["Location"] | Operational statement participating in the file's runtime behavior.
L0081 |         return response | Returns a value (or control) back to the caller.
L0082 | | Blank line used for readability and logical separation.
L0083 |     return _login | Returns a value (or control) back to the caller.
L0084 | | Blank line used for readability and logical separation.
L0085 | | Blank line used for readability and logical separation.
L0086 | @pytest.fixture() | Decorator line that modifies the behavior of the definition below.
L0087 | def consumable_count(app): | Declares a function/method as a reusable unit of behavior.
L0088 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0089 |         return Consumable.query.count() | Returns a value (or control) back to the caller.
```

File 127: tests/test_auth.py

```
L0001 | from datetime import datetime, timedelta, timezone | Imports specific names from another module for direct usage.
L0002 | | Blank line used for readability and logical separation.
L0003 | from werkzeug.security import generate_password_hash | Imports specific names from another module for direct usage.
L0004 | | Blank line used for readability and logical separation.
L0005 | from model import Activity, Consumable, User, db, UserSettings | Imports specific names from another module for direct usage.
L0006 | | Blank line used for readability and logical separation.
L0007 | from conftest import extract_hidden_input | Imports specific names from another module for direct usage.
L0008 | | Blank line used for readability and logical separation.
L0009 | | Blank line used for readability and logical separation.
L0010 | def test_dashboard_redirects_anonymous_user(client): | Declares a function/method as a reusable unit of behavior.
L0011 |     response = client.get("/dashboard/", follow_redirects=False) | Assignment statement storing or updating program state.
L0012 |     assert response.status_code == 302 | Operational statement participating in the file's runtime behavior.
L0013 |     assert "/login" in response.headers["Location"] | Operational statement participating in the file's runtime behavior.
L0014 | | Blank line used for readability and logical separation.
L0015 | | Blank line used for readability and logical separation.
L0016 | def test_login_response_echoes_request_id_header(client): | Declares a function/method as a reusable unit of behavior.
L0017 |     response = client.get("/login", headers={"X-Request-ID": "req-123"}) | Assignment statement storing or updating program state.
L0018 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0019 |     assert response.headers["X-Request-ID"] == "req-123" | Operational statement participating in the file's runtime behavior.
L0020 | | Blank line used for readability and logical separation.
L0021 | | Blank line used for readability and logical separation.
L0022 | def test_login_page_lists_all_supported_account_types(client): | Declares a function/method as a reusable unit of behavior.
L0023 |     response = client.get("/login") | Assignment statement storing or updating program state.
L0024 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0025 |     body = response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0026 |     assert 'value="developer"' in body | Assignment statement storing or updating program state.
L0027 |     assert 'value="staff"' in body | Assignment statement storing or updating program state.
L0028 |     assert 'value="manager"' in body | Assignment statement storing or updating program state.
L0029 |     assert 'value="general_manager"' in body | Assignment statement storing or updating program state.
L0030 |     assert 'value="technician"' in body | Assignment statement storing or updating program state.
L0031 | | Blank line used for readability and logical separation.
L0032 | | Blank line used for readability and logical separation.
L0033 | def test_first_user_registration_page_is_public(client): | Declares a function/method as a reusable unit of behavior.
L0034 |     response = client.get("/register/") | Assignment statement storing or updating program state.
L0035 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0036 |     assert "Create Developer Account" in response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0037 | | Blank line used for readability and logical separation.
L0038 | | Blank line used for readability and logical separation.
L0039 | def test_registration_locks_after_first_user_exists(client, developer_user): | Declares a function/method as a reusable unit of behavior.
L0040 |     response = client.get("/register/") | Assignment statement storing or updating program state.
L0041 |     assert response.status_code == 403 | Operational statement participating in the file's runtime behavior.
L0042 | | Blank line used for readability and logical separation.
L0043 | | Blank line used for readability and logical separation.
L0044 | def test_developer_login_redirects_to_dashboard(login_as_developer): | Declares a function/method as a reusable unit of behavior.
L0045 |     response = login_as_developer() | Assignment statement storing or updating program state.
L0046 |     assert response.status_code == 302 | Operational statement participating in the file's runtime behavior.
L0047 |     assert "/dashboard/" in response.headers["Location"] | Operational statement participating in the file's runtime behavior.
L0048 | | Blank line used for readability and logical separation.
L0049 | | Blank line used for readability and logical separation.
L0050 | def test_api_create_consumable_uses_authenticated_identity(app, client, developer_user, login_as_developer): | Declares a function.
L0051 |     login_as_developer() | Operational statement participating in the file's runtime behavior.
L0052 | | Blank line used for readability and logical separation.
L0053 |     response = client.get("/consumables/") | Assignment statement storing or updating program state.
```

```

L0054 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0055 |     csrf_token = extract_hidden_input(response.get_data(as_text=True), "csrf_token") | Assignment statement storing or updating pro
L0056 | | Blank line used for readability and logical separation.
L0057 |     response = client.post( | Assignment statement storing or updating program state.
L0058 |         "/api/consumables/", | Operational statement participating in the file's runtime behavior.
L0059 |         json={ | Assignment statement storing or updating program state.
L0060 |             "site_id": "SITE-001", | Operational statement participating in the file's runtime behavior.
L0061 |             "site_name": "Alpha Site", | Operational statement participating in the file's runtime behavior.
L0062 |             "description": "Smoke test consumable creation", | Operational statement participating in the file's runtime behavior.
L0063 |             "created_by": "spoofed@example.com", | Operational statement participating in the file's runtime behavior.
L0064 |             "csrf_token": csrf_token, | Operational statement participating in the file's runtime behavior.
L0065 |         }, | Operational statement participating in the file's runtime behavior.
L0066 |     ) | Operational statement participating in the file's runtime behavior.
L0067 | | Blank line used for readability and logical separation.
L0068 |     assert response.status_code == 201 | Operational statement participating in the file's runtime behavior.
L0069 | | Blank line used for readability and logical separation.
L0070 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0071 |         record = db.session.get(Consumable, response.get_json()["id"]) | Assignment statement storing or updating program state.
L0072 |         assert record is not None | Operational statement participating in the file's runtime behavior.
L0073 |         assert record.created_by == developer_user["email"] | Operational statement participating in the file's runtime behavior.
L0074 | | Blank line used for readability and logical separation.
L0075 | | Blank line used for readability and logical separation.
L0076 | def test_user_settings_persist_in_database(app, client, developer_user, login_as_developer): | Declares a function/method as a reus
L0077 |     """Test that user settings (theme, language) are saved and loaded from database.""" | Docstring boundary used to describe a mod
L0078 |     # Login as developer | Comment line documenting intent or context for nearby code.
L0079 |     login_as_developer() | Operational statement participating in the file's runtime behavior.
L0080 | | Blank line used for readability and logical separation.
L0081 |     # Get the developer user from database | Comment line documenting intent or context for nearby code.
L0082 |     from model import User | Imports specific names from another module for direct usage.
L0083 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0084 |         user = db.session.query(User).filter_by(email=developer_user["email"]).first() | Assignment statement storing or updating p
L0085 |         assert user is not None | Operational statement participating in the file's runtime behavior.
L0086 | | Blank line used for readability and logical separation.
L0087 |         # Initially no settings should exist | Comment line documenting intent or context for nearby code.
L0088 |         initial_settings = db.session.query(UserSettings).filter_by(user_id=user.id).first() | Assignment statement storing or upda
L0089 |         assert initial_settings is None | Operational statement participating in the file's runtime behavior.
L0090 | | Blank line used for readability and logical separation.
L0091 |         # Fetch settings page first to get CSRF token for POST. | Comment line documenting intent or context for nearby code.
L0092 |         response = client.get("/settings/") | Assignment statement storing or updating program state.
L0093 |         assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0094 |         csrf_token = extract_hidden_input(response.get_data(as_text=True), "csrf_token") | Assignment statement storing or updating pro
L0095 | | Blank line used for readability and logical separation.
L0096 |         # POST to settings endpoint to save theme and language | Comment line documenting intent or context for nearby code.
L0097 |         response = client.post( | Assignment statement storing or updating program state.
L0098 |             "/settings/", | Operational statement participating in the file's runtime behavior.
L0099 |             data={ | Assignment statement storing or updating program state.
L0100 |                 "theme": "dark", | Operational statement participating in the file's runtime behavior.
L0101 |                 "language": "sw", | Operational statement participating in the file's runtime behavior.
L0102 |                 "save_section": "sla_policy", | Operational statement participating in the file's runtime behavior.
L0103 |                 "sla_enabled": "active", | Operational statement participating in the file's runtime behavior.
L0104 |                 "sla_standard_hours": "36", | Operational statement participating in the file's runtime behavior.
L0105 |                 "sla_critical_hours": "18", | Operational statement participating in the file's runtime behavior.
L0106 |                 "sla_due_soon_hours": "4", | Operational statement participating in the file's runtime behavior.
L0107 |                 "sla_policy_agreed": "on", | Operational statement participating in the file's runtime behavior.
L0108 |                 "csrf_token": csrf_token, | Operational statement participating in the file's runtime behavior.

```

```

L0109 |         }, | Operational statement participating in the file's runtime behavior.
L0110 |         follow_redirects=False, | Assignment statement storing or updating program state.
L0111 |     ) | Operational statement participating in the file's runtime behavior.
L0112 |     assert response.status_code == 302 # redirect on success | Operational statement participating in the file's runtime behavior.
L0113 | | Blank line used for readability and logical separation.
L0114 |     # Verify settings were saved to database | Comment line documenting intent or context for nearby code.
L0115 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0116 |         user_settings = db.session.query(UserSettings).filter_by(user_id=user.id).first() | Assignment statement storing or updating program state.
L0117 |         assert user_settings is not None | Operational statement participating in the file's runtime behavior.
L0118 |         assert user_settings.theme == "dark" | Operational statement participating in the file's runtime behavior.
L0119 |         assert user_settings.language == "sw" | Operational statement participating in the file's runtime behavior.
L0120 |         preferences = user_settings.get_preferences() | Assignment statement storing or updating program state.
L0121 |         assert preferences["sla_policy"]["enabled"] is True | Operational statement participating in the file's runtime behavior.
L0122 |         assert preferences["sla_policy"]["standard_hours"] == 36 | Operational statement participating in the file's runtime behavior.
L0123 |         assert preferences["sla_policy"]["critical_hours"] == 18 | Operational statement participating in the file's runtime behavior.
L0124 |         assert preferences["sla_policy"]["due_soon_hours"] == 4 | Operational statement participating in the file's runtime behavior.
L0125 | | Blank line used for readability and logical separation.
L0126 |         active_policy = app.config["_get_active_sla_policy"]() | Assignment statement storing or updating program state.
L0127 |         assert active_policy["standard_hours"] == 36 | Operational statement participating in the file's runtime behavior.
L0128 |         assert active_policy["critical_hours"] == 18 | Operational statement participating in the file's runtime behavior.
L0129 |         assert active_policy["due_soon_hours"] == 4 | Operational statement participating in the file's runtime behavior.
L0130 | | Blank line used for readability and logical separation.
L0131 |     # GET settings page should reflect saved settings in session. | Comment line documenting intent or context for nearby code.
L0132 |     response = client.get("/settings/") | Assignment statement storing or updating program state.
L0133 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0134 |     with client.session_transaction() as sess: | Context manager block for safe setup and automatic cleanup.
L0135 |         assert sess.get("theme") == "dark" | Operational statement participating in the file's runtime behavior.
L0136 |         assert sess.get("language") == "sw" | Operational statement participating in the file's runtime behavior.
L0137 | | Blank line used for readability and logical separation.
L0138 | | Blank line used for readability and logical separation.
L0139 | def test_consumables_page_uses_pagination(app, client, developer_user, login_as_developer): | Declares a function/method as a reusable test function.
L0140 |     login_as_developer() | Operational statement participating in the file's runtime behavior.
L0141 | | Blank line used for readability and logical separation.
L0142 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0143 |         now = datetime.now(timezone.utc).replace(tzinfo=None) | Assignment statement storing or updating program state.
L0144 |         for index in range(60): | Loop iterating over a sequence to process elements one by one.
L0145 |             db.session.add( | Operational statement participating in the file's runtime behavior.
L0146 |                 Consumable( | Operational statement participating in the file's runtime behavior.
L0147 |                     site_id=f"SITE-{index:03d}", | Assignment statement storing or updating program state.
L0148 |                     site_name=f"Site {index}", | Assignment statement storing or updating program state.
L0149 |                     description="Pagination test", | Assignment statement storing or updating program state.
L0150 |                     created_by=developer_user["email"], | Assignment statement storing or updating program state.
L0151 |                     created_at=now + timedelta(seconds=index), | Assignment statement storing or updating program state.
L0152 |                 ) | Operational statement participating in the file's runtime behavior.
L0153 |             ) | Operational statement participating in the file's runtime behavior.
L0154 |             db.session.commit() | Operational statement participating in the file's runtime behavior.
L0155 | | Blank line used for readability and logical separation.
L0156 |             response = client.get("/consumables/?per_page=25") | Assignment statement storing or updating program state.
L0157 |             assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0158 |             body = response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0159 |             assert "Showing 25 of 60 consumables on page 1 of 3." in body | Operational statement participating in the file's runtime behavior.
L0160 | | Blank line used for readability and logical separation.
L0161 | | Blank line used for readability and logical separation.
L0162 | def test_admin_staff_page_uses_pagination(app, client, developer_user, login_as_developer): | Declares a function/method as a reusable test function.
L0163 |     login_as_developer() | Operational statement participating in the file's runtime behavior.

```

```

L0164 | | Blank line used for readability and logical separation.
L0165 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0166 |         for index in range(30): | Loop iterating over a sequence to process elements one by one.
L0167 |             db.session.add( | Operational statement participating in the file's runtime behavior.
L0168 |                 User( | Operational statement participating in the file's runtime behavior.
L0169 |                     email=f"staff-{index}@example.com", | Assignment statement storing or updating program state.
L0170 |                     full_name=f"Staff {index}", | Assignment statement storing or updating program state.
L0171 |                     role="staff", | Assignment statement storing or updating program state.
L0172 |                     password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0173 |                 ) | Operational statement participating in the file's runtime behavior.
L0174 |             ) | Operational statement participating in the file's runtime behavior.
L0175 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0176 | | Blank line used for readability and logical separation.
L0177 |     response = client.get("/admin/staff/?per_page=10") | Assignment statement storing or updating program state.
L0178 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0179 |     body = response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0180 |     assert "Showing 10 of 31 matched users on page 1 of 4." in body | Operational statement participating in the file's runtime behavior.
L0181 |     assert "Edit Profile" in body | Operational statement participating in the file's runtime behavior.
L0182 | | Blank line used for readability and logical separation.
L0183 | | Blank line used for readability and logical separation.
L0184 | def test_run_maintenance_command_escalates_overdue_high_risk_item(app): | Declares a function/method as a reusable unit of behavior
L0185 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0186 |         tech = User( | Assignment statement storing or updating program state.
L0187 |             email="cli-tech@example.com", | Assignment statement storing or updating program state.
L0188 |             full_name="CLI Tech", | Assignment statement storing or updating program state.
L0189 |             role="technician", | Assignment statement storing or updating program state.
L0190 |             password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0191 |         ) | Operational statement participating in the file's runtime behavior.
L0192 |         db.session.add(tech) | Operational statement participating in the file's runtime behavior.
L0193 |         db.session.add( | Operational statement participating in the file's runtime behavior.
L0194 |             Activity( | Operational statement participating in the file's runtime behavior.
L0195 |                 activity_type="pm", | Assignment statement storing or updating program state.
L0196 |                 details="CLI maintenance escalation test", | Assignment statement storing or updating program state.
L0197 |                 created_by=tech.email, | Assignment statement storing or updating program state.
L0198 |                 risk_score=95, | Assignment statement storing or updating program state.
L0199 |                 sla_deadline=datetime.now(timezone.utc).replace(tzinfo=None) - timedelta(hours=2), | Assignment statement storing or updating program state.
L0200 |                 approved_at=None, | Assignment statement storing or updating program state.
L0201 |             ) | Operational statement participating in the file's runtime behavior.
L0202 |         ) | Operational statement participating in the file's runtime behavior.
L0203 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0204 | | Blank line used for readability and logical separation.
L0205 |     runner = app.test_cli_runner() | Assignment statement storing or updating program state.
L0206 |     result = runner.invoke(args=["run-maintenance"]) | Assignment statement storing or updating program state.
L0207 | | Blank line used for readability and logical separation.
L0208 |     assert result.exit_code == 0 | Operational statement participating in the file's runtime behavior.
L0209 |     assert "sla_escalations=1" in result.output | Assignment statement storing or updating program state.
L0210 | | Blank line used for readability and logical separation.
L0211 | | Blank line used for readability and logical separation.
L0212 | def test_developer_dashboard_shareable_link_targets_technician_login(client, login_as_developer): | Declares a function/method as a reusable unit of behavior
L0213 |     login_as_developer() | Operational statement participating in the file's runtime behavior.
L0214 | | Blank line used for readability and logical separation.
L0215 |     response = client.get("/dashboard/") | Assignment statement storing or updating program state.
L0216 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0217 |     body = response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0218 |     assert "/technician/login" in body | Operational statement participating in the file's runtime behavior.

```

```

L0219 | | Blank line used for readability and logical separation.
L0220 | | Blank line used for readability and logical separation.
L0221 | def test_developer_can_create_staff_without_manual_password(app, client, login_as_developer): | Declares a function/method as a reu
L0222 |     login_as_developer() | Operational statement participating in the file's runtime behavior.
L0223 | | Blank line used for readability and logical separation.
L0224 |     response = client.get("/admin/add-staff/") | Assignment statement storing or updating program state.
L0225 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0226 |     csrf_token = extract_hidden_input(response.get_data(as_text=True), "csrf_token") | Assignment statement storing or updating pro
L0227 | | Blank line used for readability and logical separation.
L0228 |     response = client.post( | Assignment statement storing or updating program state.
L0229 |         "/admin/add-staff/", | Operational statement participating in the file's runtime behavior.
L0230 |         data={ | Assignment statement storing or updating program state.
L0231 |             "csrf_token": csrf_token, | Operational statement participating in the file's runtime behavior.
L0232 |             "first_name": "Auto", | Operational statement participating in the file's runtime behavior.
L0233 |             "last_name": "Password", | Operational statement participating in the file's runtime behavior.
L0234 |             "email": "auto-password@example.com", | Operational statement participating in the file's runtime behavior.
L0235 |             "region": "Central", | Operational statement participating in the file's runtime behavior.
L0236 |             "gender": "male", | Operational statement participating in the file's runtime behavior.
L0237 |             "password": "", | Operational statement participating in the file's runtime behavior.
L0238 |         }, | Operational statement participating in the file's runtime behavior.
L0239 |         follow_redirects=True, | Assignment statement storing or updating program state.
L0240 |     ) | Operational statement participating in the file's runtime behavior.
L0241 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0242 |     body = response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0243 |     assert "Staff account created" in body | Operational statement participating in the file's runtime behavior.
L0244 |     assert "Latest Issued Credentials" in body | Operational statement participating in the file's runtime behavior.
L0245 |     assert "Auto-generated by system" in body | Operational statement participating in the file's runtime behavior.
L0246 | | Blank line used for readability and logical separation.
L0247 | | Blank line used for readability and logical separation.
L0248 | def test_reset_password_shows_current_and_new_password_in_issued_credentials(app, client, login_as_developer): | Declares a functio
L0249 |     login_as_developer() | Operational statement participating in the file's runtime behavior.
L0250 | | Blank line used for readability and logical separation.
L0251 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0252 |         target = User( | Assignment statement storing or updating program state.
L0253 |             email="reset-target@example.com", | Assignment statement storing or updating program state.
L0254 |             full_name="Reset Target", | Assignment statement storing or updating program state.
L0255 |             role="staff", | Assignment statement storing or updating program state.
L0256 |             password_hash=generate_password_hash("OldPass123!"), | Assignment statement storing or updating program state.
L0257 |         ) | Operational statement participating in the file's runtime behavior.
L0258 |         db.session.add(target) | Operational statement participating in the file's runtime behavior.
L0259 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0260 |         target_id = target.id | Assignment statement storing or updating program state.
L0261 | | Blank line used for readability and logical separation.
L0262 |         response = client.get("/admin/staff/") | Assignment statement storing or updating program state.
L0263 |         assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0264 |         csrf_token = extract_hidden_input(response.get_data(as_text=True), "csrf_token") | Assignment statement storing or updating pro
L0265 | | Blank line used for readability and logical separation.
L0266 |         response = client.post( | Assignment statement storing or updating program state.
L0267 |             f"/admin/staff/{target_id}/reset-password", | Operational statement participating in the file's runtime behavior.
L0268 |             data={ | Assignment statement storing or updating program state.
L0269 |                 "csrf_token": csrf_token, | Operational statement participating in the file's runtime behavior.
L0270 |                 "current_password": "OldPass123!", | Operational statement participating in the file's runtime behavior.
L0271 |                 "new_password": "NewPass456!", | Operational statement participating in the file's runtime behavior.
L0272 |                 "q": "", | Operational statement participating in the file's runtime behavior.
L0273 |             }, | Operational statement participating in the file's runtime behavior.

```

L0274 | follow_redirects=True, | Assignment statement storing or updating program state.
L0275 |) | Operational statement participating in the file's runtime behavior.
L0276 | assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0277 | body = response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0278 | assert "Password reset for Reset Target." in body | Operational statement participating in the file's runtime behavior.
L0279 | assert "Previous Password (Provided):" in body | Operational statement participating in the file's runtime behavior.
L0280 | assert "OldPass123!" in body | Operational statement participating in the file's runtime behavior.
L0281 | assert "New password" in body | Operational statement participating in the file's runtime behavior.
L0282 | assert "NewPass456!" in body | Operational statement participating in the file's runtime behavior.

File 128: tests/test_notifications.py

```
L0001 | from werkzeug.security import generate_password_hash | Imports specific names from another module for direct usage.
L0002 | | Blank line used for readability and logical separation.
L0003 | from conftest import extract_hidden_input | Imports specific names from another module for direct usage.
L0004 | from model import Activity, Message, User, db | Imports specific names from another module for direct usage.
L0005 | | Blank line used for readability and logical separation.
L0006 | | Blank line used for readability and logical separation.
L0007 | def login_user(client, email, password, role): | Declares a function/method as a reusable unit of behavior.
L0008 |     response = client.get("/login") | Assignment statement storing or updating program state.
L0009 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0010 |     token = extract_hidden_input(response.get_data(as_text=True), "login_csrf_token") | Assignment statement storing or updating pr
L0011 | | Blank line used for readability and logical separation.
L0012 |     response = client.post( | Assignment statement storing or updating program state.
L0013 |         "/login", | Operational statement participating in the file's runtime behavior.
L0014 |         data={ | Assignment statement storing or updating program state.
L0015 |             "email": email, | Operational statement participating in the file's runtime behavior.
L0016 |             "password": password, | Operational statement participating in the file's runtime behavior.
L0017 |             "account_type": role, | Operational statement participating in the file's runtime behavior.
L0018 |             "login_csrf_token": token, | Operational statement participating in the file's runtime behavior.
L0019 |         }, | Operational statement participating in the file's runtime behavior.
L0020 |         follow_redirects=False, | Assignment statement storing or updating program state.
L0021 |     ) | Operational statement participating in the file's runtime behavior.
L0022 |     assert response.status_code == 302 | Operational statement participating in the file's runtime behavior.
L0023 | | Blank line used for readability and logical separation.
L0024 | | Blank line used for readability and logical separation.
L0025 | def test_send_message_persists_and_logs_activity(app, client): | Declares a function/method as a reusable unit of behavior.
L0026 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0027 |         db.session.add_all( | Operational statement participating in the file's runtime behavior.
L0028 |             [ | Operational statement participating in the file's runtime behavior.
L0029 |                 User( | Operational statement participating in the file's runtime behavior.
L0030 |                     email="technician@example.com", | Assignment statement storing or updating program state.
L0031 |                     full_name="Tech User", | Assignment statement storing or updating program state.
L0032 |                     role="technician", | Assignment statement storing or updating program state.
L0033 |                     password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0034 |                 ), | Operational statement participating in the file's runtime behavior.
L0035 |                 User( | Operational statement participating in the file's runtime behavior.
L0036 |                     email="staff@example.com", | Assignment statement storing or updating program state.
L0037 |                     full_name="Staff User", | Assignment statement storing or updating program state.
L0038 |                     role="staff", | Assignment statement storing or updating program state.
L0039 |                     password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0040 |                 ), | Operational statement participating in the file's runtime behavior.
L0041 |             ] | Operational statement participating in the file's runtime behavior.
L0042 |         ) | Operational statement participating in the file's runtime behavior.
L0043 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0044 | | Blank line used for readability and logical separation.
L0045 |         login_user(client, "technician@example.com", "Password123!", "technician") | Operational statement participating in the file's
L0046 | | Blank line used for readability and logical separation.
L0047 |         response = client.get("/notifications/") | Assignment statement storing or updating program state.
L0048 |         assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0049 |         csrf_token = extract_hidden_input(response.get_data(as_text=True), "csrf_token") | Assignment statement storing or updating pro
L0050 | | Blank line used for readability and logical separation.
L0051 |         response = client.post( | Assignment statement storing or updating program state.
L0052 |             "/notifications/messages/send", | Operational statement participating in the file's runtime behavior.
L0053 |             data={ | Assignment statement storing or updating program state.
```

```

L0054 |         "csrf_token": csrf_token, | Operational statement participating in the file's runtime behavior.
L0055 |         "recipient_role": "staff", | Operational statement participating in the file's runtime behavior.
L0056 |         "message_body": "Need desk support on this PM ticket.", | Operational statement participating in the file's runtime behavior.
L0057 |     }, | Operational statement participating in the file's runtime behavior.
L0058 |     follow_redirects=True, | Assignment statement storing or updating program state.
L0059 | ) | Operational statement participating in the file's runtime behavior.
L0060 | | Blank line used for readability and logical separation.
L0061 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0062 |     html = response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0063 |     assert "Message sent successfully." in html | Operational statement participating in the file's runtime behavior.
L0064 | | Blank line used for readability and logical separation.
L0065 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0066 |         message = Message.query.one() | Assignment statement storing or updating program state.
L0067 |         assert message.sender_email == "technician@example.com" | Operational statement participating in the file's runtime behavior.
L0068 |         assert message.sender_role == "technician" | Operational statement participating in the file's runtime behavior.
L0069 |         assert message.recipient_role == "staff" | Operational statement participating in the file's runtime behavior.
L0070 |         assert message.body == "Need desk support on this PM ticket." | Operational statement participating in the file's runtime behavior.
L0071 | | Blank line used for readability and logical separation.
L0072 |         activity = Activity.query.filter_by(activity_type="message").one() | Assignment statement storing or updating program state.
L0073 |         assert activity.created_by == "technician@example.com" | Operational statement participating in the file's runtime behavior.
L0074 |         assert "sent a message to staff" in activity.details | Operational statement participating in the file's runtime behavior.
L0075 | | Blank line used for readability and logical separation.
L0076 | | Blank line used for readability and logical separation.
L0077 | def test_notifications_inbox_uses_normalized_role_matching(app): | Declares a function/method as a reusable unit of behavior.
L0078 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0079 |         user = User( | Assignment statement storing or updating program state.
L0080 |             email="deskstaff@example.com", | Assignment statement storing or updating program state.
L0081 |             full_name="Desk Staff", | Assignment statement storing or updating program state.
L0082 |             role="desk_staff", | Assignment statement storing or updating program state.
L0083 |             password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0084 |         ) | Operational statement participating in the file's runtime behavior.
L0085 |         db.session.add(user) | Operational statement participating in the file's runtime behavior.
L0086 |         db.session.flush() | Operational statement participating in the file's runtime behavior.
L0087 |         db.session.add( | Operational statement participating in the file's runtime behavior.
L0088 |             Message( | Operational statement participating in the file's runtime behavior.
L0089 |                 sender_email="technician@example.com", | Assignment statement storing or updating program state.
L0090 |                 sender_role="technician", | Assignment statement storing or updating program state.
L0091 |                 recipient_role="staff", | Assignment statement storing or updating program state.
L0092 |                 recipient_email=None, | Assignment statement storing or updating program state.
L0093 |                 body="Normalized role delivery test", | Assignment statement storing or updating program state.
L0094 |             ) | Operational statement participating in the file's runtime behavior.
L0095 |         ) | Operational statement participating in the file's runtime behavior.
L0096 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0097 | | Blank line used for readability and logical separation.
L0098 |         client = app.test_client() | Assignment statement storing or updating program state.
L0099 |         login_user(client, "deskstaff@example.com", "Password123!", "staff") | Operational statement participating in the file's runtime behavior.
L0100 | | Blank line used for readability and logical separation.
L0101 |         response = client.get("/notifications/") | Assignment statement storing or updating program state.
L0102 |         assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0103 |         assert "Normalized role delivery test" in response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0104 | | Blank line used for readability and logical separation.
L0105 | | Blank line used for readability and logical separation.
L0106 | def test_send_message_get_redirects_to_notifications(login_as_developer, client): | Declares a function/method as a reusable unit of behavior.
L0107 |     login_as_developer() | Operational statement participating in the file's runtime behavior.
L0108 | | Blank line used for readability and logical separation.

```

```

L0109 |     response = client.get("/notifications/messages/send", follow_redirects=False) | Assignment statement storing or updating program state.
L0110 | | Blank line used for readability and logical separation.
L0111 |     assert response.status_code == 302 | Operational statement participating in the file's runtime behavior.
L0112 |     assert "/notifications/" in response.headers["Location"] | Operational statement participating in the file's runtime behavior.
L0113 | | Blank line used for readability and logical separation.
L0114 | | Blank line used for readability and logical separation.
L0115 | def test_sender_sees_delete_button_on_notifications_list(app): | Declares a function/method as a reusable unit of behavior.
L0116 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0117 |         db.session.add( | Operational statement participating in the file's runtime behavior.
L0118 |             User( | Operational statement participating in the file's runtime behavior.
L0119 |                 email="visible-owner@example.com", | Assignment statement storing or updating program state.
L0120 |                 full_name="Visible Owner", | Assignment statement storing or updating program state.
L0121 |                 role="staff", | Assignment statement storing or updating program state.
L0122 |                 password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0123 |             ) | Operational statement participating in the file's runtime behavior.
L0124 |         ) | Operational statement participating in the file's runtime behavior.
L0125 |         db.session.add( | Operational statement participating in the file's runtime behavior.
L0126 |             Message( | Operational statement participating in the file's runtime behavior.
L0127 |                 sender_email="visible-owner@example.com", | Assignment statement storing or updating program state.
L0128 |                 sender_role="staff", | Assignment statement storing or updating program state.
L0129 |                 recipient_role="staff", | Assignment statement storing or updating program state.
L0130 |                 recipient_email=None, | Assignment statement storing or updating program state.
L0131 |                 body="show-delete-button", | Assignment statement storing or updating program state.
L0132 |             ) | Operational statement participating in the file's runtime behavior.
L0133 |         ) | Operational statement participating in the file's runtime behavior.
L0134 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0135 | | Blank line used for readability and logical separation.
L0136 |     client = app.test_client() | Assignment statement storing or updating program state.
L0137 |     login_user(client, "visible-owner@example.com", "Password123!", "staff") | Operational statement participating in the file's runtime behavior.
L0138 | | Blank line used for readability and logical separation.
L0139 |     response = client.get("/notifications/") | Assignment statement storing or updating program state.
L0140 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0141 |     body = response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0142 |     assert "Delete Message" in body | Operational statement participating in the file's runtime behavior.
L0143 | | Blank line used for readability and logical separation.
L0144 | | Blank line used for readability and logical separation.
L0145 | def test_non_sender_does_not_see_delete_button_on_notifications_list(app): | Declares a function/method as a reusable unit of behavior.
L0146 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0147 |         db.session.add_all( | Operational statement participating in the file's runtime behavior.
L0148 |             [ | Operational statement participating in the file's runtime behavior.
L0149 |                 User( | Operational statement participating in the file's runtime behavior.
L0150 |                     email="sender-two@example.com", | Assignment statement storing or updating program state.
L0151 |                     full_name="Sender Two", | Assignment statement storing or updating program state.
L0152 |                     role="technician", | Assignment statement storing or updating program state.
L0153 |                     password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0154 |                 ), | Operational statement participating in the file's runtime behavior.
L0155 |                 User( | Operational statement participating in the file's runtime behavior.
L0156 |                     email="receiver-two@example.com", | Assignment statement storing or updating program state.
L0157 |                     full_name="Receiver Two", | Assignment statement storing or updating program state.
L0158 |                     role="staff", | Assignment statement storing or updating program state.
L0159 |                     password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0160 |                 ), | Operational statement participating in the file's runtime behavior.
L0161 |             ] | Operational statement participating in the file's runtime behavior.
L0162 |         ) | Operational statement participating in the file's runtime behavior.
L0163 |         db.session.flush() | Operational statement participating in the file's runtime behavior.

```

```

L0164 |         db.session.add( | Operational statement participating in the file's runtime behavior.
L0165 |             Message( | Operational statement participating in the file's runtime behavior.
L0166 |                 sender_email="sender-two@example.com", | Assignment statement storing or updating program state.
L0167 |                 sender_role="technician", | Assignment statement storing or updating program state.
L0168 |                 recipient_role="staff", | Assignment statement storing or updating program state.
L0169 |                 recipient_email=None, | Assignment statement storing or updating program state.
L0170 |                 body="no-delete-button", | Assignment statement storing or updating program state.
L0171 |             ) | Operational statement participating in the file's runtime behavior.
L0172 |         ) | Operational statement participating in the file's runtime behavior.
L0173 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0174 | | Blank line used for readability and logical separation.
L0175 |         client = app.test_client() | Assignment statement storing or updating program state.
L0176 |         login_user(client, "receiver-two@example.com", "Password123!", "staff") | Operational statement participating in the file's runtime behavior.
L0177 | | Blank line used for readability and logical separation.
L0178 |         response = client.get("/notifications/") | Assignment statement storing or updating program state.
L0179 |         assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0180 |         body = response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0181 |         assert "Delete Message" not in body | Operational statement participating in the file's runtime behavior.
L0182 | | Blank line used for readability and logical separation.
L0183 | | Blank line used for readability and logical separation.
L0184 | def test_sender_can_delete_own_message(app): | Declares a function/method as a reusable unit of behavior.
L0185 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0186 |         db.session.add_all( | Operational statement participating in the file's runtime behavior.
L0187 |             [ | Operational statement participating in the file's runtime behavior.
L0188 |                 User( | Operational statement participating in the file's runtime behavior.
L0189 |                     email="owner@example.com", | Assignment statement storing or updating program state.
L0190 |                     full_name="Owner User", | Assignment statement storing or updating program state.
L0191 |                     role="staff", | Assignment statement storing or updating program state.
L0192 |                     password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0193 |                 ), | Operational statement participating in the file's runtime behavior.
L0194 |                 User( | Operational statement participating in the file's runtime behavior.
L0195 |                     email="recipient@example.com", | Assignment statement storing or updating program state.
L0196 |                     full_name="Recipient User", | Assignment statement storing or updating program state.
L0197 |                     role="staff", | Assignment statement storing or updating program state.
L0198 |                     password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0199 |                 ), | Operational statement participating in the file's runtime behavior.
L0200 |             ] | Operational statement participating in the file's runtime behavior.
L0201 |         ) | Operational statement participating in the file's runtime behavior.
L0202 |         db.session.flush() | Operational statement participating in the file's runtime behavior.
L0203 |         msg = Message( | Assignment statement storing or updating program state.
L0204 |             sender_email="owner@example.com", | Assignment statement storing or updating program state.
L0205 |             sender_role="staff", | Assignment statement storing or updating program state.
L0206 |             recipient_role="staff", | Assignment statement storing or updating program state.
L0207 |             recipient_email=None, | Assignment statement storing or updating program state.
L0208 |             body="delete-me", | Assignment statement storing or updating program state.
L0209 |         ) | Operational statement participating in the file's runtime behavior.
L0210 |         db.session.add(msg) | Operational statement participating in the file's runtime behavior.
L0211 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0212 |         message_id = msg.id | Assignment statement storing or updating program state.
L0213 | | Blank line used for readability and logical separation.
L0214 |         client = app.test_client() | Assignment statement storing or updating program state.
L0215 |         login_user(client, "owner@example.com", "Password123!", "staff") | Operational statement participating in the file's runtime behavior.
L0216 | | Blank line used for readability and logical separation.
L0217 |         page = client.get("/notifications/") | Assignment statement storing or updating program state.
L0218 |         csrf_token = extract_hidden_input(page.get_data(as_text=True), "csrf_token") | Assignment statement storing or updating program state.

```

```

L0219 | | Blank line used for readability and logical separation.
L0220 |     response = client.post( | Assignment statement storing or updating program state.
L0221 |         f"/notifications/messages/{message_id}/delete", | Operational statement participating in the file's runtime behavior.
L0222 |         data={"csrf_token": csrf_token}, | Assignment statement storing or updating program state.
L0223 |         follow_redirects=True, | Assignment statement storing or updating program state.
L0224 |     ) | Operational statement participating in the file's runtime behavior.
L0225 |     assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0226 |     assert "Message deleted." in response.get_data(as_text=True) | Assignment statement storing or updating program state.
L0227 | | Blank line used for readability and logical separation.
L0228 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0229 |         assert db.session.get(Message, message_id) is None | Operational statement participating in the file's runtime behavior.
L0230 | | Blank line used for readability and logical separation.
L0231 | | Blank line used for readability and logical separation.
L0232 | def test_non_sender_cannot_delete_message(app): | Declares a function/method as a reusable unit of behavior.
L0233 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0234 |         db.session.add_all( | Operational statement participating in the file's runtime behavior.
L0235 |             [ | Operational statement participating in the file's runtime behavior.
L0236 |                 User( | Operational statement participating in the file's runtime behavior.
L0237 |                     email="sender@example.com", | Assignment statement storing or updating program state.
L0238 |                     full_name="Sender User", | Assignment statement storing or updating program state.
L0239 |                     role="technician", | Assignment statement storing or updating program state.
L0240 |                     password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0241 |                 ), | Operational statement participating in the file's runtime behavior.
L0242 |                 User( | Operational statement participating in the file's runtime behavior.
L0243 |                     email="other@example.com", | Assignment statement storing or updating program state.
L0244 |                     full_name="Other User", | Assignment statement storing or updating program state.
L0245 |                     role="staff", | Assignment statement storing or updating program state.
L0246 |                     password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0247 |                 ), | Operational statement participating in the file's runtime behavior.
L0248 |             ] | Operational statement participating in the file's runtime behavior.
L0249 |         ) | Operational statement participating in the file's runtime behavior.
L0250 |         db.session.flush() | Operational statement participating in the file's runtime behavior.
L0251 |         msg = Message( | Assignment statement storing or updating program state.
L0252 |             sender_email="sender@example.com", | Assignment statement storing or updating program state.
L0253 |             sender_role="technician", | Assignment statement storing or updating program state.
L0254 |             recipient_role="staff", | Assignment statement storing or updating program state.
L0255 |             recipient_email=None, | Assignment statement storing or updating program state.
L0256 |             body="should-stay", | Assignment statement storing or updating program state.
L0257 |         ) | Operational statement participating in the file's runtime behavior.
L0258 |         db.session.add(msg) | Operational statement participating in the file's runtime behavior.
L0259 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0260 |         message_id = msg.id | Assignment statement storing or updating program state.
L0261 | | Blank line used for readability and logical separation.
L0262 |         client = app.test_client() | Assignment statement storing or updating program state.
L0263 |         login_user(client, "other@example.com", "Password123!", "staff") | Operational statement participating in the file's runtime behavior.
L0264 | | Blank line used for readability and logical separation.
L0265 |         page = client.get("/notifications/") | Assignment statement storing or updating program state.
L0266 |         csrf_token = extract_hidden_input(page.get_data(as_text=True), "csrf_token") | Assignment statement storing or updating program state.
L0267 | | Blank line used for readability and logical separation.
L0268 |         response = client.post( | Assignment statement storing or updating program state.
L0269 |             f"/notifications/messages/{message_id}/delete", | Operational statement participating in the file's runtime behavior.
L0270 |             data={"csrf_token": csrf_token}, | Assignment statement storing or updating program state.
L0271 |             follow_redirects=True, | Assignment statement storing or updating program state.
L0272 |         ) | Operational statement participating in the file's runtime behavior.
L0273 |         assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.

```

```
L0274 |      assert "You can only delete your own messages." in response.get_data(as_text=True) | Assignment statement storing or updating p
L0275 | | Blank line used for readability and logical separation.
L0276 |      with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0277 |          assert db.session.get(Message, message_id) is not None | Operational statement participating in the file's runtime behavior
```

File 129: tests/test_security.py

```
L0001 | """Security-focused test suite. | Docstring boundary used to describe a module, class, or function.
L0002 | | Blank line used for readability and logical separation.
L0003 | Covers: | Operational statement participating in the file's runtime behavior.
L0004 | - File-upload MIME validation (magic-byte check) | Operational statement participating in the file's runtime behavior.
L0005 | - Signature image validation | Operational statement participating in the file's runtime behavior.
L0006 | - CSRF enforcement on mutations | Operational statement participating in the file's runtime behavior.
L0007 | - Role-based access control on key routes | Operational statement participating in the file's runtime behavior.
L0008 | - API error format consistency | Operational statement participating in the file's runtime behavior.
L0009 | - Rate-limit header presence | Operational statement participating in the file's runtime behavior.
L0010 | """ | Docstring boundary used to describe a module, class, or function.
L0011 | import io | Imports dependency modules: io.
L0012 | import base64 | Imports dependency modules: base64.
L0013 | import struct | Imports dependency modules: struct.
L0014 | | Blank line used for readability and logical separation.
L0015 | import pytest | Imports dependency modules: pytest.
L0016 | from werkzeug.security import generate_password_hash | Imports specific names from another module for direct usage.
L0017 | | Blank line used for readability and logical separation.
L0018 | from conftest import extract_hidden_input | Imports specific names from another module for direct usage.
L0019 | from model import Activity, Message, User, UserSettings, db, utcnow_naive | Imports specific names from another module for direct usage.
L0020 | | Blank line used for readability and logical separation.
L0021 | | Blank line used for readability and logical separation.
L0022 | # ----- | Comment line documenting intent or context for nearby code.
L0023 | # Helpers | Comment line documenting intent or context for nearby code.
L0024 | # ----- | Comment line documenting intent or context for nearby code.
L0025 | | Blank line used for readability and logical separation.
L0026 | def _png_bytes(width: int = 1, height: int = 1) -> bytes: | Declares a function/method as a reusable unit of behavior.
L0027 |     """Return a minimal but valid 1x1 PNG image as bytes.""" | Docstring boundary used to describe a module, class, or function.
L0028 |     import zlib | Imports dependency modules: zlib.
L0029 | | Blank line used for readability and logical separation.
L0030 |     def _chunk(name: bytes, data: bytes) -> bytes: | Declares a function/method as a reusable unit of behavior.
L0031 |         c = struct.pack(">I", len(data)) + name + data | Assignment statement storing or updating program state.
L0032 |         crc = zlib.crc32(name + data) & 0xFFFFFFFF | Assignment statement storing or updating program state.
L0033 |         return c + struct.pack(">I", crc) | Returns a value (or control) back to the caller.
L0034 | | Blank line used for readability and logical separation.
L0035 |     IHDR = struct.pack(">IIBBBBB", width, height, 8, 2, 0, 0, 0) | Assignment statement storing or updating program state.
L0036 |     raw = b"\x00" + b"\x00\x00\x00" * width # filter byte + RGB pixels | Assignment statement storing or updating program state.
L0037 |     IDAT = zlib.compress(raw) | Assignment statement storing or updating program state.
L0038 |     return ( | Returns a value (or control) back to the caller.
L0039 |         b"\x89PNG\r\n\x1a\n" | Operational statement participating in the file's runtime behavior.
L0040 |         + _chunk(b"IHDR", IHDR) | Operational statement participating in the file's runtime behavior.
L0041 |         + _chunk(b>IDAT", IDAT) | Operational statement participating in the file's runtime behavior.
L0042 |         + _chunk(b"IEND", b"") | Operational statement participating in the file's runtime behavior.
L0043 |     ) | Operational statement participating in the file's runtime behavior.
L0044 | | Blank line used for readability and logical separation.
L0045 | | Blank line used for readability and logical separation.
L0046 | def _png_data_url(png: bytes | None = None) -> str: | Declares a function/method as a reusable unit of behavior.
L0047 |     png = png or _png_bytes() | Assignment statement storing or updating program state.
L0048 |     return "data:image/png;base64," + base64.b64encode(png).decode() | Returns a value (or control) back to the caller.
L0049 | | Blank line used for readability and logical separation.
L0050 | | Blank line used for readability and logical separation.
L0051 | def _login_user(client, email, password, role="developer"): | Declares a function/method as a reusable unit of behavior.
L0052 |     resp = client.get("/login") | Assignment statement storing or updating program state.
L0053 |     token = extract_hidden_input(resp.get_data(as_text=True), "login_csrf_token") | Assignment statement storing or updating program state.
```

```

L0054 |     client.post( | Operational statement participating in the file's runtime behavior.
L0055 |         "/login", | Operational statement participating in the file's runtime behavior.
L0056 |         data={"email": email, "password": password, "account_type": role, "login_csrf_token": token}, | Assignment statement storing
L0057 |         follow_redirects=False, | Assignment statement storing or updating program state.
L0058 |     ) | Operational statement participating in the file's runtime behavior.
L0059 | | Blank line used for readability and logical separation.
L0060 | | Blank line used for readability and logical separation.
L0061 | # ----- | Comment line documenting intent or context for nearby code.
L0062 | # Fixtures | Comment line documenting intent or context for nearby code.
L0063 | # ----- | Comment line documenting intent or context for nearby code.
L0064 | | Blank line used for readability and logical separation.
L0065 | @pytest.fixture() | Decorator line that modifies the behavior of the definition below.
L0066 | def staff_user(app): | Declares a function/method as a reusable unit of behavior.
L0067 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0068 |         u = User( | Assignment statement storing or updating program state.
L0069 |             email="staff@example.com", | Assignment statement storing or updating program state.
L0070 |             full_name="Staff User", | Assignment statement storing or updating program state.
L0071 |             role="staff", | Assignment statement storing or updating program state.
L0072 |             password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0073 |         ) | Operational statement participating in the file's runtime behavior.
L0074 |         db.session.add(u) | Operational statement participating in the file's runtime behavior.
L0075 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0076 |     return {"email": "staff@example.com", "password": "Password123!"} | Returns a value (or control) back to the caller.
L0077 | | Blank line used for readability and logical separation.
L0078 | @pytest.fixture() | Decorator line that modifies the behavior of the definition below.
L0079 | def tech_user(app): | Declares a function/method as a reusable unit of behavior.
L0080 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0081 |         u = User( | Assignment statement storing or updating program state.
L0082 |             email="tech@example.com", | Assignment statement storing or updating program state.
L0083 |             full_name="Tech User", | Assignment statement storing or updating program state.
L0084 |             role="technician", | Assignment statement storing or updating program state.
L0085 |             password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0086 |         ) | Operational statement participating in the file's runtime behavior.
L0087 |         db.session.add(u) | Operational statement participating in the file's runtime behavior.
L0088 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0089 |     return {"email": "tech@example.com", "password": "Password123!"} | Returns a value (or control) back to the caller.
L0090 | | Blank line used for readability and logical separation.
L0091 | | Blank line used for readability and logical separation.
L0092 | @pytest.fixture() | Decorator line that modifies the behavior of the definition below.
L0093 | def manager_user(app): | Declares a function/method as a reusable unit of behavior.
L0094 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0095 |         u = User( | Assignment statement storing or updating program state.
L0096 |             email="manager@example.com", | Assignment statement storing or updating program state.
L0097 |             full_name="Manager User", | Assignment statement storing or updating program state.
L0098 |             role="manager", | Assignment statement storing or updating program state.
L0099 |             password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0100 |         ) | Operational statement participating in the file's runtime behavior.
L0101 |         db.session.add(u) | Operational statement participating in the file's runtime behavior.
L0102 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0103 |     return {"email": "manager@example.com", "password": "Password123!"} | Returns a value (or control) back to the caller.
L0104 | | Blank line used for readability and logical separation.
L0105 | | Blank line used for readability and logical separation.
L0106 | # ----- | Comment line documenting intent or context for nearby code.
L0107 | # Upload / magic-byte validation | Comment line documenting intent or context for nearby code.
L0108 | # ----- | Comment line documenting intent or context for nearby code.

```



```

L0109 | | Blank line used for readability and logical separation.
L0110 | def test_file_upload_rejects_non_image_extension(app, client, tech_user, login_as_developer): | Declares a function/method as a reusable unit of behavior.
L0111 |     """Magic-byte validator should reject non-image payloads.""" | Docstring boundary used to describe a module, class, or function.
L0112 |     from app import _check_image_magic | Imports specific names from another module for direct usage.
L0113 | | Blank line used for readability and logical separation.
L0114 |     fake_stream = io.BytesIO(b"not-an-image") | Assignment statement storing or updating program state.
L0115 |     assert _check_image_magic(fake_stream) is False | Operational statement participating in the file's runtime behavior.
L0116 | | Blank line used for readability and logical separation.
L0117 | | Blank line used for readability and logical separation.
L0118 | def test_signature_validation_rejects_invalid_base64(app): | Declares a function/method as a reusable unit of behavior.
L0119 |     """save_signature_image must return None for a corrupt payload.""" | Docstring boundary used to describe a module, class, or function.
L0120 |     from app import save_signature_image | Imports specific names from another module for direct usage.
L0121 |     import tempfile | Imports dependency modules: tempfile.
L0122 |     with tempfile.TemporaryDirectory() as tmpdir: | Context manager block for safe setup and automatic cleanup.
L0123 |         result = save_signature_image("_VALID_BASE64!!!", tmpdir) | Assignment statement storing or updating program state.
L0124 |         assert result is None | Operational statement participating in the file's runtime behavior.
L0125 | | Blank line used for readability and logical separation.
L0126 | | Blank line used for readability and logical separation.
L0127 | def test_signature_validation_rejects_wrong_magic_bytes(app): | Declares a function/method as a reusable unit of behavior.
L0128 |     """save_signature_image must reject a valid base64 payload that isn't PNG.""" | Docstring boundary used to describe a module, class, or function.
L0129 |     from app import save_signature_image | Imports specific names from another module for direct usage.
L0130 |     import tempfile | Imports dependency modules: tempfile.
L0131 |     # JPEG magic bytes wrapped in a PNG data-URL | Comment line documenting intent or context for nearby code.
L0132 |     fake = "data:image/png;base64," + base64.b64encode(b"\xff\xd8\xff\xe0fake").decode() | Assignment statement storing or updating program state.
L0133 |     with tempfile.TemporaryDirectory() as tmpdir: | Context manager block for safe setup and automatic cleanup.
L0134 |         result = save_signature_image(fake, tmpdir) | Assignment statement storing or updating program state.
L0135 |         assert result is None | Operational statement participating in the file's runtime behavior.
L0136 | | Blank line used for readability and logical separation.
L0137 | | Blank line used for readability and logical separation.
L0138 | def test_signature_validation_accepts_real_png(app): | Declares a function/method as a reusable unit of behavior.
L0139 |     """save_signature_image must accept a genuine PNG payload.""" | Docstring boundary used to describe a module, class, or function.
L0140 |     from app import save_signature_image | Imports specific names from another module for direct usage.
L0141 |     import tempfile | Imports dependency modules: tempfile.
L0142 |     data_url = _png_data_url() | Assignment statement storing or updating program state.
L0143 |     with tempfile.TemporaryDirectory() as tmpdir: | Context manager block for safe setup and automatic cleanup.
L0144 |         result = save_signature_image(data_url, tmpdir) | Assignment statement storing or updating program state.
L0145 |         assert result is not None | Operational statement participating in the file's runtime behavior.
L0146 |         assert result.endswith(".png") | Operational statement participating in the file's runtime behavior.
L0147 | | Blank line used for readability and logical separation.
L0148 | | Blank line used for readability and logical separation.
L0149 | # ----- | Comment line documenting intent or context for nearby code.
L0150 | # CSRF enforcement | Comment line documenting intent or context for nearby code.
L0151 | # ----- | Comment line documenting intent or context for nearby code.
L0152 | | Blank line used for readability and logical separation.
L0153 | def test_csrf_blocks_mutation_without_token(client, developer_user): | Declares a function/method as a reusable unit of behavior.
L0154 |     _login_user(client, developer_user["email"], developer_user["password"]) | Operational statement participating in the file's runtime behavior.
L0155 |     # POST without any CSRF token should be rejected. | Comment line documenting intent or context for nearby code.
L0156 |     resp = client.post("/notifications/messages/send", data={"recipient_role": "all", "message_body": "hi"}) | Assignment statement storing or updating program state.
L0157 |     # Should either redirect (flash) or return 400, not 200 OK with success. | Comment line documenting intent or context for nearby code.
L0158 |     assert resp.status_code in {302, 400} | Block delimiter controlling scope/structure in this language.
L0159 | | Blank line used for readability and logical separation.
L0160 | | Blank line used for readability and logical separation.
L0161 | # ----- | Comment line documenting intent or context for nearby code.
L0162 | # Role-based access control | Comment line documenting intent or context for nearby code.
L0163 | # ----- | Comment line documenting intent or context for nearby code.

```

```

L0164 | | Blank line used for readability and logical separation.
L0165 | def test_technician_cannot_access_desk_activities(client, tech_user): | Declares a function/method as a reusable unit of behavior.
L0166 |     _login_user(client, tech_user["email"], tech_user["password"], role="technician") | Assignment statement storing or updating pr
L0167 |     resp = client.get("/desk/activities/", follow_redirects=False) | Assignment statement storing or updating program state.
L0168 |     assert resp.status_code == 403 | Operational statement participating in the file's runtime behavior.
L0169 | | Blank line used for readability and logical separation.
L0170 | | Blank line used for readability and logical separation.
L0171 | def test_technician_cannot_access_admin_staff(client, tech_user): | Declares a function/method as a reusable unit of behavior.
L0172 |     _login_user(client, tech_user["email"], tech_user["password"], role="technician") | Assignment statement storing or updating pr
L0173 |     resp = client.get("/admin/staff/", follow_redirects=False) | Assignment statement storing or updating program state.
L0174 |     assert resp.status_code == 403 | Operational statement participating in the file's runtime behavior.
L0175 | | Blank line used for readability and logical separation.
L0176 | | Blank line used for readability and logical separation.
L0177 | def test_staff_cannot_access_admin_staff(client, staff_user): | Declares a function/method as a reusable unit of behavior.
L0178 |     _login_user(client, staff_user["email"], staff_user["password"], role="staff") | Assignment statement storing or updating progr
L0179 |     resp = client.get("/admin/staff/", follow_redirects=False) | Assignment statement storing or updating program state.
L0180 |     assert resp.status_code == 403 | Operational statement participating in the file's runtime behavior.
L0181 | | Blank line used for readability and logical separation.
L0182 | | Blank line used for readability and logical separation.
L0183 | def test_developer_can_edit_user_profile(client, developer_user, staff_user, app): | Declares a function/method as a reusable unit
L0184 |     _login_user(client, developer_user["email"], developer_user["password"], role="developer") | Assignment statement storing or up
L0185 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0186 |         target = User.query.filter_by(email=staff_user["email"]).first() | Assignment statement storing or updating program state.
L0187 |         assert target is not None | Operational statement participating in the file's runtime behavior.
L0188 |         user_id = target.id | Assignment statement storing or updating program state.
L0189 | | Blank line used for readability and logical separation.
L0190 |         resp = client.post( | Assignment statement storing or updating program state.
L0191 |             f"/admin/staff/{user_id}/edit-profile", | Operational statement participating in the file's runtime behavior.
L0192 |             data={ | Assignment statement storing or updating program state.
L0193 |                 "email": "staff.updated@example.com", | Operational statement participating in the file's runtime behavior.
L0194 |                 "uid": "STF-777", | Operational statement participating in the file's runtime behavior.
L0195 |                 "first_name": "Updated", | Operational statement participating in the file's runtime behavior.
L0196 |                 "last_name": "Staff", | Operational statement participating in the file's runtime behavior.
L0197 |                 "region": "West", | Operational statement participating in the file's runtime behavior.
L0198 |                 "gender": "female", | Operational statement participating in the file's runtime behavior.
L0199 |                 "avatar_key": "female_exec", | Operational statement participating in the file's runtime behavior.
L0200 |                 "support_desk": "NOC Desk", | Operational statement participating in the file's runtime behavior.
L0201 |                 "site_operations_phone": "0312000000", | Operational statement participating in the file's runtime behavior.
L0202 |                 "emergency_phone": "+256700000000", | Operational statement participating in the file's runtime behavior.
L0203 |             }, | Operational statement participating in the file's runtime behavior.
L0204 |             follow_redirects=False, | Assignment statement storing or updating program state.
L0205 |         ) | Operational statement participating in the file's runtime behavior.
L0206 |         assert resp.status_code == 302 | Operational statement participating in the file's runtime behavior.
L0207 | | Blank line used for readability and logical separation.
L0208 |         with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0209 |             updated = User.query.get(user_id) | Assignment statement storing or updating program state.
L0210 |             assert updated is not None | Operational statement participating in the file's runtime behavior.
L0211 |             assert updated.email == "staff.updated@example.com" | Operational statement participating in the file's runtime behavior.
L0212 |             assert updated.uid == "STF-777" | Operational statement participating in the file's runtime behavior.
L0213 |             assert updated.first_name == "Updated" | Operational statement participating in the file's runtime behavior.
L0214 |             assert updated.last_name == "Staff" | Operational statement participating in the file's runtime behavior.
L0215 |             assert updated.full_name == "Updated Staff" | Operational statement participating in the file's runtime behavior.
L0216 |             assert updated.region == "West" | Operational statement participating in the file's runtime behavior.
L0217 |             assert updated.gender == "female" | Operational statement participating in the file's runtime behavior.
L0218 |             assert updated.support_desk == "NOC Desk" | Operational statement participating in the file's runtime behavior.

```

```

L0219 |         assert updated.site_operations_phone == "0312000000" | Operational statement participating in the file's runtime behavior.
L0220 |         assert updated.emergency_phone == "+256700000000" | Operational statement participating in the file's runtime behavior.
L0221 | | Blank line used for readability and logical separation.
L0222 |         settings = UserSettings.query.filter_by(user_id=updated.id).first() | Assignment statement storing or updating program state.
L0223 |         assert settings is not None | Operational statement participating in the file's runtime behavior.
L0224 |         assert settings.get_preferences().get("profile_avatar") == "female_exec" | Operational statement participating in the file's runtime behavior.
L0225 | | Blank line used for readability and logical separation.
L0226 | | Blank line used for readability and logical separation.
L0227 | def test_developer_profile_edit_rejects_duplicate_email(client, developer_user, staff_user, manager_user, app): | Declares a function/method as a reusable unit of behavior.
L0228 |     _login_user(client, developer_user["email"], developer_user["password"], role="developer") | Assignment statement storing or updating program state.
L0229 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0230 |         target = User.query.filter_by(email=staff_user["email"]).first() | Assignment statement storing or updating program state.
L0231 |         assert target is not None | Operational statement participating in the file's runtime behavior.
L0232 |         original_email = target.email | Assignment statement storing or updating program state.
L0233 |         user_id = target.id | Assignment statement storing or updating program state.
L0234 | | Blank line used for readability and logical separation.
L0235 |         resp = client.post( | Assignment statement storing or updating program state.
L0236 |             f"/admin/staff/{user_id}/edit-profile", | Operational statement participating in the file's runtime behavior.
L0237 |             data={ | Assignment statement storing or updating program state.
L0238 |                 "email": manager_user["email"], | Operational statement participating in the file's runtime behavior.
L0239 |                 "uid": "STF-101", | Operational statement participating in the file's runtime behavior.
L0240 |                 "first_name": "Staff", | Operational statement participating in the file's runtime behavior.
L0241 |                 "last_name": "User", | Operational statement participating in the file's runtime behavior.
L0242 |                 "region": "Central", | Operational statement participating in the file's runtime behavior.
L0243 |                 "gender": "male", | Operational statement participating in the file's runtime behavior.
L0244 |                 "support_desk": "Desk", | Operational statement participating in the file's runtime behavior.
L0245 |                 "site_operations_phone": "0312111111", | Operational statement participating in the file's runtime behavior.
L0246 |                 "emergency_phone": "+256711111111", | Operational statement participating in the file's runtime behavior.
L0247 |             }, | Operational statement participating in the file's runtime behavior.
L0248 |             follow_redirects=False, | Assignment statement storing or updating program state.
L0249 |         ) | Operational statement participating in the file's runtime behavior.
L0250 |         assert resp.status_code == 302 | Operational statement participating in the file's runtime behavior.
L0251 | | Blank line used for readability and logical separation.
L0252 |         with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0253 |             unchanged = User.query.get(user_id) | Assignment statement storing or updating program state.
L0254 |             assert unchanged is not None | Operational statement participating in the file's runtime behavior.
L0255 |             assert unchanged.email == original_email | Operational statement participating in the file's runtime behavior.
L0256 | | Blank line used for readability and logical separation.
L0257 | | Blank line used for readability and logical separation.
L0258 | def test_manager_dashboard_shows_sla_policy_card(client, manager_user): | Declares a function/method as a reusable unit of behavior.
L0259 |     _login_user(client, manager_user["email"], manager_user["password"], role="manager") | Assignment statement storing or updating program state.
L0260 |     resp = client.get("/dashboard/", follow_redirects=False) | Assignment statement storing or updating program state.
L0261 |     assert resp.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0262 |     body = resp.get_data(as_text=True) | Assignment statement storing or updating program state.
L0263 |     assert "Desk SLA Policy" in body | Operational statement participating in the file's runtime behavior.
L0264 |     assert "Manage SLA Policy" in body | Operational statement participating in the file's runtime behavior.
L0265 | | Blank line used for readability and logical separation.
L0266 | | Blank line used for readability and logical separation.
L0267 | def test_anonymous_redirect_to_login(client): | Declares a function/method as a reusable unit of behavior.
L0268 |     for path in ["/dashboard/", "/desk/activities/", "/admin/staff/", "/field/site-form/"]: | Loop iterating over a sequence to process each element.
L0269 |         resp = client.get(path, follow_redirects=False) | Assignment statement storing or updating program state.
L0270 |         assert resp.status_code == 302 | Operational statement participating in the file's runtime behavior.
L0271 |         assert "/login" in resp.headers["Location"] | Operational statement participating in the file's runtime behavior.
L0272 | | Blank line used for readability and logical separation.
L0273 | | Blank line used for readability and logical separation.

```

```

L0274 | # ----- | Comment line documenting intent or context for nearby code.
L0275 | # API error format | Comment line documenting intent or context for nearby code.
L0276 | # ----- | Comment line documenting intent or context for nearby code.
L0277 | | Blank line used for readability and logical separation.
L0278 | def test_api_returns_consistent_error_on_forbidden(client, developer_user, staff_user): | Declares a function/method as a reusable
L0279 |     """Non-developer POSTing to consumables API should get a consistent error.""" | Docstring boundary used to describe a module, class, or function.
L0280 |     _login_user(client, staff_user["email"], staff_user["password"], role="staff") | Assignment statement storing or updating program state.
L0281 |     resp = client.post("/api/consumables/", json={"site_id": "X", "site_name": "Y", "description": "Z"}) | Assignment statement storing or updating program state.
L0282 |     assert resp.status_code == 403 | Operational statement participating in the file's runtime behavior.
L0283 |     body = resp.get_json() | Assignment statement storing or updating program state.
L0284 |     assert body["status"] == "error" | Operational statement participating in the file's runtime behavior.
L0285 |     assert "code" in body | Operational statement participating in the file's runtime behavior.
L0286 |     assert "message" in body | Operational statement participating in the file's runtime behavior.
L0287 | | Blank line used for readability and logical separation.
L0288 | | Blank line used for readability and logical separation.
L0289 | def test_api_returns_consistent_error_on_missing_fields(client, developer_user, login_as_developer): | Declares a function/method as a reusable
L0290 |     """Missing required fields on POST /api/consumables/ should return structured error.""" | Docstring boundary used to describe a module, class, or function.
L0291 |     login_as_developer() | Operational statement participating in the file's runtime behavior.
L0292 |     resp = client.post("/api/consumables/", json={"site_id": "X"}) | Assignment statement storing or updating program state.
L0293 |     assert resp.status_code == 400 | Operational statement participating in the file's runtime behavior.
L0294 |     body = resp.get_json() | Assignment statement storing or updating program state.
L0295 |     assert body["status"] == "error" | Operational statement participating in the file's runtime behavior.
L0296 |     assert body["code"] == "VALIDATION_ERROR" | Operational statement participating in the file's runtime behavior.
L0297 | | Blank line used for readability and logical separation.
L0298 | | Blank line used for readability and logical separation.
L0299 | def test_api_list_consumables_returns_status_ok(client, developer_user, login_as_developer): | Declares a function/method as a reusable
L0300 |     login_as_developer() | Operational statement participating in the file's runtime behavior.
L0301 |     resp = client.get("/api/consumables/") | Assignment statement storing or updating program state.
L0302 |     assert resp.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0303 |     body = resp.get_json() | Assignment statement storing or updating program state.
L0304 |     assert body["status"] == "ok" | Operational statement participating in the file's runtime behavior.
L0305 |     assert "items" in body | Operational statement participating in the file's runtime behavior.
L0306 | | Blank line used for readability and logical separation.
L0307 | | Blank line used for readability and logical separation.
L0308 | def test_delete_message_hides_only_for_current_user(client, app, developer_user, staff_user): | Declares a function/method as a reusable
L0309 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0310 |         msg = Message( | Assignment statement storing or updating program state.
L0311 |             sender_email=staff_user["email"], | Assignment statement storing or updating program state.
L0312 |             sender_role="staff", | Assignment statement storing or updating program state.
L0313 |             recipient_role="all", | Assignment statement storing or updating program state.
L0314 |             recipient_email=None, | Assignment statement storing or updating program state.
L0315 |             body="Visibility test", | Assignment statement storing or updating program state.
L0316 |             created_at=utcnow_naive(), | Assignment statement storing or updating program state.
L0317 |         ) | Operational statement participating in the file's runtime behavior.
L0318 |         db.session.add(msg) | Operational statement participating in the file's runtime behavior.
L0319 |         db.session.commit() | Operational statement participating in the file's runtime behavior.
L0320 |         msg_id = msg.id | Assignment statement storing or updating program state.
L0321 | | Blank line used for readability and logical separation.
L0322 |     _login_user(client, staff_user["email"], staff_user["password"], role="staff") | Assignment statement storing or updating program state.
L0323 |     resp = client.post(f"/notifications/messages/{msg_id}/delete", data={}, follow_redirects=False) | Assignment statement storing or updating program state.
L0324 |     assert resp.status_code == 302 | Operational statement participating in the file's runtime behavior.
L0325 | | Blank line used for readability and logical separation.
L0326 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0327 |         still_exists = db.session.get(Message, msg_id) | Assignment statement storing or updating program state.
L0328 |         assert still_exists is not None | Operational statement participating in the file's runtime behavior.

```

```

L0329 |         settings = UserSettings.query.filter_by(user_id=User.query.filter_by(email=staff_user["email"]).first().id).first() | Assignment statement storing or updating program state.
L0330 |         assert settings is not None | Operational statement participating in the file's runtime behavior.
L0331 |         prefs = settings.get_preferences() | Assignment statement storing or updating program state.
L0332 |         hidden_ids = prefs.get("hidden_message_ids", []) if isinstance(prefs, dict) else [] | Assignment statement storing or updating program state.
L0333 |         assert msg_id in hidden_ids | Operational statement participating in the file's runtime behavior.
L0334 | | Blank line used for readability and logical separation.
L0335 | | Blank line used for readability and logical separation.
L0336 | def test_developer_share_qr_endpoint_returns_svg_image(client, login_as_developer): | Declares a function/method as a reusable unit of behavior.
L0337 |     login_as_developer() | Operational statement participating in the file's runtime behavior.
L0338 |     resp = client.get("/developer/share-qr.png?format=svg&url=https%3A%2F%2Fexample.com") | Assignment statement storing or updating program state.
L0339 |     assert resp.status_code == 200 | Operational statement participating in the file's runtime behavior.
L0340 |     content_type = (resp.headers.get("Content-Type") or "").lower() | Assignment statement storing or updating program state.
L0341 |     assert "image/svg+xml" in content_type | Operational statement participating in the file's runtime behavior.
L0342 |     body = resp.get_data(as_text=True) | Assignment statement storing or updating program state.
L0343 |     assert "<svg" in body | Operational statement participating in the file's runtime behavior.
L0344 | | Blank line used for readability and logical separation.
L0345 | | Blank line used for readability and logical separation.
L0346 | # ----- | Comment line documenting intent or context for nearby code.
L0347 | # Risk scoring stored on Activity | Comment line documenting intent or context for nearby code.
L0348 | # ----- | Comment line documenting intent or context for nearby code.
L0349 | | Blank line used for readability and logical separation.
L0350 | def test_risk_score_constants_are_sensible(): | Declares a function/method as a reusable unit of behavior.
L0351 |     from app import HIGH_RISK_THRESHOLD, MEDIUM_RISK_THRESHOLD, SLA_DUE_SOON_HOURS | Imports specific names from another module for direct usage.
L0352 |     assert 0 < MEDIUM_RISK_THRESHOLD < HIGH_RISK_THRESHOLD <= 100 | Operational statement participating in the file's runtime behavior.
L0353 |     assert SLA_DUE_SOON_HOURS > 0 | Operational statement participating in the file's runtime behavior.
L0354 | | Blank line used for readability and logical separation.
L0355 | | Blank line used for readability and logical separation.
L0356 | def test_is_public_share_base_rejects_non_routable_hosts(): | Declares a function/method as a reusable unit of behavior.
L0357 |     from app import is_public_share_base | Imports specific names from another module for direct usage.
L0358 | | Blank line used for readability and logical separation.
L0359 |     assert is_public_share_base("http://localhost:5000") is False | Operational statement participating in the file's runtime behavior.
L0360 |     assert is_public_share_base("http://127.0.0.1:5000") is False | Operational statement participating in the file's runtime behavior.
L0361 |     assert is_public_share_base("http://0.0.0.0:5000") is False | Operational statement participating in the file's runtime behavior.
L0362 |     assert is_public_share_base("http://192.168.1.10:5000") is False | Operational statement participating in the file's runtime behavior.
L0363 | | Blank line used for readability and logical separation.
L0364 | | Blank line used for readability and logical separation.
L0365 | def test_is_public_share_base_accepts_public_dns_name(): | Declares a function/method as a reusable unit of behavior.
L0366 |     from app import is_public_share_base | Imports specific names from another module for direct usage.
L0367 | | Blank line used for readability and logical separation.
L0368 |     assert is_public_share_base("https://example.com") is True | Operational statement participating in the file's runtime behavior.
L0369 | | Blank line used for readability and logical separation.
L0370 | | Blank line used for readability and logical separation.
L0371 | def test_classify_risk_level_boundaries(): | Declares a function/method as a reusable unit of behavior.
L0372 |     from app import classify_risk_level, HIGH_RISK_THRESHOLD, MEDIUM_RISK_THRESHOLD | Imports specific names from another module for direct usage.
L0373 |     assert classify_risk_level(HIGH_RISK_THRESHOLD) == "High" | Operational statement participating in the file's runtime behavior.
L0374 |     assert classify_risk_level(HIGH_RISK_THRESHOLD - 1) == "Medium" | Operational statement participating in the file's runtime behavior.
L0375 |     assert classify_risk_level(MEDIUM_RISK_THRESHOLD) == "Medium" | Operational statement participating in the file's runtime behavior.
L0376 |     assert classify_risk_level(MEDIUM_RISK_THRESHOLD - 1) == "Low" | Operational statement participating in the file's runtime behavior.
L0377 |     assert classify_risk_level(0) == "Low" | Operational statement participating in the file's runtime behavior.
L0378 | | Blank line used for readability and logical separation.
L0379 | | Blank line used for readability and logical separation.
L0380 | def test_outage_signal_analysis_flags_site_down_as_critical(): | Declares a function/method as a reusable unit of behavior.
L0381 |     from app import analyze_outage_signals | Imports specific names from another module for direct usage.
L0382 | | Blank line used for readability and logical separation.
L0383 |     result = analyze_outage_signals("Site down with no service and multiple critical alarm events") | Assignment statement storing or updating program state.

```

```

L0384 |     assert result["risk_boost"] > 0 | Operational statement participating in the file's runtime behavior.
L0385 |     assert "site_down" in result["matched_signals"] | Operational statement participating in the file's runtime behavior.
L0386 |     assert any("outage" in flag.lower() for flag in result["critical_flags"]) | Operational statement participating in the file's runtime behavior.
L0387 | | Blank line used for readability and logical separation.
L0388 | | Blank line used for readability and logical separation.
L0389 | def test_outage_signal_analysis_scores_degraded_service_without_critical_flag(): | Declares a function/method as a reusable unit of behavior.
L0390 |     from app import analyze_outage_signals | Imports specific names from another module for direct usage.
L0391 | | Blank line used for readability and logical separation.
L0392 |     result = analyze_outage_signals("Intermittent packet loss and high latency observed") | Assignment statement storing or updating program state.
L0393 |     assert result["risk_boost"] > 0 | Operational statement participating in the file's runtime behavior.
L0394 |     assert "service_degradation" in result["matched_signals"] | Operational statement participating in the file's runtime behavior.
L0395 |     assert result["critical_flags"] == [] | Operational statement participating in the file's runtime behavior.
L0396 | | Blank line used for readability and logical separation.
L0397 | | Blank line used for readability and logical separation.
L0398 | def test_derive_sla_suggestion_returns_escalation_for_overdue_high_risk(): | Declares a function/method as a reusable unit of behavior.
L0399 |     from app import derive_sla_suggestion | Imports specific names from another module for direct usage.
L0400 | | Blank line used for readability and logical separation.
L0401 |     suggestion = derive_sla_suggestion("Overdue", "High") | Assignment statement storing or updating program state.
L0402 |     assert "SLA breached" in suggestion | Operational statement participating in the file's runtime behavior.
L0403 |     assert "escalate" in suggestion.lower() | Operational statement participating in the file's runtime behavior.
L0404 | | Blank line used for readability and logical separation.
L0405 | | Blank line used for readability and logical separation.
L0406 | def test_extract_recommendations_ignores_none_entries(): | Declares a function/method as a reusable unit of behavior.
L0407 |     from app import extract_recommendations_from_details | Imports specific names from another module for direct usage.
L0408 | | Blank line used for readability and logical separation.
L0409 |     details = """SMART INSIGHTS | Assignment statement storing or updating program state.
L0410 | Recommendations: | Operational statement participating in the file's runtime behavior.
L0411 | - None | Operational statement participating in the file's runtime behavior.
L0412 | | Blank line used for readability and logical separation.
L0413 | PHOTO SPECIFICATIONS | Operational statement participating in the file's runtime behavior.
L0414 | - Battery: https://example.com/a.jpg | Operational statement participating in the file's runtime behavior.
L0415 | """ | Docstring boundary used to describe a module, class, or function.
L0416 |     recs = extract_recommendations_from_details(details) | Assignment statement storing or updating program state.
L0417 |     assert recs == [] | Operational statement participating in the file's runtime behavior.
L0418 | | Blank line used for readability and logical separation.
L0419 | | Blank line used for readability and logical separation.
L0420 | def test_overdue_high_risk_sla_escalation_does_not_crash_request(app, client, developer_user): | Declares a function/method as a reusable unit of behavior.
L0421 |     """Regression test: overdue high-risk items should not trigger server errors.""" | Docstring boundary used to describe a module, class, or function.
L0422 |     from datetime import datetime, timedelta, timezone | Imports specific names from another module for direct usage.
L0423 | | Blank line used for readability and logical separation.
L0424 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0425 |         tech = User( | Assignment statement storing or updating program state.
L0426 |             email="overdue-tech@example.com", | Assignment statement storing or updating program state.
L0427 |             full_name="Overdue Tech", | Assignment statement storing or updating program state.
L0428 |             role="technician", | Assignment statement storing or updating program state.
L0429 |             password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0430 |         ) | Operational statement participating in the file's runtime behavior.
L0431 |         db.session.add(tech) | Operational statement participating in the file's runtime behavior.
L0432 |         db.session.add( | Operational statement participating in the file's runtime behavior.
L0433 |             Activity( | Operational statement participating in the file's runtime behavior.
L0434 |                 activity_type="pm", | Assignment statement storing or updating program state.
L0435 |                 details="Overdue high-risk PM", | Assignment statement storing or updating program state.
L0436 |                 created_by=tech.email, | Assignment statement storing or updating program state.
L0437 |                 risk_score=95, | Assignment statement storing or updating program state.
L0438 |                 sla_deadline=datetime.now(timezone.utc).replace(tzinfo=None) - timedelta(hours=1), | Assignment statement storing or updating program state.

```

```

L0439 |         approved_at=None, | Assignment statement storing or updating program state.
L0440 |     ) | Operational statement participating in the file's runtime behavior.
L0441 | ) | Operational statement participating in the file's runtime behavior.
L0442 |     db.session.commit() | Operational statement participating in the file's runtime behavior.
L0443 | | Blank line used for readability and logical separation.
L0444 |     _login_user(client, developer_user["email"], developer_user["password"], role="developer") | Assignment statement storing or up
L0445 |     resp = client.get("/dashboard/", follow_redirects=False) | Assignment statement storing or updating program state.
L0446 |     assert resp.status_code in {200, 302} | Block delimiter controlling scope/structure in this language.
L0447 | | Blank line used for readability and logical separation.
L0448 | | Blank line used for readability and logical separation.
L0449 | def test_desk_activities_shows_fallback_sla_suggestion_for_legacy_rows(app, client, staff_user): | Declares a function/method as a
L0450 |     from datetime import datetime, timedelta, timezone | Imports specific names from another module for direct usage.
L0451 | | Blank line used for readability and logical separation.
L0452 |     with app.app_context(): | Context manager block for safe setup and automatic cleanup.
L0453 |         tech = User( | Assignment statement storing or updating program state.
L0454 |             email="desk-legacy-tech@example.com", | Assignment statement storing or updating program state.
L0455 |             full_name="Desk Legacy Tech", | Assignment statement storing or updating program state.
L0456 |             role="technician", | Assignment statement storing or updating program state.
L0457 |             password_hash=generate_password_hash("Password123!"), | Assignment statement storing or updating program state.
L0458 |         ) | Operational statement participating in the file's runtime behavior.
L0459 |         db.session.add(tech) | Operational statement participating in the file's runtime behavior.
L0460 |         db.session.flush() | Operational statement participating in the file's runtime behavior.
L0461 | | Blank line used for readability and logical separation.
L0462 |         # Legacy-style row with no SMART INSIGHTS recommendations section. | Comment line documenting intent or context for nearby
L0463 |         db.session.add( | Operational statement participating in the file's runtime behavior.
L0464 |             Activity( | Operational statement participating in the file's runtime behavior.
L0465 |                 activity_type="rca", | Assignment statement storing or updating program state.
L0466 |                 details="Site Number: LEG-001\nSite Name: Legacy Site\nIssue: Old imported record", | Assignment statement storing
L0467 |                 created_by=tech.email, | Assignment statement storing or updating program state.
L0468 |                 risk_score=92, | Assignment statement storing or updating program state.
L0469 |                 sla_deadline=datetime.now(timezone.utc).replace(tzinfo=None) - timedelta(hours=2), | Assignment statement storing o
L0470 |                 approved_at=None, | Assignment statement storing or updating program state.
L0471 |             ) | Operational statement participating in the file's runtime behavior.
L0472 |         ) | Operational statement participating in the file's runtime behavior.
L0473 |         db.session.add( | Operational statement participating in the file's runtime behavior.
L0474 |             Activity( | Operational statement participating in the file's runtime behavior.
L0475 |                 activity_type="pm", | Assignment statement storing or updating program state.
L0476 |                 details="Site Number: LEG-002\nSite Name: Legacy Site 2\nIssue: Pending checks", | Assignment statement storing or
L0477 |                 created_by=tech.email, | Assignment statement storing or updating program state.
L0478 |                 risk_score=45, | Assignment statement storing or updating program state.
L0479 |                 sla_deadline=datetime.now(timezone.utc).replace(tzinfo=None) + timedelta(hours=2), | Assignment statement storing o
L0480 |                 approved_at=None, | Assignment statement storing or updating program state.
L0481 |             ) | Operational statement participating in the file's runtime behavior.
L0482 |         ) | Operational statement participating in the file's runtime behavior.
L0483 |         db.session.add( | Operational statement participating in the file's runtime behavior.
L0484 |             Activity( | Operational statement participating in the file's runtime behavior.
L0485 |                 activity_type="pm", | Assignment statement storing or updating program state.
L0486 |                 details="Site Number: LEG-003\nSite Name: Legacy Site 3\nIssue: Stable pending closure", | Assignment statement sto
L0487 |                 created_by=tech.email, | Assignment statement storing or updating program state.
L0488 |                 risk_score=30, | Assignment statement storing or updating program state.
L0489 |                 sla_deadline=datetime.now(timezone.utc).replace(tzinfo=None) + timedelta(hours=18), | Assignment statement storing
L0490 |                 approved_at=None, | Assignment statement storing or updating program state.
L0491 |             ) | Operational statement participating in the file's runtime behavior.
L0492 |         ) | Operational statement participating in the file's runtime behavior.
L0493 |         db.session.commit() | Operational statement participating in the file's runtime behavior.

```

L0494 | | Blank line used for readability and logical separation.

L0495 | _login_user(client, staff_user["email"], staff_user["password"], role="staff") | Assignment statement storing or updating program state.

L0496 | response = client.get("/desk/activities/", follow_redirects=False) | Assignment statement storing or updating program state.

L0497 | assert response.status_code == 200 | Operational statement participating in the file's runtime behavior.

L0498 | body = response.get_data(as_text=True) | Assignment statement storing or updating program state.

L0499 | assert "SLA breached: escalate immediately" in body | Operational statement participating in the file's runtime behavior.

L0500 | assert "SLA due soon" in body | Operational statement participating in the file's runtime behavior.

L0501 | assert "SLA is on track" in body | Operational statement participating in the file's runtime behavior.

File 130: upgrade_msg.txt

L0001 | ■.\.venv\Scripts\python.exe : INFO [alembic.runtime.migration] Context impl | Operational statement participating in the file's runtime behavior.

L0002 | SQLiteImpl. | Operational statement participating in the file's runtime behavior.

L0003 | At line:1 char:1 | Operational statement participating in the file's runtime behavior.

L0004 | + .\.venv\Scripts\python.exe -m flask --app app db upgrade 2>&1 \> Out-F ... | Operational statement participating in the file's runtime behavior.

L0005 | + ~~~~~ | Operational statement participating in the file's runtime behavior.

L0006 | + CategoryInfo : NotSpecified: (INFO [alembic....mpl SQLiteImpl. | Operational statement participating in the file's runtime behavior.

L0007 | :String) [], RemoteException | Operational statement participating in the file's runtime behavior.

L0008 | + FullyQualifiedErrorId : NativeCommandError | Operational statement participating in the file's runtime behavior.

L0009 | | Blank line used for readability and logical separation.

L0010 | INFO [alembic.runtime.migration] Will assume non-transactional DDL. | Operational statement participating in the file's runtime behavior.

L0011 | INFO [alembic.runtime.migration] Running upgrade -> 7332ed65ba00, Add | Operational statement participating in the file's runtime behavior.

L0012 | risk_score and sla_deadline columns and activity indexes | Operational statement participating in the file's runtime behavior.

File 131: upgrade_out_scale.txt

L0001 | ■c:/Users/jonas/OneDrive/Desktop/pm/.venv/Scripts/python.exe : INFO | Operational statement participating in the file's runtime behavior.

L0002 | [alembic.runtime.migration] Context impl SQLiteImpl. | Operational statement participating in the file's runtime behavior.

L0003 | At line:1 char:74 | Operational statement participating in the file's runtime behavior.

L0004 | + ... yContinue ; c:/Users/jonas/OneDrive/Desktop/pm/.venv/Scripts/python.e ... | Operational statement participating in the file's runtime behavior.

L0005 | + ~~~~~ | Operational statement participating in the file's runtime behavior.

L0006 | + CategoryInfo : NotSpecified: (INFO [alembic....mpl SQLiteImpl. | Operational statement participating in the file's runtime behavior.

L0007 | :String) [], RemoteException | Operational statement participating in the file's runtime behavior.

L0008 | + FullyQualifiedErrorId : NativeCommandError | Operational statement participating in the file's runtime behavior.

L0009 | | Blank line used for readability and logical separation.

L0010 | INFO [alembic.runtime.migration] Will assume non-transactional DDL. | Operational statement participating in the file's runtime behavior.

L0011 | ERROR [flask_migrate] Error: Multiple head revisions are present for given | Operational statement participating in the file's runtime behavior.

L0012 | argument 'head'; please specify a specific target revision, | Operational statement participating in the file's runtime behavior.

L0013 | '<branchname>@head' to narrow to a specific head, or 'heads' for all heads | Operational statement participating in the file's runtime behavior.

File 132: watchdog_monitor.py

```
L0001 | import time | Imports dependency modules: time.
L0002 | import hashlib | Imports dependency modules: hashlib.
L0003 | import os | Imports dependency modules: os.
L0004 | | Blank line used for readability and logical separation.
L0005 | WATCHED_DIR = "/" # your project folder | Assignment statement storing or updating program state.
L0006 | file_hashes = {} | Assignment statement storing or updating program state.
L0007 | | Blank line used for readability and logical separation.
L0008 | def hash_file(path): | Declares a function/method as a reusable unit of behavior.
L0009 |     with open(path, "rb") as f: | Context manager block for safe setup and automatic cleanup.
L0010 |         return hashlib.md5(f.read()).hexdigest() | Returns a value (or control) back to the caller.
L0011 | | Blank line used for readability and logical separation.
L0012 | def scan_files(): | Declares a function/method as a reusable unit of behavior.
L0013 |     changes = [] | Assignment statement storing or updating program state.
L0014 |     for root, _, files in os.walk(WATCHED_DIR): | Loop iterating over a sequence to process elements one by one.
L0015 |         for file in files: | Loop iterating over a sequence to process elements one by one.
L0016 |             if file.endswith((".py", ".html", ".js")): | Conditional branch that runs only when its condition is true.
L0017 |                 path = os.path.join(root, file) | Assignment statement storing or updating program state.
L0018 |                 try: | Starts an exception handling block for risky operations.
L0019 |                     new_hash = hash_file(path) | Assignment statement storing or updating program state.
L0020 |                     old_hash = file_hashes.get(path) | Assignment statement storing or updating program state.
L0021 | | Blank line used for readability and logical separation.
L0022 |                     if old_hash and old_hash != new_hash: | Conditional branch that runs only when its condition is true.
L0023 |                         changes.append(f"Modified: {path}") | Operational statement participating in the file's runtime behavior.
L0024 | | Blank line used for readability and logical separation.
L0025 |                         file_hashes[path] = new_hash | Assignment statement storing or updating program state.
L0026 |                     except: | Handles errors raised in the associated try block.
L0027 |                         pass | Flow-control keyword affecting execution in the current block.
L0028 |     return changes | Returns a value (or control) back to the caller.
L0029 | | Blank line used for readability and logical separation.
L0030 | while True: | Loop that repeats while its condition remains true.
L0031 |     changes = scan_files() | Assignment statement storing or updating program state.
L0032 |     if changes: | Conditional branch that runs only when its condition is true.
L0033 |         print("■■ Changes detected:") | Operational statement participating in the file's runtime behavior.
L0034 |         for c in changes: | Loop iterating over a sequence to process elements one by one.
L0035 |             print(c) | Operational statement participating in the file's runtime behavior.
L0036 | | Blank line used for readability and logical separation.
L0037 |     time.sleep(5) | Operational statement participating in the file's runtime behavior.
```

File 133: watchdog_reporter_errors.log

L0001 | [2026-03-27 23:51:33] read failed for C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html: [Errno 13] Permission denied: 'C:\Users\jonas\OneDrive\Desktop\pm\templates\layout.html'

L0002 | [2026-03-27 23:51:33] read failed for C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html: [Errno 13] Permission denied: 'C:\Users\jonas\OneDrive\Desktop\pm\templates\field_rca.html'