



ERGOPACK 745X Li

MOBILE AND ERGONOMIC PALLET STRAPPING SYSTEM





ERGOPACK 745X Li

Mobile and Ergonomic Pallet Strapping System

[ErgoPack X-pert Line](#)

System Information:

Line:	X-pert
Model:	745X Li
Tariff Nr.:	842240
Dimensions (l, w, h):	665 x 770 x 1200 mm
Weight:	104 kg

System Specifications:

Chain:	Standard 6 m
Flexibility (pallet width):	40 - 270 cm
Chain Speed:	66m/min
Flexibility (pallet height):	10 - 230 cm
Line-Laser Type 2:	Included
Standard Tool-Lift:	Included
Sledge 85:	Included
Control:	Electrically via joystick
Sealing head:	Mounted on Tool-Lift
Change settings:	Siemens industry touchscreen

Sealing Head:

Weight:	3,8 – 4,3 kg
Dimensions (l, w, h):	335 x 140 x 180 mm
Tension power:	400 - 4500N
Current (nominal):	Up to 10 A
Strap width:	16 - 19 mm
Strap thickness	0,80 – 1,30 mm
Strap ¹ :	Polypropylene (PP), Polyester (PET)

¹ Coil diameter: 406, 400, 200



ERGOPACK 745X Li

Mobile and Ergonomic Pallet Strapping System

[ErgoPack X-pert Line](#)

Available Options:

[Triplex-Tool-Lift:](#)

Sledge¹:

[Strap-Brake-Relief:](#)

[Headpiece with Bumper](#)²:

Spare battery:

[MOHM](#)³ up to 3.05m:

Additional chain:

Optional

47 | 47S | 85L

Optional

Optional

Optional

Optional

Optional

Battery:

Type:

Dimensions (l, w, h):

Weight:

Loading time:

Voltage (nominal):

Capacity (nominal):

Strapping cycles:

Lithium-Ion

393 x 153 x 82 mm

~5 kg

~3,5 hours

36,3 V

24,15 Ah

Up to 1200

Charging Station:

Type:

Dimensions (l, w, h):

Weight (incl. charger):

Operating voltage:

Power consumption:

Current (nominal):

Wide-range charger

225 x 156 x 69 mm

8,8 kg

100-240 V - 50/60 Hz

Up to ~650 W

Up to 10 A

Certifications:

ISO 12100:2010:

EU decl. of conformity:

AGR:

✓ Available

✓ Available

✓ Available

¹ Sledge 47 for pallets with lower clearance height (min. clearance of 55mm); standard sledge 85 for EPAL and equivalent

² Max. 40mm overhang

³ Mobile Overheight Module

ERGOPACK 745X LI

APPLICATION EXAMPLES

