Mobile and Ergonomic Pallet Strapping System

ERGOPACK 713X LI

Mobile and Ergonomic Pallet Strapping System
ErgoPack X-pert Line

System Information:
Line:	X-pert
Model:	713X Li
Tariff Nr.:	842240
Dimensions (l, w, h):	665 x 770 x 1200 mm
Weight:	103 kg

System Specifications:
Chain:	Standard 6 m
Flexibility (pallet width):	40 - 270 cm
Chain Speed:	66m/min
Flexibility (pallet height):	10 - 230 cm
Line-Laser Type 2:	Included
Standard Tool-Lift:	Included
Sledge 85:	Included
Control:	Electrically via joystick
Sealing head:	Mounted on Tool-Lift
Change settings:	Siemens industry touchscreen

Sealing Head:
Weight:	3,8 – 4,3 kg
Dimensions (l, w, h):	335 x 140 x 180 mm
Tension power:	150 - 1200N
Current (nominal):	Up to 10 A
Strap width:	9 - 13 mm
Strap thickness	0,40 – 0,80 mm
Strap[1]:	Polypropylene (PP), Polyester (PET)

[1] Coil diameter: 406, 400, 200

ERGOPACK 713X LI

Mobile and Ergonomic Pallet Strapping System
ErgoPack X-pert Line

Available Options:

Triplex-Tool-Lift:	Optional
Sledge[1]:	47 | 47S | 85L
Strap-Brake-Relief:	Optional
Headpiece with Bumper[2]:	Optional
Spare battery:	Optional
MOHM[3] up to 3.05m:	Optional
Additional chain:	Optional

Battery:

Type:	Lithium-Ion
Dimensions (l, w, h):	393 x 153 x 82 mm
Weight:	~5 kg
Loading time:	~3,5 hours
Voltage (nominal):	36,3 V
Capacity (nominal):	24,15 Ah
Strapping cycles:	Up to 1200

Charging Station:

Type:	Wide-range charger
Dimensions (l, w, h):	225 x 156 x 69 mm
Weight (incl. charger):	8,8 kg
Operating voltage:	100-240 V - 50/60 Hz
Power consumption:	Up to ~650 W
Current (nominal):	Up to 10 A

Certifications:

ISO 12100:2010:	✓ Available
EU decl. of conformity:	✓ Available
AGR:	✓ Available

---

[1] Sledge 47 for pallets with lower clearance height (min. clearance of 55mm); standard sledge 85 for EPAL and equivalent
[2] Max. 40mm overhang
[3] Mobile Overheight Module

Application Examples