



**ERGOPACK 700X Li**

---

# **MOBILE AND ERGONOMIC PALLET STRAPPING SYSTEM**





## ERGOPACK 700X Li

### Mobile and Ergonomic Pallet Strapping System

[ErgoPack X-pert Line](#)

#### System Information:

|                       |                     |
|-----------------------|---------------------|
| Line:                 | X-pert              |
| Model:                | 700X Li             |
| Tariff Nr.:           | 842240              |
| Dimensions (l, w, h): | 665 x 770 x 1200 mm |
| Weight:               | 95 kg               |

#### System Specifications:

|   |  |
|---|--|
| Chain:                                      | Standard 6 m   |
| <a href="#">Flexibility (pallet width):</a> | 40 - 270 cm  |
| Chain Speed:                                | 66m/min  |
| Flexibility (pallet height):                | 10 - 230 cm  |
| <a href="#">Line-Laser Type 2:</a>          | Optional   |
| <a href="#">Standard Tool-Lift:</a>         | Optional   |
| Sledge 85:                                  | Included   |
| Control:                                    | Electrically via joystick                                      |
| Sealing head:                               | Optional   |
| <a href="#">Change settings:</a>            | Siemens industry touchscreen                                   |
| Possible straps <sup>1</sup> :              | Polypropylene (PP), Polyester (PET),<br>Paper, Cord, Composite |

<sup>1</sup> Coil diameter: 406, 400, 200



# ERGOPACK 700X Li

## Mobile and Ergonomic Pallet Strapping System

[ErgoPack X-pert Line](#)

### Available Options:

[Triplex-Tool-Lift:](#)

Sledge<sup>1</sup>:

[Strap-Brake-Relief:](#)

[Headpiece with Bumper<sup>2</sup>:](#)

Spare battery:

[MOHM<sup>3</sup>](#) up to 3.05m:

Additional chain:

Optional

47 | 47S | 85L

Optional

Optional

Optional

Optional

Optional

### Battery:

Type:

Dimensions (l, w, h):

Weight:

Loading time:

Voltage (nominal):

Capacity (nominal):

Strapping cycles:

Lithium-Ion

393 x 153 x 82 mm

~5 kg

~3,5 hours

36,3 V

24,15 Ah

Up to 1200

### Charging Station:

Type:

Dimensions (l, w, h):

Weight (incl. charger):

Operating voltage:

Power consumption:

Current (nominal):

Wide-range charger

225 x 156 x 69 mm

8,8 kg

100-240 V - 50/60 Hz

Up to ~650 W

Up to 10 A

### Certifications:

ISO 12100:2010:

EU decl. of conformity:

AGR:

✓ Available

✓ Available

✓ Available

<sup>1</sup> Sledge 47 for pallets with lower clearance height (min. clearance of 55mm); standard sledge 85 for EPAL and equivalent

<sup>2</sup> Max. 40mm overhang

<sup>3</sup> Mobile Overheight Module

## ERGOPACK 700X LI

---

### APPLICATION EXAMPLES

