

ERGOPACK GO

MOBILE AND ERGONOMIC PALLET STRAPPING SYSTEM





ERGOPACK GO

Mobile and Ergonomic Pallet Strapping System

[ErgoPack GO](#)

System Information:

Line:	GO
Model:	700
Tariff Nr.:	842240
Dimensions (l, w, h):	630 x 770 x 1200 mm
Weight:	90,0 kg

System Specifications:

Chain:	Standard 5 m
Chain Speed:	40m/min
Flexibility (pallet width):	30 - 240 cm
Flexibility (pallet height):	80 - 190 cm
Standard Tool-Lift:	Included
Sledge 85:	Included
Control:	Electrically via joystick
Sealing head:	Flexible mounting with adapter
Change settings:	With pin
Possible straps ¹ :	Polypropylene (PP), Polyester (PET), Paper, Cord, Composite

Available Options:

Sledge ² :	47 47S 47L
Headpiece with Bumper ³ :	Optional
Spare battery:	Optional
Additional chain:	Upon request

¹ Coil diameter: 406, 400, 200

² Sledge 47 for pallets with lower clearance height (min. clearance of 55mm); standard sledge 85 for EPAL and equivalent

³ Max. 40mm overhang



ERGOPACK GO

Mobile and Ergonomic Pallet Strapping System

[ErgoPack GO](#)

Not available Options:

Triplex-Tool-Lift:	Not available
Line Laser	Not available
Safety Cutter:	Not available
Strap-Brake-Relief:	Not available

Battery:

Type:	24 V lead-fleece battery
Weight:	12,3 kg
Loading time:	8 - 10 hours
Voltage (nominal):	24 V
Strapping cycles	350

Charging Station:

Type:	3-stage lead loader
Operating voltage:	100-240 V - 50/60 Hz
Power consumption:	Max. 60 W
Power supply:	2x 12 V DC/2A

Certifications:

ISO 12100:2010:	✓ Available
EU decl. of conformity:	✓ Available
AGR:	✓ Available

ERGOPACK GO

APPLICATION EXAMPLES

