



**ERGOPACK 700E**

---

# MOBILE AND ERGONOMIC PALLET STRAPPING SYSTEM



# ERGOPACK 700E

## MOBILE AND ERGONOMIC PALLET STRAPPING SYSTEM



### SYSTEM INFORMATION:

Line:	Economy Line
Model:	<u>700E</u>
Generation:	2
Tariff Nr.:	842240
Dimensions (l, w, h):	6300 x 7700 x 1200 mm
Weight:	~88,1 kg
Flexibility (pallet width):	30 - 255 cm
Flexibility (pallet height):	10 - 230 cm
Chain Speed:	40m/min



# ERGOPACK 700E

## Mobile and Ergonomic Pallet Strapping System

ErgoPack Economy-Line

### System Information:

Line:	Economy
Model:	700E
Tariff Nr.:	842240
Dimensions (l, w, h):	630 x 770 x 1200 mm
Weight:	88,1 kg

### System Specifications:

Chain:	Standard 6 m
<a href="#"><u>Flexibility (pallet width):</u></a>	30 - 255 cm
Chain Speed:	40m/min
Flexibility (pallet height):	10 - 230 cm
<a href="#"><u>Line-Laser Type 2:</u></a>	Optional
<a href="#"><u>Standard Tool-Lift:</u></a>	Optional
Sledge 85:	Included
Control:	Electrically via joystick
Sealing head:	Optional
<a href="#"><u>Change settings:</u></a>	With pin
Possible straps <sup>1</sup> :	Polypropylene (PP), Polyester (PET), Paper, Cord, Composite

<sup>1</sup>Coil diameter: 406, 400, 200



# ERGOPACK 700E

## Mobile and Ergonomic Pallet Strapping System

ErgoPack Economy-Line

### Available Options:

[Triplex-Tool-Lift:](#)

Sledge<sup>1</sup>:

Optional

47 | 47S | 85L

[Strap-Brake-Relief:](#)

Optional

[Headpiece with Bumper<sup>2</sup>:](#)

Optional

Spare battery:

Optional

[MOHM<sup>3</sup>](#) up to 3.05m:

Optional

Additional chain:

Optional

### Battery:

Type:

24 V lead-fleece battery

Weight:

12,3 kg

Loading time:

8 - 10 hours

Voltage (nominal):

24 V

Strapping cycles

350

### Charging Station:

Type:

3-stage lead loader

Operating voltage:

100-240 V - 50/60 Hz

Power consumption:

Max. 60 W

Power supply:

2x 12 V DC/2A

### Certifications:

ISO 12100:2010:

✓ Available

EU decl. of conformity:

✓ Available

AGR:

✓ Available

<sup>1</sup> Sledge 47 for pallets with lower clearance height (min. clearance of 55mm); standard sledge 85 for EPAL and equivalent

<sup>2</sup> Max. 40mm overhang

<sup>3</sup> Mobile Overheight Module



**ERGOPACK 700E**

---

---

# **OPTIONS INCLUDED IN SYSTEM AND PRICE**



# ERGOPACK 700E

## OPTIONS INCLUDED IN SYSTEM AND PRICE

### CONTROL

- Electrical via joystick
- [Video](#)



### SET PALLET WIDTH

- With pin
- Pallet width + 20cm
- [Video](#)



### SLEDGE

- Standard sledge 85 included
- For clearance height >95mm





**ERGOPACK 700E**

---

---

# **OPTIONAL ACCESSORIES**

# ERGOPACK 700E

## ADDITIONAL OPTIONS AND ACCESSORIES

### TOOL-LIFT

- Standard for pallets >80cm
- Sealing head quick release included
- [Video](#)



### SEALING HEAD

- Sealing head installed and mounted on system



### SLEDGE

- 47 for pallets with a clearance height of 55mm to 95mm
- 47S for pallets with narrow entry, 160mm in width
- 47L extended skid for lower runner heights of up to 40mm



# ERGOPACK 700E

## ADDITIONAL OPTIONS AND ACCESSORIES

### TRIPLEX-TOOL-LIFT (TTL)

- Ideal for pallets lower than 80cm
- Suitable for pallets as low as 10cm in height
- [Video](#)



### SEALING HEAD REMOVABLE FROM TTL

- Adapter to release the sealing head from the Tool-Lift



### LINE LASER

- For optimal system positioning
- [Video](#)



# ERGOPACK 700E

## ADDITIONAL OPTIONS AND ACCESSORIES

### STRAP-BRAKE-RELIEF

- For pallets higher than 120cm
- Relief in pulling out strap
- [Video](#)



### HEAD PIECE WITH BUMPER

- For pallets with an overhang of max. 40mm
- Bumper to pass the overhang
- [Video](#)



### MORE CHAIN IN SYSTEM

- Up to 2m extra, 8m in total



### SPARE BATTERY

- Optimal for multiple shifts





## ERGOPACK 700E

### ADDITIONAL OPTIONS AND ACCESSORIES

#### MOBILE OVERHEIGHT MODULE

- For pallets higher than 230cm
- Up to 305cm
- [Video](#)



#### MOBILE SLEDGE TUNNEL

- Goods strapped on scantlings
- One pair includes two tunnels
- [Video](#)



#### STATIONARY SLEDGE TUNNEL

- Adjustable sledge tunnel for different widths
- [Video](#)



## ERGOPACK 700E

### APPLICATION EXAMPLES

