MOBILE AND ERGONOMIC PALLET STRAPPING SYSTEM

ERGOPACK 745E

Mobile and Ergonomic Pallet Strapping System
ErgoPack Economy-Line

System Information:

Line:	Economy
Model:	745E
Tariff Nr.:	842240
Dimensions (l, w, h):	630 x 770 x 1200 mm
Weight:	92,9 kg

System Specifications:

Chain:	Standard 6 m
Flexibility (pallet width):	30 - 255 cm
Chain Speed:	40m/min
Flexibility (pallet height):	10 - 230 cm
Line-Laser Type 2:	Optional
Standard Tool-Lift:	Included
Sledge 85:	Included
Control:	Electrically via joystick
Sealing head:	Mounted on Tool-Lift
Change settings:	With pin

Sealing Head:

Weight:	3,8 – 4,3 kg
Dimensions (l, w, h):	335 x 140 x 180 mm
Tension power:	400 - 4500N
Current (nominal):	Up to 10 A
Strap width:	16 - 19 mm
Strap thickness	0,80 – 1,30 mm
Strap[1]:	Polypropylene (PP), Polyester (PET)

[1] Coil diameter: 406, 400, 200

ErgoPack 745E

Mobile and Ergonomic Pallet Strapping System
ErgoPack Economy-Line

Available Options:

Triplex-Tool-Lift:	Optional
Sledge[1]:	47 | 47S | 85L
Strap-Brake-Relief:	Optional
Headpiece with Bumper[2]:	Optional
Spare battery:	Optional
MOHM[3] up to 3.05m:	Optional
Additional chain:	Optional

Battery:

Type:	24 V lead-fleece battery
Weight:	12,3 kg
Loading time:	8 - 10 hours
Voltage (nominal):	24 V
Strapping cycles	350

Charging Station:

Type:	3-stage lead loader
Operating voltage:	100-240 V - 50/60 Hz
Power consumption:	Max. 60 W
Power supply:	2x 12 V DC/2A

Certifications:

ISO 12100:2010:	✓ Available
EU decl. of conformity:	✓ Available
AGR:	✓ Available

---

[1] Sledge 47 for pallets with lower clearance height (min. clearance of 55mm); standard sledge 85 for EPAL and equivalent
[2] Max. 40mm overhang
[3] Mobile Overheight Module

Application Examples