

**ERGOPACK 700E**

---

# **MOBILE AND ERGONOMIC PALLET STRAPPING SYSTEM**





# ERGOPACK 700E

---

## Mobile and Ergonomic Pallet Strapping System

[ErgoPack Economy-Line](#)

### System Information:

Line:	Economy
Model:	700E
Tariff Nr.:	842240
Dimensions (l, w, h):	630 x 770 x 1200 mm
Weight:	88,1 kg

### System Specifications:

Chain:	Standard 6 m
<a href="#">Flexibility (pallet width):</a>	30 - 255 cm
Chain Speed:	40m/min
Flexibility (pallet height):	10 - 230 cm
<a href="#">Line-Laser Type 2:</a>	Optional
<a href="#">Standard Tool-Lift:</a>	Optional
Sledge 85:	Included
Control:	Electrically via joystick
Sealing head:	Optional
<a href="#">Change settings:</a>	With pin
Possible straps <sup>1</sup> :	Polypropylene (PP), Polyester (PET), Paper, Cord, Composite

<sup>1</sup> Coil diameter: 406, 400, 200



# ERGOPACK 700E

## Mobile and Ergonomic Pallet Strapping System

[ErgoPack Economy-Line](#)

### Available Options:

[Triplex-Tool-Lift:](#)

Sledge<sup>1</sup>:

[Strap-Brake-Relief:](#)

[Headpiece with Bumper<sup>2</sup>:](#)

Spare battery:

[MOHM<sup>3</sup>](#) up to 3.05m:

Additional chain:

Optional

47 | 47S | 85L

Optional

Optional

Optional

Optional

Optional

### Battery:

Type:

24 V lead-fleece battery

Weight:

12,3 kg

Loading time:

8 - 10 hours

Voltage (nominal):

24 V

Strapping cycles

350

### Charging Station:

Type:

3-stage lead loader

Operating voltage:

100-240 V - 50/60 Hz

Power consumption:

Max. 60 W

Power supply:

2x 12 V DC/2A

### Certifications:

ISO 12100:2010:

✓ Available

EU decl. of conformity:

✓ Available

AGR:

✓ Available

<sup>1</sup> Sledge 47 for pallets with lower clearance height (min. clearance of 55mm); standard sledge 85 for EPAL and equivalent

<sup>2</sup> Max. 40mm overhang

<sup>3</sup> Mobile Overheight Module

## ERGOPACK 700E

---

### APPLICATION EXAMPLES

