Student excuse generator

Prompts: -

1st Prompt

Write a beginner-friendly C++ console program for a Student Excuse Generator.
The program should:
1. Take the student's name as input.
2. Store at least 10 excuse templates in a vector (use {name} as placeholder).
3. Randomly select one excuse each time the program runs.
4. Replace {name} with the entered name.
5. Display the final excuse.
Provide complete working code with basic comments.

Check frontend design skill >

Here's the complete C++ program with clean comments:

Student Excuse Generator C++ program >

Output: -

```
PS C:\Users\Laxmi> cd "c:\Users\Laxmi\OneDrive\Desktop\FOCP2-ASSIGNMENT\
" ; if ($?) { g++ student_excuse_generator.cpp -o student_excuse_generat
or } ; if ($?) { .\student_excuse_generator }
Enter your name: priya

Generated Excuse:
priya's system crashed while saving the assignment.
PS C:\Users\Laxmi\OneDrive\Desktop\FOCP2-ASSIGNMENT>
```

2nd Prompt: -

Improve the randomness in my C++ program. Replace rand() and srand() with the modern <random> library using mt19937 and uniform_int_distribution. Keep the program logic the same, make the code beginner-friendly, and add short comments explaining the changes.

Output: -

```
> Users > Laxmi > OneDrive > Desktop > FOCP2-ASSIGNMENT > student_excuse_generator.cpp > main
#include <iostream>
#include <vector>
#include <random>   // for better randomness
using namespace std;

int main() {
    string name;

    // 1. Take student's name as input
    cout << "Enter your name: ";
    getline(cin, name);

```

```
PS C:\Users\Laxmi> cd "c:\Users\Laxmi\OneDrive\Desktop\FOCP2-ASSIGNMENT\
" ; if ($?) { g++ student_excuse_generator.cpp -o student_excuse_generat
or } ; if ($?) { .\student_excuse_generator }
Enter your name: xyz

Generated Excuse:
xyz got stuck in unexpected traffic for hours.
PS C:\Users\Laxmi\OneDrive\Desktop\FOCP2-ASSIGNMENT>
```

Final Prompt: -

Make my C++ Student Excuse Generator smarter and more realistic. Make sure the same excuse doesn't repeat again and again—once all excuses are used, it should reset. Ask only for the student's name and use it to personalize the excuse. Instead of a single line, generate a short 2–3 sentence story so it feels more real. Also improve randomness so some normal excuses appear more often while rare or funny ones appear less. Keep the code simple, beginner-friendly, and add clear comments explaining each part.

Final Output: -

```
PS C:\Users\Laxmi> cd "c:\Users\Laxmi\OneDrive\Desktop\FOCP2-ASSIGNMENT\" ; if ($?) { g++ student_excuse_generator.cpp -o student_exc
use_generator } ; if ($?) { .\student_excuse_generator }
Enter your name: xyz

Generated Excuse:
xyz was not feeling well while working on the assignment. Because of this, it couldn't be completed on time. xyz will try to submit i
t soon.
PS C:\Users\Laxmi\OneDrive\Desktop\FOCP2-ASSIGNMENT>
```