

Wireguard config pfsense

Étape 1 — Installer WireGuard sur pfSense

System → Package Manager → Available Packages → chercher WireGuard → Install.

Étape 2 — Créer le tunnel WireGuard

VPN → WireGuard → Tunnels → Add Tunnel

Enable : ☒
Description : VPN-Acces-Distant
Listen Port : 51820
Interface Keys : Generate → noter la clé publique du serveur
Interface Address : 10.10.100.1/24 (subnet VPN dédié)

Save

The screenshot shows the 'Edit' page for a WireGuard tunnel in pfSense. The breadcrumb trail at the top is 'VPN / WireGuard / Tunnels / Edit'. Below the breadcrumb, there are tabs for 'Tunnels', 'Peers', 'Settings', and 'Status', with 'Tunnels' being the active tab. The main content area is divided into two sections: 'Tunnel Configuration (tun_wg0)' and 'Interface Configuration (tun_wg0)'. In the 'Tunnel Configuration' section, the 'Enable' checkbox is checked, and a note states: 'Note: Tunnel cannot be disabled when assigned to a pfSense interface.' The 'Description' field contains 'Wireguard VPN'. The 'Listen Port' field contains '51820'. The 'Interface Keys' section shows a private key field (masked with dots) and a public key field containing 'MhfkL0ftcGQCFLujR1lykXlt6FEeCDcCAmXK/pwpfWQ='. There is a 'Generate' button next to the public key field. Below the 'Interface Configuration' section, there are links for 'Assignment' (WIREGUARDVPN (opt3)), 'Interface' (Interface Configuration), and 'Firewall Rules' (Firewall Configuration). At the bottom right, there is a watermark for 'Activator Windows'.

Étape 3 — Ajouter les peers (utilisateurs)

VPN → WireGuard → Peers → Add Peer

Pour chaque utilisateur :

Tunnel : VPN-Acces-Distant
Description : Nom de l'utilisateur
Public Key : clé publique du client (générée côté client)
Allowed IPs : 10.10.100.2/32 (IP unique par utilisateur)

The screenshot shows the 'Edit' page for a WireGuard peer in pfSense. The breadcrumb trail is 'VPN / WireGuard / Peers / Edit'. The 'Peers' tab is selected. The 'Peer Configuration' section includes: 'Enable' (checked), 'Tunnel' (set to 'tun_wg0 (Wireguard VPN)'), 'Description' (set to 'Responsable commerce'), 'Dynamic Endpoint' (checked), 'Keep Alive' (set to 'Keep Alive'), 'Public Key' (set to 'fCo/wO4pXw+F1fLYwPAMaz6ll7OI/HZIANNrJvBJmU4='), and 'Pre-shared Key' (empty). The 'Address Configuration' section shows 'Allowed IPs' set to '10.10.100.2 / 32' and 'Client Address' set to 'Client Address'. A watermark for 'Activator Windows' is visible on the right side of the page.

Étape 4 — Créer l'interface WireGuard dans pfSense

Interfaces → Assignments → ajouter `tun_wg0` → **Save**

Dans **Interfaces → WG** :

Enable : ☒
Description : WG
IPv4 : Static → 10.10.100.1/24

Il faut d'abord l'activer avant de pouvoir le rajouter dans l'interfaces

The screenshot shows the 'Settings' page for WireGuard in pfSense. The breadcrumb trail is 'VPN / WireGuard / Settings'. The 'Settings' tab is selected. The 'General Settings' section includes: 'Enable' (checked), 'Keep Configuration' (checked), and 'Endpoint Hostname' (set to '300'). A 'Track System Resolve Interval' checkbox is also visible.

Interfaces / Interface Assignments

Interface Assignments

Interface Groups

Wireless

VLANs

QinQs

PPPs

GREs

GIFs

Bridges

LAGGs

Interface	Network port
WAN	em0 (00:0c:29:24:7d:44)
LAN	em1 (00:0c:29:24:7d:4e) Delete
VLAN40	em2 (00:0c:29:24:7d:58) Delete
DMZ	em3 (00:0c:29:24:7d:62) Delete
WireguardVPN	tun_wg0 (tun_wg0) Delete

Save

Étape 5 — Règles firewall

Firewall → Rules → WG

Règle 1 — Autoriser accès aux partages AD :

Action : Pass
Protocol : TCP
Source : WG net (10.10.100.0/24)
Destination : 10.0.20.10
Port : 445 (SMB), 139, 135
Description : Accès partages AD

Règle 2 — Autoriser DNS :

Action : Pass
Protocol : TCP/UDP
Source : WG net
Destination : 10.0.20.10
Port : 53
Description : DNS via AD

Floating WireGuard WAN LAN VLAN40 DMZ WIREGUARDVPN

Rules (Drag to Change Order)											
☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓ 0/24 KIB	IPv4 TCP	WIREGUARDVPN net	*	10.0.20.10	445 (MS DS)	*	none		Accès partage AD	    
☐	✓ 0/0 B	IPv4 TCP	WIREGUARDVPN net	*	10.0.20.10	139 (NetBIOS-SSN)	*	none		Accès partage AD	    
☐	✓ 0/0 B	IPv4 TCP	WIREGUARDVPN net	*	10.0.20.10	135	*	none		Accès partage AD	    
☐	✓ 1/7 KIB	IPv4 TCP/UDP	WIREGUARDVPN net	*	10.0.20.10	53 (DNS)	*	none		DNS AD	    

↑ Add

↓ Add

Delete

Toggle

Copy

Save

+ Separator

Firewall → Rules → WAN

Action : Pass
Protocol : UDP
Source : Any
Destination : WAN address
Port : 51820
Description : WireGuard entrant

The screenshot shows the 'Firewall / Rules / WAN' configuration page in pfSense. The 'WAN' tab is selected. Below the tabs, there is a table of rules. The first rule is 'Block bogon networks' with a status of '0/2 KiB' and a protocol of '*'. The second rule is 'WireGuard entrant' with a status of '0/60 KiB', protocol of 'IPv4 UDP', source of '*', destination of 'WAN address', and port of '51820'. The 'WireGuard entrant' rule is checked and has a green checkmark. At the bottom, there are buttons for 'Add', 'Delete', 'Toggle', 'Copy', 'Save', and 'Separator'.

Rules (Drag to Change Order)
☒ 0/2 KiB * Reserved Not assigned by IANA Block bogon networks
☒ 0/60 KiB IPv4 UDP * WAN address 51820 * none WireGuard entrant

Ne pas oublié de désactiver le Block private networks dans Interfaces → WAN

The screenshot shows the 'Reserved Networks' configuration page. It has two sections: 'Block private networks and loopback addresses' which is unchecked, and 'Block bogon networks' which is checked. The 'Block bogon networks' section has a note: 'Blocks traffic from reserved IP addresses (but not RFC 1918) or not yet assigned by IANA. Bogons are prefixes that should never appear in the Internet routing table, and so should not appear as the source address in any packets received. This option should only be used on external interfaces (WANs), it is not necessary on local interfaces and it can potentially block required local traffic. Note: The update frequency can be changed under System > Advanced, Firewall & NAT settings.'

Étape 6 — Configurer le client WireGuard

Sur le PC de l'utilisateur, installer **WireGuard for Windows** depuis wireguard.com.

Créer une configuration :

```
[Interface]
PrivateKey = <clé privée client générée>
Address = 10.0.200.2/32
DNS = 10.0.20.10

[Peer]
PublicKey = <clé publique du serveur pfSense>
PresharedKey = <preshared créer dans le peers>
AllowedIPs = 10.0.20.0/24, 10.10.100.0/24
```

Endpoint = <IP WAN de pfsense>:51820
PersistentKeepalive = 25

→ Dans Status → Interfaces

AllowedIPs = 10.0.20.0/24 → seul le trafic vers le LAN passe par le VPN, le reste va directement sur Internet (split tunnel).

Étape 7 — Accéder aux partages

Une fois connecté au VPN, depuis le poste client :

```
\\10.0.20.10\NomDuPartage
```

Ou mapper un lecteur réseau :

powershell

```
net use Z: \\10.0.20.10\NomDuPartage /user:cyna\utilisateur
```