
ChronoHive Evaluation Package

Evaluation quickstart

CONFIDENTIAL — PROPRIETARY

**Licensed solely for evaluation under the ChronoHive Terms
of Confidentiality and the ChronoHive Evaluation License.**

Do not distribute, copy, or publicly host.

© 2026 Layer1Labs Silicon Inc. All rights reserved.

Evaluate ChronoHive's storage-admission capability. This is a **client package**: Python clients and tools that drive the hosted ChronoHive eval API — there is no server to self-host in this repository. The authoritative eval API lives with the ChronoHive service; this package is how evaluators reach it.

The API serves **real admission decisions from the ChronoHive Runtime kernel** against a **simulated** storage backend, contention model, and storage API surface. Evaluation numbers are simulation outcomes, not hardware measurements.

Quickstart (~5 minutes)

```
# 1. Get an API key from your ChronoHive contact, then read the canonical TOC:
curl https://api.layer1labs.ai/v1/toc

# 2. Sign and execute the TOC (pure-Python ed25519, no dependencies):
python3 tools/sign_toc.py --api-url https://api.layer1labs.ai \
    --key-id <your-key-id> --name "Jane Doe" \
    --org "Example Corp" --email jane@example.com --submit

# 3. Run the worked example end to end (TOC → scenario → live kernel
#    decisions → result fetch):
python3 examples/eval_walkthrough.py --api-url https://api.layer1labs.ai \
    --api-key "$CHRONOHIVE_API_KEY" --key-id <your-key-id> \
    --name "Jane Doe" --org "Example Corp" --email jane@example.com
```

The one rule: execute the TOC first

Every eval endpoint stays locked (403 `toc_acceptance_required`) until your API key has a verified Terms of Confidentiality acceptance on file. The flow:

1. Read the canonical TOC: GET `/v1/toc` (or `TOC.md` in this repo —

same text, pinned by SHA-256).

1. Sign it with `tools/sign_toc.py` (generates an ed25519 keypair,

binds the TOC hash to your key id and identity, writes `toc_signing.key` at mode 600 and to `c_acceptance.json`).

1. Submit the acceptance: POST `/v1/toc/accept`.

2. Keep `toc_signing.key` — it is your proof of execution. Never commit

it anywhere.

What's in this package

Path	What it is
clients/compile_client.py	Complete-project LF→blob compile client: hosted API mode, local pinned-toolchain mode, and an offline --check self-test
examples/eval_walkthrough.py	Worked end-to-end admission example (TOC → scenario → live kernel decisions)
tools/sign_toc.py	TOC signing and submission tool (pure-Python ed25519)
tools/toc_common.py, tools/ed25519.py	Acceptance-token format and RFC 8032 ed25519 implementation
lf/	Complete LF workload project (IoCoordinator.lf), editor config, and a checked-in reference blob for offline verification
toolchain/	Pinned LF toolchain: vendored chronoc v0.1.0 binary + lfc v0.13.0 fetch (SHA-256 verified)
scripts/compile_lf.sh	LF→blob compile helper (self-contained; needs only a JVM for lfc)
scripts/demo-lf.sh	Guided LF tour: source → validate → compile → blob provenance
scripts/fetch-lfc.sh	One-time pinned-lfc download with hash verification
docs/ARCHITECTURE.md	How it works: system architecture, request gating, and how to read your numbers (start here if you want the big picture)
docs/API.md	Full hosted API reference, including the /v1/lf/compile contract

docs/LF_TOOLCHAIN.md	Toolchain pins and the LF→blob pipeline
TOC.md	Terms of Confidentiality (pinned by SHA-256)
pdf/	Print-ready PDFs of every document: Quickstart, How It Works, API Reference, LF Toolchain, TOC

Compiling an LF workload to a blob

Lingua Franca workloads compile to the `.chb` v1 artifact the ChronoHive engine executes. The compile takes the **complete LF project** — every `.lf` file as a file map — plus an entrypt, parameters, and capacities:

```
python3 clients/compile_client.py --api-url https://api.layer1labs.ai \
  --api-key "$CHRONOHIVE_API_KEY" --capacity storage_bw=100 -o /tmp/io.chb
```

The hosted compile API requires a key with a **compile license** (issued by the operator) on top of TOC execution. It enforces the same contract the client does: ≤ 64 files, ≤ 512 KiB per file, ≤ 2 MiB aggregate, relative `.lf` paths only, 120 s compile timeout.

For a guided tour of the same chain (source → pinned-`lfc` validation → `chronoc` lowering → blob provenance), run:

```
scripts/demo-lf.sh
```

or compile the checked-in project directly with the vendored toolchain (self-contained — needs only a JVM for `lfc`):

```
scripts/compile_lf.sh lf/IoCoordinator.lf -o io.chb --capacity storage_bw=100
```

Full authoring setup (IDE extension, Java) is documented in [docs/LF_TOOLCHAIN.md](#).

Evaluation itself needs neither — the API, the worked example, and the scenarios all run on stdlib Python.

Compiling is optional for evaluation — the admission API needs neither `lfc` nor `chronoc`. The local mode (`--local`) and the offline check (`--check`, which verifies the checked-in reference blob byte-structure with no network and no `chronoc` — pinned `lfc` + a JRE are still required) cover evaluators who work air-gapped.

Verifying the package

```
python3 scripts/check.py
```

The gate byte-compiles every Python file, reproduces the RFC 8032 ed25519 test vectors, runs the branding sweep (vendor-neutrality, no internal markers), and runs the compile client's `--check` (LF project map, pinned `lfc` validation gate, reference-blob verification).

License and confidentiality

This package is **proprietary and confidential**. Your rights are limited to evaluation under [TOC.md](#) and [LICENSE](#) — no production use, no redistribution, no public hosting. See [NOTICE](#) for the honesty notes that apply to every evaluation number.