\\USER\UserProtocols\Renzo\JiaJia\MP2RAGE_slab_0.4x04x1.2_T1

USER: tfl_wip900b17a

Voxel size: 0.4×0.4×1.2 mm Rel. SNR: 1.00

PAT: 2

TA: 2:26

			_ •
Properties		Distortion Corr. Prescan Normalize	Off Off
Prio Recon	Off	Raw filter	Off
Before measurement After measurement		Elliptical filter	Off
Load to viewer	On	Geometry	
Inline movie	Off	Multi-slice mode	Single shot
Auto store images	On	Series	Interleaved
Load to stamp segments	Off		
Load images to graphic	Off	Table position	H
segments		Table position	0 mm
Auto open inline display	Off	Inline Composing	Off
Start measurement without	On	mine Composing	Oli
further preparation	.	System	
Wait for user to start	Off	V32	Off
Start measurements	single	A32	On
1	og.o	Docitioning goods	FIV
Routine		Positioning mode	FIX
Slab group 1		MSMA	S - C - T
Slabs	1	Sagittal	R >> L
Dist. factor	50 %	Coronal	A >> P
Position	R30.1 P0.3 H28.1	Transversal	F >> H
Orientation	T > S30.8 > C-11.5	Save uncombined	Off
Phase enc. dir.	R >> L	Coil Combine Mode	Adaptive Combine
Rotation	60.00 deg	AutoAlign	
Phase oversampling	0 %	Auto Coil Select	Default
Slice oversampling	0.0 %	Shim mode	Standard
Slices per slab	32	Adjust with body coil	Off
FoV read	140 mm	Confirm freq. adjustment	Off
FoV phase	100.0 %	Assume Silicone	Off
Slice thickness	1.20 mm	! Ref. amplitude 1H	277.000 V
TR	6000 ms	Adjustment Tolerance	Auto
TE	4.23 ms	Adjust volume	Auto
Averages	1	! Position	R26.7 A7.7 H20.0
Concatenations	1	! Position	
Filter	None		Transversal
Coil elements	A32	! Rotation	0.00 deg
1	, .o <u>-</u>	! R >> L	89 mm
Contrast			64 mm
Magn. preparation	Non-sel. IR	!F>> H	58 mm
TI 1	900 ms	Physio	
TI 2	2900 ms	1st Signal/Mode	None
Flip angle 1	6 deg		
Flip angle 2	7 deg	Dark blood	Off
Fat suppr.	None	Resp. control	Off
Water suppr.	None	resp. control	On
2nd Inversion Contrast	On	Composing	
Averaging mode	Long term	Sequence	
Reconstruction	Magn./Phase	Introduction	On
Measurements	1	Dimension	3D
Multiple series	Each measurement	Elliptical scanning	Off
Decelution		Asymmetric echo	Off
Resolution		Contrasts	1
Base resolution	320	Bandwidth	190 Hz/Px
Phase resolution	100 %	Flow comp.	No
Slice resolution	100 %	Echo spacing	8.6 ms
Phase partial Fourier	Off		
Slice partial Fourier	6/8	RF pulse type	Fast
PAT mode	GRAPPA	Gradient mode	Fast
Accel, factor PE	2	Excitation	Slab-sel.
Ref. lines PE	24	RF spoiling	On
Accel. factor 3D	∠ 1 1	EET Scale Factor	150 %
	Integrated	FFT Scale Factor	
Reference scan mode	Integrated	Morphometry Analysis	Off Off
Image Filter	Off	FID MoCo Logging FID Coil Phase Corr.	Off Off
		FID Coll Phase Coff.	Off

SIEMENS MAGNETOM Investigational_Device_7T syngo MR B17

LIN/PAR Swap	On
Ext. INV Pulse	On
Flip Angle	1400
Phase Filter	0 px
Uniform Image	On
Head Mask on UNI	Off
T1 Map	On
Complex Div. Image	On
Denoise Weighting	150
FLAWS	Off