

Table of contents

\\USER

<table border="1"><tr><td>Alex</td></tr></table>	Alex
Alex	

<table border="1"><tr><td><table border="1"><tr><td>VASO</td></tr></table></td></tr></table>	<table border="1"><tr><td>VASO</td></tr></table>	VASO
<table border="1"><tr><td>VASO</td></tr></table>	VASO	
VASO		

<table border="1"><tr><td><table border="1"><tr><td>20250213_aepig</td></tr></table></td></tr></table>	<table border="1"><tr><td>20250213_aepig</td></tr></table>	20250213_aepig
<table border="1"><tr><td>20250213_aepig</td></tr></table>	20250213_aepig	
20250213_aepig		

<table border="1"><tr><td><table border="1"><tr><td>rslh_ep3d_vaso_nih5h_G16_FS_tra_bw1796_SVD_wVASO</td></tr></table></td></tr></table>	<table border="1"><tr><td>rslh_ep3d_vaso_nih5h_G16_FS_tra_bw1796_SVD_wVASO</td></tr></table>	rslh_ep3d_vaso_nih5h_G16_FS_tra_bw1796_SVD_wVASO
<table border="1"><tr><td>rslh_ep3d_vaso_nih5h_G16_FS_tra_bw1796_SVD_wVASO</td></tr></table>	rslh_ep3d_vaso_nih5h_G16_FS_tra_bw1796_SVD_wVASO	
rslh_ep3d_vaso_nih5h_G16_FS_tra_bw1796_SVD_wVASO		

\\USER\Alex\VASO\20250213_aepig\rslh_ep3d_vaso_nih5h_G16_FS_tra_bw1796_SVD_wVASO

TA: 15:18 PM: FIX Voxel size: 0.8×0.8×0.8 mmPAT: 16 Rel. SNR: 1.00 : nih5g 27

Properties

Prio recon	Off
Load images to viewer	On
Inline movie	Off
Auto store images	On
Load images to stamp segments	Off
Load images to graphic segments	Off
Auto open inline display	Off
Auto close inline display	Off
Start measurement without further preparation	Off
Wait for user to start	Off
Start measurements	Single measurement

Routine

Slab group	1
Slabs	1
Position	L0.0 A0.7 F9.4 mm
Orientation	T > C-15.4
Phase enc. dir.	A >> P
AutoAlign	---
Slab Scale	-10 %
Slices per slab	200
FoV read	200 mm
FoV phase	96.6 %
Slice thickness	0.85 mm
TR 1	37.5 ms
TR 2	4880 ms
TE 1	17.50 ms
Averages	1
Filter	None
Coil elements	R63

Contrast - Common

TR 1	37.5 ms
TR 2	4880 ms
TE 1	17.50 ms
Multi-echo spacing	32 ms
Magn. preparation	Non-sel. HSN IR
TI 1	1147.5 ms
TI 2	3022.5 ms
Flip angle	18 deg
Fat suppr.	Fat sat.
Magn. Prep. Shots	1

Contrast - Dynamic

Averages	1
Averaging mode	Long term
Reconstruction	Magnitude
Measurements	186
Pause after meas.	0.0 s

Resolution - Common

FoV read	200 mm
FoV phase	96.6 %
Slice thickness	0.85 mm
Base resolution	236
Phase resolution	100 %
Slice resolution	100 %
Phase partial Fourier	7/8
Slice partial Fourier	Off

Resolution - Common

Interpolation	Off
---------------	-----

Resolution - iPAT

PAT mode	CAIPIRINHA
Acc. factor PE	4
Ref. lines PE	80
Acc. factor 3D	4
Ref. lines 3D	36
CAIPI 3D Shift	2
Reference Scan Mode	GRE/separate
CAIPI Mode (tooltip)	Skipped-CAIPI
Total PAT factor	16

Resolution - Filter Image

Image Filter	Off
Distortion Corr.	Off
Prescan Normalize	Off
Normalize	Off
B1 filter	Off

Resolution - Filter Rawdata

Raw filter	Off
Elliptical filter	Off

Geometry - Common

Slab group	1
Slabs	1
Position	L0.0 A0.7 F9.4 mm
Orientation	T > C-15.4
Phase enc. dir.	A >> P
Slab Scale	-10 %
Slices per slab	200
FoV read	200 mm
FoV phase	96.6 %
Slice thickness	0.85 mm
TR 1	37.5 ms
TR 2	4880 ms

Geometry - AutoAlign

Slab group	1
Position	L0.0 A0.7 F9.4 mm
Orientation	T > C-15.4
Phase enc. dir.	A >> P
AutoAlign	---
Initial Position	L0.0 A0.7 F9.4
L	0.0 mm
A	0.7 mm
F	9.4 mm
Initial Rotation	0.00 deg
Initial Orientation	T > C
T > C	-15.4
> S	0.0

Geometry - Saturation

Saturation mode	Standard
Fat suppr.	Fat sat.

Geometry - Tim Planning Suite

Set-n-Go Protocol	Off
Table position	H

Geometry - Tim Planning Suite

Table position	0 mm
Inline Composing	Off

System - Miscellaneous

Positioning mode	FIX
Table position	H
Table position	0 mm
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	F >> H
Coil Combine Mode	Sum of Squares
Save uncombined	Off
Matrix Optimization	Off
AutoAlign	---
Coil Select Mode	Default

System - Adjustments

B0 Shim mode	Brain
B1 Shim mode	TrueForm
Confirm freq. adjustment	Off
Assume Dominant Fat	Off
Assume Silicone	Off
Adjustment Tolerance	Auto

System - Adjust Volume

! Position	L0.0 P2.0 F5.4 mm
! Orientation	Transversal
! Rotation	0.00 deg
! A >> P	194 mm
! R >> L	157 mm
! F >> H	149 mm
Reset	Off

System - pTx Volumes

B1 Shim mode	TrueForm
Excitation	Slab-sel.

System - Tx/Rx

Frequency 1H	297.177435 MHz
Correction factor	1
Gain	Low
Img. Scale Cor.	1.000
Reset	Off
! Ref. amplitude 1H	300.000 V

Sequence - Part 1

Introduction	On
Dimension	3D
Reordering	Linear
Contrasts	1
Echo spacing	0.63 ms
Bandwidth	1766 Hz/Px

Sequence - Part 2

EPI factor	50
Segmentation	1
RF pulse type	Normal
Gradient mode	Normal
Excitation	Slab-sel.
RF spoiling	On
Turbo factor	50

Sequence - Special

PATRef FA	3 deg
RF duration	1400 us
RF BWT product	8
Ernst T1	1200 ms
PATRef prep. shots	10
Volume dummy shots	0
Dummy Measurements	0
ETL per RTEB	1
Invert PE	Off
Min. TE if PF	On
Echo Time Shift	On
Ramp Sampling	On
NORDIC	On
SVDPC	On
Sym VASO	Off
Dual-pol. EPI	On
Invert RO	Off
Invert 3D	Off
Disable PF reco	Off
Disable PF reco	Off
Save sampling	Off
PE VComp	Off
Water Exc.	-none-
External PC	per Series
Saturation RF	per Shot
FIDNavs	-none-
EPI rise time factor	1.10
Mosaic DICOMs	On
Modify Ice Config	On
G-factor map	Off
GRAPPA Regularization	10 10 ⁻⁶
HSN RF power scale	2.00
Inversion Delay	200 ms
Relaxation Delay	0 ms
Var. FA /MAGEC	4

Sequence - Assistant

Mode	Off
------	-----