

\\MARTINOS DEVELOPER\HUBER\HelloFromTheOtherSide\20240429_SP04\VASO_POPE_apr_0.85s_0.95
_BOLD

TA: 3:06 min Coil Selection: Manual Voxel Size: 1.0×1.0×1.0 mm³ Acc:: 16 Rel. SNR: 1.00

Properties

Start measurement without further preparation	Off
Wait for User to Start	Off
Start measurements	Single Measurement
Prio Recon	Off
Auto Open Inline Display	Off
Auto Close Inline Display	Off
Load Images to MR View&GO	On
Auto Store Images	On
Disable auto transfer to PACS	Off
Load Images to Stamp Segments	Off
Load Images to Graphic Segments	Off
Graphic segment	Default
Inline Movie	Off

Contrast - Dynamic

Dynamic Mode	Standard
Measurements	90
Reordering	Linear

Resolution - Common

FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	0.95 mm
Base Resolution	210
Phase Resolution	100 %
Slice Resolution	100 %
Interpolation	Off

Resolution - Acceleration

Acceleration Mode	CAIPIRINHA
Reference Scans	GRE/Separate
Acceleration Factor PE	4
Reference Lines PE	24
Acceleration Factor 3D	4
Reference Lines 3D	24
Reordering Shift 3D	2
Phase Partial Fourier	6/8
Slice Partial Fourier	Off
Asymmetric Echo	Weak

Routine

Slab Group	1
Slabs	1
Position	R1.6 A11.8 F9.3 mm
Orientation	T > C-22.5
Phase Encoding Dir.	A >> P
Slices per Slab	120
Phase Oversampling	0.0 %
Slice Oversampling	3.3 %
FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	0.95 mm
TR	32.4 ms
Vol. TR	2032 ms
TE 1	11.20 ms
Averages	1
Multi-echo Shots	1
AutoAlign	---
Coil Elements	AC

Resolution - Filter

Raw Filter	Off
Elliptical Filter	Off
Distortion Correction	3D
Normalize	Off
Image Filter	Off

Geometry - Common

Slab Group	1
Slabs	1
Position	R1.6 A11.8 F9.3 mm
Orientation	T > C-22.5
Phase Encoding Dir.	A >> P
Slices per Slab	120
Phase Oversampling	0.0 %
Slice Oversampling	3.3 %
FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	0.95 mm
TR	32.4 ms
Vol. TR	2032 ms
Multi-echo Shots	1

Contrast - Common

TR	32.4 ms
Vol. TR	2032 ms
TE 1	11.20 ms
Multi-echo spacing	29.50 ms
MTC	Off
Magn. Preparation	Non-sel. IR
TI 1	497.60 ms
TI 2	1502.00 ms
Flip Angle	30 deg
Fat-Water Contrast	Water Excitation
Contrasts	1
Reconstruction	Magnitude

Geometry - AutoAlign

Slab Group	1
Position	R1.6 A11.8 F9.3 mm
Orientation	T > C-22.5
Phase Encoding Dir.	A >> P
AutoAlign	---
Initial Position	R1.6 A11.8 F9.3
R	1.6 mm
A	11.8 mm
F	9.3 mm
Initial Orientation	T > C
T > C	-22.50
> S	0.00
Initial Rotation	0.00 deg

Geometry - Saturation

Saturation Mode	Standard
-----------------	----------

Geometry - Tim Planning Suite

Set-n-Go Protocol	Off
Table Position	0 mm
Table Position	H

System - Miscellaneous

Coil Selection	Manual
Radial Sorting	Off
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	F >> H
Coil Combination	Adaptive Combine
Matrix Optimization	Off

System - Adjustments

Adjustment Strategy	Standard
B0 Shim	Brain
B1 Shim	TrueForm
Adjustment Tolerance	Auto
Confirm Frequency	Never
Assume Silicone	Off

System - Adjust Volume

! Position	L0.9 A5.3 F1.0 mm
! Orientation	T > C-17.9 > S0.4
! Rotation	90.14 deg
! R >> L	123 mm
! A >> P	163 mm
! F >> H	87 mm
Reset	Off

System - pTx

B1 Shim	TrueForm
Excitation	Slab-sel.

System - Tx/Rx

Frequency 1H	297.136683 MHz
I Ref. Amplitude 1H	380.000 V
Reset	Off
Correction Factor	1.00
Image Scaling	0.200

Sequence - Part 1

Sequence Name	vso bb4d852
Dimension	3D
Excitation	Slab-sel.
RF Pulse Type	Low SAR
Gradient Mode	Fast
Reordering	Linear
Bandwidth	1488 Hz/Px
Echo Spacing	0.72 ms
Asymmetric Echo	Weak
Turbo Factor	31
Segmentation	1
EPI Factor	40

Sequence - Part 2

Introduction	On
RF Spoiling	On

Sequence - Special

RF duration	360 us
RF time x BW	5
PAT ref. FA	5 deg
Fat sat. FA	110 deg
Variable FA	4
T1 (Ernst FA)	1200 ms
Invert PE	Off
Min. TE w/ PF	On
Expert ramp shaping	On
Trigger per shot	Off
Noise image	Off
Relax spoilers	Off
Round up Vol. TR	Off
MT flip angle	170 deg
MT off-res.	2000 Hz
MT RF duration	12800 us
Custom Water Exc.	-none-
Phase Correction	per Series
Saturation RF	per Shot
EPI ramp factor	1.10
EPI ramp factor 2	1.20
Ramp sampling	1.00 1:max
Slab Scale	0 %
G. spoil dephasing[1]	0 pi
G. spoil dephasing[2]	2 pi
G. spoil dephasing[3]	2 pi
Modify Ice Config	On
G-factor map	Off
Mosaic DICOMs	Off

Sequence - Special

GRAPPA Regularization	5000 /10^6
Spoiling scheme	Conventional
Read polarity	Regular RO
Pre-T11 delay	0.00 ms
Pre-T12 delay	0 ms
Pre-Inv delay	0 ms

Sequence - Assistant

SAR Assistant	Off
---------------	-----