

Relational vs. NoSQL Databases

The choice between relational (SQL) and NoSQL databases depends largely on the structure of the data and the scaling requirements of the application. Relational databases, such as MySQL or PostgreSQL, use a predefined schema where data is organized into structured tables with rows and columns. They rely on Structured Query Language (SQL) for data manipulation and are optimized for complex queries and joins.

Conversely, NoSQL databases, like MongoDB or Cassandra, are non-relational and offer a flexible schema. Data can be stored as documents, key-value pairs, wide-column stores, or graphs. While relational databases are typically vertically scalable (increasing the power of a single server), NoSQL databases are designed to be horizontally scalable, allowing them to handle massive traffic by adding more servers to a cluster.

ACID versus BASE properties

ACID (Atomicity, Consistency, Isolation, Durability) ensures reliable transactions: all operations succeed or none do (Atomicity), data remains valid (Consistency), transactions are independent (Isolation), and changes persist (Durability). This is a strength for systems where accuracy is paramount, such as financial transactions.

BASE (Basically Available, Soft state, Eventually consistent) prioritizes availability and partition tolerance in distributed environments. It sacrifices immediate consistency for better uptime and scalability. Strengths of BASE include high availability even during network failures, easier horizontal scaling, and suitability for large-scale web applications where slight delays in consistency are acceptable (e.g., social media feeds or e-commerce product catalogs). An example is a shopping website using a NoSQL database: when a user updates their cart, the change is available immediately (Basically Available), but inventory counts across replicas may take seconds to sync (Eventually consistent). This prevents site downtime during high traffic, unlike a strict ACID system that might lock resources.

JSON in NoSQL Databases

JSON format plays a central role in many NoSQL databases, especially document-oriented ones. JSON (JavaScript Object Notation) is a lightweight, human-readable data-interchange format that stores data as key-value pairs, arrays, and nested objects. In NoSQL, documents are often stored directly as JSON or BSON (Binary JSON), allowing flexible, schema-less storage. This matches application code structures (e.g., JavaScript objects), reducing impedance mismatch. For exchanging data, JSON enables seamless REST API communication and easy integration across services. It supports semi-structured data, where fields can vary per document, facilitating agile development and handling evolving requirements without migrations.

References

Amazon Web Services. (n.d.). Relational vs nonrelational databases.

GeeksforGeeks. (2026, January 19). Difference between relational database and NoSQL.

Amazon Web Services. (n.d.). ACID vs BASE databases.

MongoDB. (n.d.). What is a JSON database?