




WORKLOAD IDENTITY FEDERATION- GCP

Laysa Uchoa

SERVICE ACCOUNT KEYS AS SECRETS



PAST





SERVICE ACCOUNT KEYS AS SECRETS




PAST

10 YEARS



ROTATION






WORKLOAD IDENTITY _____




PRESENT

NO ROTATION
NEEDED



PRINCIPLE OF LEAST PRIVILEGE

ARCHITECTURE



CREATE A WORKLOAD IDENTITY POOL _____

```
locals {  
  project_id = "PROJECT_ID"  
  service_account = "SERVICE_ACCOUNT"  
  organization   = "YOUR_ORGANISATION_HERE"  
  repository     = "YOUR_REPOSITORY_HERE"  
}  
  
resource "google_iam_workload_identity_pool" "github_pool" {  
  project                = local.project_id  
  workload_identity_pool_id = "github-pool-oidc"  
  display_name           = "GitHub pool"  
  description             = "Identity pool for GitHub deployment"  
}
```

```

resource "google_iam_workload_identity_pool_provider" "github" {
  project                = local.project_id
  workload_identity_pool_id = google_iam_workload_identity_pool.id
  workload_identity_pool_provider_id = "github-provider"

  attribute_mapping = {
    "attribute.aud"          = "assertion.aud"
    "google.subject"        = "assertion.sub"
    "attribute.sub"         = "assertion.sub"
    "attribute.actor"       = "assertion.actor"
    "attribute.repository"   = "assertion.repository"
    "attribute.repository_owner" = "assertion.repository_owner"
    "attribute.ref"         = "assertion.ref"
  }

  # If you want to restrict to organisation, use:
  # "assertion.repository_owner==" cant use local.organization

  # For more than one repository, use:
  # "assertion.repository==" cant use ORG/repository-1 || assertion.repository

  attribute_condition = "assertion.repository==" cant use local.organization

  oidc {
    allowed_audiences = []
    issuer_uri        = "https://token.actions.githubusercontent.com"
  }
}

```

CONFIGURE THE WORKLOAD IDENTITY POOL PROVIDER

CONFIGURE IAM ROLES

```
resource "google_service_account_iam_member" "workload_identity_us
  service_account_id = 'projects/${local.project_name}/serviceAcco
  role                = "roles/iam.workloadIdentityUser"
  member              = "principalSet://iam.googleapis.com/${google
}
```


GITHUB SETUP

```
name: Example GCP WIF with GitHub Actions

on:
  push:
    branches:
      - setup-wif-oidc

jobs:
  job_id:
    runs-on: ubuntu-latest
    permissions:
      contents: 'read'
      id-token: 'write'


    steps:
      # actions/checkout MUST come before auth
      - uses: 'actions/checkout@v3'

      - id: "auth"
        name: "Authenticate to Google Cloud"
        uses: "google-github-actions/auth@v2"
        with:
          token_format: "access_token"
          workload_identity_provider: "${{ secrets.WORKLOAD_IDENTITY_PROVIDER }}"
          service_account: YOUR_SERVICE_ACCOUNT
          export_environment_variables: true
          audience: "${{ secrets.GCP_POOL_AUDIENCE }}"
          create_credentials_file: true
          access_token_lifetime: 500
      # ... further steps are automatically authenticated


      - name: "Set up Cloud SDK"
        uses: "google-github-actions/setup-gcloud@v1"
        with:
          version: ">= 390.0.0"

      - name: Check currently authenticated user
        run: gcloud auth list
```


RUN PIPELINE

 Summary

Jobs


 job_id


Run details


 Workflow file


job_id


succeeded 23 minutes ago in 34s


>  Set up job


>  Run actions/checkout@v3


>  Authenticate to Google Cloud




>  Set up Cloud SDK

>  Run gcloud

>  Post Authenticate to Google Cloud

>  Post Run actions/checkout@v3

>  Complete job



THANK
YOU!

END

—

Laysa Uchoa