Technical Data Sheet

UNITUBE SM 2F G.652D/G.657A1/G.657A2 DROP CABLE

Construction Details	
No of Fiber and Color	: 02F per Tube - Blue, Natural.
FRP	: Single/Dual FRP
Loose Tube	: PBT Loose Tube Filled With Thixotropic Jelly
HDPE Coating	: Single Coating
Lining Option	: L1 Orange/Blue/Yellow/Green Line on Black Cable
Yarn Count	: 300/600 TEX
No of Loose Tube	: 1 Loose Tube
Tube Identification	: Natural
Strength Member	: Single (0.5mm) - Thermal/UV-Uncoated/UV-Coated FRP
Outer Jacket	: PE Black Color

Schematic Diagram Not to Scale



Fibre Characteristics (As per ITU-T Rec. G. 652 D)			
Attenuation (Transmission Characteristics)			
@ 1310 nm	: ≤ 0.4 (dB/Km)	Mode Field Diameter @ 1310 nm	: 9.2 ± 0.4 µm
@ 1550 nm	: ≤ 0.2 (dB/Km)	Mode Field Diameter @ 1550 nm	: 10.3 ± 0.5 µm
		Cladding Diameter	: 125 ± 1 µm
Dispersion		Cladding Non Circularity	: ≤ 1%
A. Total Dispersion (Chromatic Dispersion)		Core Clad Concentricity Error	
1285-1330nm	: ≤ 3.5 ps/nm.km	Coating Diameter(Uncolored)	: 245 ± 10 µm
1270-1340nm	: ≤ 5.3 ps/nm.km	Coating/Cladding Concentricity	: ≤ 12 µm
1550nm	: ≤ 18 ps/nm.km	**Cut Off Wavelength**	
1625nm	: ≤ 22.0 ps/nm.km	Fiber Cut Off Wavelength	: ≤ 1320 nm
B. Polarization Mode Dispersion at 1310 & 1550 nm		Cable Cut Off Wavelength	: ≤ 1260 nm
At Fibre Stage	: ≤ 0.2 ps/sqrt.km	**Mechanical & Operating Characteristics**	
At Cable Stage	: ≤ 0.3 ps/sqrt.km	Fibre Proof Test	: 1%
C. Dispersion Slope & Wave Length		Stripability Force	: 1.3 < F < 8.9 N
Zero Dispersion Wavelength	: 1300-1324 nm	Fibre Curl	: 4 meter radius of curvature
Zero Dispersion Slope	: ≤ 0.092 ps/nm^2.km	Operating Temperature	: -20° C to +70° C
Cable Mechanical & Physical Characteristics			
Cable Mechanical Characteristics		**Cable Physical Characteristics**	
Max. Tensile Strength	: 100 N (Short Term)	Cable Diameter	: 4.5/4.7/5mm
Crush Resistance	: 250 N/10 CM	Nominal Cable Weight	: Approx. 16 kg/km
Impact Resistance	: 10 N 0.5 m	Packing Length	: 0.5/1km ± 5%
Min. Bending Radius (Long Term)	: 20D (D= Cable Diameter mm)	Packing Details	: Coil Form
All Tests Shall be Carried out as per IEC Standards. Change in attentuation Shall be ≤0.05 dB/km			

Cable Printing Details: (Hot Foil White Emb.)	OFC wwY OPTRONIX xx 2F SC FRP Yw6 UT SM G.652D MONTH YYYY Length Code Meter Marking Note: ww will be replaced with outer diameter 45,47,50 xx will be replace with PRIME/NEO/PLATINUM