

```
%!PS-Adobe-3.0
%%BoundingBox: 18 36 577 806
%%Title: Enscript Output
%%Creator: GNU Enscript 1.6.5.90
%%CreationDate: Mon May 4 02:54:20 2026
%%Orientation: Landscape
%%Pages: (atend)
%%DocumentMedia: A4 595 842 0 () ()
%%DocumentNeededResources: (atend)
%%EndComments
%%BeginProlog
%%BeginResource: procset Enscript-Prolog 1.6.5 90
%
% Procedures.
%

/_S { % save current state
  /_s save def
} def
/_R { % restore from saved state
  _s restore
} def

/S { % showpage protecting gstate
  gsave
  showpage
  grestore
} bind def

/MF { % fontname newfontname -> - make a new encoded font
  /newfontname exch def
  /fontname exch def

  /fontdict fontname findfont def
  /newfont fontdict maxlength dict def

  fontdict {
    exch
    dup /FID eq {
      % skip FID pair
      pop pop
    } {
      % copy to the new font dictionary
      exch newfont 3 1 roll put
    } ifelse
  } forall

  newfont /FontName newfontname put

  % insert only valid encoding vectors
  encoding_vector length 256 eq {
    newfont /Encoding encoding_vector put
  } if

  newfontname newfont definefont pop
} def

/MF_PS { % fontname newfontname -> - make a new font preserving its enc
  /newfontname exch def
  /fontname exch def

  /fontdict fontname findfont def
  /newfont fontdict maxlength dict def

  fontdict {
    exch
    dup /FID eq {
```

```
% skip FID pair
pop pop
} {
% copy to the new font dictionary
exch newfont 3 1 roll put
} ifelse
} forall

newfont /FontName newfontname put

newfontname newfont definefont pop
} def

/SF { % fontname width height -> -      set a new font
/height exch def
/width exch def

findfont
[width 0 0 height 0 0] makefont setfont
} def

/SUF { % fontname width height -> -      set a new user font
/height exch def
/width exch def

/F-gs-user-font MF
/F-gs-user-font width height SF
} def

/SUF_PS { % fontname width height -> -  set a new user font preserving its enc
/height exch def
/width exch def

/F-gs-user-font MF_PS
/F-gs-user-font width height SF
} def

/M {moveto} bind def
/s {show} bind def

/Box { % x y w h -> -      define box path
/d_h exch def /d_w exch def /d_y exch def /d_x exch def
d_x d_y moveto
d_w 0 rlineto
0 d_h rlineto
d_w neg 0 rlineto
closepath
} def

/bgs { % x y height blskip gray str -> -      show string with bg color
/str exch def
/gray exch def
/blskip exch def
/height exch def
/y exch def
/x exch def

gsave
x y blskip sub str stringwidth pop height Box
gray setgray
fill
grestore
x y M str s
} def

/bgcs { % x y height blskip red green blue str -> -      show string with bg color
/str exch def
```

```
/blue exch def
/green exch def
/red exch def
/blskip exch def
/height exch def
/y exch def
/x exch def

gsave
  x y blskip sub str stringwidth pop height Box
  red green blue setrgbcolor
  fill
grestore
x y M str s
} def

% Highlight bars.
/highlight_bars {      % nlines lineheight output_y_margin gray -> -
  gsave
    setgray
    /ymarg exch def
    /lineheight exch def
    /nlines exch def

    % This 2 is just a magic number to sync highlight lines to text.
    0 d_header_y ymarg sub 2 sub translate

    /cw d_output_w cols div def
    /nrows d_output_h ymarg 2 mul sub lineheight div cvi def

    % for each column
    0 1 cols 1 sub {
      cw mul /xp exch def

      % for each rows
      0 1 nrows 1 sub {
        /rn exch def
        rn lineheight mul neg /yp exch def
        rn nlines idiv 2 mod 0 eq {
          % Draw highlight bar. 4 is just a magic indentation.
          xp 4 add yp cw 8 sub lineheight neg Box fill
        } if
      } for
    } for

  grestore
} def

% Line highlight bar.
/line_highlight {      % x y width height gray -> -
  gsave
    /gray exch def
    Box gray setgray fill
  grestore
} def

% Column separator lines.
/column_lines {
  gsave
    .1 setlinewidth
    0 d_footer_h translate
    /cw d_output_w cols div def
    1 1 cols 1 sub {
      cw mul 0 moveto
      0 d_output_h rlineto stroke
    } for
  grestore
}
```

```

} def

% Column borders.
/column_borders {
  gsave
    .1 setlinewidth
    0 d_footer_h moveto
    0 d_output_h rlineto
    d_output_w 0 rlineto
    0 d_output_h neg rlineto
    closepath stroke
  grestore
} def

% Do the actual underlay drawing
/draw_underlay {
  ul_style 0 eq {
    ul_str true charpath stroke
  } {
    ul_str show
  } ifelse
} def

% Underlay
/underlay {      % - -> -
  gsave
    0 d_page_h translate
    d_page_h neg d_page_w atan rotate

    ul_gray setgray
    ul_font setfont
    /dw d_page_h dup mul d_page_w dup mul add sqrt def
    ul_str stringwidth pop dw exch sub 2 div ul_h_ptsize -2 div moveto
    draw_underlay
  grestore
} def

/user_underlay {      % - -> -
  gsave
    ul_x ul_y translate
    ul_angle rotate
    ul_gray setgray
    ul_font setfont
    0 0 ul_h_ptsize 2 div sub moveto
    draw_underlay
  grestore
} def

% Page prefeed
/page_prefeed {      % bool -> -
  statusdict /prefeed known {
    statusdict exch /prefeed exch put
  } {
    pop
  } ifelse
} def

% Wrapped line markers
/wrapped_line_mark {      % x y charwith charheight type -> -
  /type exch def
  /h exch def
  /w exch def
  /y exch def
  /x exch def

  type 2 eq {
    % Black boxes (like TeX does)

```

[illegible]

/space	/exclam	/quotedbl	/numbersign
/dollar	/percent	/ampersand	/quoteright
/parenleft	/parenright	/asterisk	/plus
/comma	/hyphen	/period	/slash
/zero	/one	/two	/three
/four	/five	/six	/seven
/eight	/nine	/colon	/semicolon
/less	/equal	/greater	/question
/at	/A	/B	/C
/D	/E	/F	/G
/H	/I	/J	/K
/L	/M	/N	/O
/P	/Q	/R	/S
/T	/U	/V	/W
/X	/Y	/Z	/bracketleft
/backslash	/bracketright	/asciicircum	/underscore
/quoteleft	/a	/b	/c
/d	/e	/f	/g
/h	/i	/j	/k