

Built-in Template Automation Acceptance Criteria

Scope

Acceptance criteria for delivering the local WSL2 built-in template automation suite.

A. Execution Scope and Guardrails

- ☐ Suite runs only in local development context by default.
- ☐ CI context is detected and auto-skipped unless explicit override is provided.
- ☐ Runner supports both execution modes:
 - `AllTemplates`
 - `SelectedTemplates`

B. Discovery and Selection

- ☐ All built-in templates are discovered from `config/templates.json`.
- ☐ Single template selection by ID works end-to-end.
- ☐ Multiple template selection by ID works end-to-end.
- ☐ Unknown template IDs fail fast with explicit unresolved ID list.
- ☐ Dry-run mode outputs planned execution list without applying templates.

C. Real Validation Behavior

- ☐ Each executed template run performs real apply and WSL runtime probes.
- ☐ Language templates validate selected version/channel using tool-specific probes.
- ☐ Scenario templates validate expected runtime behavior (container/k8s/db/AI profile).
- ☐ Capability-gated templates classify missing prerequisites as `Blocked`, not `Fail`.

D. Status and Error Semantics

- ☐ Final status model is consistent and complete:
 - `Pass`: all required checks succeed
 - `Fail`: required checks executed and at least one fails
 - `Blocked`: required host capability unavailable
- ☐ Failure messages include actionable remediation hints.
- ☐ Blocked messages include explicit host capability reason.

E. Output and Traceability

- ☐ XML test result file is generated for each run.
- ☐ JSON run manifest is generated for each run.
- ☐ Markdown summary is generated at run-specific docs path.
- ☐ Summary includes:
 - total executed templates
 - pass/fail/blocked counts
 - failed/blocked reason list

- links to logs/artifacts
 - environment snapshot (`wsl --status`, distro, WSL version, timestamp)
- ☐ Historical index page is updated with the new run entry.

F. Compatibility Baseline

- ☐ Runner can target specified distro parameter without manual edits.
- ☐ Ubuntu LTS local baseline can execute full-catalog mode.
- ☐ Debian stable local baseline can execute mandatory language template subset.

G. Non-Functional Requirements

- ☐ Runner supports cancellation and timeout handling without process hang.
- ☐ Suite logs are deterministic and sufficient for post-run diagnosis.
- ☐ Suite does not leak credentials or sensitive host data in artifacts.

H. Release Acceptance Gate

The suite is accepted when all criteria in sections A-G are passed and no blocker-severity defects remain open for local WSL2 execution scope.