

JENKINS & CI/CD



JOHN BRYCE

Leading in IT Education

a *matrix* company

1. Continuous Integration (CI)
2. A Typical CI Flow
3. What is Jenkins?
4. Installing Jenkins
5. How Jenkins Works?
6. It's All In the Command Line!
7. Types of Jenkins Jobs
8. Not Only a Nice UI for Scripting
9. Live Demo: Configuring a Job




Jenkins

Continuous Integration (CI)

The Problem:

- Large software projects are developed by more than one developer.
- Work done by one developer may **conflict** with the work that was done by other developers.
- Developers might introduce **new errors and bugs** to the central code repository and **break** each other's work.
- The longer one developer works on his copy of the project without integrating it with the work done by other team members, the greater the risk of multiple **integration conflicts** and failures.
- The greater the difference between the code base and one specific developer's copy of the project, the more work has to be done to integrate between the versions and **resolve conflicts**.



Continuous Integration (CI)

The Goal:

- Prevent integration problems (known as: "integration hell" or "merge hell")
- Avoid one developer's work-in-progress breaking another developer's copy
- Reduce cost and time by reducing re-work

The Solution: CI - Integrating Early and Often


- Merge all developers' work to a shared mainline several times a day
- Use **automated unit and integration tests** to verify that there is no regression
- Use build servers to run the unit tests periodically or after every commit, and report the results to the developers



Continuous Delivery (CD) - further extends CI by making sure the software checked in on the mainline is always in a state that can be deployed to users and makes the deployment process very rapid.

A Typical CI Flow

1. A software developer checks-in his code changes to the central repository (e.g. git push), and then the CI system (e.g. Jenkins) steps in:
2. Pull latest code from VCS
3. Build project
4. Run automated tests
5. Send notifications
6. If all previous steps passed – Release & Deploy




What is Jenkins?

- Jenkins is an open source **automation server**
- Jenkins is a **Java application** with a Web user interface
- Jenkins can be used to automate all sorts of tasks related to software:
 - **Building**
 - **Testing**
 - **Delivering or Deploying**
- Provides hundreds of **plugins** which allow work with practically every tool in the continuous integration (CI) and continuous delivery (CD) **toolchain**
- Can be used as a simple CI server or turned into the continuous delivery hub for any project



Installing Jenkins

- Verify that you have **Java 8** installed on your OS
- Download a Jenkins installer appropriate for your OS from:
<https://jenkins.io/download/>
- On Windows, extract the downloaded ZIP file and run: **jenkins.msi**
- Follow the instructions of the installer and accept the defaults
- When the installer launches a browser at: <http://localhost:8080> – follow the instructions in the browser, and select “Install Suggested Plugins”
- Jenkins will install a bunch of plugins – a process which takes a few minutes



Getting Started

Getting Started

✓ Folders	✓ OWASP Markup Formatter	✓ Build Timeout	✓ Credentials Binding	** Pipeline: Milestone Step
✓ Timestampers	✓ Workspace Cleanup	✓ Ant	✓ Gradle	** JavaScript GUI Lib: jQuery bundles (jQuery and jQuery UI)
⚙ Pipeline	⚙ GitHub Branch Source	⚙ Pipeline: GitHub Groovy Libraries	✓ Pipeline: Stage View	** Jackson 2 API
⚙ Git	⚙ Subversion	⚙ SSH Slaves	⚙ Matrix Authorization Strategy	** JavaScript GUI Lib: ACE Editor bundle
⚙ PAM Authentication	⚙ LDAP	⚙ Email Extension	⚙ Mailer	** Pipeline: SCM Step
				** Pipeline: Groovy
				** Pipeline: Input Step
				** Pipeline: Stage Step
				** Pipeline: Job
				** Pipeline: Graph Analysis
				** Pipeline: REST API
				** JavaScript GUI Lib: Handlebars bundle
				** JavaScript GUI Lib: Moment.js bundle
				Pipeline: Stage View
				** Pipeline: Build Step
				** Pipeline: Model API
				** Pipeline: Declarative
				Extension Points API
				** Apache HttpComponents Client 4.x API
				** JSch dependency

How Jenkins Works?

- A task executed by Jenkins is called a **Job**
- A Jenkins job consists of a series of **command-line utilities** that are invoked in a useful manner
Example: **git** (pull code) → **mvn** (build the project) → **java** (run the code)
- When configuring a job, command-line utilities can be invoked from simple console scripts (**batch scripts** on Windows; **shell scripts** on Linux), or by using a dedicate plugin for each utility that we need to run (if such plugin exists).
- Jenkins plugins provide a friendly way to invoke command-line utilities and provide CLI arguments, but they are also eventually translated to command-line scripts when a job runs.



It's All In The Command Line!



REMEMBER: It's all about the command line!

- If you figure out the command lines for each of the steps you need Jenkins to perform – you'll have no problem implementing them as part of your Jenkins job.
- In order to **debug** a Jenkins job as you work on its configuration – you need to examine the job's **console output** and understand which command lines were executed by Jenkins and what were the output / error messages printed to the console.

The screenshot shows the Jenkins web interface. On the left is a sidebar with navigation links: 'Back to Project', 'Status', 'Changes', 'Console Output' (which is selected), 'View as plain text', 'Edit Build Information', 'Delete Build', 'Git Build Data', 'No Tags', and 'Previous Build'. The main area is titled 'Console Output' and displays the following text:

```
Started by user anonymous
Building in workspace E:\Jenkins\jobs\HelloWorld\workspace
> C:\Program Files\Git\bin\git.exe rev-parse --is-inside-work-tree # timeout=10
Fetching changes from the remote Git repository
> C:\Program Files\Git\bin\git.exe config remote.origin.url E:\Program #
timeout=10
Fetching upstream changes from E:\Program
> C:\Program Files\Git\bin\git.exe --version # timeout=10
> C:\Program Files\Git\bin\git.exe -c core.askpass=true fetch --tags --progress
E:\Program +refs/heads/*:refs/remotes/origin/*
> C:\Program Files\Git\bin\git.exe rev-parse
"refs/remotes/origin/master" # timeout=10
> C:\Program Files\Git\bin\git.exe rev-parse
"refs/remotes/origin/origin/master" # timeout=10
Checking out Revision 42f9a82ffadd86fb5c3a9dfe40e731a907f5c8f
(refs/remotes/origin/master)
> C:\Program Files\Git\bin\git.exe config core.sparsecheckout # timeout=10
> C:\Program Files\Git\bin\git.exe checkout -f
42f9a82ffadd86fb5c3a9dfe40e731a907f5c8f
> C:\Program Files\Git\bin\git.exe rev-list
42f9a82ffadd86fb5c3a9dfe40e731a907f5c8f # timeout=10
[workspace] $ cd /c call E:\Apps\tomcat7\temp\hudson1928478766077504601.bat

E:\Jenkins\jobs\HelloWorld\workspace>javac HelloWorld.java

E:\Jenkins\jobs\HelloWorld\workspace>java HelloWorld
Hello World

E:\Jenkins\jobs\HelloWorld\workspace>exit 0
Finished: SUCCESS
```

At the bottom of the console output, it says 'Help us localize this page' and 'Page generated: Oct 10, 2010 10:14:21 PM REST API Jenkins ver. 1.000.3'.

Types of Jenkins Jobs



Freestyle project

- This kind of job is entirely configurable from the Jenkins web UI
- Mostly relies on invocation of existing Jenkins plugins, but can also run batch or shell scripts




Pipeline

- Implemented with **Groovy** programming language scripts
- Much more powerful and flexible compared to a freestyle job
- Allows implementing complex execution flows and logic
- Supports invocation of other jobs (one job calls another job)

- Both types of jobs can invoke different Jenkins plugins, or specify general **batch** or **shell scripts** (depending on the OS type where the job should be executed).
- Both types of jobs can be **parameterized** – allowing the user to inject different values, and thus make the job configurable.

Not Only a Nice UI for Scripting



Distributed System

Jenkins jobs can be executed on the Jenkins server machine (also known as the “master” – this is the machine where Jenkins is installed), or on “nodes” (also called “slaves”) – other computers connected to the Jenkins server.

This allows **parallel** execution of Jenkins jobs on multiple “executors” at the same time.



Scheduling and Triggering

Jenkins jobs can be invoked **manually** or they can be configured to run automatically according to a certain **schedule**, or **triggered** by certain events. e.g. a new commit to the repository.



Notifications

Jenkins jobs can be configured to send automatic **email notifications** after each successful / failed build.

Live Demo: Configuring a Job

Source Code Management

- ☐ None
☒ Git

1. Pull code from GitHub

Repositories

Repository URL

Failed to connect to repository : Command "git.exe ls-remote -h https://github.com/ronyb/jb_jul18.git HEAD" returned status code 128:
stdout:
stderr: Logon failed, use ctrl+c to cancel basic credential prompt.
remote: In
fatal: Auth

Credentials

Branches to build

Branch Specifier (blank for 'any')

Build

Invoke top-level Maven targets

Goals

POM

Properties

2. Invoke Maven to build the project & execute a TestNG.xml file

Use private Maven repository ☐

Settings file

Global Settings file

Thank You!