

COMP251 Assignment 5

Lucia-Eve Berger — 260473661

Sources: Stack Overflow, Wikipedia, Class Slides

1 Problem One

Divide — Conquer : This algorithm fails in some cases.

Divide & Conquer Toole

$G = (V_1, E_1)$

Recursively solve the MST on both graphs ~~containing~~
~~A-B-C~~

$G_1 = (V_1, E_1) \Rightarrow$ MST given by A-B-C
 $G_2 = (V_2, E_2) \Rightarrow$ MST given by graph D-E

Professor Toole's algorithm \Rightarrow minimum weight edge that crosses the cut (v_1, v_2)

We could pick any edge along the cut in the above example \rightarrow all of them are a light edge with a value or weight of 1

The resulting graph would not work. It is not a MST for the graph so this algorithm does not work

Total $w = 15$ (actual MST) Total $w = 6$

2 Problem Two

Randomized Quicksort: Used to improve the performance of Quicksort by randomly picking one element in the sequence, swaps with the first element and then calls Partition. For Randomized Quicksort, $O(n)$ calls are made to RANDOM in both cases. Effectively, Randomized Quicksort improves Quicksort against its worst-case.

The worst case:

$$T(n) = T(n-1) + T(0) + (1)$$

$$T(0) = 0$$

randomized-partition is not called on a subproblem of size 0, so

$$T(n) = T(n-1) + (1)$$

$$T(n) = (n)$$

The best case: By the Master Theorem:

$$T(n) = 2T(n/2) + (1)$$

By case 1 of the Master Theorem, $T(n)$ has the solution

$$T(n) = (n)$$

3 Problem Three

Let E_{ij} be the event that $i < j$ and $A[i] > A[j]$ AND Let $X_{ij} = I_{E_{ij}} = 1 \text{ if } (i, j) \text{ is an inversion of } A$ $0 \text{ if } (i, j) \text{ is not an inversion of } A$

$$\text{Let } X = (i = 1 \Rightarrow n)(j = 1 \Rightarrow n)(X_{ij}) \Rightarrow$$

Number of A inversions

$$E[X] = E[(i = 1 \Rightarrow n)(j = 1 \Rightarrow n)(X_{ij})]$$

$$= (i = 1 \Rightarrow n)(j = 1 \Rightarrow n)(E[X_{ij}])$$

$$= (i = 1 \Rightarrow n)(j = 1 \Rightarrow n)(P(E_{ij}))$$

$$= (i = 1 \Rightarrow n)(j = i + 1 \Rightarrow n)(P(E_{ij}))$$

as we must have $i < j$

$$= (i = 1 \Rightarrow n)(j = i + 1 \Rightarrow n)(1/2)$$

we can choose the two numbers in $C(n, 2)$ ways and arrange them as required.

So $P(E_{ij}) = C(n, 2)/n(n-1)$ Thus

$$= (i = 1 \Rightarrow n)((n-i)/2)$$

$$= n(n-1)/4$$

4 Problem Four

probability	code	length
0.32	00	2
0.25	10	2
0.2	011	3
0.18	01	2
0.05	111	3

$$l = 0.32(2) + 0.25(2) + 0.2(3) + 0.18(2) + 0.05(3)$$

$$0.64 + 0.5 + 0.6 + 0.36 + 0.15$$

$$2.25 \text{ bit/symbol}$$

5 Problem Five

MERCI!