

Datamodel AI annotations

This page describes different types of AI annotations

codelist mapping

AI agents map decisions to `skos:Concepts` from a codelist (`skos:ConceptScheme`) through annotations of the following format.

```
@prefix ex: <http://example.org/> .
ex:1 a <http://www.w3.org/ns/oa#Annotation> .
ex:1 <http://mu.semte.ch/vocabularies/core/uuid> "32f0447a-b4d1-11f0-aa04-fe577d3a7416" .
ex:1 <http://www.w3.org/ns/oa#hasBody> <http://example.org/SDG-13_Climate_Action> .
ex:1 <http://www.w3.org/ns/oa#motivatedBy>
<http://www.w3.org/ns/oa#classifying> .
ex:1 <http://www.w3.org/ns/oa#hasBody>
<http://mu.semte.ch/vocabularies/ext/impact/positive> .
ex:1 <http://persistence.uni-leipzig.org/nlp2rdf/ontologies/nif-core#confidence> "1"^^<http://www.w3.org/2001/XMLSchema#float> .
ex:1 <http://www.w3.org/ns/oa#hasTarget>
<https://data.gent.be/id/besluiten/21.0915.4958.3076> .
```

This is the most simple version of annotations in the DECIDE project because they don't need a specific resource to point to a specific part of a decision. The target of the annotation is the expression itself.

This annotation has two values for `oa:hasBody` because on the one hand, it references the `skos:Concept` the decision is being mapped to, on the other hand, it references the impact the decision has on the concept from the codelist.

Possible values for this impact are:

- positive: `http://mu.semte.ch/vocabularies/ext/impact/positive`
- negative: `http://mu.semte.ch/vocabularies/ext/impact/negative`
- neutral: `http://mu.semte.ch/vocabularies/ext/impact/neutral`
- unknown: `http://mu.semte.ch/vocabularies/ext/impact/unknown`

Some AI agents may not be able to make the distinction between neutral and unknown, in that case, they should flag the impact as unknown. Impact is optional. If left blank, the value is taken to be 'unknown'.

The confidence score is optional and its meaning is left to the specification of the AI agent. In the best case it is about the confidence about the entire annotation (concept and impact), but it may also only be about the concept or only about the impact. See the documentation of the agent that generated the annotation.

named entity recognition

 This section is not relevant for the NER service of Decide, because this service returns statements (relation extraction): next to the type and label that is recognized, a relation to the Decision (Work) is returned. See below "Relation extraction".

"on this place in the text, a person is recognized"

- Annotated text is captured in `rdfs:label`
- Annotation uses the `eli:Expression` (in English) as target to extract knowledge: we found something (`oa:hasBody`) in this part of the text (Expression).
- The target can be further specified using `oa:SpecificResource` to capture position

```

@prefix oa: <http://www.w3.org/ns/oa#> .
@prefix mu: <http://mu.semte.ch/vocabularies/core/> .
@prefix prov: <http://www.w3.org/ns/prov#> .
@prefix xsd: <http://www.w3.org/2001/XMLSchema#> .
@prefix foaf: <http://xmlns.com/foaf/0.1/> .
@prefix dcterms: <http://purl.org/dc/terms/> .
@prefix skolem: <http://data.lblod.info/.well-known/genid/> .
@prefix eli: <http://data.europa.eu/eli/ontology#> .
@prefix annotations: <http://data.lblod.info/id/annotations/> .

annotations:0ab45594-9909-4aea-a7d9-63476ffe6e97 a oa:Annotation ;
  mu:uuid "0ab45594-9909-4aea-a7d9-63476ffe6e97" ;
  oa:hasBody skolem:1babaaaf-fb6d-4a83-879a-da7998cc5770 ;
  nif:confidence 0.87 ;
  oa:motivatedBy oa:tagging ;
  oa:hasTarget skolem:partOfText .

skolem:1babaaaf-fb6d-4a83-879a-da7998cc5770 a foaf:Person ;
  mu:uuid "1babaaaf-fb6d-4a83-879a-da7998cc5770" ;
  rdfs:label "Jan Jansen" .

skolem:partOfText a oa:SpecificResource ;
  oa:hasSource
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/expression/en>
;
  oa:hasSelector skolem:0a6d62b2-d23a-44c2-a4ae-a93fab86d573 .

skolem:0a6d62b2-d23a-44c2-a4ae-a93fab86d573 a oa:TextPositionSelector
;
  oa:start 412 ;
  oa:end 795 .

<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/expression/en>
a eli:Expression ;
  epvoc:expressionContent "Text of decision in English"@en ;
  eli:realizes
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> .

<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> a
eli:Work .

```

geo entities recognition

"on this place in the text, a Location with text "Schoolstraat" is recognized"

```

@prefix example: <http://www.example.org/> .
@prefix oa: <http://www.w3.org/ns/oa#> .
@prefix mu: <http://mu.semte.ch/vocabularies/core/> .
@prefix prov: <http://www.w3.org/ns/prov#> .
@prefix xsd: <http://www.w3.org/2001/XMLSchema#> .
@prefix foaf: <http://xmlns.com/foaf/0.1/> .
@prefix dcterms: <http://purl.org/dc/terms/> .
@prefix skolem: <http://www.example.org/id/.well-known/genid/> .

example:myAIAnnotation a oa:Annotation ;
  mu:uuid "0ab45594-9909-4aea-a7d9-63476ffe6e97" ;
  oa:hasBody skolem:location ;
  nif:confidence 0.87 ;
  oa:motivatedBy oa:tagging ;
  oa:hasTarget skolem:partOfText .

skolem:location a dcterms:Location ;
  rdfs:label "Schoolstraat" .

```

Locations are described following the core Location Vocabulary (<https://semiceu.github.io/Core-Location-Vocabulary/releases/2.1.0/> ↗).

Practically, this means the Location entity is (potentially) linked with a Geometry entity. We use Well-Known Text (WKT) to serialize the coordinates, as per the [GeoSPARQL specification](#) ↗. When the location represents an Address, we align with locn:Address.

The location can be identified with a well-known URI (https://en.wikipedia.org/wiki/Well-known_URI ↗), also called skolem URI, to indicate that this only a placeholder URI. The real URI of the location will be searched by the NEL service. The latter will add a `skos:exactMatch` predicate to the location with the discovered URI.

Street

```
skolem:location a dcterms:Location ,
<https://data.vlaanderen.be/ns/adres#Straatnaam> ;
  rdfs:label "Schoolstraat" ;
  locn:geometry <http://data.lblod.info/id/geometries/01973f6e-f73c-
77ff-82ff-2995d786b365> ;

<http://data.lblod.info/id/geometries/01973f6e-f73c-77ff-82ff-
2995d786b365> a locn:Geometry ;
  geosparql:asWKT "http://www.opengis.net/def/crs/EPSSG/0/4326
LINESTRING(-84.40095209050924 33.86994808034389,-84.3986958498135
33.86995048138296,-84.39443222712725
33.86994303468181)"^^http://www.opengis.net/ont/geosparql#wktLiteral .
```

Address

```
skolem:location a dcterms:Location, locn:Address
  rdfs:label "Schoolstraat 1, 9000 Gent" ;
  locn:geometry <http://data.lblod.info/id/geometries/01973f6e-f73c-
77ff-82ff-2995d786b365> ;
  locn:postName "Gent" ;
  locn:postCode "9000" ;
  locn:thoroughfare "Schoolstraat" ;
  locn:locatorDesignator "1" ;
  skos:exactMatch <https://data.vlaanderen.be/id/adres/3706808> .
```

Parcel

```
skolem:location a dcterms:Location ,
<https://data.vlaanderen.be/ns/perceel#Perceel> ;
  rdfs:label "11001B0009-00G004" ;
  locn:geometry <http://data.lblod.info/id/geometries/01973f6e-f73c-
77ff-82ff-2995d786b365> ;
  skos:exactMatch <https://data.vlaanderen.be/id/perceel/11001B0001-
00S000> .
```

Point of Interest

```
skolem:location a dcterms:Location , schema:TouristAttraction ;
  rdfs:label "Gravensteen" ;
  locn:geometry <http://data.lblod.info/id/geometries/01973f6e-f73c-
77ff-82ff-2995d786b365> ;
  skos:exactMatch <http://www.wikidata.org/entity/Q1543972> .
```

Neighbourhood

```
skolem:location a dcterms:Location ,
<http://www.wikidata.org/entity/Q123705> ;
  rdfs:label "Dampoortwijk" ;
  skos:exactMatch <http://www.wikidata.org/entity/Q1543972> .
```

Statistical sector

```
skolem:location a dcterms:Location , example:StatisticalSector ;
  rdfs:label "11001A00-" ;
  skos:exactMatch
<http://data.lblod.info/id/statisticalsector/11001A00-> .
```

Sub-municipality

```
skolem:location:skolem1 a dcterms:Location ,
<http://www.wikidata.org/entity/Q2785216> ;
  rdfs:label "Sint-Amandsberg" ;
  skos:exactMatch <http://www.wikidata.org/entity/Q2936941> .
```

relation extraction

"on this place in the text (Expression), a property/relationship on the decision (Work) is found"

For example:

- "on this place in the text, the title of the decision is found"
- "on this place in the text, the organization that made the decision is mentioned."

The subject of the Statement is typically the `eli:Work`.

Predicate has a datatype as range

Title

```
@prefix example: <http://www.example.org/> .
@prefix oa: <http://www.w3.org/ns/oa#> .
@prefix mu: <http://mu.semte.ch/vocabularies/core/> .
@prefix prov: <http://www.w3.org/ns/prov#> .
@prefix xsd: <http://www.w3.org/2001/XMLSchema#> .
@prefix foaf: <http://xmlns.com/foaf/0.1/> .
@prefix dcterms: <http://purl.org/dc/terms/> .
@prefix skolem: <http://www.example.org/id/.well-known/genid/> .

example:myAIAnnotation a oa:Annotation ;
  mu:uuid "0ab45594-9909-4aea-a7d9-63476ffe6e97" ;
  oa:hasBody example:skolem1 ;
  nif:confidence 0.87 ;
  oa:motivatedBy oa:linking ;
  oa:hasTarget skolem:partOfText .

example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate dcterms:title ;
  rdf:object "Besluit - voorbeeld"@nl .

<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> a
eli:Work .
```

Motivation

Motivation does not exist in ELI(-DL). So we will reuse `besluit:motivering` from OSLO Besluit.

We put motivation on the expression level, similar to `epvoc:expressionContent`:

```
example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731> ;
  rdf:predicate besluit:motivering ;
  rdf:object "Motivering van het besluit"@nl .

<https://data.arendonk.be/id/besluiten/24.1125.2636.6731> a
eli:Expression, besluit:Besluit .
```

Decision

```
example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731> ;
  rdf:predicate epvoc:expressionContent ;
  rdf:object "Inhoud van het besluit"@nl .

<https://data.arendonk.be/id/besluiten/24.1125.2636.6731> a
eli:Expression, besluit:Besluit .
```

Article

The number of the article is put on the expression level (like OSLO besluit).

I suggest to also create the link with its parent using `eli:is_part_of`. This is on the Work level.

 Some vendors of OSLO already support Articles in the RDFa annotations. Then, generating these NER articles does not make sense.


```

example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/artikels/24.1125.2636.6731/2> ;
  rdf:predicate eli:number ;
  rdf:object "Artikel 2"@nl .

example:skolem2 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/artikels/24.1125.2636.6731/2/work> ;
  rdf:predicate eli:is_part_of ;
  rdf:object
<https://data.arendonk.be/id/besluit/24.1125.2636.6731/work> .

<https://data.arendonk.be/id/artikels/24.1125.2636.6731/2> a
eli:Expression, besluit:Artikel ;
  eli:realizes
<https://data.arendonk.be/id/artikels/24.1125.2636.6731/2/work> .

```

Context_date

```

example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate dct:date ;
  rdf:object "2026-01-26"^^xsd:Date .

```

Context_period

```

example:skolem1 a rdf:Statement ;
  rdf:subject...
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate dct:date ;
  rdf:object skolem:period1 .

skolem:period1 a <http://www.w3.org/2006/time#ProperInterval> ;
  <http://www.w3.org/2006/time#hasBeginning> "2026-01-26"^^xsd:Date ;
  <http://www.w3.org/2006/time#hasEnd> "2026-01-30"^^xsd:Date .

```

Entry_date

Entry_date in the NER is two things:

- when applicable, eg: road works start at 25 January 2026. This maps to eli:date_applicability
- when decision comes in force, eg: the regulation enters into force on 20 January 2026. This maps to eli:first_date_entry_in_force

A text may come in force today, and state it will become applicable in 3 months.

Possible approach: map to both ELI date predicates and let the human validation decide which one it is.

```
example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate eli:first_date_entry_in_force ;
  rdf:object "2026-01-26"^^xsd:Date .
```

```
example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate eli:date_applicability ;
  rdf:object "2026-01-26"^^xsd:Date .
```

expiry_date

Same story as entry_date, but with eli:date_no_longer_in_force in stead of eli:first_date_entry_in_force:

```
example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate eli:date_no_longer_in_force ;
  rdf:object "2026-01-30"^^xsd:Date .
```

```
example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate eli:date_applicability ;
  rdf:object "2026-01-29"^^xsd:Date .
```

legal_basis_date

```
example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate eli:date_document ;
  rdf:object "2026-01-26"^^xsd:Date .
```

Publication_date

```
example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate eli:publication_date ;
  rdf:object "2026-01-26"^^xsd:Date .
```

Session_date

This is part of ELI-DL.

I think only the PDF pipeline has the session date mentioned in the decision text.

In OSLO, this is outside the decision content (and already annotated).

In OParl, the decision is "consulted" by different sessions, and the text does not mention the session date.

Suggestion to create a new URI for the Session and link to the Work:

```
example:myAIAnnotation a oa:Annotation ;
  mu:uuid "0ab45594-9909-4aea-a7d9-63476ffe6e97" ;
  oa:hasBody example:skolem1, example:skolem2 ;
  nif:confidence 0.87 ;
  oa:motivatedBy oa:linking ;
  oa:hasTarget skolem:partOfText .
```

```
example:skolem1 a rdf:Statement ;
  rdf:subject <https://data.lblod.info/id/session/171fd71a-9939-442a-9132-e0a12495c817> ;
  rdf:predicate eli-dl:activity_date ;
  rdf:object "2026-01-26"^^xsd:date .

example:skolem2 a rdf:Statement ;
  rdf:subject <https://data.lblod.info/id/session/171fd71a-9939-442a-9132-e0a12495c817> ;
  rdf:predicate eli-dl:created_a_realization_of ;
  rdf:object
    <https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> .

    <https://data.lblod.info/id/session/171fd71a-9939-442a-9132-e0a12495c817> a eli-dl:Activity ;
      eli-dl:had_activity_type besluit:Zitting .
```

validity_period

Not part of ELI and ELI-DL.

In OSLO Omgevingsvergunning and slimme raadpleegomgeving, there is the concept of "Normatieve bepaling". The validity period is the time frame of the Normatieve bepaling, when something is allowed.

```

example:myAIAnnotation a oa:Annotation ;
  mu:uuid "0ab45594-9909-4aea-a7d9-63476ffe6e97" ;
  oa:hasBody example:skolem1, example:skolem2 ;
  nif:confidence 0.87 ;
  oa:motivatedBy oa:linking ;
  oa:hasTarget skolem:partOfText .

```

```

<https://data.lblod.info/id/statement/19247bda-8783-43dc-8d38-1154f9872ec4> a rdf:Statement ;

```

```

  mu:uuid "19247bda-8783-43dc-8d38-1154f9872ec4" ;
  rdf:subject

```

```

<https://data.lblod.info/id/normatievebepaling/171fd71a-9939-442a-9132-e0a12495c817> ;

```

```

  rdf:predicate dct:extent ;

```

```

  rdf:object <https://data.lblod.info/id/period/6cf4be46-c995-468a-b0d6-9294541cc83f> .

```

```

<https://data.lblod.info/id/statement/01a5d6c8-9fc1-4e4c-9ff7-b762c8b032d7> a rdf:Statement ;

```

```

  mu:uuid "01a5d6c8-9fc1-4e4c-9ff7-b762c8b032d7";
  rdf:subject

```

```

<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;

```

```

  rdf:predicate eli:realizes ;

```

```

  rdf:object <https://data.lblod.info/id/normatievebepaling/171fd71a-9939-442a-9132-e0a12495c817> .

```

```

<https://data.lblod.info/id/normatievebepaling/171fd71a-9939-442a-9132-e0a12495c817> a

```

```

<https://data.vlaanderen.be/ns/omgevingsvergunning#NormatieveBepaling>
;

```

```

  mu:uuid "171fd71a-9939-442a-9132-e0a12495c817" .

```

```

<https://data.lblod.info/id/period/6cf4be46-c995-468a-b0d6-9294541cc83f> a <http://www.w3.org/2006/time#ProperInterval> ;

```

```

  mu:uuid "6cf4be46-c995-468a-b0d6-9294541cc83f" ;

```

```

  <http://www.w3.org/2006/time#hasBeginning> "2026-01-26"^^xsd:Date ;

```

```

  <http://www.w3.org/2006/time#hasEnd> "2026-01-30"^^xsd:Date .

```

The first date of the validity period can be mapped to eli:date_applicability:

```

example:skolem1 a rdf:Statement ;

```

```

  rdf:subject

```

```

<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;

```

```

  rdf:predicate eli:date_applicability ;

```

```

  rdf:object "2026-01-26"^^xsd:Date .

```

Example where the predicate has an entity as range:

We use `skos:exactMatch` to link to a known URI.

Participants (Mandataries)

eli:responsibility_of_agent is not ideal, because this is the agent responsible for the legislation (afterwards). Participants during the decision are not by default responsible afterwards.

So, we need to look into ELI-DL to capture participating mandatees.

Suggestion to add "Session" activity where the participant person are linked with:

```

@prefix example: <http://www.example.org/> .
@prefix oa: <http://www.w3.org/ns/oa#> .
@prefix mu: <http://mu.semte.ch/vocabularies/core/> .
@prefix prov: <http://www.w3.org/ns/prov#> .
@prefix xsd: <http://www.w3.org/2001/XMLSchema#> .
@prefix foaf: <http://xmlns.com/foaf/0.1/> .
@prefix dcterms: <http://purl.org/dc/terms/> .
@prefix skolem: <http://www.example.org/id/.well-known/genid/> .

example:myAIAnnotation a oa:Annotation ;
  mu:uuid "0ab45594-9909-4aea-a7d9-63476ffe6e97" ;
  oa:hasBody example:skolem1, example:skolem2 ;
  nif:confidence 0.87 ;
  oa:motivatedBy oa:linking ;
  oa:hasTarget skolem:partOfText .

example:skolem1 a rdf:Statement ;
  rdf:subject <https://data.lblod.info/id/session/171fd71a-9939-442a-9132-e0a12495c817> ;
  rdf:predicate eli-dl:had_participant_person ;
  rdf:object skolem:2 .

example:skolem2 a rdf:Statement ;
  rdf:subject <https://data.lblod.info/id/session/171fd71a-9939-442a-9132-e0a12495c817> ;
  rdf:predicate eli-dl:created_a_realization_of ;
  rdf:object
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> .

<https://data.lblod.info/id/session/171fd71a-9939-442a-9132-e0a12495c817> a eli-dl:Activity ;
  eli-dl:had_activity_type besluit:Zitting .

skolem:2 a foaf:Person ;
  rdfs:label "Jan Jansen" ;
  skos:exactMatch <http://data.lblod.info/id/mandatarissen/138eaca9-7d65-4189-8109-8fa5eabb47d3> .

```

 If the decision is already linked with a Session activity, reuse that URI instead of creating a new one.

Voting

Again ELI-DL where a Vote activity is created in the triple store. The found text about the voting is the `eli-dl:activity_Label` of the Vote activity.

```
example:myAIAnnotation a oa:Annotation ;
  mu:uuid "0ab45594-9909-4aea-a7d9-63476ffe6e97" ;
  oa:hasBody example:skolem1, example:skolem2 ;
  nif:confidence 0.87 ;
  oa:motivatedBy oa:linking ;
  oa:hasTarget skolem:partOfText .

example:skolem1 a rdf:Statement ;
  rdf:subject <https://data.lblod.info/id/vote/171fd71a-9939-442a-9132-e0a12495c817> ;
  rdf:predicate eli-dl:activity_label ;
  rdf:object "20 votes for, 5 against" .

example:skolem2 a rdf:Statement ;
  rdf:subject <https://data.lblod.info/id/vote/171fd71a-9939-442a-9132-e0a12495c817> ;
  rdf:predicate eli-dl:decided_on_a_realization_of ;
  rdf:object
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> .

<https://data.lblod.info/id/vote/171fd71a-9939-442a-9132-e0a12495c817>
a eli-dl:Activity, eli-dl:Vote .
```

legal_grounds

A citation to a specific law, decree, statute, or legal article that serves as the foundation for the decision


```

example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate eli:cites ;
  rdf:object skolem:2 .

skolem:2 a eli:Work ;
  rdfs:label "Het decreet over het lokaal bestuur van 22 december
2017" ;
  skos:exactMatch
<https://codex.vlaanderen.be/doc/document/1029017/work> .

```

Previous decisions

We use the most generic relation of ELI `eli:refers_to` meaning: Any entity that this work or expression refers to ; typically references are made to other Works, but it can be also to legislative processes, persons, etc.

```

@prefix example: <http://www.example.org/> .
@prefix oa: <http://www.w3.org/ns/oa#> .
@prefix mu: <http://mu.semte.ch/vocabularies/core/> .
@prefix prov: <http://www.w3.org/ns/prov#> .
@prefix xsd: <http://www.w3.org/2001/XMLSchema#> .
@prefix foaf: <http://xmlns.com/foaf/0.1/> .
@prefix dcterms: <http://purl.org/dc/terms/> .
@prefix skolem: <http://www.example.org/id/.well-known/genid/> .

example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate eli:refers_to ;
  rdf:object skolem:2 .

skolem:2 a eli:Work ;
  rdfs:label "CBS_123_2023" ;
  skos:exactMatch
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/> .

```

Administrative_body

First create an NER annotation with this body:

```
@prefix org: <http://www.w3.org/ns/org#> .

example:myNERIAAnnotation a oa:Annotation ;
  mu:uuid "0ab45594-9909-4aea-a7d9-63476ffe6e97" ;
  oa:hasBody example:skolem1 ;
  nif:confidence 0.87 ;
  oa:motivatedBy oa:classifying ;
  oa:hasTarget skolem:partOfText .

example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate eli:passed_by ;
  rdf:object example:skolem2 .

example:skolem2 a org:Organization ;
  rdfs:label "Gemeenteraad Beringen" .
```

So, the NER inserts a temporary URI for the Organization that MUST be shared with the NEL annotation.

Then create an NEL annotation with this body

```
@prefix org: <http://www.w3.org/ns/org#> .

example:myNELIAAnnotation a oa:Annotation ;
  mu:uuid "0ab45594-9909-4aea-a7d9-63476ffe6e97" ;
  oa:hasBody example:skolem3 ;
  nif:confidence 0.87 ;
  oa:motivatedBy oa:linking ;
  oa:hasTarget skolem:partOfText .

example:skolem3 a rdf:Statement ;
  rdf:subject example:skolem2 ;
  rdf:predicate skos:exactMatch ;
  rdf:object
<https://data.lblod.info/id/bestuursorganen/68f6138f7311902edb6eef1e882599971d7dd8627e003cd26c8577fb7cb33bc6> .
```

For the Human validation tool, the NER record can be hidden when showing the NEL record by doing following steps:

NEL annotation hasBody rdf:subject → skolem (the organization for example)

Filter out annotations with hasBody rdf:object = skolem

Context_location

```
example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate dct:spatial ;
  rdf:object skolem:location .

skolem:location a dcterms:Location ;
  rdfs:label "Schoolstraat" .
```

impact_location

Not in ELI. Reused from OSLO slimme raadpleegomgeving.

A similar approach like validity_period could be done, but would make it too complex for only capturing the location of impact.

```
@prefix org: <http://www.w3.org/ns/org#> .

example:skolem1 a rdf:Statement ;
  rdf:subject
<https://data.arendonk.be/id/besluiten/24.1125.2636.6731/work> ;
  rdf:predicate prov:atLocation ;
  rdf:object skolem:2 .

skolem:2 a dcterms:Location ;
  rdfs:label "Schoolstraat" ;
  skos:exactMatch
<https://data.lblod.info/id/bestuursorganen/68f6138f7311902edb6eef1e882
599971d7dd8627e003cd26c8577fb7cb33bc6> .
```