

Test statistici

July 29, 2023

Contents

1	Setup	2
2	Medie	2
2.1	Test t: 1 gruppo vs valore teorico	2
2.2	Test t: 2 gruppi indipendenti	2
2.3	Anova (2+ gruppi indipendenti)	3
2.4	Test t: 2 gruppi appaiati	3
2.5	Anova per misure ripetute (2+ gruppi appaiati)	4
3	Non parametric	4
3.1	Wilcoxon	4
3.2	Mann Whitney	5
3.3	Kruskal Wallis	5
3.4	Friedman test	5
4	Proporzioni	6
4.1	Test binomiale e CI clopper pearson	6
4.2	Test di Fisher	6
4.3	Chisquare	6
4.4	McNemar	7
4.5	Q di Cochran	7
5	Tassi	8
5.1	Comparazione 2 tassi	8
6	Correlazione	8
6.1	Pearson	8
6.2	Spearman	8
6.3	Tests	9
7	Varianze	9
7.1	Test di Bartlett	9
7.2	Test di Levene	9
7.3	Test di Fligner	9

8	Sopravvivenza	9
8.1	Logrank test	10
9	Agreement	10
9.1	Cohen's K	10
9.2	Lin coefficient	10
10	Reliability/consistency	10
10.1	Cronbach α	10
10.2	ICC	10
11	Multiplicity	10

1 Setup

Importiamo le librerie qui usate

```
>>> import numpy as np
>>> import pandas as pd
>>> import pingouin as pg
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
ModuleNotFoundError: No module named 'pingouin'
>>> from scipy import stats
```

2 Medie

2.1 Test t: 1 gruppo vs valore teorico

```
>>> x = [5.5, 2.4, 6.8, 9.6, 4.2]
>>> stats.ttest_1samp(x, popmean = 4)
TtestResult(statistic=1.3973913920955365, pvalue=0.23482367964421416, df=4)
>>> pg.ttest(x, 4)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
```

2.2 Test t: 2 gruppi indipendenti

```
>>> np.random.seed(123)
>>> trt = np.random.normal(size=18)
>>> ctrl = np.random.normal(size=22)
>>> stats.ttest_ind(trt, ctrl, equal_var = False)
TtestResult(statistic=0.62859959726889, pvalue=0.5339329415063301, df=33.04096867938182)
>>> pg.ttest(trt, ctrl)
Traceback (most recent call last):
```

```
File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
```

2.3 Anova (2+ gruppi indipendenti)

```
>>> df = pg.read_dataset('anova')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
>>> df.head()
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'df' is not defined
>>> df["Hair color"].value_counts()
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'df' is not defined
>>> # oneway classica
>>> pg.anova(dv='Pain threshold', between='Hair color', data=df, detailed = True)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
>>> chunks = [data["Pain threshold"].values
...           for color, data in df.groupby("Hair color")]
Traceback (most recent call last):
  File "<stdin>", line 2, in <module>
NameError: name 'df' is not defined
>>> stats.f_oneway(*chunks)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'chunks' is not defined
>>> # non assumendo numerosità comuni e/o varianza costante
>>> pg.welch_anova(dv='Pain threshold', between='Hair color', data=df)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
```

2.4 Test t: 2 gruppi appaiati

```
>>> pre = [5.5, 2.4, np.nan, 9.6, 4.2]
>>> post = [6.4, 3.4, 6.4, 11., 4.8]
>>> stats.ttest_rel(pre, post, nan_policy="omit")
TtestResult(statistic=-5.901869285972221, pvalue=0.009712771595911211, df=3)
>>> pg.ttest(pre, post, paired=True)
Traceback (most recent call last):
```

```
File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
```

2.5 Anova per misure ripetute (2+ gruppi appaiati)

```
>>> # dataset in formato long
>>> df = pg.read_dataset('rm_anova')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
>>> df.head()
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'df' is not defined
>>> pg.rm_anova(dv='DesireToKill', within='Disgustingness',
...             subject='Subject', data=df, detailed=True)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
>>> # dataset in formato wide
>>> df = pg.read_dataset('rm_anova_wide')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
>>> df.head()
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'df' is not defined
>>> pg.rm_anova(df)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
```

3 Non parametric

3.1 Wilcoxon

```
>>> pre = np.array([20, 22, 19, 20, 22, 18, 24, 20, 19, 24, 26, 13])
>>> post = np.array([38, 37, 33, 29, 14, 12, 20, 22, 17, 25, 26, 16])
>>> stats.wilcoxon(pre, post)
WilcoxonResult(statistic=20.5, pvalue=0.2661660677806492)
>>> pg.wilcoxon(pre, post, correction = False)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
```

```
>>> pg.wilcoxon(pre, post) # con correzione di continuità
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
```

3.2 Mann Whitney

```
>>> trt = np.random.uniform(low=0, high=1, size=20)
>>> ctrl = np.random.uniform(low=0.2, high=1.2, size=20)
>>> stats.mannwhitneyu(trt, ctrl, use_continuity=True)
MannwhitneyuResult(statistic=149.0, pvalue=0.17192970543827346)
>>> pg.mwu(trt, ctrl)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
```

TODO:
[scipy.stats.brunnermunzel](#)

3.3 Kruskal Wallis

```
>>> df = pg.read_dataset('anova')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
>>> # pingouin
>>> pg.kruskal(data=df, dv='Pain threshold', between='Hair color')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
>>> # scipy
>>> stats.kruskal(*chunks)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'chunks' is not defined
```

3.4 Friedman test

Tipo un wilcoxon con più colonne di 2

```
>>> # dati da friedman.test in R
>>> df = pd.DataFrame(np.array([5.40, 5.50, 5.55,
...                             5.85, 5.70, 5.75,
...                             5.20, 5.60, 5.50,
...                             5.55, 5.50, 5.40,
...                             5.90, 5.85, 5.70,
...                             5.45, 5.55, 5.60,
...                             5.40, 5.40, 5.35,
...                             5.45, 5.50, 5.35,
```

```

...         5.25, 5.15, 5.00,
...         5.85, 5.80, 5.70,
...         5.25, 5.20, 5.10,
...         5.65, 5.55, 5.45,
...         5.60, 5.35, 5.45,
...         5.05, 5.00, 4.95,
...         5.50, 5.50, 5.40,
...         5.45, 5.55, 5.50,
...         5.55, 5.55, 5.35,
...         5.45, 5.50, 5.55,
...         5.50, 5.45, 5.25,
...         5.65, 5.60, 5.40,
...         5.70, 5.65, 5.55,
...         6.30, 6.30, 6.25]).reshape(22,3),
...         columns = ["t0", "t1", "t2"])
>>> stats.friedmanchisquare(df.t0, df.t1, df.t2)
FriedmanchisquareResult(statistic=11.142857142857132, pvalue=0.003805040775511383)
>>> pg.friedman(df)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined

```

4 Proporzioni

4.1 Test binomiale e CI clopper pearson

```

>>> test = stats.binomtest(3, n=15, p=0.1) #p è la probabilità sotto h0 da rifiutare
>>> test
BinomTestResult(k=3, n=15, alternative='two-sided', statistic=0.2, pvalue=0.184061069106391)
>>> test.proportion_ci()
ConfidenceInterval(low=0.04331200510583602, high=0.48089113380685317)

```

4.2 Test di Fisher

Si ha per le tabelle 2x2

```

>>> # odds ratio (stima) calcolato è diverso da quello di R (vedi doc), p-uguale
>>> tea = np.array([[3, 1], [1, 3]])
>>> stats.fisher_exact(tea)
SignificanceResult(statistic=9.0, pvalue=0.48571428571428565)

```

TODO:
stats.barnard_exact

4.3 Chisquare

Per le tabelle $n \times m$

```

>>> obs = np.array([[10, 10, 20],
...                  [20, 20, 20]])
>>> stats.chi2_contingency(obs)
Chi2ContingencyResult(statistic=2.7777777777777777, pvalue=0.24935220877729622, dof=2, expected=[18., 18., 24.]])
>>> data = pg.read_dataset('chi2_independence')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
>>> pg.chi2_independence(data, x='sex', y='target')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined

```

4.4 McNemar

```

>>> data = pg.read_dataset('chi2_mcnemar')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
>>> pg.chi2_mcnemar(data, 'treatment_X', 'treatment_Y')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined

```

4.5 Q di Cochran

Mc nemar per più tempi/trattamenti su stessi soggetti

```

>>> df = pg.read_dataset('cochran')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
>>> df.head()
   t0  t1  t2
0  5.40  5.50  5.55
1  5.85  5.70  5.75
2  5.20  5.60  5.50
3  5.55  5.50  5.40
4  5.90  5.85  5.70
>>> df_wide = df.pivot_table(index="Subject", columns="Time", values="Energetic")
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
  File "/home/l/.local/lib/python3.11/site-packages/pandas/core/frame.py", line 8579, in pivot_table
    return pivot_table(
           ~~~~~

```

```

File "/home/l/.local/lib/python3.11/site-packages/pandas/core/reshape/pivot.py", line 97,
    table = __internal_pivot_table(
        .....
File "/home/l/.local/lib/python3.11/site-packages/pandas/core/reshape/pivot.py", line 143,
    raise KeyError(i)
KeyError: 'Energetic'
>>> pg.cochran(df_wide)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined

```

5 Tassi

5.1 Comparazione 2 tassi

Il test di poisson di python verifica che la differenza tra tassi sia nulla (quello di R che il rapporto sia unitario)

```

>>> # poisson.test(c(11, 6+8+7), c(800, 1083+1050+878))
>>> stats.poisson_means_test(11, 800, 6+8+7, 1083+1050+878)
SignificanceResult(statistic=1.5342150126346437, pvalue=0.13862291985862774)
>>> # i risultati sono diversi ma il manuale di python dice

```

I risultati di questo test sono differenti da quelli di R ma la documentazione di python dice che ha maggior potenza del test poissoniano esatto di R.

6 Correlazione

```

>>> # generare dati
>>> mean, cov = [4, 6], [(1, .5), (.5, 1)]
>>> x, y = np.random.multivariate_normal(mean, cov, 30).T
>>> data = {"x": x, "y": y}
>>> df = pd.DataFrame(data)

```

6.1 Pearson

```

>>> stats.pearsonr(df.x, df.y)
PearsonRResult(statistic=0.4235093682604101, pvalue=0.019697851908720997)
>>> pg.corr(df.x, df.y)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined

```

6.2 Spearman

```

>>> stats.spearmanr(df.x, df.y)
SignificanceResult(statistic=0.35973303670745277, pvalue=0.05087374850723393)

```



```
>>> pg.corr(df.x, df.y, method="spearman")
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
```

6.3 Tests

```
>>> pg.rcorr
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
```

7 Varianze

Vediamo le funzioni per la comparazione di k varianze sotto diverse ipotesi sempre meno restrittive

7.1 Test di Bartlett

Testa parametricamente la differenza di varianze ipotizzando una distribuzione normale del carattere nella popolazione. Se a 2 gruppi è il test F.

```
>>> a = [8.88, 9.12, 9.04, 8.98, 9.00, 9.08, 9.01, 8.85, 9.06, 8.99]
>>> b = [8.88, 8.95, 9.29, 9.44, 9.15, 9.58, 8.36, 9.18, 8.67, 9.05]
>>> c = [8.95, 9.12, 8.95, 8.85, 9.03, 8.84, 9.07, 8.98, 8.86, 8.98]
>>> stats.bartlett(a, b, c)
BartlettResult(statistic=22.789434813726782, pvalue=1.1254782518834538e-05)
```

7.2 Test di Levene

Testa parametricamente la differenza di varianze non ipotizzando distribuzioni normali

```
>>> stats.levene(a, b, c)
LeveneResult(statistic=7.584952754501659, pvalue=0.002431505967249681)
```

7.3 Test di Fligner

Equivalente non parametrico

```
>>> stats.fligner(a, b, c)
FlignerResult(statistic=10.803687663522238, pvalue=0.00450826080004775)
```

8 Sopravvivenza

Utilizziamo la libreria `lifelines`

8.1 Logrank test

```
>>> T1 = [1, 4, 10, 12, 12, 3, 5.4]
>>> E1 = [1, 0, 1, 0, 1, 1, 1]
>>> T2 = [4, 5, 7, 11, 14, 20, 8, 8]
>>> E2 = [1, 1, 1, 1, 1, 1, 1, 1]

>>> from lifelines.statistics import logrank_test
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
ModuleNotFoundError: No module named 'lifelines'
>>> results = logrank_test(T1, T2, event_observed_A=E1, event_observed_B=E2)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'logrank_test' is not defined
>>> results.print_summary()
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'results' is not defined
>>> # results.p_value, results.test_statistic
```

9 Agreement

9.1 Cohen's K

9.2 Lin coefficient

10 Reliability/consistency

10.1 Cronbach α

```
>>> pg.cronbach_alpha
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
```

10.2 ICC

```
>>> pg.intraclass_corr
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'pg' is not defined
```

11 Multiplicity

```
scipy.stats.tukey_hsd
```

scikit_posthocs.posthoc_dunn

statsmodels.stats.multitest.multipletests
scipy.stats.false_discovery_control

pg.multicomp
pg.pairwise_gameshowell
pg.pairwise_tukey
pg.pairwise_tests
pg.pairwise_corr
pg.ptests