

620-362

Applied Operations Research

Branch & Bound

Department of Mathematics and Statistics
The University of Melbourne

This presentation has been made in accordance with the provisions of Part VB of the copyright act for the teaching purposes of the University.

*For use of students of the University of Melbourne enrolled in the subject 620-362.
Copyright©2008 by Heng-Soon Gan*

Some contents of this presentation are adapted from year 2005 course notes for 620-362 Applied Operations Research, Department of Mathematics and Statistics, The University of Melbourne (compiled by Prof Natasha Boland and Dr Renata Sotirov)

Branch and Bound (B&B)

...method compute the optimal solution to IP, MIP and COP by *enumerating the points* in a subproblem's feasible region.

Recall:

- combinatorial optimisation problem (COP) is any optimisation problem that has a finite number of feasible solutions.
- integer programming problem (IP) is an optimisation problem in which unknown variables are all required to be integers.
- mixed integer programming problem (MIP) is an optimisation problem in which only some of the variables are required to be integers.

“Divide and Conquer”

- B&B is a divide and conquer approach

On branching...

- suppose S is the feasible region for some MILP and we wish to solve:

$$\min_{x \in S} c^T x$$

- let $S = S_1 \cup \dots \cup S_k$, then

$$\min_{x \in S} c^T x = \min_{1 \leq i \leq k} \left(\min_{x \in S_i} c^T x \right)$$

i.e. we can optimise over each subset separately.

- dividing the original problem into subproblems is called **branching**.
- taken to the extreme, this scheme is equivalent to complete enumeration.
- the complete enumeration is impossible for most problems as soon as the number of variables in an integer program exceeds 20 or 30 (!)

“Divide and Conquer”

Example: Enumeration tree for $S \subseteq \{0,1\}^3$

1. Divide S into

$$S_0 = \{x \in S : x_1 = 0\} \text{ and } S_1 = \{x \in S : x_1 = 1\}$$

2. Then

$$S_{00} = \{x \in S : x_2 = 0\} = \{x \in S : x_1 = x_2 = 0\}$$


$$S_{01} = \{x \in S : x_2 = 1\} = \{x \in S : x_1 = 0, x_2 = 1\}$$

$$S_{10} = \{x \in S : x_2 = 0\} = \{x \in S : x_1 = 1, x_2 = 0\}$$

$$S_{11} = \{x \in S : x_2 = 1\} = \{x \in S : x_1 = x_2 = 1\}$$

and so on...

“Divide and Conquer”




$$\begin{aligned} S_{00} &= \{x \in S : x_2 = 0\} = \{x \in S : x_1 = x_2 = 0\} \\ S_{01} &= \{x \in S : x_2 = 1\} = \{x \in S : x_1 = 0, x_2 = 1\} \\ S_{10} &= \{x \in S : x_2 = 0\} = \{x \in S : x_1 = 1, x_2 = 0\} \\ S_{11} &= \{x \in S : x_2 = 1\} = \{x \in S : x_1 = x_2 = 1\} \end{aligned}$$

Terminology

- if we picture the subproblems graphically, then we form a **search tree**
- each subproblem is linked to its **parent** and eventually to its **children**
- eliminating a problem from further consideration is called **pruning** or **fathoming**
- the act of bounding and then branching is called **processing**
- a subproblem that has not yet been considered is called a **candidate** for processing
- the set of candidates for processing is called the **candidate list**
- going back on the path from a node to its root is called **backtracking**

On bounding...



LP-based Branch-and-Bound

Binary IP:

$$\min cx$$

$$\text{s.t. } Ax \geq b$$

$$x \in \{0,1\}^n$$

LP relaxation:

$$\min cx$$

$$\text{s.t. } Ax \geq b$$

$$0 \leq x \leq 1$$

Branching: LP solution x^* has $x_i^* \in (0,1)$

$$\begin{array}{ccc} & \wedge & \\ x_i = 0 & & x_i = 1 \end{array}$$

LP-based Branch-and-Bound


IP:

$$\begin{aligned} \min \quad & cx \\ \text{s.t.} \quad & Ax \geq b \\ & x \in \mathbb{Z}_+^n \end{aligned}$$

LP relaxation:

$$\begin{aligned} \min \quad & cx \\ \text{s.t.} \quad & Ax \geq b \\ & x \geq 0 \end{aligned}$$

Branching: LP solution x^* has $x_i^* \in (a, a+1)$, $a \in \mathbb{Z}$



$$\begin{array}{c} \swarrow \quad \searrow \\ x_i \leq a \quad \quad x_i \geq a + 1 \end{array}$$

LP-based Branch-and-Bound

Example 1

$$\begin{aligned} \max \quad & z = x_1 + 2x_2 \\ \text{s.t.} \quad & -2x_1 + 7x_2 \leq 14 \\ & 6x_1 + 2x_2 \leq 27 \\ & x_1, x_2 \text{ integer} \end{aligned}$$


Best objective = *NONE*



LP-based Branch-and-Bound

$$\begin{aligned}\max \quad & z = x_1 + 2x_2 \\ \text{s.t.} \quad & -2x_1 + 7x_2 \leq 14 \\ & 6x_1 + 2x_2 \leq 27 \\ & x_1, x_2 \text{ integer}\end{aligned}$$


Best objective = *NONE*



LP-based Branch-and-Bound

$$\begin{aligned} \max \quad & z = x_1 + 2x_2 \\ \text{s.t.} \quad & -2x_1 + 7x_2 \leq 14 \\ & 6x_1 + 2x_2 \leq 27 \\ & x_1, x_2 \text{ integer} \end{aligned}$$


Best objective = 7



LP-based Branch-and-Bound

$$\begin{aligned} \max \quad & z = x_1 + 2x_2 \\ \text{s.t.} \quad & -2x_1 + 7x_2 \leq 14 \\ & 6x_1 + 2x_2 \leq 27 \\ & x_1, x_2 \text{ integer} \end{aligned}$$

Best objective = 7



How to choose a node?

Depth first search

(also known as last in, first out - LIFO):

Rule: if the current node is not pruned, the next node considered is one of its two children

- note that it is always easy to resolve the LP relaxation when simple constraint is added and the *optimal basis available*
- experience indicate that feasible solutions are more likely to be found *deep in the tree* than at nodes near the root
- good for feasibility
- efficiency *is bad* for deep trees (can always place a bound on the search depth)

How to choose a node?

Breadth first search:

Rule: all of the nodes at given level are considered before any nodes at the next lower level

- this node selection is *not practical* for solving general IP using LP relaxations, but it has interesting properties that are used in *heuristics*.

How to choose a node?

Best bound search:

Rule: choose the node with the best bound

- *continuous improvement* of global bound (upper bound if maximising, lower bound if minimising)

Good strategy in B&B tree:

Depth-first until an initial integer feasible solution, then switch to best-bound search


Infeasibility

It is possible for an IP to be infeasible whilst its LP relaxation is feasible and has a solution (!)

If IP infeasible, fathoming is not possible.


Case 1: LP feasible region bounded.

B&B will generate the entire tree whose leaves are all infeasible LPs



Case 2: LP feasible region unbounded.

B&B may produce an infinite number of nodes and will never detect the fact that the original IP is infeasible



Branch-and-Bound Algorithm

$$\begin{aligned} (IP) \quad & \max \quad z = cx \\ & s.t. \quad Ax \leq b \\ & \quad \quad x \text{ integer} \end{aligned}$$

Notation:

IP^i : integer program at node i of the branch and bound tree

LP^i : LP relaxation of IP^i

L : set of unexplored nodes


x^i : optimal solution to LP^i

z^i : value of upper bound on node i

\underline{z}_{IP} : best lower bound (best solution)

\underline{x}_{IP} : integer feasible solution associated with best lower bound

Branch-and-Bound Algorithm (Max. prob.)



Branch-and-Bound Algorithm

The basic philosophy of the B&B method is:


- to solve and resolve the linear programming relaxations as rapidly as possible
- to branch intelligently

B&B solvers also apply:

- preprocessing (e.g. root, in B&B tree)
- primal heuristic (e.g. diving heuristics, local branching)
- branching schemes (which variable to branch on first e.g. dichotomy, priority – user specified)
- different ways of solving the LP relaxation (e.g. primal simplex, dual simplex, subgradient method)
- alternative bounds to the LP relaxation bound (e.g. Lagrangian, heuristics)
- constraint generation (Gomory, Lift-and-project)
- special implementation (branch-and-price)

Example 1: B&B Tree

$$\begin{aligned} \max z &= x_1 + 2x_2 \\ \text{s.t. } -2x_1 + 7x_2 &\leq 14 \\ 6x_1 + 2x_2 &\leq 27 \\ x_1, x_2 &\text{ integer} \end{aligned}$$



Further reading...

Winston Chapter 9
(9.3, 9.4, 9.5)