

Evolutionary Methods in Multi-Objective Optimization

- Why do they work ? -

Lothar Thiele

Computer Engineering and Networks Laboratory
Dept. of Information Technology and Electrical Engineering
Swiss Federal Institute of Technology (ETH) Zurich



Eidgenössische Technische Hochschule Zürich
Swiss Federal Institute of Technology Zurich



Computer Engineering
and Networks Laboratory

Overview




① introduction

② limit behavior


③ run-time

④ performance measures

Black-Box Optimization



Issues in EMO




Multi-objective Optimization

Definition 1 (Dominance relation)

Let $f, g \in \mathbb{R}^m$. Then f is said to dominate g , denoted as $f \succ g$, iff

1. $\forall i \in \{1, \dots, m\} : f_i \geq g_i$
2. $\exists j \in \{1, \dots, m\} : f_j > g_j$




Definition 2 (Pareto set)

Let $F \subseteq \mathbb{R}^m$ be a set of vectors. Then the Pareto set $F^* \subseteq F$ is defined as follows: F^* contains all vectors $g \in F$ which are not dominated by any vector $f \in F$, i.e.


$$F^* := \{g \in F \mid \nexists f \in F : f \succ g\} \quad (1)$$

A Generic Multiobjective EA



Comparison of Three Implementations

2-objective knapsack problem



Performance Assessment: Approaches

Which technique is suited for which problem class?

❶ **Theoretically (by analysis):** difficult

- Limit behavior (unlimited run-time resources)
- Running time analysis

❷ **Empirically (by simulation):** standard

Problems: randomness, multiple objectives

Issues: quality measures, statistical testing,
benchmark problems, visualization, ...

Overview



1 introduction


2 limit behavior

3 run-time


4 performance measures

Analysis: Main Aspects

- Evolutionary algorithms are *random* search heuristics




Archiving



Requirements:

1. Convergence to Pareto front
2. Bounded size of archive
3. Diversity among the stored solutions


Problem: Deterioration




- New solution accepted in $t+1$ is dominated by a solution found previously (and “lost” during the selection process)

Problem: Deterioration

Goal: Maintain “good” front
(distance + diversity)




But: Most archiving strategies may forget Pareto-optimal solutions...



Limit Behavior: Related Work

Requirements for archive:

1. Convergence
2. Diversity
3. Bounded Size




[Rudolph 98,00]
[Veldhuizen 99]

[Rudolph 98,00]
[Hanne 99]


in this work

“store all”




(impractical)

“store one”



(not nice)




Solution Concept: Epsilon Dominance

Definition 1: ε -Dominance


A ε -dominates B iff
 $(1+\varepsilon) \cdot f(A) \geq f(B)$

(known since 1987)



Definition 2: ε -Pareto set


A subset of the Pareto-optimal set which ε -dominates all Pareto-optimal solutions



Keeping Convergence and Diversity

Goal: Maintain ε -Pareto set

Idea: ε -grid, i.e. maintain a set of non-dominated boxes (one solution per box)



Algorithm: (ε -update)

Accept a new solution f if

❶ the corresponding box is not dominated by any box represented in the archive A

AND

❷ any other archive member in the same box is dominated by the new solution

Correctness of Archiving Method

Theorem

Let $F = (f_1, f_2, f_3, \dots)$ be an infinite sequence of objective vectors one by one passed to the ε -update algorithm, and F_t the union of the first t objective vectors of F .

Then for any $t > 0$, the following holds:

- ❶ the archive A at time t contains an ε -Pareto front of F_t
- ❷ the size of the archive A at time t is bounded by the term
(K = “maximum objective value”, m = “number of objectives”)

$$\left(\frac{\log K}{\log(1 + \varepsilon)} \right)^{m-1}$$

Correctness of Archiving Method


Sketch of Proof:

❶ 3 possible failures for A_t not being an ε -Pareto set of F_t (indirect proof)

- at time $k \leq t$ a necessary solution was missed
- at time $k \leq t$ a necessary solution was expelled
- A_t contains an $f \notin \text{Pareto set of } F_t$



❷

- Number of total boxes in objective space $\left(\frac{\log K}{\log(1+\varepsilon)}\right)^m$
- Maximal one solution per box accepted
- Partition into $\left(\frac{\log K}{\log(1+\varepsilon)}\right)^{m-1}$ chains of boxes




Simulation Example

Rudolph and Agapie, 2000



Epsilon- Archive

Overview



Running Time Analysis: Related Work

problem domain *type of results*

Single-objective EAs

**discrete
search
spaces**

- expected RT (bounds)
- RT with high probability (bounds)

[Mühlenbein 92]
[Rudolph 97]
[Droste, Jansen, Wegener 98,02]
[Garnier, Kallel, Schoenauer 99,00]
[He, Yao 01,02]

**continuous
search
spaces**

- asymptotic convergence rates
- exact convergence rates

[Beyer 95,96,...]
[Rudolph 97]
[Jagerskupper 03]

Multiobjective EAs

[none]

Methodology


Typical “ingredients” of a Running Time Analysis:

Here:

- Simple algorithms \Rightarrow SEMO, FEMO, GEMO (“simple”, “fair”, “greedy”)
- Simple problems \Rightarrow m LOTZ, m COCZ (m -objective Pseudo-Boolean problems)
- Analytical methods & tools \Rightarrow General upper bound technique & Graph search process

1. Rigorous results for *specific* algorithm(s) on *specific* problem(s)
2. *General* tools & techniques
3. *General* insights (e.g., is a population beneficial at all?)

Three Simple Multiobjective EAs



Variant 1: SEMO

Each individual in the population is selected with the same probability (uniform selection)

Variant 2: FEMO

Select individual with minimum number of mutation trials (fair selection)


Variant 3: GEMO

Priority of convergence if there is progress (greedy selection)

SEMO


Algorithm 1 Simple Evolutionary Multi-Objective Optimizer (SEMO)

- 1: Choose an initial individual x uniformly from $X = \{0, 1\}^n$
 - 2: $P \leftarrow \{x\}$
 - 3: **loop**
 - 4: Select one element x out of P uniformly.
 - 5: Create offspring x' by flipping a randomly chosen bit.
 - 6: $P \leftarrow P \setminus \{z \in P \mid x' \succ z\}$
 - 7: **if** $\nexists z \in P$ such that $(z \succ x' \vee f(x') = f(z))$ **then**
 - 8: $P \leftarrow P \cup \{x'\}$
 - 9: **end if**
 - 10: **end loop**
-



Example Algorithm: SEMO

Simple Evolutionary Multiobjective Optimizer




1. Start with a random solution
2. Choose parent randomly (uniform)
3. Produce child by varying parent
4. If child is not dominated then
 - add to population
 - discard all dominated
5. Goto 2

Run-Time Analysis: Scenario



Problem

leading ones, trailing zeros (LOTZ)




Variation

single point mutation




one bit per individual




The Good News

SEMO behaves like a single-objective EA until the Pareto set has been reached...



SEMO: Sketch of the Analysis I

Phase 1: until first Pareto-optimal solution has been found




$i \rightarrow i-1$: probability of a successful mutation $\geq 1/n$
expected number of mutations = n

$i=n \rightarrow i=0$: at maximum $n-1$ steps ($i=1$ not possible)
expected overall number of mutations = $O(n^2)$

SEMO: Sketch of the Analysis II

Phase 2: from the first to all Pareto-optimal solutions



$j \rightarrow j+1$: probability of choosing an outer solution $\geq 1/j$, $\leq 2/j$
probability of a successful mutation $\geq 1/n$, $\leq 2/n$
expected number T_j of trials (mutations) $\geq nj/4$, $\leq nj$

$j=1 \rightarrow j=n$: at maximum n steps $\Rightarrow n^3/8 + n^2/8 \leq \sum T_j \leq n^3/2 + n^2/2$
expected overall number of mutations $= \Theta(n^3)$

SEMO on LOTZ

Lemma 1 (Expected running time for phase 1)

The expected running time of Alg. 1 until the first Pareto-optimal point is found is $O(n^2)$.

Lemma 2 (Expected running time for phase 2)

After the first Pareto-optimal point is found, the expected running time of Alg. 1 until all Pareto-optimal points are found is $\Theta(n^3)$

Corollary 1 (Expected running time Alg. 1)

The expected running time of Alg. 1 until all Pareto-optimal points are found is $\Theta(n^3)$

Can we do even better ?

- Our problem is the exploration of the Pareto-front.
- Uniform sampling is unfair as it samples early found Pareto-points more frequently.


Algorithm 2 Fair Evolutionary Multi-Objective Optimizer (FEMO)

```
1: Choose an initial individual  $x$  uniformly from  $X = \{0, 1\}^n$ 
2:  $w(x) \leftarrow 0$ 
3:  $P \leftarrow \{x\}$ 
4: loop
5:   Select one element  $x$  out of  $\{y \in P | w(y) \leq w(z) \forall z \in P\}$  uniformly.
6:    $w(x) \leftarrow w(x) + 1$ 
7:   Create offspring  $x'$  by flipping a randomly chosen bit.
8:    $P \leftarrow P \setminus \{z \in P | x' \succ z\}$ 
9:   if  $\nexists z \in P$  such that  $(z \succ x' \vee f(x') = f(z))$  then
10:     $P \leftarrow P \cup \{x'\}$ 
11:   end if
12: end loop
```

FEMO on LOTZ

Let the population P of FEMO applied to LOTZ contain exactly one Pareto-optimal solution and let $c > 0$ be an arbitrary constant. With probability at least $1 - n^{1-c}$, it takes at most $c \cdot n \log n$ mutation trials per solution to generate all remaining n Pareto-optimal solutions.

Sketch of Proof



Probability for each individual, that parent did not generate it with $c/p \log n$ trials:

$$(1 - p)^t = \left(1 - \frac{1}{1/p}\right)^{c/p \log n} = \left(1 - \frac{1}{1/p}\right)^{1/p^{c \log n}} \leq \left(\frac{1}{e}\right)^{c \log n} = \frac{1}{n^c}$$


n individuals must be produced. The probability that one needs more than $c/p \log n$ trials is bounded by n^{1-c} .

FEMO on LOTZ

With probability at least $1 - O(1/n)$, the running time FEMO needs from the discovery of the first two Pareto-optimal objective vectors of LOTZ until the whole Pareto set has been found lies in the interval $[1/4 \cdot 1/p \cdot n \log n, 2 \cdot 1/p \cdot n \log n]$. Hence, $\mathbf{P}\{T = \Theta(1/p \cdot n \log n)\} = 1 - O(1/n)$. Furthermore, $\mathbf{E}[T] = O(1/p \cdot n \log n)$.

- Single objective (1+1) EA with multistart strategy (epsilon-constraint method) has running time $\Theta(n^3)$.
- EMO algorithm with fair sampling has running time $\Theta(n^2 \log(n))$.

Generalization: Randomized Graph Search



- ⇒ Pareto front can be modeled as a graph
- ⇒ Edges correspond to mutations
- ⇒ Edge weights are mutation probabilities

How long does it take to explore the whole graph?

How should we select the “parents”?

Randomized Graph Search

Algorithm 9 Randomized Graph Search

```
1:  $w(v) \leftarrow 0$ 
2:  $V \leftarrow \{v_1\}; E \leftarrow \emptyset$ 
3: loop
4:   Select a node  $v$  out of  $\{v' \in V \mid w(v) \leq w(v') \ \forall v' \in V\}$  uniformly.
5:    $w(v) \leftarrow w(v) + 1$ 
6:    $v' \leftarrow \text{jump}(v)$ 
7:   if  $v' \notin V$  then
8:      $w(v) \leftarrow 0$ 
9:      $V \leftarrow V \cup \{v'\}; E \leftarrow E \cup \{(v, v')\}$ 
10:  end if
11: end loop
```

*With probability at least $1 - |E|^{-c}$, Algorithm 9 explores all nodes and edges of G using not more than $(c + 1) \frac{|V|}{p} \log |E|$ calls to the function **jump**. The expected number of calls to **jump** is bounded by $O(\frac{|V|}{p} \log |E|)$.*

Running Time Analysis: Comparison

Algorithms

	(1+1)-EMO	SEMO	FEMO	GEMO
LOTZ	$\Theta(n^3)$	$\Theta(n^3)$	$\Theta(n^2 \log n)$	$\Theta(n^2 \log n)$
COCZ	$\Theta(n^2 \log n)$	$O(n^2 \log n)$	$O(n^2 \log n)$	$\Theta(n^2)$
<i>m</i> LOTZ	$\Theta(n^{m/2} n^2)$	$O(n^{m+1})$	$O(n^{m+1})$	$O(n^{m/2} n \log n)$
<i>m</i> COCZ	$\Theta(n^{m/2} n \log n)$	$O(n^{m+1})$	$O(n^{m+1})$	$O(n^{m/2} n \log n)$

Problems

Population-based approach can be more efficient than multistart of single membered strategy

Overview



① introduction

② limit behavior

③ run-time

④ performance measures

Performance Assessment: Approaches

Which technique is suited for which problem class?

❶ **Theoretically (by analysis):** difficult



- Limit behavior (unlimited run-time resources)
- Running time analysis

❷ **Empirically (by simulation):** standard

Problems: randomness, multiple objectives

Issues: quality measures, statistical testing,
benchmark problems, visualization, ...

The Need for Quality Measures



Is **A** better than **B**?

independent of
user preferences

Yes

(strictly)

No

dependent on
user preferences

How much?


In what aspect?

Ideal: quality measures allow to make both type of statements

Independent of User Preferences

Pareto set approximation (algorithm outcome) =
set of incomparable
solutions


Ω = set of all Pareto set approximations



- A** weakly dominates **B**
= not worse in all objectives
sets not equal
- C** dominates **D**
= better in at least one objective
- A** strictly dominates **C**
= better in all objectives
- B** is incomparable to **C**
= neither set weakly better

Dependent on User Preferences

Goal: Quality measures compare two Pareto set approximations A and B.



	A	B
hypervolume	432.34	420.13
distance	0.3308	
diversity	0.3637	0.3463
spread	0.3622	0.3601
cardinality	6	5


comparison and
interpretation of
quality values

“A better”

Quality Measures: Examples


Unary

Hypervolume measure



Binary

Coverage measure



[Zitzler, Thiele: 1999]

Previous Work on Multiojective Quality Measures

Status:

- Visual comparisons common until recently
- Numerous quality measures have been proposed since the mid-1990s

[Schott: 1995][Zitzler, Thiele: 1998][Hansen, Jaszkiewicz: 1998][Zitzler: 1999]

[Van Veldhuizen, Lamont: 2000][Knowles, Corne, Oates: 2000][Deb et al.: 2000][Sayin: 2000][Tan, Lee, Khor: 2001][Wu, Azarm: 2001]...

- Most popular: unary quality measures (diversity + distance)
- No common agreement which measures should be used

Open questions:

- What kind of statements do quality measures allow?
- Can quality measures detect *whether* or *that* a Pareto set approximation is better than another?

[Zitzler, Thiele, Laumanns, Fonseca, Grunert da Fonseca: 2003]

Comparison Methods and Dominance Relations

Compatibility of a comparison method C:

C yields *true* \Rightarrow **A** is (weakly, strictly) better than **B**
(C detects **that** **A** is (weakly, strictly) better than **B**)

Completeness of a comparison method C:

A is (weakly, strictly) better than **B** \Rightarrow C yields *true*

Ideal: compatibility and completeness, i.e.,

A is (weakly, strictly) better than **B** \Leftrightarrow C yields *true*
(C detects **whether** **A** is (weakly, strictly) better than **B**)

Limitations of Unary Quality Measures

Theorem

There exists no unary quality measure that is able to detect

whether **A** is better than **B**.

This statement even holds, if we consider a finite combination

of unary quality measures

There exists no combination of unary measures applicable to any problem.

Power of Unary Quality Indicators

indicator	name / reference	Boolean function	compatibility	completeness
I_{HC}	enclosing hypercube indicator / Section III-B.1	$I_2^{HC}(A) < I_2^{HC}(B)$	\gg	-
I_O	objective vector indicator / Section III-B.1	$I_1^O(A) < I_1^O(B)$	\gg	-
I_H	hypervolume indicator / [7]	$I_H(A) > I_H(B)$	\nlessdot	\triangleright
I_W	average best weight combination / [19]	$I_W(A) < I_W(B)$	\nlessdot	\gg
I_D	distance from reference set / [20]	$I_D(A) < I_D(B)$	\nlessdot	\gg
$I_{\epsilon 1}$	unary ϵ -indicator / Section III-B.2	$I_{\epsilon 1}(A) < I_{\epsilon 1}(B)$	\nlessdot	\gg
I_{PF}	fraction of Pareto-optimal front covered / [22]	$I_{PF}(A) > I_{PF}(B)$	\nlessdot	-
I_P	number of Pareto points contained / Section III-B.2	$I_P(A) > I_P(B)$	\nlessdot	-
I_{ER}	error ratio / [13]	$I_{ER}(A) > 0$	\nlessdot	-
I_{CD}	chi-square-like deviation indicator / [14]	$I_{CD}(A) < I_{CD}(B)$	-	-
I_S	spacing / [23]	$I_S(A) < I_S(B)$	-	-
I_{ONVG}	overall nondominated vector generation / [13]	$I_{ONVG}(A) > I_{ONVG}(B)$	-	-
I_{GD}	generational distance / [13]	$I_{GD}(A) < I_{GD}(B)$	-	-
I_{ME}	maximum Pareto front error / [13]	$I_{ME}(A) < I_{ME}(B)$	-	-
I_{MS}	maximum spread / [21]	$I_{MS}(A) > I_{MS}(B)$	-	-
I_{MD}	minimum distance between two solutions / [24]	$I_{MD}(A) > I_{MD}(B)$	-	-
I_{CE}	coverage error / [24]	$I_{CE}(A) < I_{CE}(B)$	-	-
I_{DU}	deviation from uniform distribution / [25]	$I_{DU}(A) < I_{DU}(B)$	-	-
I_{OS}	Pareto spread / [26]	$I_{OS}(A) > I_{OS}(B)$	-	-
I_A	accuracy / [26]	$I_A(A) > I_A(B)$	-	-
I_{NDC}	number of distinct choices / [26]	$I_{NDC}(A) > I_{NDC}(B)$	-	-
I_{CL}	cluster / [26]	$I_{CL}(A) < I_{CL}(B)$	-	-

strictly dominates

doesn't weakly dominate


doesn't dominate

weakly dominates

Quality Measures: Results

Basic question: Can we say on the basis of the quality measures

whether or that an algorithm outperforms another?



hypervolume

432.34

420.13

distance

0.3308

diversity

0.3637

0.3463

spread

0.3622

0.3601

cardinality

6

5

There is no combination of unary quality measures such that

S is better than **T** in all measures **S** is equivalent to **S**


Unary quality measures usually do not tell that **S** dominates **T**; at maximum that **S** does not dominate **T**

[Zitzler et al.: 2002]

A New Measure: ε -Quality Measure


Two solutions:

$$E(\mathbf{a}, \mathbf{b}) = \max_{1 \leq i \leq n} \min_{\varepsilon} \varepsilon \cdot f_i(\mathbf{a}) \geq f_i(\mathbf{b})$$



Two approximations:

$$E(\mathbf{A}, \mathbf{B}) = \max_{\mathbf{b} \in \mathbf{B}} \min_{\mathbf{a} \in \mathbf{A}} E(\mathbf{a}, \mathbf{b})$$



Advantages: allows all kinds of statements (complete **and** compatible)

Selected Contributions

How to apply (evolutionary) optimization algorithms to large-scale multiobjective optimization problems?

Algorithms:

- Improved techniques [Zitzler, Thiele: *IEEE TEC1999*]
[Zitzler, Teich, Bhattacharyya: *CEC2000*] [Zitzler, Laumanns, Thiele: *EUROGEN2001*]
- Unified model [Laumanns, Zitzler, Thiele: *CEC2000*]
[Laumanns, Zitzler, Thiele: *EMO2001*]
- Test problems [Zitzler, Thiele: *PPSN 1998, IEEE TEC 1999*]
[Deb, Thiele, Laumanns, Zitzler: *GECCO2002*]

Theory:

- Convergence/diversity [Laumanns, Thiele, Deb, Zitzler: *GECCO2002*]