

STOCKHOLM

HYBRID CONFERENCE

Improve your tests with Makina

Luis Eduardo Bueso de Barrio

May 20 | 2022

The problem



files	blank	comment	code	files	blank	comment	
4	760	383	4513	18	500	408	1



Writing unit-tests is hard and time-consuming:



Writing unit-tests is hard and time-consuming:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
```



Writing unit-tests is hard and time-consuming:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
...
```

Property-Based Testing (PBT) philosophy:



Writing unit-tests is hard and time-consuming:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
...
```

Property-Based Testing (PBT) philosophy:

Don't write tests, generate them.



Writing unit-tests is hard and time-consuming:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
...
```

Property-Based Testing (PBT) philosophy:

Don't write tests, generate them.



Writing unit-tests is hard and time-consuming:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
...
```

Property-Based Testing (PBT) philosophy:

Don't write tests, generate them.

A test execution in PBT consists of:

1. Data generation.



Writing unit-tests is hard and time-consuming:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
...
```

Property-Based Testing (PBT) philosophy:

Don't write tests, generate them.

- Data generation.
- Property checking.



Writing unit-tests is hard and time-consuming:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
...
```

Property-Based Testing (PBT) philosophy:

Don't write tests, generate them.

- Data generation.
- 2. Property checking.
- 3. An shrinking strategy (if the property doesn't hold).



Writing unit-tests is hard and time-consuming: A property:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
...
```

Property-Based Testing (PBT) philosophy:

Don't write tests, generate them.

- 1. Data generation.
- 2. Property checking.
- An shrinking strategy (if the property doesn't hold).



Writing unit-tests is hard and time-consuming:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
...
```

A property:

```
forall list <- list() do
  list == reverse(reverse(list))
end</pre>
```

Property-Based Testing (PBT) philosophy: Don't write tests, generate them.

- 1. Data generation.
- 2. Property checking.
- An shrinking strategy (if the property doesn't hold).



Writing unit-tests is hard and time-consuming:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
...
```

Property-Based Testing (PBT) philosophy:

Don't write tests, generate them.

A test execution in PBT consists of:

- Data generation.
- 2. Property checking.
- An shrinking strategy (if the property doesn't hold).

A property:

```
forall list <- list() do
   list == reverse(reverse(list))
end</pre>
```

In each test:

list() generates a random list:



Writing unit-tests is hard and time-consuming:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
...
```

Property-Based Testing (PBT) philosophy: Don't write tests, generate them.

A test execution in PBT consists of:

- Data generation.
- Property checking.
- An shrinking strategy (if the property doesn't hold).

A property:

```
forall list <- list() do
   list == reverse(reverse(list))
end</pre>
```

In each test:

1. list() generates a random list:

```
[8 ,10 ,6] ...
```

2. Checks the property:



Writing unit-tests is hard and time-consuming:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
...
```

Property-Based Testing (PBT) philosophy: Don't write tests, generate them.

A test execution in PBT consists of:

- Data generation.
- Property checking.
- An shrinking strategy (if the property doesn't hold).

A property:

```
forall list <- list() do
   list == reverse(reverse(list))
end</pre>
```

In each test:

list() generates a random list:

```
[8 ,10 ,6] ...
```

2. Checks the property:

```
[8, 10, 6] == reverse(reverse([8, 10, 6]))
```



Writing unit-tests is hard and time-consuming:

```
reverse([]) == []
reverse([1]) == [1]
reverse([1 ,2]) == [2 ,1]
...
```

Property-Based Testing (PBT) philosophy: Don't write tests, generate them.

A test execution in PBT consists of:

- Data generation.
- Property checking.
- 3. An shrinking strategy (if the property doesn't hold).

A property:

```
forall list <- list() do
   list == reverse(reverse(list))
end</pre>
```

In each test:

1. list() generates a random list:

```
[8 ,10 ,6] ...
```

2. Checks the property:

```
[8, 10, 6] == reverse(reverse([8, 10, 6]))
```

3. If the property doesn't hold returns a counter-example.





Imagine a simple counter:

Command	Returns
start/1	:ok :error
stop/0	:ok :error
inc/0	:ok
get/0	integer()



Imagine a simple counter:

Command	Returns	
start/1	:ok :error	
stop/0	:ok :error	
inc/0	:ok	
get/0	integer()	

Unit test:

```
:ok = start(0)
:ok = inc()
1 = get()
:ok = stop()
```




Imagine a simple counter:

Command	Returns
start/1	:ok :error
stop/0	:ok :error
inc/0	:ok
get/0	integer()

Unit test:

```
:ok = start(0)
:ok = inc()
1 = get()
:ok = stop()
```

This test can be represented:






Imagine a simple counter:

Command	Returns
start/1	:ok :error
stop/0	:ok :error
inc/0	:ok
get/0	integer()

Unit test:

```
:ok = start(0)
:ok = inc()
1 = get()
:ok = stop()
```

This test can be represented:



To successfully test this program we need to:




Imagine a simple counter:

Command	Returns
start/1	:ok :error
stop/0	:ok :error
inc/0	:ok
get/0	integer()

Unit test:

```
:ok = start(0)
:ok = inc()
1 = get()
:ok = stop()
```

This test can be represented:



To successfully test this program we need to:

• Generate sequences of commands.




Imagine a simple counter:

Command	Returns
start/1	:ok :error
stop/0	:ok :error
inc/0	:ok
get/0	integer()

Unit test:

```
:ok = start(0)
:ok = inc()
1 = get()
:ok = stop()
```

This test can be represented:



To successfully test this program we need to:

- Generate sequences of commands.
- An internal state to track the changes in the program.




Imagine a simple counter:

Command	Returns
start/1	:ok :error
stop/0	:ok :error
inc/0	:ok
get/0	integer()

Unit test:

```
:ok = start(0)
:ok = inc()
1 = get()
:ok = stop()
```

This test can be represented:



To successfully test this program we need to:

- Generate sequences of commands.
- An internal state to track the changes in the program.
- A way to interact with the program under test.





Basic property of stateful programs:

```
forall cmds <- commands(Counter) do
  :ok == run_commands(Counter, cmds)
end</pre>
```



Basic property of stateful programs:

```
forall cmds <- commands(Counter) do
  :ok == run_commands(Counter, cmds)
end</pre>
```

where:



Basic property of stateful programs:

```
forall cmds <- commands(Counter) do
   :ok == run_commands(Counter, cmds)
end</pre>
```

where:

commands/1 generates sequences commands:

```
[start(0), inc(), get(), stop()] ...
```



Basic property of stateful programs:

```
forall cmds <- commands(Counter) do
   :ok == run_commands(Counter, cmds)
end</pre>
```

where:

• commands/1 generates sequences commands:

```
[start(0), inc(), get(), stop()] ...
```

run_commands executes the generated sequence.



Basic property of stateful programs:


```
forall cmds <- commands(Counter) do
   :ok == run_commands(Counter, cmds)
end</pre>
```

where:

• commands/1 generates sequences commands:

```
[start(0), inc(), get(), stop()] ...
```

run_commands executes the generated sequence.







Introduced by Erlang QuickCheck.



Introduced by Erlang QuickCheck.

Adopted by other PBT libraries such as Proper.



Introduced by Erlang QuickCheck.

Adopted by other PBT libraries such as Proper.

These libraries provide a DSL to model the system.



Introduced by Erlang QuickCheck.

Adopted by other PBT libraries such as Proper.

These libraries provide a DSL to model the system.

Proven effectiveness.



Very slow adoption.

Introduced by Erlang QuickCheck.

Adopted by other PBT libraries such as Proper.

These libraries provide a DSL to model the system.

Proven effectiveness.



Very slow adoption.

Why?

 $Introduced\ by\ {\tt Erlang}\ \ {\tt QuickCheck}.$

Adopted by other PBT libraries such as Proper.

These libraries provide a DSL to model the system.

Proven effectiveness.



	Very slow adoption.
Introduced by Erlang QuickCheck.	

Adopted by other PBT libraries such as Proper.

These libraries provide a DSL to model the

Proven effectiveness.

system.

Problems:

Why?

lems:

#CodeBEAM



Very slow adoption.

Why?

Problems:

Hard to write.

Introduced by Erlang QuickCheck.

Adopted by other PBT libraries such as Proper.

These libraries provide a DSL to model the system.

Proven effectiveness.



Introduced by Erlang QuickCheck.

QUICKOHECK.

Adopted by other PBT libraries such as Proper.

These libraries provide a DSL to model the system.

Proven effectiveness.

Very slow adoption.

Why?

- Hard to write.
- Cryptic errors.



Introduced by Erlang QuickCheck.

Adopted by other PBT libraries such as Proper.

These libraries provide a DSL to model the system.

Proven effectiveness.

Very slow adoption.

Why?

- Hard to write.
- Cryptic errors.
- Usually buggy.



Introduced by Erlang QuickCheck.

Adopted by other PBT libraries such as Proper.

These libraries provide a DSL to model the system.

Proven effectiveness.

Very slow adoption.

Why?

- Hard to write.
- Cryptic errors.
- Usually buggy.
- Code reuse is very hard.



Introduced by Erlang QuickCheck.

Adopted by other PBT libraries such as Proper.

These libraries provide a DSL to model the system.

Proven effectiveness.

Very slow adoption.

Why?

- Hard to write.
- Cryptic errors.
- Usually buggy.
- Code reuse is very hard.
- Hard to maintain.





Makina is a DSL to write PBT state machines.

 Fully compatible with Erlang QuickCheck and PropEr.



- Fully compatible with Erlang QuickCheck and PropEr.
- Improved usability.



- Fully compatible with Erlang QuickCheck and PropEr.
- Improved usability.
- Better error messages.



- Fully compatible with Erlang QuickCheck and PropEr.
- Improved usability.
- Better error messages.
- Improved error detection in models.



A Makina model contains:

- Fully compatible with Erlang QuickCheck and PropEr.
- Improved usability.
- Better error messages.
- Improved error detection in models.



A Makina model contains:

state

- Makina is a DSL to write PBT state machines.
 - Fully compatible with Erlang QuickCheck and PropEr.
 - Improved usability.
 - Better error messages.
 - Improved error detection in models.



A Makina model contains:

- Fully compatible with Erlang QuickCheck and PropEr.
- Improved usability.
- Better error messages.
- Improved error detection in models.

- state
- command



Makina is a DSL to write PBT state machines.

- Fully compatible with Erlang QuickCheck and PropEr.
- Improved usability.
- Better error messages.
- Improved error detection in models.

A Makina model contains:

- state
- command
- invariants



Makina is a DSL to write PBT state machines.

- Fully compatible with Erlang QuickCheck and PropEr.
- Improved usability.
- Better error messages.
- Improved error detection in models.

A Makina model contains:

- state
- command
- invariants

Provides code reuse mechanisms:



Makina is a DSL to write PBT state machines.

- Fully compatible with Erlang QuickCheck and PropEr.
- Improved usability.
- Better error messages.
- Improved error detection in models.

A Makina model contains:

- state
- command
- invariants

Provides code reuse mechanisms:

imports



Makina is a DSL to write PBT state machines.

- Fully compatible with Erlang QuickCheck and PropEr.
- Improved usability.
- Better error messages.
- Improved error detection in models.

A Makina model contains:

- state
- command
- invariants

Provides code reuse mechanisms:

- imports
- extends



Makina is a DSL to write PBT state machines.

- Fully compatible with Erlang QuickCheck and PropEr.
- Improved usability.
- · Better error messages.
- Improved error detection in models.

A Makina model contains:

- state
- command
- invariants

Provides code reuse mechanisms:


- imports
- extends
- composition



A blockchain is a distributed ledger that enables peer-to-peer transactions.

600 820 84 84


A blockchain is a distributed ledger that enables peer-to-peer transactions.






A blockchain is a distributed ledger that enables peer-to-peer transactions.

Ethereum is one of the largest blockchains.



800 E BEAM EUROPE

A blockchain is a distributed ledger that enables peer-to-peer transactions.




Ethereum is one of the largest blockchains.

Introduced smart-contracts.

\$ 9 9 £ \$ £ 9 M £\$\$#**\$**\$#**\$**\$#

A blockchain is a distributed ledger that enables peer-to-peer transactions.




Ethereum is one of the largest blockchains.

Introduced smart-contracts.

etherex a library to interact with Ethereum using Elixir.

800 E BEAM EUROPE

A blockchain is a distributed ledger that enables peer-to-peer transactions.



Ethereum is one of the largest blockchains.


Introduced smart-contracts.

etherex a library to interact with Ethereum using Elixir.

The properties to test:

800 E BEAM EUROPE

A blockchain is a distributed ledger that enables peer-to-peer transactions.



Ethereum is one of the largest blockchains.

Introduced smart-contracts.


etherex a library to interact with Ethereum using Elixir.

The properties to test:

1. Mining blocks.



A blockchain is a distributed ledger that enables peer-to-peer transactions.



Ethereum is one of the largest blockchains.

Introduced smart-contracts.


etherex a library to interact with Ethereum using Elixir.

The properties to test:

- 1. Mining blocks.
- Account access.



A blockchain is a distributed ledger that enables peer-to-peer transactions.



Ethereum is one of the largest blockchains.

Introduced smart-contracts.

etherex a library to interact with Ethereum using Elixir.

The properties to test:

- 1. Mining blocks.
- Account access.
- 3. Transfers between accounts.



The API:



The API:

Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>



defmodule Blocks do

The API:

Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

1. create module.



The API:

Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

defmodule Blocks do use Makina

- 1. create module.
- 2. import Makina.



The API:

Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

defmodule Blocks do use Makina

state height: 0

- 1. create module.
- import Makina.
- 3. define state.



Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

- 1. create module.
- 2. import Makina.
- 3. define state.
- 4. define invariants.

```
defmodule Blocks do
   use Makina
  state height: 0
  invariants non_neg_height: height > 0
```



Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

- 1. create module.
- import Makina.
- define state.
- 4. define invariants.
- 5. define commands.

```
defmodule Blocks do
   use Makina
  state height: 0
  invariants non_neg_height: height > 0
  command block_number() do
```



Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

- 1. create module.
- 2. import Makina.
- define state.
- 4. define invariants.
- 5. define commands.
- 6. introduce the callbacks.

```
defmodule Blocks do
    use Makina
    state height: 0
    invariants non_neg_height: height > 0
    command block_number() do
        pre true
```



Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

- 1. create module.
- 2. import Makina.
- 3. define state.
- 4. define invariants.
- 5. define commands.
- 6. introduce the callbacks.

```
defmodule Blocks do
    use Makina
    state height: 0
    invariants non_neg_height: height > 0
    command block_number() do
    pre true
    args []
```



Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

- 1. create module.
- 2. import Makina.
- define state.
- 4. define invariants.
- 5. define commands.
- 6. introduce the callbacks.

```
defmodule Blocks do
  use Makina
  state height: 0
  invariants non_neg_height: height > 0
  command block_number() do
    pre true
    args []
    valid_args true
```



Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

- 1. create module.
- 2. import Makina.
- define state.
- 4. define invariants.
- 5. define commands.
- 6. introduce the callbacks.

```
defmodule Blocks do
    use Makina
    state height: 0
    invariants non_neg_height: height > 0

    command block_number() do
    pre true
    args []
    valid_args true
    call Etherex.block_number
```



Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

- 1. create module.
- 2. import Makina.
- 3. define state.
- 4. define invariants.
- 5. define commands.
- 6. introduce the callbacks.

```
defmodule Blocks do
  use Makina
  state height: 0
  invariants non_neg_height: height > 0
  command block_number() do
    pre true
    args []
   valid_args true
    call Etherex.block number
   next []
```



Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

- 1. create module.
- 2. import Makina.
- 3. define state.
- 4. define invariants.
- 5. define commands.
- 6. introduce the callbacks.

```
defmodule Blocks do
  use Makina
  state height: 0
  invariants non_neg_height: height > 0
  command block_number() do
    pre true
    args []
   valid_args true
    call Etherex.block number
   next []
    post {:ok, height} == result
```



Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

- 1. create module.
- 2. import Makina.
- 3. define state.
- 4. define invariants.
- 5. define commands.
- 6. introduce the callbacks.

```
defmodule Blocks do
  use Makina
  state height: 0
  invariants non_neg_height: height > 0
  command block_number() do
    pre true
    args []
   valid_args true
    call Etherex.block number
   next []
    post {:ok, height} == result
  end
```



Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

- 1. create module.
- 2. import Makina.
- 3. define state.
- 4. define invariants.
- 5. define commands.
- 6. introduce the callbacks.

```
defmodule Blocks do
   use Makina, implemented_by: Etherex
  state height: 0
  invariants non_neg_height: height > 0
  command block_number() do
    post {:ok, height} == result
  end
```



Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>

- 1. create module.
- 2. import Makina.
- 3. define state.
- 4. define invariants.
- 5. define commands.
- 6. introduce the callbacks.

```
defmodule Blocks do
  use Makina, implemented_by: Etherex
  state height: 0
  invariants non_neg_height: height > 0
  command block_number() do
    post {:ok, height} == result
  end
  command mine() :: :ok do
    next height: height + 1
 end
end
```



\$ mix test



\$ mix test
Starting Quviq QuickCheck version 1.45.1



```
600K
BEAM
EURAPE
```

```
$ mix test
Starting Quviq QuickCheck version 1.45.1
Failed! After 1 tests.
    Blocks.block_number/0,
    Blocks.mine/0.
Postcondition crashed:
** (Makina.Error) invariant "non_neg_height" check failed
Shrinking x.(1 \text{ times})
    Blocks.block number/0
Last state: %{height: 0}
Finished in 0.1 seconds (0.00s async, 0.1s sync)
1 properties, 1 failure
```





```
Postcondition crashed:
** invariant "non_neg_height" check failed

Shrinking x.(1 times)
[
    Blocks.block_number/0
]

Last state: %{height: 0}
```

```
defmodule Blocks do
  use Makina, implemented_by: Etherex
  state height: 0
  invariants non_neg_height: height > 0
  command block_number() do
    post {:ok, height} == result
 end
 command mine() do
    next height: height + 1
 end
end
```



```
Postcondition crashed:
** invariant "non_neg_height" check failed

Shrinking x.(1 times)
[
    Blocks.block_number/0
]

Last state: %{height: 0}

What happened?
```

```
defmodule Blocks do
  use Makina, implemented_by: Etherex
  state height: 0
  invariants non_neg_height: height > 0
  command block_number() do
    post {:ok, height} == result
  end
  command mine() do
    next height: height + 1
 end
end
```



```
Postcondition crashed:
** invariant "non_neg_height" check failed

Shrinking x.(1 times)
[
Blocks.block_number/0]
]

Last state: %{height: 0}

What happened?
```

Invariant doesn't hold even on the initial state!

```
defmodule Blocks do
  use Makina, implemented_by: Etherex
  state height: 0
  invariants non_neg_height: height > 0
  command block_number() do
    post {:ok, height} == result
  end
  command mine() do
    next height: height + 1
 end
end
```



```
Postcondition crashed:
** invariant "non_neg_height" check failed

Shrinking x.(1 times)
[

Blocks.block_number/0
]

Last state: %{height: 0}

What happened?
```

Invariant doesn't hold even on the initial state!

```
defmodule Blocks do
  use Makina, implemented_by: Etherex
  state height: 0
  invariants non_neg_height: height >= 0
  command block_number() do
    post {:ok, height} == result
  end
  command mine() do
    next height: height + 1
 end
end
```





\$ mix test



\$ mix test
Starting Quviq QuickCheck version 1.45.1



```
$ mix test
Starting Quviq QuickCheck version 1.45.1
```

OK, passed 100 tests

51.5 Blocks.mine/0
48.5 Blocks.block_number/0

Finished in 8.6 seconds (0.00s async, 8.6s sync)



When a model is compiled automatically generates documentation.



When a model is compiled automatically generates documentation.

iex> h Blocks



When a model is compiled automatically generates documentation.

iex> h Blocks

Blocks

Contains a Makina model called Blocks.

Specifies the mining facilities of the blockchain.

Commands

- mine stored at Blocks.Command.Mine
- block_number stored at Blocks.Command.BlockNumber

Detailed information about each command can be accessed inside the interpreter:

iex> h Blocks.Command.NAME

State attributes

- height

. . .

When a model is compiled automatically generates documentation.

iex> h Blocks
iex> h Blocks.Command.Mine.post



When a model is compiled automatically generates documentation.

```
iex> h Blocks
iex> h Blocks.Command.Mine.post
...
## Available variables
```

State

- state contains the complete dynamic state of the model.
- height attribute defined in the state declaration.

Arguments

- arguments contains all the generated arguments of the command.

Result

- result variable that contains the result of the command execution.



Adding documentation



Adding documentation

```
defmodule Blocks do
  use Makina, implemented_by: Etherex
```



```
state height: Etherex.block_number!() :: non_neg_integer()
 invariants non_genesis_block: height >= 0
 command block_number() :: {:ok, non_neg_integer()} do
   post {:ok, height} == result
 end
 command mine() :: :ok do
   next height: height + 1
 end
end
```

Adding documentation

```
600 6 8 E A M
EUROPE
```

```
defmodule Blocks do
 use Makina, implemented_by: Etherex
 @moduledoc """
 Specifies the mining facilities of the blockchain.
 state height: Etherex.block_number!() :: non_neg_integer()
 invariants non_genesis_block: height >= 0
 command block_number() :: {:ok, non_neg_integer()} do
   @moduledoc "Retrieves the block number from the blockchain."
   post {:ok. height} == result
 end
 command mine() :: :ok do
   @moduledoc "Mines a new block."
   next height: height + 1
 end
end
```

Adding type information



Adding type information

```
SODE
BEAM
EUROPE
```

```
defmodule Blocks do
2
      use Makina, implemented_by: Etherex
      state height: 0
5
6
      invariants non_neg_height: height >= 0
8
      command block_number()
                                                   do
        post {:ok, height} == result
10
      end
11
12
      command mine()
13
        call Etherex.Time.mine()
14
        next height: height + 1
15
      end
16
    end
```

```
8 9 9 £
8 £ A M
EUROP£
```

```
defmodule Blocks do
2
      use Makina, implemented_by: Etherex
      state height: 0 :: integer()
5
6
      invariants non_neg_height: height >= 0
8
      command block_number()
                                                   do
        post {:ok, height} == result
10
      end
11
12
      command mine()
13
        call Etherex.Time.mine()
14
        next height: height + 1
15
      end
16
    end
```

```
6 9 9 K 8 E A M EUROPE
```

```
defmodule Blocks do
2
      use Makina, implemented_by: Etherex
      state height: 0 :: integer()
5
6
      invariants non_neg_height: height >= 0
8
      command block_number() :: {:ok, integer()} do
        post {:ok, height} == result
10
      end
11
12
      command mine() :: :ok do
13
        call Etherex.Time.mine()
14
        next height: height + 1
15
      end
16
    end
```

```
6 9 9 %
8 E A M
8 UR 9 P 8
```

```
defmodule Blocks do
2
      use Makina, implemented_by: Etherex
      state height: 0 :: integer()
5
6
      invariants non_neg_height: height >= 0
8
      command block_number() :: {:ok, integer()} do
        post {:ok, height} == result
10
      end
11
12
      command mine() :: :ok do
13
        call Etherex.Time.mine()
14
        next height: height + 1
15
      end
16
    end
    $ mix gradient
```

```
8 9 9 £
8 £ A M
EUR9PE
```

```
defmodule Blocks do
2
      use Makina, implemented_by: Etherex
      state height: 0 :: integer()
5
6
      invariants non_neg_height: height >= 0
8
      command block_number() :: {:ok, integer()} do
        post {:ok, height} == result
10
      end
11
12
      command mine() :: :ok do
13
        call Etherex.Time.mine()
14
        next height: height + 1
15
      end
16
    end
    $ mix gradient
    The function call Etherex.block_number() on line 8
    is expected to have type {:ok, quantity()}
    but it has type {:ok, quantity()} | {:error, error()}
```



\$ 9 9 £ \$ E 9 M £UR**•**P£

The API:

Command Returns get_balance/1 :ok



The API:

defmodule Accounts do

Command	Returns
get_balance/1	:ok

1. create module.



The API:

defmodule Accounts do
 use Makina, implemented_by: Etherex

Command Returns get_balance/1 :ok

alias Etherex.Type

- 1. create module.
- 2. import Makina.



The API:

Command Returns get_balance/1 :ok

```
defmodule Accounts do
   use Makina, implemented_by: Etherex
```

alias Etherex. Type

```
state accounts: Etherex.accounts!() :: [Type.address()],
    balances: Etherex.balances!() :: %{Type.address() => integer()}
```

- 1. create module.
- 2. import Makina.
- 3. define state.



The API:

Command Returns

get_balance/1 :ok

use Makina, implemented_by: Etherex
alias Etherex.Type

defmodule Accounts do

state accounts: Etherex.accounts!() :: [Type.address()],
 balances: Etherex.balances!() :: %{Type.address() => integer()}

- create module.
- 2. import Makina.
- 3. define state.
- 4. define invariants.



The API:

Command Returns
get_balance/1 :ok

- 1. create module.
- 2. import Makina.
- 3. define state.
- 4. define invariants.
- define commands.

defmodule Accounts do





\$ mix test



\$ mix test
Starting Quviq QuickCheck version 1.45.1



```
$ mix test
Starting Quviq QuickCheck version 1.45.1
```

- 1) property Accounts (ExamplesTest)
 ** (Makina.Error) argument 'account' missing in command get_balance
 stacktrace:
 (makina 0.1.0) lib/makina/error.ex:9: Makina.Error.throw_error/1
 (examples 0.1.0) lib/accounts.ex:13: Accounts.Command.GetBalance.check_args/1
 (examples 0.1.0) lib/accounts.ex:1: Accounts.Behaviour.next_state/3
 Finished in 0.1 seconds (0.00s async, 0.1s sync)
 - 1 properties, 1 failure

Fixing the model



Fixing the model



```
defmodule Accounts do
  use Makina, implemented_by: Etherex
  alias Etherex.Type
  state accounts: Etherex.accounts!() :: [Type.address()],
        balances: Etherex.balances!() :: %{Type.address() => integer()}
  command get_balance(account :: Type.address()) ::
      {:ok, Type.guantity()} | {:error, Type.error()} do
    pre accounts != []
    valid_args account in accounts
    post {:ok. balances[account]} == result
  end
end
```

Fixing the model



```
defmodule Accounts do
  use Makina, implemented_by: Etherex
  alias Etherex. Type
  state accounts: Etherex.accounts!() :: [Type.address()],
        balances: Etherex.balances!() :: %{Type.address() => integer()}
  command get_balance(account :: Type.address()) ::
      {:ok, Type.guantity()} | {:error, Type.error()} do
    pre accounts != []
    args account: oneof(accounts)
    valid_args account in accounts
    post {:ok. balances[account]} == result
  end
end
```





\$ mix test



\$ mix test
Starting Quviq QuickCheck version 1.45.1



```
$ mix test
Starting Quviq QuickCheck version 1.45.1
```

OV paged 100 tagta

OK, passed 100 tests

'100.0 Accounts.get_balance/1

Finished in 4.6 seconds (0.00s async, 4.6s sync) 1 properties, 0 failures



The API to generate and check transactions:



899 889 8

The API to generate and check transactions:

Returns
:ok
<pre>{:ok, integer()}</pre>
<pre>{:ok, integer()}</pre>
{:ok, hash()}

The API to generate and check transactions:

Command	Returns	
mine/0	:ok	
block_number/0	<pre>{:ok, integer()}</pre>	
get_balance/1	<pre>{:ok, integer()}</pre>	
transfer/3	{:ok, hash()}	

We can compose Blocks and Accounts!



The API to generate and check transactions:

Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>
get_balance/1	<pre>{:ok, integer()}</pre>
transfer/3	{:ok, hash()}

We can compose Blocks and Accounts!

```
defmodule Transactions do
   use Makina,
     extends: [Blocks, Accounts],
   implemented_by: Etherex
end
```



The API to generate and check transactions:

Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>
get_balance/1	<pre>{:ok, integer()}</pre>
transfer/3	{:ok, hash()}

We can compose Blocks and Accounts!

```
defmodule Transactions do
   use Makina,
     extends: [Blocks, Accounts],
   implemented_by: Etherex
end
```

Generates a model Transactions.Composed.



The API to generate and check transactions:

Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>
get_balance/1	<pre>{:ok, integer()}</pre>
transfer/3	{:ok, hash()}

State is the union:

- :height
- :accounts
- :balances

We can compose Blocks and Accounts!

```
defmodule Transactions do
  use Makina,
    extends: [Blocks, Accounts],
    implemented_by: Etherex
end
```

Generates a model Transactions.Composed.



The API to generate and check transactions:

Return	S
:ok	
{:ok,	integer()}
{:ok,	integer()}
{:ok,	hash()}
	:ok {:ok, {:ok,

We can compose Blocks and Accounts!

```
defmodule Transactions do
   use Makina,
     extends: [Blocks, Accounts],
   implemented_by: Etherex
end
```

Generates a model Transactions.Composed.

State is the union:

- :heiaht
- :accounts
- :balances

Invariants are the union:

:non_genesis_block



The API to generate and check transactions:

Command	Returns
mine/0	:ok
block_number/0	<pre>{:ok, integer()}</pre>
get_balance/1	<pre>{:ok, integer()}</pre>
transfer/3	<pre>{:ok, hash()}</pre>

We can compose Blocks and Accounts!

```
defmodule Transactions do
   use Makina,
     extends: [Blocks, Accounts],
   implemented_by: Etherex
end
```

Generates a model Transactions.Composed.

State is the union:

- :heiaht
- :accounts
- :balances

Invariants are the union:

:non_genesis_block

Commands are the union:

- mine/0
- block_number/0
- get_balance/1



```
defmodule Transactions do
   use Makina, implemented_by: Etherex, extends: [Accounts, Blocks]
   alias Etherex.Type
```



```
800 E 8 E A M EUROPE
```

```
defmodule Transactions do
   use Makina, implemented_by: Etherex, extends: [Accounts, Blocks]
   alias Etherex.Type

command transfer(
   from :: Type.address(),
   to :: Type.address(),
   value :: Type.quantity()
) :: {:ok, Type.hash()} do
```

end

```
600 E 8 E A M 8 UROPE
```

```
defmodule Transactions do
 use Makina, implemented_by: Etherex, extends: [Accounts, Blocks]
 alias Etherex.Type
 command transfer(
   from :: Type.address(),
   to :: Type.address().
   value :: Type.quantity()
 ) :: {:ok, Type.hash()} do
   pre accounts != []
 end
```

```
600 E 8 E A M EUROB E B B B B
```

```
defmodule Transactions do
 use Makina, implemented_by: Etherex, extends: [Accounts, Blocks]
 alias Etherex.Type
 command transfer(
   from :: Type.address(),
   to :: Type.address().
   value :: Type.quantity()
 ) :: {:ok, Type.hash()} do
   pre accounts != []
    args from: oneof(accounts), to: oneof(accounts), value: pos_integer()
 end
```

Generating transactions

```
600 E 8 E A M EUROD E
```

```
defmodule Transactions do
 use Makina, implemented_by: Etherex, extends: [Accounts, Blocks]
 alias Etherex.Type
 command transfer(
   from :: Type.address(),
   to :: Type.address().
   value :: Type.quantity()
 ) :: {:ok, Type.hash()} do
   pre accounts != []
    args from: oneof(accounts), to: oneof(accounts), value: pos_integer()
   valid_args from in accounts and to in accounts
 end
```

end

Generating transactions

```
defmodule Transactions do
 use Makina, implemented_by: Etherex, extends: [Accounts, Blocks]
 alias Etherex.Type
 command transfer(
   from :: Type.address(),
   to :: Type.address().
   value :: Type.quantity()
  ) :: {:ok, Type.hash()} do
   pre accounts != []
    args from: oneof(accounts), to: oneof(accounts), value: pos_integer()
   valid_args from in accounts and to in accounts
   next balances: update_balances(balances, from, to, value)
 end
```

end

Generating transactions

```
8 9 9 £
8 £ A M
EUROPE
```

```
defmodule Transactions do
 use Makina, implemented_by: Etherex. extends: [Accounts. Blocks]
 alias Etherex.Type
 command transfer(
   from :: Type.address(),
   to :: Type.address().
   value :: Type.quantity()
  ) :: {:ok, Type.hash()} do
   pre accounts != []
    args from: oneof(accounts), to: oneof(accounts), value: pos_integer()
   valid_args from in accounts and to in accounts
   next balances: update_balances(balances, from, to, value)
 end
 def update_balances(balances, from, to, value) do
   halances
    |> Map.update!(from, fn balance - value end)
    |> Map.update!(to, fn balance + value end)
 end
end
```



\$ mix test



\$ mix test
Starting Quviq QuickCheck version 1.45.1



```
$ mix test
Starting Quvig QuickCheck version 1.45.1
Failed! After 1 tests.
    Transactions.transfer("0xffcf8fdee72ac11b5c542428b35eef5769c409f0",
                           "0x90f8bf6a479f320ead074411a4b0e7944ea8c9c1".
                          423319221061516289).
    Transactions.get_balance("0x90f8bf6a479f320ead074411a4b0e7944ea8c9c1"),
    Transactions.mine().
    Transactions.mine().
    Transactions.block_number()
Postcondition failed.
. . .
```

Shrinking xxx.xx.x.x(4 times)



```
Shrinking xxx.xx.x.x.x(4 times)
    Transaction.transfer("0xffcf8fdee72ac11b5c542428b35eef5769c409f0",
                         "0x90f8bf6a479f320ead074411a4b0e7944ea8c9c1".
    Transactions.block_number()
Postcondition failed.
. . .
Transactions.block_number() -> {:ok. 1}
Last state: %{height: 0, ...}
Finished in 0.8 seconds (0.00s async, 0.8s sync)
1 properties, 1 failure
```





```
6 0 D K
B E A M
EURAPE
```

```
defmodule Transactions do
 use Makina, implemented_by: Etherex, extends: [Accounts, Blocks]
 alias Etherex.Type
 command transfer(
   from :: Type.address(),
   to :: Type.address().
   value :: Type.quantity()
  ) :: {:ok, Type.hash()} do
   pre accounts != []
    args from: oneof(accounts), to: oneof(accounts), value: pos_integer()
   valid_args from in accounts and to in accounts
   next balances: update balances(balances, from, to, value).
 end
 def update_balances(balances, from, to, value) do
   balances |> Map.update!(from, &(&1 - value)) |> Map.update!(to, &(&1 + value))
 end
end
```

```
8 9 D E B E P M EUROP E
```

```
defmodule Transactions do
 use Makina, implemented_by: Etherex, extends: [Accounts, Blocks]
 alias Etherex.Type
 command transfer(
   from :: Type.address(),
   to :: Type.address().
   value :: Type.quantity()
  ) :: {:ok, Type.hash()} do
   pre accounts != []
    args from: oneof(accounts), to: oneof(accounts), value: pos_integer()
   valid_args from in accounts and to in accounts
   next balances: update balances(balances, from, to, value).
         height: height + 1
 end
 def update_balances(balances, from, to, value) do
   balances |> Map.update!(from, &(&1 - value)) |> Map.update!(to, &(&1 + value))
 end
end
```





\$ mix test



\$ mix test
Starting Quviq QuickCheck version 1.45.1



```
$ mix test
Starting Quviq QuickCheck version 1.45.1
..Failed! After 2 tests.
[
...
]
Postcondition failed.
...
```

Shrinking xxxx.x.x.x.x.x(6 times)



```
Shrinking xxxx.x.x.x.x.x.x(6 times)
   Transactions.transfer("0x90f8bf6a479f320ead074411a4b0e7944ea8c9c1".
                    "0x90f8bf6a479f320ead074411a4b0e7944ea8c9c1".
                    1),
   Transactions.get_balance("0x90f8bf6a479f320ead074411a4b0e7944ea8c9c1")
Postcondition failed.
Transactions.get_balance("0x90f8bf6a479f320ead074411a4b0e7944ea8c9c1")
Last state:
. . .
   }.
Finished in 1.1 seconds (0.00s async, 1.1s sync)
1 properties, 1 failure
```

#CodeBEAM





Our model does not consider gas consumption.



Our model does not consider gas consumption.

We need to change:

1. A symbolic attribute to store transactions.



Our model does not consider gas consumption.

We need to change:

- 1. A symbolic attribute to store transactions.
- 2. balances needs to be symbolic.



Our model does not consider gas consumption.

We need to change:

- 1. A symbolic attribute to store transactions.
- 2. balances needs to be symbolic.
- 3. get_balance/0 precondition.



Our model does not consider gas consumption.

We need to change:

- A symbolic attribute to store transactions.
- 2. balances needs to be symbolic.
- 3. get_balance/0 precondition.

```
defmodule Transactions do
  state transactions: [] :: [symbolic(Type.hash())]
        balances: super()
          :: symbolic(%{Type.address() => integer()})
  command get_balance() do
    pre transactions == []
  end
  command transfer(...) do
    . . .
    next transactions: [symbolic(elem(result, 1))
                         | transactions],
         . . .
  end
```





gas_cost/1 consults the consumed command and computes the new balances.

```
command gas_cost(hash :: Type.hash()) :: {Type.address(), Type.quantity()} do
  pre transactions != []
  args hash: oneof(transactions)
  valid_args hash in transactions
  next do
    from = symbolic(elem(result, 0))
    gas = symbolic(elem(result, 1))
    [
        transactions: List.delete(transactions, hash),
        balances: discount_gas(balances, from, gas) |> symbolic()
    ]
  end
end
```





\$ mix test



\$ mix test
Starting Quviq QuickCheck version 1.45.1



```
$ mix test
Starting Quviq QuickCheck version 1.45.1
```

OK, passed 100 tests

```
'25.5 Transactions.mine/0
```

- '24.9 Transactions.block_number/0
- '23.6 Transactions.transfer/3
- '14.3 Transactions.gas_cost/1
- '11.8 Transactions.get_balance/1

Finished in 15.8 seconds (0.00s async, 15.8s sync) 1 properties, 0 failures