

Machine Learning and Artificial Intelligence

Lab 05 – SVMs and Evaluation Metrics

12/04/2022


Practical problem

We want to recognize and classify images of handwritten digits:
https://en.wikipedia.org/wiki/MNIST_database


Let's consider this time images belonging to classes '6' and '9':

- They are quite similar between each other (rotation)

«6»



«9»




Support Vector Machines

- Find the separation hyperplane between the 2 classes in order to maximize the margin, i.e., the minimum distances d^+ and d^- between the nearest positive and negative samples respectively

- The lines containing the points with these margins (d^+ and d^-) are called support vectors

- Linearly classify new data x :


$$f(\mathbf{x}) = \text{sign}(\mathbf{w} \cdot \mathbf{x} + b)$$




What if the problem is non-linear?

- We can't find a separation hyperplane that divides all the samples correctly!
- Introduction of Slack variables ξ_i , that allow some SV to exceed the margin, along and a parameter C indicating the cost for a wrong classification.
- **Kernel trick**: Map data in another, higher-dimensional space through functions called kernels.

Not Linearly Separable





Examples of kernel functions

Linear

$$K(x, z) = \langle x, z \rangle$$

Polynomial

$$K(x, z) = (\langle x, z \rangle + 1)^p$$

Radial basis functions

$$K(x, z) = e^{-\frac{\|x-z\|^2}{2\sigma^2}}$$

Sigmoid

$$K(x, z) = \tanh(a\langle x, z \rangle + b)$$

SVM in Scikit-learn

- The SVM classification algorithm can be implemented through scikit-learn (<https://scikit-learn.org/stable/modules/generated/sklearn.svm.SVC.html#sklearn.svm.SVC>)
- How?
 1. Model initialization (kernel specific): `model = SVC(...)`
 2. Model fit (training to get w and b): `model.fit()`
 3. Classification of test elements: `model.predict(x)`

Evaluation

- It is imperative to understand how a classifier behaves quantitatively.
- We need this information to:
 - *Have absolute feedback*: the goodness of a classifier/regressor.
 - *Have relative feedback*: the goodness of a classifier/regressor compared to another.

Classification evaluation metrics

- Accuracy: Number of correct predictions divided by the total number of predictions (dimensionality of the test set):

$$accuracy = \frac{\# \text{ correct classifications}}{\# \text{ classifications}}$$

- Error rate: Number of wrong predictions with respect to the total number of predictions:

$$error_rate = \frac{\# \text{ incorrect classifications}}{\# \text{ classifications}}$$

Confusion Matrix

- It allows you to understand where exactly the classifier makes mistakes.
- Introduced initially for binary classification cases.
- Example:
 - Class A: Dog(positive)
 - Class B: Not-dog (negative)

Confusion matrix for binary classification

Actual value	A	TP	FN Type I error
	B	FP Type II error	TN
		A	B
		Predicted value	

Confusion Matrix – Construction

- With each prediction on the test set, I add +1 in the appropriate box (intersection between the index predicted by the classifier and the GT index)
- In the case of balanced classes, we can normalize the values of the matrix, so that the rows sum to one.
- It's convenient to normalize values by rows and get percentages. The absolute count does contain more information though.

		Predicted	
		P	N
Real	P	20 (0.66)	10 (0.33)
	N	5 (0.17)	25 (0.83)

Confusion Matrix - Metrics

- In the range [0,1]

- Accuracy $\frac{tp + tn}{tp + tn + fp + fn}$

- Precision $\frac{tp}{tp + fp}$

- Portion of cases predicted as positive that actually are positive.
- (If high) I take as positive only elements that actually are positive.
- (If low) I say everything is positive.



Confusion Matrix - Metrics

- **Recall** (sensitivity)

- Portion of all actually positive cases that have actually been classified as such
- (If high) I don't lose positive elements
- (If low) I lose positive elements

$$\frac{tp}{tp + fn}$$

- **F-measure**


- Combine precision and recall into one measure.

$$F - measure = \frac{2 * Recall * Precision}{Recall + Precision}$$

Regression tasks

- In machine learning, we are not limited to classification tasks, even though they are common.
- In regression tasks, the model learns to predict numeric scores, so the model output is a continuous variable.
- In such a case, the metrics we mentioned before cannot be applied, because we are more interested in the magnitude of the error.

Regression evaluation metrics



$$MAE = \frac{1}{n} \sum_{i=1}^n \underbrace{|y_i - \hat{y}_i|}_{\text{predicted value} - \text{actual value}}$$

test set

$$MSE = \frac{1}{n} \sum \underbrace{(y - \hat{y})^2}_{\text{The square of the difference between actual and predicted}}$$

$$RMSE = \sqrt{\sum_{i=1}^n \frac{(\hat{y}_i - y_i)^2}{n}}$$

Evaluation metrics available in Sklearn

<https://scikit-learn.org/stable/modules/classes.html#module-sklearn.metrics>

Exercises

A slightly different scenario

- We must no longer classify only images belonging to classes '6' and '9' but all figures from '0' to '9'




From binary to multi-class

- How do we move from binary classification to multi-class classification?
- SVMs (and many other classifiers) don't support multi-class classification *natively*, we need to adopt different strategies.
- One vs Rest:
 - Train K different classifiers, one for each class.
 - Each of the classifiers considers a class as positive and the remaining as negative.
 - Another, less popular approach is One vs One

From binary to multi-class

- One vs Rest strategy:
 1. Given K classes, instantiate K different SVMs.
 2. Train each of the K classifiers to recognize a particular class (the 3rd classifier will be trained to recognize class 3 and so on...)
 3. Given the test elements, each of the K classifiers produces two probabilities:
 1. Of belonging to the k-th class
 2. Of not belonging to the k-th class
 4. The class corresponding to the test element is the one with the highest probability of membership.
 5. P.S: To output probabilities you must use the *'predict_proba'* function in the Sklearn library.

Confusion Matrix – K classes



Confusion Matrix – K classes

- Precision and Recall are associated with *a single class*.
- Given the confusion matrix $C \times C$

- Precision:
$$\frac{tp}{tp + fp} = \frac{Conf(c, c)}{\sum_d Conf(d, c)}$$

- Recall
$$\frac{tp}{tp + fn} = \frac{Conf(c, c)}{\sum_d Conf(c, d)}$$

Exercises