

Review Article



Computational Chemistry in Structure-Based Drug Design: Tools, Trends, and Transformations

Mohit Joshi^{1,2} , Irfan Pathan^{1,2} , Adarsh Sahu^{1,2} , Arif Raza^{1,2} , Yamini Sahu^{1,2} ,
Nousheen Khatoun^{1,2*}

¹Rungta College of Pharmaceutical Sciences and Research, Bhilai, (C.G.), India

²School of Pharmacy, Rungta International Skill University, Bhilai, C.G. India



Citation M. Joshi, I. Pathan, A. Sahu, A. Raza, Y. Sahu, N. Khatoun, Computational Chemistry in Structure-Based Drug Design: Tools, Trends, and Transformations. *J. Pharm. Sci. Comput. Chem.* **2025**, 1 [3], 246-266.



<https://doi.org/10.48309/jpscc.2025.535670.1020>



Article info:

Submitted: 2025-07-20

Revised: 2025-07-31

Accepted: 2025-08-02

Published: 2025-09-14

ID: JPSCC-2507-1020

Keywords:

SBDD, protein, Ligand, Molecular docking, Drug discovery, In silico prediction, Computational chemistry.

ABSTRACT

Structure-Based Drug Design (SBDD) has emerged as a pivotal strategy in modern drug discovery, enabling the rational design of therapeutics through detailed understanding of biomolecular structures. This review presents a comprehensive overview of the fundamental principles, methodologies, and computational tools that underpin SBDD. The process begins with the determination of protein structures using techniques such as X-ray crystallography, NMR spectroscopy, and cryo-electron microscopy, followed by molecular modelling and visualization using tools such as PyMOL and Chimera. Molecular docking approaches, both rigid and flexible, are employed to predict ligand binding modes and affinities, while molecular dynamics (MD) simulations provide insights into the dynamic behaviour of protein-ligand complexes. Advanced techniques such as quantum mechanics (QM) and hybrid QM/MM methods further enhance the accuracy of active site analysis and energy calculations. Pharmacophore modelling and virtual screening facilitate the identification of novel hits, while ADMET predictions support the optimization of drug-like properties early in the design process. The integration of artificial intelligence (AI) and machine learning (ML) has significantly accelerated and refined SBDD workflows, allowing for data-driven predictions and enhanced screening efficiency. Despite remarkable progress, challenges such as limited accuracy in scoring functions and computational costs persist. Future directions point toward leveraging quantum computing and next-generation AI models to overcome these limitations. This review highlights the synergistic role of computational chemistry and emerging technologies in shaping the future of rational drug design.

Introduction

Structure-Based Drug Design (SBDD) has emerged as a powerful approach in modern drug discovery, offering a rational and efficient method for identifying and optimizing bioactive compounds. Unlike traditional trial-and-error methods, SBDD relies on the detailed knowledge of the three-dimensional (3D) structure of biological targets, such as enzymes,

receptors, or nucleic acids, to design molecules that can interact specifically and effectively with them. This approach has significantly accelerated the drug development process and improved the success rate of therapeutic agents reaching the market [1]. Drug discovery is a complex, multidisciplinary process that begins with the identification of a biological target implicated in a disease, and proceeds through several stages, including hit identification, lead optimization, preclinical testing, and clinical

*Corresponding Author: Nousheen Khatoun (nskhatoun31@gmail.com)

trials. Traditionally, drug discovery has been a time-consuming and resource-intensive endeavor, with a high rate of failure [2]. However, advancements in molecular biology, genomics, and computational sciences have transformed this landscape. The integration of computational tools allows researchers to predict biological activity, assess drug-likeness, and model drug-target interactions early in the development pipeline, thereby reducing costs and time [3].

SBDD plays a vital role in rational drug design using the structural information of target biomolecules obtained from experimental techniques such as X-ray crystallography, nuclear magnetic resonance (NMR) spectroscopy, and cryo-electron microscopy (cryo-EM). Once the target structure is known, computational tools are used to design ligands that fit precisely into the active or allosteric sites of the target [4]. Techniques such as molecular docking, molecular dynamics simulations, and pharmacophore modeling are commonly employed to predict the binding modes and affinities of potential drug candidates. SBDD enables the identification of novel scaffolds and optimization of binding interactions, ultimately improving the potency, selectivity, and safety profile of lead compounds [5]. Computational chemistry is an indispensable component of SBDD, providing the theoretical framework and simulation techniques required to understand molecular interactions at the atomic level. It encompasses a wide range of methods, from quantum mechanics (QM) and molecular mechanics (MM) to hybrid QM/MM approaches. These techniques help in calculating the energetics of ligand binding, predict protein conformational changes, and stimulate reaction pathways [6]. Moreover, computational methods allow for virtual screening of large chemical libraries, prioritizing compounds with the highest likelihood of biological activity. By guiding experimental efforts and refining molecular hypotheses, computational chemistry not only accelerates the drug discovery process, but also enhances the accuracy and predictability of SBDD results. Accordingly, it is a vital tool in the development of next-generation therapeutics [7].

Fundamentals of Structure-Based Drug Design

Protein Structure and Function

Proteins are dynamic macromolecules that serve as primary drug targets due to their vital roles in cellular processes such as catalysis, signaling, and regulation. Their function is inherently linked to their three-dimensional structure, including distinct features such as active sites, binding pockets, and allosteric sites. Recent advancements in structural biology techniques, especially cryo-electron microscopy (cryo-EM) and AlphaFold's AI-based structure prediction, have significantly enhanced the accuracy and availability of protein structural data [8]. This structural information is crucial for structure-based drug design (SBDD), enabling precise modeling of protein-ligand interactions. Understanding not only static protein conformations, but also their dynamic behavior through tools like molecular dynamics simulations allows researchers to account for target flexibility, thereby enhancing the rational design of selective and potent drug candidates [9].

Ligand-Receptor Interactions

Ligand-receptor interactions form the foundation of Structure-Based Drug Design (SBDD), as the therapeutic efficacy of a drug largely depends on its ability to bind specifically and effectively to a biological target. A ligand, typically a small molecule, interacts with a receptor often a protein such as an enzyme or a membrane-bound receptor through various non-covalent forces, including hydrogen bonding, ionic interactions, hydrophobic contacts, π - π stacking, and van der Waals forces [10]. The complementarity of shape, charge, and hydrophobicity between ligand and binding site determines binding affinity and specificity. Recent advances in computational methods such as molecular docking, binding free energy calculations, and enhanced sampling simulations have improved our ability to model and predict these interactions at atomic resolution. Moreover, understanding induced fit and conformational selection where either the ligand or the receptor (or both) undergoes

structural adaptation upon binding has become increasingly important in designing high-affinity, selective drugs. These insights facilitate rational drug optimization, improving pharmacological profiles and reducing off-target effects [11].

Figure 1 displays the process of ligand-receptor interaction, a fundamental mechanism in cell signaling. It shows a ligand approaching and

binding to the extracellular domain of a membrane-bound receptor. The receptor consists of three main parts: the ligand-binding domain, the transmembrane domain, and the intracellular effector domain. Upon binding, the ligand forms a receptor-ligand complex, which induces a conformational change in the receptor structure.




Figure 1: Ligand receptor interaction

Structure Determination Techniques (X-ray, NMR, and Cryo-EM)

The precise structural data of target biomolecules are essential for Structure-Based Drug Design (SBDD), and this is primarily obtained through advanced structure determination techniques such as X-ray crystallography, nuclear magnetic resonance (NMR) spectroscopy, and cryo-electron microscopy (cryo-EM). X-ray crystallography remains the most widely used technique, providing high-resolution atomic structures of crystalline proteins, though it is limited by the need for high-quality crystals [12]. NMR spectroscopy enables the study of proteins in solution, providing insights into protein flexibility and dynamics, but is typically restricted to smaller proteins (usually < 50 kDa). Cryo-EM, a rapidly advancing technique, allows for the visualization of large and complex biomolecules in near-native states without crystallization. Recent breakthroughs in detector technology and image processing

algorithms have propelled cryo-EM into mainstream drug discovery, enabling near-atomic resolution structures of membrane proteins and macromolecular complexes. These structural methods, often used in combination with computational modeling, are critical for identifying binding sites, understanding molecular interactions, and guiding rational drug design [13].

The integration of X-ray crystallography, NMR spectroscopy, and cryo-EM has significantly transformed the landscape of drug discovery by enabling a detailed understanding of drug-target interactions at the atomic level. These techniques not only reveal the static structures of biological targets, but also allow researchers to examine conformational flexibility, binding-induced changes, and protein-ligand dynamics, which are critical for optimizing drug efficacy and selectivity [14]. For instance, cryo-EM has become particularly valuable for targets like G-protein-coupled receptors (GPCRs) and ion channels, which are difficult to crystallize, but highly relevant in pharmacology. Moreover, the

integration of AI-based tools such as AlphaFold2, which predicts protein structures with remarkable accuracy, is further accelerating the structure determination process, especially when experimental methods are limited. Together, these advancements ensure that drug design is increasingly informed by reliable structural data, enhancing the precision and efficiency of SBDD strategies [15].

Molecular Modeling and Visualization Tools

Protein and Ligand Preparation

The accurate preparation of protein and ligand is a fundamental step in molecular modeling workflows and is critical for the success of structure-based drug design (SBDD). Before the computational analyses such as docking or molecular dynamics, the raw structural data obtained from experimental techniques (*e.g.*, PDB files) must be refined and optimized. Protein preparation involves several key steps, including the addition of missing hydrogen atoms, assignment of correct bond orders, optimization of protonation states at physiological pH, and the removal of crystallographic artifacts such as water molecules or co-crystallized ligands not involved in the binding process [16]. Similarly, ligand preparation ensures that the small molecule is in the correct tautomeric and ionization states, has minimized energy, and includes accurate stereochemistry and 3D conformation. Tools such as Schrödinger's Protein Preparation Wizard, MOE, Chimera, and Open Babel are widely used for these tasks. Proper preparation improves the reliability of downstream modeling techniques by ensuring realistic biological interactions and energetically favorable conformations, thereby enhancing the predictive accuracy of drug-target binding studies [17].

Molecular Graphics Software (PyMOL, Chimera, etc.)

Molecular graphics software plays a vital role in the visualization, analysis, and interpretation of biomolecular structures, significantly aiding

structure-based drug design (SBDD). Some tools such as PyMOL, UCSF Chimera, ChimeraX, and VMD (Visual Molecular Dynamics) are widely used for rendering high-quality, three-dimensional representations of proteins, ligands, and complexes. These platforms allow researchers to inspect binding sites, analyze molecular interactions, and generate publication-ready images. PyMOL, for instance, is favored for its scripting flexibility and clarity in visualizing protein-ligand complexes, while Chimera and ChimeraX provide advanced capabilities for molecular docking analysis, surface rendering, electrostatic potential mapping, and trajectory visualization from molecular dynamics simulations [18]. These tools also support structural alignment, mutation modeling, and distance measurements, all of which are essential for understanding structure-activity relationships (SAR). The integration of molecular graphics software into the computational workflows enhances decision-making during lead optimization by intuitively exploring structural data and interaction patterns at the atomic level in Table 1 [19].

Molecular Docking

Principles and Types (Rigid vs. Flexible)

Molecular docking is a core computational technique in structure-based drug design (SBDD) used to predict the preferred orientation of a small molecule (ligand) when bound to a target protein (receptor) and to estimate the strength and nature of the interaction. The underlying principle involves searching for the optimal fit between the ligand and the binding site on the receptor based on shape complementarity, chemical interactions, and binding energy scoring. Docking algorithms typically employ two main types: rigid docking and flexible docking. In rigid docking, both the protein and the ligand are treated as inflexible bodies, simplifying the computational process but often neglecting biologically relevant conformational changes [20]. Flexible docking, on the other hand, allows the ligand (and in some cases the protein side chains or backbone) to adopt multiple conformations,

providing a more accurate and realistic prediction of binding poses and affinities. Advanced docking programs such as AutoDock, AutoDock Vina, Glide, and MOE incorporate flexible algorithms and scoring functions to improve reliability. The choice between rigid and flexible docking depends on the biological system and computational resources, but flexible docking is generally preferred for lead optimization and when protein or ligand flexibility significantly influences binding behavior [21].

Figure 2 depicts the workflow of 3D-QSAR (Quantitative Structure-Activity Relationship) guided drug design and evaluation, specifically targeting the design of new LRRK2 inhibitors. It begins with the generation of a 3D-QSAR model based on the chemical structure and biological activity of known compounds. The key molecular features such as electropositive and electronegative regions, hydrophobic and hydrophilic sites, hydrogen bond donor/acceptor regions, and electronic effects are identified and mapped.

Table 1: Strategic insights into SBDD software ecosystem

Software	Developer/Sour ce	Key Features	File Support	Scripting/Custo mization	Use in SBDD	Latest Updates / Highlights (2024–2025)	Ref.
PyMOL	Schrödinger (open-core)	High- quality 3D renderin, molecular visualizat ion, electrosta tics, and plugins	PDB, SDF, MOL2, etc.	Python scripting	Ligand- protein binding visualization, interaction mapping, structure analysis	Improved GPU rendering, integration with AI plugins, expanded support for mmCIF	[19]
UCSF Chimera	UCSF Resource for Biocomputing	Extensive visualizat ion tools, structure editing, density maps, and docking prep	PDB, MOL2, SDF, DCD, etc.	Python-based command line	Preparing structures for docking, hydrogen bond visualization, Ramachandr an analysis	Stable but being replaced by ChimeraX; still used for custom workflows	[20]
Chimera X	UCSF	Next-gen Chimera: faster rendering , better VR support, AlphaFol d integratio n	PDB, mmCIF, cryo-EM maps	Python/Command -line scripting	Advanced interaction analysis, cryo-EM, docking prep, visualization of predicted protein structures	Native AlphaFold & RoseTTAFold support, VR visualization, interactive docking tools (2024)	[21]

VMD	Theoretical Biophysics Group (UIUC)	Molecular dynamics (MD) visualization, trajectory analysis, and large systems	PDB, DCD, PSF, GRO	Tcl, Python scripting	Analysis of MD simulations, membrane modeling, and RMSD/RMSF calculations	Enhanced support for GPU-based analysis, quantum trajectory visualization (2024 update)	[22]
MOE	Chemical Computing Group	Integrated modeling + visualization, structure-based design, QSAR, and docking	PDB, MOE, MOL, SDF	Proprietary scripting (SVL)	Structure cleanup, pharmacophore modeling, docking, and ligand design	AI-enhanced scoring, new QSAR tools, expanded pharmacophore analysis (MOE 2024 release)	[23]




Figure 2: Workflow of 3D-QSAR guided drug design and evaluation

Docking Algorithms and Scoring Functions

Docking algorithms and scoring functions are vital for predictive power of molecular docking, as they determine how effectively a ligand fits into a target binding site and estimate the strength of interaction. Docking algorithms are responsible for exploring the conformational and orientational space of the ligand within the receptor site. Common search methods include

systematic searches, stochastic approaches such as genetic algorithms, Monte Carlo simulations, and molecular dynamics-based sampling [22]. These methods aim to generate a wide range of plausible binding poses by accounting for ligand flexibility, and in some advanced cases, receptor flexibility. Once potential poses are generated, scoring functions are used to evaluate and rank them based on predicted binding affinity. These functions fall

into three main categories: force-field-based, which calculate physical interaction energies (e.g., van der Waals and electrostatics); empirical, which are based on experimentally derived parameters; and knowledge-based, which rely on statistical potentials derived from known protein-ligand complexes [23]. Widely used docking programs such as AutoDock, Glide, GOLD, and DOCK use combinations of these algorithms and scoring functions to enhance prediction accuracy. Despite advances, scoring functions still face limitations in accurately predicting absolute binding affinities, and are often complemented by rescoring, consensus scoring, or post-docking refinement methods to improve reliability in virtual screening and lead optimization [24].

Docking algorithms work by probing the conformational space of the ligand and protein interactions, using various searching methods, including genetic algorithms, molecular dynamics, and Monte Carlo searches, and systematic or stochastic approaches. These algorithms aim to find multiple possible binding poses of the ligand in the active site of the target protein. These poses are evaluated using scoring functions, which can be generally categorized as force-field-based, empirical and knowledge-based [25]. Force-field-based scoring functions rely on molecular mechanical principles and calculate interaction energy via the sums of van der Waals forces, electrostatics and bonded interactions, using parameter sets such as AMBER or CHARMM. While these can be physically interpreted, force-field based scoring can be time-consuming and is less adept at considering entropic contributions and solvation effects. The empirical scoring functions rely on weighted sums of different interactions such as hydrogen bonding, lipophilic contacts, and de-solvation energies, with coefficients derived from regression based on experimental binding data. This gives empirical scoring functions speed on the scoring aspect and reasonable accuracy, although it is limited by the quality and extent of the training data [26].

Applications and Limitations

Molecular docking is widely applied across various stages of drug discovery, particularly in virtual screening, hit identification, and lead optimization. It enables the rapid screening of large compound libraries against a biological target to identify potential binders, significantly reducing the cost and time of early-stage drug development. Docking also aids in predicting binding modes, ranking ligand affinities, and understanding structure–activity relationships (SAR), thereby guiding chemical modifications to enhance potency and selectivity [27]. Additionally, it supports drug repurposing, fragment-based drug design, and the exploration of binding site druggability. However, despite its utility, molecular docking has several limitations. One major challenge is the limited accuracy of scoring functions, which may fail to reliably predict true binding affinities or discriminate between true positives and false positives. Moreover, receptor flexibility is often oversimplified, and solvent effects are either poorly approximated or neglected entirely [28]. These factors can lead to inaccurate binding pose predictions, especially for highly dynamic or allosteric sites. Therefore, docking results often require validation through molecular dynamics simulations, free energy calculations, or experimental assays. While docking remains a powerful and accessible tool in rational drug design, its predictions should be interpreted cautiously and in conjunction with complementary computational and experimental methods [29].

Despite the general applicability of molecular docking algorithms and scoring functions, they suffer from limitations that will impact their reliability as predictive methods. The major limitation is related to the incomplete representation of protein flexibility. While many docking protocols allow for some limited flexibility (or consider the receptor to be rigid), the static snapshot provided by docking does not reflect the dynamic nature of proteins nor provide accurate binding poses. On the other hand, force-field based methods are chemically rigorous but computationally costly, and sensitive to inaccuracies in parameters. Empirical scoring functions have explicit dependencies on both the quality and the

diversity of the experimental data used to train them, which limits generalizability across target classes [30]. Knowledge-based scoring functions are also computationally efficient; however, their implicit use of statistical potentials, derived from known (and previously been determined experimentally) structures, may not work at all for novel targets (or ligand chemotypes) that do not exist in the training set. Furthermore, scoring functions occasionally perform poorly for rank ordering ligands because ligands with slight structural or selectivity differences have similar binding affinities – which produces (false) positives and negatives in virtual screening. The ligand strain energy and water-mediated interactions are likely underrepresented as well, and the ability to predictably dock ligands can rapidly deteriorate due to these limitations. This is why development of integrated protocols that combine docking with "correct" post-docking analyses (e.g., MM, MD, etc) will on average produce more reliable results [31].

Molecular Dynamics (MD) Simulations

Basic Theory and Force Fields

Molecular Dynamics (MD) simulations are a powerful computational technique used to study the time-dependent behavior of biomolecular systems at the atomic level. In the context of drug design, MD simulations provide detailed insights into protein flexibility, ligand binding stability, and conformational changes that are often missed by static docking approaches. The basic theory involves numerically solving Newton's equations of motion for a system of particles (atoms), allowing simulation of their trajectories over time under defined physical conditions. To compute atomic interactions, MD relies on force fields mathematical models that describe the potential energy of the system [32]. Force fields such as AMBER, CHARMM, OPLS-AA, and GROMOS consist of parameters for bonded interactions (bonds, angles, dihedrals) and non-bonded interactions (electrostatics and van der Waals forces). Accurate force field selection is critical, as it influences the realism and predictive power of the simulation. Recent

improvements in force fields, including polarizable and machine learning-driven models, have enhanced the ability of MD to mimic physiological conditions, making it an indispensable tool in modern structure-based drug discovery [33].

System Setup and Simulation Protocols

System setup and simulation protocols are foundational to conducting reliable Molecular Dynamics (MD) simulations, particularly in the context of drug discovery and protein-ligand interaction studies. The process begins with the preparation of the molecular structure, typically a protein-ligand complex obtained from crystallographic or modeled data. This step includes assigning proper protonation states at physiological pH, adding missing hydrogen or heavy atoms, correcting bond orders, and removing crystallographic artifacts such as water molecules or unwanted ligands [34]. The ligand should also be parameterized using appropriate force field-compatible tools, such as Antechamber for AMBER, CGenFF for CHARMM, or LigParGen for OPLS-AA, to ensure correct atomic charges, topology, and bonding information. Once preparation is complete, the system is placed in a simulation box—commonly cubic or octahedral in shape and solvated with explicit water molecules using standard water models such as TIP3P or SPC/E. To maintain electrical neutrality and replicate physiological conditions, counterions such as Na⁺ or Cl[−] are added [35].

Following the system construction, a multi-step simulation protocol is employed to equilibrate and simulate the system under realistic biological conditions. The first stage involves energy minimization to relieve any steric clashes or unfavorable interactions in the initial structure. This is followed by equilibration phases, typically performed under the canonical (NVT) and isothermal-isobaric (NPT) ensembles, during which temperature and pressure are gradually stabilized while applying positional restraints to the heavy atoms of the protein and ligand. Once equilibration is achieved, the production phase begins an unrestrained simulation, allowing the system to evolve naturally according to Newton's laws of

motion, usually over nanosecond to microsecond timescales, depending on the study objective. A time step of 1-2 femtoseconds is commonly used, with temperature and pressure control algorithms such as Langevin dynamics or Berendsen thermostat and barostat. The long-range electrostatics are calculated using methods such as Particle Mesh Ewald (PME), and periodic boundary conditions are applied to mimic an infinite system [36].

Enhanced Sampling Techniques

While conventional molecular dynamics (MD) simulations provide valuable insights into biomolecular behavior, they are often limited by timescale constraints, particularly when attempting to observe rare events such as ligand binding, conformational transitions, or protein folding. To overcome these limitations, enhanced sampling techniques have been developed to accelerate the exploration of conformational space and improve sampling efficiency. These methods help escape local energy minima and capture biologically relevant, yet infrequent events within feasible computational timeframes [37]. One widely used technique is metadynamics, which adds history-dependent biasing potentials to a set of collective variables, encouraging the system to explore new configurations. Replica Exchange Molecular Dynamics (REMD) runs multiple simulations (replicas) at different temperatures, allowing exchanges between replicas to improve conformational sampling and reduce energy barriers. Accelerated Molecular Dynamics (aMD) modifies the potential energy surface to flatten energy wells, facilitating transitions between states that are otherwise kinetically inaccessible [38]. Other methods, such as umbrella sampling, steered MD, and Gaussian accelerated MD (GaMD), are employed to quantify free energy landscapes and study specific reaction pathways or unbinding events. Enhanced sampling is particularly valuable in structure-based drug design for capturing the full flexibility of protein targets, identifying transient or cryptic binding pockets, and refining binding affinity predictions. These techniques, when combined

with conventional MD and experimental validation, significantly enhance the reliability of in silico drug discovery [39].

Quantum Mechanics (QM) and QM/MM Methods

Overview of QM Methods (DFT, HF)

Quantum mechanical (QM) methods provide an atomistic and electronic-level description of molecular systems, making them essential for accurately modeling chemical processes such as bond formation/breaking, charge transfer, and enzyme catalysis. Two widely used QM approaches in computational chemistry are Hartree-Fock (HF) and Density Functional Theory (DFT). The HF method is an ab initio approach that solves the Schrödinger equation for a many-electron system by approximating electron-electron repulsion through a mean-field potential [40], while computationally efficient, HF neglects electron correlation, which limits its accuracy for many chemical systems. However, DFT includes electron correlation through functionals of electron density, rather than wavefunctions, providing a better balance between accuracy and computational cost. Popular DFT functionals, such as B3LYP or PBE, are widely applied in organic, inorganic, and biological chemistry for calculating molecular geometries, reaction energies, and electronic properties. Both methods are particularly useful in drug design when evaluating reaction mechanisms, metal-ligand interactions, or electronic structure-based reactivity, which are often beyond the capability of classical force fields. Nevertheless, the high computational cost of QM methods restricts their use to small molecules or localized regions of larger biomolecular systems, prompting the development of hybrid techniques such as QM/MM [41].

Hybrid QM/MM in Active Site Analysis

Hybrid Quantum Mechanics/Molecular Mechanics (QM/MM) methods combine the accuracy of quantum mechanics with the efficiency of classical molecular mechanics, making them highly suitable for studying complex biological systems, particularly active

sites of enzymes and protein-ligand complexes. In this approach, the system is partitioned into two regions: the QM region, which typically includes the ligand, catalytic residues, cofactors, and nearby water molecules directly involved in the chemical reaction; and the MM region, comprising the rest of the protein and solvent environment [42]. The QM region is treated using methods such as DFT or semi-empirical QM approaches, while the MM region is modeled with classical force fields such as AMBER, CHARMM, or OPLS. This hybridization allows for high-accuracy modeling of electronic events such as bond breaking/forming, proton transfers, and charge redistribution in the active site, without incurring the computational cost of a full QM treatment. QM/MM has proven

especially valuable in elucidating enzyme mechanisms, modeling transition states, designing inhibitor, and studying metal coordination [43]. It also allows the calculation of reaction energy barriers and potential energy surfaces, providing mechanistic insights that are critical for rational drug design. By capturing the quantum nature of chemical reactions within a realistic biological environment, QM/MM provides a powerful tool for analyzing reactivity and guiding the design of more effective and selective drug candidates [44]. The comparison of key aspects across DFT, HF, and hybrid QM/MM approaches for structure-based drug design is indicated in Table 2.

Table 2: Comparison of key aspects across DFT, HF, and hybrid QM/MM approaches

Aspect	Density Functional Theory (DFT)	Hartree-Fock (HF)	Hybrid QM/MM Methods	Ref.
Core Principle	Electron density-based quantum calculations	Wavefunction-based mean-field approximation	QM for reactive site; MM for rest of system	[45]
Level of Theory	Post-HF accuracy with lower cost	Fundamental ab initio method	Multi-scale simulation combining quantum and classical mechanics	[46]
Accuracy	High for ground-state properties, bond energies	Moderate accuracy, lacks electron correlation	High for localized phenomena; balances accuracy and efficiency	[47]
Computational Cost	Moderate to high (basis-set dependent)	Generally lower than DFT, but less accurate	Lower than full QM; scalable for large biomolecules	[48]
Application in Drug Design	Predicting electronic structure, reactivity, charge distribution	Basic estimation of energy levels, orbitals	Studying enzyme mechanisms, active site reactions, metal coordination	[49]
Use in Active Site Analysis	Detailed interaction energies, transition states	Orbital models of ligand binding	Reaction pathways, ligand-metal coordination, enzyme catalysis	[50]
Software Tools	Gaussian, ORCA, Q-Chem, NWChem	Gaussian, GAMESS, and Psi4	ONIOM (Gaussian), ChemShell, Amber-QM/MM, CHARMM-QM/MM	[51]

Advantages	Good trade-off between speed and accuracy; suitable for drug molecules	Conceptually simple; foundation for more complex theories	Allows realistic modeling of large systems without full QM expense	[52]
Limitations	Struggles with dispersion, excited states (unless corrected)	Ignores electron correlation, not suitable for complex systems	Accuracy depends on boundary treatment and QM/MM partitioning	[53]
Recent Advances (2024-25)	Integration with AI-driven QM predictions; GPU-accelerated DFT	Used as base for hybrid models or ML training	Real-time QM/MM dynamics, machine-learned force fields, cloud platforms	[54]

Energy Calculations and Reactivity

Energy calculations lie at the heart of quantum chemical methods and are essential for understanding molecular reactivity, stability, and interaction strength key aspects in rational drug design. Quantum Mechanics (QM) and hybrid QM/MM approaches allow for accurate estimation of potential energy surfaces (PES), which depict the energetic landscape of molecular systems as a function of nuclear positions [55]. These calculations enable the identification of stable intermediates, transition states, and reaction pathways, providing insights into the energetics of enzyme catalysis, ligand binding, and drug metabolism. Key parameters derived from QM calculations include reaction energies, activation barriers, ionization potentials, electron affinities, and HOMO–LUMO gaps, which are closely related to a molecule's chemical reactivity and pharmacological potential. In QM/MM simulations, energy decomposition techniques can be utilized to quantify the contributions of specific residues or functional groups to binding or catalysis, aiding in the identification of hot spots for drug targeting or optimization [56]. Additionally, free energy calculations using methods such as umbrella sampling, thermodynamic integration, or metadynamics can be coupled with QM or QM/MM models to estimate reaction kinetics and binding affinities more accurately. By capturing both electronic effects and environmental influences, energy and reactivity analyses provide a mechanistic

foundation for designing more potent and selective therapeutics [57].

Pharmacophore Modeling

Concept and Generation

Pharmacophore modeling is a key computational technique in drug discovery that represents the essential spatial arrangement of molecular features required for optimal interaction with a specific biological target [58]. A pharmacophore is defined as an abstract, 3D ensemble of features—such as hydrogen bond donors/acceptors, hydrophobic centers, aromatic rings, and positive or negative ionizable groups—that are responsible for a molecule's biological activity. The concept is based on identifying the common features shared among a set of active compounds, or deducing the interaction features directly from the structure of a known receptor-ligand complex. Ligand-based pharmacophore modeling involves aligning multiple active ligands to extract a shared pharmacophore, while structure-based pharmacophore modeling derives these features from the 3D structure of the binding site, often using protein-ligand complexes obtained from crystallography or docking studies [59]. Tools such as LigandScout, Discovery Studio, PharmaGist, and MOE facilitate pharmacophore generation by detecting interaction features, optimizing spatial alignment, and validating models using known actives and decoys. Once generated, pharmacophore models can be used

for virtual screening of large compound libraries, identifying new scaffolds, and guiding medicinal chemistry efforts by highlighting key interaction points. By abstracting critical binding features, pharmacophore modeling provides a powerful, target-specific approach to identify novel lead compounds and improve hit-to-lead progression [60].

In pharmacophore modeling combined with QM/MM approaches, the electrostatic embedding and mechanical embedding schemes refer to how quantum mechanical (QM) and molecular mechanical (MM) regions interact, particularly in hybrid simulations. In mechanical embedding, the QM and MM regions interact only through classical (MM-level) van der Waals and bonded terms, with no effect of the MM point charges on the QM electron density—meaning the QM calculations are performed as if in a vacuum, unaffected by the electrostatic environment of the surrounding MM atoms. This limits accuracy when modeling systems where polarization effects or charge transfer between the QM and MM regions are significant. However, electrostatic embedding includes the MM point charges in the QM Hamiltonian, allowing the QM wavefunction to respond to the electrostatic field created by the MM atoms. This provides a more realistic depiction of interactions, especially important when the active site or pharmacophore region involves charged or highly polar residues [61].

QM/MM becomes necessary over classical molecular dynamics (MD) when electronic effects such as bond breaking/forming, charge delocalization, tautomerism, metal coordination, or proton transfer are critical to understanding ligand binding or pharmacophore interactions. Classical MD, based solely on fixed force fields, cannot account for such electronic changes and may misrepresent key features of the pharmacophore if they involve polarization or electronic rearrangement. QM/MM, especially with electrostatic embedding, is essential in modeling systems such as metalloenzymes, reactive covalent inhibitors, or transition-state mimetics, where electron redistribution significantly influences binding or activity, and precise representation of the electronic

environment is crucial for identifying pharmacophoric elements [62].

Virtual Screening Based on Pharmacophores

Virtual screening based on pharmacophores is a highly efficient and widely used method in early-stage drug discovery for identifying novel bioactive compounds from large chemical libraries. Once a validated pharmacophore model is generated either from known active ligands (ligand-based) or from a target's structural information (structure-based) it serves as a 3D query to scan databases of small molecules [63]. Each compound is assessed for its ability to map onto the defined pharmacophoric features using conformational flexibility and spatial arrangement matching algorithms. Only those molecules that fulfill the spatial and chemical constraints of the pharmacophore are retrieved as potential hits. This technique allows for the rapid and cost-effective filtering of millions of compounds to prioritize those most likely to exhibit the desired biological activity [64]. Advanced software tools such as LigandScout, Discovery Studio, Pharmit, ZINCPharmer, and MOE support high-throughput pharmacophore-based virtual screening, often incorporating scoring functions to rank hits based on geometric fit, feature alignment, and energy terms. This method is especially valuable for identifying scaffold-hopping candidates, novel chemotypes, and non-obvious bioisosteres that may not emerge from conventional similarity searches. By focusing on key interaction features rather than full chemical structure, pharmacophore-based virtual screening enables broader chemical diversity and increases the chances of discovering unique, potent lead compounds [65].

Figure 3 demonstrates the workflow of virtual screening based on pharmacophore modeling, a technique used to identify potential drug candidates from a compound library. It begins with a library of curcumin derivatives, which are structurally diverse compounds. A known active compound, Axitinib, is used to generate a pharmacophore query model by identifying essential chemical features required for biological activity, such as hydrogen bond

donors, acceptors, aromatic rings, and hydrophobic regions. This pharmacophore model is then used to perform pharmacophore-

based screening, during which the compound library is filtered to identify molecules that match the essential features.




Figure 3: Virtual screening based on pharmacophore

Validation and Optimization

Validation and optimization are critical steps in pharmacophore modeling to ensure the reliability and predictive performance of the generated model before it is applied to virtual screening. Validation typically involves assessing the model's capability to discriminate between known active and inactive compounds using statistical metrics such as sensitivity, specificity, enrichment factor (EF), and receiver operating characteristic (ROC) curves [66]. A well-validated pharmacophore should correctly identify a high percentage of actives while minimizing false positives. Common validation approaches include test set validation, where the model is applied to a curated set of known actives and decoys, and cross-validation, which involves building and testing multiple models based on different ligand subsets. Following validation, optimization may be necessary to improve model performance. This can involve refining the spatial arrangement and tolerance of pharmacophoric features, adjusting feature weights, or incorporating excluded volumes to account for steric hindrance within the binding pocket [67]. In structure-based models, optimization may also include reanalyzing the protein-ligand interactions or integrating additional structural data. Some tools such as LigandScout, MOE, and PharmaGist offer built-in workflows for both validation and

optimization. Rigorous validation and careful refinement enhance the model's ability to retrieve novel and biologically relevant compounds, making pharmacophore screening a powerful tool for hit identification and lead generation in drug discovery pipelines [68].

ADMET Prediction and Optimization

In Silico Prediction (ADME and Toxicity)

In silico ADMET prediction is a crucial component of modern drug design, aiming to assess and optimize the pharmacokinetic and safety profiles of drug candidates early in the development pipeline. ADMET properties such as absorption, distribution, metabolism, excretion, and toxicity determine a compound's *in vivo* performance and are major contributors to late-stage drug attrition [69]. Computational tools use quantitative structure-activity relationship (QSAR) models, machine learning algorithms, and rule-based filters (*e.g.*, Lipinski's Rule of Five) to predict ADMET characteristics based on molecular structure. Absorption predictions focus on some factors such as intestinal permeability, solubility, and P-glycoprotein interactions, while distribution models estimate the volume of distribution, plasma protein binding, and blood-brain barrier penetration. Metabolism is analyzed using models that simulate cytochrome P450

(CYP450) interactions, enzyme inhibition/induction potential, and metabolic stability [70]. Excretion predictions include renal clearance and biliary elimination, while toxicity models assess risks such as hepatotoxicity, cardiotoxicity (*e.g.*, hERG inhibition), mutagenicity, and carcinogenicity. Tools such as SwissADME, admetSAR, pkCSM, Derek Nexus, and TOPKAT are commonly used to perform these predictions. Integrating

ADMET screening early in the drug discovery process helps prioritize compounds with favorable safety and pharmacokinetic profiles, reduces experimental costs, and improves the likelihood of clinical success. Moreover, the iterative ADMET optimization—guided by predictive modeling—can inform structural modifications to enhance drug-likeness without compromising efficacy [71].

Table 3: *In silico* ADMET profiling tools for structure-based drug design

ADMET Parameter	<i>In Silico</i> Prediction Methods	Key Tools and Software	Relevance to SBDD	Ref.
Absorption	Lipinski's Rule of Five, Caco-2 permeability models, and logP/logD	SwissADME, ADMETlab, pkCSM, and QikProp	Helps pre-filter compounds with poor oral bioavailability	[72]
Distribution	Volume of distribution (Vd), plasma protein binding (PPB), and BBB models	pkCSM, ADMET Predictor, PreADMET	Predicts tissue penetration and CNS availability	[73]
Metabolism	CYP450 interaction prediction, metabolic site identification	SMARTCyp, MetaSite, FAME 3, and ADMETlab	Avoids metabolic liabilities and drug-drug interactions	[74]
Excretion	Renal clearance, total clearance, and half-life ($t_{1/2}$) estimation	pkCSM and ADMETlab	Ensures appropriate dosing and elimination profile	[75]
Toxicity	hERG inhibition, mutagenicity (Ames test), hepatotoxicity	ProTox-II, VEGA QSAR, Toxtree, ADMET Predictor	Filters out toxic hits early in drug development	[76]

Integration with SBDD Workflow

The integration of ADMET prediction and other computational methodologies into the Structure-Based Drug Design (SBDD) workflow enhances the efficiency, accuracy, and translational success of drug discovery efforts. SBDD typically begins with identifying and modeling a biologically relevant target, followed by structure analysis, ligand design, and molecular docking. At each stage, *in silico* ADMET prediction tools can be employed to filter out compounds with poor pharmacokinetic or toxicity profiles, thereby minimizing the risk of late-stage failure [77]. After initial docking and binding affinity assessments, top-ranking hits undergo ADMET profiling, which helps prioritize compounds not only based on efficacy, but also on their drug-likeness and safety. Additionally, molecular

dynamics simulations and QM/MM calculations can refine binding poses and explore reaction mechanisms, while parallel pharmacophore modeling can assist in the identification of novel scaffolds [78]. This iterative process enables medicinal chemists to perform structure-guided optimizations that enhance both binding affinity and ADMET characteristics. Moreover, contemporary workflows often integrate machine learning models to predict multi-parameter optimization (MPO) outcomes, aligning potency, selectivity, and developability within a unified decision-making framework. By seamlessly combining target structural information, binding energetics, and predictive pharmacokinetics/toxicology, SBDD workflows become increasingly data-driven and rational, accelerating the transition from hit to lead and

ultimately to preclinical candidates with improved success rates [79].

Artificial Intelligence and Machine Learning in SBDD

9.1. Deep Learning Models for Drug Discovery

Deep learning, a subfield of machine learning, has emerged as a transformative tool in structure-based drug design (SBDD), enabling the automatic extraction of complex, nonlinear relationships from large and multidimensional datasets. Deep learning models, such as convolutional neural networks (CNNs), recurrent neural networks (RNNs), graph neural networks (GNNs), and transformer architectures, are increasingly applied to predict molecular properties, protein-ligand interactions, binding affinities, and ADMET profiles with high accuracy [80]. In drug discovery, these models are trained on vast datasets comprising molecular structures, bioactivity data, and protein-ligand complexes

to learn underlying patterns that conventional methods may overlook. For example, CNNs are used to process 3D voxelized representations of protein binding pockets and ligand structures to predict docking scores, while GNNs treat molecules as graphs, effectively capturing atomic connectivity and molecular topology for tasks such as property prediction and de novo drug design. Platforms such as DeepChem, AtomNet, MolBERT, and AlphaFold showcase how deep learning can accelerate hit identification, optimize binding poses, and improve protein structure prediction [81]. These models not only reduce the time and cost associated with traditional experimental screening, but also enhance predictive power and scalability across diverse chemical and biological spaces. As data availability continues to grow, the integration of deep learning into SBDD workflows holds great promise for discovering novel therapeutics with improved efficacy, selectivity, and safety profiles as shown in Table 4 [82].

Table 4: Overview of artificial intelligence models and databases in structure-based drug design

Model / Dataset	Type	Application	Key Features	Example Use Cases	Ref.
DeepChem	ML Framework / Toolkit	General-purpose drug discovery platform	Provides tools for molecular featurization, ML pipelines	Toxicity prediction, QSAR modeling, and virtual screening	[83]
MoleculeNet	Benchmark Dataset	Evaluating ML models on chemical data	Standardized datasets for molecular properties	Solubility, toxicity, and binding affinity	[84]
AlphaFold2	Deep Learning Model	Protein structure prediction	Predicts 3D structures with high accuracy from sequence	Structure-based docking, binding site prediction	[85]
D-MPNN (Chemprop)	Graph Neural Network	Molecular property prediction	Directed Message Passing Neural Network	ADMET prediction, bioactivity scoring	[86]
MolBERT	Transformer Model	Molecular representation learning	Pretrained on SMILES using NLP-style techniques	Molecular generation, activity prediction	[87]
AtomNet	3D CNN	Structure-based virtual screening	Uses 3D protein-ligand structures to	Hit identification in kinase	[88]

predict binding inhibitors

Integration with Molecular Docking and QSAR

Artificial intelligence (AI) and machine learning (ML) are increasingly being integrated with traditional computational techniques such as molecular docking and quantitative structure–activity relationship (QSAR) modeling to enhance the precision and efficiency of structure-based drug design (SBDD) [89]. In molecular docking, ML algorithms are employed to improve scoring functions, predict binding affinities, and prioritize ligand poses with greater accuracy by learning from large datasets of known protein-ligand complexes. This approach addresses the limitations of classical scoring functions that often fail to fully capture complex intermolecular interactions. Simultaneously, ML models enhance QSAR analyses by identifying non-linear and higher-order relationships between chemical descriptors and biological activity, that conventional regression models might miss [90]. Techniques such as random forests, support vector machines (SVMs), and deep neural networks (DNNs) are commonly used to construct robust, predictive QSAR models for virtual screening and lead optimization. Furthermore, hybrid frameworks are being developed in which AI models guide docking-based screening by filtering libraries for drug-likeness and ADMET properties, while docking results feed back into ML pipelines for iterative refinement. This synergy enables more accurate hit identification, reduces false positives, and allows for data-driven molecular optimization, making AI-driven docking-QSAR integration a powerful strategy for accelerating drug discovery and enhancing predictive reliability in SBDD [90].

Challenges and Future Directions

Despite their transformative role in modern drug discovery, current computational methods

in structure-based drug design (SBDD) face several critical limitations that constrain their predictive accuracy and translational reliability. One major challenge is the static nature of protein structures used in molecular docking, which often fail to capture the dynamic conformational changes that occur during ligand binding. Although molecular dynamics (MD) simulations provide dynamic insights, they are computationally intensive and sensitive to force field limitations. Additionally, scoring functions used in docking often oversimplify intermolecular interactions, leading to false positives or inaccurate binding affinity predictions. In virtual screening, the quality and chemical diversity of compound libraries, as well as the completeness of protein structural data, significantly influence outcomes. Pharmacophore models and QSAR techniques may suffer from data bias, overfitting, and limited applicability domains if not validated rigorously. Even with the advent of AI and machine learning, the interpretability and generalizability of many models remain problematic due to the “black-box” nature of deep learning algorithms and the dependence on large, high-quality annotated datasets. Moreover, computational predictions often lack experimental correlation, necessitating time-consuming and costly *in vitro* or *in vivo* validation. These limitations underscore the need for improved algorithms, enhanced integration with experimental workflows, and more interpretable, physiologically relevant computational frameworks in the future. Next-generation technologies such as artificial intelligence (AI) and quantum computing are poised to revolutionize structure-based drug design (SBDD), providing unprecedented opportunities to overcome the limitations of traditional computational methods. AI, particularly through deep learning, enables the rapid identification of novel drug candidates by learning complex molecular patterns, predicting protein-ligand interactions, and optimizing ADMET profiles with high accuracy. Some tools such as AlphaFold2 have already

demonstrated the power of AI in protein structure prediction, while graph-based neural networks and transformer models are enabling more nuanced molecular generation and property prediction. Meanwhile, quantum computing promises to transform molecular simulations by solving quantum mechanical equations exponentially faster than classical computers. This could enable highly accurate ab initio calculations, electronic structure predictions, and reaction pathway modeling, even for large biomolecular systems. Hybrid quantum/classical algorithms such as the Variational Quantum Eigensolver (VQE) are being explored to compute binding affinities and energy landscapes with unprecedented precision.

Conclusion

The exploration of computational chemistry techniques for structural elucidation underscores their pivotal role in modern chemical and pharmaceutical research. By integrating rigorous quantum mechanical frameworks with scalable molecular mechanics models, researchers can simulate, predict, and refine molecular structures with remarkable accuracy. These methodologies, when paired with dynamic simulations and machine learning algorithms, not only accelerate drug discovery, but also provide deep insights into reactivity, conformational flexibility, and biomolecular interactions. The synergistic use of QM/MM hybrids, solvation models, and AI-driven potentials enables researchers to model complex biological systems more realistically. This convergence of computational efficiency and molecular precision represents a paradigm shift in how structural data is interpreted and utilized. Ultimately, the continued refinement and integration of these tools will expand the frontier of molecular design, fostering innovation across medicinal chemistry, materials science, and chemical informatics.

Acknowledgments

The author would like to acknowledge the e-library of Rungta College of Pharmaceutical Sciences and Research, Kohka, Kurud Road,

Bhilai, Chhattisgarh, India, for providing the necessary literature to compile this work. The author also would also like to acknowledge DST-FIST Project Level-0 (SR/FST/College-2018-431-C) for providing financial assistance.

ORCID

Mohit Joshi

<https://orcid.org/0009-0004-1968-5019>

Irfan Pathan

<https://orcid.org/0009-0004-5269-6633>

Adarsh Sahu

<https://orcid.org/0009-0001-0356-0738>

Arif Raza

<https://orcid.org/0009-0001-9586-7525>

Yamini Sahu

<https://orcid.org/0009-0004-5440-9546>

Nousheen Khatoon*

<https://orcid.org/0009-0003-7378-2859>

Reference

- [1] Batool, M., Ahmad, B., Choi, S. [A structure-based drug discovery paradigm](#). *International Journal of Molecular Sciences*, **2019**, 20(11), 2783.
- [2] Singh, N., Vayer, P., Tanwar, S., Poyet, J.L., Tsaïoun, K., Villoutreix, B.O. [Drug discovery and development: introduction to the general public and patient groups](#). *Frontiers in Drug Discovery*, **2023**, 3, 1201419.
- [3] Serrano, D.R., Luciano, F.C., Anaya, B.J., Ongoren, B., Kara, A., Molina, G., Tomietto, G. [Artificial intelligence \(AI\) applications in drug discovery and drug delivery: Revolutionizing personalized medicine](#). *Pharmaceutics*, **2024**, 16(10), 1328.
- [4] Bajad, N.G., Rayala, S., Gutti, G., Sharma, A., Singh, M., Kumar, A., Singh, S.K. [Systematic review on role of structure based drug design \(SBDD\) in the identification of anti-viral leads against SARS-Cov-2](#). *Current Research in Pharmacology and Drug Discovery*, **2021**, 2, 100026.
- [5] Ferreira, L.G., Dos Santos, R.N., Oliva, G., Andricopulo, A.D. [Molecular docking and structure-based drug design strategies](#). *Molecules*, **2015**, 20(7), 13384-13421.
- [6] Palermo, G., De Vivo, M. [Computational chemistry for drug discovery](#). In *Encyclopedia of Nanotechnology*, **2015**, 1-15.
- [7] Giordano, D., Biancaniello, C., Argenio, M.A., Facchiano, A. [Drug design by pharmacophore and virtual screening approach](#). *Pharmaceutics*, **2022**, 15(5), 646.

- [8] Tunuhe, A., Zheng, Z., Rao, X., Yu, H., Ma, F., Zhou, Y., Xie, S. [Protein-based materials: Applications, modification and molecular design](#). *BioDesign Research*, **2025**, 7(1), 100004.
- [9] Nam, K., Wolf-Watz, M. [Protein dynamics: The future is bright and complicated!](#) *Structural Dynamics*, **2023**, 10(1),
- [10] Sharma, V., Wakode, S., Kumar, H. [Structure- and ligand-based drug design: Concepts, approaches, and challenges](#). *Chemoinformatics and Bioinformatics in the Pharmaceutical Sciences*, **2021**, 27-53.
- [11] Fukunishi, Y., Nakamura, H. [Prediction of ligand-binding sites of proteins by molecular docking calculation for a random ligand library](#). *Protein Science*, **2011**, 20(1), 95-106.
- [12] Rathore, I., Mishra, V., Bhaumik, P. [Advancements in macromolecular crystallography: From past to present](#). *Emerging Topics in Life Sciences*, **2021**, 5(1), 127-149.
- [13] Shukla, V.K., Heller, G.T., Hansen, D.F. [Biomolecular NMR spectroscopy in the era of artificial intelligence](#). *Structure*, **2023**, 31(11), 1360-1374.
- [14] Son, A., Kim, W., Park, J., Lee, W., Lee, Y., Choi, S., Kim, H. [Utilizing molecular dynamics simulations, machine learning, Cryo-EM, and NMR spectroscopy to predict and validate protein dynamics](#). *International Journal of Molecular sciences*, **2024**, 25(17), 9725.
- [15] García-Nafría, J., Tate, C.G. [Structure determination of GPCRs: cryo-EM compared with X-ray crystallography](#). *Biochemical Society Transactions*, **2021**, 49(5), 2345-2355.
- [16] Śledź, P., Caflisch, A. [Protein structure-based drug design: from docking to molecular dynamics](#). *Current Opinion in Structural Biology*, **2018**, 48, 93-102.
- [17] Maltarollo, V.G. [Computer-Aided and Machine Learning-Driven Drug Design](#). Springer, 2025.
- [18] Eng, E.T., Valdez, N.R. [Applications of visualization technology in the structural sciences](#). *Structural Dynamics*, **2025**, 12(3).
- [19] Kibbey, C., Calvet, A. [Molecular Property eXplorer: a novel approach to visualizing SAR using tree-maps and heatmaps](#). *Journal of Chemical Information and Modeling*, **2005**, 45(2), 523-532.
- [20] Agu, P.C., Afiukwa, C.A., Orji, O., Ezech, E., Ofoke, I., Ogbu, C., Aja, P. [Molecular docking as a tool for the discovery of molecular targets of nutraceuticals in diseases management](#). *Scientific Reports*, **2023**, 13(1), 13398.
- [21] Pagadala, N.S., Syed, K., Tuszynski, J. [Software for molecular docking: a review](#). *Biophysical Reviews*, **2017**, 9(2), 91-102.
- [22] Novič, M., Tibaut, T., Anderluh, M., Borišek, J., Tomašič, T. [The comparison of docking search algorithms and scoring functions: an overview and case studies](#). In *Pharmaceutical Sciences: Breakthroughs in Research and Practice*, **2017**, 820-849.
- [23] Yang, C., Chen, E.A., Zhang, Y. [Protein-ligand docking in the machine-learning era](#). *Molecules*, **2022**, 27(14), 4568.
- [24] Sarkar, A., Concilio, S., Sessa, L., Marrafini, F., Piotto, S. [Advancements and novel approaches in modified AutoDock Vina algorithms for enhanced molecular docking](#). *Results in Chemistry*, **2024**, 7, 101319.
- [25] Sarkar, A., Concilio, S., Sessa, L., Marrafini, F., Piotto, S. [Advancements and novel approaches in modified AutoDock Vina algorithms for enhanced molecular docking](#). *Results in Chemistry*, **2024**, 7, 101319.
- [26] Pissurlenkar, R.R., Shaikh, M.S., Iyer, R.P., Coutinho, E.C. [Molecular mechanics force fields and their applications in drug design](#). *Anti-Infective Agents in Medicinal Chemistry*, **2009**, 8(2), 128-150.
- [27] Oliveira, T.A.D., Silva, M.P.D., Maia, E.H.B., Silva, A.M.D., Taranto, A.G. [Virtual screening algorithms in drug discovery: a review focused on machine and deep learning methods](#). *Drugs and Drug Candidates*, **2023**, 2(2), 311-334.
- [28] Pinzi, L., Rastelli, G. [Molecular docking: shifting paradigms in drug discovery](#). *International Journal of Molecular Sciences*, **2019**, 20(18), 4331.
- [29] Salo-Ahen, O.M., Alanko, I., Bhadane, R., Bonvin, A.M., Honorato, R.V., Hossain, S., Larsen, A.S. [Molecular dynamics simulations in drug discovery and pharmaceutical development](#). *Processes*, **2020**, 9(1), 71.
- [30] Zhou, Y., Jiang, Y., Chen, S.J. [RNA-ligand molecular docking: Advances and challenges](#). *Wiley Interdisciplinary Reviews: Computational Molecular Science*, **2022**, 12(3), e1571.
- [31] Huang, S.Y., Zou, X. [Scoring and lessons learned with the CSAR benchmark using an improved iterative knowledge-based scoring function](#). *Journal of Chemical Information and Modeling*, **2011**, 51(9), 2097-2106.
- [32] Grewal, S., Deswal, G., Grewal, A.S. [Molecular dynamics simulations: Insights into protein and protein ligand interactions](#). In *Advances in Pharmacology*, **2025**, 103, 139-162.
- [33] Lyubartsev, A.P., Rabinovich, A.L. [Force field development for lipid membrane simulations](#). *Biochimica et Biophysica Acta (BBA)-Biomembranes*, **2016**, 1858(10), 2483-2497.
- [34] De Vivo, M., Masetti, M., Bottegoni, G., Cavalli, A. [Role of molecular dynamics and related methods in drug discovery](#). *Journal of Medicinal Chemistry*, **2016**, 59(9), 4035-4061.

- [35] Chakravorty, A., Hussain, A., Cervantes, L.F., Lai, T.T., Brooks III, C.L. Exploring the limits of the generalized CHARMM and AMBER force fields through predictions of hydration free energy of small molecules. *Journal of Chemical Information and Modeling*, **2024**, 64(10), 4089-4101.
- [36] Ormeño, F., General, I.J. Convergence and equilibrium in molecular dynamics simulations. *Communications Chemistry*, **2024**, 7(1), 26.
- [37] Hollingsworth, S.A., Dror, R.O. Molecular dynamics simulation for all. *Neuron*, **2018**, 99(6), 1129-1143.
- [38] Tiwary, P., Parrinello, M. From metadynamics to dynamics. *Physical Review Letters*, **2013**, 111(23), 230602.
- [39] Bhattarai, A., Miao, Y. Gaussian accelerated molecular dynamics for elucidation of drug pathways. *Expert opinion on Drug Discovery*, **2018**, 13(11), 1055-1065.
- [40] Ainsley, J., Lodola, A., Mulholland, A.J., Christov, C.Z., Karabancheva-Christova, T.G. Combined quantum mechanics and molecular mechanics studies of enzymatic reaction mechanisms. *Advances in Protein Chemistry and Structural Biology*, **2018**, 113(1-32).
- [41] Craig, B., Skylaris, C.K., Schoetz, T., de León, C.P. A computational chemistry approach to modelling conducting polymers in ionic liquids for next generation batteries. *Energy Reports*, **2020**, 6, 198-208.
- [42] Friesner, R.A. Combined quantum and molecular mechanics (QM/MM). *Drug Discovery Today: Technologies*, **2004**, 1(3), 253-260.
- [43] Suh, D., Arattu Thodika, A.R., Kim, S., Nam, K., Im, W. CHARMM-GUI QM/MM interfacier for a quantum mechanical and molecular mechanical (QM/MM) simulation setup: 1. Semiempirical methods. *Journal of Chemical Theory and Computation*, **2024**, 20(12), 5337-5351.
- [44] Senn, H.M., Thiel, W. QM/MM methods for biomolecular systems. *Angewandte Chemie International Edition*, **2009**, 48(7), 1198-1229.
- [45] Tzeliou, C.E., Mermigki, M.A., Tzeli, D. Review on the QM/MM methodologies and their application to metalloproteins. *Molecules*, **2022**, 27(9), 2660.
- [46] Hu, H., Yang, W. Development and application of ab initio QM/MM methods for mechanistic simulation of reactions in solution and in enzymes. *Journal of Molecular Structure: Theochem*, **2009**, 898(1-3), 17-30.
- [47] Lawson Daku, L.V.M., Aquilante, F., Robinson, T.W., Hauser, A. Accurate spin-state energetics of transition metal complexes. 1. CCSD (T), CASPT2, and DFT study of [M (NCH) 6] 2+ (M= Fe, Co). *Journal of Chemical Theory and Computation*, **2012**, 8(11), 4216-4231.
- [48] Yilmazer, N.D., Korth, M. Enhanced semiempirical QM methods for biomolecular interactions. *Computational and Structural Biotechnology Journal*, **2015**, 13(169-175).
- [49] Castro, C.B., Ferreira, M.P., Netto, C.G.M. Metalloenzyme mechanisms correlated to their turnover number and metal lability. *Current Research in Chemical Biology*, **2021**, 1,100004.
- [50] Castro, C.B., Ferreira, M.P., Netto, C.G.M. Metalloenzyme mechanisms correlated to their turnover number and metal lability. *Current Research in Chemical Biology*, **2021**, 1, 100004.
- [51] Marti, S. QMCube (QM3): An all-purpose suite for multiscale QM/MM calculations. *Journal of Computational Chemistry*, **2021**, 42(6), 447-457.
- [52] Salo-Ahen, O.M., Alanko, I., Bhadane, R., Bonvin, A.M., Honorato, R.V., Hossain, S., Larsen, A.S. Molecular dynamics simulations in drug discovery and pharmaceutical development. *Processes*, **2020**, 9(1), 71.
- [53] Götz, A.W., Clark, M.A., Walker, R.C. An extensible interface for QM/MM molecular dynamics simulations with AMBER. *Journal of Computational Chemistry*, **2014**, 35(2), 95-108.
- [54] Cruzeiro, V.W.D., Manathunga, M., Merz Jr, K.M., Gotz, A.W. Open-source multi-GPU-accelerated QM/MM simulations with AMBER and QUICK. *Journal of Chemical Information and Modeling*, **2021**, 61(5), 2109-2115.
- [55] Cavasotto, C.N. Binding free energy calculation using quantum mechanics aimed for drug lead optimization. *Quantum Mechanics in Drug Discovery*, **2020**, 257-268.
- [56] Li, D., Wang, Y., Han, K. Recent density functional theory model calculations of drug metabolism by cytochrome P450. *Coordination Chemistry Reviews*, **2012**, 256(11-12), 1137-1150.
- [57] Souaille, M., Roux, B. Extension to the weighted histogram analysis method: combining umbrella sampling with free energy calculations. *Computer Physics Communications*, **2001**, 135(1), 40-57.
- [58] Wolber, G., Seidel, T., Bendix, F., Langer, T. Molecule-pharmacophore superpositioning and pattern matching in computational drug design. *Drug Discovery Today*, **2008**, 13(1-2), 23-29.
- [59] Seidel, T., Wieder, O., Garon, A., Langer, T. Applications of the pharmacophore concept in natural product inspired drug design. *Molecular Informatics*, **2020**, 39(11), 2000059.
- [60] Vuorinen, A., Schuster, D. Methods for generating and applying pharmacophore models as virtual screening filters and for bioactivity profiling. *Methods*, **2015**, 71, 113-134.
- [61] Ginex, T., Vázquez, J., Estarellas, C., Luque, F.J. Quantum mechanical-based strategies in drug

- discovery: Finding the pace to new challenges in drug design. *Current Opinion in Structural Biology*, **2024**, 87, 102870.
- [62] Kar, R.K. Benefits of hybrid QM/MM over traditional classical mechanics in pharmaceutical systems. *Drug Discovery Today*, **2023**, 28(1), 103374.
- [63] Dror, O., Schneidman-Duhovny, D., Inbar, Y., Nussinov, R., Wolfson, H.J. Novel approach for efficient pharmacophore-based virtual screening: method and applications. *Journal of Chemical Information and Modeling*, **2009**, 49(10), 2333-2343.
- [64] Ruiz-Moreno, A.J., Cedillo-Gonzalez, R., Cordova-Bahena, L., An, Z., Medina-Franco, J.L., Velasco-Velazquez, M.A. Consensus pharmacophore strategy for identifying novel SARS-Cov-2 Mpro inhibitors from large chemical libraries. *Journal of Chemical Information and modeling*, **2024**, 64(6), 1984-1995.
- [65] Molla, M.H.R., Aljahdali, M.O., Sumon, M.A.A., Asseri, A.H., Altayb, H.N., Islam, M.S., Ahammad, F. Integrative ligand-based pharmacophore modeling, virtual screening, and molecular docking simulation approaches identified potential lead compounds against pancreatic cancer by targeting FAK1. *Pharmaceuticals*, **2023**, 16(1), 120.
- [66] Kohlbacher, S.M., Schmid, M., Seidel, T., Langer, T. Applications of the novel quantitative pharmacophore activity relationship method QPhAR in virtual screening and lead-optimisation. *Pharmaceuticals*, **2022**, 15(9), 1122.
- [67] Mathai, N., Chen, Y., Kirchmair, J. Validation strategies for target prediction methods. *Briefings In Bioinformatics*, **2020**, 21(3), 791-802.
- [68] Muhammed, M.T., Aki-yalcin, E. Pharmacophore modeling in drug discovery: methodology and current status. *Journal of the Turkish Chemical Society Section A: Chemistry*, **2021**, 8(3), 749-762.
- [69] Suvidhi, S. Kumar, Sumanshu, R. K. Vaid. In silico admet predictions: enhancing drug development through qsar modeling. *Futuristic Trends in Agriculture Engineering & Food Sciences*, **2024**, 3, 41-52.
- [70] Pires, D.E., Blundell, T.L., Ascher, D.B. pkCSM: predicting small-molecule pharmacokinetic and toxicity properties using graph-based signatures. *Journal of Medicinal Chemistry*, **2015**, 58(9), 4066-4072.
- [71] Ye, L., Ngan, D.K., Xu, T., Liu, Z., Zhao, J., Sakamuru, S., Simeonov, A. Prediction of drug-induced liver injury and cardiotoxicity using chemical structure and in vitro assay data. *Toxicology and Applied Pharmacology*, **2022**, 454, 116250.
- [72] Hörmann, L., Stark, W.G., Maurer, R.J. Machine learning and data-driven methods in computational surface and interface science. *npj Computational Materials*, **2025**, 11(1), 196.
- [73] Lombardo, F., Obach, R.S., Shalaeva, M.Y., Gao, F. Prediction of volume of distribution values in humans for neutral and basic drugs using physicochemical measurements and plasma protein binding data. *Journal of Medicinal Chemistry*, **2002**, 45(13), 2867-2876.
- [74] Ogu, C.C., Maxa, J.L. Drug interactions due to cytochrome P450. In *Baylor University Medical Center Proceedings*, **2000**, 13, 421-423.
- [75] Dulsat, J., López-Nieto, B., Estrada-Tejedor, R., Borrell, J.I. Evaluation of free online ADMET tools for academic or small biotech environments. *Molecules*, **2023**, 28(2), 776.
- [76] Bhat, V., Chatterjee, J. The use of in silico tools for the toxicity prediction of potential inhibitors of SARS-CoV-2. *Alternatives to Laboratory Animals*, **2021**, 49(1-2), 22-32.
- [77] Niazi, S.K., Mariam, Z. Computer-aided drug design and drug discovery: a prospective analysis. *Pharmaceuticals*, **2023**, 17(1), 22.
- [78] Bultum, L.E., Tolossa, G.B., Kim, G., Kwon, O., Lee, D. In silico activity and ADMET profiling of phytochemicals from Ethiopian indigenous aloes using pharmacophore models. *Scientific Reports*, **2022**, 12(1), 22221.
- [79] D Segall, M. Multi-parameter optimization: identifying high quality compounds with a balance of properties. *Current Pharmaceutical Design*, **2012**, 18(9), 1292-1310.
- [80] Segall, M. Advances in multiparameter optimization methods for de novo drug design. *Expert Opinion on Drug Discovery*, **2014**, 9(7), 803-817.
- [81] Rezaei, M.A., Li, Y., Wu, D., Li, X., Li, C. Deep learning in drug design: protein-ligand binding affinity prediction. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, **2020**, 19(1), 407-417.
- [82] Vijayan, R., Kihlberg, J., Cross, J.B., Poongavanam, V. Enhancing preclinical drug discovery with artificial intelligence. *Drug Discovery Today*, **2022**, 27(4), 967-984.
- [83] Korshunova, M., Ginsburg, B., Tropsha, A., Isayev, O. OpenChem: a deep learning toolkit for computational chemistry and drug design. *Journal of Chemical Information and Modeling*, **2021**, 61(1), 7-13.
- [84] Wu, Z., Ramsundar, B., Feinberg, E.N., Gomes, J., Geniesse, C., Pappu, A.S., Pande, V. MoleculeNet: a benchmark for molecular machine learning. *Chemical Science*, **2018**, 9(2), 513-530.

- [85] Borkakoti, N., Thornton, J.M. [AlphaFold2 protein structure prediction: Implications for drug discovery](#). *Current Opinion in Structural Biology*, **2023**, 78, 102526.
- [86] Heid, E., Greenman, K.P., Chung, Y., Li, S.-C., Graff, D.E., Vermeire, F.H., McGill, C.J. [Chemprop: a machine learning package for chemical property prediction](#). *Journal of Chemical Information and Modeling*, **2023**, 64(1), 9-17.
- [87] Mswahili, M.E., Jeong, Y.S. [Transformer-based models for chemical SMILES representation: A comprehensive literature review](#). *Heliyon*, **2024**, 10(20).
- [88] Ocana, A., Pandiella, A., Privat, C., Bravo, I., Luengo-Oroz, M., Amir, E., Gyorffy, B. [Integrating artificial intelligence in drug discovery and early drug development: a transformative approach](#). *Biomarker Research*, **2025**, 13(1), 45.
- [89] Torres, P.H., Sodero, A.C., Jofily, P., Silva-Jr, F.P. [Key topics in molecular docking for drug design](#). *International Journal of Molecular sciences*, **2019**, 20(18), 4574.
- [90] Gawehn, E., Hiss, J.A., Schneider, G. [Deep learning in drug discovery](#). *Molecular Informatics*, **2016**, 35(1), 3-14.

Graphical Abstract

