

Troubleshooting Failed Webhook Deliveries

Doc ID: HC-102 | Source type: help_center_article | Title: Troubleshooting Failed Webhook Deliveries | Last updated: 2026-07-15 | Version: v3.6

Webhooks let external systems receive real-time updates from CloudDesk. This article covers the most common delivery problems and how to fix them.

How webhook delivery works

When an event occurs, CloudDesk sends an HTTPS POST to your configured endpoint. If your endpoint doesn't respond with a 2xx status within 10 seconds, CloudDesk retries on a backoff schedule: 1 minute, 5 minutes, 30 minutes, 2 hours, then 12 hours — six attempts total.

If more than 20 consecutive events fail, the webhook is automatically disabled and must be manually re-enabled from the Webhooks dashboard.

Common problems and fixes

1. Webhooks arriving late or not at all

Usually means your endpoint is timing out or returning errors. Acknowledge the webhook immediately with a 200 response, then process the payload asynchronously rather than doing slow work inline.

2. Signature verification always fails

The most common cause is verifying against a re-serialized JSON object instead of the raw request body — even whitespace or key-order differences will break the HMAC comparison. Always verify against the raw bytes received.

3. Webhook got automatically disabled

This happens after 20+ consecutive failures, commonly due to an expired TLS certificate on your endpoint. Renew your certificate, then re-enable the webhook and use the event replay endpoint to recover any missed events.

4. Firewall blocking deliveries

If your security team allowlists inbound IPs, make sure CloudDesk's current sending ranges (available via the API) are included.

5. Bulk payloads look truncated

Payloads over 512 KB (e.g., bulk ticket updates) are split across multiple deliveries with a page field. Make sure your handler reassembles paginated payloads.

Related: [API Documentation — Webhooks Reference](#). [Engineering Runbook — Webhook Delivery Failure Response](#).