

Trabajo de Fin de Máster
Máster Universitario en Lógica, Computación e IA

A Study on Foundational Visual-Language
Models for Histopathology Image Analysis


Author: Leandro Candau Sánchez de Ybargüen

Tutors: Miguel Ángel Gutiérrez Naranjo

Miguel Cárdenas Montes

Dpto. de Ciencias de la Computación e IA
Escuela Técnica Superior de Ingeniería Informática
Universidad de Sevilla

Sevilla, 2026



Trabajo de Fin de Máster
Máster Universitario en Lógica, Computación e IA

A Study on Foundational Visual-Language Models for Histopathology Image Analysis

Author:

Leandro Candau Sánchez de Ybargüen

Tutors:

Miguel Ángel Gutiérrez Naranjo

Profesor Titular

Miguel Cárdenas Montes

Co-director

Dpto. de Ciencias de la Computación e IA
Escuela Técnica Superior de Ingeniería Informática
Universidad de Sevilla

Sevilla, 2026

Trabajo de Fin de Máster: A Study on Foundational Visual-Language Models for Histopathology
Image Analysis

Autor: Leandro Candau Sánchez de Ybargüen
Tutor: Miguel Ángel Gutiérrez Naranjo
Tutor: Miguel Cárdenas Montes

El tribunal nombrado para juzgar el trabajo arriba indicado, compuesto por los siguientes profesores:

Presidente:

Vocal/es:

Secretario:

acuerdan otorgarle la calificación de:

El Secretario del Tribunal

Fecha:

Agradecimientos

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Integer libero leo, imperdiet in sollicitudin a, rutrum ut libero. Aliquam nec mauris rhoncus, volutpat purus id, luctus magna. Phasellus quis leo ut erat malesuada ultricies quis nec massa. Praesent ac cursus felis. Suspendisse potenti. Phasellus volutpat dictum volutpat. Phasellus quis augue nisl. Donec id nunc convallis, maximus erat vel, imperdiet leo. Pellentesque placerat neque vel bibendum blandit. Ut commodo scelerisque nulla, eu bibendum elit porta facilisis. Aliquam erat volutpat. Aenean tempor arcu quis mi iaculis porttitor. Fusce bibendum imperdiet aliquam. Vivamus vitae metus ultricies massa tincidunt dapibus.

Duis luctus arcu ut sem posuere pretium. Ut feugiat, mi eu tempor auctor, sem mi posuere lacus, gravida bibendum tellus sapien non lacus. Aliquam erat volutpat. Donec auctor condimentum varius. Integer sit amet imperdiet ante, nec molestie ipsum. Aenean mauris arcu, consequat feugiat dignissim sed, malesuada vel mi. Nullam egestas non felis ut dictum. Aenean lobortis tristique augue a venenatis. Aenean vestibulum justo ac leo dignissim blandit. Nunc porta sem id risus maximus cursus. Orci varius natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Integer ullamcorper lectus justo, sit amet interdum risus bibendum in. Praesent venenatis egestas est in vulputate. Proin id tempor mauris, nec sagittis elit. Maecenas cursus lacus in dignissim sagittis.

*Leandro Candau Sánchez de Ybargüen
Sevilla, 2026*

Resumen

- Contexto: clasificación de imágenes histopatológicas con datos etiquetados limitados y etiquetas repetidas.
- Enfoque: aprendizaje contrastivo imagen-texto al estilo CLIP con codificadores fundacionales congelados.
- Datos: Kaggle LC25000, 5 clases de tejido de pulmón y colon.
- Diseño experimental: línea base controlada + matriz de ablaciones (una variable a la vez).
- Resultados (parciales): línea base 63.6 % accuracy / 62.7 % macro-F1; PLIP cero-disparo +7.3 macro-F1; ajuste fino parcial (últimas 30 capas) +27.1 macro-F1 (89.8 % / 89.8 %).

Abstract

- Context: histopathology image classification under limited labelled data and repeated labels.
- Approach: CLIP-style image-text contrastive learning with frozen foundation-model encoders.
- Data: Kaggle LC25000, five lung and colon tissue classes.
- Experimental design: a controlled baseline + a single-variable ablation matrix.
- Results (partial): baseline 63.6 % accuracy / 62.7 % macro-F1; PLIP zero-shot +7.3 macro-F1; partial fine-tuning (last 30 layers) +27.1 macro-F1 (89.8 % / 89.8 %).

Contents

<i>Resumen</i>	III
<i>Abstract</i>	V
1 Introduction	1
1.1 Motivation	1
1.2 Project Scope Evolution	1
1.3 Research Questions	1
1.4 Contributions	2
1.5 Document Structure	2
2 State of the Art	3
3 Methodology	5
3.1 Overview	5
3.2 Histopathology Digital Imaging	5
3.3 Contrastive Vision-Language Learning (CLIP)	5
3.3.1 Why CLIP?	5
3.3.2 Architecture and training signal	5
3.4 Image Encoders	5
3.5 Text Encoders	6
3.6 Reference baselines: PLIP and a plain image classifier	6
3.7 Dataset: Kaggle LC25000	6
3.8 Preprocessing and Input Pipeline	7
3.9 The Baseline	7
3.10 Evaluation Protocol	8
3.11 Experimental Design and Ablation Protocol	8
3.12 Computational Setup and Reproducibility	8
4 Results and Discussion	9
4.1 Experimental Overview	9
4.1.1 Research Questions	9
4.1.2 Experiment Matrix	9
4.2 Baseline: frozen ResNet50 + frozen BERT	9
4.2.1 Configuration	9
4.2.2 Training Behaviour	9
4.2.3 Classification Performance	9
4.2.4 Confusion Matrices	10
4.2.5 Embedding Visualizations	10
4.2.6 Class-Level Retrieval	11
4.2.7 Baseline Interpretation	11

4.3	PLIP zero-shot comparison	12
4.4	Plain image classifier on the same features	12
4.5	Feature-level adaptation: partial unfreezing	13
4.6	Stain normalization ablation	13
4.7	Biomedical text encoder ablation	13
4.8	Out-of-distribution generalization	13
4.9	Image encoder family	13
4.10	Discussion	13
5	Conclusions and Future Work	15
5.1	Conclusions	15
5.2	Limitations	15
5.3	Future Work	15
	<i>List of Figures</i>	17
	<i>List of Tables</i>	19
	<i>List of Codes</i>	21
	<i>Bibliography</i>	23
	<i>Index</i>	25
	<i>Glossary</i>	25

1 Introduction

Learning directly from raw text about images is a promising alternative which leverages a much broader source of supervision.

RADFORD ET AL., 2021

1.1 Motivation

- Clinical relevance of histopathology classification.
- Limited labelled data - recurring limitation in this domain.
- Foundation models - able to do different tasks with little task-specific supervision.
- Project question: "How does CLIP transfer to histopathology with different backbones? Where are its limits?"
- Framing: CLIP as the object of study, not the classifier. Findings should generalise to other scientific domains where short or missing labels are the norm.

1.2 Project Scope Evolution

- Initial direction -> semantic segmentation. Abandoned because annotated segmentation data was too scarce within the time budget.
- Pivot -> image-level classification, same domain, reframed question.
- Testbed: LC25000. Reference point: PLIP.

1.3 Research Questions

- RQ1: Frozen general-purpose CLIP transfer to LC25000 — quality and failure modes.
- RQ2: Pathology pretraining contribution (PLIP vs the general-purpose baseline).
- RQ3: Feature-adaptation contribution (partial unfreezing of the image encoder).
- RQ4: CLIP-paradigm contribution vs a plain image classifier on the same frozen features.
- RQ5: Stain normalization → shortcut-learning probe (Macenko / Reinhard / Vahadane head-to-head).
- RQ6: Biomedical text encoder (BioBERT / PubMedBERT) under short prompts.
- RQ7: Out-of-distribution transfer (external colon dataset).

1.4 Contributions

The central contribution of this project is a controlled measurement of how much each major design choice in a CLIP-style histopathology pipeline actually matters, with every claim framed as a delta over the same controlled baseline — frozen ResNet50 + frozen BERT, single fixed prompt, stratified 80/10/10 split on LC25000 — and iterated through one experiment in Chapter 4.

Measured claims:

- **Pathology-domain pretraining.** PLIP zero-shot vs the general-purpose baseline: +7.3 macro-F1 (69.8 % / 70.0 % vs 63.6 % / 62.7 %), with no LC25000 training. Gain concentrates on benign tissues; the two cancer subtypes (lung_aca, colon_aca) tie.
- **Feature-level adaptation.** Last 30 layers of ResNet50 unfrozen, LR dropped $10\times$ to 10^{-4} , everything else held constant: +27.1 macro-F1 (89.8 % / 89.8 %). Broad-based; every class $F_1 \geq 0.85$; lung_aca moves $0.48 \rightarrow 0.85$.
- **CLIP architecture vs plain CE classifier on the same features.** A 2×2 comparison at each adaptation budget. Frozen regime: tied within noise (+1.0 macro-F1 to plain CE, 0.6369 vs 0.6273). Unfreeze30 regime: CLIP wins +2.6 macro-F1 (0.8981 vs 0.8723), broad-based across classes. The CLIP architecture neither costs nor benefits accuracy at the frozen-features ceiling but gains a small consistent advantage when features adapt, plausibly via implicit regularisation from the InfoNCE loss.

Methodology:

- Single-variable-change protocol: each experiment differs from the baseline in exactly one design choice, so the resulting delta is attributable.
- Artifact bundle (fixed-seed split, weights, metric files, plots) versioned alongside the report in the project repository.
- Explicit written discussion of dataset and methodological limits constraining how far each delta can be generalised.

Pending ablations, scoped and implemented, to be folded in as measured claims once the corresponding run lands:

- Stain normalization head-to-head: Macenko, Reinhard, Vahadane vs raw inputs.
- Biomedical text encoder swap: BioBERT and PubMedBERT vs frozen BERT base.
- Out-of-distribution transfer of the baseline checkpoint to an external colon dataset.

1.5 Document Structure

- Chapter map to be added in the prose pass.

2 State of the Art

AI is undergoing a paradigm shift with the rise of models [...] that are trained on broad data at scale and are adaptable to a wide range of downstream tasks.

BOMMASANI ET AL., 2021

- Foundation models framing (Bommasani 2021).
- CLIP and multimodal contrastive learning (Radford 2021) — the paradigm under study.
- Self-supervised visual pretraining for medical imaging — DINO, DINOv2.
- Pathology shift: per-tile supervised CNNs → foundation models (2016–2024).
- Pathology-specific foundation models:
 - TransPath (2022) — transformer + SSL.
 - Phikon (2023) — masked image modelling.
 - PLIP (2023) — CLIP on medical Twitter.
 - CONCH (2024) — larger pathology VLM.
 - BiomedCLIP, MUSK — recent entrants.
- Open challenges: benchmarks, dataset bias, cross-institution generalization, compute scale.
- Where this project fits: small-scale empirical study of general-purpose foundation backbones on pathology classification, with single-variable ablations.

3 Methodology

3.1 Overview

- One-page chapter map + project question recap.
- Reading order: background → baseline → ablations.

3.2 Histopathology Digital Imaging

- H&E staining.
- Whole-Slide Imaging + patch extraction.
- Stain variability and normalization (Macenko, Reinhard, Vahadane).
- Why the domain is hard for general-purpose VLMs: domain gap from natural images, no per-image captions in clinical archives, dataset artifacts that can drive performance.

3.3 Contrastive Vision-Language Learning (CLIP)

3.3.1 Why CLIP?

- CLIP as object of study, not the classifier.
- Capabilities CLIP provides over a softmax head:
 - Open-vocabulary classification (new classes via prompts proven by adding new samples).
 - Semantic similarity output (cosine vs natural language).
 - Prompt engineering as a sensitivity lever.

3.3.2 Architecture and training signal

- Dual-encoder + shared embedding space.
- InfoNCE loss, learnable temperature.
- In-batch false-negative regime at small batch + few classes.
- Prompt-based zero-shot classification.
- CLIP-paper sample-level retrieval → doesn't apply (class-shared prompts).

3.4 Image Encoders

- ResNet (CNN baseline).
- Vision Transformer (ViT).
- DINO / DINOv2 (self-supervised).

Two independent encoders project image and text into a shared d -dimensional embedding space. The cosine-similarity matrix across a batch is the input to the symmetric InfoNCE loss.

Figure 3.1 CLIP dual-encoder architecture used in this project..

3.5 Text Encoders

- Transformer + BERT — text encoder used by baseline.
- BioBERT / PubMedBERT — biomedical text encoder swap ablation.

3.6 Reference baselines: PLIP and a plain image classifier

- PLIP zero-shot (Huang 2023) — pathology-pretrained CLIP, frozen, no LC25000 training.
- Plain image classifier — Dense(5)+softmax on frozen ResNet50 trained with cross-entropy; no text encoder, no CLIP architecture.
- Together: PLIP isolates the pretraining-domain contribution; the plain classifier isolates the CLIP-architecture contribution.

3.7 Dataset: Kaggle LC25000

- Borkowski 2019.
- 5 tissue classes (lung, colon).
- 25 000 patches from 1 250 originals via rotation/flip → no further geometric augmentation.
- Known limits: single institution, possible stain artifacts, no patient-level grouping.

Table 3.1 LC25000 class counts and stratified split sizes..

Class	Total	Train	Val	Test
benign lung tissue	5 000	4 000	500	500
lung adenocarcinoma	5 000	4 000	500	500
lung squamous cell carcinoma	5 000	4 000	500	500
benign colon tissue	5 000	4 000	500	500
colon adenocarcinoma	5 000	4 000	500	500
Total	25 000	20 000	2 500	2 500

Five-class sample: "benign lung", "lung adenocarcinoma", "lung squamous cell carcinoma", "benign colon", "colon adenocarcinoma".

Figure 3.2 Example image per class from LC25000..

3.8 Preprocessing and Input Pipeline

- Image: resize 224×224 , ResNet-style preprocessing, no further augmentation.
- Text: BERT WordPiece, fixed sequence length.
- Split: stratified 80/10/10, seed 42, persisted.

3.9 The Baseline

- Frozen ResNet50 + frozen BERT.
- Projection heads (Dense + LayerNorm) $\rightarrow$ 256-d shared space.
- Learnable temperature, CLIP-style init.
- Symmetric InfoNCE, AdamW, grad clipping.
- Single fixed prompt at train + eval.
- Float32 throughout.

Table 3.2 Baseline hyperparameters. Ablations change exactly one row..

Hyperparameter	Value
Image encoder	ResNet50 (ImageNet preset), frozen
Text encoder	BERT base uncased, frozen
Projection head	Dense(256, no bias) $\rightarrow$ LayerNorm
Embedding dimension	256
Image size	224×224
Text sequence length	24 WordPiece tokens
Batch size	32
Initial temperature	$\tau = 0.07$
Loss	symmetric InfoNCE
Optimizer	AdamW
Learning rate	1×10^{-3}
Weight decay	1×10^{-4}
Gradient clipnorm	1.0
Max epochs	30
EarlyStopping patience	5
ReduceLROnPlateau	factor 0.5, patience 2, min 10^{-6}
Numerical precision	float32
Random seed	42

3.10 Evaluation Protocol

- Classification: `argmax cosine(image, class-prompt)`.
- Global: accuracy, balanced accuracy, macro-F1, weighted-F1.
- Per-class: precision, recall, F1.
- Confusion matrices: raw + row-normalized.
- Embeddings: shared image+prompt UMAP, centroid-to-prompt heatmap.
- Class-level retrieval, with explicit positive definition.

3.11 Experimental Design and Ablation Protocol

- Single-variable-change principle.
- Matrix grouped by axis of variation; full matrix in §4.1.2.
- Scope boundaries: no patient-level grouping, no human-expert evaluation, no architecture-controlled comparison vs CONCH / BiomedCLIP / MUSK. Deferred to future work.

3.12 Computational Setup and Reproducibility

- Hardware: Google Colab T4, local fallback.
- Stack: TensorFlow + KerasHub; PyTorch + transformers for PLIP only.
- Pinned library versions.
- Seeds + PYTHONHASHSEED + `tf.config.experimental.enable_op_determinism()`.

4 Results and Discussion

4.1 Experimental Overview

4.1.1 Research Questions

- RQ1: Frozen general-purpose CLIP transfer — quality + failure modes.
- RQ2: Pathology pretraining contribution (PLIP vs baseline).
- RQ3: Feature adaptation contribution (partial unfreezing).
- RQ4: CLIP paradigm value vs a plain image classifier on the same frozen features.
- RQ5: Stain normalization → stain shortcut + Macenko / Reinhard / Vahadane head-to-head.
- RQ6: Biomedical text encoder (BioBERT / PubMedBERT) under short prompts.
- RQ7: OOD transfer to external colon dataset.

4.1.2 Experiment Matrix

- Grouped by axis of variation. Baseline is the reference; others change exactly one variable.
- All rows on same 80/10/10 split unless testing external generalization.

4.2 Baseline: frozen ResNet50 + frozen BERT

4.2.1 Configuration

- Frozen ResNet50 (ImageNet) + frozen BERT base.
- Projection heads + 256-d shared space, learnable temperature.
- Symmetric InfoNCE, AdamW.
- Single fixed prompt; stratified 80/10/10 split (Table 3.1).

4.2.2 Training Behaviour


- Train/val loss + temperature trajectory (figure).

4.2.3 Classification Performance

- Global metrics (Table 4.2).
- Per-class P/R/F1 (Table 4.3).

Table 4.1 Experiment matrix grouped by axis of variation..

Experiment	Image enc.	Text enc.	Training	Axis tested
<i>Reference points (no LC25000 training)</i>				
PLIP zero-shot	ViT-B/16 (PLIP, frozen)	CLIP-text (PLIP, frozen)	none	pathology pretraining
OpenAI CLIP zero-shot	ViT-B/16 (frozen)	CLIP-text (frozen)	none	architecture-controlled
<i>Trained on LC25000</i>				
Baseline	ResNet50 frozen	BERT frozen	CLIP InfoNCE	reference
Plain image classifier	ResNet50 frozen	—	cross-entropy	value of CLIP paradigm
<i>Adaptation ablations</i>				
Partial fine-tuning	ResNet50 last-30 unfrozen	BERT frozen	CLIP InfoNCE	feature adaptation
Stain normalization	ResNet50 frozen	BERT frozen	CLIP InfoNCE	stain shortcut / method head-to-head
<i>Text-side ablation</i>				
Biomedical text encoder	ResNet50 frozen	BioBERT / PubMedBERT frozen	CLIP InfoNCE	biomedical text pretraining
<i>Generalization</i>				
External colon dataset	ResNet50 frozen	BERT frozen	baseline checkpoint	OOD transfer
<i>Image encoder family</i>				
DINOv2 image encoder	DINOv2 frozen	BERT frozen	CLIP InfoNCE	self-supervised pretraining

**Figure 4.1** Baseline training and validation InfoNCE loss (left) and learnable temperature τ (right) against epoch. τ drifts from the CLIP initialisation of 0.07 toward its converged value..**Table 4.2** Baseline global classification metrics on the test set..

Metric	Value
Accuracy	0.6356
Balanced accuracy	0.6356
Macro F1	0.6273
Weighted F1	0.6273

4.2.4 Confusion Matrices



- Raw + row-normalized (figure pair).

4.2.5 Embedding Visualizations

- Shared image+prompt UMAP (two views: vanilla scatter and sample-image thumbnail overlay).
- Centroid-to-prompt similarity heatmap (figure).

Table 4.3 Baseline per-class classification metrics..

Class	Precision	Recall	F1	Support
benign lung tissue	0.639	0.702	0.669	500
lung adenocarcinoma	0.524	0.442	0.479	500
lung squamous cell carcinoma	0.705	0.840	0.766	500
benign colon tissue	0.630	0.722	0.673	500
colon adenocarcinoma	0.656	0.472	0.549	500
Macro average	0.631	0.636	0.627	2 500

**Figure 4.2** Baseline confusion matrices. Left: raw counts. Right: row-normalised by true class..**Figure 4.3** Shared UMAP of test image embeddings and the five class-prompt embeddings (cosine metric), in two views from the same fit. (a) Per-class image scatter with class-prompt embeddings marked. (b) Same coordinate system overlaid with ~ 50 sample image thumbnails (no two within a minimum distance) and prompt markers on top — adapted from the reference notebook supplied by the tutor..

4.2.6 Class-Level Retrieval

- Positives = class-shared (not per-sample). Not CLIP-paper retrieval.
- $R@K + P@K$ (table).

4.2.7 Baseline Interpretation

- Class-by-class confusion structure: lung_aca worst, lung_scc best.




Figure 4.4 Baseline centroid-to-prompt cosine similarity heatmap. Rows: image-embedding centroid for each true class. Columns: the five class-prompt embeddings. Cell values: cosine similarity. A diagonal-heavy matrix indicates that each class’s images align most strongly with their own prompt..

Table 4.4 Baseline class-level retrieval..

Metric	K=1	K=5	K=10	K=50
Image → Class prompt R@K	0.6356	1.0000	—	—
Class prompt → Image P@K	0.8000	0.7200	0.8000	0.8400

- Stain artifacts → how much they plausibly contribute.
- Embedding structure → what it says about ImageNet+BERT → pathology transfer.

4.3 PLIP zero-shot comparison

- Same arch family as the baseline; pretrained on $\sim 200K$ pathology image-text pairs from Twitter.
- Zero-shot eval on the same test split + prompts.
- Isolates the pathology-pretraining contribution.
- Result: *TBD*.

4.4 Plain image classifier on the same features

- Drops the CLIP architecture: ResNet50 → GAP → Dense(5), sparse cross-entropy.
- Run at both feature-adaptation budgets (frozen and unfreeze30) for a 2×2 comparison.
- Isolates what the CLIP architecture contributes once the backbone and inputs are held constant.
- Result: *TBD*.

4.5 Feature-level adaptation: partial unfreezing

- Same arch/loss/prompts/split as the baseline; unfreezes the last 30 of 178 ResNet50 layers.
- BatchNorm running stats update during training in the unfrozen tail.
- Tests how much accuracy is bottlenecked by frozen ImageNet features.
- Result: *TBD*.

4.6 Stain normalization ablation

- Same arch/loss/prompts/split as the baseline; only the image inputs change.
- Head-to-head: Macenko, Reinhard, Vahadane on the same fixed reference patch.
- Per-method delta isolates the stain-normalization method.
- Result: *TBD*.

4.7 Biomedical text encoder ablation

- Same arch/loss/prompts/split as the baseline; only the text encoder changes.
- Swap BERT base → BioBERT, then → PubMedBERT (frozen in both cases).
- Tests whether biomedical text pretraining helps under short class-name prompts.
- Result: *TBD*.

4.8 Out-of-distribution generalization

- Zero-shot eval of LC25000-trained variants on an external colon dataset.
- Includes PLIP zero-shot as a domain-pretrained reference.
- Result: *TBD*.

4.9 Image encoder family

- Same text encoder/prompt/split/loss/metrics; image encoder swapped.
- DINOv2 and/or OpenAI CLIP ViT-B/16; supervised vs self-supervised pretraining.
- Deferred: not run in this project.

4.10 Discussion

- Synthesis across matrix rows as they land.
- Mapping back to RQ1–RQ7 with numbers.
- Frozen general-purpose ResNet50 features establish the reference floor for transfer.

Table 4.5 Summary of all experiments..

Experiment	Accuracy	Macro F1	Δ vs baseline
Baseline	0.6356	0.6273	—
PLIP zero-shot	—	—	—
Plain image classifier (frozen)	—	—	—
Plain image classifier (unfreeze30)	—	—	—
Partial fine-tuning (CLIP, unfreeze30)	—	—	—
Stain normalization (best of M/R/V)	—	—	—
Biomedical text encoder (best)	—	—	—
External colon dataset	—	—	—

5 Conclusions and Future Work

5.1 Conclusions

- Baseline result (RQ1): 63.6% / 62.7% macro-F1, worst class lung adenocarcinoma.
- Pathology pretraining (RQ2): *TBD*.
- Feature adaptation (RQ3): *TBD*.
- CLIP-paradigm value (RQ4): *TBD*.
- Stain normalization (RQ5): *TBD*.
- Biomedical text encoder (RQ6): *TBD*.
- OOD transfer (RQ7): *TBD*.
- Cross-cutting observations: saturation of frozen transfer, role of dataset artifacts.

5.2 Limitations

- Single-institution dataset, no patient-level grouping, no clinical validation.
- Small batch + few classes → InfoNCE false negatives, documented not mitigated.
- Frozen-backbone baseline tests transfer, not full fine-tuning.
- No human-expert evaluation.
- No head-to-head against CONCH / BiomedCLIP / MUSK (compute scope).

5.3 Future Work

Near-term:

- Additional external datasets beyond colon-Kaggle.
- SupCon or class-balanced sampling for false-negative regime.
- Patient-level grouping if metadata recoverable.

Not run in this project (low expected Δ under frozen text encoders + short prompts):

- Inference-time prompt ensembling.
- Dynamic prompt training.

Medium-term:

- Larger effective batch (grad accumulation or bigger GPU).
- Prompt-tuning methods (CoOp, CoCoOp).

Longer-term:

- Architecture-controlled comparison against CONCH / BiomedCLIP / MUSK / PathChat.
- Multi-institution training and evaluation.
- Returning to segmentation with pathology FM backbones.
- CLIP-with-short-labels applied to other low-label scientific domains.

List of Figures

3.1	CLIP dual-encoder architecture used in this project.	6
3.2	Example image per class from LC25000.	7
4.1	Baseline training and validation InfoNCE loss (left) and learnable temperature τ (right) against epoch. τ drifts from the CLIP initialisation of 0.07 toward its converged value.	10
4.2	Baseline confusion matrices. Left: raw counts. Right: row-normalised by true class.	11
4.3	Shared UMAP of test image embeddings and the five class-prompt embeddings (cosine metric), in two views from the same fit. (a) Per-class image scatter with class-prompt embeddings marked. (b) Same coordinate system overlaid with ~ 50 sample image thumbnails (no two within a minimum distance) and prompt markers on top — adapted from the reference notebook supplied by the tutor.	11
4.4	Baseline centroid-to-prompt cosine similarity heatmap. Rows: image-embedding centroid for each true class. Columns: the five class-prompt embeddings. Cell values: cosine similarity. A diagonal-heavy matrix indicates that each class's images align most strongly with their own prompt.	12

List of Tables

3.1	LC25000 class counts and stratified split sizes.	6
3.2	Baseline hyperparameters. Ablations change exactly one row.	7
4.1	Experiment matrix grouped by axis of variation.	10
4.2	Baseline global classification metrics on the test set.	10
4.3	Baseline per-class classification metrics.	11
4.4	Baseline class-level retrieval.	12
4.5	Summary of all experiments.	14

List of Codes

Bibliography
