

API Mensajeros Urbanos BFF (1.0.0)

Download OpenAPI specification: [Download](#)

E-mail: soporte-it@mensajerosurbanos.com | License: [Apache 2.0](#)

This is implements all service do you need to create a Service

Authentication

Authentication services.

Delivery

Endpoints for delivery services.

Calculates the total cost of a service

This endpoint calculates de total cost of a service based on the information provided

REQUEST BODY SCHEMA: application/json
required

The data should always use **type_service=4** to indicate the delivery service type

access_token required	number <string> access_token
type_service required	number
roundtrip required	number <int> (Roundtrip) Enum: ☐ 0 ☐ 1

Sort order:

- - One way
- - Roundtrip. (After delivering the products, the courier must return to the store again, either to deliver cash or a POS.)

declared_value
required

number <int>

Value of the products.

city
required

number <int> (City)

Enum:

Sort order:

- - bogota
- - cali
- - medellin
- - barranquilla
- - cartagena
- - sta_marta
- - bucaramanga
- - ibague
- - armenia
- - pereira
- - manizales
- - Monterrey
- - neiva
- - ciudad mexico
- - valledupar
- - Guadalajara
- - Santiago de Querétaro
- - Heroica Puebla de Zaragoza

if dane_code is not specified, city field is required

parking_surcharge
required

number <int>

Surcharge for parking

coordinates >
required

Array of objects (CalculateServiceCoordinate)

Responses

> 200

Returns the total cost of the service (The total value is returned in the field total_service and total kilometers in the total_distance field among other values

> 400 If there is an error consuming the service.

> 403 If Token acces is not valid

POST /api/calculate

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ0b2t1biI6ImRmOGQ3ZGMwNDQzYjgxeZl",
  "type_service": 4,
  "roundtrip": 0,
  "declared_value": 1250,
  "city": 1,
  "parking_surcharge": 2000,
  - "coordinates": [
    + { ... },
    + { ... }
  ]
}
```

Response samples

200**400****403****Content type**

application/json

Copy

Expand all

Collapse all

```
{
  "version": "v1",
  "status": "success",
  "status_code": 200,
  "message": "OK",
  "href": "https://dev.api.mensajerosurbanos.com/calculate",
}
```

```

- "data": {
  "base_value": 4700,
  "distance_surcharge": 5200,
  "surcharge_stops": 0,
  "insurance_surcharge": 6.25,
  "roundtrip_surcharge": 0,
  "declared_value": 1250,
  "total_service": 11906.25,
  "total_distance": 15,
  "total_surcharge": 5200,
  "stops": 0,
  "add_distancia": 13,
  "surcharge_KM": "400",
  "roundtrip": 0,
  "discounted_value": 0,
  "total_service_sd": 11906.25,
  "code_status": 0,
  "other_values": 0,
  "surcharge_time": 0,
  "night_surcharge": 0,
  "parking_surcharge": 2000,
+ "adress_data": [ ... ],
  "iva": 0
}
})

```

Creates a store

Creates a store with the given information

REQUEST BODY SCHEMA: application/json
required

access_token required	number <int> Access_token
--------------------------	------------------------------

id_point required	string Point id.
----------------------	---------------------

name
required

string
Point name.

address
required

string
Point address.

city
required

number <int> (City)
Enum: ☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 8 ☐ 9 ☐ 10
Sort order:

- ☐ 1 - bogota
- ☐ 2 - cali
- ☐ 3 - medellin
- ☐ 4 - barranquilla
- ☐ 8 - cartagena
- ☐ 9 - sta_marta
- ☐ 10 - bucaramanga
- ☐ 11 - ibague
- ☐ 29 - armenia
- ☐ 30 - pereira
- ☐ 31 - manizales
- ☐ 41 - Monterrey
- ☐ 42 - neiva
- ☐ 50 - ciudad mexico
- ☐ 55 - valledupar
- ☐ 57 - Guadalajara
- ☐ 63 - Santiago de Querétaro
- ☐ 64 - Heroica Puebla de Zaragoza

if dane_code is not specified, city field is required

phone

string
Contact phone number.

schedule

string
An informative string with the store hours.

parking

number <int>

Value of the parking given to the courier when a delivery needs to be picked up.

address_complement string <string>
refers to the address complement.

Responses

> **200** If the store was created successfully.

> **400** If an error is found during the store creation of the service.

POST /api/Add-store

Request samples

Payload

Content type

application/json

Copy

```
{
  "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ0b2t1biI6ImRmOGQ3ZGMwNDQzYjgxZl",
  "id_point": "1point",
  "name": "Rincon Del Chico",
  "address": "Cra 7 # 20-20",
  "city": 1,
  "phone": "3101111111",
  "schedule": "L-V de 8:00AM - 07:00PM",
  "parking": 1000,
  "address_complement": "apto 302, edificio Velencia&estrada"
```

Response samples

200**400**

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "version": "v1",
  "status": "success",
  "status_code": 200,
  "message": "success",
  "href": "https://dev.api.mensajerosurbanos.com/Add-store",
  - "data": {
    "id": "8466"
  }
}
```

Create a delivery service.

This endpoint creates a delivery service.

REQUEST BODY SCHEMA: application/json
required

The data should always use **type_service=4** to indicate the delivery service type (it is necessary to create a store before creating a service, since a store id is required to create a service).

access_token
required

string <int>

access_token provided by MU

type_service
required

number <int> (ServiceType)

Enum: 1 2 3 4 5 6 7 8

Sort order:

- 1 - Mensajería.

- - Domicilios.
- - E-Commerce.
- - Recaudos.
- - TAT.

roundtrip
required

number <int> (Roundtrip)

Enum:

Sort order:

- - One way
- - Roundtrip. (After delivering the products, the courier must return to the store again, either to deliver cash or a POS.)

declared_value
required

number <int>

Value of the products.

dane_code

number

Dane code of city, if you send this value city field is not required

city
required

number <int> (City)

Enum:

Sort order:

- - bogota
- - cali
- - medellin
- - barranquilla
- - cartagena
- - sta_marta
- - bucaramanga
- - ibague
- - armenia
- - pereira
- - manizales
- - Monterrey
- - neiva
- - ciudad mexico

- **55** - valledupar
- **57** - Guadalajara
- **63** - Santiago de Querétaro
- **64** - Heroica Puebla de Zaragoza

if dane_code is not specified, city field is required

start_date
required

string

Date of the service in the YYYY-MM-DD format

start_time
required

string

Hour of the service in the HH:MM:SS format

observation
required

string

General description of the service.

description
required

string

Delivery Details.

os
required

string

Versión of the API. It should always be "NEW API 2.0"

coordinates >
required

Array of objects (CreateServiceCoordinate)

Responses

> **200** Service created successfully.

> **400** If an error is found during the creation of the service.

POST /api/create

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all

```
{
  "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ0b2t1biI6ImY1Y2VlM2QzOGJmOWYzNT",
  "type_service": 4,
  "roundtrip": 0,
  "declared_value": 1250,
  "dane_code": 11001,
  "city": 1,
  "start_date": "2017-04-18",
  "start_time": "15:59:00",
  "observation": "Servicio XXXX para WWW",
  "description": "Servicio XXXX para WWW",
  "os": "NEW API 2.0",
  - "coordinates": [
    + { ... }
  ]
}
```

Response samples

200**400**

Content type

application/json

Copy Expand all Collapse all

```
{
  "version": "v1",
  "status": "success",
  "status_code": 200,
  "message": "success",
  "href": "https://dev.api.mensajerosurbanos.com/Create-services",
}
```

```
- "data": {  
  "task_id": 23178306,  
  "uuid": "611fc74f6b0a9",  
  "status": 2,  
  "total": 4106.25,  
  "date": "2021-08-20 10:16:31",  
  "distance": 1,  
  "error": 0  
}
```

Tracking

Endpoints for tracking a service.

Get the information of a service.

Shows the detailed information of a service

REQUEST BODY SCHEMA: application/json
required

access_token string
required

Access_token.

uuid string
required

UUID of the service.

Responses

> **200** Returns the information of the service.

> **400** If the request was not successful.

POST /api/track

Request samples

Payload

Content type

application/json

Copy

```
{  
  "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ0b2t1biI6IjE0ODQ1YjVhMWM4MmWY2Nm",  
  "uuid": "56ce313b3235d"  
}
```

Response samples

200

400

Content type

application/json

Copy

Expand all

Collapse all

```
{  
  "version": "v1",  
  "status": "success",  
  "status_code": 200,  
  "message": "OK",  
  "href": "http://dev.api.mensajerosurbanos.com/task",  
}
```

```
- "data": {  
  "task_id": 28852,  
  "type_task_id": 4,  
  "type_task": "Domicilios",  
  "date_start": "2016-02-25",  
  "time_start": "16:00:00",  
  "date_created": "2016-02-24",  
  "total_value": 4,  
  "city_id": 1,  
  "city": "bogota",  
  "status_payout_id": 3,  
  "status_payout": "Pospago",  
  "uuid": "56ce313b3235d",  
  "status_id": 3,  
  "status": "Asignado",  
+ "address": [ ... ],  
+ "resource": [ ... ],  
+ "history": [ ... ],  
  "base_value": 1000,  
  "invoice": true  
}  
})
```

Endpoint getting evidences for a service.

Shows the evidences of the service

REQUEST BODY SCHEMA: application/json

required

access_token string
required

Access_token.

uuid string
required

UUID of the service.

Responses

> **200** Returns the information of the service.

> **400** If the request was not successful.

POST /api/evidences

Request samples

Payload

Content type

application/json

Copy

```
{
  "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ0b2t1biI6IjYjVhMWM4MMWY2Nm",
  "uuid": "56ce313b3235d"
```

Response samples

200

400

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "version": "v1",
  "status": "success",
  "status_code": 200,
  "message": "Listado de evidencias",
  "href": "https://dev.api.mensajerosurbanos.com/task/{uuid}/evidences",
```

```
- "data": [  
  + { ... }  
]  
)
```

Webhook

MU will notify status changes to this webhook, in this case an endpoint of your system, you can add your endpoint with /api/webhook service.

track a service (callback)

Shows the detailed information of a service

REQUEST BODY SCHEMA: application/json
optional

token	string If your endpoint requires token or x-api-key you can send in the configuration at support email
id_company	number <int> company id provided by MU
type	string Description
date	string <date>
order_id	string <string> tracking or (invoice) number assigned by you for your service
details >	object

Responses

> **200** Returns the information of the service.

> **400** If the request was not successful.

POST /your-endpoint

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all



```
"token": "61267ab9403b4aeiof",  
"id_company": 123456,  
"type": null,  
"date": "2020-06-23 16:27:27",  
"order_id": "RB00235",
```

```
- "details": {
  "uuid": "61267ab9403b4",
  "status": "in_progress",
  "status_id": 4,
  "num_place": 1,
  "status_place": 1,
  "url": "http://dev.front.mensajerosurbanos.com/track-service-external#?uuid=5ef272d2",
  "mensajero": "Juan Robledo",
  "phone": "+573114682419",
  "vehicle_plate": "23j34",
  "photo_url": "https:\\\\devmuadmin.s3.us-west-2.amazonaws.com\\\\images\\\\recursos\\",
  "ETA": 345,
  "order_id": "RB00235",
  "finish_status": 1,
  "finish_type": "finalizado sin problema",
  "finish_description": "se realiza la entrega al cliente final y se toman evidencias"
}
```

Response samples

200**400**

Content type

application/json

Copy



Crea un webhook para recibir notificaciones.

Este endpoint permite registrar un webhook para recibir callbacks de eventos.



REQUEST BODY SCHEMA: application/json

required

access_token required	string Token de acceso JWT.
token_id	string or null ID del token (opcional).
endpoint required	string URL del endpoint donde se enviarán los callbacks.
token_endpoint required	string Tipo de endpoint (por ejemplo, 'php').

Responses

> **201** Webhook creado exitosamente.

— **400** Solicitud inválida.

— **401** No autorizado.

— **500** Error interno del servidor.

POST /api/webhook

Request samples

Payload

Content type
application/json



"access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",

Copy

```
"token_id": null,  
"endpoint": "http://localhost/test/prueba.php",  
"token_endpoint": "php"
```



Response samples

201**Content type**

application/json

Copy



```
"empresas_id": 146562,  
"token_id": "aaa",  
"endpoint": "http://localhost/test/prueba.php",  
"token_endpoint": "php",  
"access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ0b2t1biI6IjE0ODQ1YjVhMWM4MWMY2N."
```



Cancel

Cancels a service

Shows the detailed information of a service

REQUEST BODY SCHEMA: application/json
optional

access_token

string <string>

task_uuid
required

string
uuid of the service

cancellation_type
required

number <int> (CancelType)

Enum: 1 2 3 4

Sort order:

- 1 - No hay mensajero asignado.
- 2 - Error al crear servicio.
- 3 - Cliente final cancela.
- 4 - Otros.

description
required

string
Description

Responses

> **200** Returns the information of the service.

> **400** If the request was not successful.

POST /api/cancel

Request samples

Payload

Content type

application/json

Copy



```
"access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ0b2t1biI6ImF1Nzg3MzcwNTdiZDNjYz"
```

```
"task_uuid": "61267ab9403b4",  
"cancellation_type": 4,  
"description": "demo"
```

```
}
```

Re

200

400

Content type

application/json

Copy

```
{
```

```
"version": "1.0.0",  
"status": "error 400",  
"status_code": 200,  
"message": "Servicio 60b906ebeca25 cancelado de forma exitosa",  
"href": "http://dev.api.mensajerosurbanos.com/calcel-task-uuid"
```

```
}
```