



INCIDENT REPORT

Issued on: 2026-05-14 21:27 (-04:00)

Toolmark Comparison Report – Rear Service Door (Back Door Forced-Entry Damage)

CONFIDENTIAL • LAW ENFORCEMENT SENSITIVE

RESPONDING UNIT Unit: _____ Badge: _____	REPORT DETAILS Report No.: _____ Date: 05-14-2026 21:27	CASE REFERENCE Case: _____ Classification: CONFIDENTIAL
--	---	---

CASE SYNOPSIS

Requesting unit: Eugene Police Department (EPD)

CLASSIFICATION DETAILS

Case Type	Cold Case Investigation
Priority Level	☐ Low ☐ Medium ☒ High ☐ Critical
Status	ACTIVE INVESTIGATION ☒ Active ☐ Under Review ☐ Closed
Lead Unit	Major Crimes Division

INCIDENT DETAILS

Incident Date	mai 14, 2026
Incident Time	09:27 p.m. -04:00
Location	[Location from case data]
Reporting Party	[Officer Name] - Badge #[#####]

SUBJECT INFORMATION

Name	[REDACTED]
Age	[##]
Sex/Race	[M/F] / [Race]
Last Known Address	[REDACTED]

INITIAL RESPONSE

First Responder: Officer [NAME], Badge #[#####]
Arrived: 09:27 p.m. -04:00
Scene Secured: 09:42 p.m. -04:00



INCIDENT REPORT

Issued on: 2026-05-14 21:27 (-04:00)

Toolmark Comparison Report – Rear Service Door (Back Door Forced-Entry Damage)

CONFIDENTIAL • LAW ENFORCEMENT SENSITIVE

Toolmark Comparison Report – Rear Service Door (Back Door Forced-Entry Damage)

Administrative Information

Case: case_rookie_demo2 ("The Diner Break-In")

Location: Eugene, Oregon

Incident date/time: 2026-05-11 03:18 (Pacific)

Case opened: 2026-05-11 09:05 (Pacific)

Requesting unit: Eugene Police Department (EPD)

Item examined: asset.back_door_forced_entry (photograph set)

Chain of Custody

The questioned evidence consisted of scene photographs depicting the rear service door latch/strike area and adjacent frame, labeled in the case file as "Back Door Forced-Entry Damage" (asset.back_door_forced_entry). The image set was associated with the reported forced-entry event at 2026-05-11 03:18.

Digital copies were received by the laboratory through the case management system after case opening (2026-05-11 09:05) and logged for examination on 2026-05-11 09:22. The laboratory conducted analysis on 2026-05-11 10:05–11:22. The original physical door and hardware were not submitted; conclusions are therefore limited to what is visible and measurable within the provided photographic documentation.

Evidence handling for this report remained fully digital. No enhancement steps were performed that altered original files; any viewing adjustments were non-destructive (contrast/brightness/zoom for visualization only) and are documented in methodology.

Methodology

The examination followed standard comparative toolmark principles: assessing class characteristics (general features consistent with a tool type/shape) and individual characteristics (microscopic/irregular features that may arise from tool wear or damage) within the constraints of the available imagery.

The photographs were reviewed for: (1) prying directionality indicators (lip deformation, feathering, uplift), (2) contact surfaces likely to retain striations or impressions (strike plate edges, latch channel margins, painted wood/metal frame), and (3) repeated/overlapping mark patterns indicative of multiple insertions.

Comparisons were conducted between distinct mark clusters within the latch/strike region to evaluate internal consistency (i.e., whether marks appear to originate from the same general tool geometry and edge condition). A reference "suspected tool type" profile was then considered (flat, wedge-like prying implement such as a flathead screwdriver, small pry bar, or similar), based on visible width, edge transitions, and leverage-induced deformation patterns.

No physical exemplar tool was submitted for direct test-mark comparison. As a result, this report provides an association assessment based on toolmark morphology and investigative context rather than an absolute source determination from physical test marks.

Findings

1) Class characteristics consistent with a flat prying tool.

The latch/strike area exhibits localized compression and edge displacement consistent with insertion of a flat, wedge-like implement between door and frame. The marks include linear edge impressions and prying-related deformation



INCIDENT REPORT

Issued on: 2026-05-14 21:27 (-04:00)

Toolmark Comparison Report – Rear Service Door (Back Door Forced-Entry Damage)

CONFIDENTIAL • LAW ENFORCEMENT SENSITIVE

consistent with levering against the strike/latch interface.

2) Directionality and repeated insertion indicators.

The photographed damage shows deformation patterns consistent with prying force applied outward from the door seam, including displaced material at the strike-side edge and scuffing adjacent to the latch channel. The distribution of marks suggests more than one insertion/attempt rather than a single contact event.

3) Mark morphology supportive of a narrow-to-moderate blade width.

Within the photographed scale and perspective, the principal impression/abrasion bands appear consistent with a flat blade edge rather than a rounded shank. The mark boundaries and edge transitions are consistent with a tool having relatively squared shoulders and a thin leading edge (e.g., screwdriver/pry tool), as opposed to a wide, curved crowbar contact surface.

4) Internal consistency across mark clusters.

Multiple mark groupings in the latch/strike region display similar edge geometry and striation character, supporting the interpretation that the damage could plausibly have been produced by the same general tool type and edge condition.

5) Association to suspect Dennis Yu (contextual linkage).

Based on the investigative information provided in the case file—namely Dennis Yu's reported presence in the rear area during the incident window and documented familiarity with the door's latch behavior—these toolmark features are evaluated as supportive of association with his suspected means/opportunity (use of a readily available flat prying tool) and are not inconsistent with a tool he could plausibly possess or access.

Limitations

This examination was conducted from photographs only. The absence of the physical door hardware prevents microscopic comparison, three-dimensional assessment, and production of test marks from a submitted exemplar tool, all of which would materially strengthen (or potentially weaken) source-level conclusions.

Toolmark examination is inherently comparative. Many flat tools can produce similar class characteristics; therefore, absent a recovered tool and controlled test marks, the laboratory cannot uniquely identify a specific tool as the sole source of the damage.

Environmental and operational factors (paint layers, prior wear, subsequent handling, and overlapping contacts during the incident response) may obscure or mimic fine detail. The conclusions herein are accordingly limited to the observable features in the submitted images.

Conclusion

The toolmarks and deformation visible at the rear service door latch/strike area are consistent with forced entry using a flat, prying-type tool (e.g., screwdriver/small pry implement). The morphology and internal consistency of the mark clusters support the interpretation of repeated prying actions.

Given the investigative context provided, these findings are assessed as supportive of association with suspect Dennis Yu as a plausible user of such a tool during the forced-entry event at 2026-05-11 03:18, while recognizing that the evidence, as documented photographically, does not permit a unique, source-level identification to a specific individual tool without an exemplar for test-mark comparison.

REPORTING OFFICER CERTIFICATION



INCIDENT REPORT

Issued on: 2026-05-14 21:27 (-04:00)

Toolmark Comparison Report – Rear Service Door (Back Door Forced-Entry Damage)

CONFIDENTIAL • LAW ENFORCEMENT SENSITIVE

	Badge #: _____ Badge Number	05-14-2026 Date
Officer Signature		
	Badge #: _____ Badge Number	_____ Date
Supervisor Signature (if required)		