


Azure Resource Manager Template

Step 1



Step 2

The below **Deploy to Azure** button embeds an Azure ARM

<https://github.com/PaloAltoNetworks/azure/tree/master/two-tier-sample>

Deploy a two-tiered application environment secured by the VM-Series firewall

This ARM template deploys a VM-Series next generation firewall VM in an Azure resource group along with a web and db server similar to a typical two tier architecture. It also adds the relevant User-Defined Route (UDR) tables to send all traffic through the VM-Series firewall.

Deployment Guide

Support Policy

This ARM template is released under an as-is, best effort, support policy. These scripts should be seen as community supported and Palo Alto Networks will contribute our expertise as and when possible. We do not provide technical support or help in using or troubleshooting the components of the project through our normal support options such as Palo Alto Networks support teams, or ASC (Authorized Support Centers) partners and backline support options. The underlying product used (the VM-Series firewall) by the scripts or templates are still supported, but the support is only for the product functionality and not for help in deploying or using the template or script itself. Unless explicitly tagged, all projects or work posted in our GitHub repository (at <https://github.com/PaloAltoNetworks>) or sites other than our official Downloads page on <https://support.paloaltonetworks.com> are provided under the best effort policy.


[Deploy to Azure](#)
[Visualize](#)

Click “Visualize” for a visual representation of the various resources the template launches. Click “Deploy to Azure” link. You will be prompted to log in to your Azure account and prompted to specify some template parameters.

Create the following


Resource Group: username, E.g: lcastrose

Storage Account Name: username, E.g: lcastrose



The screenshot shows the Microsoft Azure portal's 'Custom deployment' page. The page is titled 'Custom deployment' with a subtitle 'Deploy from a custom template'. On the left is a navigation sidebar with various icons. The main content area is divided into sections: 'TEMPLATE', 'BASICS', 'SETTINGS', and 'TERMS AND CONDITIONS'. Under 'TEMPLATE', a 'Customized template' is selected, showing '20 resources' and 'Edit' and 'Learn more' links. The 'BASICS' section includes 'Subscription' (set to 'pay-as-you-go'), 'Resource group' (with 'Create new' selected and 'two-tier-resource-grp' entered), and 'Location' (set to 'West US'). The 'SETTINGS' section includes 'Storage Account Name' (set to 'storageacct'), 'Firewall Dns Name' (set to 'pan-fw'), 'Web Server Dns Name' (set to 'pan-web'), 'Firewall Vm Name' (set to 'pan-fw'), 'Firewall Vm Size' (set to 'Standard_D3_v2'), 'From Gateway Login' (set to '0.0.0.0/0'), and 'Ip Address Prefix' (set to '10.5'). The 'TERMS AND CONDITIONS' section includes a link to 'Azure Marketplace Terms', a paragraph of legal text, a checkbox for 'I agree to the terms and conditions stated above' (which is checked), and a 'Pin to dashboard' checkbox. At the bottom is a 'Purchase' button.


If the ARM template deployment was successful, the deployment state will show as “3 Succeeded”



Step 4

Review the Provisioned Resources

Verify that the resources match this topology.



Home > Icastrose

Icastrose Resource group

Search (Cmd+/) «

+ Add Edit columns Delete resource group Refresh Move Export to CSV Assign tags Delete Export template Feedback

Essentials

Filter by name... Type == all Location == all Add filter

Showing 1 to 16 of 16 records. Show hidden types No grouping

Name ↑↓	Type ↑↓	Location ↑↓
database-vm	Virtual machine	East US
DB-to-FW	Route table	East US
DBeth0	Network interface	East US
DefaultNSG	Network security group	East US
FWeth0	Network interface	East US
FWeth1	Network interface	East US
FWeth2	Network interface	East US
fwPublicIP	Public IP address	East US
fwVNET3515	Virtual network	East US
Icastrose3515	Storage account	East US
pan-fw	Virtual machine	East US

< Previous Page 1 of 1 Next >

Step 5



PanOS UI

Login to the VM-Series firewall


Review key portions of the firewall configurations

To access the firewall login page, access the URL from the azure portal template deployment summary page.

You should be able to log into the VMSeriesURL using the username/password: paloalto/Pal0Alt0@123




Step 6 - Networking



The interface (Ethernet 1/1) in the Unturst zone is the interface that is exposed to the outside world. All traffic enters through this interface.

The interface in the Trust zone (Ethernet 2/2) is the interface where the assets that need to be protected reside (in this case the web and database servers).

NOTE: Go the Network and set both E1/1 and E1/2 interfaces to UP, then click Commit




Then validate both interfaces are up “green”

Interface	Interface Type	Management Profile	Link State	IP Address	Virtual Router	Tag	VLAN / Virtual-Wire	Security Zone	SD-WI Profile
ethernet1/1	Layer3			Dynamic-DHCP Client	default	Untagged	none	Untrust	
ethernet1/2	Layer3			Dynamic-DHCP Client	default	Untagged	none	Trust	

Step 7

Verify Static Content on Web Server


Using the second URL (WebserverURL) in the output section of the deployment summary access the static content of the webserver and you should see:



Go to the Wordpress Server

Add the following string at the end of the second URL from the deployment:


<<http://pan-web2wgx.eastus.cloudapp.azure.com>>/wordpress



Step 8 - Simulate attacks to the web server

<<http://pan-web2wgx.eastus.cloudapp.azure.com>>/sql-attack.html

Click on Launch Web to DB SSH Attempt, to simulate East-West Traffic




Attack the database



LAUNCH WEB TO DB SSH ATTEMPT

LAUNCH BRUTE FORCE SQL ROOT PASSWORD GUESSING

Then go to the PANW to the monitor Tab and look for the deny logs using the following filter:


(port.dst eq 22)



	Receive Time	Type	From Zone	To Zone	Source	Source User	Destination	Dynamic User Group	To Port	Application	Action	Rule	Session End Reason
	05/24 19:06:12	drop	Trust	Trust	10.5.3.5		10.5.4.5		22	not-applicable	deny	Log default deny	policy-deny
	05/24 19:06:11	drop	Trust	Trust	10.5.3.5		10.5.4.5		22	not-applicable	deny	Log default deny	policy-deny

Step 9 - Simulate Brute Force attack

Go back and click on Launch Brute Force SQL Root Password Guessing



Attack the database

LAUNCH WEB TO DB SSH ATTEMPT

LAUNCH BRUTE FORCE SQL ROOT PASSWORD GUESSING

Go to the PANW Monitor Tab on Threat Log



	Receive Time	Type	Name	From Zone	To Zone	Attacker	Attacker Name	Victim	To Port	Application	Action	Severity	URL
	01/30 23:40:42	vulnerability	MySQL Login Authentication Failed	Trust	Trust	10.5.3.5		10.5.4.5	3306	mysql	reset-client	informational	

Step 10 - Cleanup

If done, delete the resource group in order to cleanup and remove all the resources created.

