EC-252: COMPUTER ARCHITECTURE AND MICROPROCESSORS

Vaskar Raychoudhury

Indian Institute of Technology Roorkee

Instruction Execution with 4 Registers

- Memory Address Register (MAR)
  - Connected to address bus
  - Specifies address for read or write op
- Memory Buffer Register (MBR)
  - Connected to data bus
  - Holds data to write or last data read
- Program Counter (PC)
  - Holds address of next instruction to be fetched
- Instruction Register (IR)
  - Holds last instruction fetched

Example of Program Execution



Instruction Cycle

- Two steps:
  - Fetch
  - Execute



Fetch Cycle

- Program Counter (PC) holds address of next instruction to fetch
- Processor fetches instruction from memory location pointed to by PC
- Increment PC
  - Unless told otherwise
- Instruction loaded into Instruction Register (IR)
- Processor interprets instruction and performs required actions

Fetch Sequence

- Address of next instruction is in PC
- Address (MAR) is placed on address bus
- Control unit issues READ command
- Result (data from memory) appears on data bus
- Data from data bus copied into MBR
- PC incremented by 1 (in parallel with data fetch from memory)
- Data (instruction) moved from MBR to IR
- MBR is now free for further data fetches

Execute Cycle

- Processor-memory
  - Data transfer between CPU and main memory
- Processor I/O
  - Data transfer between CPU and I/O module
- Data processing
  - Some arithmetic or logical operation on data
- Control
  - Alteration of sequence of operations
  - e.g. jump
- Combination of above

Instruction Cycle with Indirect



Instruction Cycle State Diagram


Instruction fetch
Operand fetch
Operand store
Multiple operands
Multiple results
Instruction address calculation
Instruction operation decoding
Operand address calculation
Data Operation
Operand address calculation
Instruction complete, fetch next instruction
Return for string or vector data

Data Flow (Instruction Fetch)

- Depends on CPU design
- In general:
- Fetch
  - PC contains address of next instruction
  - Address moved to MAR
  - Address placed on address bus
  - Control unit requests memory read
  - Result placed on data bus, copied to MBR, then to IR
  - Meanwhile PC incremented by 1

Data Flow (Fetch Diagram)



MBR = Memory buffer register
MAR = Memory address register
IR = Instruction register
PC = Program counter

Data Flow (Data Fetch)

- IR is examined
- If indirect addressing, indirect cycle is performed
  - Right most N bits of MBR transferred to MAR
  - Control unit requests memory read
  - Result (address of operand) moved to MBR

Data Flow (Indirect Diagram)



Data Flow (Execute)

- May take many forms
- Depends on instruction being executed
- May include
  - Memory read/write
  - Input/Output
  - Register transfers
  - ALU operations

Data Flow (Interrupt)

- Simple
- Predictable
- Current PC saved to allow resumption after interrupt
- Contents of PC copied to MBR
- Special memory location (e.g. stack pointer) loaded to MAR
- MBR written to memory
- PC loaded with address of interrupt handling routine
- Next instruction (first of interrupt handler) can be fetched

Data Flow (Interrupt Diagram)



Prefetch

- Fetch accessing main memory
- Execution usually does not access main memory
- Can fetch next instruction during execution of current instruction
- Called instruction prefetch

Two Stage Instruction Pipeline



(a) Simplified view



(b) Expanded view

Improved Performance

- But not doubled:
  - Fetch usually shorter than execution
    - Prefetch more than one instruction?
  - Any jump or branch means that prefetched instructions are not the required instructions
- Add more stages to improve performance

Pipelining is Natural!

- Laundry Example
- Ann, Brian, Cathy, Dave
  each have one load of clothes
  to wash, dry, and fold
- Washer takes 30 minutes
- Dryer takes 40 minutes
- “Folder” takes 20 minutes







Sequential Laundry



- Sequential laundry takes 6 hours for 4 loads
- If they learned pipelining, how long would laundry take?

Pipelined Laundry: Start work ASAP



- Pipelined laundry takes 3.5 hours for 4 loads

Pipelining

- Fetch instruction
- Decode instruction
- Calculate operands (i.e. EAs)
- Fetch operands
- Execute instructions
- Write result

- Overlap these operations

Timing Diagram for Instruction Pipeline Operation

Time →

	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Instruction 1	FI	DI	CO	FO	EI	WO								
Instruction 2		FI	DI	CO	FO	EI	WO							
Instruction 3			FI	DI	CO	FO	EI	WO						
Instruction 4				FI	DI	CO	FO	EI	WO					
Instruction 5					FI	DI	CO	FO	EI	WO				
Instruction 6						FI	DI	CO	FO	EI	WO			
Instruction 7							FI	DI	CO	FO	EI	WO		
Instruction 8								FI	DI	CO	FO	EI	WO	
Instruction 9									FI	DI	CO	FO	EI	WO

The Effect of a Conditional Branch on Instruction Pipeline Operation



	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Instruction 1	FI	DI	CO	FO	EI	WO								
Instruction 2		FI	DI	CO	FO	EI	WO							
Instruction 3			FI	DI	CO	FO	EI	WO						
Instruction 4				FI	DI	CO	FO							
Instruction 5					FI	DI	CO							
Instruction 6						FI	DI							
Instruction 7							FI							
Instruction 15								FI	DI	CO	FO	EI	WO	
Instruction 16									FI	DI	CO	FO	EI	WO

Six Stage Instruction Pipeline



Alternative Pipeline Depiction



	FI	DI	CO	FO	EI	WO
1	I1					
2	I2	I1				
3	I3	I2	I1			
4	I4	I3	I2	I1		
5	I5	I4	I3	I2	I1	
6	I6	I5	I4	I3	I2	I1
7	I7	I6	I5	I4	I3	I2
8	I8	I7	I6	I5	I4	I3
9	I9	I8	I7	I6	I5	I4
10		I9	I8	I7	I6	I5
11			I9	I8	I7	I6
12				I9	I8	I7
13					I9	I8
14						I9

(a) No branches



	FI	DI	CO	FO	EI	WO
1	I1					
2	I2	I1				
3	I3	I2	I1			
4	I4	I3	I2	I1		
5	I5	I4	I3	I2	I1	
6	I6	I5	I4	I3	I2	I1
7	I7	I6	I5	I4	I3	I2
8	I15					I3
9	I16	I15				
10		I16	I15			
11			I16	I15		
12				I16	I15	
13					I16	I15
14						I16

(b) With conditional branch

Pipelining Lessons



- Pipelining doesn't help latency of single task, it helps throughput of entire workload
- Pipeline rate limited by slowest pipeline stage
- Multiple tasks operating simultaneously using different resources
- Potential speedup = Number pipe stages
- Unbalanced lengths of pipe stages reduces speedup
- Time to "fill" pipeline and time to "drain" it reduces speedup
- Stall for Dependences