Endpoints

Fleet Development

- POST /fleet-development/series
- POST /fleet-development/vessels
- POST /fleet-development/summary
- GET /fleet-development/limits/dates

Voyage

- POST /voyage/legs
- POST /voyage/legs/series

API Products

Emissions
European gas API
Onshore Asset Monitoring
Refineries
AIS
Insight
Power
Cargo
Supply & Demand
Arbitrage
Next Destination
Freight
Routes
Financial flows
Vessel Ownership & Particulars
Risk & Compliance
Container Tracking

Freight

Freight Analytics gives shipping professionals and traders the real-time market intelligence they need to execute fixtures, time decisions, and manage risk with confidence.

Download Specification

Fleet Development

Fleet Development tracks fleet supply through four key metrics (Available Vessels, Deliveries, Orders, and Removals), giving shipowners, charterers, and analysts the insights needed to monitor tonnage trends, anticipate supply shifts, and support chartering or investment decisions.

/fleet-development/series

JSON CSV

Get fleet development series data

Returns time series data for fleet development metrics

Request

Request Body required

object

`matchers` object defaults to {}

Filters applied to fleet development queries. Combine date bounds, vessel identifiers, vessel attributes, and deadweight range filters to narrow the dataset.

`metric` string optional defaults to available

Metric to use for the data:
- available: Number of active vessels available in service at the end of each period (excludes cancelled orders and dead vessels)
- deliveries: Number of newly built vessels that entered service within each period (excludes cancelled orders)
- orders: Number of vessels newly ordered within the period
- removals: Number of vessels permanently removed from service within the period

Possible values

available deliveries orders removals

`projection` string optional defaults to actual

Deliveries projection mode:
- actual: caps buildAt at today
- predictive: also includes future buildAt dates within the requested range

Only affects the deliveries metric

Possible values

granularity string optional defaults to weekly

Time granularity to use for the data

Possible values

daily weekly monthly quarterly yearly

aggMetric string optional defaults to count

Aggregation metric:
- count returns vessel count
- deadweight returns sum of deadweight tonnage

Possible values

count deadweight

splitBy string optional

Dimension to split series data by.

Possible values

vesselClassification vesselCoating scrubberType engineType fuelType

numberOfSplits number optional

Desired number of split values to return. When specified, returns top N splits + Others bucket. When not specified, returns all split values.

Response

200 application/json object

date string

Date of the series data point in granularity format

datasets object[]

Datasets for this date point

metadata object

Metadata about the response

unit string

Unit of measurement for the data values in the response

Possible values

count tons

/fleet-development/vessels

JSON CSV

Get fleet development vessels data

Returns vessel data matching the specified criteria

Request

POST /fleet-development/vessels

Request Body required

object

matchers object defaults to {}

Filters applied to fleet development queries. Combine date bounds,

and deadweight range filters to narrow the dataset.

`metric` string optional defaults to available

Metric to use for the data:
- available: Number of active vessels available in service at the end of each period (excludes cancelled orders and dead vessels)
- deliveries: Number of newly built vessels that entered service within each period (excludes cancelled orders)
- orders: Number of vessels newly ordered within the period
- removals: Number of vessels permanently removed from service within the period

Possible values

available deliveries orders removals

`projection` string optional defaults to actual

Deliveries projection mode:
- actual: caps buildAt at today
- predictive: also includes future buildAt dates within the requested range

Only affects the deliveries metric

Possible values

actual predictive

`from` number optional defaults to 0

Number of vessels to skip for pagination

`size` number optional defaults to 40

Number of vessels to return per page

Response

200 application/json object

vessels object[]

Vessels matching the request criteria

imo number optional

The unique International Maritime Organization (IMO) number assigned to a vessel

id number

Unique ID assigned to vessels visible on the Kpler Terminal

name string

The vessel's current registered name

deadweight number optional

Maximum weight of cargo, fuel, provisions, and stores a vessel can carry, excluding its own weight, measured in tonnes

orderAt string optional

Date when the vessel was ordered

buildAt string

Date when construction of the vessel was completed (delivery date), or the planned construction completion/delivery date

deadAt string optional

Date when the vessel was scrapped or declared a total loss

scrubber object optional

Scrubber information for the vessel

vesselClassification string optional

The commercial grouping of ships, used

Possible values

VLCC Suezmax/LR3 Aframax/LR2 Panamax/LR1 MR Handy/MR1 Intermediate Tankers Short Sea Tankers Small Tankers VLGC VLEC VLAC LGC MGC Handy SGC Q-Max Q-Flex Upper Conventional Mid Conventional Lower Conventional Mid-Scale Small-Scale Large-Scale Floater Valemax VLOC Newcastlemax Capesize Baby Capes Post-Panamax Kamsarmax Panamax Ultramax Supramax Handymax Handysize Mini Bulker Megamax ULCS Neo-Panamax Feeder Unknown

`vesselCoating` string optional

Type of coating applied to the tanks

Possible values

Fully Coated Partly Coated Not Coated Unknown

`engine` object optional

Engine information for the vessel

`status` string optional

Current operational status of the vessel

Possible values

Reported Order On Order In Build Cancelled Order Launched In Service Under Repair Laid Up

Under Conversion Unknown

/fleet-development/summary

JSON

Get fleet development summary data

Returns summary data comparing current, previous, and last year periods

Request

POST /fleet-development/summary

Request Body required

object

`matchers` object defaults to {}

Filters applied to fleet development queries. Combine date bounds, vessel identifiers, vessel attributes, and deadweight range filters to narrow the dataset.

`metric` string optional defaults to available

Metric to use for the data:
- available: Number of active vessels available in service at the end of each period (excludes cancelled orders and dead vessels)
- deliveries: Number of newly built vessels that entered service within each period (excludes cancelled orders)
- orders: Number of vessels newly ordered within the period

Possible values

available deliveries orders removals

projection string optional defaults to actual

Deliveries projection mode:
- actual: caps buildAt at today
- predictive: also includes future buildAt dates within the requested range
Only affects the deliveries metric

Possible values

actual predictive

granularity string optional defaults to weekly

Time granularity to use for the data

Possible values

daily weekly monthly quarterly yearly

aggMetric string optional defaults to count

Aggregation metric:
- count returns vessel count
- deadweight returns sum of deadweight tonnage

Possible values

count deadweight

Response

current object

Summary data for the current period

values number

Numeric value for the summary period

period string

Period identifier in granularity format

previous object

Summary data for the previous period of the same granularity

values number

Numeric value for the summary period

period string

Period identifier in granularity format

lastYear object

Summary data for the same period in the previous year

values number

Numeric value for the summary period

period string

Period identifier in granularity format

/fleet-development/limits/dates

JSON

Get fleet development date query boundaries

Returns the min and max dates accepted by fleet development endpoints.

Response

200 application/json object

minDate string

Earliest allowed date for startDate and endDate queries

maxDate string

Latest allowed date for startDate and endDate queries (5 years from today, evaluated at request time)

Endpoints for querying voyage legs.

/voyage/legs

BETA JSON CSV

List legs

Returns a list of legs matching the request filters

Request

POST /voyage/legs

Request Body required

object

Request body for listing voyage legs

matchers object optional

Filters to narrow the leg results

pagination object optional defaults to {

sort object[] optional

Sort rules

expand string[] optional

Related resources to embed in each leg. Enrichment is opt-in and off by default.

Possible values

port_calls tonnage_metrics

Response

200 application/json object

legs object[]

Legs matching the request

imo number optional

Unique International Maritime Organization (IMO) number assigned to the vessel

vesselName string optional

The vessel's current registered name

vesselId number

Unique ID assigned to vessels visible on the Kpler Terminal

chronologyId string

Unique identifier for the chronology. Mutable when chronologies are recomputed.

legId string

Stable identifier derived from the vessel id and the leg's anchor

`toVesselEventId` string optional

Id of the event that closes the leg, if any

`fromVesselEventCategory` string optional

Category of the event that opens the leg, if any

Possible values

PortCall

`toVesselEventCategory` string optional

Category of the event that closes the leg, if any

Possible values

PortCall

`startAt` oneOf optional

When the leg started, as an ISO 8601 UTC instant. Null value means the leg is the first ever leg of the vessel.

Possible types:

- **`string`**
- **`null`**

`endAt` oneOf optional

When the leg ended, as an ISO 8601 UTC instant. Null value means the leg is the last open leg of the vessel.

Possible types:

- **`string`**
- **`null`**

`cargoOnBoard` object optional

Cargo on board when the leg opens, taken from the from-event when it is a port call

Zone of the port call that opens the leg; absent when no such port call

`fromParentZoneIds` number[] optional

Parent zones of the port call that opens the leg, the zone itself first; absent when no such port call

`toZoneId` number optional

Zone of the port call that closes the leg; absent when no such port call

`toParentZoneIds` number[] optional

Parent zones of the port call that closes the leg, the zone itself first; absent when no such port call

`fromPortCall` object optional

Port call that opens the leg. Present only when expand includes port_calls and fromVesselEventCategory is PortCall.

`toPortCall` object optional

Port call that closes the leg. Present only when expand includes port_calls and toVesselEventCategory is PortCall.

`tonMiles` anyOf optional

Ton-miles for the leg, in ktm (kilo ton-miles). Present when `expand` includes `tonnage_metrics`. Null when no tonnage data exists for this leg.

Possible types:

- **`undefined`** oneOf optional

  Possible types:

  - **`number`**
  - **`null`**

- **`null`**

Ton-days for the leg, in ktd (kilo ton-days). Present when `expand` includes `tonnage_metrics`. Null when no tonnage data exists for this leg.

Possible types:

- **undefined** oneOf optional

  Possible types:

  - **number**
  - **null**

- **null**

distance anyOf optional

Distance travelled on the leg, in nautical miles. Present when `expand` includes `tonnage_metrics`. Null when no tonnage data exists for this leg.

Possible types:

- **undefined** oneOf optional

  Possible types:

  - **number**
  - **null**

- **null**

duration anyOf optional

Duration of the leg, in days. Present when `expand` includes `tonnage_metrics`. Null when no tonnage data exists for this leg.

Possible types:

- **undefined** oneOf optional

  Possible types:

  - **number**
  - **null**

- **null**

speed anyOf optional

Median speed in knots. Present when `expand` includes `tonnage_metrics`. Null when no tonnage data exists for this leg or no speed values.

- `number`
- `null`

- `null`

/voyage/legs/series

BETA JSON CSV

Get leg series data

Returns time-bucketed leg series for the given filters and granularity

Request

POST /voyage/legs/series

Request Body required

object

Request body for leg series aggregation

`matchers` object optional

Filters to narrow the leg results. The series accepts the same filters as POST /legs.

`period` object optional

Chart time range for the series. When you omit from, it defaults to 2017-01-01. When you omit to, it defaults to now (UTC). Neither bound may be after the end of the current UTC day. When from is after to, the API rejects the request.

`aggField` string optional defaults to endAt

Leg timestamp used as the histogram

Required as startAt when completionState is set (open legs have no leg end timestamp).

Possible values

endAt startAt

granularity string optional defaults to monthly

Time granularity for the series buckets

Possible values

daily weekly monthly quarterly yearly

aggMetric string optional defaults to legs

Aggregation metric:
- legs: number of legs in each period
- voyages: number of distinct voyages with at least one leg in the period
- vessels: number of distinct vessels with at least one leg in the period
When matchers.cargoOnBoard restricts legs to laden or ballast, voyages counts distinct voyages among matching legs only.
Not supported with loadingState split: voyages (one voyage can include both ballast and laden legs). Not supported with completionState split: voyages (one voyage can include both open and closed legs).

Possible values

legs voyages vessels

Dimension to split series data by:
- vesselClassification: commercial vessel size groupings
- loadingState: ballast (cargo on board is zero), loaded (cargo on board > 0), or unknown (cargo on board is missing). Use legs or vessels, not voyages.
- completionState: open (no leg end timestamp) vs closed. Requires startAt as the bucket key (open legs have no leg end timestamp). Use legs or vessels, not voyages.
- fromZone: top N opening port zones (leg.fromZoneId) plus Others.
- toZone: top N closing port zones (leg.toZoneId) plus Others.

Possible values

vesselClassification loadingState completionState fromZone toZone

`numberOfSplits` number optional defaults to 10

Desired number of split values to return when vesselClassification, fromZone, or toZone is set. Defaults to 10. Returns top N splits plus an Others bucket for the remainder when more values exist. Ignored when loadingState or completionState is set.

Response

200 application/json object

`series` object[]

Series data points

Date of the series data point in granularity format

`datasets` object[]

Datasets for this date point

`metadata` object

Metadata about the response

`unit` string

Unit of measurement for the data values in the response

Possible values

count

SOC 2 Type 1 COMPLIANT 2024