

LETTER TO THE EDITOR

Symbolic analysis of (MO)(I)CCI(II)(III)-based analog circuits

E. Tlelo-Cuautle^{1,*}, C. Sánchez-López² and D. Moro-Frías¹

¹INAOE—Department of Electronics, Luis Enrique Erro No. 1, Puebla, Mexico 72840, Mexico

²UAT—Department of Electronics Engineering, Tlaxcala, Mexico

SUMMARY

New nullor-based models are introduced to describe the behavior of the first generation current conveyor (CCI), second generation current conveyor (CCII), third generation current conveyor (CCIII), their inverting equivalents (ICCI(II)(III)), and/or their multiple output topologies (MO(I)CCI(II)(III)). These nullor equivalents include only grounded resistors to improve the formulation of equations in symbolic nodal analysis. In this manner, it is highlighted the usefulness of the proposed models to calculate analytical expressions in MO(I)CCI(II)(III)-based analog circuits. Copyright © 2009 John Wiley & Sons, Ltd.

Received 28 March 2008; Revised 16 October 2008; Accepted 7 January 2009

KEY WORDS: current conveyor; nodal analysis; nullor; symbolic analysis; universal filter

1. INTRODUCTION

The nullor is quite useful for the development of analysis, synthesis, and design procedures [1], because it allows us to model the behavior of any active device [2, 3]. For instance, among the plethora of active devices, the current conveyor (CC) is a universal one [3, 4], whose derivations are known as first generation CC (CCI) [5–7], second generation CC (CCII) [8–13], and third generation CC (CCIII) [14, 15]. These three kinds of CCs have been designed to provide tunable characteristics [16, 17], and also they have their inverting topologies [18, 19]. In particular, the positive-type CCII (CCII+) can be evolved to design the current feedback opamp (CFOA) [20]. Furthermore, CCs are suitable to design active filters [21–39], simulated inductances [40–43], gyrators [44], and impedances [45, 46]. Besides, their parasitic effects must be taken into account to improve circuit performances [47]. CFOAs also provide advantages in active filter design [48–50].

*Correspondence to: E. Tlelo-Cuautle, INAOE—Department of Electronics, Luis Enrique Erro No. 1, Puebla, Mexico 72840, Mexico.

†E-mail: e.tlelo@ieee.org

Contract/grant sponsor: CONACyT; contract/grant numbers: 48396-Y, J56673

By modeling the behavior of analog circuits using nullors, some circuit transformations can be performed [51–54]. On the other hand, symbolic analysis can be applied to calculate analytical expressions of analog circuits [55–82]. For instance, in [68] it was shown the application of symbolic analysis to CCII-based circuits using nullors by applying graph methods [69]. Furthermore, in this work new nullor-based equivalents are introduced for the CCI(II)(III)s, their inverting equivalents ICCI(II)(III)s, and their multiple output equivalents MO(I)CCI(II)(III)s. All these equivalents consist of nullors with grounded resistances in order to improve the formulation of equations in symbolic nodal analysis (NA) [70–76], because floating resistances require more computational work since they have four entries [68], while grounded ones have only one entry in NA. Henceforth, this paper introduces new (MO)(I)CCI(II)(III)s models to enhance the calculation of analytical expressions.

2. NULLOR-BASED EQUIVALENTS

This section introduces new nullor-based equivalents of the (MO)(I)CCI(II)(III)s and CFOA by including its parasitic resistance at the terminal X (R_x), in order to perform symbolic NA. Although there can be different nullor-based equivalents of CCs, it is desirable to generate models with grounded passive elements because they have only one entry in the NA formulation, while floating ones have four entries. Therefore, in Figure 1 are shown the nullor-based equivalents of: (a) positive-type CCI (CCI+), (b) negative-type CCI (CCI–), (c) inverted CCI+ (ICCI+), (d) inverted CCI– (ICCI–), and (e) multiple-outputs ICCI (MOICCI).

In Figure 2 are shown the nullor-based equivalents of: (a) positive-type CCII (CCII+), (b) negative-type CCII (CCII–), (c) inverted CCII+ (ICCI+), (d) inverted CCII– (ICCI–), and (e) multiple-output CCII (MOCCII).

The CCIII is not a very popular topology in the literature founded until this moment. Besides, in Figure 3 are shown the nullor-based equivalents of: (a) positive-type CCIII (CCIII+), (b) negative-type CCIII (CCIII–), (c) inverted CCIII+ (ICCI+), (d) inverted CCIII– (ICCI–), and (e) multiple-outputs ICCIII (MOICCI).

By cascading the CCII+ with a voltage follower (VF [83]), one gets the nullor-based equivalent of the CFOA, as shown in Figure 4.

3. SYMBOLIC NA

The formulation and solution of the system of equations describing the behavior of an analog circuit are the main computer tasks in symbolic analysis [55–63]. Using nullors, one is able to formulate a system of equations by only applying NA [72–76], because all non-NA compatible elements can be transformed as NA compatible ones [73]. Further, the solution can be performed by applying determinant decision diagrams [64, 65].

In order to verify the usefulness of the proposed nullor-based equivalents, this section shows the symbolic NA applied to CC-based circuits. It is worthy to mention that in [68] one can find only the nullor equivalent of the CCII+; however, that model does not include R_x and generates four entries for each floating (two) resistor. On the other hand, the nullor equivalent proposed herein in Figure 2(a) is quite appropriate for NA because it generates only two entries and includes R_x .




Figure 1. Nullor equivalents: (a) CCI+; (b) CCI-; (c) ICCI+; (d) ICCI-; and (e) MOICCI.

The ($\mathbf{i}=\mathbf{Y}\mathbf{v}$) NA-formulation of nullor circuits has been presented in [72–75], and it has been improved in [76] by exploiting the properties of the nullator and norator [84]. Let us consider the dual-output CCII-based current-mode universal filter shown in Figure 5 [85]. Its nullor equivalent




Figure 2. Nullor equivalents: (a) CCII+; (b) CCII-; (c) ICCII+; (d) ICCII-; and (e) MOCCII.

is shown in Figure 6. By applying the symbolic NA-method [76], the formulation is given by Equation (1) and the current relationships are given by Equation (2). By setting: $I_1 = I_{in}$ and $I_2 = I_3 = 0$, one obtains a low-pass (LP), with $I_2 = I_{in}$ and $I_1 = I_3 = 0$, a band-pass (BP), with




Figure 3. Nullor equivalents: (a) $CCI(III)^+$; (b) $CCI(III)^-$; (c) $ICC(III)^+$; (d) $ICC(III)^-$; and (e) $MOICCI(III)$.




Figure 4. Nullor equivalent of the CFOA.




Figure 5. Current-mode DOCCII-based universal filter.

$-I_1 = I_2 = I_3 = I_{in}$, a high-pass (HP), and with $I_2 = I_3 = I_{in}$ and $I_1 = 0$, a Notch response.

$$\begin{bmatrix} I_1 \\ I_2 \\ 0 \\ I_3 \\ 0 \\ 0 \\ 0 \end{bmatrix} = \begin{bmatrix} sC_2 + g_{x2} & 0 & 0 & 1 & 0 & 1 & 0 \\ 0 & sC_1 + g_{x1} & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & -g_{x1} & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 & g_L \\ 0 & 0 & 0 & 1 & 1 & 0 & 0 \\ 0 & -g_{x2} & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 1 \end{bmatrix} \begin{bmatrix} v_1 \\ v_2 \\ v_{3,4,5} \\ v_{6,7} \\ v_{8,9,10} \\ v_{11,12} \\ v_o \end{bmatrix} \quad (1)$$

$$I_{out} = \frac{(s^2 R_{x1} R_{x2} C_1 C_2 + s R_{x2} C_2 + 1) I_3 - (s R_{x2} C_2) I_2 + I_1}{s^2 R_{x1} R_{x2} C_1 C_2 + s R_{x2} C_2 + 1} \quad (2)$$

From Equation (2), the center or cut-off frequency is given by Equation (3), where for a frequency response of 2 MHz: $C_1 = C_2 = 200$ pF and $R_{x1} = R_{x2} = 419.63 \Omega$. In Figure 7 are shown the LP, BP, HP and Notch responses in dashed line. When more parasitic elements are included, the





Figure 6. Nullor equivalent of Figure 5.

Figure 7. Responses of the filter including R_x (dashed lines), and including R_x , R_{z+} , and R_{z-} (solid line).

symbolic expressions grow and the simulation results may be degraded. For instance, by adding $R_{z+} = 704.38 \text{ k}\Omega$ and $R_{z-} = 697.95 \text{ k}\Omega$, the LP, BP, HP, and Notch responses are in solid line in Figure 7.

$$\omega_o = \sqrt{\frac{1}{R_{x1} R_{x2} C_1 C_2}} \quad (3)$$

As shown in [86], parasitic impedances, e.g. R_x , play an important role in filter performances. As a result, the proposed (MO)(I)CCI(II)(III) nullor equivalents are quite useful to compute symbolic expressions by applying NA.

4. CONCLUSIONS

New (MO)(I)CCI(II)(III) models have been introduced consisting of nullors and only grounded resistances. The proposed nullor equivalents allow to an integrated circuit designer to include parasitic elements, and from Section 3 it can be concluded that they are quite suitable to compute analytical expressions of CC-based analog circuits.

ACKNOWLEDGEMENTS

This work is supported by CONACyT under the projects 48396-Y and J56673.

REFERENCES

1. Kumar P, Senani R. Bibliography on nullors and their applications in circuit analysis, synthesis and design. *Analog Integrated Circuits and Signal Processing* 2002; **33**(1):65–76.
2. Svoboda JA. Current conveyors, operational amplifiers and nullors. *IEE Proceedings G Circuits, Devices and Systems* 1989; **136**(6):317–322.
3. Schmid H. Approximating the universal active element. *IEEE Transactions on Circuits and Systems II: Analog and Digital Signal Processing* 2000; **47**(11):1160–1169.
4. Wilson B. Tutorial review: trends in current conveyor and current-mode amplifier design. *International Journal of Electronics* 1992; **73**(3):573–583. DOI: 10.1080/00207219208925692.
5. Smith KC, Sedra A. The current conveyor: a new circuit building block. *Proceedings of the IEEE* 1968; **56**:1368–1369.
6. Bruun E. Class AB. CMOS first-generation current conveyor. *Electronics Letters* 1995; **31**(6):422–423.
7. Fabre A, Amrani H, Barthélemy H. A novel class AB first generation current conveyor. *IEEE Transactions on Circuits and Systems II* 1999; **46**(1):96–98.
8. Sedra A, Smith KC. A second generation current conveyor and its application. *IEEE Transactions on Circuit Theory* 1970; **17**:132–134.
9. Arbel A. Towards a perfect CMOS CCII. *Analog Integrated Circuits and Signal Processing* 1997; **12**:119–132.
10. Mahmoud SA. New fully-differential CMOS second-generation current conveyor. *ETRI Journal* 2006; **28**(4):495–501.
11. Salem SB, Fakhfakh M, Masmoudi DS, Loulou M, Loumeau P, Masmoudi N. A high performances CMOS CCII and high frequency applications. *Analog Integrated Circuits and Signal Processing* 2006; **49**(1):71–78.
12. Awad IA, Soliman AM. High accuracy class AB CCII-. *AEU—International Journal of Electronics and Communications* 2004; **58**(4):237–243.
13. Tlelo-Cuautle E, Moro-Frías D, Sánchez-López C, Duarte-Villaseñor MA. Synthesis of CCII-s by superimposing VFs and CFs through genetic operations. *IEICE Electronics Express* 2008; **5**(11):411–417.

14. Minaei S. A new high performance CMOS third generation current conveyor (CCIII) and its application. *Electrical Engineering* 2003; **85**(3):147–153.
15. Fabre A. Third-generation current conveyor: a new helpful active element. *Electronics Letters* 1995; **31**(5):338–339.
16. Tangsrirat W, Prasertsom D. Electronically tunable low-component-count current-mode biquadratic filter using dual-output current followers. *Electrical Engineering* 2007; **90**(1):33–37.
17. Minaei S, Sayin OK, Kuntman H. A new CMOS electronically tunable current conveyor and its application to current-mode filters. *IEEE Transactions on Circuits and Systems I: Regular Papers* 2006; **53**(7):1448–1457.
18. Soliman AM. The inverting second generation current conveyors as universal building blocks. *AEU-International Journal of Electronics and Communications* 2008; **62**(2):114–121.
19. Awad IA, Soliman AM. Inverting second generation current conveyors: the missing building blocks, CMOS realizations and applications. *International Journal of Electronics* 1999; **86**(4):413–432.
20. Mahmoud SA, Madian AH, Soliman AM. Low-voltage CMOS current feedback operational amplifier and its application. *ETRI Journal* 2007; **29**(2):212–218.
21. Tlelo-Cuautle E, Duarte-Villaseñor MA. Evolutionary electronics: automatic synthesis of analog circuits by GAs. *Success in Evolutionary Computation*, Yang A, Yin S, Lam B (eds). Chapter 8. Series: Studies in Computational Intelligence, vol. 92. Springer: Berlin, 2008; 165–188.
22. Fakhfakh M, Loulou M, Tlelo-Cuautle E. Synthesis of CCII and design of simulated CCII-based floating inductances. *IEEE ICECS*, 2007; 379–382. Marrakech, Morocco.
23. García-Ortega JM, Tlelo-Cuautle E, Sánchez-López C. Design of current-mode Gm-C filters from the transformation of opamp-RC filters. *Journal of Applied Sciences* 2007; **7**(9):1321–1326.
24. Yuce E, Kircay A, Tokat S. Universal resistorless current-mode filters employing CCCII. *International Journal of Circuit Theory and Applications*. DOI: 10.1002/cta.455.
25. Jiraseree-Amornkun A, Surakampontorn W. Efficient implementation of tunable ladder filters using multi-output current controlled conveyors. *AEU—International Journal of Electronics and Communications* 2008; **62**(1):11–23.
26. Chang CM, Soliman AM, Swamy MNS. Analytical synthesis of low-sensitivity high-order voltage-mode DDCC and FDCCII-grounded R and C all-pass filter structures. *IEEE Transactions on Circuits and Systems I: Regular Papers* 2007; **54**(7):1430–1443.
27. Keskin AU, Cam U. Insensitive high-output impedance minimum configuration SITO-type current-mode biquad using dual-output current conveyors and grounded passive components. *AEU—International Journal of Electronics and Communications* 2007; **61**(5):341–344.
28. Metin B, Yuce E, Cicekoglul O. A novel dual output universal filter topology using a single current conveyor. *Electrical Engineering* 2007; **89**(7):563–567.
29. Tangsrirat W, Surakampontorn W. Electronically tunable current-mode universal filter employing only plus-type current-controlled conveyors and grounded capacitors. *Circuits, Systems, and Signal Processing* 2006; **25**(6):701–713.
30. Kumar P, Senani R. A systematic realization of current mode universal biquad filters. *International Journal of Electronics* 2006; **93**(9):623–636.
31. Horng JW, Kaewpoonsuk CL, Chang CM, Chou HP, Lin CT. High input impedance voltage-mode universal biquadratic filter with one input and five outputs using current conveyors. *Circuits, Systems, and Signal Processing* 2006; **25**(6):767–777.
32. Singh VK, Singh AK, Senani R. Dual function capability of recently proposed four-current-conveyor-based VM biquad. *Journal of Circuits, Systems, and Computers* 2005; **14**(1):51–56.
33. Wu J, El-Masry E. Current-mode ladder filters using multiple output current conveyors. *IEE Proceedings Circuits Devices Systems* 1996; **143**(4):218–222.
34. Aronhime P, Nelson D, Adams C. Applications of a first-generation current conveyor in current-mode circuits. *Electronics Letters* 1990; **26**(18):1456–1457.
35. Soliman AM. The CCII+ and the ICCII as basic building blocks in low-pass filter realizations. *International Journal of Circuit Theory and Applications* 2008; **36**(4):493–509.
36. Soliman AM. Current mode filters using two output inverting CCII. *International Journal of Circuit Theory and Applications*. DOI: 10.1002/cta.463.
37. Soliman AM. Generation of grounded capacitor ICCII-based band-pass filters. *Journal of Circuits, Systems, and Computers* 2007; **16**(4):553–566.
38. Soliman AM. Voltage mode and current mode Tow Thomas bi-quadratic filters using inverting CCII. *International Journal of Circuit Theory and Applications* 2007; **35**(4):463–467.

39. Minaei S, Yuce E, Cicekoglu O. ICCII-based voltage-mode filter with single input and six outputs employing grounded capacitors. *Circuits, Systems, and Signal Processing* 2006; **25**(4):559–566.
40. Yuce E, Minaei S, Cicekoglu O. Limitations of the simulated inductors based on a single current conveyor. *IEEE Transactions on Circuits and Systems I: Regular Papers* 2006; **53**(12):2860–2867.
41. Metin B, Cicekoglu O. A novel floating lossy inductance realization topology with NICs using current conveyors. *IEEE Transactions on Circuits and Systems II: Express Briefs* 2006; **53**(6):483–486.
42. Salem SB, Masmoudi DS, Loulou M. A novel CCII-based tunable inductance and high frequency current-mode band pass filter application. *Journal of Circuits, Systems, and Computers* 2006; **15**(6):849–860.
43. Cabeza R, Carlosena A. Computational synthesis of arbitrary floating impedances. *International Journal of Circuit Theory and Applications* 1998; **26**(5):463–475.
44. Saad RA, Soliman AM. Generation, modeling, and analysis of CCII-based gyrators using the generalized symbolic framework for linear active circuits. *International Journal of Circuit Theory and Applications* 2008; **36**(3):289–309.
45. Godara B, Fabre A. Versatile wideband impedance matching circuit based on current conveyors. *Electronics Letters* 2007; **43**(6):37–38.
46. Ananda-Mohan PV. Floating capacitance simulation using current conveyors. *Journal of Circuits, Systems, and Computers* 2005; **14**(1):123–128.
47. Cabeza R, Carlosena A. A cautionary note on stability of current conveyor-based circuits. *International Journal of Circuit Theory and Applications* 1998; **26**(2):215–218.
48. Djebbi M, Assi A, Sawan M. Design of monolithic tunable CMOS band-pass filter using current feedback operational amplifiers. *Analog Integrated Circuits and Signal Processing* 2005; **45**(2):143–154.
49. Sharma RK, Senani R. On the realization of universal current mode biquads using a single CFOA. *Analog Integrated Circuits and Signal Processing* 2004; **41**(1):65–78.
50. Sharma RK, Senani R. Multifunction CM/VM biquads realized with a single CFOA and grounded capacitors. *AEU—International Journal of Electronics and Communications* 2003; **57**(5):301–308.
51. Wang HY, Chang SH, Jeang YL, Huang CY. Rearrangement of mirror elements. *Analog Integrated Circuits and Signal Processing* 2006; **49**(1):87–90.
52. Cel J. Adjoint nullator–norator networks. *International Journal of Circuit Theory and Applications* 1994; **22**(5):409–418.
53. Carlosena A, Moschytz GS. Nullators and norators in voltage to current mode transformations. *International Journal of Circuit Theory and Applications* 1993; **21**(4):421–424.
54. Svoboda JA. Opamp relocation and the complementary transformation. *International Journal of Circuit Theory and Applications* 1990; **18**(5):535–540.
55. Tan SXD. Symbolic analysis of analog circuits by boolean logic operations. *IEEE Transactions on Circuits and Systems II: Express Briefs* 2006; **53**(11):1313–1317.
56. Tan SXD, Guo W, Qi Z. Hierarchical approach to exact symbolic analysis of large analog circuits. *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems* 2005; **24**(8):1241–1250.
57. Doboli A, Vemuri R. A regularity-based hierarchical symbolic analysis method for large-scale analog networks. *IEEE Transactions on Circuits and Systems II: Analog and Digital Signal Processing* 2001; **48**(11):1054–1068.
58. Gielen G, Wambacq P, Sansen WM. Symbolic analysis methods and applications for analog circuits: a tutorial overview. *Proceedings of the IEEE* 1994; **82**(2):287–304.
59. Wambacq P, Fernández FV, Gielen G, Sansen W, Rodríguez-Vázquez A. Algorithm for efficient symbolic analysis of large analogue circuits. *Electronics Letters* 1994; **30**(14):1108–1109.
60. Chua LO, Lin PM. *Computer-Aided Analysis of Electronic Circuits: Algorithms and Computational Techniques*. Prentice-Hall: Englewood Cliffs, NJ, 1975.
61. Gielen GE, Sansen W. *Symbolic Analysis for Automated Design of Analog Integrated Circuits*. Kluwer: Dordrecht 1991.
62. Fernández FV, Rodríguez-Vázquez A, Huertas JL, Gielen GE. *Symbolic Analysis Techniques: Applications to Analog Design Automation*. IEEE Press: New York, 1998.
63. Rutenbar RA, Gielen GE, Antao BA. *Computer-aided Design of Analog Integrated Circuits and Systems*. Wiley: New York, 2002.
64. Verhaegen W, Gielen G. Efficient DDD-based symbolic analysis of linear analog circuits. *IEEE Transactions on Circuits and Systems II: Analog and Digital Signal Processing* 2002; **49**(7):474–487.
65. Shi CJR, Tan XD. Canonical symbolic analysis of large analog circuits with determinant decision diagrams. *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems* 2000; **19**(1):1–18.

66. Daems W, Gielen G, Sansen W. Circuit simplification for the symbolic analysis of analog integrated circuits. *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems* 2002; **21**(4):395–407.
67. Rodríguez-García JD, Guerra O, Roca E, Fernández FV, Rodríguez-Vázquez A. Error control in simplification before generation algorithms for symbolic analysis of large analogue circuits. *Electronics Letters* 1999; **35**(4): 260–261.
68. Grimbleby JB. Symbolic analysis of networks containing current conveyors. *Electronics Letters* 1992; **28**(15): 1401–1403.
69. Grimbleby JB. Symbolic analysis of circuits containing active elements. *Electronics Letters* 1981; **17**(20):754–756.
70. Svoboda JA. Using nullors to analyse linear networks. *International Journal of Circuit Theory and Applications* 1986; **14**(3):169–180.
71. Svoboda JA. Unique solvability of RLC nullor networks. *International Journal of Circuit Theory and Applications* 1983; **11**(1):1–6.
72. Floberg H. *Symbolic Analysis in Analog Integrated Circuit Design*. Kluwer: Boston, 1997.
73. Tlelo-Cuautle E, Sánchez-López C, Sandoval-Ibarra F. Computing symbolic expressions in analog circuits using nullors. *Computación y Sistemas* 2005; **9**(2):119–132.
74. Tlelo-Cuautle E, Quintanar-Ramos A, Gutiérrez-Pérez G, González de la Rosa M. SIASCA: interactive system for the symbolic analysis of analog circuits. *IEICE Electronics Express* 2004; **1**(1):19–23.
75. Tlelo-Cuautle E, Sánchez-López C, Sandoval-Ibarra F. Symbolic analysis: a formulation approach by manipulating data structures. *IEEE ISCAS*, vol. 4, 2003; 640–643. Bangkok, Thailand.
76. Sánchez-López C, Moro-Frías D, Tlelo-Cuautle E. Improving the formulation process of the system of equations of analog circuits. *SM²ACD*, Erfurt, Germany, October 7–8, 2008; 102–106.
77. Bruun E. Analysis of the noise characteristics of CMOS current conveyors. *Analog Integrated Circuits and Signal Processing* 1997; **12**(1):71–78.
78. Ferri G, Guerrini NC. Noise determination in differential pair-based second generation current conveyors. *Analog Integrated Circuits and Signal Processing* 2004; **41**(1):35–46.
79. Sánchez-López C, Tlelo-Cuautle E, Fakhfakh M, Loulou M. Computing simplified noise-symbolic-expressions in CMOS CCs by applying SPA and SAG. *IEEE ICM*, 2007; 159–162. Cairo, Egypt.
80. Fakhfakh M, Loulou M, Masmoudi N, Sánchez-López C, Tlelo-Cuautle E. Symbolic noise figure analysis of CCII+s. *International Multi-conference on Systems, Signals and Devices*, vol. 4, 2007. Hammamet, Tunisia.
81. Tlelo-Cuautle E, Sánchez-López C. Symbolic computation of NF of transistor circuits. *IEICE Transactions on Fundamentals of Electronics, Communications and Computer Sciences* 2004; **E87-A**(9):2420–2425.
82. Sánchez-López C, Tlelo-Cuautle E. Behavioral model generation for symbolic analysis of analog integrated circuits. *IEEE ISSCS*, vol. 1, 2005; 327–330. Iasi, Romania.
83. Tlelo-Cuautle E, Duarte-Villaseñor MA, Guerra-Gómez I. Automatic synthesis of VFs and VMs by applying genetic algorithms. *Circuits, Systems and Signal Processing* 2008; **27**(3):391–403.
84. Moschytz GS. *Linear Integrated Networks: Fundamentals*. VanNostrand Reinhold: New York, 1974.
85. Tangsrirat W, Prasertsom D. Electronically tunable low-component-count current-mode biquadratic filter using dual-output current followers. *Electrical Engineering* 2007; **90**(1):33–37.
86. Yuce E, Minaei S. Universal current-mode filters and parasitic impedance effects on the filter performances. *International Journal of Circuit Theory and Applications* 2008; **36**(2):161–171.