

# Decidability of Weak Simulation on One-Counter Nets

Piotr Hofman<sup>1</sup>   Richard Mayr<sup>2</sup>   Patrick Totzke<sup>2</sup>

University of Warsaw<sup>1</sup>   University of Edinburgh<sup>2</sup>

September 21, 2013

# Weak Steps

For  $a \neq \tau \in \text{Act}$  and define

$$\xRightarrow{\tau} := \xrightarrow{\tau}^* \qquad \xRightarrow{a} := \xrightarrow{\tau}^* \xrightarrow{a} \xrightarrow{\tau}^*$$

# Weak Simulation Games

... are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

# Weak Simulation Games

... are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

In each round


$\alpha$  vs.  $\beta$

- 1 Spoiler moves from  $\alpha$
- 2 Duplicator responds from  $\beta$
- 3 game continues from  $\alpha'$  vs.  $\beta'$

# Weak Simulation Games

... are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

In each round




- 1 Spoiler moves from  $\alpha$
- 2 Duplicator responds from  $\beta$
- 3 game continues from  $\alpha'$  vs.  $\beta$

# Weak Simulation Games

... are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

In each round




- 1 Spoiler moves from  $\alpha$
- 2 Duplicator responds from  $\beta$
- 3 game continues from  $\alpha'$  vs.  $\beta'$

# Weak Simulation Games

... are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

In each round



1 Spoiler moves from  $\alpha$


2 Duplicator responds from  $\beta$

3 game continues from  $\alpha'$  vs.  $\beta'$

# Weak Simulation Games

...are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

In each round



**1** Spoiler moves from  $\alpha$

**2** Duplicator responds from  $\beta$


**3** game continues from  $\alpha'$  vs.  $\beta'$

Def: Weak Simulation  $\preceq$


$\alpha \preceq \beta$  iff Duplicator has a strategy to win from  $\alpha$  vs.  $\beta$ .



# Example




# Example



■  $A0 \not\sim B0$


# Example



■  $A0 \not\preceq B0$


■  $A0 \preceq B0$

# Example



- $A0 \not\preceq B0$
- $A0 \preceq B0$
- $B0 \xRightarrow{a} Cn$  for every  $n \in \mathbb{N}$

# Example



- $A0 \not\sim B0$
- $A0 \not\sim^a B0$
- $B0 \xRightarrow{a} Cn$  for every  $n \in \mathbb{N}$

# Our Contribution

We show decidability of the

## OCN Weak Simulation Problem

Input: A net  $\mathcal{N} = (Q, \text{Act}, \delta)$  and configurations  $pm, qn$ .

Question:  $pm \preceq qn$ ?

# Our Contribution

We show decidability of the

## OCN Weak Simulation Problem

Input: A net  $\mathcal{N} = (Q, \text{Act}, \delta)$  and configurations  $pm, qn$ .

Question:  $pm \preceq qn$ ?

## Theorem

*For a given net, the relation  $\preceq$  is effectively semilinear.*

# Why should you care?

In practice, modelling might use both  $\infty$ -states and branching:


- network protocols/queues keeping track of their workload
- random guesses

Theoretically, surprising:


- rare positive result for behavioral preorder that is not finitely approximable  $\preceq \neq \preceq_\omega$ .
- goes against the usual 'finer is easier' trend




## Some Context – Strong Case



# Some Context – Strong Case



# Some Context – Weak Case



# Proof Overview

Symbolic infinite branching

1

Reduce  $(\text{OCN} \preceq \text{OCN}) \rightsquigarrow (\text{OCN} \preceq \omega\text{-Net})$

# Proof Overview

Symbolic infinite branching

1

Reduce  $(\text{OCN} \preceq \text{OCN}) \rightsquigarrow (\text{OCN} \preceq \omega\text{-Net})$

Approximants for the new game

2

$\exists$  finite sequence  $\preceq^0 \supseteq \preceq^1 \supseteq \preceq^2 \supseteq \dots \supseteq \preceq^k = \preceq$

# Proof Overview

Symbolic infinite branching

1

Reduce  $(\text{OCN} \preceq \text{OCN}) \rightsquigarrow (\text{OCN} \preceq \omega\text{-Net})$

Approximants for the new game

2

$\exists$  finite sequence  $\preceq^0 \supseteq \preceq^1 \supseteq \preceq^2 \supseteq \dots \supseteq \preceq^k = \preceq$

Compute approximants for finite  $k$

3

Recursively compute  $\preceq^k$  by reduction to  $(\text{OCN} \preceq \text{OCN})$

# Proof Overview

Symbolic infinite branching

1

Reduce  $(\text{OCN} \preceq \text{OCN}) \rightsquigarrow (\text{OCN} \preceq \omega\text{-Net})$

Approximants for the new game

2

$\exists$  finite sequence  $\preceq^0 \supseteq \preceq^1 \supseteq \preceq^2 \supseteq \dots \supseteq \preceq^k = \preceq$

Compute approximants for finite  $k$

3

Recursively compute  $\preceq^k$  by reduction to  $(\text{OCN} \preceq \text{OCN})$

# Approximants for strong simulation (OCN vs. $\omega$ -Net)

$$\leq^k$$




# Approximants for strong simulation (OCN vs. $\omega$ -Net)

$$\leq^k$$


... holds if Duplicator can guarantee to either

- enforce an infinite game or
- explicitly make use of  $\infty$ -branching  $k$  times.


# Example



# Example




# Example




■  $A0 \not\sim B0$

# Example




- $A0 \not\preceq B0$
- $A0 \preceq^1 B0$

# Example



- $A0 \not\leq B0$
- $A0 \leq^1 B0$
- $A0 \not\leq^2 B0$

# Example



- $A0 \not\preceq B0$
- $A0 \preceq^1 B0$
- $A0 \not\preceq^2 B0$
- $\preceq = \preceq^2$

# Proof Overview

Symbolic infinite branching

1

Reduce  $(\text{OCN} \preceq \text{OCN}) \rightsquigarrow (\text{OCN} \preceq \omega\text{-Net})$

Approximants for the new game

2

$\exists$  finite sequence  $\preceq^0 \supseteq \preceq^1 \supseteq \preceq^2 \supseteq \dots \supseteq \preceq^k = \preceq$

Compute approximants for finite  $k$

3

Recursively compute  $\preceq^k$  by reduction to  $(\text{OCN} \preceq \text{OCN})$



# Proof Overview

Symbolic infinite branching

1

Reduce  $(\text{OCN} \preceq \text{OCN}) \rightsquigarrow (\text{OCN} \preceq \omega\text{-Net})$

Approximants for the new game

2

$\exists$  finite sequence  $\preceq^0 \supseteq \preceq^1 \supseteq \preceq^2 \supseteq \dots \supseteq \preceq^k = \preceq$

Compute approximants for finite  $k$

3

Recursively compute  $\preceq^k$  by reduction to  $(\text{OCN} \preceq \text{OCN})$

# Our Main Contribution

## OCN Weak Simulation Problem

Input: A net  $\mathcal{N} = (Q, \text{Act}, \delta)$  and configurations  $pm, qn$ .

Question:  $pm \preceq qn$ ?

## Theorem

For a given net, the relation  $\preceq$  is effectively semilinear.

# Our Main Contribution

## OCN Weak Simulation Problem

Input: A net  $\mathcal{N} = (Q, \text{Act}, \delta)$  and configurations  $pm, qn$ .

Question:  $pm \preceq qn$ ?

## Theorem

For a given net,

- $\preceq$  is semilinear and can be represented in EXPSPACE.
- The Weak Sim. Problem is PSPACE-complete.

# Our Main Contribution

## OCN Weak Simulation Problem

Input: A net  $\mathcal{N} = (Q, \text{Act}, \delta)$  and configurations  $pm, qn$ .

Question:  $pm \preceq qn$ ?

# Questions?

## Theorem

For a given net,

- $\preceq$  is semilinear and can be represented in EXPSPACE.
- The Weak Sim. Problem is PSPACE-complete.