

Well-Quasi-Ordering, Overview and its Applications

Mizuhito Ogawa

Japan Advanced Institute of Science and Technology

mizuhito@jaist.ac.jp

This talk shows theorems, techniques, and applications of *well-quasi-ordering* (WQO).

First, we introduce what is WQO, and Kruskal-type theorems on various data structures [31, 15, 16, 23, 34, 33]. The basic proof technique, *minimal bad sequence* (MBS), will be introduced for the simplest case, *Higman's Lemma*. Then, WQO will be extended to *better-quasi-ordering* (BQO) for infinite data structures [31, 25, 24, 26, 18, 36, 39]. The variation with the *gap-condition* will be also mentioned [37, 17, 12, 13, 40].

Second, the relation between WQO and regularity will be discussed. The basic fact is that a set of finite words is regular if, and only if, it is upward-closed wrt some WQO on finite words [8]. Its variations are also mentioned [14, 5, 28].

Based on these theoretical results, we overview applications of WQO techniques:

1. simple termination in rewriting [6], its extensions [30, 19], and automation [7],
2. upper bound of complexity [9, 4], including some instance of algorithm generation [27],
3. well structured transition system [1, 10, 3, 2].

Simple termination is one of well-known applications of WQO. It reduces termination to syntactical conditions, and validates well-foundedness of the family of path orderings (such as lexicographical path ordering). This also gives a reasonably large class in which termination can be automatically detected. For instance, termination of Ackerman function can be automatically proved. These techniques are also used to show termination of partial evaluation [38, 20, 21].

For a quite broad class of problems, the upper bound of complexity can be estimated by finiteness of *forbidden minors*. For instance, a known algorithm of the k -searcher problem remains at $O(n^{2k^2+4k+8})$, whereas WQO techniques shows the existence of a linear time algorithm [35, 29]. Note that this *does not* give any sight on how to construct such a linear time algorithm. This strange phenomena occurs from highly non-constructive nature of MBS. When a Kruskal-type theorem has a constructive proof, one may be able to construct an efficient algorithm. For instance, constructive proofs of Higman's Lemma are quite well-investigated [22, 32, 11] (supplied even in Coq theorem prover library!), and an open problem in relational database is solved by automatic generation [28].

Model checking is one of recent hot topics. Usually, decidability of model checking relies on finiteness of a model space. WQO sometimes guarantees decidability of model checking on an infinite space. This is known as *well-structured transition system*, and we will conclude the talk with its overview.

References

- [1] P.A. Abdulla and B. Jonsson. Ensuring completeness of symbolic verification methods for infinite-state machine. *Theoretical Computer Science*, 256:145–167, 2001.
- [2] P.A. Abdulla and A. Nylén. Better is better than well: on efficient verification of infinite-state systems. In *Proc. 15th IEEE Symposium on Logic in Computer Science*, pages 132–140, 2000.
- [3] P.A. Abdulla, K. Čerāns, B. Jonsson, and Y.-K. Tsay. General decidability theorems for infinite-state systems. In *Proc. 11th IEEE Symposium on Logic in Computer Science*, pages 313–320, 1996.
- [4] Mohar B. Embedding graphs in an arbitrary surface in linear time. In *Proc. 28th ACM Sympo. on Theory of Computing*, pages 392–397, 1996.
- [5] A. de Luca and S. Varricchio. Well quasi-orders and regular languages. *Acta Informatica*, 31:539–557, 1994.
- [6] N. Dershowitz and J.-P. Jouannaud. Rewrite systems. In J. van Leeuwen, editor, *Handbook of Theoretical Computer Science*, volume B, chapter 6, pages 243–320. Elsevier Science Publishers, 1990.
- [7] D. Detlefs and R. Forgaard. A procedure for automatically proving the termination of a set of rewrite rules. In *Proc. RTA'85*, pages 255–270, 1985. LNCS 202.
- [8] A. Ehrenfeucht, D. Hausser, and G. Rozenberg. On regularity of context-free languages. *Theoretical Computer Science*, 27:311–332, 1983.
- [9] M.R. Fellows and M.A. Langston. Nonconstructive tools for proving polynomial-time decidability. *JACM*, 35(3):727–739, 1988.

- [10] A. Finkel and Ph. Schnoebelen. Well-structured transition systems everywhere! *Theoretical Computer Science*, 256:63–92, 2001.
- [11] A. Geser. A proof of Higman’s lemma by open induction. Technical Report MIP-9606, Passau University, April 1996.
- [12] L. Gordeev. Generalizations of the one-dimensional version of the Kruskal-Friedman theorems. *Journal of Symbolic Logic*, 54(1):101–121, 1989.
- [13] L. Gordeev. Generalizations of the Kruskal-Friedman theorems. *Journal of Symbolic Logic*, 55(1):157–181, 1990.
- [14] D. Haussler. Another generalization of Higman’s well quasi order result on σ^* . *Discrete Mathematics*, 57:237–243, 1985.
- [15] G. Higman. Ordering by divisibility in abstract algebras. *Proc. London Mathematical Society*, 2:326–336, 1952.
- [16] J. Kruskal. Well-quasiordering, the tree theorem, and Vazsonyi’s conjecture. *Trans. American Mathematical Society*, 95:210–223, 1960.
- [17] I. Kříž. Well-quasiordering finite trees with gap-condition. proof of Harvey Friedman’s conjecture. *Ann. of Math.*, 130:215–226, 1989.
- [18] R. Laver. Better-quasi-orderings and a class of trees. In *Studies in foundations and combinatorics, advances in mathematics supplementary studies*, volume 1, pages 31–48. Academic Press, 1978.
- [19] P. Lescanne. Well rewrite orderings and well quasi-orderings. *Journal of Symbolic Computation*, 14:419–435, 1992.
- [20] M. Leuschel. Improving homeomorphic embedding for online termination. In P. Flener, editor, *LOPSTR, 8th International Workshop on Logic Programming Synthesis and Transformation*, pages 199–218, 1998. Lecture Notes in Computer Science, Vol. 1559, Springer-Verlag.
- [21] M. Leuschel. On the power of homeomorphic embedding for online termination. In G. Levi, editor, *5th International Symposium on Static Analysis, SAS 98*, pages 230–245, 1998. Lecture Notes in Computer Science, Vol. 1503, Springer-Verlag.
- [22] C.R. Murthy and J.R. Russell. A constructive proof of Higman’s lemma. In *Proc. 5th IEEE Symposium on Logic in Computer Science*, pages 257–267, 1990.
- [23] C.ST.J.A. Nash-Williams. On well-quasi-ordering finite trees. *Proc. Cambridge Phil. Soc.*, 59:833–835, 1963.
- [24] C.ST.J.A. Nash-Williams. On well-quasi-ordering infinite trees. *Proc. Cambridge Phil. Soc.*, 61:697–720, 1965.
- [25] C.ST.J.A. Nash-Williams. On well-quasi-ordering transfinite sequences. *Proc. Cambridge Phil. Soc.*, 61:33–39, 1965.
- [26] C.ST.J.A. Nash-Williams. On better-quasi-ordering transfinite sequences. *Proc. Cambridge Phil. Soc.*, 64:273–290, 1968.
- [27] M. Ogawa. A linear time algorithm for monadic querying of indefinite data over linearly ordered domains. *Information and Computation*, 186(2):236–259, 2003.
- [28] M. Ogawa. Well-quasi-orders and regular omega-languages. *Theoretical Computer Science*, 324(1):55–60, 2004.
- [29] L. Perković and B. Reed. An improved algorithm for finding tree decompositions of small width. *International Journal on Foundations of Computer Science*, 11(3):365–371, 2000. previously presented at WG’99, LNCS 1665.
- [30] L. Puel. Using unavoidable set of trees to generalize Kruskal’s theorem. *Journal of Symbolic Computation*, 8:335–382, 1989.
- [31] R. Rado. Partial well-ordering of sets of vectors. *Mathematika*, 1:89–95, 1954.
- [32] F. Richman and G. Stolzenberg. Well quasi-ordered sets. *Advances in Mathematics*, 97:145–153, 1993.
- [33] N. Robertson and P.D. Seymour. Graph minors XV. Wagner’s conjecture, 1988. preprint.
- [34] N. Robertson and P.D. Seymour. Graph minors IV. tree-width and well-quasi-ordering. *Journal of Combinatorial Theory Series B*, 48:227–254, 1990.
- [35] N. Robertson and P.D. Seymour. Graph minors xiii. the disjoint path problem. *Journal of Combinatorial Theory Series B*, 63:65–110, 1995.
- [36] S.G. Simpson. Bqo Theory and Fraïssé’s Conjecture. In *Recursive Aspects of Descriptive Set Theory*, volume 11 of *Oxford Logic Guides*, chapter 9. Oxford University Press, 1985.
- [37] S.G. Simpson. Nonprovability of certain combinatorial properties of finite trees. In L. A. Harrington, editor, *Harvey Friedman’s research on the foundation of mathematics*, pages 87–117. North-Holland, 1985.
- [38] M.H. Sorensen and R. Glück. An algorithm of generalization in positive supercompilation. In J.W. Lloyd, editor, *1995 International Symposium on Logic Programming (ILPS 1995)*, pages 465–479. MIT Press, 1995.

- [39] R. Thomas. A counter-example to ‘Wagner’s conjecture’ for infinite graphs. *Proc. Cambridge Phil. Soc.*, 103:55–57, 1988.
- [40] R. Thomas. Well-quasi-ordering infinite graphs with forbidden finite planar minor. *Trans. AMS*, 312(1):279–313, 1989.