




Effective Translation of LTL to Deterministic Rabin Automata: Beyond the (F,G)-Fragment


Tomáš Babiak František Blahoudek Mojmír Křetínský Jan Strejček

Masaryk University, Czech Republic


Highlights 2013




- well studied
- efficient tools: SPOT, LTL2BA, LTL3BA,...
- produces **nondeterministic** Büchi automata




- well studied
- efficient tools: SPOT, LTL2BA, LTL3BA,...
- produces **nondeterministic** Büchi automata
- **deterministic** automata needed for
 - model checking of probabilistic systems
 - control synthesis



- well studied
- efficient tools: SPOT, LTL2BA, LTL3BA,...
- produces **nondeterministic** Büchi automata
- **deterministic** automata needed for
 - model checking of probabilistic systems
 - control synthesis
- LTL cannot be translated into deterministic Büchi automata
⇒ another acceptance condition - Rabin, Streett, parity, ...



- well studied
- efficient tools: SPOT, LTL2BA, LTL3BA,...
- produces **nondeterministic** Büchi automata
- **deterministic** automata needed for
 - model checking of probabilistic systems
 - control synthesis
- LTL cannot be translated into deterministic Büchi automata
⇒ another acceptance condition - **Rabin**, Streett, parity, ...




The Big Picture

LTL

$G(XFa \wedge XFb) \vee Gb$


DRA



Rabin pairs: $\{(\bullet, \bullet), (\blacktriangle, \blacktriangle)\}$


The Big Picture

- Typical workflow – 1t12dstar [Klein2005]



The Big Picture

- Typical workflow – lt12dstar [Klein2005]





- Rabinizer [Gaiser-J. Křetínský-Esparza2012]



The Big Picture


- Typical workflow – lt12dstar [Klein2005]



Generalized Rabin pairs: $\{(\bullet, \{\bullet, \bullet\}), (\blacktriangle, \emptyset)\}$

The Big Picture


- Typical workflow – lt12dstar [Klein2005]



- Rabinizer [Gaiser-J. Křetínský-Esparza2012]




- LTL3DRA [ATVA 2013]



The Big Picture


- Typical workflow – lt12dstar [Klein2005]



- Rabinizer [Gaiser-J. Křetínský-Esparza2012]




- LTL3DRA [ATVA 2013]



The Big Picture


- Typical workflow – lt12dstar [Klein2005]



- Rabinizer [Gaiser-J. Křetínský-Esparza2012]




- LTL3DRA [ATVA 2013]



The Big Picture


- Typical workflow – lt12dstar [Klein2005]



- Rabinizer [Gaiser-J. Křetínský-Esparza2012]





- LTL3DRA [ATVA 2013]



- Rabinizer 2 [J. Křetínský-Ledesma-Garza2013]









[Gastin-Oddoux2001]


Very Weak Alternating Automata

- alternating automata
- co-Büchi acceptance
- cycles = selfloops






May/Must Alternating Automata = VWAA with three types of states




May/Must Alternating Automata = VWAA with three types of states

May

selfloop under tt
co-Büchi accepting






May/Must Alternating Automata = VWAA with three types of states

May


selfloop under tt
co-Büchi accepting



Must


selfloop in each transition
co-Büchi nonaccepting





May/Must Alternating Automata = VWAA with three types of states


May
selfloop under tt
co-Büchi accepting





Must
selfloop in each transition
co-Büchi nonaccepting







Loopless
initial
no predecessors


























double powerset construction
dealternation and determinization













Generalized Rabin pairs: $\{(\bullet, \{\bullet, \bullet\}), (\blacktriangle, \emptyset)\}$

Experiments on parametric formulae




$$\theta(n) = \neg((\bigwedge_{i=1}^n \text{GF} p_i) \rightarrow G(q \rightarrow \text{Fr}))$$

Experiments on parametric formulae




Experiments on parametric formulae




$$R(n) = \bigwedge_{i=1}^n (\text{GF} p_i \vee \text{FG} p_{i+1})$$


- Extended translation



■ Extended translation




- Extended translation



- LTL3DRA available at <http://sourceforge.net/projects/ltl3dra/>
- experimental comparison of LTL to DRA translators submitted to LPAR'13

- Extended translation



- LTL3DRA available at <http://sourceforge.net/projects/ltl3dra/>
- experimental comparison of LTL to DRA translators submitted to LPAR'13

New tools are appearing, but only `ltl2dstar` can handle the whole LTL. Yet?