

A machine-independent characterization of timed languages

Sławomir Lasota
University of Warsaw

joint work with Mikołaj Bojańczyk

HIGHLIGHTS 2013

deterministic timed automata

with uninitialized clocks


deterministic timed automata

with uninitialized clocks




deterministic timed automata

with uninitialized clocks




deterministic timed automata

with uninitialized clocks



deterministic timed automata


with uninitialized clocks



the guards use the structure $(\mathbb{R}, <, +1)$


deterministic timed automata

with uninitialized clocks




deterministic timed automata

with uninitialized clocks




deterministic timed automata

with uninitialized clocks




deterministic timed automata

with uninitialized clocks



deterministic timed automata

with uninitialized clocks




the automaton accepts words $t_1 \ t_2 \ t_3 \in \mathbb{R}^3$ such that




deterministic timed automata

with uninitialized clocks




the automaton accepts words $t_1 \ t_2 \ t_3 \in \mathbb{R}^3$ such that




deterministic timed automata

with uninitialized clocks




the automaton accepts words $t_1 \ t_2 \ t_3 \in \mathbb{R}^3$ such that




deterministic timed automata

with uninitialized clocks



the automaton accepts words $t_1 \ t_2 \ t_3 \in \mathbb{R}^3$ such that



Myhill-Nerode theorem

Myhill-Nerode theorem

let L be a language over a finite alphabet A

Myhill-Nerode theorem

let L be a language over a finite alphabet A

L is recognized by a DFA

iff

Myhill-Nerode theorem

let L be a language over a finite alphabet A

L is recognized by a DFA

iff

\approx_L has finitely many equivalence classes

Myhill-Nerode theorem

let L be a language over a finite alphabet A

L is recognized by a DFA

iff

\approx_L has finitely many equivalence classes


$$w \approx_L u \quad \text{iff} \quad \forall v (wv \in L \text{ iff } uv \in L)$$

Myhill-Nerode theorem

let L be a language over a finite alphabet A

L is recognized by a DFA

iff

\approx_L has finitely many equivalence classes


$$w \approx_L u \quad \text{iff} \quad \forall v (wv \in L \text{ iff } uv \in L)$$

The same for deterministic timed automata?

Myhill-Nerode theorem

let L be a language over a finite alphabet A

L is recognized by a DFA

iff

\approx_L has finitely many equivalence classes


$$w \approx_L u \quad \text{iff} \quad \forall v (wv \in L \text{ iff } uv \in L)$$

The same for deterministic timed automata?

Problems:

Myhill-Nerode theorem

let L be a language over a finite alphabet A

L is recognized by a DFA

iff

\approx_L has finitely many equivalence classes


$$w \approx_L u \quad \text{iff} \quad \forall v (wv \in L \text{ iff } uv \in L)$$

The same for deterministic timed automata?

Problems:

- infinitely many equivalence classes*

Myhill-Nerode theorem

let L be a language over a finite alphabet A

L is recognized by a DFA

iff

\approx_L has finitely many equivalence classes


$$w \approx_L u \quad \text{iff} \quad \forall v (wv \in L \text{ iff } uv \in L)$$

The same for deterministic timed automata?

Problems:


- infinitely many equivalence classes*
- no canonical minimal timed automaton*

deterministic timed automata
with uninitialized clocks
do not minimize

deterministic timed automata

with uninitialized clocks


do not minimize



deterministic timed automata

with uninitialized clocks

do not minimize



Solution: move to sets with atoms

deterministic timed automata
with uninitialized clocks

Solution: move to sets with atoms

deterministic orbit-finite automata
in sets with atoms $(R, <, +1)$


deterministic timed automata
with uninitialized clocks

Solution: move to sets with atoms

deterministic orbit-finite automata
in sets with atoms $(R, <, +1)$

deterministic timed automata
with uninitialized clocks

finite automata
up to automorphisms of
 $(R, <, +1)$



Solution: move to sets with atoms

deterministic orbit-finite automata
in sets with atoms $(\mathbf{R}, <, +1)$

deterministic timed automata
with uninitialized clocks

finite automata
up to automorphisms of
 $(\mathbf{R}, <, +1)$


0

Solution: move to sets with atoms

deterministic orbit-finite automata
in sets with atoms $(\mathbf{R}, <, +1)$

deterministic timed automata
with uninitialized clocks

finite automata
up to automorphisms of
 $(\mathbf{R}, <, +1)$




Solution: move to sets with atoms

deterministic orbit-finite automata
in sets with atoms $(\mathbf{R}, <, +1)$

deterministic timed automata
with uninitialized clocks

finite automata
up to automorphisms of
 $(\mathbf{R}, <, +1)$




Solution: move to sets with atoms

deterministic orbit-finite automata
in sets with atoms $(\mathbf{R}, <, +1)$

finite automata
up to automorphisms of
 $(\mathbf{R}, <, +1)$

deterministic timed automata
with uninitialized clocks



Solution: move to sets with atoms

deterministic orbit-finite automata
in sets with atoms $(R, <, +1)$

deterministic timed automata
with uninitialized clocks

finite automata
up to automorphisms of
 $(R, <, +1)$

resemble
timed automata
with updates

Solution: move to sets with atoms

deterministic orbit-finite automata
in sets with atoms $(R, <, +1)$

deterministic timed automata
with uninitialized clocks

finite automata
up to automorphisms of
 $(R, <, +1)$

resemble
timed automata
with updates

closed under
minimization

Solution: move to sets with atoms

deterministic orbit-finite automata
in sets with atoms $(\mathbb{R}, <, +1)$

deterministic timed automata
with uninitialized clocks

minimal automata for languages
of deterministic timed automata
with uninitialized clocks

finite automata
up to automorphisms of
 $(\mathbb{R}, <, +1)$

resemble
timed automata
with updates

closed under
minimization

Myhill-Nerode theorem for timed languages

Myhill-Nerode theorem for timed languages

let L be a language over $A \times \mathbf{R}$

Myhill-Nerode theorem for timed languages

let L be a language over $A \times \mathbf{R}$

such that

- L contains only increasing words

Myhill-Nerode theorem for timed languages

let L be a language over $A \times \mathbf{R}$

such that

- L contains only increasing words
- L is invariant under $\text{Aut}(\mathbf{R}, <, +1)$

Myhill-Nerode theorem for timed languages

let L be a language over $A \times \mathbf{R}$

such that

- L contains only increasing words
- L is invariant under $\text{Aut}(\mathbf{R}, <, +1)$

L is recognized by a deterministic timed automaton
with uninitialized clocks

iff

Myhill-Nerode theorem for timed languages

let L be a language over $A \times \mathbf{R}$


such that

- L contains only increasing words
- L is invariant under $\text{Aut}(\mathbf{R}, <, +1)$

L is recognized by a deterministic timed automaton
with uninitialized clocks

iff

- \approx_L has orbit-finite set of equivalence classes



deterministic orbit-finite automata
in sets with atoms $(\mathbf{R}, <, +1)$

Myhill-Nerode theorem for timed languages

let L be a language over $A \times \mathbf{R}$

such that

- L contains only increasing words
- L is invariant under $\text{Aut}(\mathbf{R}, <, +1)$

L is recognized by a deterministic timed automaton
with uninitialized clocks

iff

- \approx_L has orbit-finite set of equivalence classes
- L is forgetful

deterministic orbit-finite automata
in sets with atoms $(\mathbf{R}, <, +1)$

deterministic timed automata
with uninitialized clocks

L is forgetful iff

L is forgetful iff

there is $M \in \mathbf{R}$ such that

L is forgetful iff

there is $M \in \mathbb{R}$ such that
for every timed word

L is forgetful iff

there is $M \in \mathbb{R}$ such that
for every timed word



L is forgetful iff

there is $M \in \mathbb{R}$ such that

for every timed word

and $\pi \in \text{Aut}(\mathbb{R}, <, +1)$




L is forgetful iff

there is $M \in \mathbb{R}$ such that

for every timed word
and $\pi \in \text{Aut}(\mathbb{R}, <, +1)$

for every factorization




L is forgetful iff

there is $M \in \mathbb{R}$ such that

for every timed word

and $\pi \in \text{Aut}(\mathbb{R}, <, +1)$

for every factorization




L is forgetful iff

there is $M \in \mathbb{R}$ such that

for every timed word

and $\pi \in \text{Aut}(\mathbb{R}, <, +1)$

for every factorization



summary

- Myhill-Nerode theorem for timed languages
- superclass of deterministic timed automata
closed under minimization

summary

- Myhill-Nerode theorem for timed languages
- superclass of deterministic timed automata
closed under minimization

} both result due to
sets with atoms

summary

- Myhill-Nerode theorem for timed languages
 - superclass of deterministic timed automata
closed under minimization
- } both result due to
sets with atoms

Thank you!